



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
10.10.2012 Bulletin 2012/41

(51) Int Cl.:
B01L 3/14 (2006.01) **G01N 1/00** (2006.01)
G01N 33/49 (2006.01)

(21) Application number: **12172336.5**

(22) Date of filing: **21.07.2009**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

- **Gram, Jess**
Scottsdale, AZ Arizona 85255 (US)
- **Crawford, Jamieson W.**
Demarest, NJ New Jersey 07627 (US)

(30) Priority: **21.07.2008 US 82356 P**
21.07.2008 US 82365 P

(74) Representative: **von Kreisler Selting Werner**
Deichmannhaus am Dom
Bahnhofsvorplatz 1
50667 Köln (DE)

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
09790681.2 / 2 326 421

Remarks:

This application was filed on 18-06-2012 as a divisional application to the application mentioned under INID code 62.

(71) Applicant: **Becton, Dickinson and Company**
Franklin Lakes, New Jersey 07417-1880 (US)

(72) Inventors:
• **Battles, Christopher A.**
Seymour, CT Connecticut 06483 (US)

(54) **Density phase separation device**

(57) A mechanical separator for separating a fluid sample into first and second phases is disclosed. The mechanical separator includes a float having a passage-way extending between first and second ends thereof with a pierceable head enclosing the first end of the float, a ballast longitudinally moveable with respect to the float, and a bellows extending between a portion of the float and a portion of the ballast. The bellows is adapted for deformation upon longitudinal movement of the float and the ballast, with the bellows isolated from the pierceable head. The float has a first density and the ballast has a second density greater than the first density. The bellows is structured for sealing engagement with a cylindrical wall of a tube, and the pierceable head is structured for application of a puncture tip therethrough. The separation device is suitable for use with a standard medical collection tube.




FIG.23

Description

CROSS REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to United States Provisional Patent Application No. 61/082,356, filed July 21, 2008, entitled "Density Phase Separation Device", and to United States Provisional Patent Application No. 61/082,365 filed July 21, 2008, entitled "Density Phase Separation Device", the entire disclosures of each of which are herein incorporated by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The subject invention relates to a device for separating heavier and lighter fractions of a fluid sample. More particularly, this invention relates to a device for collecting and transporting fluid samples whereby the device and fluid sample are subjected to centrifugation in order to cause separation of the heavier fraction from the lighter fraction of the fluid sample.

Description of Related Art

[0003] Diagnostic tests may require separation of a patient's whole blood sample into components, such as serum or plasma, (the lighter phase component), and red blood cells, (the heavier phase component). Samples of whole blood are typically collected by venipuncture through a cannula or needle attached to a syringe or an evacuated blood collection tube. After collection, separation of the blood into serum or plasma and red blood cells is accomplished by rotation of the syringe or tube in a centrifuge. In order to maintain the separation, a barrier must be positioned between the heavier and lighter phase components. This allows the separated components to be subsequently examined.

[0004] A variety of separation barriers have been used in collection devices to divide the area between the heavier and lighter phases of a fluid sample. The most widely used devices include thixotropic gel materials, such as polyester gels. However, current polyester gel serum separation tubes require special manufacturing equipment to both prepare the gel and fill the tubes. Moreover, the shelf-life of the product is limited. Over time, globules may be released from the gel mass and enter one or both of the separated phase components. These globules may clog the measuring instruments, such as the instrument probes used during the clinical examination of the sample collected in the tube. Furthermore, commercially available gel barriers may react chemically with the analytes. Accordingly, if certain drugs are present in the blood sample when it is taken, an adverse chemical reaction with the gel interface can occur.

[0005] Certain mechanical separators have also been proposed in which a mechanical barrier can be employed

between the heavier and lighter phases of the fluid sample. Conventional mechanical barriers are positioned between heavier and lighter phase components utilizing differential buoyancy and elevated gravitational forces applied during centrifugation. For proper orientation with respect to plasma and serum specimens, conventional mechanical separators typically require that the mechanical separator be affixed to the underside of the tube closure in such a manner that blood fill occurs through or around the device when engaged with a blood collection set. This attachment is required to prevent the premature movement of the separator during shipment, handling, and blood draw. Conventional mechanical separators are affixed to the tube closure by a mechanical interlock between the bellows component and the closure. One example of such a device is described in United States Patent No. 6,803,022.

[0006] Conventional mechanical separators have some significant drawbacks. As shown in **FIG. 1**, conventional separators include a bellows **34** for providing a seal with the tube or syringe wall **38**. Typically, at least a portion of the bellows **34** is housed within, or in contact with a closure **32**. As shown in **FIG. 1**, as the needle **30** enters through the closure **32**, the bellows **34** is depressed. This creates a void **36** in which blood may pool during insertion or removal of the needle. This can result in sample pooling under the closure, device pre-launch in which the mechanical separator prematurely releases during blood collection, trapping of a significant quantity of fluid phases, such as serum and plasma, and/or poor sample quality. Furthermore, previous mechanical separators are costly and complicated to manufacture due to the complicated multi-part fabrication techniques.

[0007] Accordingly, a need exists for a separator device that is compatible with standard sampling equipment and reduces or eliminates the aforementioned problems of conventional separators. A need also exists for a separator device that is easily used to separate a blood sample, minimizes cross-contamination of the heavier and lighter phases of the sample during centrifugation, is independent of temperature during storage and shipping and is stable to radiation sterilization.

SUMMARY OF THE INVENTION

[0008] The present invention is directed to an assembly for separating a fluid sample into a higher specific gravity phase and a lower specific gravity phase. Desirably, the mechanical separator of the present invention may be used with a tube, and the mechanical separator is structured to move within the tube under the action of applied centrifugal force in order to separate the portions of a fluid sample. Most preferably, the tube is a specimen collection tube including an open end, a second end, and a sidewall extending between the open end and second end. The sidewall includes an outer surface and an inner surface and the tube further includes a closure disposed to fit in the open end of the tube with a resealable septum.

Alternatively, both ends of the tube may be open, and both ends of the tube may be sealed by elastomeric closures. At least one of the closures of the tube may include a needle pierceable resealable septum.

[0009] The mechanical separator may be disposed within the tube at a location between the top closure and the bottom of the tube. The separator includes opposed top and bottom ends and includes a float having a pierceable head, a ballast, and a bellows. The components of the separator are dimensioned and configured to achieve an overall density for the separator that lies between the densities of the phases of a fluid sample, such as a blood sample.

[0010] In one embodiment, the mechanical separator for separating a fluid sample into first and second phases within a tube includes a float having a passageway extending between first and second ends thereof with a pierceable head enclosing the first end of the float. The mechanical separator also includes a ballast longitudinally moveable with respect to the float, and a bellows extending between a portion of the float and a portion of the ballast, the bellows adapted for deformation upon longitudinal movement of the float and the ballast. The bellows of the mechanical separator are isolated from the pierceable head. In one embodiment, the float has a first density and the ballast has a second density, wherein the first density is less than the second density.

[0011] The pierceable head of the mechanical separator is structured to resist deformation upon application of a puncture tip therethrough. The pierceable head may comprise a rim portion for engagement with a closure, and optionally, the rim portion may define at least one notch.

[0012] The pierceable head may be received at least partially within an upper recess of the float. The bellows may be circumferentially disposed about at least a portion of the float. In one configuration, the pierceable head and the bellows are isolated by a portion of the float. In another configuration, the pierceable head and the bellows are isolated by a neck portion of the float. In yet another configuration, the bellows includes an interior wall defining a restraining surface, and the float includes a shoulder for engaging the restraining surface.

[0013] The ballast can define an interlock recess for accommodating a portion of the bellows for attachment thereto. In this manner, the bellows and the ballast can be secured. Additionally, the ballast can include an exterior surface defining an annular shoulder circumferentially disposed within the exterior surface to assist in the assembly process.

[0014] In one embodiment of the mechanical separator, the float can be made of polypropylene, the pierceable head can be made of a thermoplastic elastomer (TPE), such as Kraton®, commercially available from Kraton Polymers, LLC, the bellows can also be made of a thermoplastic elastomer, and the ballast can be made of polyethylene terephthalate (PET).

[0015] In another embodiment, a separation assembly

for enabling separation of a fluid sample into first and second phases includes a tube, having an open end, a second end, and a sidewall extending therebetween, and a closure adapted for sealing engagement with the open end of the tube. The closure defines a recess and the separation assembly includes a mechanical separator releasably engaged within the recess. The mechanical separator includes a float having a passageway extending between first and second ends thereof with a pierceable head enclosing the first end of the float. The mechanical separator also includes a ballast longitudinally moveable with respect to the float, and a bellows extending between a portion of the float and a portion of the ballast, the bellows adapted for deformation upon longitudinal movement of the float and the ballast. The bellows of the mechanical separator are isolated from the pierceable head. In one embodiment, the float has a first density and the ballast has a second density, wherein the first density is less than the second density.

[0016] The pierceable head of the float may be structured to resist deformation upon application of a puncture tip therethrough. In one configuration, the pierceable head and the bellows are isolated by a portion of the float. In another configuration, the pierceable head and the bellows are isolated by a neck portion of the float. Optionally, the bellows includes an interior wall defining a restraining surface, and the float comprises a shoulder for engaging the restraining surface. The ballast may define an interlock recess for accommodating a portion of the bellows for attachment thereto.

[0017] In another embodiment, the mechanical separator includes a first sub-assembly including a float having a pierceable head enclosing a first end thereof, and a second sub-assembly having a ballast and a bellows. The first sub-assembly may have a first density and the second sub-assembly may have a second density, the second density being greater than the first density of the first sub-assembly. The first sub-assembly and the second sub-assembly may be attached through the bellows such that the ballast is longitudinally movable with respect to the float upon deformation of the bellows. The bellows of the second sub-assembly is isolated from the pierceable head of the first sub-assembly.

[0018] In yet another embodiment of the present invention, a method of assembling a mechanical separator includes the steps of providing a first sub-assembly, the first sub-assembly including a float with a neck and a pierceable head, providing a second sub-assembly, the second sub-assembly including a bellows extending from a ballast and including an interior restraining surface, and joining the first sub-assembly with the second sub-assembly. The first sub-assembly and the second sub-assembly are joined such that the neck of the float is in mechanical interface with the interior restraining surface of the bellows. The float may have a first density and the ballast may have a second density greater than the first density of the float. Optionally, the joining step includes inserting and guiding the float through an interior of the

bellows until the neck of the float is in mechanical interface with the interior restraining surface of the bellows. The ballast may also include an exterior surface defining an annular shoulder circumferentially disposed thereabout for receipt of a mechanical assembler therein.

[0019] In another embodiment of the present invention, a separation assembly for enabling separation of a fluid sample into first and second phases includes a closure adapted for sealing engagement with a tube, with the closure defining a recess. The separation assembly further includes a mechanical separator. The mechanical separator includes a float defining a passageway extending between first and second ends thereof with a pierceable head enclosing the first end of the float. The pierceable head is releasably engaged within the recess. The mechanical separator also includes a ballast longitudinally movable with respect to the float, the ballast having a second density greater than the first density of the float. The mechanical separator further includes a bellows extending between a portion of the float and a portion of the ballast, the bellows being adapted for deformation upon longitudinal movement of the float and the ballast with the bellows being isolated from the pierceable head.

[0020] In one configuration, the interface between the closure and the mechanical separator occurs only between the pierceable head and the recess. The separation assembly may also be configured such that the mechanical separator may be released from the closure without elongation of the deformable bellows.

[0021] In accordance with another embodiment of the present invention, a mechanical separator for separating a fluid sample into first and second phases within a tube includes a float comprising a passageway extending between a first upwardly oriented end and a second downwardly oriented end thereof. The mechanical separator also includes a ballast longitudinally movable with respect to the float, and a bellows extending between a portion of the float and a portion of the ballast, the bellows being adapted for deformation upon longitudinal movement of the float and the ballast, and isolated from the first upwardly oriented end of the float.

[0022] In accordance with another embodiment of the present invention, a separation assembly for enabling separation of a fluid sample into first and second phases includes a tube having an open end, a second end, and a sidewall extending therebetween. The separation assembly also includes a closure adapted for sealing engagement with the open end of the tube, the closure defining a recess, and a mechanical separator releasably engaged within the recess. The mechanical separator includes a float having a passageway extending between a first upwardly oriented end and a second downwardly oriented end thereof. The mechanical separator also includes a ballast longitudinally movable with respect to the float, and a bellows extending between a portion of the float and a portion of the ballast. The bellows being adapted for deformation upon longitudinal movement of the float and the ballast, and isolated from the first up-

wardly oriented end of the float. Optionally, the separation assembly is adapted to introduce a fluid sample into the tube and around the mechanical separator without passing through the mechanical separator.

[0023] In accordance with yet another embodiment of the present invention, a mechanical separator for separating a fluid sample into first and second phases within a tube includes a float defining an interior having a moveable plug disposed therein. The moveable plug is adapted to transition from a first position to a second position along a longitudinal axis of the float in response to expansion of the fluid sample within the interior of the float.

[0024] In one configuration, the float defines a transverse hole and the moveable plug defines a transverse hole substantially aligned with the transverse hole of the float in the first position and blocked by a portion of the float in the second position. Optionally, the moveable plug is restrained within the interior of the float by a pierceable head. The mechanical separator may also include a ballast longitudinally movable with respect to the float, and a bellows extending between a portion of the float and a portion of the ballast. The bellows may be adapted for deformation upon longitudinal movement of the float and the ballast, and may be isolated from the first upwardly oriented end of the float.

[0025] In accordance with yet a further embodiment of the present invention, a mechanical separator for separating a fluid sample into first and second phases within a tube includes a float, a ballast longitudinally movable with respect to the float, and a bellows extending between a portion of the float and a portion of the ballast. The bellows may be adapted for deformation upon longitudinal movement of the float and the ballast, and may be adapted to separate at least partially from the float to allow venting of gas therebetween.

[0026] The assembly of the present invention is advantageous over existing separation products that utilize separation gel. In particular, the assembly of the present invention will not interfere with analytes, whereas many gels interact with bodily fluids. Another attribute of the present invention is that the assembly of the present invention will not interfere with therapeutic drug monitoring analytes.

[0027] The assembly of the present invention is also advantageous over existing mechanical separators in that the separate pierceable head and bellows allows for isolating the seal function of the bellows from the needle interface of the mechanical separator. This enables different materials or material thicknesses to be used in order to optimize the respective seal function and needle interface function. Also, this minimizes device pre-launch by providing a more stable target area at the puncture tip interface to reduce sample pooling under the closure. In addition, pre-launch is further minimized by precompression of the pierceable head against the interior of the stopper. The reduced clearance between the exterior of the float and the interior of the ballast minimizes the loss of trapped fluid phases, such as serum and plasma. Ad-

ditionally, the assembly of the present invention does not require complicated extrusion techniques during fabrication, and may optimally employ two-shot molding techniques.

[0028] As described herein, the mechanical separator of the present invention does not occlude an analysis probe like traditional gel tubes. Further details and advantages of the invention will become clear from the following detailed description when read in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0029] FIG. 1 is a partial cross-sectional side view of a conventional mechanical separator.

[0030] FIG. 2 is an exploded perspective view of a mechanical separator assembly including a closure, a bellows, a ballast, a pierceable head, a float, and a collection tube in accordance with an embodiment of the present invention.

[0031] FIG. 3 is a perspective view of the bottom surface of the closure of FIG. 2.

[0032] FIG. 4 is a cross-sectional view of the closure of FIG. 2, taken along line 4-4 of FIG. 3.

[0033] FIG. 5 is a perspective view of the pierceable head of FIG. 2.

[0034] FIG. 6 is a top view of the pierceable head of FIG. 2.

[0035] FIG. 7 is a side view of the pierceable head of FIG. 2.

[0036] FIG. 8 is a cross-sectional view of the pierceable head of FIG. 2, taken along line 8-8 of FIG. 7.

[0037] FIG. 9 is a side view of the float of FIG. 2.

[0038] FIG. 10 is a cross-sectional view of the float of FIG. 2, taken along line 10-10 of FIG. 9.

[0039] FIG. 11 is close-up cross-sectional view of a portion of the float of FIG. 2 taken along section XI of FIG. 10.

[0040] FIG. 12 is a top view of the float of FIG. 2.

[0041] FIG. 13 is a perspective view of the bellows of FIG. 2.

[0042] FIG. 14 is a side view of the bellows of FIG. 2.

[0043] FIG. 15 is a cross-sectional view of the bellows of FIG. 2, taken along line 15-15 of FIG. 14.

[0044] FIG. 16 is a perspective view of the ballast of FIG. 2.

[0045] FIG. 17 is a side view of the ballast of FIG. 2.

[0046] FIG. 18 is a cross-sectional view of the ballast of FIG. 2, taken along line 18-18 of FIG. 17.

[0047] FIG. 19 is a close-up cross-sectional view of a portion of the bellows of FIG. 2 taken along section IXX of FIG. 18.

[0048] FIG. 20 is a perspective view of the mechanical separator including the pierceable head, float, bellows, and ballast in accordance with an embodiment of the present invention.

[0049] FIG. 21 is a front view of the mechanical separator of FIG. 20.

[0050] FIG. 22 is a cross-sectional view of a mechanical separator of FIG. 20, taken along line 22-22 of FIG. 21.

[0051] FIG. 23 is a cross-sectional view of a mechanical separator affixed to a closure in accordance with an embodiment of the present invention.

[0052] FIG. 24 is a partial cross-sectional perspective view of a mechanical separator assembly including a tube, a mechanical separator positioned within the tube, a closure, a shield surrounding the closure and a portion of the tube, and a needle accessing the tube in accordance with an embodiment of the present invention.

[0053] FIG. 25 is a front view of an assembly including a tube having a closure and a mechanical separator disposed therein in accordance with an embodiment of the present invention.

[0054] FIG. 26 is a cross-sectional front view of the assembly of FIG. 25 having a needle accessing the interior of the tube and an amount of fluid provided through the needle into the interior of the tube in accordance with an embodiment of the present invention.

[0055] FIG. 27 is a cross-sectional front view of the assembly of FIG. 25 having the needle removed therefrom during use and the mechanical separator positioned apart from the closure in accordance with an embodiment of the present invention.

[0056] FIG. 27A is a partial cross-sectional front view of an assembly including a tube having a mechanical separator disposed therein under load in accordance with an embodiment of the present invention.

[0057] FIG. 27B is a partial cross-sectional front view of the assembly of FIG. 27A after centrifugation.

[0058] FIG. 28 is a cross-sectional front view of the assembly of FIG. 25 having the mechanical separator separating the less dense portion of the fluid from the denser portion of the fluid in accordance with an embodiment of the present invention.

[0059] FIG. 29 is a perspective view of an alternative embodiment of a mechanical separator having a ballast snap in accordance with an embodiment of the present invention.

[0060] FIG. 30 is a cross-sectional front view of the mechanical separator of FIG. 29.

[0061] FIG. 31 is a front view of the mechanical separator of FIG. 29.

[0062] FIG. 32 is a cross-sectional view of the mechanical separator of FIG. 29 taken along line 32-32 of FIG. 31.

[0063] FIG. 33 is a partial cross-sectional view of the mechanical separator of FIG. 29 taken along section XXXIII of FIG. 30.

[0064] FIG. 34 is an alternative embodiment of the partial cross-sectional view of FIG. 33 having a tapered profile in accordance with an embodiment of the present invention.

[0065] FIG. 35 is a front view of a first sub-assembly having a pierceable head portion and a float in accordance with an embodiment of the present invention.

[0066] FIG. 36 is a cross-sectional view of the first sub-

assembly of **FIG. 35**.

[0067] **FIG. 37** is a perspective view of a second sub-assembly having a bellows and a ballast in accordance with an embodiment of the present invention.

[0068] **FIG. 38** is a partial cross-sectional front view of the second sub-assembly of **FIG. 37**.

[0069] **FIG. 39** is a cross-sectional front view of an assembled first sub-assembly and second sub-assembly of a mechanical separator in accordance with an embodiment of the present invention.

[0070] **FIG. 40** is a perspective view of the assembled mechanical separator of **FIG. 39**.

[0071] **FIG. 41** is a perspective view of a mechanical separator in accordance with an embodiment of the present invention.

[0072] **FIG. 42** is a front view of the mechanical separator of **FIG. 41**.

[0073] **FIG. 43** is a left side view of the mechanical separator of **FIG. 41**.

[0074] **FIG. 44** is a rear view of the mechanical separator of **FIG. 41**.

[0075] **FIG. 45** is a right side view of the mechanical separator of **FIG. 41**.

[0076] **FIG. 46** is a top view of the mechanical separator of **FIG. 41**.

[0077] **FIG. 47** is a bottom view of the mechanical separator of **FIG. 41**.

[0078] **FIG. 48** is a perspective view of the float of the mechanical separator of **FIG. 41**.

[0079] **FIG. 49** is a top perspective view of the pierceable head of the mechanical separator of **FIG. 41**.

[0080] **FIG. 50** is a bottom perspective view of the pierceable head of **FIG. 49**.

[0081] **FIG. 51** is a cross-sectional front view of the mechanical separator of **FIG. 41** positioned within a closure of the present invention.

[0082] **FIG. 52** is a front view of a specimen collection container having a closure with the mechanical separator of **FIG. 41** disposed therein.

[0083] **FIG. 53** is a cross-sectional front view of the specimen collection container, closure and mechanical separator of **FIG. 52** taken along line **53-53** of **FIG. 52**.

[0084] **FIG. 54** is a partial cross-sectional front view of a closure and a portion of a mechanical separator in accordance with an embodiment of the present invention.

[0085] **FIG. 55** is a perspective of the top view of the closure of **FIG. 54**.

[0086] **FIG. 56** is a perspective of the bottom view of the closure of **FIG. 54**.

[0087] **FIG. 57** is a cross-sectional front view of an alternative closure and a portion of a mechanical separator in accordance with an embodiment of the present invention.

[0088] **FIG. 58** is a cross-sectional side view of the alternative closure of **FIG. 57** taken along line **58-58** of **FIG. 57** and a portion of a mechanical separator in accordance with an embodiment of the present invention.

[0089] **FIG. 58A** is a cross-sectional front view of the

alternative closure of **FIGS. 57-58** engaged with a specimen collection container having a mechanical separator disposed therein in accordance with an embodiment of the present invention.

[0090] **FIG. 59** is a partial cross-sectional perspective view of a mechanical separator having a moveable plug disposed within the float in accordance with an embodiment of the present invention.

[0091] **FIG. 60** is a cross-sectional front view of the float having a moveable plug disposed therein of **FIG. 59** in an initial position.

[0092] **FIG. 61** is a cross-sectional front view of the float and moveable plug of **FIG. 60** in a displaced position.

[0093] **FIG. 62** is a partial cross-sectional view of a mechanical separator having a solid float in accordance with an embodiment of the present invention.

[0094] **FIG. 63** is a cross-sectional front view of the mechanical separator of **FIG. 62** disposed within a specimen collection container and engaged with a closure.

[0095] **FIG. 64** is a cross-sectional front view of the mechanical separator of **FIG. 63** having a needle disposed through a portion of the closure for introducing sample into the specimen collection container.

[0096] **FIG. 65** is a partial cross-sectional front view of an alternative embodiment of a mechanical separator disposed within a specimen collection container having a separation component in accordance with an embodiment of the present invention.

[0097] **FIG. 66** is a partial cross-sectional front view of an alternative embodiment of a mechanical separator disposed within a specimen collection container having a ribbed protrusion in accordance with an embodiment of the present invention.

[0098] **FIG. 67** is a partial cross-sectional front view of an alternative embodiment of a mechanical separator disposed within a specimen collection container having a cutout in accordance with an embodiment of the present invention.

[0099] **FIG. 68** is a partial cross-sectional front view of the mechanical separator of **FIG. 63** having a washer disposed about a portion of the mechanical separator in accordance with an embodiment of the present invention.

[0100] **FIG. 69** is a perspective view of a washer of **FIG. 68**.

[0101] **FIG. 70** is a perspective view of an alternative embodiment of the washer of **FIG. 68**.

[0102] **FIG. 71** is a cross-sectional front view of a specimen collection container having a closure engaged therewith and having a mechanical separator disposed therein in accordance with an embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0103] For purposes of the description hereinafter, the words "upper", "lower", "right", "left", "vertical", "horizontal", "top", "bottom", "lateral", "longitudinal" and like spa-

tial terms, if used, shall relate to the described embodiments as oriented in the drawing figures. However, it is to be understood that many alternative variations and embodiments may be assumed except where expressly specified to the contrary. It is also to be understood that the specific devices and embodiments illustrated in the accompanying drawings and described herein are simply exemplary embodiments of the invention.

[0104] As shown in exploded perspective view in **FIG. 2**, the mechanical separator assembly **40** of the present invention includes a closure **42** with a mechanical separator **44**, for use in connection with a tube **46** for separating a fluid sample into first and second phases within the tube **46**. The tube **46** may be a sample collection tube, such as a proteomics, molecular diagnostics, chemistry sample tube, blood or other bodily fluid collection tube, coagulation sample tube, hematology sample tube, and the like. Desirably tube **46** is an evacuated blood collection tube. In one embodiment, the tube **46** may contain additional additives as required for particular testing procedures, such as clot inhibiting agents, clotting agents, and the like. Such additives may be in particle or liquid form and may be sprayed onto the cylindrical sidewall **52** of the tube **46** or located at the bottom of the tube **46**. The tube **46** includes a closed bottom end **48**, such as an apposing end, an open top end **50**, and a cylindrical sidewall **52** extending therebetween. The cylindrical sidewall **52** includes an inner surface **54** with an inside diameter "**a**" extending substantially uniformly from the open top end **50** to a location substantially adjacent the closed bottom end **48**.

[0105] The tube **46** may be made of one or more than one of the following representative materials: polypropylene, polyethylene terephthalate (PET), glass, or combinations thereof. The tube **46** can include a single wall or multiple wall configurations. Additionally, the tube **46** may be constructed in any practical size for obtaining an appropriate biological sample. For example, the tube **46** may be of a size similar to conventional large volume tubes, small volume tubes, or microtainer tubes, as is known in the art. In one particular embodiment, the tube **46** may be a standard 3 ml evacuated blood collection tube, as is also known in the art.

[0106] The open top end **50** is structured to at least partially receive the closure **42** therein to form a liquid impermeable seal. The closure includes a top end **56** and a bottom end **58** structured to be at least partially received within the tube **46**. Portions of the closure **42** adjacent the top end **56** defines a maximum outer diameter which exceeds the inside diameter "**a**" of the tube **46**. As shown in **FIGS. 2-4**, portions of the closure **42** at the top end **56** include a central recess **60** which define a pierceable resealable septum. Portions of the closure **42** extending downwardly from the bottom end **58** may taper from a minor diameter which is approximately equal to, or slightly less than, the inside diameter "**a**" of the tube **46** to a major diameter that is greater than the inside diameter "**a**" of the tube **46** at the top end **56**. Thus, the bottom

end **58** of the closure **42** may be urged into a portion of the tube **46** adjacent the open top end **50**. The inherent resiliency of closure **42** can insure a sealing engagement with the inner surface of the cylindrical sidewall **52** of the tube **46**.

[0107] In one embodiment, the closure **42** can be formed of a unitarily molded elastomeric material, having any suitable size and dimensions to provide sealing engagement with the tube **46**. The closure **42** can also be formed to define a bottom recess **62** extending into the bottom end **58**. The bottom recess **62** may be sized to receive at least a portion of the mechanical separator **44**. Additionally, a plurality of spaced apart arcuate flanges **64** may extend around the bottom recess **62** to at least partially restrain the mechanical separator **44** therein.

[0108] Referring again to **FIG. 2**, the mechanical separator **44** includes a pierceable head **66**, a float **68** engaged with a portion of the pierceable head **66**, a bellows **70** disposed about a portion of the float **68**, and a ballast **72** disposed about at least a portion of the float **68** and engaged with the bellows **70**.

[0109] Referring to **FIGS. 5-8**, the pierceable head **66** of the mechanical separator **44** may be extruded and/or molded of a resiliently deformable and self-sealable material, such as TPE. The pierceable head **66** includes an upper rim portion **76** and a lower portion **78**, opposite the upper rim portion **76**. The upper rim portion **76** may have a generally curved shape for correspondingly mating to the shape of the bottom recess **62** of the closure **42**, shown in **FIGS. 3-4**. In order to mitigate pre-launch, the pierceable head **66** may be precompressed against the bottom recess **62** of the closure **42**. In one embodiment, as shown in **FIG. 7**, the upper rim portion **76** of the pierceable head **66** has a curvature angle **A** of about 20 degrees. In another embodiment, the upper rim portion **76** of the pierceable head **66** includes a slightly tapered or flattened portion **74**. The portion **74** can have any suitable dimensions, however, it is preferable that the portion **74** have a diameter of from about 0.120 inch to about 0.150 inch.

[0110] The portion **74** of the pierceable head **66** is structured to allow a puncture tip, shown in **FIG. 26**, such as a needle tip, needle cannula, or probe, to pass therethrough. Upon withdrawal of the puncture tip from the portion **74**, the pierceable head **66** is structured to reseal itself to provide a liquid impermeable seal. The flattened shape of the portion **74** allows for a penetration by the puncture tip without significant deformation. In one embodiment, the portion **74** of the pierceable head **66** is structured to resist deformation upon application of a puncture tip therethrough. The generally curved shape of the upper rim portion **76** and the small diameter of the portion **74** make the pierceable head **66** of the present invention more stable and less likely to "tent" than the pierceable region of existing mechanical separators. To further assist in limiting sample pooling and premature release of the separator **44** from the bottom recess **62** of the closure **42**, the portion **74** of the pierceable head **66**

may optionally include a thickened region, such as from about 0.010 inch to about 0.030 inch thicker than other portions of the upper rim portion 76 of the pierceable head 66.

[0111] The pierceable head 66 also includes a lower portion 78, opposite the upper rim portion 76, structured to engage at least a portion of the float 68, shown in FIG. 2. The pierceable head 66 may define at least one cut-out notch 80, shown in FIGS. 5-6, extending from the upper rim portion 76 to the lower portion 78 and from an outer circumference 82 of the upper rim portion 76 to a location 84 circumferentially inward from the outer circumference 82. The cut-out notch 80 may be provided to allow the upper rim portion 76 of the pierceable head 66 to bend, such as upon application of a puncture tip through the access portion 74, without significant resulting hoop-stress to the pierceable head 66. In one embodiment, a plurality of cut-out notches 80 may be provided at a plurality of locations about the outer circumference 82 of the pierceable head 66. A plurality of cut-out notches 80 may enable the pierceable head 66 to flex in such a manner as to control the release load of the mechanical separator 44 from the closure 42.

[0112] As shown in FIGS. 7-8, the upper rim portion 76 of the pierceable head 66 may include an extended portion 82 dimensioned to overhang the lower portion 78. In one embodiment, the extended portion 82 of the pierceable head 66 may be dimensioned to have a diameter "b" that is greater than the diameter "c" of the lower portion 78. In another embodiment, the lower portion 78 of the pierceable head 66 may be dimensioned for engagement with, such as receipt within, a portion of the float 68 as shown in FIG. 2. In yet another embodiment, as shown in FIGS. 5-6, the pierceable head 66 may be optionally vented with a plurality of slits 85 created by a post-molding assembly operation. The pierceable head 66 may include three such spaced slits 85.

[0113] Referring to FIGS. 9-12, the float 68 of the mechanical separator 44 is a generally tubular structure 90 having an upper end 86, a lower end 92, and a passage 94 extending longitudinally therebetween. As shown in FIGS. 9-10, the float 68 of the mechanical separator 44 includes an upper end 86 defining an upper recess 88 for receiving the lower portion 78 of the pierceable head 66. The upper end 86 of the float 68 has a diameter "d" which may be larger than the diameter "c" of the lower portion 78 of the pierceable head 66, shown in FIG. 8, to allow receipt of the pierceable head 66 therein. In one embodiment, the diameter "d" of the upper end 86 of the float 68 is smaller than the diameter "b" of the extended portion 82 of the pierceable head 66, also shown in FIG. 8. In another embodiment, the diameter "e" of the tubular structure 90 of the float 68 is greater than the diameter "b" of the upper rim portion 76 of the pierceable head 66, therefore, the lower portion 78 of the pierceable head 66 may be received within the float 68 while the extended portion 82 of the pierceable head 66 extends beyond the interior of the float 68 when the pierceable head 66 and

the float 68 are engaged. Optionally, the diameter "d" of the float 68 may be equal to the diameter "c" of the pierceable head 66. This may be particularly preferable for two-shot molding techniques.

[0114] The annular engagement of the lower portion 78 of the pierceable head 66 within the recess 88 establishes a mechanical engagement for providing structural rigidity to the pierceable head 66. Such structural rigidity, in combination with the profile and dimensions of the access portion 74 of the pierceable head 66, limits the amount of deformation thereof when a puncture tip is pressed therethrough. In this manner, sample pooling and premature release of the separator 44 from the closure 42 can be prevented.

[0115] Referring again to FIGS. 9-12, the upper end 86 of the float 68 also includes a generally tubular neck 96. Adjacent the neck 96, and extending circumferentially around the longitudinal axis L of the float 68 is a shoulder 98 having an exterior surface 100. As shown in a close-up view in FIG. 11 taken along section XI, in one embodiment the exterior surface 100 has an angled slope B of about 29 degrees to facilitate the shedding of cells around the mechanical separator 44 during centrifugation.

[0116] In another embodiment, a plurality of protrusions 102 may be located about the shoulder 98 of the float 68. The protrusions 102 may be a plurality of segmented protrusions spaced about a circumference of float 68. The protrusions 102 may create channels for venting of air from within the mechanical separator 44 when the mechanical separator 44 is submerged in fluid during centrifugation. In one embodiment, the venting pathway is created by a hole or series of holes through a wall in the float 68 adjacent the junction of the bellows 70 and the float 68.

[0117] In one embodiment, it is desirable that the float 68 of the mechanical separator 44 be made from a material having a density lighter than the liquid intended to be separated into two phases. For example, if it is desired to separate human blood into serum and plasma, then it is desirable that the float 68 have a density of no more than about 0.902 gm/cc. In another embodiment, the float 46 can be formed from polypropylene. In yet another embodiment, the pierceable head 66, shown in FIGS. 2 and 5-8, and the float 68, shown in FIGS. 2 and 9-12, can be co-molded, such as two-shot molded, or co-extruded as a first sub-assembly.

[0118] As shown in FIGS. 13-15 the bellows 70 are extruded and/or molded of a resiliently deformable material that exhibits good sealing characteristics with the tube material(s). The bellows 70 is symmetrical about a center longitudinal axis C, and includes an upper end 106, a lower end 108, and a hollow interior 104. The bellows 70 also defines a deformable sealing portion 112 positioned between the upper end 106 and the lower end 108 for sealing engagement with the cylindrical sidewall 52 of the tube 46, as shown in FIG. 2. The bellows 70 can be made of any sufficiently elastomeric material sufficient to form a liquid impermeable seal with the cylin-

dricial sidewall 52 of the tube 46. In one embodiment, the bellows is TPE and has an approximate dimensional thickness of from about 0.020 inch to about 0.050 inch.

[0119] The deformable sealing portion 112 can have a generally toroidal shape having an outside diameter "f" which, in an unbiased position, slightly exceeds the inside diameter "a" of the tube 46, shown in FIG. 2. However, oppositely directed forces on the upper end 106 and the lower end 108 will lengthen the bellows 70, simultaneously reducing the diameter of the deformable sealing section to a dimension less than "a". Accordingly, the bellows 70 are adapted to deform upon longitudinal movement of the float 68 in a first direction and the ballast 72 in a second opposite direction.

[0120] The bellows 70 can be disposed about, such as circumferentially disposed about, at least a portion of the float 68, shown in FIG. 2. As shown in FIGS. 13-15, the bellows 70 includes an interior wall 114 within the interior 104. Adjacent the upper end 106 of the bellows 70, the interior wall 114 defines an interior restraining surface 116 for mechanical interface with the shoulder 98 of the float 68, shown in FIGS. 9-12. In one embodiment, the interior restraining surface 116 of the bellows 70, shown in FIGS. 13-15, has a slope that corresponds to the slope of the shoulder 98 of the float 68, shown in FIGS. 9-12.

[0121] In this embodiment, the diameter "g" of the opening 115 of the upper end 106 of the bellows 70 defined by the interior wall 114 is smaller than the diameter "d" of the upper end 86 of the float 68, shown in FIG. 9, and smaller than the diameter "e" of the tubular structure 90 of the float 68, also shown in FIG. 9. During centrifugation, the diameter "g" of the bellows 70 increases in size beyond the diameter "d" of the float and enables the venting of air from within the mechanical separator 44. This allows the neck 96 of the float 68, shown in FIG. 9, to pass through the upper end 106 of the bellows 70 but restrains the shoulder 98 of the float 68 against the interior restraining surface 116 of the interior wall 114 of the bellows 70. The tubular structure 90 of the float is not able to pass through the upper end 106 of the bellows 70.

[0122] Portions of the exterior wall of the bellows 70 between the deformable sealing portion 112 and the lower end 108 define a generally cylindrical ballast mounting section 118 having an outer diameter "h" structured to receive the ballast 72 of the mechanical separator 44 thereon.

[0123] As shown in FIGS. 16-19, the ballast 72 of the mechanical separator 44 includes a generally cylindrical section 120 having an interior surface 122 structured to engage the ballast mounting section 118 of the bellows 70, shown in FIGS. 13-15. In one embodiment, at least a portion of the ballast 72 extends along the ballast mounting section 118 of the bellows 70, again shown in FIGS. 13-15. The ballast 72 includes opposed upper and lower ends 124, 126. In one embodiment, the upper end 124 includes a recess 128 for receiving the lower end 108 of the bellows 70, shown in FIGS. 13-15, therein.

The diameter "i" of the recess 128 is greater than the outer diameter "h" of the bellows 70, and the outer diameter "j" of the ballast 72 is less than the inside diameter "a" of the tube 46, as shown in FIG. 2. Accordingly, the lower end 108 of the bellows 70 may be received within the upper end 124 of the ballast 72 and the mechanical separator 44, shown in FIG. 2, may be received within the interior of the tube 46, also shown in FIG. 2. In one embodiment, the diameter "i" of the ballast 72 is equal to the diameter "h" of the bellows 70. Optimally, the ballast 72 may be molded first and the bellows 70 may be subsequently molded onto the ballast 72. In one embodiment, the bellows 70 and the ballast 72 exhibit material compatibility such that the bellows 70 and the ballast 72 bond together as a result of two-shot molding. [0124] As shown in FIG. 17, in one embodiment, the ballast 72 may include a mechanical interlock recess 130 extending through the generally cylindrical section 120, such as adjacent the upper end 124. In another embodiment, the ballast 72 may include the mechanical interlock recess 130 within an interior wall 131, such as within recess 128. A corresponding interlock attachment protrusion 132 may be provided on the exterior surface of the lower end 108 of the bellows 70, shown in FIG. 15, to mechanically engage the bellows 70 with the ballast 72.

[0125] In one embodiment, it is desirable that the ballast 72 of the mechanical separator 44 be made from a material having a density heavier than the liquid intended to be separated into two phases. For example, if it is desired to separate human blood into serum and plasma, then it is desirable that the ballast 72 have a density of at least 1.326 gm/cc. In one embodiment, the ballast 72 can be formed from PET. In yet another embodiment, the bellows 70, shown in FIGS. 2 and 13-15, and the ballast 72, shown in FIGS. 2 and 16-19, can be co-molded, such as two-shot molded, or co-extruded as a second sub-assembly.

[0126] In yet another embodiment, the exterior surface of the ballast 72 may define an annular recess 134 circumferentially disposed about a longitudinal axis D of the ballast 72 and extending into the exterior surface. In this embodiment, the annular recess 134 is structured to allow for an automated assembly to engage the second sub-assembly, including the bellows and the ballast for joinder with the first sub-assembly, including the pierceable head and the float.

[0127] As shown in FIGS. 20-22, when assembled, the mechanical separator 44 includes a pierceable head 66 engaged with a portion of a float 68, and a bellows 70 circumferentially disposed about the float 68 and engaged with the shoulder 98 of the float 68, and a ballast 72 disposed about the float 68 and engaged with a portion of the bellows 70. As shown in FIGS. 20-22, the pierceable head 66 can be at least partially received within the float 68. The bellows 70 can be disposed about the float 68 and the shoulder 98 of the float 68 can be mechanically engaged with the restraining surface 116 of the bellows

70. The ballast **72** can be circumferentially disposed about the float **68** and at least a portion of the bellows **70**, and the mechanical interlock recess **130** and the attachment protrusion **132** can mechanically secure the bellows **70** with the ballast **72**. Optimally, the bellows **70** and the ballast **72** may be two-shot molded and the mechanical interlock may further secure the ballast **72** and the bellows **70**.

[0128] In one embodiment, the first sub-assembly including the pierceable head **66** and the float **68**, and the second sub-assembly including the bellows **70** and the ballast **72** can be separately molded or extruded and subsequently assembled. Maintenance of the float density within the specified tolerances is more easily obtained by using a standard material that does not require compounding with, for example, glass micro-spheres in order to reduce the material density. In one embodiment, the material of the float **68** is polypropylene with a nominal density of about 0.902 gm/cc. In addition, co-molding, such as two-shot molding, the first sub-assembly and the second sub-assembly reduces the number of fabrication steps required to produce the mechanical separator **44**.

[0129] As shown in **FIG. 23**, the assembled mechanical separator **44** may be urged into the bottom recess **62** of the closure **42**. This insertion engages the flanges **64** of the closure **42** with the neck **96** of the float **68** or against the pierceable head **66**. During insertion, at least a portion of the pierceable head **66** will deform to accommodate the contours of the closure **42**. In one embodiment, the closure **42** is not substantially deformed during insertion of the mechanical separator **44** into the bottom recess **62**. In one embodiment, the mechanical separator **44** is engaged with the closure **42** by an interference fit of the pierceable head **66** and the bottom recess **62** of the closure **42**.

[0130] Referring again to **FIG. 23**, the pierceable head **66** and the bellows **70** are physically isolated from one another by a portion of the float **68**, such as the neck **96**. This isolation allows for the pierceable head **66** to control both the release load from the closure **42** and the amount of deformation caused by application of a puncture tip through the access portion **74** independent of the bellows **70**. Likewise, the bellows **70** may control the seal load with the tube **46**, shown in **FIG. 2**, during applied centrifugal rotation independent of the restraints of the pierceable head **66**.

[0131] As shown in **FIGS. 24-25**, the subassembly including the closure **42** and the mechanical separator **44** are inserted into the open top end of the tube **46**, such that the mechanical separator **44** and the bottom end **58** of the closure **42** lie within the tube **46**. The mechanical separator **44**, including the bellows **70**, will sealingly engage the interior of the cylindrical sidewall **52** and the open top end of the tube **46**. The assembly including the tube **46**, the mechanical separator **44** and the closure **42** may then be inserted into a needle holder **136** having a puncture tip **138**, such as a needle, extending there-through. Optionally, the closure **42** may be at least par-

tially surrounded by a shield, such as a Hemogard® Shield commercially available from Becton Dickinson and Company, to shield the user from droplets of blood in the closure **42** and from potential blood aerosolisation effects when the closure **42** is removed from the tube **46**.

[0132] As shown in **FIG. 26**, a liquid sample is delivered to the tube **46** by the puncture tip **138** that penetrates the septum of the top end **56** of the closure **42** and the access portion **74** of the pierceable head **66**. For purposes of illustration only, the liquid is blood. Blood will flow through the central passage **94** of the float **68** and to the closed bottom end **48** of the tube **46**. The puncture tip **138** will then be withdrawn from the assembly. Upon removal of the puncture tip **138**, the closure **42** will reseal itself. The pierceable head **66** will also reseal itself in a manner that is substantially impervious to fluid flow.

[0133] As shown in **FIG. 27**, when the assembly is subjected to an applied rotational force, such as centrifugation, the respective phases of the blood will begin to separate into a denser phase displaced toward the bottom **58** of the tube **46**, and a less dense phase displaced toward the top **50** of the tube **46**. The applied centrifugal force will urge the ballast **72** of the mechanical separator **44** toward the closed bottom end and the float **68** toward the top end of the tube **46**. This movement of the ballast **72** will generate a longitudinal deformation of the bellows **70**. As a result, the bellows **70** will become longer and narrower and will be spaced concentrically inward from the inner surface of the cylindrical sidewall **52**. Accordingly, lighter phase components of the blood will be able to slide past the bellows **70** and travel upwards, and likewise, heavier phase components of the blood will be able to slide past the bellows **70** and travel downwards.

[0134] Initially, the neck **96** of the mechanical separator **44** will be engaged with the flanges **64** of the closure **42**. However, upon application of applied centrifugal force, the mechanical separator **44** is subject to a force that acts to release the mechanical separator **44** from the closure **42**. In one embodiment, the closure **42**, particularly the flanges **64**, are not dimensionally altered by the application of applied centrifugal force and, as a consequence, do not deform. It is noted herein, that the longitudinal deformation of the bellows **70** during applied centrifugal force does not affect or deform the pierceable head **66** as the pierceable head **66** and the bellows **70** are isolated from one another by the neck **96** of the float **68**.

[0135] In one embodiment referring to **FIGS. 27A-27B**, during centrifuge, the negative buoyancy F_{Ballast} of the ballast **72** opposes the positive buoyancy F_{Float} of the float **68** creating a differential force which causes the bellows **70** to contract away from the interior surface of the sidewall **52** of the tube **46**. This elongation of the bellows **70** causes an opening **71** between the float **68** and the sealing surface **73** of the bellows **70** under load. Once the opening **71** is formed between the float **68** and the sealing surface **73** of the bellows **70**, as shown in **FIG. 27A**, air trapped within the mechanical separator **44** may

be vented through the opening **71** into the tube at a location above the mechanical separator **44**. In this configuration, the bellows **70** deform away from the float **68** allowing venting to occur therebetween. After centrifugation, as shown in **FIG. 27B**, the bellows **70** resiliently returns to the undeformed position and re-sealingly engages the interior surface of the sidewall **52** of the tube **46**. Thus, the opening **71** between the float **68** and the sealing surface **73** of the bellows **70** is sealed as the sealing surface **73** of the bellows **70** contacts the float **68** at contact surface **75**. With reference to **FIGS. 5-6**, during centrifuge, the slits **85** positioned within the pierceable head portion **66** may open due to the elongation of the pierceable head portion material, allowing air trapped within the interior of the float **68** to be vented there-through.

[0136] As noted above, the mechanical separator **44** has an overall density between the densities of the separated phases of the blood. Consequently, as shown in **FIG. 28**, the mechanical separator **44** will stabilize in a position within the tube **46** such that the heavier phase components **140** will be located between the mechanical separator **44** and the closed bottom end **48** of the tube **46**, while the lighter phase components **142** will be located between the mechanical separator **44** and the top end of the tube **50**.

[0137] After this stabilized state has been reached, the centrifuge will be stopped and the bellows **70** will resiliently return to its unbiased state and into sealing engagement with the interior of the cylindrical sidewall **52** of the tube **46**. The formed liquid phases may then be accessed separately for analysis.

[0138] In an alternative embodiment, as shown in **FIGS. 29-33**, the mechanical separator **44a** may include one or more ballast snaps **200** for preventing the float **68a** from passing entirely through the bellows **70a** under applied load. The ballast snaps **200** may be co-molded with the ballast **72a** to limit the movement of the float **68a** with respect to the ballast **72a**, such as by contacting and being restrained by a restraining surface **70x** of the float **68a** under applied load. As shown in detail in **FIG. 33**, the ballast snaps **200** may include a restraint portion **201** for engaging a corresponding recess **202** within the bellows **70a**.

[0139] In another alternative embodiment, as shown in **FIG. 34**, the bellows **70b** may have a tapered profile **300** adjacent the recess **202** for corresponding engagement with the restraint portion **201** of the ballast snaps **200** of the ballast **72b**. The tapered profile **300** of the bellows **70b** may minimize the formation of bellows pinching due to axial movement of the ballast **72b**.

[0140] In another alternative embodiment, a first sub-assembly **400** including a pierceable head **66c** and a float **68c** may be co-molded as shown in **FIGS. 35-36**. The first sub-assembly **400** may include a relief ring **402** for mating adaptation with the ballast (shown in **FIGS. 37-38**) to limit relative travel during assembly and application of accelerated forces. The pierceable head **66c**

may be provided with a target area dome **403** to reduce tenting and to facilitate the shedding of debris therefrom. The pierceable head **66c** may also be provided with a rigid halo surface **404** to increase launch load and reduce movement of the mechanical separator during insertion into the closure. As shown in **FIGS. 37-38**, the second sub-assembly **408** including a ballast **72c** and a bellows **70c**, may also be co-molded. As shown in **FIG. 37**, protrusions **410** on the bellows **70c** may engage with corresponding recesses **412** within the ballast **72c** to form a locking structure **413** to improve bond strength and securement of the bellows **70c** and ballast **72c**. In one embodiment, a plurality of protrusions **410** and corresponding recesses **412** are provided within the bellows **70c** and ballast **72c**, respectively. As shown in **FIGS. 37-38**, a relief ring **414** may be circumferentially provided about the ballast **72c** to assist in assembly of the second sub-assembly **408** with the first sub-assembly **400**, shown in **FIGS. 35-36**.

[0141] The assembled mechanical separator **420** is shown in **FIGS. 39-40** including the joined first sub-assembly **400** (shown in **FIGS. 35-36**) and the second sub-assembly **408** (shown in **FIGS. 37-38**). In one embodiment, the assembled mechanical separator **420** may be scaled to fit within a 13 mm collection tube (not shown).

[0142] In accordance with yet another embodiment of the present invention, as shown in **FIGS. 41-47**, a mechanical separator **500** may include a ballast **572**, a bellows **570**, a float **568**, and a pierceable head **566** as similarly described above. In this configuration, the float **568** and the pierceable head **566** may be co-formed or separately formed and subsequently assembled into a first sub-assembly, as described above. Referring specifically to **FIG. 48**, the float **568** may include an upper portion **570** having a profile **P** adapted for receiving the pierceable head portion **566**, shown in **FIGS. 49-50**, in such a fashion that the thickness **T** of the pierceable head portion **566** is substantially uniform across the diameter **D** of the pierceable head portion **566**, shown in **FIG. 49**. In one configuration, the upper portion **570** of the float **568** may have a recess **571** and the pierceable head portion **566** may have a corresponding protrusion **572** for mating with the recess **571** of float **568**. In another configuration, the upper portion **570** of the float **568** may have a protrusion **573**, such as a protrusion **573** flanked by corresponding recesses **574**. The pierceable head portion **566** may also have a protrusion **575** having a mating surface **576** for abutting a corresponding surface **577** of the protrusion **573** of the float **568**. The protrusion **575** of the pierceable head portion **566** may also include flanked protrusions **578** for engaging the corresponding recesses **574** of the float **568**. The pierceable head portion **566** may be provided over the upper portion **570** such that the thickness **T** of the pierceable head portion **566** is uniform over the opening **579** of the float **568**. In another embodiment, the pierceable head portion **566** may be provided over the upper portion **570** such that the thickness **T** of the pierceable head portion **566** is uniform over both the opening

579 of the float 566 and the surrounding ridge 581 of the float 566.

[0143] Referring once again to FIGS. 41-47, the ballast 572 and the bellows 570 may be co-formed or separately formed and subsequently assembled into a second sub-assembly, as described above. In one embodiment, the bellows 570 may include a protrusion 540, and the ballast 572 may include a corresponding recess 541 for receiving the protrusion 540 therein. The protrusion 540 and the recess 541 may correspondingly engage to form a locking structure 542, such that the ballast 572 and the bellows 570 are joined, and to improve bond strength and securement. In another embodiment, the bellows 570 may include a plurality of protrusions 540 spaced about a circumference of the bellows 570, and the ballast 572 may include a plurality of corresponding recesses 541 spaced about a circumference of the ballast 572.

[0144] The mechanical separator 500, shown in FIGS. 41-47 is shown in FIGS 51-53 disposed within a specimen collection container 530 and a closure 532, as described herein.

[0145] As shown in FIGS. 54-56, an alternative closure 42d may be utilized with the mechanical separator 420 of the present invention. In one embodiment, the closure 42d includes a receiving well 422 disposed within a portion of the closure adapted to receive a puncture tip (not shown) therein. The receiving well 422 may have any suitable dimensions to assist in centering the closure 42d with the puncture tip. In another embodiment, the receiving well 422 may include a tapered profile 423 for angling the puncture tip to the center 424 of the closure 42d. In yet another embodiment, as shown in FIGS. 57-58A, an alternative closure 42e may be utilized with the mechanical separator 420 of the present invention. In this configuration, the closure 42e may include an enlarged receiving well 422a adapted to receive a puncture tip (not shown) therein. The closure 42e may also include a smaller chamfered surface 483 adjacent the lower end 421 of the closure 42e for engaging a portion of the mechanical separator 420. In one embodiment, the chamfered surface 483 may include a first angled surface 484 and a second angled surface 485, with the first angled surface 484 having a greater angle than the second angled surface 485 for improving release of the mechanical separator 420 from the closure 42e.

[0146] In accordance with yet another embodiment of the present invention, shown in FIG. 59, a mechanical separator 600 may include a pierceable head portion 666, a float 668, a bellows 670, and a ballast 672 as described herein. In one configuration, the float 668 may be provided with a moveable plug 620 disposed within an interior portion 622 of the float 668. In one embodiment, the moveable plug 620 may be formed from the same material as the float 668, and in another embodiment, the moveable plug 620 may be formed from a material having substantially the same density as the density of the float 668. In yet another embodiment, the moveable plug 620 may be inserted within an interior portion 622

of the float 668 after formation of the float 668.

[0147] In certain situations, a mechanical separator 600 including a float 668 having a moveable plug 620 may be advantageous. For example, certain testing procedures require that a sample be deposited into a specimen collection container and that the specimen collection container be subjected to centrifugal force in order to separate the lighter and heavier phases within the sample, as described herein. Once the sample has been separated, the specimen collection container and sample disposed therein may be frozen, such as at temperatures of about -70 °C, and subsequently thawed. During the freezing process, the heavier phase of the sample may expand forcing a column of sample to advance upwardly in the specimen collection container and through a portion of the interior portion 622 of the float 668 thereby interfering with the barrier disposed between the lighter and heavier phases. In order to minimize this volumetric expansion effect, a moveable plug 620 may be provided within the interior portion 622 of the float 668.

[0148] The moveable plug 620 may be provided with a transverse hole 623 which is substantially aligned with a transverse hole 624 provided in the float 668 in the initial position, shown in FIG. 60, and is substantially blocked by a blocking portion 625 of the float 668 in the displaced position, as shown in FIG. 61. In one embodiment, the transverse hole 624 of the moveable plug 620 is disposed substantially perpendicular to a longitudinal axis R of the moveable plug 668. The moveable plug 668 may also be provided with a longitudinal hole 626 that is substantially aligned with the interior portion 622 of the float 668 to allow sample to be directed therethrough upon introduction of a sample into the mechanical separator, as discussed above.

[0149] Referring to FIG. 60, in the initial position a sample is introduced into the mechanical separator disposed within a specimen collection container (not shown) through the pierceable head portion 666, through the longitudinal hole 626 of the moveable plug 620 and through the interior portion 622 of the float 668. After sampling and during application of centrifugal force to the mechanical separator, air trapped within the interior portion 622 of the float 668 may be vented through the transverse hole 623 of the moveable plug and the transverse hole 624 of the float 668 and released from the mechanical separator 600. Specifically, air may be vented from between the float 668 and the bellows 670 as described herein.

[0150] Referring to FIG. 61, once the sample is separated into lighter and denser phases within the specimen collection container (not shown) the sample may be frozen. During the freezing process, the denser portion of the sample may expand upwardly. In order to prevent the upwardly advanced denser portion of the sample from interfering with the lighter phase, and to prevent the denser portion of the sample from escaping the float 668, the moveable plug 620 advances upwardly with the expansion of the denser phase of the sample. As the moveable

plug **620** is upwardly advanced, the transverse hole **623** of the moveable plug **620** aligns with a blocking portion **625** of the float **668**, which prevents sample from exiting the moveable plug **620** and interior portion **622** of the float **668** through the transverse hole **623**. The moveable plug **620** is adapted to advance with the expanded column of denser material present within the interior portion **622** of the float during freezing. It is anticipated herein, that the moveable plug **620** may be restrained at an upper limit of the pierceable head portion **666**, shown schematically in **FIGS. 59-61**. In this configuration, the elasticity of the pierceable head portion **666** acts as a stretchable balloon to constrain the moveable plug **620** within the mechanical separator **600**.

[0151] The advancement of the moveable plug **620** may be entirely passive and responsive to the externally applied freezing conditions of the sample. In certain instances, the moveable plug **620** may also be provided to return to its initial position upon subsequent thawing of the sample.

[0152] In yet another embodiment, as shown in **FIGS. 62-64**, a mechanical separator **700** may include a bellows **770**, a ballast **772**, as described herein, and a solid float **768** that does not require a pierceable head portion. In this configuration, it is anticipated that the mechanical separator **700** may be restrained within a specimen collection container **720** in an initial position. In one configuration, the mechanical separator **700** may be restrained with the specimen collection container **720** due to a frictional interference with a portion of the sidewall **722** of the specimen collection container **720**. In another embodiment, the specimen collection container **720** may include a first portion **724** having a first diameter **E** and a second portion **726** having a second diameter **F**, with the first diameter **E** being larger than the second diameter **F**. In this configuration, the mechanical separator **700** may be restrained at the interface of the first portion **724** and the second portion **726**.

[0153] During introduction of a sample into the specimen collection container **720**, a needle **730** pierces a portion of the closure **740** and introduces a sample into the interior **745** of the specimen collection container **720**. It is anticipated herein that the needle **730** does not pierce the float **768** but rather introduces the sample onto a top surface of the float **768**. Sample is then directed around the mechanical separator **700** and passes into the lower portions of the specimen collection container **720**. After the sample is introduced into the interior **745** of the specimen collection container **720**, the needle is removed and the closure re-seals. Upon application of centrifugal force, the mechanical separator **700** disengages from a restrained position with the sidewall **722** of the specimen collection container **720** upon deformation of the bellows **770** as described herein. In one configuration, at least one of the mechanical separator **700** and the specimen collection container **720** may include a recess for allowing sample to pass between the mechanical separator **700** and the sidewall **722** of the specimen collection container

720 during introduction of the sample.

[0154] In accordance with yet another embodiment, as shown in **FIG. 65**, a separation component **800** may be provided between a portion of the bellows **770** and the sidewall **722** of the specimen collection container **720** to assist in at least one of the restraint of the bellows **770** with the sidewall **722**, and the passage of sample around the bellows **770** upon entry of the sample into the specimen collection container. In this configuration, the separation component **800** may be a sleeve having an angled portion **801** adapted to allow passage of sample therearound. In accordance with another embodiment, as shown in **FIG. 66**, the specimen collection container **720** may include a ribbed protrusion **802**, such as a plurality of radially spaced ribbed protrusions **802**, spaced inwardly from a portion of the sidewall **722**. The ribbed protrusion **802** may allow sample to pass therearound while restraining at least a portion of the bellows **770** with the sidewall **722** of the specimen collection container **720**. In accordance with yet another embodiment, as shown in **FIG. 67**, the specimen collection container **720** may include a cutout **804**, such as a plurality of radially spaced cutouts **804**, within a portion of the sidewall **722**. The cutouts **804** may allow sample to pass therethrough while a portion of the sidewall **722** of the specimen collection container **720** restrains at least a portion of the bellows **770**.

[0155] In accordance with yet another embodiment, as shown in **FIGS. 68-70**, the mechanical separator **700** may be restrained against a sidewall **722** of the specimen collection container **720** by a washer **806**. The washer **806** may constrain a portion of the mechanical separator **700** such as a portion of the float **768** through an opening **810** in the washer **806**. The washer **806** may restrain the mechanical separator **700** with the sidewall **722** through an interference fit. Optionally, the washer **806** may be bonded to the sidewall **722** of the specimen collection container **720**. The washer **806** is configured to restrain the mechanical separator **700** with a portion of the specimen collection container **720** and to allow sample to pass around the mechanical separator **700** when introduced into the specimen collection container **720**. The washer **806** may hold the mechanical separator **700** in such a fashion that it substantially prevents the mechanical separator **700** from occluding the flow of sample into the specimen collection container **720**. Specifically, the washer **806** may hold the mechanical separator **700** in place within the specimen collection container **720** such that sample may pass between the bellows of the mechanical separator **700** and the sidewall **722** of the specimen collection container **720**. The washer **806** may also be used with a specimen collection container **700** having a first portion having a larger diameter and a second portion having a smaller diameter as shown herein. In this configuration, the washer **806** may prevent the bellows of the mechanical separator **700** from sealing the junction of the first portion and the second portion of the specimen collection container **720**, such as where the specimen

collection container **720** "necks down." In this configuration, the washer **806** prevents the mechanical separator **700** from occluding the path of sample into the specimen collection container **720**.

[0156] In one embodiment the washer **806** includes a plurality of ports **820** adapted to allow passage of the sample therethrough, as shown in **FIG. 69**. In another embodiment, the washer **806** includes a cut-away portion **822** adapted to allow passage of the sample between the washer **806** and a portion of the sidewall **722** of the specimen collection container **720**, as shown in **FIG. 70**.

[0157] In accordance with yet another embodiment, as shown in **FIG. 71**, in certain embodiments a portion of the sidewall **912** of the specimen collection container **900** may include a protrusion **914**. Optionally, opposing portions of the sidewall **912** may include opposing protrusions **914** adapted to allow a sample entering the specimen collection container **900** to pass around a portion of the bellows **916** of a mechanical separator **918** disposed therein. In this configuration, a portion of the sidewall **912** having a substantially straight profile may contact a portion of the bellows **916** to secure the mechanical separator **918** within the specimen collection container **900** by an interference fit. Another portion of the sidewall **912** of the specimen collection container **900**, such as opposing portions of the sidewall **912**, may include opposing protrusions having a substantially outwardly curved profile for allowing sample to pass between the sidewall **912** and the bellows **916**. In this configuration, the portion of the bellows **916** aligned with the opposing protrusions **914** do not touch the sidewall **912** of the specimen collection container **900**, establishing a space **920** for flow of sample therebetween.

[0158] Although the present invention has been described in terms of a mechanical separator disposed within the tube adjacent the open end, it is also contemplated herein that the mechanical separator may be located at the bottom of the tube, such as affixed to the bottom of the tube. This configuration can be particularly useful for plasma applications in which the blood sample does not clot, because the mechanical separator is able to travel up through the sample during centrifugation.

[0159] While the present invention is described with reference to several distinct embodiments of a mechanical separator assembly and method of use, those skilled in the art may make modifications and alterations without departing from the scope and spirit. Accordingly, the above detailed description is intended to be illustrative rather than restrictive.

Claims

1. A mechanical separator for separating a fluid sample into first and second phases within a tube, comprising:

a float comprising a passageway extending be-

tween a first upwardly oriented end and a second downwardly oriented end thereof;
a ballast longitudinally movable with respect to the float; and

a bellows extending between a portion of the float and a portion of the ballast, the bellows adapted for deformation upon longitudinal movement of the float and the ballast, the bellows isolated from the first upwardly oriented end of the float.




FIG.1
PRIOR ART




FIG.2




FIG.3




FIG.4




FIG. 6




FIG. 8




FIG. 5




FIG. 7




FIG. 9




FIG. 10




FIG.12




FIG.11




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG.23




FIG.24




FIG.25

FIG.26




FIG. 27




FIG. 28




FIG. 27A




FIG. 27B




FIG.30




FIG.29




FIG. 32




FIG. 31





FIG. 33

FIG. 34






FIG. 35




FIG. 36




FIG. 38




FIG. 37





FIG.39

420



420

FIG.40




FIG. 41




FIG. 42




FIG. 43




FIG. 45




FIG. 44




FIG. 47




FIG. 46






FIG.48






FIG.51




FIG. 52




FIG. 53




FIG. 54




FIG. 55






FIG. 56






Fig. 58A




Fig. 59




Fig. 60









Fig. 61








Fig. 71



EUROPEAN SEARCH REPORT

Application Number
EP 12 17 2336

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 2002/132367 A1 (MILLER HENRY F [US] ET AL) 19 September 2002 (2002-09-19) * page 5, paragraph 111-131 - page 6; figures 1-6 *	1	INV. B01L3/14 G01N1/00 G01N33/49
A	US 2002/094305 A1 (DICESARE PAUL C [US] ET AL) 18 July 2002 (2002-07-18) * paragraphs [0012] - [0090]; claim 1; figures *	1	
X	EP 1 006 360 A (BECTON DICKINSON CO [US]) 7 June 2000 (2000-06-07) * paragraphs [0053] - [0055], [0119], [0122]; example 2 *	1	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (IPC)
			B01L
Place of search		Date of completion of the search	Examiner
Munich		4 September 2012	Smith-Hewitt, Laura
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

1
EPO FORM 1503 03.02 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 12 17 2336

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-09-2012

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2002132367 A1	19-09-2002	NONE	

US 2002094305 A1	18-07-2002	DE 60023823 D1	15-12-2005
		DE 60023823 T2	10-08-2006
		EP 1106253 A2	13-06-2001
		ES 2253175 T3	01-06-2006
		JP 4722284 B2	13-07-2011
		JP 2001224982 A	21-08-2001
		US 2002094305 A1	18-07-2002

EP 1006360 A	07-06-2000	AT 328275 T	15-06-2006
		DE 69931584 T2	10-05-2007
		EP 1006360 A2	07-06-2000
		ES 2260882 T3	01-11-2006
		JP 4306902 B2	05-08-2009
		JP 2000199760 A	18-07-2000
		US 6479298 B1	12-11-2002

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 61082356 B [0001]
- US 61082365 B [0001]
- US 6803022 B [0005]