



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
07.11.2012 Bulletin 2012/45

(51) Int Cl.:
A01D 34/73 (2006.01) A01D 34/82 (2006.01)

(21) Application number: **12165759.7**

(22) Date of filing: **11.02.2009**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

(72) Inventor: **Koorn, Maarten**
3123 CP Schiedam (NL)

(30) Priority: **18.02.2008 NL 1035035**

(74) Representative: **Postma, Robert Erwin et al**
Octrooibureau Van der Lely N.V.
Weverskade 110
3147 PA Maassluis (NL)

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
09075069.6 / 2 090 150

Remarks:

This application was filed on 26-04-2012 as a divisional application to the application mentioned under INID code 62.

(71) Applicant: **Lely Patent N.V.**
3147 PA Maassluis (NL)

(54) **Mowing device**

(57) Mowing device (1) for plants, comprising at least one rotor with a rotor axis or first rotation axis, in particular a vertical rotor axis, and at least two blades (8) driven in rotation by the rotor, in which each blade (8) is attached

to an associated blade holder (11 a; 11 b), in which the blade holders (11 a, 11 b) are parts which are separate from one another and are attached to the rotor via a shearing connection.




FIG. 2

Description

BACKGROUND OF THE INVENTION

[0001] The invention relates to a mowing device for plants, such as grass.

[0002] Mowing devices are known comprising a series of adjacent cutting discs arranged on a beam structure, each of which is provided with one or more cutting blades and is rotated about vertical centre axes. The mowing device can in this case be coupled to an external drive, such as a power take-off of a tractor.

[0003] By means of a central top cover and a central bolt, the cutting disc is attached to a hub which forms part of the rotor. In this case, the cutting disc rests on a top flange of the hub.

[0004] Each of the cutting blades is elongate and rotatably attached to the cutting disc by means of a vertical bolt connection, so that, when a foreign object is hit, the cutting blade can turn inwards, out of the way of the object. When the blade is turned inwards with great force as a result of the impact, it may hit parts of the mowing beam which could thereby become damaged. In order to prevent the latter, the cutting disc is provided with a stop which is fitted on the bottom side of the cutting disc.

[0005] Not only the blades, but also the cutting discs themselves can hit foreign objects. The cutting discs may in this case become deformed and/or cause the drive components to be overloaded. These drive components may become damaged in the process and may have to be replaced. The cutting discs can also be deformed after such a blow and/or become misaligned with the adjacent cutting discs, which may result in the blades interfering with one another and further damage being caused.

SUMMARY OF THE INVENTION

[0006] It is an object of the invention to provide a mowing device which makes it possible to reduce the risk of damage occurring as a result of said impact.

[0007] It is an object of the invention to provide a mowing device which makes it possible to reduce the consequences of said impact.

[0008] It is an object of the invention to provide a mowing device which will be damaged less easily when said impact occurs.

[0009] It is an object of the invention to provide a mowing device which will become overloaded less easily when said impact occurs.

[0010] According to one aspect, the invention provides a mowing device for plants, comprising at least one rotor with a rotor axis or first rotation axis, in particular a vertical rotor axis, and at least one blade driven in rotation by the rotor, in which the blade is attached to a blade holder, which is attached to the rotor and is at least potentially rotatable about a second rotation axis which is situated at a radial distance from the first rotation axis.

[0011] By making the holder of the blade potentially

rotatable, the blade holder and the blade will be able to carry out a pivoting movement after an impact, thus making it possible to prevent damage to parts.

[0012] In one embodiment, the blade holder is then rotatable between a normal operating position, in which the orbit path of the blade holder has a greatest first diameter, and a retracted impact position, in which the orbit path has a greatest second diameter, the first diameter being greater than the second diameter. The mowing device can in this case be provided with means for forcing the blade holder to the impact position.

[0013] The connection of the blade holder to the rest of the rotor may comprise a shearing connection which keeps the blade holder in the normal operating position, in which rotation of the blade holder about the second rotation axis is prevented. Upon impact, the shearing connection breaks and rotatability is possible.

[0014] In one embodiment, it is possible to allow the second rotation axis, viewed in a perpendicular projection on a plane at right angles to the rotor axis, to be situated outside the blade, as a result of which the joint pivoting movement can be boosted.

[0015] The inward pivoting movement following an impact is supported by situating the second rotation axis, viewed in the direction of rotation of the rotor, in front of the frontmost radial plane through the first rotation axis and the blade.

[0016] When installing the blade holder, it may be advantageous if the distance between the second rotation axis and the rotor axis is smaller than the distance between the radial inner end of the blade and the first rotation axis.

[0017] In a further development of the mowing device according to the invention, the assembly of the blade holder and blade, viewed in the normal operating position, consists of a first portion which is situated, viewed in the direction of rotation of the rotor, in front of the radial plane with respect to a radial plane through the rotor axis or first rotation axis and the second rotation axis, and a second portion, adjoining the first portion and situated behind said radial plane to which the blade is attached, in which the first portion has a mass which is greater than the mass of the second portion. With such an arrangement, the holder might bend to a position where the blade and the blade holder are pivoted inwards.

[0018] In this case, the mowing device may be provided with a shearing connection between the respective blade holder and the rest of the rotor in order to keep the blade holder in the normal operating position. Upon the abovementioned impact, the shearing connection will break and the holder can then rotate in order to pivot the blade and the blade holder inwards.

[0019] In one embodiment, the rotor is provided with several separate blade holders which are each provided with a blade and which are arranged at regular distances from one another in the direction of rotation. Viewed in a perpendicular projection on a plane at right angles to the rotor axis, the blade holders may determine an interrupt-

ed plane, which may result in a saving in mass. Furthermore, the accessibility of the rotor can be improved for inspection, replacement of parts or lubrication.

[0020] Preferably, the shearing connection is designed to release several holders upon said impact so that they can rotate, thus preventing imbalance. In a simple embodiment, the shearing connection is combined for several blade holders. In another simple embodiment, the shearing connection is arranged in between blade holders.

[0021] In one embodiment, the rotor is provided with one or more stops for limiting the rotation of the blade holder about the second rotation axis. Thus, the blade itself does not have to absorb the impact load acting on the stop.

[0022] In a further development of the mowing device according to the invention, the blade is attached to the blade holder so as to be rotatable about a third rotation axis which is situated at a distance from the second rotation axis and preferably substantially parallel to the first rotation axis. Upon impact, the blade can then perform two additional rotation movements (that is in addition to the rotor movement).

[0023] In this case, the second rotation axis, viewed in the direction of rotation of the rotor, may be situated in front of a radial plane through the first rotation axis and the third rotation axis.

[0024] According to a further aspect, the invention provides a mowing device for plants, comprising a rotor with a rotor axis or first rotation axis, in particular a vertical rotor axis, and at least one blade driven in rotation by the rotor, in which the mowing device comprises a blade holder for the blade, in which the blade is, during normal operation, attached to the blade holder by a blade pivot pin or shaft which is situated at a radial distance from the first rotation axis so as to be freely rotatable, at least through an angle, in which the blade pivot pin can be displaced radially inwards. In this case, the blade pivot pin may be displaceable with a tangential directional component which extends in the same direction as the direction of rotation of the rotor. During normal use (i.e. when there has not yet been any impact), the blade may be able to rotate about the blade pivot pin against a stop, as is usual.

[0025] The blade holder can be connected to the rest of the rotor about a latent dedicated second rotation axis, which is situated at a distance from both the first rotation axis and the pivot pin. The first and second rotation axes and the pivot pin may determine a triangle in a plane of projection at right angles to the first rotation axis.

[0026] According to a further aspect, the invention provides a mowing device for plants, comprising at least one rotor with a rotor axis, in particular a vertical rotor axis, and at least two blades driven in rotation by the rotor, in which each blade is attached to an associated blade holder, in which the blade holders are parts which are separate from one another and are attached to the rotor via a shearing connection.

[0027] Preferably, the shearing connection is designed to release several blade holders upon said impact so that they can rotate, thus preventing imbalance. In a simple embodiment, the shearing connection is provided in between blade holders.

[0028] In an alternative embodiment, the shearing connection operates between each blade holder and a central part of the rotor. The central part of the rotor may form a hub for locking the bearings of the rotor. Alternatively, the central part itself may be attached to a hub which is intended for locking the bearings of the rotor.

[0029] According to a further aspect, with one or more of the above-described mowing devices, the invention provides that the rotor, which drives the blades for rotation in a blade rotation plane, is provided with means for bringing the blade outside the blade rotation plane when the blade holder is rotated with respect to the rest of the rotor. Following the impact mentioned, the respective blade, viewed vertically, then comes to lie above or below and outside the path of the blades of the adjacent cutting discs.

[0030] These means may, for example, comprise inclined surfaces for the blade holder, which become active upon rotation of the blade holder about its rotation axis. Following the said impact, the blade holder, and thus the blade which is attached thereto, will be forced into a higher or lower position by the inclined surfaces. Preferably, the inclined surfaces engage with the bottom side of the blade holder and extend upwards.

[0031] These means may, for example, also or alternatively comprise an arrangement of the blade holder in which the rotation axis for the blade holder is at an angle to the blade rotation plane.

[0032] Preferably, the rotation axis of the blade holder extends in an upward direction and, viewed in the direction of rotation of the blade holder about its rotation axis, backward direction with respect to a line which contains the rotation axis of the blade holder and a point of the blade, preferably of the cutting edge of the blade, preferably of the outer end of the cutting edge of the blade.

[0033] According to a further aspect, the invention provides a mowing device for plants, comprising at least one rotor with a rotor axis or first rotation axis, in particular a vertical rotor axis, and at least one blade which is driven in rotation by the rotor and in this case travels in a blade rotation plane, in which the blade is attached to a blade holder, which co-rotates with the rotor, in which the blade holder is connected to the rest of the rotor via a shearing connection and, when the latter breaks, is rotatable with respect to the rest of the rotor, in which the rotor is provided with means for bringing the blade outside the blade rotation plane when the blade holder is rotated with respect to the rest of the rotor.

[0034] According to a further aspect, the invention provides a mowing device for plants, comprising at least one rotor with a rotor axis or first rotation axis, in particular a vertical rotor axis, and at least one blade which is driven in rotation by the rotor, in which the blade is attached to

a blade holder, which co-rotates with the rotor and is attached to the rotor so as to at least potentially be rotatable about a second rotation axis which is situated at a radial distance from the rotor axis, in which the centre of gravity of the blade holder with the blade, viewed with respect to a line through the first and the second rotation axes, is situated on the side of that line which is turned away from the blade.

[0035] According to a further aspect, the invention provides a method for mowing plants, in which plants are mowed using a mowing device comprising at least one rotor with a rotor axis or first rotation axis, in particular a vertical rotor axis, and at least one blade which is driven in rotation by the rotor, in which a blade edge of the blade is turned opposite to the direction of rotation of the rotor in order to cut the plants while passing through a first orbit path, in which the blade, when it encounters an object which cannot be cut, rotates under the effect of a centrifugal force of the rotor rotation about a second rotation axis at a radial distance from the first rotation axis to a stable, retracted position under the effect of a centrifugal force of the rotor rotation, in which it follows a second orbit path which is concentric to the first orbit path but has a smaller diameter.

[0036] According to a further aspect, the invention provides a blade holder which is clearly suitable and intended for a mowing device according to the invention.

[0037] The aspects and measures described in this description and claims of the application and/or illustrated in the drawings of this application can, where possible, also be applied separately. These separate aspects, such as blades which pivot with holders, blades which rotate in multiple directions, several separate blade holders, the vertical displacement of the blades following an impact, and other aspects may be the subject of divisional patent applications to this effect. This applies in particular to the measures and aspects which have been described as such in the subclaims.

SHORT DESCRIPTION OF THE DRAWINGS

[0038] The invention will be explained with reference to an exemplary embodiment illustrated in the attached drawings, in which:

Fig. 1 shows a top view of a mowing device;

Fig. 2 shows a top view of a cutting disc assembly with two blade holders according to an embodiment of the invention, during normal operation;

Fig. 2A shows a vertical cross section through a portion of the assembly from Fig. 2, along line II A-II A;

Fig. 3 shows a vertical view with cross section of the cutting disc assembly from Fig. 2;

Fig. 4 shows the cutting disc assembly from Fig. 3, after an impact;

Fig. 4A shows a diagrammatic representation of a possible attachment of a blade holder according to the invention, and

Fig. 4B shows a diagrammatic representation of a possible angular range for the direction of a rotation axis for a blade holder.

DETAILED DESCRIPTION OF THE DRAWINGS

[0039] The mowing device 1 illustrated in Fig. 1 is attached, by means of frame 5, to the three-point suspension 4 of a tractor 2 which can move in a forward direction A. A power take-off 3 is connected to the mowing device for driving the former.

[0040] The frame 5 has a transversely projecting mowing beam 6, which accommodates a drive mechanism (not shown) which is coupled to the power take-off 3. The mowing beam furthermore has a series of cutting disc assemblies 7, the disc assemblies 7a of which rotate in the one direction B and the disc assemblies 7b rotate in the opposite direction C. In this example, the cutting disc assemblies have two blades 8 situated at opposite positions.

[0041] The cutting disc assembly 7 is illustrated in more detail in Figs. 2 and 3. Each blade 8 is provided with a cutting edge 9, which is directed in the direction of rotation C. By means of a pivot pin 10, each blade 8 is attached to a dedicated blade holder 11a, 11b, each of which is bent and panel-shaped (with the concave side on top) and, viewed in top view, have gaps 30 between them. The blade holders 11a,b have a leading edge region 13, which is formed in order to pass plants mowed by the preceding blade upwards, and a trailing edge region 14. The blade holders 11a,b are rotatably attached to a flange 21 of a hub 20 by means of bolts 15, illustrated in more detail in Fig. 3, the respective rotation axis being denoted by S2. The blades 8 themselves are attached to the dedicated blade holder 11a, 11b so as to be rotatable about rotation axis S3 of the pivot pin 10, with the pivot angle being limited by a stop at the bottom side of the respective blade holder, if desired. The rotation axes S1 and S3 are vertical and parallel to one another. The blade holders 11a,b are furthermore fixed to the flange 21 by means of breaking pins 16, as a result of which, during normal operation, without impact, they are held against rotation about rotation axis S2. However, following breaking of the breaking pin 16, they are potentially rotatable about said axis. By means of a central bolt 22, the hub 20 is attached to a gearwheel 25 which is driven by a drive shaft 27 via a right-angled transmission with gearwheel 26. The drive shaft 27 is indirectly driven by the power take-off 3 and extends in the longitudinal direction of the mowing beam 6 through housing 28 and drives several cutting disc assemblies which are arranged next to one another.

[0042] In Figs. 2 and 3, the central rotation axis S1 of the cutting disc assembly 7 is indicated. The outer path X1 of the ends of the blades 8, having a radius R1, is indicated and the outer path Y1 of the edge of the blade holders 11a,b is, having a radius R3, indicated. By drawing a radial T running through hinge 15, the blade holder

can be seen divided into a first portion I and a second portion II, which also carries the blade 8. The first portion I has a mass which is greater than that of the second portion II.

[0043] If, during operation, a blade 8 hits a hard foreign object, such as a stone, the blade can turn inwards about rotation axis S3. If the impact force experienced exceeds a specific value, the respective blade holder 11a, 11b can exert a force on the connection with the hub 20, as a result of which the breaking force of the breaking pin 16 is exceeded. This may also occur when the blade holder 11a, 11b itself hits the foreign object. In this case, it should be considered, that the speed in the direction A may be 15 km/h and the rotary speed of the cutting disc assembly 7 may be 3000/min. As a result of the breaking of the breaking pin 16, the respective blade holder remains connected to the hub 20 only at the location of bolt 15. As a result of the larger mass of portion I, the latter will bend outwards and the second portion II will bend inwards about the hinge 15 and rotation axis S2. The outer path X2 of the respective blade end will now take up a smaller radius R2. The outer path Y2 of the edge of the blade holders 11a,b will also take up a smaller radius R4. The same will happen if the other blade and/or the other blade holder also hits the same hard object. As a result of the weight distribution in the blade holders, the two blade ends and blade holders remain in the retracted position, in which they are outside the path of the blade ends and blade holders of the adjacent cutting disc assemblies.

[0044] If desired, a stop 24 may be provided on the hub or the other blade holder by means of which the blade holder is held in the position from Fig. 3.

[0045] If desired, a clamping means may be provided on the hub 20 or on the other blade holder 11b; 11a, by means of which the inward rotation of the blade holder 11a; 11b is limited.

[0046] It is also possible to combine the breaking pins 16 into a single shearing connection which is active directly between both blade holders 11a,b, for example in the form of a pull strip (not shown). Alternatively, the blade holders may overlap at the location of a single breaking pin which extends through both blade holders and the rest of the rotor, such as hub 20.

[0047] In order, after impact, to bring the blades 8 and/or the blade holder edges outside the paths of adjacent similar parts, use can also be made of one or more features by means of which the position in the vertical direction is changed. This can be done, for example, by designing the supporting surface 29 on the flange 21 for the blade holder 11a,b to rise in the direction of rotation of the blade holder 11a,b about rotation axis S2 (Fig. 4A). After the shearing connection has broken, the blade holder will then be forced upwards over the ascending surface 29, resulting in the blade 8 coming to lie higher as well (from Z1 to Z2). In this case, or alternatively, the rotation axis S2 may be allowed to be at an angle, by designing the hole in the flange 21 for the bolt 15 accordingly (Fig.

4A). The angle α of the ascending surfaces 29 and of rotation axis S2 may be in the order of magnitude of 10-20 degrees, so that the vertical displacement can take place quickly. The direction of the inclination can be related to the cutting edge of the blade 8, in particular the end thereof, so that this moves directly upwards after the breaking pin 16 has broken. In Fig. 4B, the line v has been rendered as a spot, which line, on the one hand, contains the intersection of a vertical and the rotation axis S2 and contains, on the other hand, the end of the cutting edge of the blade 8 (see also Fig. 4). In this example, the rotation axis will be situated in the upward direction on the trailing side (based on the direction of rotation D after impact) of the vertical. The rotation axis S2 is in this case inclined at an angle β of, for example, the abovementioned 10-20 degrees.

[0048] The above description is given in order to illustrate the operation of preferred embodiments of the invention and not in order to limit the scope of the invention. On the basis of the above explanation, many variations which fall within the spirit and scope of the present invention will be obvious to the person skilled in the art.

Claims

1. Mowing device (1) for plants, comprising at least one rotor with a rotor axis, in particular a vertical rotor axis or first rotation axis, and at least one blade (8) driven in rotation by the rotor, in which the blade (8) is attached to a blade holder (11a; 11b), which is attached to the rotor and is at least potentially rotatable about a second rotation axis which is situated at a radial distance from the rotor axis.
2. Mowing device (1) according to Claim 1, in which the blade holder (8) is rotatable between a normal operating position, in which the orbit path of the blade holder (8) has a greatest first diameter, and a retracted impact position, in which the orbit path has a greatest second diameter, the first diameter being greater than the second diameter.
3. Mowing device (1) according to Claim 2, provided with means for forcing the blade holder (11a; 11b) to the impact position.
4. Mowing device (1) according to Claim 1, 2 or 3, in which the connection of the blade holder (11a; 11b) to the rest of the rotor comprises a shearing connection which keeps the blade holder (11a; 11b) in the normal operating position.
5. Mowing device (1) according to one of the preceding claims, in which the second rotation axis, viewed in a perpendicular projection on a plane at right angles to the first rotation axis, is situated outside the blade (8), in which the second rotation axis, viewed in the

direction of rotation of the rotor, is preferably situated in front of the frontmost radial plane through the first rotation axis and the blade (8).

6. Mowing device (1) according to one of the preceding claims, in which the distance between the second rotation axis and the first rotation axis is smaller than the distance between the radial inner end of the blade (8) and the first rotation axis.
7. Mowing device (1) according to one of the preceding claims, in which the assembly of blade holder (11a; 11b) and blade (8), viewed in the normal operating position, consists of a first portion which is situated, viewed in the direction of rotation of the rotor, in front of the radial plane with respect to a radial plane through the first rotation axis and the second rotation axis, and a second portion, adjoining the first portion and situated behind said radial plane to which the blade (8) is attached, in which the first portion has a mass which is greater than the mass of the second portion.
8. Mowing device (1) according to one of the preceding claims, in which the rotor is provided with several separate blade holders (11a, 11b) which are each provided with a blade (8) and which are arranged at regular distances from one another in the direction of rotation.
9. Mowing device (1) according to Claim 8, in which, viewed in a perpendicular projection on a plane at right angles to the first rotation axis, the blade holders (11a, 11b) determine an interrupted plane.
10. Mowing device (1) according to Claim 4 and 8 or 9, in which the shearing connection is designed to release several blade holders (11a, 11b) upon said impact so that they can rotate.
11. Mowing device (1) according to Claim 10, in which the shearing connection is arranged in between blade holders (11a, 11b).
12. Mowing device (1) according to one of the preceding claims, in which the rotor is provided with one or more stops for limiting the rotation of the blade holder about the second rotation axis.
13. Mowing device (1) according to one of the preceding claims, in which the blade (8) is attached to the blade holder (11a; 11b) so as to be rotatable about a third rotation axis which is substantially parallel to the first rotation axis and is situated at a distance from the second rotation axis.
14. Mowing device (1) according to Claim 13, in which the second rotation axis, viewed in the direction of

rotation of the rotor, is situated in front of a radial plane through the first rotation axis and the third rotation axis.


15. Mowing device (1) for plants, comprising a rotor with a rotor axis or first rotation axis, in particular a vertical rotor axis, and at least one blade (8) rotatably driven by the rotor, in which the mowing device comprises a blade holder (11a; 11b) for the blade (8), in which the blade (8) is, during normal operation, attached to the blade holder (11a; 11b) by a blade pivot pin (10) or shaft which is situated at a radial distance from the first rotation axis so as to be freely rotatably, at least through an angle, in which the blade pivot pin (10) can be displaced radially inwards.
16. Mowing device (1) according to Claim 15, in which the blade pivot pin (10) is displaceable with a tangential directional component which extends in the same direction as the direction of rotation of the rotor.
17. Mowing device (1) according to Claim 15 or 16, in which the blade holder (11a; 11b) is connected to the rest of the rotor about a latent dedicated second rotation axis, which is situated at a distance from both the first rotation axis and the pivot pin (10).
18. Mowing device (1) according to Claim 15, 16 or 17, in which the first and second rotation axes and the pivot pin (10) determine a triangle in a plane of projection at right angles to the first rotation axis.
19. Mowing device (1) for plants, comprising at least one rotor with a rotor axis or first rotation axis, in particular a vertical rotor axis, and at least two blades (8) driven in rotation by the rotor, in which each blade (8) is attached to an associated blade holder (11a; 11b), in which the blade holders (11a, 11b) are parts which are separate from one another and are attached to the rotor via a shearing connection.
20. Mowing device (1) according to Claim 19, in which the shearing connection is active between both blade holders (11a, 11b).
21. Mowing device (1) according to Claim 19, in which the shearing connection is active between each blade holder (11a; 11b) and a central part of the rotor.
22. Mowing device (1) according to Claim 21, in which the central part of the rotor forms a hub (20) for locking the bearings of the rotor.
23. Mowing device (1) according to Claim 21, in which the central part is attached to a hub (20) which is intended for locking the bearings of the rotor.
24. Mowing device (1) according to one of the preceding

claims, in which the rotor drives the blade (8) for rotation in a blade rotation plane, furthermore provided with means for bringing the blade (8) outside the blade rotation plane when the blade holder (11a, 11b) is rotated with respect to the rest of the rotor.

25. Mowing device (1) according to Claim 24, in which said means comprise inclined surfaces for the blade holder (11a;11b), which become active upon rotation of the blade holder (11a;11b) about its rotation axis.
26. Mowing device (1) according to Claim 25, in which the inclined surfaces engage with the bottom side of the blade holder (11a;11b) and extend upwards.
27. Mowing device (1) according to Claim 24, 25 or 26, in which said means comprise an arrangement of the blade holder (11a;11b) in which the rotation axis for the blade holder (11a;11b) is at an angle to the blade rotation plane.
28. Mowing device (1) according to Claim 27, in which the rotation axis of the blade holder (11a;11b) extends in an upward direction and, viewed in the direction of rotation of the blade holder about its rotation axis, backward direction with respect to a line which contains the rotation axis of the blade holder (11a;11b) and a point of the blade (8), preferably of the cutting edge (9) of the blade (8), preferably of the outer end of the cutting edge (9) of the blade.
29. Mowing device (1) for plants, comprising at least one rotor with a rotor axis or first rotation axis, in particular a vertical rotor axis, and at least one blade (8) driven in rotation by the rotor which rotates in a blade rotation plane, in which the blade (8) is attached to a dedicated blade holder (11a;11b), which co-rotates with the rotor, in which the blade holder (11a;11b) is connected to the rest of the rotor via a shearing connection and, when the latter breaks, is rotatable with respect to the rest of the rotor, in which the rotor is provided with means for bringing the blade (8) outside the blade rotation plane when the blade holder (11a; 11b) is rotated with respect to the rest of the rotor.
30. Mowing device (1) for plants, comprising at least one rotor with a rotor axis or first rotation axis, in particular a vertical rotor axis, and at least one blade (8) which is driven in rotation by the rotor, in which the blade (8) is attached to a blade holder (11a;11b), which co-rotates with the rotor and is attached to the rotor so as to at least potentially be rotatable about a second rotation axis which is situated at a radial distance from the rotor axis, in which the centre of gravity of the blade holder with the blade, viewed with respect to a line through the first and the second rotation axes, is situated on the side of that line which is

turned away from the blade.

31. Blade holder (11a;11b), clearly suitable and intended for a mowing device (1) according to one of the preceding claims.
32. Cutting disc assembly comprising a beam with a number of mowing devices according to one of Claims 1-30 arranged thereon.
33. Method for mowing plants, in which plants are mowed using a mowing device comprising at least one rotor with a rotor axis or first rotation axis, in particular a vertical rotor axis, and at least one blade which is driven in rotation by the rotor, in which a blade edge of the blade is turned opposite to the direction of rotation of the rotor in order to cut the plants while passing through a first orbit path, in which the blade, when it encounters an object which cannot be cut, rotates under the effect of a centrifugal force resulting from the rotor rotation about a second rotation axis at a radial distance from the first rotation axis to a stable, retracted position under the effect of a centrifugal force of the rotor rotation, in which it follows a second orbit path which is concentric to the first orbit path but has a smaller diameter.
34. Device provided with one or more of the measures described in the attached description and/or illustrated in the attached drawings.
35. Method comprising one or more of the characterizing steps described in the attached description and/or illustrated in the attached drawings.







FIG. 2A




FIG. 4A




FIG. 4




FIG. 3




FIG. 4B

**PARTIAL EUROPEAN SEARCH REPORT**

Application Number

under Rule 62a and/or 63 of the European Patent Convention.
This report shall be considered, for the purposes of
subsequent proceedings, as the European search report

EP 12 16 5759

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	EP 0 394 176 A1 (ANDERSEN BERNT [DK] SPRAGELSE MASKINFABRIK AS [DK]) 24 October 1990 (1990-10-24) * the whole document *	19-29,32	INV. A01D34/73 A01D34/82
A	WO 2006/135952 A1 (ABERNETHY RAYMOND ERIC [AU]) 28 December 2006 (2006-12-28) * abstract * * page 8, line 23 - line 32 * * figure 16 *	19-29,32	
A	US 4 651 510 A (MALUTICH WILLIAM J [US]) 24 March 1987 (1987-03-24) * the whole document *	19-29,32	
A	US 5 791 131 A (HILL AMOS G [US] ET AL) 11 August 1998 (1998-08-11) * abstract *	19-29,32	
A	NL 8 101 567 A (MULTINORM BV) 3 August 1981 (1981-08-03) * the whole document *	19-29,32	
			TECHNICAL FIELDS SEARCHED (IPC)
			A01D
INCOMPLETE SEARCH			
The Search Division considers that the present application, or one or more of its claims, does/do not comply with the EPC so that only a partial search (R.62a, 63) has been carried out. Claims searched completely : Claims searched incompletely : Claims not searched : Reason for the limitation of the search: see sheet C			
Place of search		Date of completion of the search	Examiner
The Hague		27 September 2012	Espeel, Els
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

1
EPO FORM 1503 03.82 (P04E07)



**INCOMPLETE SEARCH
SHEET C**

Application Number

EP 12 16 5759

Claim(s) completely searchable:
19-23, 29

Claim(s) searched incompletely:
24-28, 32

Claim(s) not searched:
1-18, 30, 31, 33-35

Reason for the limitation of the search:

In response to the Rule 63(1) EPC communication sent by the EPO the Applicant confirmed (see the letter of 13.09.2012) that the claims submitted with the Applicant's letter of 26.06.2012 are indeed the claims for which the Applicant wants a search report to be drawn up.

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 12 16 5759

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

27-09-2012

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP 0394176	A1	24-10-1990	AU	635347 B2	18-03-1993
			AU	6467490 A	18-06-1992
			DE	69005881 D1	24-02-1994
			DK	194689 A	21-10-1990
			EP	0394176 A1	24-10-1990
			US	5090186 A	25-02-1992

WO 2006135952	A1	28-12-2006	US	2010043378 A1	25-02-2010
			WO	2006135952 A1	28-12-2006

US 4651510	A	24-03-1987	NONE		

US 5791131	A	11-08-1998	NONE		

NL 8101567	A	03-08-1981	NONE		
