



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:
Corrected version no 1 (W1 A3)
Corrections, see
Bibliography INID code(s) 72

(51) Int Cl.:
H01R 13/506 (2006.01) H01R 13/52 (2006.01)

(48) Corrigendum issued on:
21.01.2015 Bulletin 2015/04

(88) Date of publication A3:
29.10.2014 Bulletin 2014/44

(43) Date of publication A2:
12.12.2012 Bulletin 2012/50

(21) Application number: **12003835.1**

(22) Date of filing: **15.05.2012**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

(30) Priority: **06.06.2011 JP 2011126371**

(71) Applicant: **Sumitomo Wiring Systems, Ltd.**
Yokkaichi-city,
Mie 510-8503 (JP)

(72) Inventors:
• **Kitajima, Mitsunori**
Yokkaichi-city Mie 510-8503 (JP)
• **Hashimoto, Youjirou**
Yokkaichi-city Mie 510-8503 (JP)
• **Nakai, Kazuo**
Yokkaichi-city Mie 510-8503 (JP)

(74) Representative: **Müller-Boré & Partner**
Patentanwälte PartG mbB
Friedenheimer Brücke 21
80639 München (DE)

(54) **Connector and assembling method therefor**

(57) An object of the present invention is to easily unlock a locking means for locking an inner housing and an outer housing in an assembled state.

A connector includes a one-piece rubber plug 30 arranged to cover a rear surface 10R of an inner housing 10 and align seal holes 31 with cavities 12, an outer housing 20 including a tubular portion 21 surrounding the inner housing 10 and a rear wall portion 24 arranged to cover a rear surface 30R of the one-piece rubber plug 30 and align insertion holes 25 with the seal holes 31, locking holes 26A, 26B formed to be open on a rear surface 24R of the rear wall portion 24, and locking portions 17A, 17B formed on the inner housing 10 and engaged with the locking holes 26A, 26B to lock the both housings 10, 20 in an assembled state.

FIG. 2

