



(11) **EP 2 541 028 A8**

CORRECTED EUROPEAN PATENT APPLICATION

published in accordance with Art. 153(4) EPC

(15) Correction information:

(12)

Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 71, 72

(48) Corrigendum issued on: 17.04.2013 Bulletin 2013/16

(43) Date of publication: **02.01.2013 Bulletin 2013/01**

(21) Application number: 10846509.7

(22) Date of filing: 25.02.2010

(51) Int Cl.: **F02D 45/00** (2006.01)

(86) International application number: PCT/JP2010/052967

(87) International publication number: WO 2011/104844 (01.09.2011 Gazette 2011/35)

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

(71) Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA
Toyota-shi,
Aichi-ken, 471-8571 (JP)

(72) Inventors:

SATA, Kota
 Toyota-shi,
 Aichi-ken, 471-8571 (JP)

 OI, Yasuhiro Toyota-shi, Aichi-ken, 471-8571 (JP) SOEJIMA, Shinichi Toyota-shi, Aichi-ken, 471-8571 (JP)

 UEDA, Koichi Toyota-shi, Aichi-ken, 471-8571 (JP)

 OKAZAKI, Shuntaro Toyota-shi, Aichi-ken, 471-8571 (JP)
 YOSHIZAKI, Satoshi

Toyota-shi,
Aichi-ken, 471-8571 (JP)

(74) Representative: Kuhnen & Wacker Patent- und Rechtsanwaltsbüro Prinz-Ludwig-Strasse 40A 85354 Freising (DE)

(54) CONTROL DEVICE OF INTERNAL COMBUSTION ENGINE

(57) A control apparatus is provided for an internal combustion engine, which is capable of appropriately incorporating various types of requirements concerned with performance of the internal combustion engine, in particular, a requirement concerned with a time-integrated value of a control amount rather than an instantaneous value of the control amount in a target value of the control amount, and does not require that such requirements be expressed in a form of a requirement value of the control amount.

A control apparatus for an internal combustion engine is provided, in which various types of requirements

concerned with performance of the internal combustion engine are acquired and a restricting range of values of a control amount is set according to a specific detail of each requirement. At this time, the set restricting range is varied with time for specific requirements concerned with a time-integrated value of the control amount rather than an instantaneous value of the control amount. Next, the control apparatus determines a final restricting range based on overlaps between restricting ranges set for the requirements and determines a target value of the control amount, which falls within the final restricting range.

Fig.2

