(11) EP 2 570 625 A8

(12) CORRECTED EUROPEAN PATENT APPLICATION

published in accordance with Art. 153(4) EPC

(15) Correction information:

Corrected version no 1 (W1 A1) Corrections, see

Bibliography INID code(s) 72

(48) Corrigendum issued on: **05.06.2013 Bulletin 2013/23**

(43) Date of publication: **20.03.2013 Bulletin 2013/12**

(21) Application number: 10851394.6

(22) Date of filing: 12.05.2010

(51) Int Cl.: **F01N 3/08** (2006.01)

(86) International application number: PCT/JP2010/058036

(87) International publication number: WO 2011/142011 (17.11.2011 Gazette 2011/46)

(84) Designated Contracting States:

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

- (71) Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA Toyota-shi, Aichi-ken, 471-8571 (JP)
- (72) Inventors:
 - TOSHIOKA, Shunsuke Toyota-shi, Aichi-ken, 471-8571 (JP)

- HIROTA, Shinya Toyota-shi, Aichi-ken, 471-8571 (JP)
- ITOH, Kazuhiro Toyota-shi, Aichi-ken, 471-8571 (JP)
- FUKUDA, Koichiro Toyota-shi, Aichi-ken, 471-8571 (JP)
- MIKAMI, Akira Toyota-shi, Aichi-ken, 471-8571 (JP)
- (74) Representative: Kuhnen & Wacker Patent- und Rechtsanwaltsbüro Prinz-Ludwig-Strasse 40A 85354 Freising (DE)

(54) EXHAUST GAS PURIFICATION SYSTEM FOR INTERNAL COMBUSTION ENGINE

(57)An object of the present invention is to increase the flexibility in the layout of an exhaust gas purification system for an internal combustion engine including selective catalytic reduction catalyst provided in an exhaust passage of the internal combustion engine and an addition device for supplying reducing agent derived from ammonia to the selective catalytic reduction catalyst, without a deterioration of the performance in reducing nitrogen oxides. To achieve the object, the exhaust gas purification system for an internal combustion engine according to the present invention is configured to supply hydrocarbon at the same time when reducing agent derived from ammonia is supplied to the selective catalytic reduction catalyst, thereby producing reducing agent that is hard to be oxidized by a precious metal catalyst.




FIG.4

EP 2 570 625 A8