

(19)



(11)

EP 2 609 872 B2

(12)

NEW EUROPEAN PATENT SPECIFICATION

After opposition procedure

(45) Date of publication and mention
of the opposition decision:
02.01.2019 Bulletin 2019/01

(51) Int Cl.:
A61B 17/12 ^(2006.01) **A61B 17/34** ^(2006.01)
A61B 17/00 ^(2006.01) **A61F 2/95** ^(2013.01)

(45) Mention of the grant of the patent:
07.01.2015 Bulletin 2015/02

(21) Application number: **12189638.5**

(22) Date of filing: **06.05.2009**

(54) Medical device for a delivery of a medical implant

Medizinisches Vorrichtung zur Abgabe eines medizinischen Implantats

Dispositif médical pour fournir un implant médical

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL
PT RO SE SI SK TR**

(43) Date of publication of application:
03.07.2013 Bulletin 2013/27

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
09159586.8 / 2 248 471

(73) Proprietors:
• **Occlutech Holding AG**
8201 Schaffhausen (CH)
• **Maslanka, Herbert**
78532 Tuttlingen (DE)

(72) Inventors:
• **Nielsen, Stevan**
72108 Rottenburg Am Neckar (DE)
• **Maslanka, Herbert**
78532 Tuttlingen (DE)

(74) Representative: **KIPA AB**
P O Box 1065
251 10 Helsingborg (SE)

(56) References cited:
EP-A2- 0 698 373 **WO-A-2009/016265**
US-A- 5 486 193 **US-A- 5 725 552**
US-A1- 2003 045 901 **US-A1- 2003 181 945**
US-A1- 2007 112 381 **US-B1- 6 355 052**

EP 2 609 872 B2

Description

Field of the Invention

[0001] This invention pertains in general to the field of medical implants and delivery devices for such implants, as well as methods for transluminal delivery of medical devices into a body.

Background of the Invention

[0002] It is known that deployment of a medical implant within a patient's cardiovascular system.

[0003] For instance WO9742878A1 discloses a medical implant having an end for threadably attachment to a delivery wire.

[0004] However, treaded attachment may in certain clinical situations not unlock inside the body, when the implant is positioned. Consequently the implant has to be removed from the body together with delivery wire. This increases the time of surgery and related costs unnecessarily. Also, patient safety is reduced due to such unintended and undesired procedure.

[0005] Furthermore, the threaded attachment may loosen before implant is at final position and is unintentionally released in the patient's body. Loosening may for instance be initiated when the implant is collapsed in a catheter and the delivery wire is rotated during delivery relative a surrounding catheter. This may be done unintentionally by the human factor. Embolies may be caused by the loosened medical devices uncontrollably released in the body.

[0006] Both above failures have dire consequences for the patient and the health care system. Patient risk is increased.

[0007] Also, when the medical device is released from the catheter, and still attached to the threaded delivery wire, the medical implant is subject to bending, relative the longitudinal axis of the delivery wire, at least in certain anatomical positions. This is for instance the case in the heart where delivery is difficult perpendicular to a septal wall having an opening to be closed by the implant. This may affect the material of the device leading to fatigue of the device.

[0008] The implant is also affected by a force at release which either transposes through the medical implant and may then have a negative impact on the surrounding tissue or the medical implant inherently grasp the force and is affected as described above.

[0009] Also, a more flexible delivery is desired in terms of adjustments of the device used and applied methods, due to the fact that different patients are anatomically slightly different to one another and that the deficiency to be treated is most often individual and unique for each patient treated.

[0010] In US 2003/0181945 a coupling system for placement of implants is disclosed. Using for example a bead tethered from a medical implant, two prongs are

used to trap the implant. A pivoting movement of the implant is allowed along a plane of a half circular arc or slot which the two prongs form when they are trapping the implant.

[0011] US2007/112381 discloses a holder for an implant having gripper tongs with gripping jaws which open and close by a push/pull system, and which force-fit grips the head section of the holder.

[0012] In WO 2009/016265 A2 a method for producing a connection between two components of differing materials is taught. A sleeve is provided which is placed in a non-clamped manner around the welded end of a bundle of strands comprising the medical device. The sleeve is then to be held during a medical procedure.

[0013] US6355052 discloses an insertion aid inside a catheter for engaging a portion of an implant comprising a wire frame work.

[0014] Thus, there is a need for a deployment device which adjusts for differences in the cardiovascular system between patients still allowing a secure deployment of a medical implant.

[0015] Hence, an improved delivery device or system and a method would be advantageous. Also, a medical implant facilitating such improved delivery would be advantageous.

[0016] Hence, an improved delivery device or system, medical implant, and a method would be advantageous and in particular allowing for increased flexibility, cost-effectiveness, and/or patient safety would be advantageous.

Summary of the Invention

[0017] Accordingly, embodiments of the present invention preferably seeks to mitigate, alleviate or eliminate one or more deficiencies, disadvantages or issues in the art, such as the above-identified, singly or in any combination by providing a device, aggregate, according to the appended patent claims.

[0018] Further embodiments of the invention are defined in the dependent claims, wherein features for the second and subsequent aspects of the invention are as for the first aspect mutatis mutandis.

[0019] More particularly the invention relates to an apparatus for delivering of an occlusion device, and more particularly to intravascular delivery device for delivery of an occlusion device in the cardiovascular system.

[0020] Some embodiments of the invention provide for flexible delivery of a medical implant to anatomically difficult to reach sites in a body of a human or animal.

[0021] Some embodiments of the invention also provide for secure delivery of a medical implant

[0022] The new delivery system allows significant improvements in product handling. Before release of the occluder, the system allows a tilted angle of up to approximately 45 degrees without any stress or pull on the implant. Especially in challenging cases this feature has proven vital.

[0023] This allows the product to be placed in the final position without any adverse pull from a delivery wire. The safe-handling attachment system avoids any risk of unintended release during handling and allows a safe pull back into the catheter should the implantation be interrupted.

[0024] It should be emphasized that the term "comprises/comprising" when used in this specification is taken to specify the presence of stated features, integers, steps or components but does not preclude the presence or addition of one or more other features, integers, steps, components or groups thereof.

Brief Description of the Drawings

[0025] These and other aspects, features and advantages of which embodiments of the invention are capable of will be apparent and elucidated from the following description of embodiments of the present invention, reference being made to the accompanying drawings, in which

Fig. 1 is assembly view of kit;
 Fig. 2 is a rendered graphical composition;
 Fig. 3 is a cross-sectional view of the device;
 Fig. 4a and 4b are illustrations of the device in locked position (fig.4a) and a releasable position (fig.4b);
 Fig. 5 is a schematic view of the distal tip in a locked position;
 Fig. 6 is a schematic view of the distal tip in the release configuration;
 Fig. 7 is a schematic view illustrating the principle of locking a detachable device used in an embodiment of the invention;
 Fig. 8 is a schematic view of an interlocked device;
 Fig. 9a, b and c are schematic view illustrating another embodiment of the invention of interlocking a medical implant;
 Fig. 10 a and b are schematic views showing yet a further embodiment of the invention of interlocking medical implant;
 Fig. 11a, b and c are schematic views showing the flexibility in the joint between delivery catheter vs. medical implant;
 Fig. 12 is an illustration of an end of a medical implantable device;
 Fig. 13 is an illustration of a holding unit in various positions between locking and release;
 Fig. 14 is a perspective view of a proximal portion of a delivery device having a resiliently flexible unit;
 Figs. 15a and b are illustrations of a holding unit in release and locking position.

Description of embodiments

[0026] Specific embodiments of the invention now will be described with reference to the accompanying drawings. This invention may, however, be embodied in many

different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. The terminology used in the detailed description of the embodiments illustrated in the accompanying drawings is not intended to be limiting of the invention. In the drawings, like numbers refer to like elements.

[0027] The following description focuses on an embodiment of the present invention applicable to a septal occluder. However, it will be appreciated that the invention is not limited to this application but may be applied to many other medical implantable devices, including for example filters, stents, laa occluders, aneurysm treatment devices, grafts, etc.

[0028] An intravascular delivery device 1 comprises a delivery wire 100 having a proximal 10a and a distal end 10b and an interior lumen 151 extending therebetween (Fig. 3). The distal end 10b comprises a connection interface 140 adapted to matingly interlock with a proximal end portion 200 of a medical implantable device 2. The delivery device comprises a locking unit 110 arranged to secure the connection interface in a locking position.

[0029] The medical device is thus pivotably locked before a controlled release. Pivotally locked means that the medical device is securely attached to the distal end of the delivery device, while it still is able to move in a certain degree of freedom in relation to a longitudinal axis of the distal end of the delivery device. A degree of freedom is for instance rotatable around the longitudinal axis, or tiltable in relation thereto. This is described in more detail below.

[0030] In an embodiment, the intravascular delivery device comprises a locking wire 150 arranged moveably within the lumen 151 of the delivery wire 100 for relative longitudinal movement therein, the locking wire having a distal end comprising a holding structure 141, whereby the holding structure is axially moveable relative the delivery wire 100 between the locking position (Fig. 15b) at which the delivery wire encloses the holding structure and a second position at which the holding structure at least partly protrudes beyond the distal end of the delivery wire (Fig. 13, 15a) such that the connection interface unlocks and the medical implantable device is controllably released.

[0031] In an embodiment, the medical implantable device is an occlusion device for occluding a selected site in a body. The medical implantable device may be collapsible or expandible, such as self expandible. The medical implantable device 2 may thus be advantageously and securely delivered to a target site via a lumen of the body. At the target site, the device is moved forward out of the catheter, but still securely attached to the delivery wire at the connection interface 140.

[0032] The occlusion device is for instance an ASD or PFO occluder for septal occlusion.

[0033] The occlusion device is for instance an atrial

appendage occluder in other embodiments.

[0034] In this relation, for instance a first expanded diameter of the medical implantable device 2 may be positioned on a distal side of an opening in a wall, such as a septal or atrial wall. Then a second expanded diameter of the medical implantable device 2 may be positioned on a proximal side of the opening in the wall. Thus the opening is reliably occluded when the device is grown into the tissue of the wall, e.g. by endothelialisation.

[0035] Positioning in this anatomically demanding delivery application is facilitated by the delivery device of the present embodiments.

[0036] However, the device has to be reliably released from the delivery device 1. To this end, a locking unit 110 is unlocked. Here by threaded movement from the locked position (Fig. 4A) to the unlocked position (Fig. 4B). Alternatively, or in addition to threaded locking, other locking units may be provided, such as a latch, spring latch, cap, cover, lid, seal, enclosure, etc. The internal locking wire 150 in the lumen may now be moved forward to push the holding unit 141 at the connection interface out of a sleeve 150 thereof. As can be seen in Fig. 9 for instance, the medical implantable device is now free for release.

[0037] During delivery, the medical implantable device 2, when expanded out of the catheter, and also during delivery inside the catheter is rotatably free and may pivot both axially and radially. This increases flexibility during delivery through narrow passages of the lumen for delivery. In addition, when expanded out of the catheter, but still movably locked to the connection interface, the medical implantable device 2 may rotate freely and pivot/tilt both axially and radially, see e.g. Fig. 10 or 11. This provides a large degree of flexibility during delivery and adaptation to different anatomical situations at the target site of the medical implantable device 2.

[0038] In an embodiment, the connection interface holding the medical implantable device provides for an axial flexibility such that the medical implantable device may tilt relative the longitudinal axis of the delivery device.

[0039] Tilting angles of approximately 45 degrees are thus obtainable.

[0040] In an embodiment, the holding structure 141 is provided radially enlarged to at least partly contact the interior lumen of the distal end of the delivery wire, see e.g. Fig. 13.

[0041] The holding structure may have a distal recess into which a bundle of wires snugly fits. When the bundle of wires has a thickening, e.g. the spherically shaped end as shown in Fig. 12, it interlocks with the holding unit, once this is drawn into the sleeve 145.

[0042] Locking of the medical device 2 to the holding unit is provided by a positive fit which allows for a degree of free movement relative the delivery wire when locked.

[0043] In an embodiment, the distal part of the holding structure 141 is bowl-shaped and has a recess in the edge of the bowl-shaped portion at the distal end of the holding structure for receiving a portion of the medical implantable device. The bowl shaped portion, together

with a welded clot at the proximal end 200 having a substantially spherical shape (Fig. 12) provides for the pivotably in an embodiment.

[0044] In an embodiment, the recess is configured to enclose the proximal end portion of the medical implantable device at least partly.

[0045] Loading of the medical implantable device in to the delivery device and locking at the connection interface is e.g. illustrated in Figs. 7, 9 and 10. The flexibly locked position is shown in Fig. 8.

[0046] In an embodiment, the intravascular delivery device comprises a control device connected to the proximal end of the delivery wire for controllably unlocking of the connection interface. Thus may be integrated into a handle for convenient operation. The push operating unit 130 may be operated to move the entire delivery wire with the interlocked medical implantable device 2 at the distal end 10b through a catheter (not shown). When at the target site, and the medical implantable device provided out of the distal end of the catheter, it may be conveniently unlocked for detachment. Locking unit 110 is unlocked. A spring 115 provides a pre-load of the release operating unit 120. The spring may be tensioned against a stop unit 112. Upon pushing against the spring load, the locking wire 150 is pushed in the distal direction and the holding unit is moved out of the distal end 10b. Thus the medical implantable device is released and detached from the delivery device 1.

[0047] In an embodiment, the control device is secured when the holding structure is in the locking position such that the control device has to be manually operated to allow for the unlocking of the connection interface for controlled release of the medical implantable device from the delivery device, see Fig. 4A and B.

[0048] In an embodiment, a medical implantable device is provided having a proximal end portion adapted to matingly interlock with the connection interface. This is for instance the spherically welded clot of the medical implantable device 2 at the proximal end 200 thereof mating with the spherical recess (bowl-shaped) in the holding unit 141.

[0049] Fig. 14 is a perspective view of a proximal portion of a delivery device having a resiliently flexible unit 115b. The resiliently flexible unit is for instance a disc. The resiliently flexible unit is for instance made of rubber, silicone, or similar materials. Locking unit 110b has a broadened proximal end, in order to provide a larger fitting area to the resiliently flexible unit 115b.

[0050] The resiliently flexible unit 115b provides for flexibility of the delivery system even when the holding unit is in the locking position. In this manner, an axial flexibility may be provided when a medical device is locked to the holder unit 141 at the connection interface 140.

[0051] Spring 115 provides for a pre-tension of the holding structure 141 in sleeve of the connection interface 140 towards the locking position. This further enhances security of the delivery system. An unintentional

loosening of the medical device in the locked position is effectively avoided. Furthermore, when the medical device is positioned in the extended holding structure 141, the holding structure 141 is drawn back into the sleeve of the connection interface 140 when the spindle or release operating unit 120 is released. By screwing the locking unit 110 proximally, the connection interface is secured in the locking position.

[0052] The resiliently flexible unit 115b provides in this locking position several advantageous properties.

[0053] Firstly, a slight axial mobility is provided to the medical device when it is securely locked to the holder unit 141 at the connection interface 140. The axial movement is of course less than holder unit 141 moving out of the sleeve of the holding structure 141. The retracted locking position may also be provided so far in the sleeve of the holding structure 141 that this axial flexibility ends with the distal end of the holding structure 141 flush at the distal end 10b, as shown in Fig. 15b.

[0054] Secondly, the entire delivery device is kept flexible during delivery and a tension hardening of the flexible shaft 103. The flexible shaft is wound in form of a spiral. Bending of the flexible shaft is made at a larger radius than bending of the delivery wire 150 in the shaft 103. Forces may be extensive, which may damage the delivery instrument. The resiliently flexible unit 115b solves this issue by providing sufficient flexibility of the delivery device, in particular shaft 103 and delivery wire 150 therein, while securely keeping the medical device attached to the delivery device.

[0055] In an embodiment, the medical implantable device comprises a bundle of strands or wires (see Fig. 12), wherein the bundle of strands of the device comprising a welded end having a welded proximal end portion, wherein the welded proximal end portion has defined proportions and dimensions configured as a connection interface adapted to matingly interlock with a holding structure. The medical implantable device may be braided.

[0056] In an embodiment, the connection interface has a generally spherical shape.

[0057] In embodiments, the connection interface allows for pivotal movement when locked.

[0058] In an embodiment, an assembly is provided comprising:

- a delivery device 1 according to above, and
- a medical implantable device 2 according to above, arranged in a catheter for intravascular delivery of the medical implantable device 2.

[0059] In an embodiment, the assembly comprises an intravascular delivery device comprising a delivery wire having a proximal and a distal end and an interior lumen extending therebetween and wherein the distal end comprises a connection interface adapted to matingly interlock with a proximal end portion of a medical implantable device, an internal wire extending within the lumen of the delivery

wire which is controllable for relative longitudinal movement from the proximal end of the delivery wire, the internal wire having a distal end that carries a holding structure wherein the holding structure is axially moveable relative the delivery wire from a first position at which the delivery wire encloses the holding structure whereby the connection interface is adapted to matingly interlock with the proximal end portion of the medical implantable device to a second position at which the holding structure at least partly protrudes beyond the distal end of the delivery wire such that the connection interface unlocks and the medical implantable device is released; a control device connected to the proximal end of the delivery wire;

a medical implantable device comprising a bundle of strands, the bundle of strands of the device comprising a welded end having a welded proximal end portion, wherein the welded proximal end portion has defined proportions and dimensions configured as a connection interface adapted to matingly interlock with a holding structure, and;

wherein the medical implantable device is extendable from a relaxed condition capable of assuming a convoluted condition, to an extended, linear condition in which the medical implantable device can be advanced through the lumen of the catheter.

[0060] In one example, a method is provided for controlled delivery of the medical implantable device according to above at a selected site in a body vessel. The method comprises:

- introducing a distal end of the above described assembly into a lumen of the body to a delivery site;
- releasing the medical implantable device from the distal end of the catheter by pushing the delivery wire distally;
- controllably unlocking the medical implantable device from the connection interface by operating the locking unit to unlock, and;
- withdrawing the catheter and delivery wire from the body.

[0061] The medical implant may be made of a shape memory polymer material.

[0062] The medical implant may be made of metal, such as Nitinol.

[0063] The retention ball 200 is shaped from laser welded biocompatible Nitinol only, using no other metals. In addition to reducing the amount of material implanted and giving a less traumatic tip, this gives several additional advantages. Most importantly, by not locking the strands at the distal part into a rigid structure, the occluders remain more flexible providing:

- Superior adaptation to the septal tissue upon implantation
- Superior adaptation to challenging anatomy
- Sizing flexibility reducing the number of sizes needed

on stock

- Softer rims

[0064] As the occluder device does not have any threaded hub or clamp to provide an attachment for a delivery system. The amount of material implanted in this area is reduced substantially, such as with over 70% by utilizing a specific welding process to form a ball specifically designed for compatibility with the delivery system.

[0065] Furthermore, producing a medical implant has been perfected by its Nitinol surface technology to obtain an extremely smooth and flexible outer layer. A golden color of the implant has become synonymous with the highest standard in biocompatibility without risking cracks or deformations forming upon compression/ expansion. The composition of the layer is identical to what has been used in 100.000 of Nitinol medical implants with the added advantage of being more flexible.

[0066] The present invention has been described above with reference to specific embodiments. However, other embodiments than the above described are equally possible within the scope of the invention. The different features and steps of the invention may be combined in other combinations than those described. The scope of the invention is only limited by the appended patent claims.

Table of reference signs:

[0067]

1	delivery device
2	medical implantable device
3	assembly
10	handle
10a	distal end
10b	proximal end
100	delivery wire
110	Locking unit
110a	Locking unit
103	spiral - flexible shaft
111	thread
112	stop unit
115	spring
115b	resiliently flexible element
120	release operating unit
130	push operating unit
140	connection interface
141	holding unit
150	locking wire
200	proximal end portion with weld

Claims

1. An intravascular delivery device (1) comprising a delivery wire (100) having a proximal (10a) and a distal end (10b) and an interior lumen (151) extend-

ing longitudinally therebetween and wherein said distal end (10b) comprises a connection interface (140) adapted to matingly interlock with a proximal end portion (200) of a medical implantable device (2), wherein said delivery device (1) comprises a locking unit (110) arranged to secure said connection interface (140) in a locking position in which said medical implant is pivotably locked before a controlled release,

a locking wire (150) arranged moveably within the lumen of said delivery wire (100), said locking wire (150) having a distal end comprising a holding structure (141), said locking wire is movable forward to push said holding structure at said connection interface out of a sleeve thereof,

characterized by;

a recess in a distal edge of the distal end of said holding structure for receiving a portion of said medical implantable device whereby said medical implantable device is freely rotatable and both axially and radially pivotable.

3. The intravascular delivery device (1) according to claim 1, wherein said medical implantable device (2) is an occlusion device for occluding a selected site in a body.

4. The intravascular delivery device (1) according to any of claims 1 to 3, wherein said connection interface (140) holding said medical implantable device (2) provides for an axial flexibility such that said medical implantable device (2) may tilt relative the longitudinal axis of said delivery device (1).

5. The intravascular delivery device (1) according to any of claims 1 to 4, wherein said holding structure (141) is radially enlarged to at least partly contact the interior lumen of said distal end (10b) of said delivery wire (100).

6. The intravascular delivery device (1) according to claim 1, wherein said recess is configured to enclose said proximal end portion (200) of said medical implantable device (2) at least partly.

7. The intravascular delivery device according to any of claims 1 to 6 comprising a resiliently flexible unit (115b) arranged to provides for flexibility of the delivery system in said locking position.

8. In combination, a delivery device (1) of any of claims 1 to 7, and a medical implantable device (2) having a proximal end portion (200) adapted to matingly interlock with said connection interface (140) of said delivery device (1).

9. The combination of claim 8, wherein said medical implantable device (2) comprises a bundle of

strands, said bundle of strands of said device comprising a welded end having a welded proximal end portion (200), wherein said welded proximal end portion (200) has defined proportions and dimensions configured as a connection interface adapted to matingly interlock with a holding structure (141), wherein said connection interface has a generally spherical shape.

10. The combination of claim 8 or 9, wherein said connection interface (140) allows for pivotal movement when locked.
11. The combination of claim 8 to 10 arranged in a catheter for intravascular delivery of said medical implantable device.
12. The combination according to claim 8 for use with a catheter comprising: an intravascular delivery device (1) comprising
a delivery wire (100) having a proximal (10a) and a distal end (10b) and an interior lumen (151) extending there between and wherein said distal end (10b) comprises a connection interface (140) adapted to matingly interlock with a proximal end portion (10a) of a medical implantable device (2),
an internal wire extending within the lumen of said delivery wire (100) which is controllable for relative longitudinal movement from said proximal end (10a) of said delivery wire (100), said internal wire having a distal end that carries a holding structure (141) wherein said holding structure (141) is axially moveable relative said delivery wire (100) from a first position at which said delivery wire encloses said holding structure whereby said connection interface (140) is adapted to matingly interlock with said proximal end portion (10a) of said medical implantable device (2) to a second position at which said holding structure (141) at least partly protrudes beyond said distal end (10a) of said delivery wire (100) such that said connection interface (140) unlocks and said medical implantable device (2) is released;
a control device connected to said proximal end (10a) of said delivery wire;
a medical implantable device comprising a bundle of strands, said bundle of strands of said device comprising a welded end having a welded proximal end portion (200), wherein said welded proximal end portion (200) has defined proportions and dimensions configured as a connection interface adapted to matingly interlock with a holding structure (140), and;
wherein said medical implantable device (2) is extendable from a relaxed condition capable of assuming a convoluted condition, to an extended, linear condition in which said medical implantable device (2) can be advanced through the lumen of said catheter.

Patentansprüche

1. Intravaskuläre Zuführvorrichtung (1), umfassend ein Zuführdraht (100), der ein proximales (10a) und ein distales Ende (10b) sowie ein inneres Lumen (151) umfasst, das sich in Längsrichtung zwischen diesen erstreckt, und wobei das distale Ende (10b) eine Verbindungsschnittstelle (140) umfasst, die so angepasst ist, dass sie formschlüssig mit einem proximalen Endabschnitt (200) einer medizinischen implantierbaren Vorrichtung (2) ineinandergreift, wobei die Zuführvorrichtung (1) eine Verriegelungseinheit (110) umfasst, die so angeordnet ist, dass sie die Verbindungsschnittstelle (140) in einer Verriegelungsposition sichert, in der das medizinische Implantat auf schwenkbare Weise verriegelt ist, bevor eine kontrollierte Freigabe stattfindet, ein Verriegelungsdraht (150), der auf bewegliche Weise innerhalb des Lumens des Zuführdrahtes (100) angeordnet ist, wobei der Verriegelungsdraht (150) ein distales Ende (10b) aufweist, das eine Haltestruktur (141) umfasst, wobei sich der Zuführdraht nach vorn bewegen lässt, um die Haltestruktur an der Verbindungsschnittstelle aus deren Hülse zu schieben,
dadurch gekennzeichnet, dass
eine Aussparung an einer distalen Kante des distalen Endes der Haltestruktur zur Aufnahme eines Abschnittes der medizinischen implantierbaren Vorrichtung, wodurch sich die medizinische implantierbare Vorrichtung frei drehen und sowohl axial als auch radial verschwenken lässt.
3. Intravaskuläre Zuführvorrichtung (1) gemäß Anspruch 1, wobei es sich bei der medizinischen implantierbaren Vorrichtung (2) um eine Okklusionsvorrichtung zur Okklusion einer ausgewählten Stelle in einem Körper handelt.
4. Intravaskuläre Zuführvorrichtung (1) gemäß einem beliebigen der Ansprüche 1 bis 3, wobei die Verbindungsschnittstelle (140), welche die medizinische implantierbare Vorrichtung (2) hält, eine axiale Flexibilität gewährleistet, so dass die medizinische implantierbare Vorrichtung (2) in Bezug auf die Längsachse der Zuführvorrichtung (1) gekippt werden kann.
5. Intravaskuläre Zuführvorrichtung (1) gemäß einem beliebigen der Ansprüche 1 bis 4, wobei die Haltestruktur (141) radial vergrößert ist, so dass sie mindestens teilweise mit dem inneren Lumen des distalen Endes (10b) des Zuführdrahtes (100) in Kontakt kommt.
6. Intravaskuläre Zuführvorrichtung (1) gemäß Anspruch 1, wobei die Aussparung so eingerichtet ist, dass sie einen proximalen Endabschnitt (200) der

medizinischen implantierbaren Vorrichtung (2) mindestens teilweise umschließt.

7. Intravaskuläre Zuführvorrichtung gemäß einem beliebigen der Ansprüche 1 bis 6, umfassend eine elastisch flexible Einheit (115b), die so angeordnet ist, dass sie die Flexibilität des Zuführsystems in der Verriegelungsposition gewährleistet. 5
8. Kombination aus einer Zuführvorrichtung (1) gemäß einem beliebigen der Ansprüche 1 bis 7 und einer medizinischen implantierbaren Vorrichtung (2), die einen proximalen Endabschnitt (200) umfasst, der so angepasst ist, dass er auf formschlüssige Weise mit der Verbindungsschnittstelle (140) ineinandergreift. 10
9. Kombination gemäß Anspruch 8, wobei die medizinische implantierbare Vorrichtung (2) einen Bündel aus Strängen umfasst, wobei das Bündel aus Strängen der Vorrichtung ein geschweißtes Ende aufweist, das einen geschweißten proximalen Endabschnitt (200) umfasst, wobei der geschweißte proximale Endabschnitt (200) definierte Proportionen und Dimensionen aufweist, die als eine Verbindungsschnittstelle eingerichtet sind, welche so angepasst ist, dass sie auf formschlüssige Weise mit einer Haltestruktur (141) ineinandergreift, wobei die Verbindungsschnittstelle eine im Allgemeinen kugelförmige Form aufweist. 15
10. Kombination aus Anspruch 8 oder 9, wobei die Verbindungsschnittstelle (140) bei Verriegelung eine Schwenkbewegung erlaubt. 20
11. Kombination gemäß Anspruch 8 bis 10, angeordnet in einem Katheter zur intravaskulären Zufuhr der medizinischen implantierbaren Vorrichtung. 25
12. Kombination gemäß Anspruch 8 zur Benutzung mit einem Katheter, umfassend: eine intravaskuläre Zuführvorrichtung (1), umfassend 30
 - einen Zuführdraht (100), der ein proximales (10a) und ein distales Ende (10b) sowie ein inneres Lumen (151) aufweist, das sich zwischen diesen erstreckt, und wobei das distale Ende (10b) eine Verbindungsschnittstelle (140) umfasst, die so angepasst ist, dass sie auf formschlüssige Weise mit einem proximalen Endabschnitt (10a) einer medizinischen implantierbaren Vorrichtung (2) ineinandergreift, 35
 - einen inneren Draht, der sich innerhalb des Lumens des Zuführdrahtes (100) erstreckt, der sich für eine relative Längsbewegung von dem proximalen Ende (10a) des Zuführdrahtes (100) steuern lässt, wobei der innere Draht ein distales Ende umfasst, das eine Haltestruktur (141) trägt, wobei sich die Haltestruktur (141) in Bezug auf den Zuführdraht (100) von einer ersten Position, in welcher der Zuführdraht die Hal-

testruktur umgibt, wodurch die Verbindungsschnittstelle (140) so angepasst ist, dass sie auf formschlüssige Weise mit dem proximalen Endabschnitt (10a) der medizinischen implantierbaren Vorrichtung (2) ineinandergreift, axial in eine zweite Position bewegen lässt, in welcher die Haltestruktur (141) mindestens teilweise bis über ein distales Ende (10a) des Zuführdrahtes (100) hervorragt, so dass die Verbindungsschnittstelle (140) entriegelt und die medizinische implantierbare Vorrichtung (2) freigegeben wird;

eine Steuervorrichtung, die mit dem proximalen Ende (10a) des Zuführdrahtes verbunden ist;

eine medizinische implantierbare Vorrichtung, die ein Bündel aus Strängen umfasst, wobei das Bündel aus Strängen der Vorrichtung ein geschweißtes Ende umfasst, das einen geschweißten proximalen Endabschnitt (200) aufweist, wobei der geschweißte proximale Endabschnitt (200) definierte Proportionen und Dimensionen aufweist, die als eine Verbindungsschnittstelle eingerichtet sind, welche so angepasst ist, dass sie auf formschlüssige Weise mit einer Haltestruktur (140) ineinandergreift, und;

wobei sich die medizinische implantierbare Vorrichtung (2) aus einem entspannten Zustand, der einen zusammengerollten Zustand einnehmen kann, in einen erweiterten, linearen Zustand erweitern lässt, in dem sich die medizinische implantierbare Vorrichtung (2) durch das Lumen des Katheters vorwärts schieben lässt.

Revendications

1. Dispositif de mise en place intravasculaire (1) comprenant 35
 - un câble de mise en place (100) présentant une extrémité proximale (10a) et une extrémité distale (10b) et une lumière intérieure (151) s'étendant longitudinalement entre celles-ci et où ladite extrémité distale (10b) comprend une interface de liaison (140) conçue pour s'interverrouiller par emboîtement avec une partie d'extrémité proximale (200) d'un dispositif médical implantable (2), où ledit dispositif de mise en place (1) comprend une unité de verrouillage 40 (110) agencée afin de fixer ladite interface de liaison (140) dans une position de verrouillage dans laquelle ledit implant médical est verrouillé avec possibilité de pivotement avant une libération contrôlée,
 - un câble de verrouillage (150) agencé de façon à pouvoir être déplacé dans la lumière dudit câble de mise en place (100), ledit câble de verrouillage (150) présentant une extrémité distale comprenant une structure de maintien (141), ledit câble de verrouillage pouvant être déplacé vers l'avant pour pousser ladite structure de maintien au niveau de ladite interface de liaison hors d'une gaine de celle-ci 45
- caractérisé par ;** 55

- un évidement dans un bord distal de l'extrémité distale de ladite structure de maintien pour recevoir une partie dudit dispositif médical implantable grâce à quoi ledit dispositif médical implantable peut librement pivoter axialement et radialement.
3. Dispositif de mise en place intravasculaire (1) selon la revendication 1, dans lequel ledit dispositif médical implantable (2) est un dispositif d'occlusion destiné à occlure un site sélectionné dans un corps.
 4. Dispositif de mise en place intravasculaire (1) selon l'une quelconque des revendications 1 à 3, dans lequel ladite interface de liaison (140) supportant ledit dispositif médical implantable (2) permet une flexibilité axiale de telle sorte que ledit dispositif médical implantable (2) peut être incliné par rapport à l'axe longitudinal dudit dispositif de mise en place (1).
 5. Dispositif de mise en place intravasculaire (1) selon l'une quelconque des revendications 1 à 4, dans lequel ladite structure de maintien (141) est élargie radialement pour être au moins partiellement en contact avec la lumière intérieure de ladite extrémité distale (10b) dudit câble de mise en place (100).
 6. Dispositif de mise en place intravasculaire (1) selon la revendication 1, dans lequel ledit évidement est configuré pour entourer ladite partie d'extrémité proximale (200) dudit dispositif médical implantable (2) au moins partiellement.
 7. Dispositif de mise en place intravasculaire (1) selon l'une quelconque des revendications 1 à 6 comprenant une unité flexible de manière résiliente (115b) agencée pour permettre une flexibilité du système de mise en place dans ladite position de verrouillage.
 8. En combinaison, un dispositif de mise en place (1) selon l'une quelconque des revendications 1 à 7, et un dispositif médical implantable (2) présentant une partie d'extrémité proximale (200) conçue pour s'interverrouiller par emboîtement avec ladite interface de liaison (140) dudit dispositif de mise en place (1).
 9. Combinaison selon la revendication 8, dans laquelle ledit dispositif médical implantable (2) comprend un faisceau de brins, ledit faisceau de brins dudit dispositif comprenant une extrémité soudée présentant une partie d'extrémité proximale soudée (200), où ladite partie d'extrémité proximale soudée (200) a des proportions et des dimensions définies configurées comme une interface de liaison conçue pour s'interverrouiller par emboîtement avec une structure de maintien (141), où ladite interface de liaison présente une forme globalement sphérique.
 10. Combinaison selon la revendication 8 ou 9, dans laquelle ladite interface de liaison (140) permet un mouvement de pivotement lorsqu'elle est verrouillée.
 11. Combinaison selon les revendications 8 à 10 agencée dans un cathéter pour une mise en place intravasculaire dudit dispositif médical implantable.
 12. Combinaison selon la revendication 8 destinée à être utilisée avec un cathéter comprenant : un dispositif de mise en place intravasculaire (1) comprenant un câble de mise en place (100) présentant une extrémité proximale (10a) et une extrémité distale (10b) et une lumière intérieure (151) s'étendant entre celles-ci et où ladite extrémité distale (10b) comprend une interface de liaison (140) conçue pour s'interverrouiller par emboîtement avec une partie d'extrémité proximale (10a) d'un dispositif médical implantable (2), un câble interne s'étendant dans la lumière dudit câble de mise en place (100), lequel est contrôlable pour un mouvement longitudinal relatif par rapport à ladite extrémité proximale (10a) dudit câble de mise en place (100), ledit câble interne présentant une extrémité distale qui porte une structure de maintien (141), où ladite structure de maintien (141) peut être déplacée axialement par rapport audit câble de mise en place (100) entre une première position à laquelle ledit câble de mise en place entoure ladite structure de maintien grâce à quoi ladite interface de liaison (140) est conçue pour s'interverrouiller par emboîtement avec ladite partie d'extrémité proximale (10a) dudit dispositif médical implantable (2) et une deuxième position à laquelle ladite structure de maintien (141) dépasse au moins partiellement au-delà de ladite extrémité distale (10a) dudit câble de mise en place (100) de telle sorte que ladite interface de liaison (140) est déverrouillée et que ledit dispositif médical implantable (2) est libéré ; un dispositif de contrôle relié à ladite extrémité proximale (10a) dudit câble de mise en place ; un dispositif médical implantable comprenant un faisceau de brins, ledit faisceau de brins dudit dispositif comprenant une extrémité soudée présentant une partie d'extrémité proximale soudée (200), où ladite partie d'extrémité proximale soudée (200) a des proportions et des dimensions définies configurées comme une interface de liaison conçue pour s'interverrouiller par emboîtement avec une structure de maintien (140), et ; où ledit dispositif médical implantable (2) peut être déployé à partir d'un état relâché pouvant adopter un état convoluto, à un état linéaire déployé dans lequel ledit dispositif médical implantable (2) peut être avancé à travers la lumière dudit cathéter.





Fig. 1




Fig. 2




Fig. 3




Fig. 4A




Fig. 4B




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15a




Fig. 15b

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 9742878 A1 [0003]
- US 20030181945 A [0010]
- US 2007112381 A [0011]
- WO 2009016265 A2 [0012]
- US 6355052 B [0013]