



(11)

EP 2 615 808 A1

(12)

EUROPEAN PATENT APPLICATION
published in accordance with Art. 153(4) EPC

(43) Date of publication:
17.07.2013 Bulletin 2013/29

(51) Int Cl.:
H04M 1/725 (2006.01) **H04L 29/06** (2006.01)
H04W 88/00 (2009.01)

(21) Application number: **11822993.9**

(86) International application number:
PCT/CN2011/071192

(22) Date of filing: **23.02.2011**

(87) International publication number:
WO 2012/031470 (15.03.2012 Gazette 2012/11)

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(72) Inventor: **LIANG, Xiguang**
Shenzhen
Guangdong 518057 (CN)

(30) Priority: **06.09.2010 CN 201010274114**

(74) Representative: **D'Halleweyn, Nele Veerle Trees**
Gertrudis et al
Arnold & Siedsma
Sweelinckplein 1
2517 GK Den Haag (NL)

(71) Applicant: **ZTE Corporation**
Shenzhen, Guangdong 518057 (CN)

(54) **MOBILE TERMINAL**

(57) The disclosure provides a mobile terminal, comprising: a fixed network access control module, configured to connect mobile terminal with analogue subscriber line and notify central processor that the mobile terminal is connected with fixed telephone network when analogue subscriber line is connected with analogue subscriber line interface, a frequency shift keying processing module, configured to identify the signaling from the analogue subscriber line, then send the signaling to the central processor, and to identify the signaling from the central processor, and then send the signaling to the analogue subscriber line, a call processing module, configured to extract the voice signal from the analogue subscriber line and send the voice signal to the voice output device of the mobile terminal to be played, and send the voice signal from the user to the analogue subscriber line, a mobile communication module, and a central processor.




Fig. 1

EP 2 615 808 A1

Description

Field of the Invention

[0001] The invention relates to the field of communication, and in particular to a mobile terminal.

Background of the Invention

[0002] With the continuous development of the telecommunication network, the broadcast-TV network and the Internet, at present, it is proposed that the three networks should be converged together. The "triple-play" technology is currently under development. Through the convergence of the three networks, interconnection and resource sharing can be realized among the three networks to provide various services to users, such as voice, data and broadcast TV. Actually, the triple-play is essentially the convergence of services. And, the convergence of services eventually reflects on the terminals. Therefore, how to design reasonable terminals according to the demands of triple-play becomes an important factor in realizing triple-play.

[0003] With the continuous expansion of the communication service scale of the mobile communication system, the limit of the capacity of the mobile communication system due to the finiteness of the radio resources (radio frequency spectrums) has been shown. The industry has considered and is preparing to combine the finite radio resources and the relatively infinite wired resources, to fully utilize the existed fixed communication network resources to improve the capacity of the mobile communication system and the user experience.

[0004] On the other hand, with the development of the society, people are more concerned about the environment. More and more people are aware of the hazards of radio waves to the health. Simultaneously, for quite a number of mobile users, they stay in an environment with fixed telephone network access resources in most occasions without needing mobile communication. For example, when the user stays in the office or at home, it is very possible that there is a fixed telephone beside the user and the user also takes the mobile phone along. But, other users calling this user may not know whether there is a fixed telephone in the environment where the user stays. Then, when in communication with the user, they still call the mobile phone of the user, which obviously wastes resources and causes unnecessary damages to the environment and the health.

[0005] However, the related mobile terminals are unable to utilize more environmentally-friendly wired communication modes to perform communication. No effective solution has been proposed in the related art.

Summary of the Invention

[0006] In allusion to the problems of serious waste of resources when in communication and considerable

damage to the health and the environment caused as the mobile terminals are unable to utilize wired communication modes to perform communication in the related technologies, the disclosure proposes a mobile terminal, a fixed communication network access processing module is added in the related mobile terminals, so that not only the flexibility of the related mobile terminals is maintained, but also the fixed network communication resources can be utilized to perform communication in wired mode.

[0007] The technical solution of the disclosure is implemented as follows. According to one aspect of the disclosure, a mobile terminal is provided.

[0008] The mobile terminal comprises a central processor, a fixed network access control module, a frequency shift keying processing module, a call processing module, a mobile communication module and an electronic switch module.

[0009] Specifically, the fixed network access control module is connected with the central processor, comprises an analogue subscriber line interface, and is configured to connect the mobile terminal and an analogue subscriber line, and to notify the central processor that the mobile terminal is connected with a fixed telephone network when the analogue subscriber line is connected with the analogue subscriber line interface; the frequency shift keying processing module is connected with the central processor, and is configured to identify a signaling from the connected analogue subscriber line and send the signaling from the connected analogue subscriber line to the central processor, and to identify a signaling from the central processor and send the signaling from the central processor to the connected analogue subscriber line; the call processing module is configured to extract a voice signal from the analogue subscriber line and send the voice signal from the analogue subscriber line to a voice output device of the mobile terminal to be played, and to send a voice signal from a user to the analogue subscriber line; the mobile communication module is configured to achieve communication between the mobile terminal and outside based on a radio network; and the central processor is configured to process a signaling from the frequency shift keying processing module and send a signaling to be transmitted by the subscriber line to the frequency shift keying processing module, and to control the electronic switch module to close a radio frequency sending/receiving function of the mobile communication module when the fixed network access control module notifies that the mobile terminal is connected with the fixed network.

[0010] The mobile terminal may further comprise: a ringing current processing module, connected with the central processor, and configured to identify a ringing current signal from the analogue subscriber line and report a ringing corresponding to the ringing current signal to the central processor.

[0011] In addition, the central processor is further configured to determine whether a called number received

by the frequency shift keying processing module is a user number of the mobile terminal, and if yes, control the mobile terminal to continue to perform incoming call processing.

[0012] Furthermore, the electronic switch module is further configured to, under control of the central processor, enable at least one of the frequency shift keying processing module, the call processing module and the ringing current processing module to be connected with the analogue subscriber line.

[0013] In addition, the central processor is further configured to control the electronic switch module to connect the ringing current processing module with the analogue subscriber line when the mobile terminal accesses the fixed telephone network.

[0014] Further, the central processor is further configured to control the electronic switch module to connect the call processing module with the analogue subscriber line when the mobile terminal needs to perform voice communication.

[0015] Furthermore, the central processor is further configured to control the electronic switch module to connect the frequency shift keying processing module with the analogue subscriber line when the mobile terminal performs short message transmission.

[0016] In addition, the mobile terminal may further comprise an audio input module and an audio output module; and the call processing module may be further configured to send the voice signal from the user, which is input through the audio input module, to the analogue subscriber line, and send the voice signal from the analogue subscriber line to the voice output module.

[0017] Optionally, the central processor may be one of the following: a baseband processor and a central processing unit.

[0018] The technical solution of the disclosure reconstructs the mobile terminal, and sets the functional modules for signaling transmission, voice signal transmission and analogue subscriber line. Thus, the mobile terminal can access and stay in the fixed telephone network, and can perform voice signal transmission and signaling (including short message) transmission with the fixed telephone network through the analogue subscriber line. Therefore, the convergence of mobile communication and fixed telephone network communication is realized for the mobile terminal. On the basis of maintaining the mobile communication function, the function of the wired communication is added. Hence, the hazard of radio waves to health and environment is reduced, and the radio resources are saved.

Brief Description of the Drawings

[0019]

Fig. 1 is a structure block diagram of a mobile terminal according to an embodiment of the disclosure;
Fig. 2 is a diagram of a fixed network access control

module in a converged terminal according to an embodiment of the disclosure;

Fig. 3 is a specific structure block diagram of a converged terminal according to an embodiment of the disclosure;

Fig. 4 is a processing flow chart of accessing the fixed telephone network when the converged terminal is in the idle state according to an embodiment of the disclosure;

Fig. 5 is a processing flow chart of accessing the fixed telephone network when the converged terminal is in a call according to an embodiment of the disclosure;

Fig. 6 is a processing flow chart of exiting the fixed telephone network when the converged terminal is in the idle state according to an embodiment of the disclosure;

Fig. 7 is a processing flow chart that the converged terminal exits the fixed telephone network during a call according to an embodiment of the disclosure;

Fig. 8 is a flow chart of the processing that the converged terminal connected to the fixed telephone network initiates a call according to an embodiment of the disclosure;

Fig. 9 is a flow chart of the processing that the converged terminal connected to the fixed telephone network receives a call according to an embodiment of the disclosure;

Fig. 10 is a flow chart of the processing that the converged terminal connected to the fixed telephone network sends a short message according to an embodiment of the disclosure; and

Fig. 11 is a flow chart of the processing that the converged terminal connected to the fixed telephone network receives a short message according to an embodiment of the disclosure.

Detailed Description of the Embodiments

[0020] There is the problem in the related art that the mobile terminals are unable to utilize wired communication mode to perform communication, which causes serious waste of communication resources and considerable damage to health and environment. And, the present fixed telephone network technology is mature, the network coverage is comprehensive, and the scale of the network still is developing and expanding. The disclosure proposes to reconstruct the mobile terminal, so that the mobile terminal can access and stay in the fixed telephone network (hereinafter also referred to as fixed network), and can perform voice signal transmission and signaling (including short messages) transmission with the fixed telephone network through the analogue subscriber line. Thus, the convergence of mobile communication and fixed telephone network communication is realized for the mobile terminal. On the basis of maintaining the mobile communication function, the function of the wired communication is added. The hazards of radio

waves to health and environment are reduced, and the radio resources are saved.

[0021] The disclosure is described below in detail with reference to the drawings.

[0022] Fig. 1 is a structure block diagram of a mobile terminal according to an embodiment of the disclosure. As shown in Fig. 1, the mobile terminal comprises a central processor 1, a fixed network access control module 2, a ringing current processing module (not shown in Fig. 1), a frequency shift keying processing module 3, a call processing module 4, a mobile communication module 5 and an electronic switch module 6.

[0023] The fixed network access control module 2 is connected with the central processor 1, comprises an analogue subscriber line interface, and is configured to connect the terminal with the analogue subscriber line, and to notify the central processor 1 that the mobile terminal is connected with a fixed telephone network when the analogue subscriber line is connected with the terminal. And, the fixed network access control module 2 is further configured to notify the central processor 1 that the mobile terminal is disconnected with the fixed telephone network when the analogue subscriber line is disconnected with the terminal, wherein the central processor 1 may be one of the following: the baseband processor and the central processing unit.

[0024] The frequency shift keying processing module 3 is connected with the central processor 1, and is configured to identify the signaling from the connected analogue subscriber line and send the signaling from the analogue subscriber line to the central processor 1, and to identify the signaling from the central processor 1 and send the signaling from the central processor 1 to the connected analogue subscriber line.

[0025] The call processing module 4 is configured to receive and process the voice signal from the analogue subscriber line and send the voice signal to the voice output device of the terminal to be played, and to receive and process the voice signal from the audio input device of the terminal and send the voice signal from the audio input device of the terminal to the analogue subscriber line. Specifically, the call processing module 4 mainly has the following functions: 2/4 wire conversion, sidetone removal and voice signal amplification, to extract the voice signal from the analogue subscriber line and send the voice signal from the analogue subscriber line to the voice output device of the terminal to be played, and to send the voice signal from the user to the analogue subscriber line.

[0026] The mobile communication module 5 is configured to achieve the communication between the mobile terminal and the outside based on the radio network.

[0027] The central processor 1 is configured to process the signaling from the frequency shift keying processing module 3, and send the signaling to be transmitted by network to the frequency shift keying processing module 3, and to control the electronic switch module 6 to close the radio frequency sending/receiving function of the mo-

5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

[0028] The ringing current processing module (not shown in Fig. 1) is connected with the central processor 1, and is configured to identify the ringing current from the analogue subscriber line and report the ringing signal to the central processor 1. In the specific implementation, the central processor 1 may be further configured to determine whether the mobile terminal is the called terminal

according to the incoming called terminal identifier, and to control the mobile terminal to continue to perform the incoming call processing when determining that the mobile terminal is the called terminal.

[0029] The mobile terminal further comprises an audio input/output module (for example, the microphone and the earpiece) (not shown in Fig. 1). The call processing module is configured to send the voice signal generated by the user through the audio input module to the analogue subscriber line, and to send the voice signal from the analogue subscriber line to the audio output module.

[0030] In the above, the electronic switch module 6 is further configured to, under the control of the central processor 1, to enable at least one of the frequency shift keying processing module 3, the call processing module 4 and the ringing current processing module 5 to be connect with the analogue subscriber line.

[0031] Specifically, the central processor 1 may control the electronic switch module to execute the following operations. When the mobile terminal accesses the fixed telephone network, the central processor 1 is configured to control the electronic switch module to connect the ringing current processing module 5 with the analogue subscriber line. When the mobile terminal needs to perform voice communication, the central processor 1 is configured to control the electronic switch module to disconnect the ringing current processing module with the subscriber line, and to connect the subscriber line DC loop to connect the call processing module 4 with the analogue subscriber line. When the mobile terminal needs to perform short message transmission, the central processor 1 is configured to control the electronic switch module to disconnect the ringing current processing module with the subscriber line, and to connect the subscriber line DC loop to connect the frequency shift keying processing module 3 with the analogue subscriber line. And, the central processor 1 is further configured to, when the mobile terminal performs voice communication in the condition that there is wired access, control the electronic switch module to connect the audio input/output module with the call processing module.

[0032] As the mobile terminal in the disclosure converges functions of the fixed telephone network communication and the mobile network communication, the mobile terminal in the disclosure is also called as the converged terminal hereinafter.

[0033] Fig. 2 is a diagram of a fixed network access control module in a converged terminal according to an embodiment of the disclosure, mainly showing the possible shape of the subscriber line plug and the connection method of the subscriber line plug with the terminal. The plug may have many shapes. For example, the key switch may be controlled by the top of the plug. The location of the jack may be arranged at the lower part of the converged terminal. Through the fixed network access control module, on one hand, the line a1 b1 inside the converged terminal may be connected with the analogue subscriber line (line ab) of the fixed telephone network,

so that the converged terminal can be further connected with the fixed telephone network through the analogue subscriber line. On the other hand, the converged terminal also may detect the plug-in and plug-out of the plug in time, and notify the central processor that the terminal is connected or disconnected with the subscriber line, in order to start the processing logic of accessing and exiting the fixed network.

[0034] As shown in Fig. 2, the subscriber line plug is cylindrical. The upper left part shows the vertical section of the plug, the upper right part shows the cross section of the plug, and the lower part shows the corresponding components inside the jack of the converged terminal. A metal shell is arranged outside the outer layer 21 of the plug to connect line a of the subscriber line. A metal core is arranged in the center of the inner layer 22 of the plug to connect line b of the subscriber line. An insulating layer 23 is configured to separate line a and line b. A groove 24 and a protrusion 27 are matched. After the plug is plugged into the jack, the protrusion is blocked inside the groove to prevent the plug from slipping off easily. Three contacts 25, 26 and 27 are positioned inside the jack, corresponding to line b1 inside the converged terminal, connection detection switch and line a1 inside the terminal respectively. In the above, contacts 25 and 27 are metal contacts. After the plug is pushed into the jack, lines a1 b1 inside the terminal may be connected with line ab of the external subscriber line. The spring contact switch 28 may be connected with low level under the push of the contact 26 after the plug is plugged into the jack, in order to notify the central processor with the plug-in of the plug. When the plug is not plugged into the jack, the spring contact switch 28 is connected with high level to indicate to the central processor that the plug is not plugged into the jack.

[0035] The disclosure implements the convergence of the mobile terminal and the fixed terminal. The result can also be called the converged terminal. The solution performs communication by utilizing the related analogue subscriber line in the fixed communication network. The devices involved comprises: an MS (mobile converged terminal, also called converged terminal), a fixed telephone network and a mobile communication network.

[0036] Fig. 3 is a specific structure block diagram of a converged terminal according to an embodiment of the disclosure. As shown in Fig. 3, the converged terminal has two interfaces, one of which is a radio interface, and the other one is a subscriber line interface. The signaling on the radio interface is completely the same as that the signaling on the radio interface between the mobile terminal and the mobile communication network in the related technology. No repeated detail is given here. The physical medium and voice transmission of the subscriber line interface are completely the same as the physical medium and voice transmission on the interface between the analogue fixed telephone and the fixed communication network in the related technology. However, the new user signaling is formed of a group of messages and the

corresponding interaction thereof. These messages are transferred on the subscriber line in the mode of Frequency-shift Keying (FSK), in order to implement the accessing and exiting of the terminal to and from the fixed network, the establishment and termination of calls, and the receiving and sending of short messages.

[0037] As shown in Fig. 3, the converged terminal consists of a mobile communication part, a fixed telephone processing part and a public part. In the above, the vibrator, the display, the keyboard, the microphone, the earpiece, the hands-free/ring are essential input/output modules in the related mobile terminal equipment, which are shared by the mobile communication part and the fixed telephone processing part in the converged terminal. The central processor may be a (digital) baseband processor in the related mobile terminal, and also may be an independent Central Processing Unit (CPU), for example, the CPU in a net book. The central processor is configured to overall control the actions of the converged terminal. The mobile communication part of the converged terminal completes the mobile communication function in the related technology, and opens and closes the radio frequency sending/receiving function of the mobile communication module under the control of the central processor.

[0038] The fixed telephone processing part of the converged terminal consists of a fixed network access control module, a signaling processing module and a call processing module. The signaling processing module further consists of an FSK processing module and a ringing current processing module. Inside the converged terminal, when the converged terminal is in the idle state, the ringing current processing module is connected with the line ab (i.e., subscriber line), and the subscriber line DC loop is disconnected. When the converged terminal is in a call, the ringing current processing module is disconnected with the subscriber line, and the subscriber line DC loop is connected, so that the call processing module is connected with the line ab. All these modules inside the converged terminal coordinately operate under the uniform control of the central processor to complete the call processing under the fixed telephone network mode.

[0039] The call processing module may connect or disconnect with the line ab under the control of the central processor, in order to implement and end the voice communication, and to implement 2/4 wire conversion, sidetone removal, sending and receiving of voice signals, and amplification of voice signals. The call processing module shares the earpiece and microphone modules with the mobile communication part. Therefore, the input/output of the call processing module from/to these modules must meet the corresponding technical requirements.

[0040] Under the control of the central processor, the signaling processing module implements all the signaling interaction functions between the converged terminal and the fixed telephone network. Two sub-modules in

the signaling processing module may connect or disconnect with the line ab under the control of the central processor. When the converged terminal is in the idle state, the ringing current processing module is always connected with the line ab, to monitor the ringing signal (ringing current) that may appear on the line ab.

[0041] The fixed network access control module detects the plug-in and plug-out of the subscriber line plug in time, and notifies the central processor with the connection and disconnection between the converged terminal and the subscriber line, in order to start the processing logic of accessing and exiting the fixed network.

[0042] A plurality of different mobile converged terminals may access the fixed network through the same pair of analogue subscriber lines. Different mobile converged terminals are distinguished by their respective telephone numbers. When one mobile converged terminal serves as the calling terminal, the calling number of the outgoing call is the user number corresponding to the mobile converged terminal. When other users use the number of one mobile converged terminal as the called terminal, only the mobile converged terminal serving as the called terminal rings to its user. On the same pair of analogue subscriber lines, only one converged terminal can perform communication at each time, and the signaling processing module can identify whether there already is a call on the analogue subscriber lines.

[0043] The functions and operating process of the converged terminal in the embodiments of the disclosure is described in detail hereinafter with reference to specific flows.

[0044] Fig. 4 is a processing flow chart of accessing the fixed telephone network when the converged terminal is in the idle state according to an embodiment of the disclosure. As shown in Fig. 4, the flow comprises the following processing.

[0045] Step 401: After the subscriber line plug is plugged into the subscriber line jack of the converged terminal, the fixed network access control module in the converged terminal detects this event and reports it to the central processor. The central processor starts the processing of accessing the fixed telephone network when the terminal is idle, controls the electronic switch to connect the subscriber DC loop, connects the FSK processing module with the subscriber line, and simultaneously disconnects the ringing current processing module with the subscriber line, and receives the user signaling from the network side.

[0046] Step 402: After the subscriber loop is connected in the converged terminal, the subscriber interface circuit in the fixed telephone network may supply power to the subscriber line loop. The fixed telephone network detects this power supply, i.e., the off-hook. That is, the converged terminal sends an off-hook event to the fixed telephone network and waits for the response of the network side.

[0047] Step 403: After the fixed telephone network detects the off-hook event, the fixed telephone network

starts the call processing, verifies the property of the port through which the network side is connected with the subscriber line (for example, whether the port is available; and if yes, continuing the following processing, otherwise, ending the flow), and allocates the local signaling link number (network link number) and other resources (such as call control block, call processing task etc.) required by this call.

[0048] Step 404: The fixed telephone network responds the off-hook event of the converged terminal, and sends an off-hook response message to the converged terminal to request to establish a signaling link, wherein the off-hook response message carries the network link number.

[0049] Step 405: After receiving the off-hook response message, the FSK processing module of the converged terminal sends this message to the fixed network access processing logic of the central processor. The fixed network access processing logic of the central processor continues to process the fixed network access of the terminal, allocates the local signaling link number (terminal link number) and other resources (such as memories, threads etc.) required by this call. Specifically, the central processor generates an access request message taking the user mobile phone number as the parameter, and sends this message to the FSK processing module.

[0050] Step 406: The FSK processing module of the converged terminal sends the access request message to the fixed telephone network, wherein the access request message carries the terminal link number, the user number of this terminal (mobile phone number) and the network link number.

[0051] Step 407: After receiving the access request message, the fixed telephone network coordinately completes the wired access processing of the converged terminal with the mobile communication network, and registers the information of the Local Exchange (LE) to which the converged terminal is connected through the subscriber line in the network.

[0052] Step 408: The fixed telephone network sends an access response message to the converged terminal to notify the converged terminal that the converged terminal successfully accesses the fixed telephone network, wherein the access response message carries the terminal link number and the information of successfully accessing the fixed telephone network.

[0053] Step 409: After receiving the response message, the converged terminal closes the radio frequency sending/receiving function, does not send/receive any radio waves any more, releases resources allocated for this access, and enters the fixed telephone network access operating mode.

[0054] Step 410: The central processor in the converged terminal disconnects the subscriber loop, i.e., on-hook. That is, the converged terminal sends an on-hook event to the fixed telephone network, and simultaneously the central processor connects the ringing current processing module with the subscriber lines.

[0055] Step 411: The fixed telephone network detects that the terminal is on-hook, and releases the related resources. This access processing ends.

[0056] Fig. 5 is a processing flow chart of accessing the fixed telephone network operating mode when the converged terminal is in a call according to an embodiment of the disclosure. As shown in Fig. 5, the flow comprises the following processing.

[0057] Step 501: When in a call, the user plugs the subscriber line plug into the subscriber line jack of the converged terminal. The fixed network access control module in the converged terminal detects this event and reports it to the central processor. The central processor starts the switch-to-fixed-network processing logic, and controls the electronic switch to connect the subscriber loop to connect the FSK processing module with the subscriber line.

[0058] Step 502: The converged terminal connects the subscriber loop. That is, the converged terminal sends an off-hook event to the fixed telephone network and waits for the response of the network side.

[0059] Step 503: After the fixed telephone network detects the off-hook event, the fixed telephone network starts the call processing. For example, verifying whether the port is available; and if yes, continuing the following processing, otherwise, ending the flow. And the fixed telephone network allocates the local signaling link number (network link number) and other resources (such as call control block, call processing task etc.) required by this call.

[0060] Step 504: The fixed telephone network responds the off-hook event of the converged terminal, and sends an off-hook response message to the converged terminal to request to establish a signaling link, wherein the off-hook response message carries the network link number.

[0061] Step 505: After receiving the off-hook response message, the FSK processing module of the converged terminal sends this off-hook response message to the central processor. The central processor analyzes the off-hook response message, and continues the switch-to processing of the converged terminal. The switch-to processing includes, for example, allocating the local signaling link number (terminal link number) and other resources (such as, task, call control block etc.) required by this call. Then, the central processor generates a switch-to message taking the user mobile phone number as the parameter, and sends this message to the FSK processing module.

[0062] Step 506: The FSK processing module of the converged terminal sends the switch-to message to the fixed telephone network, wherein the switch-to message carries the terminal link number, the number of the terminal user and the network link number.

[0063] Step 507: After receiving the switch-to message, the fixed telephone network coordinates with the mobile communication network to record the fixed telephone network location of the converged terminal in the

network. That is, the fixed telephone network starts the switch-to processing, and registers in the network the identification information of the LE of the subscriber line with which the converged terminal is connected. Specifically, after the network completes the switch-to processing, the location where the terminal is connected with the fixed network will be recorded in the MSC, VLR or even HLR in the mobile network. The user data of the terminal and the correspondence relationship between the access port and the user number will also be recorded in the end office exchange where the fixed network is connected with the terminal.

[0064] Step 508: The fixed telephone network sends a switch-to response message to the converged terminal to notify the converged terminal that the converged terminal is successfully switched to the fixed telephone network, wherein the switch-to response message carries the terminal link number and information of successfully accessing the fixed telephone network.

[0065] Step 509: After the converged terminal receives the switch-to response message, the central processor connects the call processing module with the audio input/output module (microphone, earpiece), enters the fixed telephone network access operating mode, closes the radio frequency sending/receiving function, does not send/receive radio waves any more, and releases resources allocated for this switch-to.

[0066] Step 510: The converged terminal connects the audio input/output module with the call processing module, and the call processing module is connected with the subscriber line. Hence, the fixed network communication voice channel inside the terminal is connected. The fixed telephone network completes the switch-to processing of the terminal. The MSC of the mobile communication network cooperates with the accessed end office exchange of the converged terminal to switch the call from the mobile voice channel (for example, a voice channel consisting of a base station controller, a base station and a radio channel) to the fixed network voice channel with participation of the subscriber line and the accessed end office exchange. The two parties continue the call through the fixed telephone network.

[0067] Fig. 6 is a processing flow chart of exiting the fixed telephone network when the converged terminal is in the idle state according to an embodiment of the disclosure, i.e., a chart of the processing flow after the subscriber line plug is plugged out from the converged terminal in the idle state. As shown in Fig. 6, the flow comprises the following processing.

[0068] Step 601: After the subscriber line plug is plugged out from the converged terminal in the idle state, the fixed network access control module of the converged terminal detects the plug-out of the subscriber line plug, and notifies the central processor. The central processor indicates the mobile communication module to open the radio frequency sending/receiving function and starts the location update processing flow.

[0069] Step 602 - Step 604: The converged terminal

sends a location update request (LU_UPDATE_REQ) to the mobile communication network. The mobile communication network processes this location update request and changes the location information of the terminal in the network from the fixed telephone network to the mobile communication network. The mobile communication network sends a location update confirmation (LU_UPDATE_CONFIRM) message to the converged terminal and completes the location update of the converged terminal. In the above, the location update process is the same as the location update process in the related technology and is not described herein.

[0070] Step 605: The converged terminal enters the mobile access mode.

[0071] Fig. 7 is a processing flow chart that the converged terminal exits the fixed telephone network during a call according to an embodiment of the disclosure, i.e., a chart of the processing flow after the subscriber line plug is plugged out from the converged terminal that is in a call. As shown in Fig. 7, the flow comprises the following processing.

[0072] Step 701: After the subscriber line plug is plugged out from the converged terminal that is in a call, the fixed network access control module of the converged terminal detects the plug-out of the subscriber line plug. The central processor indicates the mobile communication module to open the radio frequency sending/receiving function and starts the location update processing flow.

[0073] Step 702 - Step 704: The converged terminal sends a location update request to the mobile communication network, and the mobile communication network processes this location update request and changes the location information of the terminal in the network from the fixed telephone network to the mobile communication network. The mobile communication network sends a location update confirmation message to the converged terminal and completes the location update of the converged terminal. Inside the converged terminal, the audio input/output module is disconnected with the call processing module. That is, the fixed network communication voice channel inside the terminal is disconnected. In the above, the location update process is the same as the location update process in the related technology and is not described herein.

[0074] Step 705: Inside the converged terminal, the audio input/output module is connected with the central processor. That is, the radio communication voice channel inside the terminal is connected. The mobile communication network establishes a voice bearer with the converged terminal and switches the call to the bearer. Specifically, the mobile communication network cooperates with the converged terminal to establish a voice bearer with participation of the air interface and the corresponding radio access equipment (such as BSC and BS) in the mobile communication network, and switches the call to the mobile channel.

[0075] Fig. 8 is a flow chart of the processing that the

converged terminal connected to the fixed telephone network initiates a call according to an embodiment of the disclosure. As shown in Fig. 8, the flow comprises the following processing.

[0076] Step 801: After the user dials the number of the opposite user and presses the off-hook key (the operation is the same as that when the converged terminal is in the mobile access mode), the central processor of the converged terminal starts the call processing logic inside the terminal, allocates corresponding resources (call processing task, call control block etc.), and starts the FSK processing module, to monitor the response at the network side.

[0077] Step 802: The terminal sends an off-hook signal to the end office exchange by connecting the subscriber line loop.

[0078] Step 803: The terminal connects the audio input/output module (microphone, earpiece) with the call processing module, and establishes a voice channel inside the terminal, to facilitate the user to monitor the signal tone that may appear on the subscriber line.

[0079] Step 804: After detecting the off-hook of the user, the fixed telephone network starts the call processing and allocates the network link number.

[0080] Step 805: The fixed telephone network sends an off-hook response message to the converged terminal to respond the off-hook of the converged terminal, wherein the off-hook response message carries the allocated network link number.

[0081] Step 806: After receiving the off-hook response message, the converged terminal continues to process the call and to allocate the terminal link number.

[0082] Step 807: The converged terminal sends a Call Originated (CO) message to the fixed telephone network, wherein the CO message carries the network link number, the terminal link number, the calling number (i.e., the number of the converged terminal) and the called number.

[0083] Step 808: The fixed telephone network analyzes the calling number and the called number, and starts the CO processing of the fixed network accessing (this process is similar to that in the related technology and is not described herein).

[0084] Step 809: After the called terminal rings, the fixed telephone network sends a CO response message to the converged terminal. The CO response message carries the terminal link number and the ringing event indicator. The call at the network side enters the state of waiting for the off-hook of the called user. After the terminal receives the CO response message, the corresponding call processing also enters the state of waiting for the off-hook of the called user.

[0085] Step 810: During the period that the call waits for the off-hook of the called user, the fixed telephone network sends a ring-back tone to the converged terminal. The terminal sends the ring-back tone to the audio output module to be played. The user hears the ring-back tone.

[0086] Step 811: The called user hooks off. The fixed telephone network stops sending the ring-back tone to the converged terminal. The user may talk with the opposite user after hearing that the ring-back tone stops.

[0087] Step 812: The calling user and the called user talk with each other.

[0088] Fig. 9 is a flow chart of the processing that the converged terminal connected to the fixed telephone network receives a call according to an embodiment of the disclosure. As shown in Fig. 9, the flow comprises the following processing.

[0089] Step 901: After the incoming call request reaches the end office exchange at the network side, the end office exchange detects that the subscriber line to which the converged terminal is connected is idle. The end office exchange starts the incoming call processing logic, creates call processing task, and allocates call control block etc., and finally sends a ringing current to the subscriber line to which the converged terminal is connected.

[0090] Step 902: According to the flow shown in Fig. 5 of the embodiment of the disclosure, after the converged terminal accesses the fixed telephone network, the converged terminal in the idle state connects the ringing current processing module with the subscriber line. After monitoring the ringing current signal on the subscriber line, the ringing current processing module reports the ringing event to the central processor. The central processor starts the incoming call processing, creates call processing task, allocates the resources such as call control block and signaling link local identifiers (terminal link number), connects the FSK processing module with the subscriber line to receive messages from the network side, and sends a ringing response message to the network side to respond the ringing current signal at the network side. The ringing response message carries the terminal link number.

[0091] Step 903: The end office exchange of the fixed telephone network sends the call information to the converged terminal through the CT message, wherein the CT message carries the terminal link number, the network link number, the calling number and the called number.

[0092] Step 904: The converged terminal compares the received called number with its own user number. If the called number is identical to the user number of the terminal, the converged terminal sends the calling number to the display of the converged terminal to be displayed, and drives the hands-free/ring to ring, or drives the vibrator to vibrate, or by other way, to notify the user with the incoming call. And, the converged terminal continues the subsequent processing of the call. If the called number is not identical to the user number of the terminal, the converged terminal stops the processing of this call.

[0093] Step 905: The user hears the ring or senses other call prompts, and sees the calling number displayed on the display. If the user agrees to receive this call, the user presses the off-hook key. The central processor receives the off-hook event of the user, makes the call into

the state of talking, and sends the CT response message to the network side through the FSK processing module to notify the network that the terminal user has hooked off. The CT response message carries the network link number.

[0094] Step 906: The converged terminal connects the call processing module with the subscriber line to connect the call loop.

[0095] Step 907: The fixed telephone network and the mobile communication network connect the corresponding voice channel.

[0096] Step 908: The calling user and the called user start to talk with each other.

[0097] Fig. 10 is a flow chart of the processing that the converged terminal connected to the fixed telephone network sends a short message according to an embodiment of the disclosure. As shown in Fig. 10, the flow comprises the following processing.

[0098] Step 1001: After the user uses the converged terminal to edit a short message and selects the sending function, the converged terminal starts the sending processing. The central processor connects the subscriber DC loop to send an off-hook signal to the fixed telephone network. The FSK processing module is connected with the subscriber line to receive messages from the network side.

[0099] Step 1002: After detecting the off-hook of the user, the fixed telephone network starts the call processing and allocates the network link number. Then, the fixed telephone network sends an off-hook response message to the converged terminal to respond the off-hook of the converged terminal, wherein the off-hook response message carries the allocated network link number.

[0100] Step 1003: After receiving the off-hook response message, the converged terminal continues the sending processing, allocates the terminal link number, generates a Message Originated (MO) message, and sends the MO message to the fixed telephone network through the FSK processing module. The MO message carries the calling number (i.e., the number of the converged terminal), the called number, the number of the short message service center, the contents of the short message, the network link number and the terminal link number, wherein the number of the short message service center is stored in the central processor in advance.

[0101] Step 1004: The fixed telephone network and the mobile communication network process the MO message, store the contents of the short message into the designated short message center, and send an MO response message to the converged terminal, wherein the MO response message carries the terminal link number and the confirmation information.

[0102] Step 1005: The FSK processing module of the converged terminal receives the MO response message and sends the MO response message to the central processor of the converged terminal. The central processor releases resources required for this sending, and disconnects the subscriber loop, i.e., on-hook. That is, the con-

verged terminal sends an on-hook event to the fixed telephone network, and the sending process of the short message ends.

[0103] Fig. 11 is a flow chart of the processing that the converged terminal connected to the fixed telephone network receives a short message according to an embodiment of the disclosure. As shown in Fig. 11, the flow comprises the following processing.

[0104] Step 1101: The fixed telephone network receives a short message sent to the converged terminal, starts the short message receiving processing, and when the converged terminal is in the idle state, sends a ringing current to the subscriber line to call the converged terminal.

[0105] Step 1102: The converged terminal detects the ringing current on the subscriber line, starts the call processing, creates the call processing task, allocates the terminal link number, connects the subscriber loop to connect the FSK processing module with the subscriber line, and sends a ringing response message to the fixed telephone network to respond the ringing current signal sent by the fixed telephone network. The ringing response message carries the terminal link number.

[0106] Step 1103: The fixed telephone network receives the ringing response message, continues the short message receiving processing, allocates the network link number, and sends a Message Terminated (MT) message to the converged terminal. The MT message carries the terminal link number, the network link number, the calling number, the called number (i.e., the number of the converged terminal), the contents of the short message and the receiving time.

[0107] Step 1104: The converged terminal receives and processes the MT message, and sends an MT response message to the fixed telephone network, wherein the MT response message carries the network link number and the successful confirmation information. The method for the terminal to process the short message is the same as the related mobile terminal technology, such as storing the short message, prompting the user of the arrival of the short message, displaying the contents of the short message according to the instruction of the user, deleting or forwarding the short message etc.

[0108] Step 1105: The converged terminal releases resources required to receive the short message, disconnects the subscriber DC loop, and connects the ringing current processing module with the subscriber line. That is, the terminal is hooked on, the terminal enters the idle state, and the receiving process of the short message ends.

[0109] The converged terminal in the embodiments of the disclosure accesses the fixed telephone network through the related analogue subscriber line. The fixed telephone network communication technology and the mobile network communication technology can be converged. The converged terminal accesses the fixed telephone network through the present large-scale 2-wire analogue subscriber telephone line. Therefore, commu-

nication is implemented effectively and conveniently by fully utilizing the fixed communication network resources and the flexibility of the mobile communication.

[0110] Above contents are only preferred embodiments of the disclosure and should not be used for limiting the disclosure. Any modifications, equivalent replacements and improvements within the principle of the disclosure should be contained within the protection scope of the disclosure.

Claims

1. A mobile terminal, **characterized by** comprising: a central processor, a fixed network access control module, a frequency shift keying processing module, a call processing module, a mobile communication module and an electronic switch module, wherein the fixed network access control module is connected with the central processor, comprises an analogue subscriber line interface, and is configured to connect the mobile terminal and an analogue subscriber line, and to notify the central processor that the mobile terminal is connected with a fixed telephone network when the analogue subscriber line is connected with the analogue subscriber line interface; the frequency shift keying processing module is connected with the central processor, and is configured to identify a signaling from the connected analogue subscriber line and send the signaling from the connected analogue subscriber line to the central processor, and to identify a signaling from the central processor and send the signaling from the central processor to the connected analogue subscriber line; the call processing module is configured to extract a voice signal from the analogue subscriber line and send the voice signal from the analogue subscriber line to a voice output device of the mobile terminal to be played, and to send a voice signal from a user to the analogue subscriber line; the mobile communication module is configured to achieve communication between the mobile terminal and outside based on a radio network; and the central processor is configured to process a signaling from the frequency shift keying processing module and send a signaling to be transmitted by the subscriber line to the frequency shift keying processing module, and to control the electronic switch module to close a radio frequency sending/receiving function of the mobile communication module when the fixed network access control module notifies that the mobile terminal is connected with the fixed network.
2. The mobile terminal according to claim 1, **characterized by** further comprising: a ringing current processing module, connected with the central processor, and configured to identify a ringing current signal from the analogue subscriber line and report a ringing corresponding to the ringing current signal to the central processor.
3. The mobile terminal according to claim 1, **characterized in that** the central processor is further configured to determine whether a called number received by the frequency shift keying processing module is a user number of the mobile terminal, and if yes, control the mobile terminal to continue to perform incoming call processing.
4. The mobile terminal according to claim 2, **characterized in that** the electronic switch module is further configured to, under control of the central processor, enable at least one of the frequency shift keying processing module, the call processing module and the ringing current processing module to be connected with the analogue subscriber line.
5. The mobile terminal according to claim 4, **characterized in that** the central processor is further configured to control the electronic switch module to connect the ringing current processing module with the analogue subscriber line when the mobile terminal accesses the fixed telephone network.
6. The mobile terminal according to claim 4, **characterized in that** the central processor is further configured to control the electronic switch module to connect the call processing module with the analogue subscriber line when the mobile terminal needs to perform voice communication.
7. The mobile terminal according to claim 4, **characterized in that** the central processor is further configured to control the electronic switch module to connect the frequency shift keying processing module with the analogue subscriber line when the mobile terminal performs short message transmission.
8. The mobile terminal according to any one of claims 1 to 7, **characterized in that** the mobile terminal further comprises an audio input module and an audio output module; and the call processing module is further configured to send the voice signal from the user, which is input through the audio input module, to the analogue subscriber line, and send the voice signal from the analogue subscriber line to the voice output module.
9. The mobile terminal according to any one of claims 1 to 7, **characterized in that** the central processor is a baseband processor or a central processing unit.




Fig. 1




Fig. 2


**Fig. 3**

Fig. 4




Fig. 5




Fig. 6




Fig. 7







Fig. 8

**Fig. 9**

**Fig. 10**

**Fig. 11**

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2011/071192

A. CLASSIFICATION OF SUBJECT MATTER

See the extra sheet

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: H04M, H04L, H04W, H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

CPRS, WPI, VEN, CPRSABS: combin+ system, DTMF, FSK, interface, terminal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	CN201332429Y(XIAMEN STELCOM INFORMATION & T) 21 Oct. 2009(21.10.2009)Description pages 1-4, Fig. 2	1-9
Y	CN201274576Y(FUJIAN SITE ELECTRONICS CO., LTD.)15 Jul. 2009(15.07.2009) Description pages 2-3, Fig. 1	1-9
Y	CN2862539Y(XIAN DATANG TELECOM LTD.)24 Jan. 2007(24.01.2007) Description pages 3-8, Figures 1, 6	4-7
A	GB2467854A(NIGEL SLATER)18 Aug. 2010(18.08.2010)The whole document	1-9

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier application or patent but published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim (S) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

20 May 2011(20.05.2011)

Date of mailing of the international search report

16 Jun. 2011 (16.06.2011)

Name and mailing address of the ISA/CN
The State Intellectual Property Office, the P.R.China
6 Xitucheng Rd., Jimen Bridge, Haidian District, Beijing, China
100088
Facsimile No. 86-10-62019451

Authorized officer

QI, Ji

Telephone No. (86-10)62411484

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/CN2011/071192

Patent Documents referred in the Report	Publication Date	Patent Family	Publication Date
CN201332429Y	21 Oct. 2009(21.10.2009)	NONE	
CN201274576Y	15 Jul. 2009(15.07.2009)	NONE	
CN2862539Y	24 Jan. 2007(24.01.2007)	NONE	
GB2467854A	18 Aug. 2010(18.08.2010)	NONE	

Form PCT/ISA/210 (patent family annex) (July 2009)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2011/071192

A. CLASSIFICATION OF SUBJECT MATTER

H04M 1/725(2006.01)i

H04L 29/06(2006.01)n

H04W 88/00(2009.01)n