



(11) **EP 2 626 265 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 71, 72

(51) Int Cl.:
B60W 10/08 (2006.01) **B60K 6/445** (2007.10)
B60W 10/06 (2006.01) **B60W 20/00** (2006.01)

(48) Corrigendum issued on:
26.02.2014 Bulletin 2014/09

(86) International application number:
PCT/JP2010/067638

(43) Date of publication:
14.08.2013 Bulletin 2013/33

(87) International publication number:
WO 2012/046324 (12.04.2012 Gazette 2012/15)

(21) Application number: **10858132.3**

(22) Date of filing: **07.10.2010**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR

(71) Applicant: **TOYOTA JIDOSHA KABUSHIKI**
KAISHA
Toyota-shi, Aichi-ken, 471-8571 (JP)

(72) Inventors:
• **YOKOUCHI, Yoshimitsu**
Toyota-shi, Aichi-ken, 471-8571 (JP)

• **MIYASAKA, Kenji**
Toyota-shi, Aichi-ken, 471-8571 (JP)
• **HORI, Tetsuo**
Toyota-shi, Aichi-ken, 471-8571 (JP)
• **WATANABE, Hideto**
Toyota-shi, Aichi-ken, 471-8571 (JP)

(74) Representative: **Kuhnen & Wacker**
Patent- und Rechtsanwaltsbüro
Prinz-Ludwig-Straße 40A
85354 Freising (DE)

(54) **POWER TRAIN, AND POWER TRAIN CONTROL METHOD AND CONTROL DEVICE**

(57) A powertrain includes: an engine provided with a plurality of cylinders; a first motor generator coupled to an output shaft of the engine; and an ECU for controlling them. When misfire in the engine is detected, the output shaft of the engine is rotated by driving the first motor generator with ignition and supply of fuel to the engine being suspended.

FIG. 11

