

(19)



(11)

EP 2 631 419 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

28.08.2013 Bulletin 2013/35

(51) Int Cl.:

E21B 33/08 (2006.01)
F16K 41/04 (2006.01)

F16J 15/32 (2006.01)

(21) Application number: **13169036.4**

(22) Date of filing: **02.03.2007**

(84) Designated Contracting States:
DE DK GB NL

(30) Priority: **02.03.2006 US 366078**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
07103416.9 / 1 830 034

(71) Applicant: **Weatherford/Lamb Inc.**
Houston, Texas 77056 (US)

(72) Inventors:

- **Bailey, Thomas F.**
Houston, TX Texas 77079 (US)
- **Chambers, James W.**
Hackett, AR Arkansas 72937 (US)

- **Hannegan, Don M.**
Fort Smith, AR Arkansas 72916 (US)
- **Gravouia, Mark F.**
Broussard, LA Louisiana 70518 (US)

(74) Representative: **Hagmann-Smith, Martin P.**
Marks & Clerk LLP
Fletcher House
Heatley Road
The Oxford Science Park
Oxford OX4 4GE (GB)


Remarks:

This application was filed on 23-05-2013 as a divisional application to the application mentioned under INID code 62.

(54) **Rotating control head radial seal protection and leak detection systems**

(57) A system and method for reducing repairs to radial seals used in a rotating control head (100) used while drilling is disclosed. Also, a system and method to detect

leaks in the rotating control head (100) and a latching system to latch the rotating control head to a housing is disclosed.



EP 2 631 419 A1

Description

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation-in-part of U.S. Application Serial No. 10/285,336 entitled "Active/Passive Seal Rotating Control Head" filed October 31, 2002, and U.S. Application Serial No. 10/995,980 entitled "Riser Rotating Control Device" filed November 23, 2004, both of which are incorporated by reference in their entirety for all purposes.

STATEMENTS REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

[0002] Not applicable.

REFERENCE TO A MICROFICHE APPENDIX

[0003] Not applicable.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0004] Embodiments of the present invention relate generally to a method and a system for a rotating control head used in a drilling operation. More particularly, the invention relates to a remote leak detection system, radial seal protection system and an improved cooling system for a rotating control head and a method for using the systems. The present invention also includes a leak detection system for a latch system to latch the rotating control device to a housing.

2. Description of the Related Art

[0005] Drilling a wellbore for hydrocarbons requires significant expenditures of manpower and equipment. Thus, constant advances are being sought to reduce any downtime of equipment and expedite any repairs that become necessary. Rotating equipment requires maintenance as the drilling environment produces forces, elevated temperatures and abrasive cuttings detrimental to the longevity of seals, bearings, and packing elements.

[0006] In a typical drilling operation, a drill bit is attached to a drill pipe. Thereafter, a drive unit rotates the drill pipe through a drive member, referred to as a kelly as the drill pipe and drill bit are urged downward to form the wellbore. In some arrangements, a kelly is not used, thereby allowing the drive unit to attach directly to the drill pipe or tubular. The length of the wellbore is determined by the location of the hydrocarbon formations. In many instances, the formations produce fluid pressure that may be a hazard to the drilling crew and equipment unless properly controlled.

[0007] Several components are used to control the fluid pressure. Typically, one or more blowout preventers (BOP) are mounted with the well forming a BOP stack to seal the well. In particular, an annular BOP is used to selectively seal the lower portions of the well from a tubular that allows the discharge of mud. In many instances, a conventional rotating control head is mounted above the BOP stack. An inner portion or member of the conventional rotating control head is designed to seal and rotate with the drill pipe. The inner portion or member typically includes at least one internal sealing element mounted with a plurality of bearings in the rotating control head.

[0008] The internal sealing element may consist of either one, two or both of a passive seal assembly and/or an active seal assembly. The active seal assembly can be hydraulically or mechanically activated. Generally, a hydraulic circuit provides hydraulic fluid to the active seal in the rotating control head. The hydraulic circuit typically includes a reservoir containing a supply of hydraulic fluid and a pump to communicate the hydraulic fluid from the reservoir to the rotating control head. As the hydraulic fluid enters the rotating control head, a pressure is created to energize the active seal assembly. Preferably, the pressure in the active seal assembly is maintained at a greater pressure than the wellbore pressure. Typically, the hydraulic circuit receives input from the wellbore and supplies hydraulic fluid to the active seal assembly to maintain the desired pressure differential.

[0009] During the drilling operation, the drill pipe or tubular is axially and slidably moved through the rotating control head. The axial movement of the drill pipe along with other forces experienced in the drilling operation, some of which are discussed below, causes wear and tear on the bearing and seal assembly and the assembly subsequently requires repair. Typically, the drill pipe or a portion thereof is pulled from the well and the bearing and seal assembly in the rotating control head is then released. Thereafter, an air tugger or other lifting means in combination with a tool joint on the drill string can be used to lift the bearing and seal assembly from the rotating control head. The bearing and seal assembly is replaced or reworked, the bearing and seal assembly installed into the rotating control head, and the drilling operation is resumed.

[0010] The thrust generated by the wellbore fluid pressure, the radial forces on the bearing assembly and other forces cause a substantial amount of heat to build in the conventional rotating control head. The heat causes the seals and bearings to wear and subsequently require repair. The conventional rotating control head typically includes a cooling system that circulates fluid through the seals and bearings to remove the heat.

[0011] Cooling systems have been known in the past for rotating control heads and rotating blowout preventers. For example, U.S. Patent Nos. 5,178,215, 5,224,557 and 5,277,249 propose a heat exchanger for cooling hydraulic fluid to reduce the internal temperature of a rotary blowout preventer to extend the operating life of various bearing and seal assemblies found therein.

[0012] Figure 10 discloses a system where hydraulic fluid moves through the seal carrier C of a rotating control head, generally indicated at RCH, in a single pass to cool top radial seals S1 and S2 but with the fluid external to the bearing section B. Similarly, U.S. Patent No. 5,662,181, assigned to the assignee of the present invention, discloses use of first inlet and outlet fittings for circulating a fluid, i.e. chilled water and/or antifreeze, to cool top radial seals in a rotating control head. A second lubricant inlet fitting is used for supplying fluid for lubricating not only the top radial seals but also top radial bearings, thrust bearings, bottom radial bearings and bottom radial seals all positioned beneath the top radial seals. (See '181 patent, col. 5, ln. 42 to col. 6, ln. 10 and col. 7, lns. 1-10.) These two separate fluids require their own fluid flow equipment, including hydraulic/pneumatic hoses.

[0013] Also, U.S. Patent No. 5,348,107 proposes means for circulating lubricant around and through the interior of a drilling head. More particularly, Figures 3 to 6 of the '107 patent propose circulating lubricant to seals via a plurality of passageways in the packing gland. These packing gland passageways are proposed to be in fluid communication with the lubricant passageways such that lubricant will freely circulate to the seals. (See '107 patent, col. 3, lns. 27-65.)

[0014] U.S. Patent Nos. 6,554,016 and 6,749,172, assigned to the assignee of the present invention, propose a rotary blowout preventer with a first and a second fluid lubricating, cooling and filtering circuit separated by a seal. Adjustable orifices are proposed connected to the outlet of the first and second fluid circuits to control pressures within the circuits. Such pressures are stated to affect the wear rates of the seals and to control the wear rate of one seal relative to another seal.

[0015] Therefore, an improved system for cooling radial seals and the bearing section of a rotating control head with one fluid is desired. If the radial seals are not sufficiently cooled, the localized temperature at the sealing surface will rise until the temperature limitations of the seal material is reached and degradation of the radial seal begins. The faster the rise in temperature means less life for the radial seals. In order to obtain sufficient life from radial seals, the rate of heat extraction should be fast enough to allow the temperature at the sealing surface to level off at a temperature lower than that of the seal material's upper limit.

[0016] Also, to protect the radial seals in a rotating control head, it would be desirable to regulate the differential pressure across the upper top radial seal that separates the fluid from the environment. Typically, fluid pressure is approximately 200 psi above the wellbore pressure. This pressure is the differential pressure across the upper top radial seal. Radial seals have a PV factor, which is differential pressure across the seal times the rotary velocity of the inner portion or member of the rotating control head in surface feet per minute. When this value is exceeded, the radial seal fails prematurely. Thus, the PV factor is the limitation to the amount of pressure and RPM that a rotating control head can be expected to perform. When the PV factor is exceeded, either excessive heat is generated by friction of the radial seals on the rotating inner member, which causes the seal material to break down, or the pressure forces the radial seal into the annular area between the rotating inner member and stationary outer member which damages the deformed seal.

[0017] In general, this PV seal problem has been addressed by limiting the RPM, pressure or both in a rotating control head. The highest dynamic, but rarely experienced, rating on a rotating control head is presently approximately 2500 psi. Some companies publish life expectancy charts which will provide the expected life of a radial seal for a particular pressure and RPM value. An annular labyrinth ring has also been used in the past between the lubricant and top radial seal to reduce the differential pressure across the top radial seal. Pressure staging and cooling of seals has been proposed in U.S. Patent No. 6,227,547, assigned on its face to Kalsi Engineering, Inc. of Sugar Land, Texas.

[0018] Furthermore, U.S. Serial No. 10/995,980 discloses in Figure 14 a remote control display 1400 having a hydraulic fluid indicator 1488 to indicate a fluid leak condition. Figure 18 of the '980 application further discloses that the alarm indicator 1480 and horn are activated based in part on the fluid leak indicator 1488 being activated for a predetermined time.

[0019] The above discussed U.S. Patent Nos. 5,178,215; 5,224,557; 5,277,249; 5,348,107; 5,662,181; 6,227,547; 6,554,016; and 6,749,172 are incorporated herein by reference in their entirety for all purposes.

[0020] There is a need therefore, for an improved, cost-effective rotating control head that reduces repairs to the seals in the rotating control head and an improved leak detection system to indicate leaks pass these seals. There is a further need for a cooling system in a rotating control head for top radial seals that can be easily implemented and maintained. There is yet a further need for an improved rotating control head where the PV factor is reduced by regulating the differential pressure across the upper top radial seal. There is yet a further need for an improved leak detection system for the rotating control head and its latching system.

BRIEF SUMMARY OF THE INVENTION

[0021] The present invention generally relates to a system and method for reducing repairs to a rotating control head and a system and method to detect leaks in the rotating control head and its latching system.

[0022] In particular, the present invention relates to a system and method for cooling a rotating control head while regulating the pressure on the upper top radial seal in the rotating control head to reduce its PV factor. The improved rotating control head includes an improved cooling system using one fluid to cool the radial seals and bearings in combination with a reduced PV factor radial seal protection system.

[0023] A leak detection system and method of the present invention uses a comparator to compare fluid values in and from the latch assembly of the latch system and/or in and from the bearing section or system of the rotating control head.

[0024] In another aspect, a system and method for sealing a tubular in a rotating control head is provided. The method includes supplying fluid to the rotating control head and activating a seal arrangement to seal around the tubular. The system and method further includes passing a cooling medium through the rotating control head while maintaining a pressure differential between a fluid pressure in the rotating control head and a wellbore pressure.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0025] So that the manner in which the above recited features of the present invention can be understood in detail, a more particular description of the invention, briefly summarized above, may be had by reference to embodiments, some of which are illustrated in the appended drawings. It is to be noted, however, that the appended drawings illustrate only typical embodiments of this invention and are therefore not to be considered limiting of its scope, for the invention may be used in other equally effective embodiments.

Figure 1 is an elevational section view illustrating a rotating control head having an active seal assembly positioned above a passive seal assembly latched in a housing in accord with the present invention.

Figure 2A illustrates a rotating control head cooled by a heat exchanger.

Figure 2B illustrates a schematic view of the heat exchanger.

Figure 3A illustrates a rotating control head cooled by flow a gas.

Figure 3B illustrates a schematic view of the gas in a substantially circular passageway.

Figure 4A illustrates a rotating control head cooled by a fluid mixture.

Figure 4B illustrates a schematic view of the fluid mixture circulating in a substantially circular passageway.

Figure 5A illustrates the rotating control head cooled by a refrigerant.

Figure 5B illustrates a schematic view of the refrigerant circulating in a substantially circular passageway.

Figure 6 illustrates a rotating control head actuated by a piston intensifier in communication with the wellbore pressure.

Figure 7A illustrates an alternative embodiment of a rotating control head with a passive seal assembly and an active seal assembly mechanical annular blowout preventer (BOP) in an unlocked position.

Figure 7B illustrates the rotating control head of Figure 7A with the annular BOP in a locked position.

Figure 8 illustrates an alternative embodiment of a rotating control head with a passive seal assembly positioned above an active seal assembly in accord with the present invention.

Figure 9 is an elevational section view showing a rotating control head with two passive seal assemblies latched in a housing in accord with the present invention.

Figure 10 is an enlarged section view of a prior art rotating control head system where cooling fluid moves through the seal carrier in a single pass but with the fluid external to the bearing section.

Figure 11 is an enlarged section view of a rotating control head cooling system where air moves through a passageway similar to the passageway shown in above Figures 2A and 2B.

Figure 12 is an enlarged section view of a rotating control head where hydraulic fluid moves through the seal carrier to cool the top radial seals in a single pass.

Figure 13 is an enlarged section view showing staging pressure on radial seals for a rotating control head in accord with the present invention, including regulating pressure between an upper top radial seal and a high flow lower top radial seal.

Figure 14 is an enlarged section view of a multi-pass heat exchanger for a rotating control head in accord with the present invention where a hydraulic fluid is both moved through the bearing section and makes multiple passes around the radial seals.

Figures 15A and 15B are schematics of the preferred hydraulic system for the present invention.

Figure 16 is a flowchart for operation of the hydraulic system of Figure 15 of the present invention.

Figure 17 is a continuation of the flowchart of Figure 16.

Figure 18 is a continuation of the flowchart of Figure 17.

Figure 19 is a flowchart of a subroutine for controlling the pressure in the bearing section of the rotating control head

of the present invention.

Figure 20 is a continuation of the flowchart of Figure 19.

Figure 21 is a continuation of the flowchart of Figure 20.

Figure 22 is a continuation of the flowchart of Figure 21.

Figure 23 is a flowchart of a subroutine for controlling either the pressure of the latching system in the housing, such as shown in Figures 1 and 9, or the pressure on the radial seals, as shown in Figure 13, of the present invention.

Figure 24 is a continuation of the flowchart of Figure 23.

Figure 25 is a plan view of a control console in accord with the present invention.

Figure 26 is an enlarged elevational section view of a latch assembly in the latched position with a perpendicular port communicating above a piston indicator valve that is shown in a closed position.

Figure 27 is a view similar to Figure 26 but taken at a different section cut to show another perpendicular port communicating below the closed piston indicator valve.

DETAILED DESCRIPTION OF THE INVENTION

[0026] Generally, the present invention relates to a rotating control head for use with a drilling rig. Typically, an inner portion or member of the rotating control head is designed to seal around a rotating tubular and rotate with the tubular by use of an internal sealing element and bearings. Additionally, the inner portion of the rotating control head permits the tubular to move axially and slidably through the rotating control head on the drilling rig.

[0027] Figure 1 is a cross-sectional view illustrating the rotating control head, generally indicated at 100, in accord with the present invention. The rotating control head 100 preferably includes an active seal assembly 105 and a passive seal assembly 110. Each seal assembly 105, 110 includes components that rotate with respect to a housing 115. The components that rotate in the rotating control head are mounted for rotation about a plurality of bearings 125.

[0028] As depicted, the active seal assembly 105 includes a bladder support housing 135 mounted within the plurality of bearings 125. The bladder support housing 135 is used to mount bladder 130. Under hydraulic pressure, as discussed below, bladder 130 moves radially inward to seal around a tubular, such as a drilling pipe or tubular (not shown). In this manner, bladder 130 can expand to seal off a borehole using the rotating control head 100.

[0029] As illustrated in Figure 1, upper and lower caps 140, 145 fit over the respective upper and lower end of the bladder 130 to secure the bladder 130 within the bladder support housing 135. Typically, the upper and lower caps 140, 145 are secured in position by a setscrew (not shown). Upper and lower seals 155, 160 seal off chamber 150 that is preferably defined radially outwardly of bladder 130 and radially inwardly of bladder support housing 135.

[0030] Generally, fluid is supplied to the chamber 150 under a controlled pressure to energize the bladder 130. A hydraulic control will be illustrated and discussed in Figures 2-6. Essentially, the hydraulic control maintains and monitors hydraulic pressure within pressure chamber 150. Hydraulic pressure P1 is preferably maintained by the hydraulic control between 0 to 200 psi above a wellbore pressure P2. The bladder 130 is constructed from flexible material allowing bladder surface 175 to press against the tubular at approximately the same pressure as the hydraulic pressure P1. Due to the flexibility of the bladder, it also may conveniently seal around irregular shaped tubular string, such as a hexagonal kelly. In this respect, the hydraulic control maintains the differential pressure between the pressure chamber 150 at pressure P1 and wellbore pressure P2. Additionally, the active seal assembly 105 includes support fingers 180 to support the bladder 130 at the most stressful area of the seal between the fluid pressure P1 and the ambient pressure.

[0031] The hydraulic control may be used to de-energize the bladder 130 and allow the active seal assembly 105 to release the seal around the tubular. Generally, fluid in the chamber 150 is drained into a hydraulic reservoir (not shown), thereby reducing the pressure P1. Subsequently, the bladder surface 175 loses contact with the tubular as the bladder 130 becomes de-energized and moves radially outward. In this manner, the seal around the tubular is released allowing the tubular to be removed from the rotating control head 100.

[0032] In the embodiment shown in Figure 1, the passive seal assembly 110 is operatively attached to the bladder support housing 135, thereby allowing the passive seal assembly 110 to rotate with the active seal assembly 105. Fluid is not required to operate the passive seal assembly 110 but rather it utilizes pressure P2 to create a seal around the tubular. The passive seal assembly 110 is constructed and arranged in an axially downward conical shape, thereby allowing the pressure P2 to act against a tapered surface 195 to close the passive seal assembly 110 around the tubular. Additionally, the passive seal assembly 110 includes an inner diameter 190 smaller than the outer diameter of the tubular to provide an interference fit between the tubular and the passive seal assembly 110.

[0033] Figure 2A illustrates a rotating control head 200 cooled by heat exchanger 205. As shown, the rotating control head 200 is depicted generally to illustrate this embodiment of the invention, thereby applying this embodiment to a variety of different types of rotating control heads. A hydraulic control 210 provides fluid to the rotating control head 200. The hydraulic control 210 typically includes a reservoir 215 to contain a supply of fluid, a pump 220 to communicate the fluid from the reservoir 215 to the rotating control head 200 and a valve 225 to remove excess pressure in the rotating control head 200.

[0034] Generally, the hydraulic control 210 provides fluid to energize a bladder 230 and lubricate a plurality of bearings 255. As the fluid enters a port 235, the fluid is communicated to the plurality of bearings 255 and a chamber 240. As the chamber 240 fills with a fluid, pressure P1 is created. The pressure P1 acts against the bladder 230 causing the bladder 230 to expand radially inward to seal around a tubular string (not shown). Typically, the pressure P1 is maintained

between 0 - 200 psi above a wellbore pressure P2.

[0035] The rotating control head 200 is cooled by the heat exchanger 205. The heat exchanger 205 is constructed and arranged to remove heat from the rotating control head 200 by introducing a gas, such as air, at a low temperature into an inlet 265 and thereafter transferring heat energy from a plurality of radial seals 275A and 275B and the plurality of bearings 255 to the gas as the gas passes through the heat exchanger 205. Subsequently, the gas at a higher temperature exits the heat exchanger 205 through an outlet 270. Typically, gas is pumped into the inlet 265 by a blowing apparatus (not shown). However, other means of communicating gas to the inlet 265 may be employed, so long as they are capable of supplying a sufficient amount of gas to the heat exchanger 205.

[0036] Figure 2B illustrates a schematic view of the heat exchanger 205. As illustrated, the heat exchanger 205 comprises a passageway 280 with a plurality of substantially square curves. The passageway 280 is arranged to maximize the surface area covered by the heat exchanger 205. The low temperature gas entering the inlet 265 flows through the passageway 280 in the direction illustrated by arrow 285. As the gas circulates through the passageway 280, the gas increases in temperature as the heat from the rotating control head 200 is transferred to the gas. The high temperature gas exits the outlet 270 as indicated by the direction of arrow 285. In this manner, the heat generated by the rotating control head 200 is transferred to the gas passing through the heat exchanger 205.

[0037] Figure 3A illustrates a rotating control head 300 cooled by a gas. As shown, the rotating control head 300 is depicted generally to illustrate this embodiment of the invention, thereby applying this embodiment to a variety of different types of rotating control heads. A hydraulic control 310 supplies fluid to the rotating control head 300. The hydraulic control 310 typically includes a reservoir 315 to contain a supply of fluid and a pump 320 to communicate the fluid from the reservoir 315 to the rotating control head 300. Additionally, the hydraulic control 310 includes a valve 345 to relieve excess pressure in the rotating control head 300.

[0038] Generally, the hydraulic control 310 supplies fluid to energize a bladder 330 and lubricate a plurality of bearings 355. As the fluid enters a port 335, a portion is communicated to the plurality of bearings 355 and another portion is used to fill a chamber 340. As the chamber 340 fills with a fluid, a pressure P1 is created. Pressure P1 acts against the bladder 330 causing the bladder 330 to move radially inward to seal around a tubular (not shown). Typically, the pressure P1 is maintained between 0 to 200 psi above a wellbore pressure P2. If the wellbore pressure P2 drops, the pressure P1 may be relieved through valve 345 by removing a portion of the fluid from the chamber 340.

[0039] The rotating control head 300 is cooled by a flow of gas through a substantially circular passageway 380 through an upper portion of the rotating control head 300. The circular passageway 380 is constructed and arranged to remove heat from the rotating control head 300 by introducing a gas, such as air, at a low temperature into an inlet 365, transferring heat energy to the gas and subsequently allowing the gas at a high temperature to exit through an outlet 370. The heat energy is transferred from a plurality of radial seals 375A and 375B and the plurality of bearings 355 as the gas passes through the circular passageway 380. Typically, gas is pumped into the inlet 365 by a blowing apparatus (not shown). However, other means of communicating gas to the inlet 365 may be employed, so long as they are capable of supplying a sufficient amount of gas to the substantially circular passageway 380.

[0040] Figure 3B illustrates a schematic view of the gas passing through the substantially circular passageway 380. The circular passageway 380 is arranged to maximize the surface area covered by the circular passageway 380. The low temperature gas entering the inlet 365 flows through the circular passageway 380 in the direction illustrated by arrow 385. As the gas circulates through the circular passageway 380, the gas increases in temperature as the heat from the rotating control head 300 is transferred to the gas. The high temperature gas exits the outlet 370 as indicated by the direction of arrow 385. In this manner, the heat generated by the rotating control head 300 is removed allowing the rotating control head 300 to function properly.

[0041] In an alternative embodiment, the rotating control head 300 may operate without the use of the circular passageway 380. In other words, the rotating control head 300 would function properly without removing heat from the plurality of radial seals 375A and 375B and the plurality of bearings 355. This alternative embodiment typically applies when the wellbore pressure P2 is relatively low.

[0042] Figures 4A and 4B illustrate a rotating control head 400 cooled by a fluid mixture. As shown, the rotating control head 400 is depicted generally to illustrate this embodiment of the invention, thereby applying this embodiment to a variety of different types of rotating control heads. A hydraulic control 410 supplies fluid to the rotating control head 400. The hydraulic control 410 typically includes a reservoir 415 to contain a supply of fluid and a pump 420 to communicate the fluid from the reservoir 415 to the rotating control head 400. Additionally, the hydraulic control 410 includes a valve 445 to relieve excess pressure in the rotating control head 400. In the same manner as the hydraulic control 310, the hydraulic control 410 supplies fluid to energize a bladder 430 and lubricate a plurality of bearings 455.

[0043] The rotating control head 400 is cooled by a fluid mixture circulated through a substantially circular passageway

480 on an upper portion of the rotating control head 400. In the embodiment shown, the fluid mixture preferably consists of water or a water-glycol mixture. However, other mixtures of fluid may be employed, so long as, the fluid mixture has the capability to circulate through the circular passageway 480 and reduce the heat in the rotating control head 400.

[0044] The circular passageway 480 is constructed and arranged to remove heat from the rotating control head 400 by introducing the fluid mixture at a low temperature into an inlet 465, transferring heat energy to the fluid mixture and subsequently allowing the fluid mixture at a high temperature to exit through an outlet 470. The heat energy is transferred from a plurality of radial seals 475A and 475B and the plurality of bearings 455 as the fluid mixture circulates through the circular passageway 480. The fluid mixture is preferably pumped into the inlet 465 through a fluid circuit 425. The fluid circuit 425 is comprised of a reservoir 490 to contain a supply of the fluid mixture and a pump 495 to circulate the fluid mixture through the rotating control head 400.

[0045] Figure 4B illustrates a schematic view of the fluid mixture circulating in the substantially circular passageway 480. The circular passageway 480 is arranged to maximize the surface area covered by the circular passageway 480. The low temperature fluid entering the inlet 465 flows through the circular passageway 480 in the direction illustrated by arrow 485. As the fluid circulates through the circular passageway 480, the fluid increases in temperature as the heat from the rotating control head 400 is transferred to the fluid. The high temperature fluid exits out the outlet 470 as indicated by the direction of arrow 485. In this manner, the heat generated by the rotating control head 400 is removed allowing the rotating control head 400 to function properly.

[0046] Figures 5A and 5B illustrate a rotating control head 500 cooled by a refrigerant. As shown, the rotating control head 500 is depicted generally to illustrate this embodiment of the invention, thereby applying this embodiment to a variety of different types of rotating control heads. A hydraulic control 510 supplies fluid to the rotating control head 500. The hydraulic control 510 typically includes a reservoir 515 to contain a supply of fluid and a pump 520 to communicate the fluid from the reservoir 515 to the rotating control head 500. Additionally, the hydraulic control 510 includes a valve 545 to relieve excess pressure in the rotating control head 500. In the same manner as the hydraulic control 310, the hydraulic control 510 supplies fluid to energize a bladder 530 and lubricate a plurality of bearings 555.

[0047] The rotating control head 500 is cooled by a refrigerant circulated through a substantially circular passageway 580 in an upper portion of the rotating control head 500. The circular passageway 580 is constructed and arranged to remove heat from the rotating control head 500 by introducing the refrigerant at a low temperature into an inlet 565, transferring heat energy to the refrigerant and subsequently allowing the refrigerant at a high temperature to exit through an outlet 570. The heat energy is transferred from a plurality of radial seals 575A and 575B and the plurality of bearings 555 as the refrigerant circulates through the circular passageway 580. The refrigerant is preferably communicated into the inlet 565 through a refrigerant circuit 525. The refrigerant circuit 525 includes a reservoir 590 containing a supply of vapor refrigerant. A compressor 595 draws the vapor refrigerant from the reservoir 590 and compresses the vapor refrigerant into a liquid refrigerant. Thereafter, the liquid refrigerant is communicated to an expansion valve 560. At this point, the expansion valve 560 changes the low temperature liquid refrigerant into a low temperature vapor refrigerant as the refrigerant enters inlet 565.

[0048] Figure 5B illustrates a schematic view of the vapor refrigerant circulating in the substantially circular passageway 580. The circular passageway 580 is arranged in an approximately 320-degree arc to maximize the surface area covered by the circular passageway 580. The low temperature vapor refrigerant entering the inlet 565 flows through the circular passageway 580 in the direction illustrated by arrow 585. As the vapor refrigerant circulates through the circular passageway 580, the vapor refrigerant increases in temperature as the heat from the rotating control head 500 is transferred to the vapor refrigerant. The high temperature vapor refrigerant exits out the outlet 570 as indicated by the direction of arrow 585. Thereafter, the high temperature vapor refrigerant rejects the heat to the environment through a heat exchanger (not shown) and returns to the reservoir 590. In this manner, the heat generated by the rotating control head 500 is removed allowing the rotating control head 500 to function properly.

[0049] Figure 6 illustrates a rotating control head 600 actuated by a piston intensifier circuit 610 in communication with a wellbore 680. As shown, the rotating control head 600 is depicted generally to illustrate this embodiment of the invention, thereby applying this embodiment to a variety of different types of rotating control heads. The piston intensifier circuit 610 supplies fluid to the rotating control head 600. The piston intensifier circuit 610 typically includes a housing 645 and a piston arrangement 630. The piston arrangement, generally indicated at 630, is formed from a larger piston 620 and a smaller piston 615. The pistons 615, 620 are constructed and arranged to maintain a pressure differential between a hydraulic pressure P1 and a wellbore pressure P2. In other words, the pistons 615, 620 are designed with a specific surface area ratio to maintain about a 200 psi pressure differential between the hydraulic pressure P1 and the wellbore pressure P2, thereby allowing the P1 to be 200 psi higher than P2. The piston arrangement 630 is disposed in the housing 645 to form an upper chamber 660 and lower chamber 685. Additionally, a plurality of seal members 605, 606 are disposed around the pistons 615, 620, respectively, to form a fluid tight seal between the chambers 660, 685.

[0050] The piston intensifier circuit 610 mechanically provides hydraulic pressure P1 to energize a bladder 650. Initially, fluid is filled into upper chamber 660 and is thereafter sealed. The wellbore fluid from the wellbore 680 is in fluid communication with lower chamber 685. Therefore, as the wellbore pressure P2 increases more wellbore fluid is communi-

cated to the lower chamber 685 creating a pressure in the lower chamber 685. The pressure in the lower chamber 685 causes the piston arrangement 630 to move axially upward forcing fluid in the upper chamber 660 to enter port 635 and pressurize a chamber 640. As the chamber 640 fills with a fluid, the pressure P1 increases causing the bladder 650 to move radially inward to seal around a tubular (not shown). In this manner, the bladder 650 is energized allowing the

rotating control head 600 to seal around a tubular.
[0051] A fluid, such as water-glycol, is circulated through the rotating control head 600 by a fluid circuit 625. Typically, heat on the rotating control head 600 is removed by introducing the fluid at a low temperature into an inlet 665, transferring heat energy to the fluid and subsequently allowing the fluid at a high temperature to exit through an outlet 670. The heat energy is transferred from a plurality of radial seals 675A and 675B and the plurality of bearings 655 as the fluid circulates through the rotating control head 600. The fluid is preferably pumped into the inlet 665 through the fluid circuit 625. Generally, the circuit 625 comprises a reservoir 690 to contain a supply of the fluid and a pump 695 to circulate the fluid through the rotating control head 600.

[0052] In another embodiment, the piston intensifier circuit 610 is in fluid communication with a nitrogen gas source (not shown). In this embodiment, a pressure transducer (not shown) measures the wellbore pressure P2 and subsequently injects nitrogen into the lower chamber 685 at the same pressure as pressure P2. The nitrogen pressure in the lower chamber 685 may be adjusted as the wellbore pressure P2 changes, thereby maintaining the desired pressure differential between hydraulic pressure P1 and wellbore pressure P2.

[0053] Figure 7A illustrates an alternative embodiment of a rotating control head 700 in an unlocked position. The rotating control head 700 is arranged and constructed in a similar manner as the rotating control head 100 shown on Figure 1. Therefore, for convenience, similar components that function in the same manner will be labeled with the same numbers as the rotating control head 100. The primary difference between the rotating control head 700 and rotating control head 100 is the active seal assembly.

[0054] As shown in Figure 7A, the rotating control head 700 includes an active seal assembly, generally indicated at 705. The active seal assembly 705 includes a primary seal 735 that moves radially inward as a piston 715 wedges against a tapered surface of the seal 735. The primary seal 735 is constructed from flexible material to permit sealing around irregularly shaped tubular string such as a hexagonal kelly. The upper end of the seal 735 is connected to a top ring 710.

[0055] The active sealing assembly 705 includes an upper chamber 720 and a lower chamber 725. The upper chamber 720 is formed between the piston 715 and a piston housing 740. To move the rotating control head 700 from an unlocked or relaxed position to a locked or sealed position, fluid is pumped through port 745 into an upper chamber 720. As fluid fills the upper chamber 720, the pressure created acts against the lower end of the piston 715 and urges the piston 715 axially upward towards the top ring 710. At the same time, the piston 715 wedges against the tapered portion of the primary seal 735 causing the seal 735 to move radially inward to seal against the tubular (not shown). In this manner, the active seal assembly 705 is in the locked or sealed position as illustrated in Figure 7B.

[0056] As shown on Figure 7B, the piston 715 has moved axially upward contacting the top ring 710 and the primary seal 735 has moved radially inward. To move the active seal assembly 705 from the locked position to the unlocked position, fluid is pumped through port 755 into the lower chamber 725. As the chamber fills up, the fluid creates a pressure that acts against surface 760 to urge the piston 715 axially downward, thereby allowing the primary seal 735 to move radially outward, as shown on Figure 7A.

[0057] Figure 8 illustrates an alternative embodiment of a rotating control head 800 in accord with the present invention. The rotating control head 800 is constructed from similar components as the rotating control head 100, as shown on Figure 1. Therefore, for convenience, similar components that function in the same manner will be labeled with the same numbers as the rotating control head 100. The primary difference between the rotating control head 800 and rotating control head 100 is the location of the active seal assembly 105 and the passive seal assembly 110.

[0058] As shown in Figure 8, the passive seal assembly 110 is disposed above the active seal assembly 105. The passive seal assembly 110 is operatively attached to the bladder support housing 135, thereby allowing the passive seal assembly 110 to rotate with the active seal assembly 105. The passive seal assembly 110 is constructed and arranged in an axially downward conical shape, thereby allowing the pressure in the rotating control head 800 to act against the tapered surface 195 and close the passive seal assembly 110 around the tubular (not shown). Additionally, the passive seal assembly 110 includes the inner diameter 190, which is smaller than the outer diameter of the tubular to allow an interference fit between the tubular and the passive seal assembly 110.

[0059] As depicted, the active seal assembly 105 includes the bladder support housing 135 mounted on the plurality of bearings 125. The bladder support housing 135 is used to mount bladder 130. Under hydraulic pressure, bladder 130 moves radially inward to seal around a tubular such as a drilling tubular (not shown). Generally, fluid is supplied to the chamber 150 under a controlled pressure to energize the bladder 130. Essentially, a hydraulic control (not shown) maintains and monitors hydraulic pressure within pressure chamber 150. Hydraulic pressure P1 is preferably maintained by the hydraulic control between 0 to 200 psi above a wellbore pressure P2. The bladder 130 is constructed from flexible material allowing bladder surface 175 to press against the tubular at approximately the same pressure as the hydraulic

pressure P1.

[0060] The hydraulic control may be used to de-energize the bladder 130 and allow the active seal assembly 105 to release the seal around the tubular. Generally, the fluid in the chamber 150 is drained into a hydraulic reservoir (not shown), thereby reducing the pressure P1. Subsequently, the bladder surface 175 loses contact with the tubular as the bladder 130 becomes de-energized and moves radially outward. In this manner, the seal around the tubular is released allowing the tubular to be removed from the rotating control head 800.

[0061] Figure 9 illustrates another alternative embodiment of a rotating control head, generally indicated at 900. The rotating control head 900 is generally constructed from similar components as the rotating control head 100, as shown in Figure 1. Therefore, for convenience, similar components that function in the same manner will be labeled with the same numbers as the rotating control head 100. The primary difference between rotating control head 900 and rotating control head 100 is the use of two passive seal assemblies 110, an alternative cooling system using one fluid to cool the radial seals and bearings in combination with a radial seal pressure protection system, and a secondary piston SP in addition to a primary piston P for urging the piston P to the unlatched position. These differences will be discussed below in detail.

[0062] While Figure 9 shows the rotating control head 900 latched in a housing H above a diverter D, it is contemplated that the rotating control heads as shown in the figures could be positioned with any housing or riser as disclosed in U.S. Patent Nos. 6,138,774, 6,263,982, 6,470,975, U.S. Patent Application Serial No. 10/281,534, filed October 28, 2002 and published June 12, 2003 under U.S. Patent Application No. 2003-0106712-A1, or U.S. Patent Application No. 10/995,980, filed November 23, 2004, all of which are assigned to the assignee of the present invention and incorporated herein by reference for all purposes.

[0063] As shown in Figure 9, both passive seal assemblies 110 are operably attached to the inner member support housing 135, thereby allowing the passive seal assemblies to rotate together. The passive seal assemblies are constructed and arranged in an axially-downward conical shape, thereby allowing the wellbore pressure P2 in the rotating control head 900 to act against the tapered surfaces 195 to close the passive seal assemblies around the tubular T. Additionally, the passive seal assemblies include inner diameters which are smaller than the outer diameter of the tubular T to allow an interference fit between the tubular and the passive seal assemblies.

[0064] Figure 11 discloses a cooling system where air enters a passageway, formed as a labyrinth L, in a rotating control head RCH similar to the passageway shown in Figures 2A and 2B of the present invention.

[0065] Figure 12 discloses a cooling system where hydraulic fluid moving through inlet I to outlet O is used to cool the top radial seals SI and S2 with a seal carrier in a rotating control head RCH.

[0066] Turning now to Figures 9, 13 and 14, the rotating control head 900 is cooled by a heat exchanger, generally indicated at 905. As best shown in Figures 13 and 14, heat exchanger 905 is constructed and arranged to remove heat from the rotating control head 900 using a fluid, such as an unctuous combustible substance. One such unctuous combustible substance is a hydraulic oil, such as Mobil 630 ISO 90 weight oil. This fluid is introduced at a low temperature into inlet 965, thereafter transferring heat from upper top radial seal 975A and lower top radial seal 975B, via seal carrier 982A and its thermal transfer surfaces 982A' and a plurality of beatings, including bearings 955, to the fluid as the fluid passes through the heat exchanger 905 and, as best shown in Figure 14, to outlet 970.

[0067] In particular, the top radial seals 975A and 975B are cooled by circulating the hydraulic fluid, preferably oil, in and out of the bearing section B and making multiple passes around the seals 975A and 975B through a continuous spiral slot 980C in the seal housing 982B, as best shown in Figures 9, 13 and 14. Since the hydraulic fluid that passes through slot passageway or slot 980C is the same fluid used to pressure the bearing section B, fluid can be circulated close to and with the radial seals 975A and 975B to improve the heat transfer properties. Although the illustrated embodiment uses a continuous spiral slot, other embodiments are contemplated for different methods for making multiple passes with one fluid adjacent to and in fluid contact with the radial seals.

[0068] As best shown in Figure 14, the passageway of the heat exchanger 905 includes inlet passageway 980A, outlet passageway 980B, and slot passageway 980C that spirals between the lower portion of inlet passageway 980A to upper outlet passageway 980B. These multiple passes adjacent the radial seals 975A and 975B maximize the surface area covered by the heat exchanger 905. The temperature hydraulic oil entering the inlet 965 flows through the passageway in the direction illustrated by arrows 985. As the oil circulates through the passageway, the oil increases in temperature as the heat from the rotating control head 900 is transferred to the oil. The higher temperature oil exits the outlet 970. In this manner, the heat generated about the top radial seals in the rotating control head 900 is transferred to the oil passing through the multiple pass heat exchanger 905. Moreover, separate fluids are not used to cool and to lubricate the rotating control head 900. Instead, only one fluid, such as a Mobil 630 ISO fluid 90 weight oil, is used to both cool and lubricate the rotating control head 900.

[0069] Returning to Figure 9, it is contemplated that a similar cooling system using the multiple pass heat exchanger of the present invention could be used to cool the bottom radial seals 975C and 975D of the rotating control head 900.

[0070] Returning now to Figure 13, the top radial seals 975A and 975B are staged in tandem or series. The lower top radial 975B, which would be closer to the bearings 955, is a high flow seal that would allow approximately two gallons

of oil per minute to pass by seal 975B. The upper top radial seal 975A, which would be the seal closer to the atmosphere or environment, would be a low flow seal that would allow approximately 1cc of oil per hour to pass by the seal 975A. A port 984, accessible from the atmosphere, is formed between the radial seals 975A and 975B. As illustrated in both Figures 13 and 15B, an electronically-controlled valve, generally indicated at V200, would regulate the pressure between the radial seals 975A and 975B. Preferably, as discussed below in detail, the pressure on upper top radial seal 975A is approximately half the pressure on lower top radial seal 975B so that the differential pressure on each radial seal is lower, which in turn reduces the PV factor by approximately half. Testing of a Weatherford model 7800 rotating control head has shown that when using a Kalsi seal, with part number 381-6-11, for the upper top radial seal 975A, and modified (as discussed below) Kalsi seal, with part number 432-32-10CCW (cutting and gluing), for the lower top radial seal 975B, has shown increased seal life of the top radial seals.

[0071] The Kalsi seals referred to herein can be obtained from Kalsi Engineering, Inc. of Sugar Land, Texas. The preferred Kalsi 381-6-11 seal is stated by Kalsi Engineering, Inc. to have a nominal inside diameter of 10½", a seal radial depth of .415" ± 0.008", a seal axial width of 0.300", a gland depth of 0.380", a gland width of 0.342" and an approximate as-molded seal inside diameter of 10.500" (266.7 mm). This seal is further stated by Kalsi to be fabricated from HSN (peroxide cured, high ACN) with a material hardness of Shore A durometer of 85 to 90. While the preferred Kalsi 432-32-10CCW seal is stated by Kalsi Engineering, Inc. to have a nominal inside diameter of 42.375", a seal radial depth of .460" ± 0.007", a seal axial width of 0.300", a gland width of 0.342" and an approximate as-molded seal inside diameter of 42.375" (1,076 mm), this high flow seal was reduced to an inside diameter the same as the preferred Kalsi 381-6-11 seal, i.e. 10½". This high flow seal 975B is further stated by Kalsi to be fabricated from HSN (fully saturated peroxide cured, medium-high ACN) with a material hardness of Shore A durometer of 85 ± 5. It is contemplated that other similar sizes and types of manufacturers' seals, such as seals provided by Parker Hannifin of Cleveland, Ohio, could be used.

Startup Operation

[0072] Turning now to Figures 15A to 25 along with below Tables 1 and 2, the startup operation of the hydraulic or fluid control of the rotating control head 900 is described. Referring particularly to Figure 25, to start the power unit, button PB10 on the control console, generally indicated at CC, is pressed and switch SW10 is moved to the ON position. As discussed in the flowcharts of Figures 16-17, the program of the programmable logic controller PLC checks to make sure that button PB10 and switch SW10 were operated less than 3 seconds of each other. If the elapsed time is equal to or over 3 seconds, the change in position of SW10 is not recognized. Continuing on the flowchart of Figure 16, the two temperature switches TS10 TS20, also shown in Figure 15B, are then checked. These temperature switches indicate oil tank temperature. When the oil temperature is below a designated temperature, e.g. 80°F, the heater HT10 (Figure 15B) is turned on and the power unit will not be allowed to start until the oil temperature reaches the designated temperature. When the oil temperature is above a designated temperature, e.g. 130°F, the heater is turned off and cooler motor M2 is turned on. As described in the flowchart of Figure 17, the last start up sequence is to check to see if the cooler motor M2 needs to be turned on.

[0073] Continuing on the flowchart of Figure 16, the wellbore pressure P2 is checked to see if below 50psi. As shown in below Table 2, associated alarms 10, 20, 30 and 40, light LT100 on control console CC, horn HN10 in Figure 15B, and corresponding text messages on display monitor DM on console CC will be activated as appropriate. Wellbore pressure P2 is measured by pressure transducer PT70 (Figure 15A). Further, reviewing Figures 15B to 17, when the power unit for the rotating control head, such as a Weatherford model 7800, is started, the three oil tank level switches LS10, LST20 and LS30 are checked. The level switches are positioned to indicate when the tank 634 is overfull (no room for heat expansion of the oil), when the tank is low (oil heater coil is close to being exposed), or when the tank is empty (oil heater coil is exposed). As long as the tank 634 is not overfull or empty, the power unit will pass this check by the PLC program.

[0074] Assuming that the power unit is within the above parameters, valves V80 and V90 are placed in their open positions, as shown in Figure 15B. These valve openings unload gear pumps P2 and P3, respectively, so that when motor M1 starts, the oil is bypassed to tank 634. Valve V150 is also placed in its open position, as shown in Figure 15A, so that any other fluid in the system can circulate back to tank 634. Returning to Figure 15B, pump P1, which is powered by motor M1, will compensate to a predetermined value. The pressure recommended by the pump manufacturer for internal pump lubrication is approximately 300 psi. The compensation of the pump P1 is controlled by valve V10 (Figure 15B).

[0075] Continuing review of the flowchart of Figure 16, fluid level readings outside of the allowed values will activate alarms 50, 60 or 70 (see also below Table 2 for alarms) and their respective lights LT100, LT50 and LT60. Text messages corresponding to these alarms are displayed on display monitor DM.

[0076] When the PLC program has checked all of the above parameters the power unit will be allowed to start. Referring to the control console CC in Figure 25, the light LT10 is then turned on to indicate the PUMP ON status of the power unit. Pressure gauge PG20 on console CC continues, to read the pump pressure provided by pressure transducer PT10,

shown in Figure 15B.

[0077] When shutdown of the unit desired, the PLC program checks to see if conditions are acceptable to turn the power unit off. For example, the wellbore pressure P2 should be below 50psi. Both the enable button PB10 must be pressed and the power switch SW10 must be turned to the OFF position within 3 seconds to turn the power unit off.

Latching Operation System Circuit

Closing the Latching System

[0078] Focusing now on Figures 9, 15A, 18, 23 and 24, the retainer member LP of the latching system of housing H is closed or latched, as shown in Figure 9, by valve V60 (Figure 15A) changing to a flow position, so that the ports P-A, B-T are connected. The fluid pilot valve V110 (Figure 15A) opens so that the fluid on that side of the primary piston P can go back to tank 634 via line FM40L through the B-T port. Valve V100 prevents reverse flow in case of a loss of pressure. Accumulator A (which allows room for heat expansion of the fluid in the latch assembly) is set at 900psi, slightly above the latch pressure 800psi, so that it will not charge. Fluid pilot valve V140 (Figure 15A) opens so that fluid underneath the secondary piston SP goes back to tank 634 via line FM50L and valve V130 is forced closed by the resulting fluid pressure. Valve V70 is shown in Figure 15A in its center position where all ports (APBT blocked) are blocked to block flow in any line. The pump P1, shown in Figure 15B, compensates to a predetermined pressure of approximately 800psi.

[0079] The retainer member LP, primary piston P and secondary piston SP of the latching system are mechanically illustrated in Figure 9 (latching system is in its closed or latched position), schematically shown in Figure 15A, and their operations are described in the flowcharts in Figures 18, 23 and 24. Alternative latching systems are disclosed in Figures 1 and 8 and in US. Patent Application No. 10/995,980, filed November 23, 2004.

[0080] With the above described startup operation achieved, the hydraulics switch SW20 on the control console CC is turned to the ON position. This allows the pump P1 to compensate to the required pressure later in the PLC program. The bearing latch switch SW40 on console CC is then turned to the CLOSED position. The program then follows the process outlined in the CLOSED leg of SW40 described in the flowchart of Figure 18. The pump P1 adjusts to provide 800psi and the valve positions are then set as detailed above. As discussed below, the PLC program then compares the amount of fluid that flows through flow meters FM30, FM40 and FM50 to ensure that the required amount of fluid to close or latch the latching system goes through the flow meters. Lights LT20, LT30, LT60 and LT70 on console CC show the proper state of the latch. Pressure gauge PG20, as shown on the control console CC, continues to read the pressure from pressure transducer PT10 (Figure 15B).

Primary Latching System Opening

[0081] Similar to the above latch closing process, the PLC program follows the OPEN leg of SW40 as discussed in the flowchart of Figure 18 and then the OFF leg of SW50 of Figure 18 to open or unlatch the latching system. Turning to Figure 15A, prior to opening or unlatching the retainer member LP of the latching system, pressure transducer PT70 checks the wellbore pressure P2. If the PT70 reading is above a predetermined pressure (approximately 50psi), the power unit will not allow the retainer member LP to open or unlatch. Three-way valve V70 (Figure 15A) is again in the APBT blocked position. Valve V60 shifts to flow position P-B and A-T. The fluid flows through valve V110 into the chamber to urge the primary piston P to move to allow retainer member LP to unlatch. The pump P1, shown in Figure 15B, compensates to a predetermined value (approximately 2000psi). Fluid pilots open valve V100 to allow fluid of the primary piston P to flow through line FM30L and the A-T ports back to tank 634.

Secondary Latching System Opening

[0082] The PLC program following the OPEN leg of SW40 and the OPEN leg of SW50, described in the flowchart of Figure 18, moves the secondary piston SP. The secondary piston SP is used to open or unlatch the primary piston P and, therefore, the retainer member LP of the latching system. Prior to unlatching the latching system, pressure transducer PT70 again checks the wellbore pressure P2. If PT70 is reading above a predetermined pressure (approximately 50psi), the power unit will not allow the latching system to open or unlatch. Valve V60 is in the APBT blocked position, as shown in Figure 15A. Valve V70 then shifts to flow position P-A and B-T. Fluid flows to the chamber of the secondary latch piston SP via line FM50L. With valve V140 forced closed by the resulting pressure and valve V130 piloted open, fluid from both sides of the primary piston P is allowed to go back to tank 634 through the B-T ports of valve V70.

Bearing Assembly Circuit

[0083] Continuing to review Figures 9, 15A, 15B and 18 and the below Tables 1 and 2, now review Figures 19 to 22 describing the bearing assembly circuit.

[0084] Valve positions on valve V80 and valve V90, shown in Figure 15B, and valve V160, shown in Figure 15A, are moved to provide a pressure in the rotating control head that is above the wellbore pressure P2. In particular, the wellbore pressure P2 is measured by pressure transducer PT70, shown in Figure 15A. Depending on the wellbore pressure P2, valve V90 and valve V80 (Figure 15B) are either open or closed. By opening either valve, pressure in the rotating control head can be reduced by allowing fluid to go back to tank 634. Also, depending on pressure in the rotating control head, valve V160 will move to a position that selects a different size orifice. The orifice size, e.g. 3/32" or 1/8" (Figure 15A), will determine how much back pressure is in the rotating control head. By using this combination of valves V80, V90 and V160, four different pressures can be achieved.

[0085] During the operation of the bearing assembly circuit, the temperature switches TS10 and TS20, described in the above startup operation, continue to read the oil temperature in the tank 634, and operate the heater HT10 or cooler motor M2, as required. For example, if the oil temperature exceeds a predetermined value, the cooler motor M2 is turned on and the cooler will transfer heat from the oil returning from the bearing section or assembly B.

[0086] Flow meter FM10 measures the volume or flow rate of fluid or oil to the chamber in the bearing section or assembly B via line FM10L. Flow meter FM20 measures the volume or flow rate of fluid or oil from the chamber in the bearing section or assembly B via line FM20L. As discussed further below in the bearing leak detection system section, if the flow meter FM20 reading is greater than the flow meter FM10 reading, this could indicate that wellbore fluid is entering the bearing assembly chamber. Valve V150 is then moved from the open position, as shown in Figure 15A, to its closed position to keep the wellbore fluid from going back to tank 634.

Regulating Pressure in the Radial Seals

[0087] Reviewing Figures 13, 14, 15B, 22 and 23 along with the below Tables 1 and 2, pressure transducer PT80 (Figure 15B) reads the amount of fluid "seal bleed" pressure between the top radial seals 975A and 975B via port 984. As discussed above, proportional relief valve V200 adjusts to maintain a predetermined pressure between the two radial seals 975A and 975B. Based on the well pressure P2 indicated by the pressure transducer PT70, the valve V200 adjusts to achieve the desired "seal bleed" pressure as shown in the below Table 1.

TABLE 1

WELL PRESSURE	SEAL BLEED PRESSURE
0-500	100
500-1200	300
1200-UP	700

[0088] The flowchart of Figure 18 on the CLOSED leg of SW40 and after the subroutine to compare flow meters FM30, FM40 and FM50, describes how the valves adjust to match the pressures in above Table 1. Figures 19 to 22 describes a subroutine for the program to adjust pressures in relation to the wellbore pressure P2.

Alarms

[0089] During the running of the PLC program, certain sensors such as flow meters and pressure transducers are checked. If the values are out of tolerance, alarms are activated. The flowcharts of Figures 16-18 describe when the alarms are activated. Below Table 2 shows the lights, horn and causes associated with the activated alarms. The lights listed in Table 2 correspond to the lights shown on the control console CC of Figure 25. As discussed below, a text message corresponding to the cause is sent to the display monitor DM on the control console CC.

Latch Leak Detection System

FM30/FM40 Comparison

[0090] Usually the PLC program will run a comparison where the secondary piston SP is "bottomed out" or in its latched position, such as shown in Figure 9, or when only a primary piston P is used, such as shown in Figure 1, the piston P

is bottomed out. In this comparison, the flow meter FM30 coupled to the line FM30L measures either the flow volume value or flow rate value of fluid to the piston chamber to move the piston P to the latched position, as shown in Figure 9, from the unlatched position, as shown in Figure 1. Also, the flow meter FM40 coupled to the line FM40L measures the desired flow volume value or flow rate value from the piston chamber. Since the secondary piston SP is bottomed out, there should be no flow in line FM50L, as shown in Figure 9. Since no secondary piston is shown in Figure 1, there is no line FM50L or flow meter FM50.

[0091] In this comparison, if there are no significant leaks, the flow volume value or flow rate value measured by flow meter FM30 should be equal to the flow volume value or flow rate value, respectively, measured by flow meter FM40 within a predetermined tolerance. If a leak is detected because the comparison is outside the predetermined tolerance, the results of this FM30/FM40 comparison would be displayed on display monitor DM on control console CC, as shown in Figure 25, preferably in a text message, such as "Alarm 90 - Fluid Leak". Furthermore, if the values from flow meter FM30 and flow meter FM40 are not within the predetermined tolerance, i.e. a leak is detected, the corresponding light LT100 would be displayed on the control console CC.

FM30/FM50 Comparison

[0092] In a less common comparison, the secondary piston SP would be in its "full up" position. That is, the secondary piston SP has urged the primary piston P, when viewing Figure 9, as far up as it can move to its full unlatched position. In this comparison, the flow volume value or flow rate value, measured by flow meter FM30 coupled to line FM30L, to move piston P to its latched position, as shown in Figure 9, is measured. If the secondary piston SP is sized so that it would block line FM40L, no fluid would be measured by flow meter FM40. But fluid beneath the secondary piston SP would be evacuated via line FM50L from the piston chamber of the latch assembly. Flow meter 50 would then measure the flow volume value or flow rate value. The measured flow volume value or flow rate value from flow meter FM30 is then compared to the measured flow volume value or flow rate value from flow meter FM50.

[0093] If the compared FM30/FM50 values are within a predetermined tolerance, then no significant leaks are considered detected. If a leak is detected, the results of this FM30/FM50 comparison would be displayed on display monitor DM on control console CC, preferably in a text message, such as "Alarm 100 - Fluid Leak". Furthermore, if the values from flow meter FM30 and flow meter FM50 are not within a predetermined tolerance, the corresponding light LT100 would be displayed on the control console CC.

FM30/FM40 + FM50 Comparison

[0094] Sometimes the primary piston P is in its full unlatched position and the secondary piston SP is somewhere between its bottomed out position and in contact with the fully unlatched piston P. In this comparison, the flow volume value or flow rate value measured by the flow meter FM30 to move piston P to its latched position is measured. If the secondary piston SP is sized so that it does not block line FM40L, fluid between secondary piston SP and piston P is evacuated by line FM40L. The flow meter FM40 then measures the flow volume value or flow rate value via line FM40L. This measured value from flow meter FM40 is compared to the measured value from flow meter FM30. Also, the flow value beneath secondary piston SP is evacuated via line FM50L and measured by flow meter FM50.

[0095] If the flow value from flow meter FM30 is not within a predetermined tolerance of the compared sum of the flow values from flow meter FM40 and flow meter FM50, then the corresponding light LT100 would be displayed on the control console CC. This detected leak is displayed on display monitor DM in a text message.

Measured Value/Predetermined Value

[0096] An alternative to the above leak detection methods of comparing measured values is to use a predetermined or previously calculated value. The PLC program then compares the measured flow value in and/or from the latching system to the predetermined flow value plus a predetermined tolerance.

[0097] It is noted that in addition to indicating the latch position, the flow meters FM30, FM40 and FM50 are also monitored so that if fluid flow continues after the piston P has moved to the closed or latched position for a predetermined time period, a possible hose or seal leak is flagged.

[0098] For example, alarms 90, 100 and 110, as shown in below Table 2, could be activated as follows:

[0099] Alarm 90 - primary piston P is in the open or unlatched position. The flow meter FM40 measured flow value is compared to a predetermined value plus a tolerance to indicate the position of piston P. When the flow meter FM40 reaches the tolerance range of this predetermined value, the piston P is indicated in the open or unlatched position. If the flow meter FM40 either exceeds this tolerance range of the predetermined value or continues to read a flow value after a predetermined time period, such as an hour, the PLC program indicates the alarm 90 and its corresponding light and text message as discussed herein.

[0100] Alarm 100 - secondary piston SP is in the open or unlatched position. The flow meter FM50 measured flow value is compared to a predetermined value plus a tolerance to indicate the position of secondary piston SP. When the flow meter FM50 reaches the tolerance range of this predetermined value, the secondary piston SP is indicated in the open or unlatched position. If the flow meter FM50 either exceeds this tolerance range of the predetermined value or continues to read a flow value after a predetermined time period, such as an hour, the PLC program indicates the alarm 100 and its corresponding light and text message as discussed herein.

[0101] Alarm 110 - primary piston P is in the closed or latched position. The flow meter FM30 measured flow value is compared to a predetermined value plus a tolerance to indicate the position of primary piston P. When the flow meter FM30 reaches the tolerance range of this predetermined value, the primary piston P is indicated in the closed or latched position. If the flow meter FM30 either exceeds this tolerance range of the predetermined value or continues to read a flow value after a predetermined time period, such as an hour, the PLC program indicates the alarm 110 and its corresponding light and text message as discussed herein.

Bearing Leak Detection System

FM10/FM20 Comparison

[0102] A leak detection system can also be used to determine if the bearing section or assembly B is losing fluid, such as oil, or, as discussed above, gaining fluid, such as wellbore fluids. As shown in Figure 15A, line FM10L and line FM20L move fluid to and from the bearing assembly B of a rotating control head and are coupled to respective flow meters FM10 and FM20.

[0103] If the measured fluid value, such as fluid volume value or fluid rate value, from flow meter FM10 is not within a predetermined tolerance of the measured fluid value from flow meter FM20, then alarms 120, 130 or 140, as described below in Table 2, are activated. For example, if the measured flow value to the bearing assembly B is greater than the measured flow value from the bearing assembly plus a predetermined percentage tolerance, then alarm 120 is activated and light LT90 on control console CC is turned on. Also, a text message is displayed on display monitor DM on the control console CC, such as "Alarm 120- Losing Oil." For example, this loss could be from the top radial seals leaking oil to the atmosphere, or the bottom radial seals leaking oil down the wellbore.

[0104] If the measured flow value from the bearing assembly read by flow meter FM20 is greater than the measured flow value to the bearing assembly read by flow meter FM10 plus a predetermined percentage tolerance, then alarm 130 is activated, light LT90 is turned on and a text message such as "Alarm 130 - Gaining Oil" is displayed on display monitor DM.

[0105] If the measured flow meter FM20 flow value/measured flow meter FM10 flow value is higher than the alarm 130 predetermined percentage tolerance, then alarm 140 is activated, light LT90 is turned on and a horn sounds in addition to a text message on display monitor DM, such as "Alarm 140 - Gaining Oil."

[0106] An alternative to the above leak detection methods of comparing measured values is to use a predetermined or previously calculated value. The PLC program then compares the measured flow value in and/or from the bearing assembly B to the predetermined flow value plus a predetermined tolerance.

TABLE 2

ALARM #	LIGHT	HORN	CAUSE
10	LT100	WB>100	WELLBORE>50, PT10=0; NO LATCH PUMP PRESSURE
20	LT100	WB>100	WELLBORE>50, PT20=0; NO BEARING LUBE PRESSURE
30	LT100	Y	WELLBORE>50, LT20=OFF; LATCH NOT CLOSED
40	LT100	Y	WELLBORE>50, LT30=OFF; SECONDARY LATCH NOT CLOSED
50	LT100		LS30=ON; TANK OVERFULL
60	LT50		LS20=OFF; TANK LOW
70	LT50	Y	LS10=OFF; TANK EMPTY
80	LT100	Y	WELLBORE>100, PT10=0; NO LATCH PRESSURE
90	LT100		FM40; FLUID LEAK; 10% TOLERANCE + FLUID MEASURE
100	LT100		FM50; FLUID LEAK; 10% TOLERANCE + FLUID MEASURE
110	LT100		FM30; FLUID LEAK; 10% TOLERANCE + FLUID MEASURE

(continued)

ALARM #	LIGHT	HORN	CAUSE
120	LT90		FM10>FM20 + 25%; BEARING LEAK (LOSING OIL)
130	LT90		FM20>FM10 + 15%; BEARING LEAK (GAINING OIL)
140	LT90	Y	FM20>FM10 + 30%; BEARING LEAK (GAINING OIL)

Piston Position Indicators

[0107] Additional methods are contemplated to indicate position of the primary piston P and/or secondary piston SP in the latching system. One example would be to use an electrical sensor, such as a linear displacement transducer, to measure the distance the selected piston has moved.

[0108] Another method could be drilling the housing of the latch assembly for a valve that would be opened or closed by either the primary piston P, as shown in the embodiment of Figure 1, or the secondary piston SP, as shown in the embodiment of Figures 9, 26 and 27. In this method, a port PO would be drilled or formed in the bottom of the piston chamber of the latch assembly. Port PO is in fluid communication with an inlet port IN (Figure 26) and an outlet port OU (Figure 27) extending perpendicular (radially outward) from the piston chamber of the latch assembly. These perpendicular ports would communicate with respective passages INP and OUP that extend upward in the radially outward portion of the latch assembly housing. Housing passage OUP is connected by a hose to a pressure transducer and/or flow meter. A machined valve seat VS in the port to the piston chamber receives a corresponding valve seat, such as a needle valve seat. The needle valve seat would be fixedly connected to a rod R receiving a coil spring CS about its lower portion to urge the needle valve seat to the open or unlatched position if neither primary piston P (Figure 1 embodiment) nor secondary piston SP (Figures 9, 26 and 27 embodiments) moves the needle valve seat to the closed or latched position. An alignment retainer member AR is sealed as the member is threadably connected to the housing H. The upper portion of rod R is slidably sealed with retainer member AR.

[0109] If a flow value and/or pressure is detected in the respective flow meter and/or pressure transducer communicating with passage OUP, then the valve is indicated open. This open valve indicates the piston is in the open or unlatched position. If no flow value and/or pressure is detected in the respective flow meter and/or pressure transducer communicating with passage OUP, then the valve is indicated closed. This closed valve indicates the piston is in the closed or latched position. The above piston position would be shown on the console CC, as shown in Figure 25, by lights LT20 or LT60 and LT30 or LT70 along with a corresponding text message on display monitor DM.

[0110] The invention may also be described by means of the following numbered clauses.

9. The system of clause 1A wherein the thermal transfer fluid is an unctuous combustible substance that is at least liquefiable on warming.

10. The system of clause 5A further comprising a tubular wherein one of the members having a bore sized to receive the tubular.

11. The system of clause 5A wherein the at least one bearing comprising:

a radial bearing, and
a thrust bearing.

25. A thermal transfer system adapted for use with a rotating control head, comprising:

a first member movable relative to a second member;
one of the members having a thermal transfer surface;
a first seal positioned with one of the members for sealing the first member with the second member while the first member moves relative to the second member;
a second seal positioned with one of the members for sealing the first member with the second member wherein the first seal allows flow of fluid at a first predetermined pressure and the second seal allows flow of fluid at a second predetermined pressure different than the first predetermined pressure;
a thermal transfer fluid circulated with at least one of the members; and
the thermal transfer surface transferring thermal units through multiple passes of the thermal transfer fluid adjacent the thermal transfer surface.

26. The system of clause 25, wherein the multiple passes comprises a spiral slot formed on one of the members adjacent the thermal transfer surface.

29. The method of clause 15A, wherein the cooling medium is an unctuous combustible substance that is at least liquefiable on warming.

36. The system of clause 20A, wherein the first piston is hydraulically actuated by the fluid to move between the latched position and the unlatched position.

37. The system of clause 20A, further comprising:

a first fluid line operatively connected to the latch assembly for delivering the fluid to the latch assembly;
a first meter coupled to the first fluid line, the first meter measuring a first fluid volume value for fluid delivered to the latch assembly;
a second fluid line operatively connected to the latch assembly for communicating the fluid from the latch assembly;
a second meter coupled to the second fluid line, the second meter measuring a second fluid volume value for fluid from the latch assembly;
the comparator configured to compare the measured first fluid volume value to the measured second fluid volume value; and
a display coupled to the comparator.

38. The system of clause 37, wherein the display indicates the results of the comparison of the measured first fluid volume value relative to the measured second fluid volume value.

39. The system of clause 37, the display comprising a text message.

41. The system of clause 23A, wherein the display indicates the results of the comparison of the first measured fluid value to the second fluid value.

43. The system of clause 24A, wherein the measured first fluid value is a measured fluid volume value for fluid delivered to the chamber, and wherein the measured second fluid value is a measured second fluid volume value.

44. The system of clause 43, wherein the results of the compared measured first fluid volume value and the measured second fluid volume value is displayed on the display.

45. The system of clause 24A, wherein the measured first fluid value is a measured fluid flow rate value, and wherein the measured second fluid value is a measured second fluid flow rate value.

46. The system of clause 24A, wherein the display indicates a text message resulting from the compared measured first fluid value to the measured second fluid value.

47. A system, comprising:

a rotating control head;
a latch assembly, latchable to the rotating control head, comprising:

a retainer member, radially movable between an unlatched position and a latched position, the retainer member latched with the rotating control head in the latched position; and
a piston having a first side and a second side, movable between a first position and a second position, the piston urging the retainer member to move to the latched position when the piston is in the first position and the first piston allowing the retainer member to move to the unlatched position when the piston is in the second position;

a comparator system, remotely coupled to the latch assembly, comprising:

a first fluid line operatively coupled to communicate fluid to a chamber for receiving the piston;
a first meter coupled to the first fluid line, the first meter measuring a first fluid value;

a second fluid line operatively coupled to communicate fluid from the chamber for receiving the piston;
a second meter coupled to the second fluid line, the second meter measuring a second fluid value;
a comparator, coupled to the first meter and the second meter, configured to compare the measured first
fluid value to the measured second fluid value; and
a display coupled to the comparator.

48. The system of clause 47, wherein the measured first fluid value is a measured fluid volume value for fluid delivered to the chamber on one side of the piston, and the measured second fluid value is a measured fluid volume value for fluid from the chamber on the other side of the piston.

49. The system of clause 48, wherein the compared measured first fluid volume value and, the measured second fluid volume value is displayed on the display.

50. The system of clause 47, wherein the first measured first fluid value is a measured fluid flow rate value, and the measured second fluid value is a measured second fluid flow rate value.

52. The method of clause 25A, the steps of measuring a volume of fluid comprising:

measuring the fluid with a totalizing flow meter;
reading the totalizing flow meter, producing the measured fluid volume value.

53. A method for use of a rotating control head having a bearing assembly for rotating while drilling, comprising the steps of:

positioning a chamber in the bearing assembly;
forming a first opening into the chamber;
forming a second opening into the chamber;
delivering a fluid to the first opening;
communicating the fluid from the second opening;
measuring a flow value of the fluid to the first opening;
measuring a flow value of the fluid from the second opening; and
comparing the measured flow value to the first opening to the measured flow value from the second opening.

54. The method of clause 26A, the steps of measuring a flow value of the fluid to the first opening comprising:

measuring the flow rate to the first opening with a first flow meter; and
reading the first flow meter and producing a measured first flow rate value.

55. The method of clause 54, the step of measuring a flow value of the fluid to the first opening comprising:

measuring the flow rate from the second opening with a first flow meter; and
reading the first flow meter and producing a measured first flow rate value.

56. The method of clause 55, further comprising the steps of comparing the measured first flow rate value to the first opening to the measured second flow rate from the second opening.

57. The method of clause 26A, the step of measuring a flow value of the fluid to the first opening comprising:

measuring the flow volume with a first flow meter; and
reading the first flow meter and producing a measured first flow volume value.

58. The method of clause 57, the step of measuring a flow value of the fluid from the second opening comprising:

measuring the flow volume with a second flow meter; and
reading the second flow meter and producing a measured second flow volume value.

59. The method of clause 58, further comprising the step of comparing the measured first flow volume value to the measured second flow volume.

1A. A thermal transfer system adapted for use with a rotating control head, comprising:

a first member movable relative to a second member;
one of the members having a thermal transfer surface;
a first seal positioned with one of the members for sealing the first member and the second member while the first member moves relative to the second member;
a thermal transfer fluid circulated with at least one of the members; and
the thermal transfer surface transferring thermal units through multiple passes of the thermal transfer fluid adjacent the thermal transfer surface.

2A. The system of claim 1A further comprising:

the thermal transfer surface comprises a surface of a seal carrier;
the seal carrier disposed with one of the members; and
the first seal positioned with the seal carrier for sealing the first member with the second member while the first member moves relative to the second member.

3A. The system of claim 1A or 2A, wherein the multiple passes comprise:

a spiral slot formed on one of the members adjacent the thermal transfer surface.

4A. The system of claim 3A wherein the spiral slot provides a continuous flow passageway for the thermal transfer fluid.

5A. The system of claim 1A further comprising:

at least one bearing provided between the first member and the second member.

6A. The system of claim 5A wherein the thermal transfer fluid is pressurized and communicates with the bearing.

7A. The system of claim 1A or 2A further comprising a port formed in one of the members or in the seal carrier to communicate with the first seal and to regulate the pressure of the fluid on the first seal.

8A. The system of claim 1A or 2A further comprising a second seal positioned with one of the members or with the seal carrier and for sealing the first member and the second member.

9A. The system of claim 8A further comprising a port formed in one of the members or in the seal carrier to communicate with the first seal and the second seal and to regulate the pressure of the fluid between the first seal and the second seal.

10A. The system of claim 8A further comprising the first seal allowing a first predetermined flow of the thermal transfer fluid to pass by the first seal, and the second seal allowing a second predetermined flow of the thermal transfer fluid to pass by the second seal and the second predetermined flow is greater than the first predetermined flow.

11A. The system of claim 8A wherein one of the seals allows flow of fluid at a first predetermined pressure and the other seal allows flow of fluid at a second predetermined pressure, the first predetermined pressure is higher than the second predetermined pressure.

12A. A system adapted for use with a rotating control head, comprising:

a first member movable relative to a second member;
a fluid circulated with at least one of the members;
a first seal positioned with one of the members for providing a predetermined flow value of the fluid between the first member and the second member; and
a port formed in one of the members, the port communicating with the first seal to regulate the fluid flowing by the first seal.

13A. The system of claim 12A further comprising a second seal positioned with the first member and the second member, wherein one of the seals allows flow of fluid at a first predetermined pressure and the other seal allows flow of fluid at a second predetermined pressure.

14A. The system of claim 12A further comprising a second seal positioned with the first member and the second member, wherein the first seal allowing a first predetermined flow of the fluid to pass by the first seal, and the second seal allowing a second predetermined flow of the fluid to pass by the second seal and the second predetermined flow is different than the first predetermined flow.

15A. A method for cooling a first radial seal in a rotating control head, comprising:

passing a cooling medium through the rotating control head with multiple passes adjacent to the first radial seal;
and
regulating the pressure of the cooling medium on the first radial seal.

16A. The method of claim 15A, further comprising the step of:

spiraling the cooling medium about the first radial seal in the rotating control head.

17A. The method of claim 15A further comprising a second radial seal and further comprising the step of

sealing between a first member that moves relative to the second member in the rotating control head with the first radial seal and the second radial seal.

18A. The method of claim 17A further comprising the step of:

regulating the pressure between the first radial seal and the second radial seal.

19A. The method of claim 17A further comprising the step of:

allowing flow of fluid past the second radial seal at a higher rate than the flow of fluid past the first radial seal.

20A. A system, comprising:

a latch assembly comprising a first piston movable between a latched position and an unlatched position;
a comparator configured to compare a fluid value moving to and from the latch assembly; and
wherein the latch assembly is remotely actuatable.

21A. The system of claim 20A, further comprising:

a rotating control head,
wherein the rotating control head is latched to the latch assembly when the first piston is in the latched position.

22A. The system of claim 21A, the latch assembly further comprising:

a housing forming a chamber,
wherein the first piston is positioned within the chamber.

23A. A comparator system for use with a latching assembly to latch a rotating control head, comprising:

a first fluid line operatively connected to the latch assembly for delivering a fluid to the latch assembly;
a first meter coupled to the first line, the first meter measuring a first fluid value for fluid delivered to the latch assembly;
a second fluid line operatively connected to the latch assembly for communicating the fluid from the latch assembly;
a second meter coupled to the second fluid line, the second meter measuring a second fluid value for fluid from the latch assembly;
a comparator configured to compare the measured first fluid value to the second fluid value; and

a display coupled to the comparator.

24A. A comparator system for use with a bearing assembly of a rotating control head, comprising:

a first fluid line operatively coupled to communicate fluid to a chamber defined by the bearing assembly;
a first meter coupled to the first fluid line, the first meter measuring a first fluid value;
a second fluid line operatively coupled to communicate fluid from the chamber defined by the bearing assembly;
a second meter coupled to the second fluid line, the second meter measuring a second fluid value;
a comparator, coupled to the first meter and the second meter, configured to compare the measured first fluid value to the measured second fluid value; and
a display coupled to the comparator.

25A. A method for comparing fluid to and from a latch assembly for latching a rotating control head, comprising the steps of:

delivering a fluid to a first side of a piston for moving the piston from a first position to a second position;
measuring a volume of fluid delivered to the first side of the piston producing a measured first fluid volume value;
communicating the fluid from a second side of the piston;
measuring a volume of fluid from the second side of the piston producing a measured second fluid volume value; and
comparing the measured first fluid volume value to a measured second fluid volume value.

26A. A method for use of a rotating control head having a bearing assembly, comprising the steps of:

positioning a chamber in the bearing assembly;
forming a first opening into the chamber;
forming a second opening into the chamber;
delivering a fluid to the first opening;
communicating the fluid from the second opening;
measuring a flow value of the fluid to the first opening;
measuring a flow value of the fluid from the second opening; and
comparing the measured flow value to the first opening to the measured flow value from the second opening.

[0111] Although the invention has been described in terms of preferred embodiments as set forth above, it should be understood that these embodiments are illustrative only and that the claims are not limited to those embodiments. Those skilled in the art will be able to make modifications and alternatives in view of the disclosure which are contemplated as falling within the scope of the appended claims. Each feature disclosed or illustrated in the present specification may be incorporated in the invention, whether alone or in any appropriate combination with any other feature disclosed or illustrated herein.

Claims

1. A thermal transfer system adapted for use with a rotating control head, comprising:

a first member movable relative to a second member;
one of the members having a thermal transfer surface;
a first seal positioned with one of the members for sealing the first member and the second member while the first member moves relative to the second member;
a thermal transfer fluid circulated with at least one of the members; and
the thermal transfer surface transferring thermal units through multiple passes of the thermal transfer fluid adjacent the thermal transfer surface.

2. The system of claim 1 further comprising:

the thermal transfer surface comprises a surface of a seal carrier;
the seal carrier disposed with one of the members; and
the first seal positioned with the seal carrier for sealing the first member with the second member while the first

member moves relative to the second member.

3. The system of claim 1 or 2, wherein the multiple passes comprise:

5 a spiral slot formed on one of the members adjacent the thermal transfer surface.

4. The system of claim 3 wherein the spiral slot provides a continuous flow passageway for the thermal transfer fluid.

5. The system of claim 1 further comprising:

10 at least one bearing provided between the first member and the second member.

6. The system of claim 5 wherein the thermal transfer fluid is pressurized and communicates with the bearing.

7. The system of claim 1 or 2 further comprising a port formed in one of the members or in the seal carrier to communicate with the first seal and to regulate the pressure of the fluid on the first seal.

8. The system of claim 1 or 2 further comprising a second seal positioned with one of the members or with the seal carrier and for sealing the first member and the second member.

9. The system of claim 8 further comprising a port formed in one of the members or in the seal carrier to communicate with the first seal and the second seal and to regulate the pressure of the fluid between the first seal and the second seal.

10. The system of claim 8 further comprising the first seal allowing a first predetermined flow of the thermal transfer fluid to pass by the first seal, and the second seal allowing a second predetermined flow of the thermal transfer fluid to pass by the second seal and the second predetermined flow is greater than the first predetermined flow.

11. The system of claim 8 wherein one of the seals allows flow of fluid at a first predetermined pressure and the other seal allows flow of fluid at a second predetermined pressure, the first predetermined pressure is higher than the second predetermined pressure.

12. A method for cooling a first radial seal in a rotating control head, comprising:

35 passing a cooling medium through the rotating control head with multiple passes adjacent to the first radial seal;
and
regulating the pressure of the cooling medium on the first radial seal.

13. The method of claim 12, further comprising the step of:

40 spiraling the cooling medium about the first radial seal in the rotating control head.

14. The method of claim 12 further comprising a second radial seal and further comprising the step of sealing between a first member that moves relative to the second member in the rotating control head with the first radial seal and the second radial seal.

15. The method of claim 14 further comprising the step of:

50 regulating the pressure between the first radial seal and the second radial seal and/or
allowing flow of fluid past the second radial seal at a higher rate than the flow of fluid past the first radial seal.




FIG. 1





FIG.3B





FIG.3A

FIG. 4B





FIG. 4A

FIG.5B





FIG.5A




FIG. 6




FIG. 7B

FIG. 7A




FIG.8




FIG.10
(PRIOR ART)






FIG.11








FIG. 14





FIG. 15A



70
FIG. 15B




FIG.15B





FIG. 17








FIG. 18

FIG. 19








FIG. 21

FIG. 22




FIG. 23







FIG. 24









EUROPEAN SEARCH REPORT

Application Number
EP 13 16 9036

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 4 143 881 A (BUNTING ALISON R) 13 March 1979 (1979-03-13) * column 5, lines 11, 22-29; figure 3 *	1-6	INV. E21B33/08 F16J15/32 F16K41/04
X	US 2 808 230 A (MCNEILL ROBERT C ET AL) 1 October 1957 (1957-10-01) * column 4, lines 47-48, 50-53, 55-57, 65-68; figures 1-3 * * column 5, lines 14-19, 39-45 *	1,2,5, 7-10,12, 14,15	
X	GB 2 394 741 A (WEATHERFORD LAMB [US]) 5 May 2004 (2004-05-05) * page 10, lines 10-18,25-28; figures 2-6 * * page 11, lines 3-5 * * page 16, lines 2-6 *	1-9,12, 14,15	
A	US 4 087 097 A (BOSSENS JACKY ET AL) 2 May 1978 (1978-05-02) * column 2, lines 16-48; figure 1 * * column 4, lines 2-51 * * column 5, lines 2,3,8-12 *	1-15	TECHNICAL FIELDS SEARCHED (IPC)
A	US 3 401 600 A (DEREK WOOD) 17 September 1968 (1968-09-17) * column 6, lines 26-31,35-39; figure 2 * * column 7, lines 5-11 *	1-15	E21B F16K F16J
A	US 6 244 359 B1 (BRIDGES CHARLES D [US] ET AL) 12 June 2001 (2001-06-12) * figure 5 *	1-15	
A	US 4 383 577 A (PRUITT ALFRED B [US]) 17 May 1983 (1983-05-17) * column 7, lines 24-30; figure 1 *	1-15	
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 26 June 2013	Examiner Georgescu, Mihnea
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

1
EPO FORM 1503 03.82 (P04C01)



EUROPEAN SEARCH REPORT

Application Number
EP 13 16 9036

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	US 3 481 610 A (SLATOR DAMON T ET AL) 2 December 1969 (1969-12-02) * column 1, lines 66-71; figure 1 * -----	1-15	
A	GB 2 019 921 A (REED TOOL CO) 7 November 1979 (1979-11-07) * page 1, lines 42-46 * -----	1-15	
A	US 4 757 584 A (PAV JOSEF [DE] ET AL) 19 July 1988 (1988-07-19) * column 2, lines 64-66; figure 1 * * column 3, lines 3-8,28-32,45-50 * -----	1-15	
			TECHNICAL FIELDS SEARCHED (IPC)
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 26 June 2013	Examiner Georgescu, Mihnea
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

1
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 13 16 9036

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-06-2013

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4143881	A	13-03-1979	NONE	
US 2808230	A	01-10-1957	NONE	
GB 2394741	A	05-05-2004	CA 2447196 A1	30-04-2004
			GB 2394741 A	05-05-2004
			US 2004084220 A1	06-05-2004
US 4087097	A	02-05-1978	AU 508502 B2	20-03-1980
			AU 2180677 A	10-08-1978
			BE 850560 A1	16-05-1977
			CA 1052833 A1	17-04-1979
			CH 598513 A5	28-04-1978
			DE 2704740 A1	11-08-1977
			ES 226186 U	01-04-1977
			FR 2356064 A1	20-01-1978
			GB 1514695 A	21-06-1978
			IT 1076238 B	27-04-1985
			JP S52101349 A	25-08-1977
			NL 7701118 A	11-08-1977
			SE 422488 B	08-03-1982
			SE 7701385 A	10-08-1977
			US 4087097 A	02-05-1978
US 3401600	A	17-09-1968	DE 1481515 A1	06-02-1969
			FR 1506041 A	15-12-1967
			GB 1152403 A	21-05-1969
			US 3401600 A	17-09-1968
US 6244359	B1	12-06-2001	AU 3550199 A	25-10-1999
			US 6244359 B1	12-06-2001
			WO 9951852 A1	14-10-1999
US 4383577	A	17-05-1983	NONE	
US 3481610	A	02-12-1969	NONE	
GB 2019921	A	07-11-1979	CA 1081686 A1	15-07-1980
			GB 2019921 A	07-11-1979
US 4757584	A	19-07-1988	BR 8603454 A	04-03-1987
			CA 1271352 A1	10-07-1990
			DE 3526283 A1	05-02-1987
			EP 0210388 A1	04-02-1987
			FI 862974 A	24-01-1987
			JP H0361042 B2	18-09-1991

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 13 16 9036

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on

The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-06-2013

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		JP S6224022 A	02-02-1987
		US 4757584 A	19-07-1988

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 28533602 A [0001]
- US 99598004 A [0001] [0062]
- US 5178215 A [0011] [0019]
- US 5224557 A [0011] [0019]
- US 5277249 A [0011] [0019]
- US 5662181 A [0012] [0019]
- US 5348107 A [0013] [0019]
- US 6554016 B [0014]
- US 6749172 B [0014]
- US 6227547 B [0017]
- US 10995980 B [0018] [0079]
- US 6227547 A [0019]
- US 6554016 A [0019]
- US 6749172 A [0019]
- US 6138774 A [0062]
- US 6263982 B [0062]
- US 6470975 B [0062]
- US 28153402 A [0062]
- US 20030106712 A1 [0062]