



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 72

(51) Int Cl.:
H02G 3/16 (2006.01) H02G 3/14 (2006.01)

(86) International application number:
PCT/JP2010/071120

(48) Corrigendum issued on:
15.01.2014 Bulletin 2014/03

(87) International publication number:
WO 2012/070146 (31.05.2012 Gazette 2012/22)

(43) Date of publication:
02.10.2013 Bulletin 2013/40

(21) Application number: **10859953.1**

(22) Date of filing: **26.11.2010**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR

(72) Inventor: **YUASA, Hiroaki**
Toyota-shi, Aichi-ken, 471-8571 (JP)

(71) Applicant: **TOYOTA JIDOSHA KABUSHIKI**
KAISHA
Toyota-shi, Aichi-ken, 471-8571 (JP)

(74) Representative: **Kuhnen & Wacker**
Patent- und Rechtsanwaltsbüro
Prinz-Ludwig-Straße 40A
85354 Freising (DE)

(54) **ELECTRICAL APPARATUS**

(57) An electrical apparatus that can prevent erroneous attachment of a fuse (41) is provided. A PCU includes a housing having a surface. A fuse storage space (40) is formed in the housing. The fuse storage space (40) communicates with a region outside of the housing through an opening formed at the surface. The PCU further includes a cover member (30) covering the opening,

and an overcurrent-protection fuse (41) located in the fuse storage space (40). The cover member (30) includes a cover body (35) closing the opening, and a projection section (31) projecting inward of the fuse storage space (40) relative to the cover body (35). The projection section (31) interferes with the fuse (41) when the fuse (41) is attached erroneously in the fuse storage space (40).

FIG.3

