



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 72

(51) Int Cl.:
B60R 19/48 (2006.01) B60K 11/04 (2006.01)

(86) International application number:
PCT/JP2010/073035

(48) Corrigendum issued on:
12.02.2014 Bulletin 2014/07

(87) International publication number:
WO 2012/086014 (28.06.2012 Gazette 2012/26)

(43) Date of publication:
30.10.2013 Bulletin 2013/44

(21) Application number: **10861030.4**

(22) Date of filing: **21.12.2010**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(72) Inventor: **ITO, Keita**
Toyota-shi, Aichi-ken, 471-8571 (JP)

(71) Applicant: **TOYOTA JIDOSHA KABUSHIKI KAISHA**
Toyota-shi, Aichi-ken, 471-8571 (JP)

(74) Representative: **Kuhnen & Wacker**
Patent- und Rechtsanwaltsbüro
Prinz-Ludwig-Straße 40A
85354 Freising (DE)

(54) **BUMPER MODULE**

(57) To suppress, even when an air guide rib is integrally formed on a body portion, variations in the reaction force on an impactor obtained in each site of the body portion.

A bumper module (10) includes: a body portion (16) that is positioned between a front bumper cover (12) and a heat exchanger (14) in a vehicle front-and-rear direction and is disposed extending in a vehicle width direction and the vehicle front-and-rear direction; plural longitudinal ribs (18) that are integrally formed on a lower surface of the body portion (16), extend toward a vehicle lower side, are disposed extending in the vehicle front-and-rear direction, and are lined up at intervals apart from each other in the vehicle width direction; and an air guide rib (20) that is integrally formed on an upper surface of the body portion (16), extends toward a vehicle upper side, guides cooling air from a vehicle front to the heat exchanger (14), and whose front end (20A) is unaligned in at least one direction of the vehicle width direction and the vehicle front-and-rear direction with respect to front ends (18A) of the plural longitudinal ribs (18).

FIG. 1

