

(19)



(11)

EP 2 658 042 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

30.10.2013 Bulletin 2013/44

(51) Int Cl.:

H01R 13/631 (2006.01)**H01R 13/53** (2006.01)**H01R 101/00** (2006.01)(21) Application number: **12165840.5**(22) Date of filing: **27.04.2012**

(84) Designated Contracting States:

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated Extension States:


BA ME• **Simonsohn, Thilo****81735 München (DE)**• **Hardt, Falk****83059 Kolbermoor (DE)**(74) Representative: **Patentanwaltskanzlei WILHELM & BECK****Prinzenstraße 13****80639 München (DE)**(71) Applicant: **Tyco Electronics Raychem GmbH****85521 Ottobrunn (DE)**

(72) Inventors:

• **Mikli, Norbert****85560 Ebersberg (DE)**(54) **Connector**

(57) The invention relates to a connector with a housing with a plug opening for receiving an electrical plug and with a cable opening for receiving a terminal of a conductor of a cable, whereby a middle axis of the plug opening and a middle axis of the cable opening are disposed in a predetermined angle, whereby the cable

opening leads in a chamber, whereby the plug opening passes over via an opening face in the chamber, whereby the chamber is arranged along a longitudinal axis of the cable opening, whereby the chamber extends opposite to the cable opening in the longitudinal axis of the cable opening over the opening face, providing a space beside the opening face for receiving a front part of the terminal.

**EP 2 658 042 A1**

Description

[0001] The invention refers to a connector according to claim 1.

[0002] In the state of the art different types of connectors are known. EP 1624537 B1 describes a connector with a predetermined position of a plug opening that is used for connecting the connector to a correspondent electrical contact. If a cable has a larger cross-sectional area and therefore a higher stiffness, it will be difficult to move the cable according to a predetermined position of the contact.

[0003] The object of the invention is to provide a cable connector with a simple design that simplifies an adjustment of the position of the plug opening relative to the cable for receiving an electrical plug or a second connector.

[0004] The object of the invention is solved by the connector according to claim 1. The connector according to claim 1 has the advantage that the plug opening can be moved relative to the cable. Therefore, it is possible to adjust the position of the housing to the position of a contact without the need to lift or flex the cable in larger amounts.

[0005] This advantage is attained by a chamber within the housing of the connector that is provided for receiving the terminal of a conductor of the cable, whereby the chamber extends opposite to the cable opening and the longitudinal axis of the cable opening over an opening face between the plug opening and the chamber providing space beside the opening face for receiving a front part of the terminal. Thus it is possible to move the housing relative to the cable.

[0006] The proposed connector allows a simple adjustment of the position of the plug opening of the housing relative to the cable to receive an electrical plug or a second connector without the need to move the cable.

[0007] Further embodiments of the invention are disclosed in the dependent claims.

[0008] In one embodiment, a simple terminal is provided that can be used for connecting an electrical plug or a second connector in different positions of the housing. This advantage is attained by a terminal that comprises a hole for fixing an electrical contact, whereby the hole is embodied such that different fixing positions of the electric contact along the terminal are possible. A simple embodiment may be a long hole. However, also a series of holes can be arranged in the terminal. The long hole has the advantage that the position of the housing can be used without depending on the predetermined positions as it is the case using several holes in a terminal plate.

[0009] In a further embodiment, one type of cable can be used for different positions of the housing relative to the cable. This advantage is attained by an adaptor section that is fixed to a cable jacket, whereby the adaptor section is at least partially arranged in the cable opening closing the cable opening. The adaptor section has a length that allows different insertion depths of the cable

in the cable opening of the housing providing different positions of the plug opening relative to the cable. The adaptor section and the cable opening are embodied in such a way as to seal the introduction of the cable in the connector housing. Therefore, the housing can be positioned in several positions relative to the cable without worsening the sealing and electrical stress control. Furthermore, the needed minimum of the distance between stress cone of adapter and Faraday Cage of the housing is guaranteed.

[0010] In a further embodiment, the connector provides a large distance within which the housing can be moved relative to the cable, wherein the connector has a small size. This advantage is attained by a chamber that protrudes opposite to the cable opening from a shape of the housing. This means that the connector housing itself has a small size with a projecting part for the chamber. Therefore, the chamber extends a large distance from the opening face providing a large distance for moving the terminal and the cable within the housing. As not the whole shape of the connector is enlarged but only a part of the connector projects from the shape that provides the space for the chamber the relative increase of the size of the connector is small. Therefore, only some more material is necessary. This reduces the increase of the costs and the weight of the connector. In a further embodiment, the chamber is covered by an electrical conductive layer forming a Faraday cage. This provides a protection against electrical flashover and improves electrical stress control.

[0011] In a further embodiment, the electrical contact between the terminal and the electrical contact is improved. This advantage is attained by a contact plate that is arranged in the chamber laying on the terminal at the side of the plug opening being in contact with the electrical contact. Thus it is possible to increase a contact surface between the electrical contact and the terminal.

[0012] In a further embodiment, the contact plate has a rectangular shape according to a shape of the terminal and comprises several bores that are arranged for providing several fixing positions of the electrical contact.

[0013] In a further embodiment, the terminal is embodied as a barrel with a palm, whereby the barrel is connected to the conductor of the cable.

[0014] In a further embodiment the contact plate comprises a bar for aligning the contact plate along a longitudinal axis of the terminal. Thus improves the mounting process.

[0015] In a further embodiment a further bar of the contact plate protrudes from a long hole of the terminal, whereby a front face of the further bar is in contact with a further contact of the further plug, and wherein a side face of the contact plate is in contact with the contact. This increases the contact area to the further contact and to the electrical contact. As a result more power can be guided through the terminal without damaging the palm.

[0016] In a further embodiment a hole of the further plate is arranged in an asymmetrical position referring to

a longitudinal extension of the further plate. This embodiment allows the use of a long further plate although the distance between the electrical contact and a wall of the chamber is small.

[0017] In a further embodiment a contact face of the terminal and/or the plate comprises an uneven surface or a coating for improving the electrical conductivity.

[0018] The invention will now be explained in more detail with the reference to the figures, in which:

Figure 1 shows a schematic view of a connector, whereby the housing is in a first position relative to the cable,

Figure 2 shows the connector of figure 1, whereby the housing is in a second position relative to the cable and the cable lug to adjust a second position of a second plug,

Figure 3 shows a top view of the connector of figure 1,

Figure 4 shows a schematic view of the terminal,

Figure 5 shows a top view on a contact plate,

Figure 6 shows a side view of the terminal with the contact plate,

Figures 7 to 9 show different positions for connecting two cables using two connectors that have moveable housings, and

Figures 10 to 12 show different positions of connecting a connector to an electrical contact.

Figure 13 shows a further embodiment of the connector.

Figure 14 shows a further embodiment of the electrical contact.

Figure 15 shows a further embodiment of a palm.

Figures 16 to 19 show further embodiments of a contact plate.

Figures 20 to 24 show another embodiment of a contact plate.

Figures 25 to 27 show a further embodiment of a contact plate.

Figure 28 shows a further embodiment of an electrical contact.

Figure 29 shows a further embodiment of the further plate of Figure 18.

Figure 30 shows a further embodiment of the further plate of Figure 19.

[0019] Figure 1 shows a schematic view of a cable connector 1 that comprises a housing 2 that is connected to a cable 9.

[0020] The housing 2 comprises a cable section 10 for introducing a terminal 5 of the cable 9. The terminal 5 may be embodied as a terminal lug. Furthermore, the housing 2 comprises a contact section 11 for receiving a plug 53 that should be connected with a conductor 26 of the cable 9. A longitudinal axis 17 of the contact section 11 is disposed in a predetermined angle referring to a second longitudinal axis 46 of the cable section 10, in this embodiment 90 degrees, disposing the connector 1 as a t-connector. Depending on the used embodiment, the angle between the longitudinal axis of the cable 9 and the longitudinal axis of the housing 2 may be different, for example between 10 degrees and 170 degrees defining a kind of elbow housing.

[0021] The cable section 10 comprises a cable opening 4 that is arranged along the longitudinal second axis 46 of the cable section 10 protruding from the contact section 11. A cross-section of the cable opening 4 may decrease within the contact section 11 to a smaller cross-section. Especially the shape of the cross-section may change from a circular cross-section in the cable section 10 to a rectangular cross-section in the contact section 11. The changeover between the circular cross-section and the rectangular cross-section is performed within a transforming section 12 that is arranged in the contact section 11 of the housing 2. The cable opening 4 emerges in a chamber 6 that is arranged in contact section 11 of the housing 2. The chamber 6 extends along the longitudinal axis of the cable section 10. The chamber 6 is connected to a plug opening 3 via an opening face 14. The plug opening 3 is provided for receiving a plug 53 with a contact 16 that has to be connected to the conductor 26 of the cable 9.

[0022] Opposite to the plug opening 3 a mounting opening 13 is provided in the contact section 10 that is also connected to the chamber 6. The mounting chamber 13 is closed with a further plug 15, preferably a molded part made from epoxy resin with metal inserts depending on the voltage level and a cap. For voltages up to 10 kV or in some cases up to 20 kV, a specially designed cap is used. An electrical contact 16 in the shape of a threaded pin is arranged in the contact section 11, whereby the electrical contact 16 extends from the mounting chamber 13 via the chamber 6 to the plug opening 3 that is a middle axis of the plug opening 3. The electrical contact 16 is connected to a contact of the plug. The electrical contact 16 may be embodied as a bushing contact. The electrical contact 16 is arranged in the axis 17 of the plug opening 3. The chamber 6 extends from the transforming section 12 to an opposite side in an area that is arranged beside the opening face 14. The chamber 6 extends over the opening face 14 to a side face 18 of the housing 2. De-

pending on the used embodiment, the chamber 6 ends within the housing 2 and provides space 19 beside the opening face 14 opposite to the cable section 10. Depending on the used embodiment, the space 19 extends along the second axis beside the opening face 14, a length of about 200mm, preferably at least 5mm.

[0023] In the shown embodiment, the chamber 6 extends in a projecting part 20 of the housing 2. The projecting part 20 provides a chamber 6 that extends a larger distance referring to the axis 17 of the plug opening 3 compared to an embodiment that does not provide a projecting part 20. The small shape of the housing 2 which is achieved by using a projecting part 20 has the advantage that the size of the connector is small. In comparison with a larger connector, material is saved and the connector is cheaper.

[0024] The cable 9 comprises an outer jacket 21 that is removed from an end section 22 of the cable 9. The outer jacket 21 covers a shielding layer 23 that is folded back in a contact section 24. An adapter 30 is arranged in the cable section. The adapter 30 comprises for example a conductive electrical stress cone 25 and an outer insulating portion 50 in the shape of a cylindrical cover. In the shown embodiment, only one conductor 26 is arranged that is covered by an insulating layer 52. The conductor 26 with the insulating layer 52 is covered by a conductive cable shielding 51. The cable shielding 51 ends in the stress cone 25. Depending on the used embodiment, several conductors may be arranged in a cable 9. A part of the jacket 21 and the folded back shielding layer 23 and also a part of the insulating layer 52 is enclosed in the adapter 30. The adapter 30 is made of an insulating material and comprises preferably a stress cone 25 for reducing electrical stress. The adapter 30 is introduced in the cable opening 4, whereby the material of the cable section 10 and the material of the adapter 30 are constructed in that way that the cable opening 4 is closed by the adapter section 30. The cable section 10 of the housing 2 is made of an elastic and insulating material, for example silicon rubber. The adapter 30 is for example also made of silicon rubber.

[0025] An end-part of the conductor 26 is free from the insulating layer 52 and connected to a terminal 5. The terminal 5 is for example embodied as a lug with a barrel 28 and a palm 29. Depending on the used embodiment, the terminal 5 can also be embodied in other shapes. The conductor 26 is mechanically fixed to the barrel 28 and electrically connected to the barrel 28 and the palm 29.

[0026] The palm 29 extends in the chamber 6 and lays with a front end 31 at an inner face 47 of the projecting part 20. This means that the position of the contact section 11 is at a nearest position referring to the position of the cable 9. The electrical contact 16 is mechanically fixed i.e. by a nut 32 to the palm 29. A contact plate 33 may be arranged between the palm 29 and the plug opening 3. Therefore, the electrical contact 16 is mechanically and electrically connected to the palm 29. In the shown

embodiment, the palm 29 is embodied as a plate and comprises a long hole 34 through that the electrical contact 16 is guided. An inner section 48 of the cable opening 4 and the chamber 6 are covered by a conductive layer 35 providing a Faraday cage.

[0027] A plug 53 is introduced in the plug opening 3. The plug 53 comprises an insulating part 56 with a cone shape that is fit in the plug opening 3. In the insulating part 56 a further electrical contact 54 is arranged. The further electrical contact 54 is constructed as a pin with a sleeve 57 at its end with or without a thread. The sleeve 57 receives the electrical contact 16. The electrical contact 16 is fixed to or at least in contact with the further electrical contact 54. The electrical contact 16 may be constructed as a pin with a thread. In this embodiment, the electrical contact 16 is screwed to the further electrical contact 54. In a simple embodiment the electrical contact 16 is only pushed in the sleeve 57 of the further contact 54 and connected by a press fit connection with the further contact 54. The plug 53 comprises electrical lines that are connected to the further contact 54, but not shown in figure 1.

[0028] Figure 2 shows the connector 1 of figure 1, whereby the contact section 11 is arranged in a furthest position referring to the cable 9. The difference between the two positions of figure 1 and figure 2 are shown in figure 2 by means of an arrow A. Due to the chamber 6 and due to the terminal 27 with the possibility to fix the electrical contact 16 in several different positions it is possible to change the position of the plug opening 3 referring to the position of the cable 9 and the palm 29. Therefore, it is possible to adjust the position of the plug opening 3 depending on the position of the electrical plug.

[0029] The adapter 30 overlaps in Fig. 1 and 2 with the conductive layer 35 of the inner section 48. Preferably the adapter 30 is constructed to provide the necessary electrical functions for example the stress control and the minimum distance of stress cone to the end of conductive layer 35 of the Faraday cage.

[0030] Figure 3 shows a top view of the connector 1 of figure 2. As can be seen, the housing 2 has a small shape, whereby a projecting part 20 projects the shape of the housing 2.

[0031] Figure 4 depicts the terminal 5 in the shape of the barrel 28 and the palm 29, whereby the palm 29 comprises a long hole 34, which is shown in more detail.

[0032] Figure 5 depicts a preferred embodiment of the contact plate 33 comprising several bores 36. Instead of the embodiment of the contact plate 33 shown in figure 5, the contact plate 33 can also be embodied as a simple ring plate as shown in figures 1 and 2.

[0033] Figure 6 shows the contact plate 33 disposed on the palm 29 and between the palm 29 and the plug 53. In this embodiment, the electrical contact 16 can be connected in three different positions that are determined by the bores 36 of the contact plate 33. Another plate 60 is arranged between the palm 29 and the nut 32.

[0034] Figure 7 shows a connector 1 as described in

figures 1 and 2 and a second connector 40 that is embodied in the same structure as the connector 1 but comprises instead of a contact section with a plug opening 3 a second contact section 41 with a plug 42. The second contact section 42 of the second connector 40 is moveable referring to a second cable 43 in the same way as the contact section 11 referring to the cable 9. The plug 42 comprises a hole 44 for receiving the contact 16 of the connector 1. In the situation shown in Figure 7, the cables 9, 43 are fixed and cannot be pulled nearer to the other cable.

[0035] Figure 8 shows a solution for connecting the cables 9, 43. The connector 1 and the second connector 40 are moved relative to their cables 9, 43 as depicted by arrows. Then, as shown in figure 9, the two connectors can be mounted by bending the cables 9, 43. Figure 9 shows further steps for connecting the electrical contacts of the first and the second connector.

[0036] Figures 10 to 12 show different steps for connecting the connector 1 with a fixed contact 44 that is part of a substation 45. Figure 11 shows that the connector 1 is moved up relative to the cable 9. Figure 12 shows that the connector 1 is mounted to the fixed contact by bending the cable 9.

[0037] Figure 13 shows a partial view of a further embodiment of the connector with an electrical contact 16 that comprises a contact plate 33 that is fixed to the electrical contact 16. The contact comprises a thread 55 at a first end. At the first end, the nut 32 is screwed onto the thread 55. The opposite end of the electrical contact 16 is received by the further contact 54 of the plug 53.

[0038] Figure 14 shows the electrical contact 16 that is embodied as a pin with the fixed contact plate 33. The contact plate 33 may be one piece with the electrical contact 16 or in a further fixed by a thread with the pin of the electrical contact.

[0039] Figure 15 shows a third embodiment of a barrel 28 and a palm 29, whereby the palm 29 comprises two long holes 34. This embodiment has the advantage that it is possible to adjust the position of the cable referring to a further contact within the distance of the two long holes 34. Furthermore, a contact area between the palm 29 and a further contact may be larger since a larger contact area is available between the palm 29 and the contact plate 33.

[0040] Figure 16 shows a partial view of a third embodiment, whereby a plug 53 with a further contact 54 that is constructed as a sleeve with a thread on its inner face is arranged within the plug opening of the housing that is not depicted. An electrical contact 16 embodied as a threaded pin is screwed in the further contact 54. Between the palm 29 and a contact face 58 of the further contact 54 a further plate 59 is arranged. Opposite to the further plate 59 the nut 32 is screwed on the electrical contact 16 fixing the electrical contact 16 to the palm 29. Between the nut 32 and the palm 29, another plate 60 is arranged. The another plate 60 may have the shape of a ring plate.

[0041] The further plate 59 comprises two parallel bars 61 that protrude in the long hole 34. The bars 61 are used for aligning the further plate 59 along a longitudinal axis of the palm 29.

[0042] Figure 17 depicts a cross-sectional view A-A of figure 16. In this view it is shown that the bars 61 are arranged in parallel and that the bars 61 have a length that is a bit shorter than the width of the long hole 34. Depending on the used embodiment, only one bar 61 may be sufficient to align the further plate 59 along the longitudinal axis of the long hole 34. The further plate 59 is depicted with a dashed line and has the same width as the palm 29. The further plate 59 has a basically rectangular shape. The contact face 58 has a ring-shape that encircles the circular cross-section of the first contact 16. The further plate 59 increases the contact area between the contact face 58 and the palm 29. As a result of the long hole 34 the contact area between the contact face 58 and the palm 29 is reduced without using the further plate 59. The further plate increases the contact area so that a high current can be guided via the palm 29 and the contact 16 to the further contact 54.

[0043] Figure 18 shows three different views of the further contact plate 59 with the bars 61 and the hole 62. Figure 19 shows a further embodiment of the further contact plate 59, whereby the bars 61 are arranged at opposite sides of the further plate 59, encompassing in a mounted position opposite long sides of the palm 29. Also these bars 61 can be used for aligning the further plate 59.

[0044] Figure 20 shows another embodiment with a fourth plate 63 that is arranged between the contact face 58 of the further contact 54 and the nut 32 or a further plate 60 that is arranged between the nut 32 and the fourth plate 63. The fourth plate 63 comprises further bars 64 that protrude through the long hole 34 of the palm 29.

[0045] Figure 21 shows a cross-sectional view A-A of figure 20, showing the cross-sectional area of the further bars 64 that protrude the long-hole 34 as a lined area.

[0046] Figure 22 shows a top-view on the fourth plate 63 with the further bars 64.

[0047] Figure 23 shows a side-view of the fourth plate 63.

[0048] Figure 24 shows the perspective view of the fourth plate 64 that comprises a rectangular base plate 65 with two further bars 64 that are arranged on opposite sides of the hole 62. The further bars 64 comprise inner faces 66 that have a part circular shape as the circular shape of the hole 62 for receiving the contact 16.

[0049] Figure 25 shows a top view of a further embodiment of the fourth plate 63 that comprises at opposite sides two guiding bars 61 that encompass in a mounted position long sides of the palm 29, as shown in figure 26. The guiding bars 66 increase the contact face between the fourth plate 63 and the palm 29.

[0050] Figure 27 shows a perspective view of the fourth plate 63 of Figure 25.

[0051] Figure 28 shows a third embodiment, whereby the electrical contact 16 is embodied as a pin with a plate 33 as shown in figure 14. The electrical contact 16 comprises a thread 55 and is guided through the long hole 34 of the palm 29. The contact 16 is fixed to the palm 29 by a nut 32 that comprises studs 67. The studs 67 protrude in the long hole 34 and prevent a rotation of the nut 32. In this embodiment the electrical contact 16 is fixed in the palm 29 by screwing the electrical contact 16 in the nut 32.

[0052] The faces of the palm 29, the contact plate 33, the further plates 59, 63 and the contact face 58 that are used as electrical contact areas for transmitting current from one part to another comprise an unevenness surface that improves the electrical contact between the contact surfaces. The unevenness may be attained by scratches or fractions or heights. The uneven surface provides a larger area for increasing the contact face conductivity. In a further embodiment, additionally or instead of the uneven surface, coatings, for example made of silver, may be used to improve the surface conductivity between the parts.

[0053] Figure 29 shows a further embodiment of the further plate 59 of Figure 18. In this embodiment, the hole 62 is not arranged in the middle between the two bars 61, which is defined by a middle axis 70. Similar to the principle shown in figure 15 there could be more than one hole 62 or a long hole.

[0054] Figure 30 shows a further embodiment of the further plate 59 of Figure 19, whereby the hole 62 is not arranged in the middle which is defined by the middle axis. The asymmetrical position of the hole 62 has the advantage that a relatively long further plate 59 can be used although the distance of the mounted contact 16 referring to a side wall of the chamber 6 is small. Thus, the contact face is increased.

Claims

1. Connector (1, 40) with a housing (2) with a plug opening (3) for receiving an electrical plug (53) or a second connector (40), with a cable opening (4) for receiving a terminal (5) of a conductor (26) of a cable (9), whereby a middle axis (17) of the plug opening (3) and a middle axis (46) of the cable opening (4) are disposed in a predetermined angle, whereby the cable opening (4) leads in a chamber (6), whereby the plug opening (3) passes over via an opening face (14) in the chamber (6), whereby the chamber (6) is arranged along a longitudinal axis of the cable opening (4), whereby the chamber (6) extends opposite to the cable opening (4) in the longitudinal axis (46) of the cable opening (4) over the opening face (14) providing a space (19) beside the opening face (14) for receiving a front part of the terminal (5, 29).

2. Connector according to claim 1, whereby the cham-

ber (6) protrudes opposite to the cable opening (4) from a shape of the housing (2) providing a projection part (20).

3. Connector according to claim 1 or 2, whereby the terminal (5, 28, 29) is arranged in the chamber (6), whereby the terminal (5, 28, 29) comprises at least one hole (34, 36) for guiding an electrical contact (16), whereby the hole (34, 36) is embodied such that different positions of the electrical contact (16) are provided along the terminal (5, 28, 29).

4. Connector according to claim 3, whereby at least one hole is embodied as a long hole (34), whereby the long hole (34) allows different fixing positions of the electrical contact (16) along the terminal (5, 28, 29).

5. Connector according to claim 3 or 4, whereby the cable (9) comprises an adapter (30) that encompasses a cable jacket (21), whereby the adapter (30) is at least partially arranged in the cable opening (4) closing the cable opening (4), whereby the adapter (30) has a length that allows different insertion depths of the cable in the cable opening (4) of the housing (2).

6. Connector according to any one of the preceding claims, whereby the chamber (6) is covered by an electrical conductive layer (35) forming a Faraday cage.

7. Connector according to any one of the claims 3 to 6, whereby a contact plate (39) is arranged in the chamber (6) lying on the terminal (5, 28, 29) adjacent to an opening face (14) of the plug opening (3).

8. Connector according to claim 3, whereby the contact plate (33) has a rectangular shape according to a shape of the terminal and comprises more than one bore (36), or long holes (34) or any other kind of opening that are arranged for providing several positions of the electrical contact (16).

9. Connector according to one of the preceding claims, whereby the terminal (5) is embodied as a barrel (28) with a palm (29), whereby the barrel (28) is connected to the conductor (26) of the cable (9).

10. Connector according to one of the preceding claims, whereby the contact element (16) is a contact pin with a fixed contact plate (33).

11. Connector according to one of claims 7 to 10, whereby the contact plate (59) comprises a bar (61) for aligning the contact plate (59) along a longitudinal axis of the terminal (29).

12. Connector according to one of claims 7 to 11, whereby a further bar (64) of the contact plate (63) protrudes from a long hole (34) of the terminal (5, 29), whereby a front face of the further bar (64) is in contact with a further contact (54) of the further plug (53), and wherein a side face (66) of the contact plate (63) is in contact with the contact (16). 5
13. Connector according to one of claims 7 to 12, wherein one or more holes (62) of the further plate (52) are arranged in an asymmetrical position referring to a longitudinal extension of the further plate (59). 10
14. Connector according to one of the preceding claims, whereby a contact face of the terminal and/or the plate (33, 59, 63) comprise an uneven surface or a coating for improving the electrical conductivity. 15
15. Connector according to one of the preceding claims, whereby the chamber (6) extends opposite to the cable opening (4) in the longitudinal axis (46) of the cable opening (4) over the opening face (14) at least 5mm. 20

25

30

35

40

45

50

55






Fig. 1

Fig. 2






Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29




Fig. 30



EUROPEAN SEARCH REPORT

Application Number
EP 12 16 5840

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	EP 0 087 267 A1 (Y S SECURITIES LTD [GB]) 31 August 1983 (1983-08-31) * figures 1-3 * -----	1-3,6,7,9,10,14,15	INV. H01R13/631 H01R13/53 ADD. H01R101/00
			TECHNICAL FIELDS SEARCHED (IPC) H01R
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 5 September 2012	Examiner Esmiol, Marc-Olivier
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

1
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 12 16 5840

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

05-09-2012

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0087267	A1	31-08-1983	AU 562777 B2	18-06-1987
			AU 1160283 A	25-08-1983
			DE 3368819 D1	05-02-1987
			DK 67283 A	21-08-1983
			EP 0087267 A1	31-08-1983
			GB 2116381 A	21-09-1983
			JP 58194265 A	12-11-1983
			MY 8700674 A	31-12-1987
			SG 51287 G	04-03-1988
			ZA 8301039 D	30-11-1983

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- EP 1624537 B1 [0002]