



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 72

(51) Int Cl.:
B60S 1/46 (2006.01)

(86) International application number:
PCT/JP2011/080337

(48) Corrigendum issued on:
12.02.2014 Bulletin 2014/07

(87) International publication number:
WO 2013/098979 (04.07.2013 Gazette 2013/27)

(43) Date of publication:
11.12.2013 Bulletin 2013/50

(21) Application number: **11864129.9**

(22) Date of filing: **27.12.2011**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(72) Inventors:
• **YASUMOTO, Ryo**
Toyota-shi, Aichi-ken, 471-8571 (JP)
• **KUNIYASU, Susumu**
Toyota-shi, Aichi-ken, 471-8571 (JP)

(71) Applicant: **TOYOTA JIDOSHA KABUSHIKI KAISHA**
Toyota-shi, Aichi-ken, 471-8571 (JP)

(74) Representative: **Kuhnen & Wacker**
Patent- und Rechtsanwaltsbüro
Prinz-Ludwig-Straße 40A
85354 Freising (DE)

(54) **VEHICLE WIPER DEVICE**

(57) Cleaning liquid is easily prevented from adhering to a main wiping side of a windshield glass when a main wiping side wiper, that rotates reciprocally, moves to a reciprocal rotation inbound side. Cleaning liquid (W3) is jetted-out from a jetting-out opening (256) of a jetting-

out nozzle (250), but the cleaning liquid (W3) does not stick to a reciprocal rotation outbound side (S1) of a driver's seat side wiper (110). Accordingly, cleaning liquid W does not remain without being wiped-off at a driver's seat side of a windshield glass 50.

