## 

## (11) **EP 2 672 093 A8**

## (12) CORRECTED EUROPEAN PATENT APPLICATION

published in accordance with Art. 153(4) EPC

(15) Correction information:

Corrected version no 1 (W1 A1)

Corrections, see

Bibliography INID code(s) 72

(48) Corrigendum issued on:12.03.2014 Bulletin 2014/11

(43) Date of publication: 11.12.2013 Bulletin 2013/50

(21) Application number: 11857567.9

(22) Date of filing: 01.02.2011

(51) Int Cl.: **F02D 41/04** (2006.01)

(86) International application number: PCT/JP2011/052041

(87) International publication number: WO 2012/104998 (09.08.2012 Gazette 2012/32)

(84) Designated Contracting States:

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(71) Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA
Toyota-shi, Aichi-ken, 471-8571 (JP)

- (72) Inventor: TANAKA, Satoru
  Toyota-shi, Aichi-ken, 471-8571 (JP)
- (74) Representative: Kuhnen & Wacker Patent- und Rechtsanwaltsbüro Prinz-Ludwig-Straße 40A 85354 Freising (DE)

## (54) CONTROL DEVICE FOR INTERNAL COMBUSTION ENGINE

(57) A control device calculates a maximum amount of increase in an intake pipe pressure in a  $\Delta t$  obtained by moving a throttle to an opening side at a maximum speed, and calculates a maximum amount of decrease in an intake pipe pressure in the  $\Delta t$  obtained by moving the throttle to a closing side at a maximum speed. Then, command values for each of a VVT and a WGV are de-

termined such that an amount of change in an intake pipe pressure in the  $\Delta t$  required to achieve a target intake air amount falls within a range from the maximum amount of decrease to the maximum amount of increase. Then, a target opening for the throttle for a purpose of achieving the target intake air amount is calculated on the basis of command values that have been determined for the VVT and the WGV.




Fig. 3