

(19)



(11)

EP 2 737 813 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
04.06.2014 Bulletin 2014/23

(51) Int Cl.:
A24C 5/44 (2006.01)

(21) Application number: **13194374.8**

(22) Date of filing: **26.11.2013**

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**
Designated Extension States:
BA ME

(71) Applicant: **Prevost, David**
Portland, OR 97218 (US)

(72) Inventor: **Prevost, David**
Portland, OR 97218 (US)

(74) Representative: **Hoefer & Partner**
Pilgersheimer Straße 20
81543 München (DE)


(30) Priority: **03.12.2012 US 201213692875**

(54) Cigarette rolling and forming devices

(57) Embodiments provide cigarette rolling and forming devices that include parallel cylinders extending between a pair of support plates, and a looped belt trained therearound. One cylinder is moveable relative to the other via a pair of curvilinear slots, and the device is configured for alternately receiving and compressing loose tobacco into a tobacco rod with the belt. In some devices, a nozzle is provided to allow longitudinal displacement

of the formed tobacco rod into a pre-formed cigarette tube, and some devices include a pushing device to effect this longitudinal displacement. Some devices include a support trough disposed to prevent sections of the belt from contacting each other, and some devices include a clamping device configured to clamp a pre-formed cigarette tube on the nozzle to prevent its dislodging during use.

Fig. 1



EP 2 737 813 A1

Description

Cross Reference to Related Applications

[0001] The present application is a Continuation-in-Part of and claims priority to U.S. Patent Application No. 12/136,650, filed June 10, 2008, entitled "CIGARETTE ROLLING AND FORMING DEVICES," the disclosure of which is hereby incorporated by reference in its entirety.

Technical Field

[0002] This disclosure relates generally to devices for making rolled cigarettes, and more particularly to hand-operated devices for making rolled cigarettes one at a time.

Background

[0003] Some cigarette smokers prefer the process of making their own cigarettes to buying pre-rolled and pre-packaged cigarettes. For example, the individual components of a cigarette, such as tobacco and cigarette papers, when purchased in bulk, are often less expensive per cigarette than pre-made cigarettes. In addition, some people find enjoyment in making their own cigarettes, and may even consider cigarette-rolling to be a challenging endeavor in which to demonstrate skill.

[0004] One way to make cigarettes individually and manually is to place an amount of loose tobacco in a cigarette paper and roll it between one's fingers. However, this approach is limited in that it is somewhat difficult to produce a cigarette of uniform shape and fill, and outside influences (for example, bad weather in an outdoor setting, or jostling from other people in a crowded area) may increase the difficulty. Relatively small and simple devices that allow a user to make cigarettes are available; however, such devices small enough to fit comfortably in one's hand or on a table may not be capable of rolling consistently a high-quality cigarette. Other devices, though capable of improved function, may be too large to be carried easily in a pocket or handbag, if they may be carried at all.

[0005] Rolling devices conventionally include a framework in which two roughly parallel rollers are closely arranged, and in which a looped belt is configured to encompass the rollers, with enough slack to form a groove or recess between the rollers in which loose tobacco may be formed into a cylindrical shape. Usually, at least one of the rollers is movable between two positions: an "open" configuration in which the rollers have their greatest separation, so that a broad, shallow recess in the belt between the rollers is formed, into which loose tobacco may be placed, and a "closed" configuration in which the rollers have their least separation, so that the belt forms a narrower and deeper recess, in which the loose tobacco may be compressed or shaped by movement of the belt over the rollers. In such devices, a piece of cigarette pa-

per may then be fed between the rollers and rolled around the compressed tobacco to form a finished cigarette.

[0006] Different constructions are used to enable movement of the rollers relative to each other. In some devices, the ends of the movable roller may be journaled in a slot that defines a range of movement of the roller (relative to the other roller), as the ends are slid along the slot. In some devices, the moveable roller is mounted on a pair of hinged arms that may swing the moveable roller away from, or toward, the other roller. Some devices may include two pairs of arms on a central hinge, so that the rollers may be moved away from, or toward, each other by opening and closing the hinge. Such devices, however, are prone to a number of difficulties in use, such as in manipulating the looped belt to form a cylinder of tobacco having a cigarette paper around it, rolling the rollers or otherwise smoothly moving the belt over the rollers to compress the tobacco, accumulating tobacco debris within the slots or openings holding the ends of the rollers, and binding of the looped belt as it passes through the device, and so forth. Each of these difficulties may result in a substandard manually-rolled cigarette, user frustration, mechanical failure, and so forth.

[0007] Also, such devices typically do not provide a mechanism by which a compressed cylinder of tobacco may be inserted into a pre-formed cigarette tube, for example if a user would prefer to use a pre-formed cigarette tube instead of a leaf of cigarette paper. Pre-formed tubes are commercially available, some of which include filter tips, which may be difficult to incorporate into a cigarette rolling device. Instead, different types of injector machines are available, which operate by compressing loose tobacco in a chamber, and then forcing the compressed tobacco into a pre-formed tube. Such machines are generally too large and/or mechanically complex to allow portability.

Brief Description of the Drawings

[0008] Embodiments will be readily understood by the following detailed description in conjunction with the accompanying drawings. Embodiments are illustrated by way of example and not by way of limitation in the figures of the accompanying drawings.

Fig. 1 is a top perspective view of an embodiment of a cigarette rolling device;

Fig. 2 is an elevation view of a proximal support plate of the cigarette rolling device of **Fig. 1**;

Fig. 3 is an elevation view of a guard plate of the device of **Fig. 1**, shown in relation to the support plate of **Fig. 2**;

Fig. 4 is a side elevation view of the proximal end of the device of **Fig. 1**, with the device in an open configuration;

Fig. 5 is a side elevation view of the proximal end of the device of **Fig. 1**, with the device in a closed configuration;

Fig. 6 is a side elevation view of the distal end of the device of **Fig. 1**, with the device in a closed configuration;

Fig. 7 is a top view of the device of **Fig. 1** in a closed position;

Fig. 8 is a bottom view of the device of **Fig. 1**;

Fig. 9 is a perspective view of a base and a trough;

Figs. 10A-10C are three perspective views of a distal support plate having a recess for a clamping device (**Fig. 10A**), the distal support plate of **Fig. 10A** with the clamping device in an open position (**Fig. 10B**), and the distal support plate of **Fig. 10A** with the clamping device in closed position (**Fig. 10C**);

Figs. 11A and 11 B are a partial cutaway view of the device of **Fig. 1**, showing a close-up side view of the pushing device, with the translatable cylinder in a closed position (**Fig. 11A**), and a partial cutaway view of the device of **Fig. 1**, showing a close-up side view of the pushing device, with the translatable cylinder in an open position (**Fig. 11 B**); all in accordance with various embodiments.

Detailed Description of Disclosed Embodiments

[0009] In the following detailed description, reference is made to the accompanying drawings which form a part hereof, and in which are shown by way of illustration embodiments that may be practiced. It is to be understood that other embodiments may be utilized and structural or logical changes may be made without departing from the scope. Therefore, the following detailed description is not to be taken in a limiting sense, and the scope of embodiments is defined by the appended claims and their equivalents.

[0010] Various operations may be described as multiple discrete operations in turn, in a manner that may be helpful in understanding embodiments; however, the order of description should not be construed to imply that these operations are order dependent.

[0011] The description may use perspective-based descriptions such as up/down, back/front, and top/bottom. Such descriptions are merely used to facilitate the discussion and are not intended to restrict the application of disclosed embodiments.

[0012] The terms "coupled" and "connected," along with their derivatives, may be used. It should be understood that these terms are not intended as synonyms for each other. Rather, in particular embodiments, "connected" may be used to indicate that two or more elements are in direct physical or electrical contact with each other. "Coupled" may mean that two or more elements are in direct physical or electrical contact. However, "coupled" may also mean that two or more elements are not in direct contact with each other, but yet still cooperate or interact with each other.

[0013] For the purposes of the description, a phrase in the form "A/B" or in the form "A and/or B" means (A), (B), or (A and B). For the purposes of the description, a phrase

in the form "at least one of A, B, and C" means (A), (B), (C), (A and B), (A and C), (B and C), or (A, B and C). For the purposes of the description, a phrase in the form "(A)B" means (B) or (AB) that is, A is an optional element.

[0014] The description may use the terms "embodiment" or "embodiments," which may each refer to one or more of the same or different embodiments. Furthermore, the terms "comprising," "including," "having," and the like, as used with respect to embodiments, are synonymous.

[0015] Disclosed herein are several embodiments of cigarette rolling and forming devices, which generally include two (or more) cylinders and a looped belt trained thereon, and which are configured to selectively compress a quantity of loose tobacco into a shaped tobacco cylinder. Some embodiments of cigarette rolling devices according to the present disclosure include one or more features that minimize or prevent mechanical clogging due to loose tobacco. For example, in some embodiments, a pair of opposing support plates extends from a base, with two cylinders extending between the support plates and rotatably mounted thereto. The support plates include a pair of corresponding slots, with axle portions of one of the cylinders being journaled therein for slidable movement, such the cylinder is translationally moveable relative to the support plates through a range of motion defined by the slots. In various embodiments, the base may have a curved, contoured, or generally "hourglass" shape, which may provide clearance for a user's fingers when opening and closing the device, forming the tobacco rod, and/or inserting the tobacco rod into a pre-formed cigarette tube. In some embodiments, the contoured or hourglass shape of the base also may reduce the size and/or weight of the device, and/or may facilitate single-handed operation of the device.

[0016] Some embodiments may also include guard plates disposed between the ends of the movable cylinder and the slot in which the axle portions are journaled, the guard plate being configured to prevent loose tobacco from the recess from entering the slot. In such embodiments of cigarette rolling devices, a guard plate may include a movement slot through which the axle portion extends, the movement slot configured to accommodate a path of movement of the axle portion of the translatable cylinder as the first cylinder is moved within the range of motion defined by the curvilinear slots. Optionally, the guard plate may be partially or wholly recessed in a corresponding recess in the support plate, or be otherwise disposed between the cylinder and the curvilinear slot.

[0017] Some embodiments of cigarette rolling devices according to the present disclosure may include a trough extending between the support plates, the trough having a top surface and a bottom surface, with the belt being trained around the cylinders and the trough, so that the portion of the belt forming the recess in which loose tobacco may be compressed is prevented from contacting other portions of the belt. In some embodiments, the trough may be configured to snap into one or more cor-

responding recesses on the base, and/or the trough may be configured to interconnect the support plates.

[0018] Some embodiments of cigarette forming devices according to the present disclosure also include a pushing device mounted for movement along an axis parallel to the cylinders, the pushing device including a pushing element adapted to engage and push one end of a shaped tobacco rod in the cylindrical recess toward one of the support plates, for example, to push the tobacco rod into a pre-formed cigarette tube. In such embodiments, the support plate may further include an opening and a nozzle disposed in the support plate, and optionally a nozzle guard to protect the nozzle from accidental damage and/or to facilitate visualization of the nozzle by a user. In various embodiments, the nozzle may extend in a direction away from the cylinders and may be configured to receive and retain one end of a pre-formed cigarette tube against the plate. The pushing device may thus be adapted to selectively push the tobacco rod from the recess into a pre-formed cigarette tube retained on the nozzle. In some embodiments, the pushing device may further be configured, after pushing the tobacco rod into the tube, to compress the tobacco rod into the tube.

[0019] In additional embodiments, the pushing device also may be configured to rotate around the fixed cylinder, and thus may be used to open and close the device (e.g., slide the translatable cylinder in the journaled slot). In these embodiments, when rotated about the axis of the fixed cylinder (e.g., away from the translatable cylinder), the pushing device may include a pushing element that exerts force on the translatable cylinder, causing it to move in its journaled slots into an open position.

[0020] In various embodiments, the nozzle also may be associated with a clamping mechanism, which may be configured to hold the pre-formed cigarette tube in place against and/or around the nozzle. In some embodiments, the clamping mechanism may be used to retain the pre-formed cigarette tube on the nozzle, for example while the pushing device is being used to slide the tobacco rod into the pre-formed cigarette tube. In some embodiments, the clamping mechanism may be configured to be activated by a user without needing to alter the user's grip on the cigarette rolling device.

[0021] In some embodiments, the cigarette rolling device also may be configured to form a tobacco rod having a slightly asymmetrical (e.g., slightly conical) shape, wherein a first end of the tobacco rod has a slightly smaller diameter than the second end of the tobacco rod. In some embodiments, this asymmetrical shape may be achieved by varying the length of the slots at the first and second ends of the device, thus aligning the translatable cylinder slightly out of parallel with the fixed cylinder. In some embodiments, this slightly conical tobacco rod shape may ease the displacement of the rod through the nozzle and into the pre-formed cigarette tube.

[0022] These and other illustrative embodiments of cigarette rolling and/or forming devices may incorporate any combination of the features, components, and con-

cepts discussed herein. Several illustrative, non-exclusive examples of cigarette rolling devices according to the present disclosure are disclosed below in connection with **Figs. 1-11**. As explained in more detail with respect to each embodiment, the illustrative embodiments differ from each other primarily in terms of different mechanical configurations and features. Alternative configurations and/or variants of several of the embodiments may also be presented, such as to illustrate variations of structural components and arrangement of such components. The various embodiments, configurations, and methods disclosed in the paragraphs below are examples and should not be considered in a limiting sense, but merely for illustrative purposes of one or more of the aspects of the subject matter described herein. Numerous variations are possible and considered to be within the scope of this disclosure.

[0023] The cigarette rolling devices in **Figs. 1-11** are illustrated in somewhat simplified form as including a contoured or hourglass-shaped base from which opposing support plates extend, with at least two cylinders extending between the support plates. As discussed, these devices may alternatively incorporate different support structures such as those variously described, illustrated, and/or incorporated herein or otherwise consistent with the present disclosure. Similarly, any of the following illustrative examples of rolling devices may be utilized with any or all of the described features or components, may have any suitable relative size and shape, and may be incorporated into a handheld device or a larger mechanical system. It is within the scope of the present disclosure that components, subcomponents, and variants of the subsequently described **Figs. 1-11** may be used with other cigarette rolling devices within the scope of the present disclosure, such as those otherwise described and/or incorporated herein.

[0024] One illustrative and non-exclusive embodiment of a cigarette rolling device **100** is shown in **Figs. 1-5**. This embodiment of a cigarette rolling device **100** includes a pair of support plates **101** (separately indicated at **101a**, **101b**) extending from a contoured or hourglass-shaped base **102**, which may be coupled to each support plate **101 a**, **101b**. In various embodiments, base **102** and support plates **101** together may form the outer edges of the device. As a matter of convenience, the support plates are sometimes referred to herein as "proximal" and "distal," with "proximal" used herein to indicate "relatively closer to the body of a user as typically held during use" (e.g., closer to the non-nozzle end), and signified by **P** in **Fig. 1**, and "distal" indicating "relatively farther from the body of a user as typically held during use" (e.g., closer to the nozzle end), and signified by **D** in **Fig. 1**. These conventions are used herein to describe the relative relationships between elements of all of the illustrated embodiments of the cigarette rolling device.

[0025] **Fig. 4** is a side elevation view of the proximal end of the device of **Fig. 1**, with the device in an open configuration, and **Fig. 5** is a side elevation view of the

proximal end of the device of **Fig. 1**, with the device in a closed configuration. The support plates **101** are shown to be attached firmly to each other by way of base **102**. As shown also in **Figs. 2, 4, and 5**, the base may be connected to the support plates **101** at anchor points **105**, such as by screws, rivets, or other mechanical linkages, or by any appropriate fastening means, to form a stable structure. As can be best seen in **Figs. 1 and 8**, base **102** may have a curved, contoured, or generally "hourglass" shape, and a radiused portion **102a**, which may provide clearance and/or a convenient resting place for a user's fingers when opening and closing the device, forming the tobacco rod, and/or inserting the tobacco rod into a pre-formed cigarette tube. In some embodiments, the contoured, radiused, hourglass shape of base **102** also may reduce the size and/or weight of the device, and/or may facilitate single-handed operation of the device.

[0026] As shown best in **Fig. 1 6**, translatable cylinder **103** and fixed cylinder **104** are shown to be mounted to, and extending between, the support plates. In the illustrative embodiment **100**, each cylinder is shown to include axle portions **106** protruding in a longitudinal direction from the ends of the cylinder, the axle portions being mounted or otherwise rotatably coupled to the support plates. In particular, and as shown in **Fig. 2**, each support plate is shown to include a slot **107** in which the axle portions of translatable cylinder **103** are journaled, and a mounting site **108** (shown as a hole) in which the axle portions of fixed cylinder **104** are journaled. Slot **107** and mounting site **108** may allow cylinders **103** and **104**, respectively, to be rotated relative to the support plates.

[0027] As shown in **Figs. 4 and 5**, in device **100**, mounting site **108** may allow fixed cylinder **104** to be rotatable about a single, fixed axis defined by the placement of the axle portions relative to the support plates. As such, the mounting site may include any rotatable linkage; for example, instead of a hole through the support plate (as shown), a recessed portion into the proximal surface of the support plate may be used, or a stud or other mount that protrudes proximally from the support plate surface to rest within a corresponding depression-shaped axle portion on fixed cylinder **104**. Such variations are considered to be within the scope of this disclosure.

[0028] Slot **107a** allows translatable cylinder **103** to be selectively translatablely moved relative to the support plates (and relative to fixed cylinder **104**), through a range of motion defined by the size and shape of the slot, by sliding the axle portions of translatable cylinder **103** along the slots. Thus, translatable cylinder **103** is configured to be rotatable about a non-fixed axis.

[0029] As described in greater detail below, the inverted "J" shape of the slot shown in **Figs. 4 and 5** may provide stability when shaping a quantity of loose tobacco in a belt trained around the cylinders, such as by retaining the translatable cylinder **103** in (or otherwise preventing or reducing inadvertent movement of the translatable cylinder **103** from) a desired position in the slot, such as that

shown in **Fig. 5**. As such, the slot may have any desired configuration. For simplicity, the slots in the illustrated embodiments are all shown to have a generally curvilinear configuration, and may be referred to herein as "curvilinear slots" for convenience and clarity, such as to distinguish among other types of slots described herein. However, the slots may be curved, straight, or otherwise shaped, in various embodiments and alternative configurations of various embodiments, so the term "curvilinear slots" is not meant to be restrictive. Further, some configurations may include a slot-shaped recess in the proximal surface of the support plates, instead of a slot through the support plates (as shown), or a slot that includes portions that extend all the way through the support plate and recessed portions, and so forth, and such variations are considered to be within the scope of this disclosure.

[0030] Turning now to **Fig. 6**, which is a side elevation view of the distal end (e.g., the nozzle end) of the device of **Fig. 1**, and **Fig. 7**, which is a top view of the device of **Fig. 1** in a closed position, in some embodiments, slot **107b** may be slightly longer than corresponding slot **107a**, or may be positioned slightly closer to fixed cylinder **104** than corresponding slot **107a**, which is shown in **Figs. 4 and 5**. This asymmetry in slot length and/or position results in translatable cylinder **103** being positioned slightly out of parallel with respect to fixed cylinder **104** when the device is in a closed position (see, e.g., **Fig. 7**). This asymmetry results in a tobacco rod having a very slightly tapered or conical shape, which may facilitate dislodging of the formed tobacco rod from the device. In various embodiments, the degree to which translatable cylinder is out of parallel with fixed cylinder **104** may be between about 1 degree and 15 degrees, for example about 5-10 degrees out of parallel. In some embodiments, this angle may be adjusted by a user by varying the position of the translatable cylinder **103** with regard to slot **107b** when the device is in a closed position.

[0031] Returning to **Figs. 4 and 5**, rolling device **100** is also shown in **Figs. 4 and 5** to include a looped belt **109** trained around the cylinders. The belt is shown to be somewhat loose, with the portion of the belt disposed between the cylinders forming a recess, indicated at **114**. In various embodiment, this recess may be relatively broad and shallow when cylinder **104** is spaced away from cylinder **103** (e.g., when the device is in an open position, see e.g., **Fig. 4**), and substantially cylindrical when the cylinders are substantially adjacent each other (e.g., when the device is in a closed position, see, e.g., **Fig. 5**).

[0032] As can be seen in **Figs. 4 and 5**, as well as in greater detail in **Fig. 9**, the device also may include a trough **130** extending from a corresponding notch **131** in base **102**. The trough is shown to have a U-shaped or semicircular cross-section, with a first or inner surface **132**, and a second, or outer, surface **134** (see, e.g., **Fig 9**). As can be seen in **Figs. 4-6**, one layer of belt **109** is shown to be trained around the outer surface of the

trough, which is thus disposed between the portion of the belt forming the recess and the portion surrounding the recess portion.

[0033] The trough may facilitate efficient use of the device, for example, by reducing drag. For example, if the trough were not present, the portion of the belt that forms the recess may be urged toward, or even against, the other layer of the belt that moves in the opposite direction of the portion forming the recess, when a quantity of loose tobacco is being shaped in the recess via rolling of the belt. The inner surface of the belt may further have a texture to reduce the amount of friction generated when portions of the surface slide or contact each other. However, in some circumstances, the inner surface of the belt that slides against itself when the two layers are moved in opposite directions may eventually become worn from repeated use, and/or create drag that interferes with rolling, due to two surfaces moving relative to each other. Moreover, moisture or loose tobacco particles may cause layers of the belt to bind or otherwise adhere to each other, pulling both layers in the same direction, which may lead to binding of the cylinders, creasing or tearing the belt, or other mechanical interference or damage to the device.

[0034] Also, distensions or other irregularities in the belt surface may in turn lead to uneven rolling of a leaf of cigarette paper around a shaped tobacco rod, or may create creases and folds in a leaf of cigarette paper, which many users may find undesirable. The trough may thus reduce or prevent drag by providing a stable sliding surface for one layer of the belt, or otherwise preventing the portion of the belt forming the recess from rubbing or sliding against, or otherwise contacting, other portions of the belt, such as a layer of the belt moving in the opposite direction when the belt is rolled.

[0035] As mentioned briefly above, a quantity of loose tobacco is compressed and shaped into a tobacco rod by rolling the belt, as the tension of the belt itself, in addition to forces urging the tobacco against surfaces over which the belt is moved. The trough may function to increase the tension of the belt (or reduce slack) overall or when the cylinders are in the closed configuration, by providing another surface around which the belt is trained. Increasing the tension of the belt may in turn provide stability to the device and/or increase consistency of cigarettes produced using the device by positionally stabilizing the cylindrical recess formed when the cylinders are in the closed configuration. In such configurations, only the portion of the belt trained around the outer surface of the trough may come in contact with the trough.

[0036] In some configurations, such as those in which the portion of the belt forming the recess comes in contact with a trough (such as the inner surface of the trough), the trough may facilitate forming of a tobacco rod by providing a support surface against which the tobacco in the recess may be urged when the belt is moved over the cylinders (or rolled around the rollers). The roller surfaces and the surface tension of the unsupported portion of the

belt itself collectively provide a compressive force on the tobacco in the cylindrical recess, but repeated use over time may tend to stretch the belt so that the surface tension is weakened, or the belt is slackened sufficiently, and so forth, so that the belt may become unsuitable for compressing tobacco. As such, the support trough in such configurations may provide a support surface against which the belt may be urged, which may reduce or even prevent distension of the belt via the compressive force delivered to the tobacco in the recess by the cylinders.

[0037] Optionally, the trough may function to establish the diameter of a finished cigarette, such as by providing a support surface of constant diameter, and/or by increasing the tension of the belt surface, as discussed above, either of which may assist a user in determining the correct quantity of loose tobacco to use. By reducing or preventing variation in the diameter of tobacco rod shaped in the device, a user can be assured of relatively consistent results, which may in turn reduce waste if the tobacco rod produced is too large for a standard pre-formed cigarette tube to surround. The trough may thus have any configuration, shape, thickness, cross-section, and so forth, suitable to achieve any of the aforementioned results. For example, alternative configurations may include a flatter or more curved cross-section than that shown (e.g., a semi-circular cross section with a different diameter), be a different thickness, and so forth, as well as be of composite construction and/or discontinuous construction. Furthermore, in some embodiments, the trough may help align the axis of the tobacco rod formed in the recess of the belt with the axis of the nozzle. In some embodiments, without the backup support and alignment the trough provides, the tobacco rod might fail to align with the nozzle, and thus might not be displaceable by the pushing device through the nozzle.

[0038] As shown in **Figs. 3, 4, and 5**, device **100** may also include a pair of guard plates **110**, each of which is disposed between an end of the translatable cylinder **103** and the curvilinear slot **107**. As can be seen in **Figs. 2 and 3**, in some embodiments, each support plate **101** may include a circular recess **113** in which each guard plate **110** may be at least partially seated. However, in other embodiments, support plate **101** may not include this circular recess, and each guard plate **110** may be at seated adjacent support plate **101**, rather than recessed into support plate **101**.

[0039] As shown in **Fig. 3**, guard plate **110** may include an axle portion **116**, which is journaled within a mounting site on the support plate **101**. Guard plate **110** also includes a movement slot **111**, through which axle portion **106** of translatable cylinder **103** extends; as such, guard plate accommodates movement of translatable cylinder **103** while preventing loose tobacco from the recess **114** from entering the curvilinear slot **107**. Although two guard plates are shown, other embodiments of a cigarette rolling device may include only one guard plate, or even multiple guard plates.

[0040] As can be seen in **Fig. 4**, about half of the curvilinear slot **107** overlaps recess **114** in at least the "open" configuration and in at least part of the range of movement of cylinder **103**. Loose tobacco typically includes a sufficient amount of moisture such that stray pieces of tobacco may have a tendency to stick to, clog, or otherwise interfere with moveable components of a cigarette rolling device, which may in turn interfere with intended operation and require periodic cleaning. As configured, however, the guard plate **110** of cigarette rolling device **100** is disposed between the end of the cylinder and the curvilinear slot, preventing loose tobacco from the recess **114** from entering the slot **107**, while allowing movement of the translatable cylinder **103** between open and closed configurations. Guard plate **110** may thus be configured as desired to prevent loose tobacco from the belt, or more particularly from the recess formed by the portion of the belt between the cylinders, from entering the curvilinear slot, while accommodating movement of the axle portion as the cylinder is moved back and forth. In general, embodiments incorporating one or more pairs of curvilinear slots and one or more cylinders journaled for slidable movement therein, the shape of the guard plate, and/or the configuration of the movement slot in a guard plate, may relate to such factors as the shape and/or length of the slot, the relative size(s) of the moveable cylinder(s), and so forth.

[0041] As described above, although device **100** may be used to roll cigarettes in cigarette papers, which typically come in books of packets of flat leaves, pre-formed cigarette tubes are also commercially available, for example if a user prefers to hand-roll a tobacco rod, but does not want to roll a leaf of cigarette paper around the tobacco rod. Some commercially available cigarette tubes also include filter tips positioned within the otherwise empty tube, into which a user may place a shaped tobacco rod. Thus, embodiments of a cigarette rolling device may instead include a mechanism by which a tobacco rod shaped in the cigarette rolling device, as explained in detail above, may be pushed or injected into a pre-formed cigarette tube.

[0042] As shown in **Fig. 7**, and as shown in greater detail in **Figs. 11A** and **11B**, device **100** may also include a pushing device **150** mounted for movement relative to the cylinders **103**, **104** along an axis parallel to the cylinders, and optionally, mounted for movement relative to the fixed cylinder about an axis parallel to the fixed cylinder **104**. Pushing device **150** includes an outer surface **152** and an inner surface **154**, the inner surface further including a collar portion **156** which is shaped to removably clamp to fixed cylinder **104** to retain the pushing device on the cylinder, but to also allow slidable movement of the sliding device therealong. The outer surface is shown in **Figs. 11A** and **11B** to include a tab **153** that provides for ease of both slidable and rotational movement, for example, by a user's thumb or index fingers, but the outer surface may have any suitable configuration.

[0043] In various embodiments, an arm **158** is shown to extend from the collar portion **156** in a direction such that when pushing device is mounted on fixed cylinder **104**, the arm descends generally into a recess **114** formed by the portion of the belt **109** trained around the cylinders **103**, **104**. An extension **159** protrudes from the arm, for example at a right angle in some embodiments, and terminates in a substantially circular pushing element **160**. So configured, the pushing element is adapted to engage and push the end of a shaped tobacco rod in the cylindrical recess, for instance by sliding the pushing device along the cylinder. More particularly, the pushing device is adapted to be slid toward one support plate, designated as the "distal" support plate, from the direction of the other, "proximal" support plate, and back again. In other words, if the pushing device is initially positioned near the proximal support plate, when a tobacco rod is shaped in the cylindrical recess, sliding the pushing device toward the distal support plate will engage the pushing element with the end of the tobacco rod and push the end of the tobacco rod toward the first support plate, to longitudinally compress the tobacco rod.

[0044] As mentioned above, "tapping" or compressing the end of a shaped tobacco rod may more securely pack the tobacco into a cylindrical form, making the tobacco rod less likely to break apart and/or to reduce or even prevent loose tobacco from flaking away or otherwise coming loose from the tobacco rod. As such, longitudinal compression may allow a cigarette to last longer in storage, without tobacco coming loose from the end of the cigarette. Compression of one or both ends of a tobacco rod may also provide a flat surface against which cigarette paper, or the end of a cigarette tube, may be folded, such as to hold tobacco in the paper or tube while the cigarette is being held, stored, or smoked, and/or simply for aesthetic effect.

[0045] In addition to slidable movement, the collar portion **156** and inner surface **154** are configured to move in a predetermined range of rotatable movement about the cylinder to which the device **150** is clamped, such as to ensure stability of the pushing device on the cylinder **104**. For example, in some embodiments, as cylinder **103** is moved from a "closed" position to an "open" position, the portion of the belt trained between the cylinders moves from defining a relatively deeper, cylindrical recess to defining a broader, relatively shallower recess. As this belt portion moves from one configuration to the other, it may push against the portion of the pushing device within the recess (e.g., the pushing element **160**, the extension **159**, and/or the pushing device arm **158**). However, the collar portion **156** and inner surface **154** of the pushing device are configured to allow the pushing device to "rock" back and forth on the cylinder, for example to accommodate the movement of the belt when the cylinders are moved between "open" and "closed" configurations, without becoming detached therefrom.

[0046] In various embodiments, pushing device **150** also may include an outrigger portion **192** extending from

collar portion **156** and configured to limit rotation of pushing device **150** about fixed cylinder **104** by coming in contact with the portion of belt **109** that is wrapped around translatable cylinder **103**. This configuration allows outrigger portion **192** to prevent over-rotation of pushing device **150** about fixed cylinder **104**, which otherwise might allow the pushing device **150** (and particularly the pushing element **160**, the extension **159**, and/or the pushing device arm **158**) to pinch belt **109** against trough **130**.

[0047] Additionally, outrigger portion **192** may serve to orient the axis of the pushing element **160** and align it to the axis of the formed tobacco rod. Additionally, in various embodiments, outrigger portion **192** may provide stability to the pushing device **150**, as well as providing an additional slide bearing surface that reduces overall contact pressure of the pushing device **150** against belt **190** when extending it to displace the tobacco rod.

[0048] In some embodiments, such as the embodiment illustrated in Figs. **11A** and **11B**, the collar portion **156** may be configured to rotate outward and away from translatable cylinder **103** along the longitudinal axis of fixed cylinder **104**, for example when tab **153** is depressed by a user. In some embodiments, this rotation of the collar portion may result in the portion of the pushing device within the recess (e.g., the pushing element **160**, the extension **159**, and/or the pushing device arm **158**) exerting sufficient pressure against translatable cylinder **103** to cause the translatable cylinder to move along slots **107** into an open position (see, e.g., Fig. **11B**). This feature may allow a user to conveniently "flip" the device into an open position, for example to receive tobacco in recess **114**, and may be accomplished with a single hand. As illustrated in Fig. **8**, pushing device **150** typically may be moved into a center position along the longitudinal axis of fixed cylinder **104** prior to being rotated about the longitudinal axis of fixed cylinder **104**, so that it may exert approximately equal pressure on both the proximal and distal ends of translatable cylinder **103**. However, one of skill in the art will appreciate that in some embodiments, pushing device may be used to open device **100** in any position along fixed cylinder **104**.

[0049] In various embodiments, proximal support plate **101a** may be configured to receive and house at least a portion of pushing device **150**, such as to allow the pushing device to be moved substantially out of recess **114** while a quantity of loose tobacco is being shaped into a tobacco rod, so as not to interfere with the rolling process. In various embodiments, therefore, proximal support plate **101a** thus may include a recess for receiving a portion of pushing device **150**. As such, the pushing device may be selectively moved to the support plate, housing a portion thereof within the recess in the support plate, so that after a tobacco rod is formed, the pushing device may be deployed to urge the pushing element against the end of the tobacco rod.

[0050] As such, in some embodiments, a pushing device as described above may function as a compression element, such as to longitudinally compress the tobacco

rod. However, as may be seen in Figs. **6** and **7**, some embodiments of the cigarette rolling device may also include an opening **170** in the distal support plate **101 b**, and a corresponding nozzle **172** disposed on the support plate that couples to or extends through the opening. In various embodiments, the nozzle **172** may have a circular cross-section and may be positioned on the distal support plate **101 b** to be aligned with the substantially circular recess **114** formed by the belt **109** when the cylinders **103**, **104** are in a "closed" configuration, such that the contents of the cylindrical recess **114** (such as a shaped tobacco rod) may be pushed through the opening **170** and the nozzle **172**, when the pushing device **150** is slid from the proximal support plate **101a** toward the distal support plate **101 b**. In the some embodiments, the nozzle may be mounted to the support plate by means of a retaining rim on support plate, but any suitable mounting method may be used.

[0051] The size of the cross-section of the nozzle is such that an end of pre-formed cigarette tube (not shown) may be fitted snugly over the nozzle and retained against the support plate. As such, after a quantity of loose tobacco has been shaped into a compressed tobacco rod in the substantially cylindrical recess formed by the belt, sliding the pushing device from the second support plate toward the first support plate functions to engage the pushing element with the end of the tobacco rod and urges the tobacco rod through the opening **170** and nozzle **172**, and into the cigarette tube retained against the first support plate, to form a cigarette. In some embodiments, a nozzle guard **174** may be used in conjunction with the nozzle **172**, for example to protect the nozzle from accidental damage during transport, but also to serve as a visual guide to assist a user in fitting the pre-formed cigarette tube over the nozzle. In some embodiments, nozzle guard **174** may have a contrasting color when compared with nozzle **172**, for instance to help make nozzle **172** more visually distinct.

[0052] Also, in various embodiments, sliding the pushing device **150** to the extent of the movement allowed by the distal support plate **101 b** may project at least a portion of the pushing element **160** partially through the opening **170**, by means of extension **159** on arm **158**. When the length of the cylinders corresponds to the length of the cigarette tube, this configuration thus may allow the tobacco rod, once injected into the cigarette tube, to be further compressed or "tapped" into the tube. Optionally, of course, the pushing device also may be used to push bits of loose tobacco from the belt, for example to clean the belt of the device between uses.

[0053] Turning now to Figs. **10A-10C**, some embodiments of the device also include a clamping device **180** that is selectively operable to retain a pre-formed cigarette tube on the nozzle **172**. Although any suitable configuration may be used, clamping device **180** is shown in Figs. **10A-10C** to include a three-pronged clamping element **182** housed within distal support plate **101 b**, the clamping element terminating in two or more clamp-

ing surfaces **184a**, **184b**, **184c** that are shaped to hold an end of the tube against the exterior surface of the nozzle **172**. Clamping element **182** may be biased away from nozzle **172** by means of an internal biasing element (which in the illustrated embodiment is clamping element **182**), such that pressing a button **190** at the other end of clamping element **182** urges a trio of clamping surfaces **184a**, **184b**, **184c**, against the nozzle **172**, securing a pre-formed cigarette tube in place, such as for receiving a tobacco rod from the device **100**. In some embodiments, three-pronged clamping element **182** may travel within a recess **188** within the distal support plate **101 b**, and actuation of button **190** may force the outer two **184a**, **184c** of the three clamping surfaces against the sides of recess **188**, thus urging force the outer two **184a**, **184c** of the three clamping surfaces inward, and against the exterior surface of nozzle **172**. The inner clamping surface **184b** may simultaneously be pressed against the underside of nozzle **172**. Thus, in the illustrated embodiment, clamping device **180** exerts pressure on three sides of nozzle **172**. Although a three-pronged clamping member is illustrated herein, one of skill in the art will also appreciate that such clamping mechanisms may be used that have one, two, three, or even more clamping surfaces.

[0054] The overall structural configuration of a cigarette rolling device **100** having been explained, an illustrative explanation of the use of such a device, in general, is given in the paragraphs below. In the following explanation, several of the individual components are further discussed, as well as variations to the structural configuration and some components of the illustrated embodiments. All of such variations are considered to be within the scope of this disclosure.

[0055] In use, such as to roll a cigarette, a user may first move cylinder **103** away from cylinder **104**, such as by applying force to the tab **153** on pushing device **150** sufficient to cause the portion of the pushing device within the recess (e.g., the pushing surface **160**, the extension **159**, and/or the pushing device arm **158**) to exerting sufficient pressure against translatable cylinder **103** to cause the axles **106** of translatable cylinder **103** to move along slots **107** into an open position. One of skill in the art will appreciate that the device may be opened in other ways, even if pushing device **150** is present, such as by applying pressure directly to translatable cylinder **103** or to the belt **109** trained around the cylinder.

[0056] As mentioned above, the configuration of the slot **107** may be suitable to provide a desired amount of ease of movement of cylinder **103**, such as by restricting or allowing freedom of movement along the slot; to provide a desired range of separation of the cylinders when cylinder **103** is moved near to or away from cylinder **104**; and so forth. Additionally, as described in greater detail above, the two slots **107a**, **107b** may be of different lengths, or may be positioned differently on support plates **101a**, **101b**, such that the cylinders **103**, **104** are not quite parallel to one another. In particular, the cylin-

ders **103**, **104** may be spaced more closely together at the distal end (e.g., the nozzle end) of the device when the device is in the closed position, so as to create a slightly cone-shaped tobacco rod, for instance to ease displacement of the formed tobacco rod out of recess **114** through the nozzle **172**. Thus, even though the slots in the illustrated embodiments are all shown, in general, to have an inverted "J" shape, any desired shape may be used, and the slots may be of different lengths or have different positioning with respect to one another.

[0057] A user may then place a quantity of loose tobacco on the portion of the belt **109** between the cylinders **103**, **104**, and may prepare to shape the loose tobacco into a tobacco rod by moving the translatable cylinder **103** toward the fixed cylinder **104**, into a "closed" configuration, as shown in **Fig. 5**. Throughout the disclosure, the term "substantially adjacent" is used to describe the relative positions of the cylinders in this configuration, the term indicating that the cylinders are positioned close enough together so that loose tobacco placed in the recess shapes the recess into a substantially cylindrical form when the cylinders are urged into this configuration, but still spaced to provide sufficient clearance so that the portions of the belt trained over each cylinder do not come into contact when the belt is moved.

[0058] "Substantially cylindrical," in turn, signifies a shape with a relatively constant and substantially circular cross-section, such that a quantity of loose tobacco, when rolled in such a substantially cylindrical recess, is formed into a cylindrical shape, also referred to herein as a "tobacco rod." As can be seen in **Fig. 5**, the cross-section of the recess **114** when the cylinders are substantially adjacent is slightly teardrop-shaped, with the point of the teardrop extending to the space between the cylinders. However, the movement of the belt over the cylinders compresses any loose tobacco in the tip area into a cylindrical shape.

[0059] In general, a quantity of loose (uncompressed) tobacco sufficient to form a cigarette will occupy a greater volume than when compressed, and, when the cylinders are moved into the "closed" configuration, will urge the belt outward into the substantially cylindrical shape shown in **Fig. 5**. The size and cross-section of the cylindrical recess **114**, for a given quantity of loose tobacco, may be determined by factors such as the length of the belt **109** relative to the configuration of the cylinders **103**, **104**, the elasticity of the belt, the size of the cylinders, and so forth. As such, the belt (and the cylinders) may be configured as desired to provide a tobacco rod of desired dimension and/or desired compression. For example, the belt may be longer or shorter than as shown, and/or elastic or non-elastic, such as to form a differently-sized cylindrical recess in which the tobacco may be compressed.

[0060] After a quantity of loose tobacco is placed on the belt **109**, and the cylinders have been moved to a "closed" configuration, the belt may be moved over the cylinders to shape the loose tobacco into a tobacco rod.

As can be seen in **Fig. 5**, the portion of the belt forming recess **114** will "roll" the loose tobacco as the belt is moved over the cylinders, via the force exerted on the tobacco by the surface tension of the portion of the belt forming the cylindrical recess, and any surfaces against which the belt is urged (for example, the lower portion of the belt against which the cylindrical recess portion is slid, the surfaces of the cylinders, and so forth).

[0061] In the cigarette rolling devices illustrated herein, the cylinders (such as cylinders **103**, **104**) are all shown to be rotatably mounted to the support plates, and thus may be rolled in either direction to move the belt and compress the tobacco. As such, such cylinders may also be referred to herein as "rollers." Rotating the cylinders may allow easy movement of the belt over the cylinders. However, one or more of the cylinders may instead be nonrotatably mounted, for example in embodiments in which the belt may be slid over the one or more nonrotatable cylinders. For example, an alternative configuration may include a nonrotatable cylinder in place of cylinder **104**, together with a rotatable cylinder such as translatable cylinder **103**, or any desired combination of rotatable and nonrotatable cylinders.

[0062] The surfaces of the cylinders thus may be textured to provide a desired degree of friction against the belt. The belt may also (or alternatively) have a textured outer and/or inner surface, such as to provide a desired degree of friction when moved over the cylinders and/or against the tobacco. In embodiments incorporating rotatable cylinders (or rollers), for example, the surface of the belt that is urged against the surface of the rollers may be textured or otherwise fabricated to assure a "grip" of the belt over the rollers, such that a user may be able to roll the rollers by exerting force on the belt. In embodiments incorporating nonrotatable cylinders or structures around which the belt is slid, the surface of the belt that moves against such cylinders may be smoothly textured or otherwise configured to reduce drag. Also, the surface of the belt that is urged against the tobacco may be textured or otherwise fabricated to "grip" the loose tobacco, such as to facilitate compression as the belt is rolled around the tobacco, as desired.

[0063] In configurations that incorporate nonrotatable cylinders, a "cylinder" may be configured to have a partially cylindrical or even geometrically noncylindrical shape, and consist of one or more surfaces over which the belt may be slid. Such surfaces may have a partially cylindrical or curved shape, such as to facilitate sliding, or any desired geometry to provide a sliding surface, and/or a surface against which the belt may be urged in order to compress a quantity of loose tobacco into a tobacco rod when the belt is moved over the cylinders. Such variations are considered to be within the scope of this disclosure, and, as such, are considered to be within the scope of the term "cylinder," as used herein. For the sake of clarity, however, all of the illustrated embodiments are shown to include rotatably mounted cylinders.

[0064] After the belt has been moved over the cylinders

to compress the tobacco into a tobacco rod, a user may place a pre-formed cigarette tube over nozzle **172**, and optionally may depress button **190** in order to activate the clamping device **180** and hold the pre-formed cigarette tube in place. Longitudinal pressure may then be applied to pushing device tab **153** to slide the collar portion **156** of pushing device **150** from the proximal end to the distal end of fixed cylinder **104**, which simultaneously advances the pushing device arm **158**, extension **159**, and substantially circular pushing surface **160** within recess **114**. This movement pushes the formed tobacco rod through opening **170** and nozzle **172** into the pre-formed cigarette tube. Once the tobacco rod has been inserted into the pre-formed cigarette tube, further sliding of pushing device **150** may cause the tobacco rod to be tamped within the tube as described above in greater detail.

[0065] Alternately, a user may insert one end of a piece (or "leaf") of cigarette paper between the cylinders and continue moving the belt, to roll the paper received between the cylinders around the tobacco rod. Cigarette papers are commercially available in several standard sizes, and the overall width of the cylinders may be appropriate, in various embodiments, to accommodate leaves of various sizes. Commercially available cigarette papers are usually gummed along one edge, or include some other adhesive property, so that when the gummed edge is oriented to be the trailing edge of the leaf as it is rolled around the tobacco rod, the gummed edge adheres to the surface of a portion of the paper already rolled. As such, if such a cigarette paper is used in the rolling device, a user may stop rolling and moisten the trailing, gummed edge prior to rolling the paper completely around the tobacco rod. Once the paper is rolled around the rod, the cylinders may be moved into the "open" configuration and the formed cigarette may be removed.

[0066] Although certain embodiments have been illustrated and described herein, it will be appreciated by those of ordinary skill in the art that a wide variety of alternate and/or equivalent embodiments or implementations calculated to achieve the same purposes may be substituted for the embodiments shown and described without departing from the scope. Those with skill in the art will readily appreciate that embodiments may be implemented in a very wide variety of ways. This application is intended to cover any adaptations or variations of the embodiments discussed herein. Therefore, it is manifestly intended that embodiments be limited only by the claims and the equivalents thereof.

Claims

1. A cigarette forming device comprising:

- a base with first and second support plates extending therefrom;
- a translatable cylinder and a fixed cylinder ex-

- tending between the support plates and rotatably mounted thereto, the translatable cylinder being translatable moveable between a first position in which the translatable cylinder is spaced from the fixed cylinder, and a second position in which the translatable cylinder is substantially adjacent to the fixed cylinder;
- a looped belt trained around the translatable and fixed cylinders, wherein a portion of the belt between the translatable and fixed cylinders forms an open recess adapted to receive a quantity of loose tobacco when the translatable cylinder is in the first position, and wherein the portion forms a substantially cylindrical recess in which the tobacco may be shaped into a tobacco rod when the belt is moved about the translatable and fixed cylinders when the translatable cylinder is in the second position;
- a pushing device slidably and rotatably coupled to the fixed cylinder and configured for movement around and along the fixed cylinder, wherein the pushing device comprises an pushing element adapted to engage and slidably push one end of a shaped tobacco rod in the cylindrical recess toward the first support plate, and wherein rotation of the pushing device about the fixed cylinder causes the pushing element to move the translatable cylinder from the second position to the first position.
2. The cigarette forming device of claim 1, wherein the first support plate further includes an opening and a nozzle disposed thereon, the nozzle being configured to receive and retain one end of a pre-formed cigarette tube thereupon, and wherein the pushing device is adapted to selectively push the shaped tobacco rod from the recess, through the nozzle, and into the pre-formed cigarette tube.
 3. The cigarette forming device of claim 1 or 2, wherein the pushing device further includes:
 - (a) a collar portion adapted for slidable movement along the fixed cylinder, the collar portion including an arm extending therefrom and generally into the recess formed by the portion of the belt between the translatable and fixed cylinders, and wherein the pushing element is disposed on the arm;
 - (b) an extension disposed on the arm, the extension extending towards the nozzle, and wherein the pushing element is disposed on an end of the extension; or
 - (c) both (a) and (b).
 4. The cigarette forming device of claim 1 or 2, wherein one of the first and second support plates includes a recess, and wherein the pushing device is adapted to selectively move at least a portion of the arm, extension, and/or pushing element into the recess.
 5. The cigarette forming device of claim 3, wherein the collar portion is configured to removably clamp to the fixed cylinder for slidable and rotational movement thereon.
 6. The cigarette forming device of claim 1 or 2, further comprising a clamping device selectively operable to retain the pre-formed cigarette tube on the nozzle.
 7. The cigarette forming device of claim 1 or 2, wherein the first and second support plates include corresponding first and second slots; wherein the translatable cylinder includes axle portions protruding from each end, each axle portion being journaled in one of the slots for slidable movement therein.
 8. The cigarette forming device of claim 7, wherein the first slot is shorter than the second slot.
 9. The cigarette forming device of claim 8, wherein the translatable cylinder is positioned slightly out of parallel with the fixed cylinder when the translatable cylinder is in the second position.
 10. The cigarette forming device of claim 7, wherein the device further includes a guard plate disposed between one end of the translatable cylinder and first slot, the guard plate being configured to prevent loose tobacco from the recess from entering the first slot.
 11. The cigarette forming device of claim 1 or 2, further including a trough extending between and interconnecting the first and second support plates, the trough having a top surface and a bottom surface; and
 - wherein the looped belt is trained around the translatable and fixed cylinders and the trough;
 - wherein the recess is formed by a portion of the belt between the translatable and fixed cylinders; and
 - wherein the trough is adapted to prevent the portion of the belt forming the recess from contacting other portions of the belt.
 12. The cigarette forming device of claim 1 or 2, wherein the base is contoured in an hourglass shape.
 13. The cigarette forming device of claim 1 or 2, further comprising:
 - a light source disposed in the first or second support plate and configured to illuminate a portion of the cigarette forming device when coupled to a power source;
 - an activation member configured to control ac-

tivation of the light source; and
a power source electrically coupled to the light
source and adapted to provide power to illumi-
nate the light source.

5

14. The cigarette forming device of claim 13, wherein
the first support plate further includes an opening
and a nozzle disposed thereon, the nozzle being
configured to receive and retain one end of a pre-
formed cigarette tube thereupon, and wherein the
light source is disposed in the first or second support
plate and configured to illuminate at least a portion
of the nozzle, at least a portion of the cylindrical re-
cess, or both a portion of the nozzle and a portion of
the cylindrical recess.

10

15

15. The cigarette forming device of claim 13, wherein
the light source, power source, and activation mem-
ber are all disposed in the first support plate.

20

25

30

35

40

45

50

55

Fig. 1




Fig. 2




Fig. 3





Fig. 4

Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10A




Fig. 10B




Fig. 10C




Fig. 11A





Fig. 11B





EUROPEAN SEARCH REPORT

Application Number
EP 13 19 4374

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	DE 29 43 136 A1 (KUERBI & NIGGELOH [DE]) 7 May 1981 (1981-05-07) * the whole document *	1-15	INV. A24C5/44
A	GB 466 895 A (EVANS CONCINNUM LTD; HENRY JAMES BARKER) 8 June 1937 (1937-06-08) * the whole document *	1-15	
A	US 2009/301501 A1 (PREVOST DAVID [US]) 10 December 2009 (2009-12-10) * the whole document *	1-15	
			TECHNICAL FIELDS SEARCHED (IPC)
			A24C
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 11 March 2014	Examiner Cardan, Cosmin
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

1
EPO FORM 1503 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 13 19 4374

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-03-2014

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 2943136	A1	07-05-1981	NONE
GB 466895	A	08-06-1937	NONE
US 2009301501	A1	10-12-2009	CA 2731191 A1 17-12-2009
			EP 2328430 A1 08-06-2011
			US 2009301501 A1 10-12-2009
			WO 2009152057 A1 17-12-2009

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 13665008 A [0001]