



(11) EP 2 738 083 A1

(12)

EUROPEAN PATENT APPLICATION
published in accordance with Art. 153(4) EPC

(43) Date of publication:
04.06.2014 Bulletin 2014/23

(51) Int Cl.:
B63C 11/00 (2006.01)

(21) Application number: **12872307.9**

(86) International application number:
PCT/KR2012/008120

(22) Date of filing: **08.10.2012**

(87) International publication number:
WO 2014/046331 (27.03.2014 Gazette 2014/13)

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(72) Inventors:

- KANG, Hee Jin**
Chungcheongnam-do 321-765 (KR)
- LEE, Dong Kon**
Yuseong-gu, Daejeon 305-308KR (KR)

(30) Priority: **24.09.2012 KR 20121056018**


(74) Representative: **Thum, Bernhard**
Wuesthoff & Wuesthoff
Patent- und Rechtsanwälte
Schweigerstrasse 2
81541 München (DE)

(54) **RADAR REFLECTOR OPERATING DEVICE FOR DISTRESS POSITION INDICATION**

(57) Embodiments of the inventive concept provide a radar reflector operating device for indicating an emergency position, capable of permitting a victim to indicate his location by means of a radar reflector even when he is dropped into seawater without a life jacket, easily actuating the radar reflector by simply pulling or pressing a switch even when low seawater temperature dulls a victim's consciousness and senses of fingers, arms, etc., maintaining an operation of the radar reflector due to safety means even without sustenance of power by a

victim once the victim applies power in a predetermined level to operate the radar reflector, allowing an appropriate reflection section and distant recognition by preventing the radar reflector, to which hydrodynamic wings is attached, from being lowered due to wind, etc., and securing a victim, who cannot swim, against dangerous environments by rendering him to use the radar reflector as a life buoy and hold the wings by hands to float on the sea.

[Fig. 1]



Description**TECHNICAL FIELD**

[0001] Embodiments of the inventive concept relate to a radar cross section reflector for indicating an emergency position.

BACKGROUND ART

[0002] Safety Of Life At Sea (SOLAS) proposes that a radar cross section (RCS) for recognizing an object on the sea should be 10 m^2 and obligates that the RCS should be equipped in vessels so as to prevent a clash between small and large vessels.

[0003] An RCS is proposed with its verified result for a typical radar reflector and can be largely extended in a multi-hedral structure such as a di-hedral or tri-hedral structure.

[0004] FIG. 11 shows a basic theory about the RCS. According to the theory, it can be seen that in a radar reflector on which a di-hedral or tri-hedral metal films, a tri-hedral radar reflector having one side of 1 for a radar wave of a conventional 3GHz band is equipped with an RCS over 3500 times of a spherical metal reflective surface having a radius of 1 and even over 3 times of a planar metal reflective surface.

[0005] Therefore, when there is emergency at sea, utilizing the characteristics of such a radar reflector helps a victim to effectively indicate his emergency position to a vessel or relief squad, which is passing by, by means of the radar reflector.

[0006] With regard to this view, the present applicant made the application (Application No. 10-2008-0050410) at May 29, 2008, entitled "Emergency position indicating device using RCS (Radar Cross Section) characteristics" (hereinafter referred to as 'related art'), which was issued for patent at December 2, 2010 (Patent No. 10-0999442) (see FIG. 12).

[0007] The related art is provided to solve a problem that makes it difficult to find a victim's position when there is an emergency on the sea. According to the related art, it is possible to quickly find an emergency position in the daytime or nighttime regardless of marine environments, overcoming the shortness arising from an Emergency Position Indicating Radio Beacon (EPIRB) that operates a large error bound of 4 mile and a cyalume lightstick limited in indication range. Referring to the related art, to effectively indicate an emergency position, radar emitted from a vessel or relief squad passing by the emergency position is intensively reflected on a balloon-type device embedding a radar reflector on which a di-hedral or tri-hedral metal film is covered to maximize an RCS, or on a self-floating radar reflector, while the device or the self-floating reflector is floating for a long time over the emergency position in a sufficient height 10 ~ 30 m after injecting a gas, which is lighter than air, thereinto.

[0008] While the related art, operable by attaching an

EPIRB, which includes a radar reflector, to a life jacket, is theoretically capable of indicating an emergency position in the daytime or nighttime regardless of marine environments, there would be inconvenience or limits as follows in operation for actual emergency on the sea.

[0009] First, in an actual case of emergency on the sea, victims are usually dropped into seawater without wearing life jackets beforehand. Since most victims are incapable of swimming, the utility of the related art would be lower.

[0010] Second, if seawater temperature is low, a victim's consciousness rapidly goes down and senses of fingers, arms and legs dull to cause their movement to be hard. As a result, it would be difficult to operate a device of the related art for indicating his emergency position.

[0011] Third, the lack of means for safely operating a device of the related art would cause a victim to be damaged if the device malfunctions in emergency. And, if some important components of the device of the related art get out of order, it cannot be used.

[0012] Fourth, while a radar reflector needs to be floated over an appropriate height for providing a proper reflection section and securing distant recognition, the device of the related art may be floated lower than a desired height due to wind.

PRIOR ART DOCUMENT**30 PATENT DOCUMENT**

[0013] Emergency position indicating device using RCS (Radar Cross Section) characteristics (Korean Application No. 10-2008-0050410)

35 SUMMARY OF THE INVENTION**PROBLEM TO BE SOLVED BY THE INVENTION**

[0014] Embodiments of the inventive concept provide a radar reflector operating device for indicating an emergency position, capable of permitting a victim to indicate his location by means of a radar reflector even when he is dropped into seawater without a life jacket, easily actuating the radar reflector by simply pulling or pressing a switch even when low seawater temperature dulls a victim's consciousness and senses of fingers, arms, etc., maintaining an operation of the radar reflector due to safety means even without sustenance of power by a victim once the victim applies power in a predetermined level to operate the radar reflector, allowing an appropriate reflection section and distant recognition by preventing the radar reflector, to which hydrodynamic wings is attached, from being lowered due to wind, etc., and securing a victim, who cannot swim, against dangerous environments by rendering him to use the radar reflector as a life buoy and hold the wings by hands to float on the sea.

MEANS FOR SOLVING THE PROBLEM

[0015] In accordance with an aspect according to embodiments of the inventive concept, a radar reflector operating device for indicating an emergency position includes: a case including an accommodation space; a pull trigger accommodated in the inside of the case and fixedly caught on a first detent installed in the case; a compressed air container configured to store a compressed gas and include a gas jet, and accommodated in the inside of the pull trigger, the gas jet being connected to a gas ejection nozzle that is installed at a through hole of the pull trigger; a radar reflector made of a flexible material and accommodated in the inside of the case in a winkle type like a zabra, including a gas injection nozzle that is placed at one end of the body and closely connected to the gas ejection nozzle, configured to inflate and secede from the inside of the case if the compressed gas is injected through the gas injection nozzle float, and float in the air; a cable configured to connect the case 1 with the radar reflector; a pull switch connected to the pull trigger and configured to pull the pull trigger to allow the gas ejection nozzle to enter at the gas jet; and a press switch installed at the case and configured to press the compressed air container to allow the gas jet to enter at the gas ejection nozzle.

[0016] The technical objectives of the inventive concept are not limited to the above disclosure; other objectives may become apparent to those of ordinary skill in the art based on the following descriptions.

EFFECTS OF THE INVENTION

[0017] Embodiments of the inventive concept provide a radar reflector operating device for indicating an emergency position, capable of permitting a victim to indicate his location by means of a radar reflector even when he is dropped into seawater without a life jacket, easily actuating the radar reflector by simply pulling or pressing a switch even when low seawater temperature dulls a victim's consciousness and senses of fingers, arms, etc., maintaining an operation of the radar reflector due to safety means even without sustenance of power by a victim once the victim applies power in a predetermined level to operate the radar reflector, allowing an appropriate reflection section and distant recognition by preventing the radar reflector, to which hydrodynamic wings are attached, from being lowered due to wind, etc., and securing a victim, who cannot swim, against dangerous environments by rendering him to use the radar reflector as a life buoy and hold the wings by hands to float on the sea.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] The foregoing and other features and advantages of the inventive concepts will be apparent from the more particular description of preferred embodiments of

the inventive concepts, as illustrated in the accompanying drawings in which like reference characters refer to the same parts throughout the different views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the inventive concepts. In the drawings:

FIG. 1 illustrates a feature that a radar reflector is accommodated in a case in accordance with embodiments of the inventive concept;

FIG. 2 illustrates a feature of injecting a compressed gas into the radar reflector by means of a pull switch in accordance with embodiments of the inventive concept;

FIG. 3 illustrates a feature of injecting a compressed gas into the radar reflector by means of a press switch in accordance with embodiments of the inventive concept;

FIG. 4 illustrates a procedure that the radar reflector containing the compressed gas abruptly inflates to secede from the inside of the case in accordance with embodiments of the inventive concept;

FIG. 5 illustrates a feature that the radar reflector containing the compressed gas is entirely floating in the air in accordance with embodiments of the inventive concept;

FIG. 6 illustrates a feature of fixing the radar reflector to the case in order to utilize the inflated radar reflector as a life buoy in accordance with embodiments of the inventive concept;

FIG. 7 illustrates a feature of manually injecting air into the radar reflector by a victim in accordance with embodiments of the inventive concept;

FIG. 8 illustrates a feature of utilizing the radar reflector as a life buoy by a victim in accordance with embodiments of the inventive concept;

FIG. 9 illustrates a feature that the radar reflector is floating in the air with unfolded wings in accordance with embodiments of the inventive concept;

FIG. 10 illustrates a principle of forming hydrodynamic sections for generating lift on the wings attached to the radar reflector in accordance with embodiments of the inventive concept;

FIG. 11 shows a basic theory of an RCS; and

FIG. 12 shows a configuration of the related art (Patent No. 10-0999442) by the present applicant.

EXPLANATION OF REFERENCE NUMERALS

50 [0019]

1: case

2: sodium alginate cover

3: first detent

4: second detent

5: third detent

6: pull trigger

7: first projection

- 8: second projection
- 9: through hole
- 10: spring
- 11: gas ejection nozzle
- 12: compressed gas container
- 13: gas jet
- 14: radar reflector
- 15: wing(s)
- 16: air inlet
- 17: air outlet
- 18: gas injection nozzle
- 19: cable
- 20: pull switch
- 21: press switch
- 22: firs loop
- 23: second loop

MODELS FOR CARRYING THE INVENTION

[0020] Various embodiments will now be described more fully with reference to the accompanying drawings in which some embodiments are shown. These inventive concepts may, however, be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure is thorough and complete and fully conveys the inventive concept to those skilled in the art. In the drawings, the sizes and relative sizes of layers and regions may be exaggerated for clarity.

[0021] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the present inventive concept. As used herein, the singular forms "a," "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0022] Embodiments are described herein with reference to cross-sectional illustrations that are schematic illustrations of idealized embodiments (and intermediate structures). As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, embodiments should not be construed as limited to the particular shapes of regions illustrated herein but are to include deviations in shapes that result, for example, from manufacturing.

[0023] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this inventive concept belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpret-

ed as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

[0024] FIG. 1 illustrates a detailed configuration of a radar reflector operating device for indicating an emergency position in accordance with embodiments of the inventive concept, including a case 1, a pull trigger 6, a compressed gas container 12, a radar reflector 14, a cable 19, a pull switch 20 and a press switch 21. As shown in FIG. 1, the radar reflector 14 is normally folded and preserved in the case 1.

[0025] Referring to FIG. 1, as the case 1 has a preservation space in the inside, the pull trigger 6, the compressed gas container 12, the radar reflector 14 and the cable 19 are accommodated in the inside of the case 1. While the case 1 is normally shaped in a cylinder, it may have another shape but a cylinder. It is preferred to make the case 1 with a firm material not to be easily broken

down due to even an impact occurring in emergency.

[0026] One end of the case 1 (E of FIG. 1) is open, which is provided to allow the radar reflector 14 to inflate and secede from the inside of the case 1 when injecting a compressed gas thereinto as described later. If the end E of the case 1 is fully open from the beginning, the radar reflector 14 may not normally operate in emergency because of impurities or humidity in the inside of the case 1. For that reason, it is desirable to put a sodium alginate cover 2 over the open end E of the case 1. The sodium alginate 2 forms a film in a dry state and melts away by water.

[0027] The pull trigger 6 is fixedly caught by a first detent 3 in the inside of the case 1, fixedly caught by a first detent 3. This fixation of the pull trigger 6 means that the pull trigger 6 maintains an unmovable state as long as no power is applied thereto, not permanently fixed to the case 1 so as to be unmovable anyway. In other words, if power is applied to the pull trigger 6, the fixed part thereof can be released to move the pull trigger 6.

[0028] Continued to this feature, as illustrated in FIG. 1, the pull trigger 6 includes a first projection 7, which can be caught on the first detent 3, at the outside of the body. The first projection 7 is formed in right triangle section and the first detent 3 is formed in tetragonal section.

The pull trigger 6 is fixed within the case 1 when a vertical surface of the first projection is caught on the first detent 3. It can be seen from FIG. 1 that if power is applied to the pull trigger 6, the pull trigger 6 is blocked to move toward direction A due to the first detent 3, but can move toward direction B. To make the pull trigger 6 move toward direction B, end C of the pull trigger 6 must be protruded out of the case 1 (see FIG. 2), for which end D of the case 1 is equipped with a through hole 9 to allow the pull trigger 6 to protrude out of the case 1

[0029] The compressed gas container 12, as a receptacle for containing a compressed gas such as helium, includes a gas jet 13 for exhausting the compressed gas to the outside. The compressed gas container 12 is ac-

commodated in the pull trigger 6, as shown in FIG. 1, and supported by a spring 10 in an interval from the inner side of the pull trigger 6. With this condition, the gas jet 13 of the compressed gas container 12 is connected to a gas ejection nozzle 11 installed at the through hole 9 of the pull trigger 6.

[0030] In this structure, if predetermined power (this means an action to pull the pull switch 20 or press the press switch 21) is applied to make the gas ejection nozzle 11 enter at the gas jet 13 or reversely make the gas jet 13 enter at the gas ejection nozzle 11, the gas ejection nozzle 11 operates to press the compressed gas container 12 connected with the gas jet 13. Then, the compressed gas is released from the compressed gas container 12, passing through the gas ejection nozzle 11. The compressed gas passing through the gas ejection nozzle 11 is finally injected into the radar reflector 14 by way of a gas injection nozzle 18 that will be described later.

[0031] As the radar reflector 14 is made up of a flexible material, it is accommodated in the case 1 in a folded type such as a wrinkled bucket (called 'zabara' in Japanese) and the gas injection nozzle 18 installed at one end of the body is closely connected with the gas jet 11. As aforementioned, if the compressed gas is injected into the radar reflector 14 by way of the gas injection nozzle 18, the radar reflector 14 abruptly inflates to secede from the inside of the case 1 (in this case, the radar reflector 14 is pushed out of the case 1, for which its end folded in a wrinkled type as shown in FIG. 4 first inflates to be released out of the case 1 and during this, the gas injection nozzle 18 is separated from the gate jet 11) and float in the air. While floating in the air, radar emitted from a vessel or life squad passing by the emergency position is intensively reflected on the radar reflector 14 to effectively indicate the emergency position (see FIG. 5).

[0032] In a distress situation, a victim drifting about in the sea is able to inject the compressed gas into the radar reflector 14 even by using either the pull switch 20 or the press switch 21. This means that it is permissible for a victim to selectively operate the radar reflector 14 freely in correspondence with current conditions such as his poses, etc. in emergency.

[0033] FIG. 2 illustrates a feature of injecting the compressed gas into the radar reflector 14 by means of the pull switch 20 in accordance with embodiments of the inventive concept. And FIG. 3 illustrates a feature of injecting the compressed gas into the radar reflector 14 by means of the press switch 21 in accordance with embodiments of the inventive concept.

[0034] Now first will be described the pull switch 20. As shown in FIG. 1, the pull switch 20 is connected to the pull trigger 6; acting to pull the pull trigger 6 so as to allow the gas ejection nozzle 11 to enter at the gas jet 13. FIG. 2 will be further referred to detail the mechanism of operating the pull switch 20. If a victim pulls the pull switch 20, the pull trigger 6 moves toward direction B. Accordingly, end C of the pull trigger 6 moves toward

direction B to protrude out of the case 1. End F of the pull trigger 6 moves toward direction B to be close to the compressed gas container 12. During this, together with end F of the pull trigger 6, the gas ejection nozzle 11 enters at the gas jet 13 and presses the compressed gas container 12 connected with the gas jet 13. As a result, the compressed gas is released from the compressed air container 12 by way of the gas jet 13, passing through the gas ejection nozzle 11. The compressed gas passing through the gas ejection nozzle 11 is finally injected into the radar reflector 14 by way of the gas injection nozzle 18.

[0035] In this operation, as shown in FIG. 2, it is preferred to provide a second detent 4 in the inside of the case 1. The second detent 4 functions to fix, as it is, the pull trigger 6 that is being pulled. From the embodiments illustrated in FIG. 2, the second detent 4 is placed along direction B in a predetermined interval with the first detent 3. The second detent 5 is shaped in a right triangle section. A slope of the second detent 5 is normally conditioned to meet with a slope of the first projection 7 (if a victim does not pull the pull switch 20). Therefore, if a victim pulls the pull switch 20, the slope of the first projection 7 slides down the slope of the second detent 4 to allow the pull trigger 6 to move toward direction B. From this condition, even if the victim releases the pull switch 20, the pull trigger 6 cannot move again toward direction A. This is because the vertical surface of the first projection 7 is caught by a vertical surface of the second detent 4 to interrupt the movement of the pull trigger 6.

[0036] As aforementioned, with the second detent 4 installed in the inside of the case 1, the radar reflector 15 can be actuated only if a victim pulls the pull switch 20 with power over a predetermined level enough to overcome resistance of the second detent 4. Therefore, it is possible to preliminarily prevent the radar reflector 14 from being inadvertently actuated even in a non-emergent situation. Additionally, once the radar reflector 14 operates, it maintains its operating state although a victim does not continuously pulls the pull switch 20. Thus, a victim, anyone having power only capable of pulling the pull switch 20, can be helped by the radar reflector 14.

[0037] In the meantime, as shown in FIG. 2, the pull switch 20 is installed to protrude out of the case 1, but preferably formed in a loop. Therefore, even in an emergent condition without time to spare, a victim is able to easily identify and pull the pull switch 20. As also, even when a victim is going down in consciousness due to low seawater temperature and dulling with his fingers or arms to be restricted in motion, he is able to easily actuate the radar reflector 14 by simply pulling the pull switch 20. The pull switch 20 shaped in a loop may be fixedly hooked on a life jacket of a victim, preventing it from being lost on the sea.

[0038] Now will be described the press switch 21. Referring to FIG. 1, the press switch 21 is installed in the case 1. The press switch 21 acts to directly press the compressed air container 12, allowing the gas jet 13 to

enter at the gas ejection nozzle 11. Hereinafter will be more detailed the mechanism of operating the press switch 21 in conjunction with FIG. 3. If a victim presses the press switch 21, the compressed air container 12 is pushed to move toward direction A due to the press switch 21. Then, the gas jet 13 enters at the gas ejection nozzle 11. The gas ejection nozzle 11 presses the compressed air container 12 connected to the gas jet 13. As a result, the compressed gas is released from the compressed air container 12 by way of the gas jet 13, passing through the gas ejection nozzle 11 (as also, during this, the pull trigger 6 is being fixed by the first detent 3). The compressed gas passing through the gas ejection nozzle 11 is finally injected into the radar reflector 14 by way of the gas injection nozzle 18.

[0039] In this case, as shown in FIG. 3, it is preferred to place a third detent 5 in the inside of the case 1. The third detent 5 functions to fix the press switch 21 as it is pressed. From the embodiments of FIG. 3, at the outer side of the press switch 21 is included a second projection 8 configured to be caught on a third detent 5. The second projection 8 is shaped in a right triangle section and the third detent 5 is also shaped in a right triangle section. A slope of the third detent 5 is normally conditioned to meet with a slope of the second projection 8 (if a victim does not press the press switch 21). Therefore, if a victim presses the press switch 21, the slope of the second projection 8 slides down the slope of the third detent 5 to allow the press switch 21 to move toward direction A. From this condition, even if the victim releases the press switch 21, the press switch 21 cannot move again toward direction B, because a vertical surface of the second projection 8 is caught on a vertical surface of the third detent 5 and thereby interrupted to move.

[0040] As aforementioned, if the third detent 5 is installed in the inside of the case 1, a victim must press the press switch 21 with power over a predetermined level enough to overcome resistance of the third detent 5 in order to actuate the radar reflector 14. Therefore, it is possible to preliminarily prevent the radar reflector 14 from inadvertent actuation even in a non-emergent situation. Additionally, although a victim does not continue to press the press switch 21 after once actuating the radar reflector 14, the radar reflector 14 maintains its operating state. Thus, anyone who has power capable of pressing the press switch 21, as a victim, can be easily helped by the radar reflector 14.

[0041] In the meantime, as illustrated in FIG. 3, while the press switch 21 is installed to protrude out of the case 1, it is preferred to place the press switch 21 in contact with the compressed air container 12. By installing the press switch 21 to protrude out of the case 1, a victim is able to easily identify and press the press switch 21 even in an urgent and emergent situation. Additionally, by placing the press switch 21 in contact with the compressed air container 12, it is possible to effectively push the compressed air container 12 with small power for pressing the press switch 21. Therefore, even when severe envi-

ronments such as low seawater temperature cause a victim's consciousness to go down and dull motions of his fingers or arms, the victim is able to easily actuate the radar reflector 14 by simply pressing the press switch 21.

[0042] Even when the radar reflector 14 containing the compressed gas is floating in the air, it maintains a connection state to the case 1 by way of the cable 19 (see FIG. 5). The gas injection nozzle 18 acts as a unilateral valve to inhibit leakage of the compressed gas that is injected into the radar reflector 14. If the compressed gas has not been injected into the radar reflector 14 or is released from the radar reflector 14, a victim is able to blow air into the radar reflector 14 through the gas injection nozzle 18 and utilize the radar reflector 14 as a life buoy (see FIG. 7).

[0043] If the radar reflector 14 is utilized as a life buoy, even a non-swimmable victim is able to indicate his position by means of the radar reflector 14, while using the radar reflector 14 as the life buoy, when he has been dropped into water without a life jacket.

[0044] With regard to the utilization of the radar reflector 14 for a life buoy, the radar reflector 14 may include a first loop 22 allowing the radar reflector 14 to hang on a certain object (see FIG. 1) and the case 1 may include a second loop 23 allowing the first loop 22 of the radar reflector 14 to hang thereon (see FIG. 1). The first loop 22 of the radar reflector 14 can be used as not only a handle when a victim blows air into the radar reflector 14 through the gas injection nozzle 18 (see FIG. 7), but also means for preventing a victim from losing the radar reflector 14, which is used as a life buoy, by suspending the radar reflector 14 from the victim's body (see FIG. 8). If it is impossible for a victim to directly suspend the radar reflector 14 from his body, the radar reflector 14 can be utilized as a life buoy by suspending the first loop 22 of the radar reflector 14 from the second loop 23 of the case 1 and holding the case 1. Additionally, if a victim fixes the case 1 to a life jacket by means of the second loop 23, it is possible to prevent a fatal miscarriage such as loss of the radar reflector 14 at the sea.

[0045] On the other hand, a wing (or wings) 15 is (are) provided to the radar reflector 14 (see FIG. 9). The wing 15 is made of a flexible material as same as the radar reflector 14. The wing 15 is attached to the radar reflector 14 and accommodated in the inside of the case 1 together with the radar reflector 14 in a folded state. While the radar reflector 14 inflates and floats in the air, the wing 15 spreads out together to maintain a floating height of the radar reflector 14 (see FIG. 9).

[0046] The spreading mechanism of the wing 15 attached to the radar reflector 14 is as follows. Referring to FIG. 10, the wing 15 includes an air inlet 16 for allowing air to be introduced thereto. The wing 15 may include an air outlet 17 together for allowing air, which has flowed into the inside, to be exhausted to the outside. With this structure, while the wing 15 is floating in the air together with radar reflector 14, air flows into the wing 15 through the air inlet 16 and goes out of the wing 15 through the

air outlet 17. These air inflow and outflow continue repetitively to form, what is called, an air pillar in the inside of the wing 15, hence spreading out the wing 15. If an area of a material forming the top of the wing 15 is designed to be larger than that of a material forming the bottom of the wing 15, the wing 15 has a hydrodynamic section (G of FIG. 10) that enables lift to be generated in the spread state.

[0047] As stated above, by attaching the hydrodynamic wing 15 to the radar reflector 14, the radar reflector 14 floating in the air is prevented from being lower to enable an appropriate reflection area and distant recognition. Moreover, as aforementioned, if the radar reflector 14 is utilized as a life buoy, a victim is able to use the wing 15 for preventing the radar reflector 14 from being lost, e.g. binding the radar reflector 14 to his body by means of the wing 15 or holding the wing 15 by hands (see FIG. 8).

[0048] The foregoing is illustrative of embodiments and is not to be construed as limiting thereof. Although a few embodiments have been described, those skilled in the art will readily appreciate that many modifications are possible in embodiments without materially departing from the novel teachings and advantages. Accordingly, all such modifications are intended to be included within the scope of this inventive concept as defined in the claims. In the claims, means-plus-function clauses are intended to cover the structures described herein as performing the recited function, and not only structural equivalents but also equivalent structures. Therefore, it is to be understood that the foregoing is illustrative of various embodiments and is not to be construed as limited to the specific embodiments disclosed, and that modifications to the disclosed embodiments, as well as other embodiments, are intended to be included within the scope of the appended claims.

Claims

1. A radar reflector operating device for indicating an emergency position, comprising:

a case 1 including an accommodation space;
a pull trigger 6 accommodated in the inside of the case and fixedly caught on a first detent installed in the case;
a compressed air container configured to store a compressed gas and include a gad jet 13, and accommodated in the inside of the pull trigger 6, the gas jet 13 being connected to a gas ejection nozzle 11 that is installed at a through hole 9 of the pull trigger 6;
a radar reflector 14 made of a flexible material and accommodated in the inside of the case 1 in a winkle type like a zabra, including a gas injection nozzle 18 that is placed at one end of the body and closely connected to the gas ejection nozzle 11, configured to inflate and secede

from the inside of the case 1 if the compressed gas is injected through the gas injection nozzle 18 float, and float in the air;
a cable 19 configured to connect the case 1 with the radar reflector 14;
a pull switch 20 connected to the pull trigger 6 and configured to pull the pull trigger 6 to allow the gas ejection nozzle 11 to enter at the gas jet 13; and
a press switch 21 installed at the case 1 and configured to press the compressed air container 13 to allow the gad jet 13 to enter at the gas ejection nozzle 11.

5 2. The radar reflector operating device according to claim 1, further comprising:
a second detent 4 installed in the inside of the case 1 and configured to allow the pull trigger 6 to be fixed while being pulled.

10 3. The radar reflector operating device according to claim 1, further comprising:
a third detent 5 installed in the inside of the case 1 and configured to allow the press switch 21 to be fixed while being pressed.

15 4. The radar reflector operating device according to claim 1, wherein the pull switch 20 is installed to protrude out of the case 1.

20 5. The radar reflector operating device according to claim 4, wherein the pull switch 20 is shaped in a loop.

25 6. The radar reflector operating device according to claim 1, wherein the press switch 21 is installed to protrude out of the case 1.

30 7. The radar reflector operating device according to claim 6, wherein the press switch 21 is installed in contact with the compressed air container 12.

35 8. The radar reflector operating device according to claim 1, further comprising:
a spring 10 installed at the pull trigger 6 and configured to support the compressed air container 12.

40 9. The radar reflector operating device according to claim 1, further comprising:
a first loop 22 installed at the radar reflector 14 and configured to allow the radar reflector 14 to hang on the first loop 22.

45 10. The radar reflector operating device according to

claim 9, further comprising:

a second loop 23 installed at the case 1 and
configured to allow the first loop 22 to hang on
the second loop 23. 5

11. The radar reflector operating device according to
claim 1, further comprising:

a wing 15 attached to the radar reflector 14 and 10
accommodated in the inside of the case 1 to-
gether with the radar reflector 14 in a folded type,
and configured to spread out, while the radar
reflector 14 is floating in the air, to allow the radar
reflector 14 to maintain a floating height. 15

12. The radar reflector operating device according to
claim 11, wherein the wing 15 comprises:

an air inlet 16 configured to allow air to flow into 20
the wing 15.

13. The radar reflector operating device according to
claim 12, wherein the wing 15 further comprises:

25
an air outlet 17 configured to allow air, which
has flow into the inside of the wing 15 through
the air inlet 16, to flow out to the outside of the
wing 15. 30

14. The radar reflector operating device according to
claim 11, wherein the wing 15 is configured to have
a hydrodynamic section to make lift while spreading
out. 35


15. The radar reflector operating device according to
claim 1, wherein the case 1 has one open end cov-
ered by a sodium alginate cover 2.

16. The radar reflector operating device according to 40
claim 1, wherein the gas injection nozzle 18 config-
ured to act as a unilateral valve to prevent leakage
of the compressed gas that has bee injected into the
radar reflector 14. 45


50

55


[Fig. 1]




[Fig. 2]




[Fig. 3]




[Fig. 4]




[Fig. 5]




[Fig. 6]




[Fig. 7]




[Fig. 8]




[Fig. 9]




[Fig. 10]



[Fig. 11]



[Fig. 12]



INTERNATIONAL SEARCH REPORT		International application No. PCT/KR2012/008120
A. CLASSIFICATION OF SUBJECT MATTER		
B63C 11/00(2006.01)i		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) B63C 11/00; G01S 13/00; B63C 9/20; G08B 5/00; G01S 13/04; A62B 37/00; F21V 14/00		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Korean Utility models and applications for Utility models: IPC as above Japanese Utility models and applications for Utility models: IPC as above		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) eKOMPASS (KIPO internal) & Keywords: distress location, reflection, radar, compressed gas, percussion		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	KR 10-0999442 B1 (KOREA OCEAN RESEARCH AND DEVELOPMENT INSTITUTE) 09 December 2010 See claim 1; figure 2.	1-16
A	JP 2002-024950 A (JULIAN, S. Shen) 25 January 2002 See page 4; figure 1.	1-16
A	JP 2002-029493 A (SUEHIRO, Nagaoka) 29 January 2002 See paragraphs [0009], [0015]-[0017]; figures 1, 3.	1-16
A	KR 10-0358331 B1 (PARK, Sang-Chul) 15 January 2003 See pages 2-3; figures 1, 2c.	1-16
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
<p>* Special categories of cited documents:</p> <p>“A” document defining the general state of the art which is not considered to be of particular relevance</p> <p>“E” earlier application or patent but published on or after the international filing date</p> <p>“L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>“O” document referring to an oral disclosure, use, exhibition or other means</p> <p>“P” document published prior to the international filing date but later than the priority date claimed</p> <p>“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>“&” document member of the same patent family</p>		
Date of the actual completion of the international search 27 MARCH 2013 (27.03.2013)		Date of mailing of the international search report 28 MARCH 2013 (28.03.2013)
Name and mailing address of the ISA/KR Korean Intellectual Property Office Government Complex-Daejeon, 189 Seonsa-ro, Daejeon 302-701, Republic of Korea Facsimile No. 82-42-472-7140		Authorized officer Telephone No.

Form PCT/ISA/210 (second sheet) (July 2009)

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/KR2012/008120

Patent document cited in search report	Publication date	Patent family member	Publication date
KR 10-0999442 B1	09.12.2010	GB 2462777 A US 2010-0300347 A1 WO 2009-002023 A1	24.02.2010 02.12.2010 31.12.2008
JP 2002-024950 A	25.01.2002	NONE	
JP 2002-029493 A	29.01.2002	NONE	
KR 10-0358331 B1	15.01.2003	NONE	

Form PCT/ISA/210 (patent family annex) (July 2009)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 1020080050410 A [0006]
- WO 100999442 A [0006] [0018]
- KR 1020080050410 [0013]