



(11)

EP 2 750 412 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
02.07.2014 Bulletin 2014/27

(51) Int Cl.:

(21) Application number: **12199761.3**

(22) Date of filing: 28.12.2012

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NC
PL PT RO RS SE SI SK SM TR**
Designated Extension States:
BA ME

(71) Applicant: **GN ReSound A/S**
2750 Ballerup (DK)

(72) Inventors:

- Gran, Karl-Fredrik Johan
SE-216 11 Malmö (SE)
- Ma, Guilin
DK-2800 Lyngby (DK)
- Telcs, Jacob Ulrik
DK-2200 København N (DK)

(74) Representative: **Zacco Denmark A/S**
Hans Bekkevolds Allé 7
2900 Hellerup (DK)

(54) Improved localization with feedback

(57) A hearing aid includes: a cue filter having an input that is provided with an output from the BTE sound input transducer; an adaptive feedback canceller configured to provide an output modelling a feedback path between the output transducer and the BTE sound input transducer, wherein the output modelling the feedback path is provided to a subtractor for subtraction of the output modelling the feedback path from the output of the BTE sound input transducer to obtain a difference, the subtractor outputting the difference to the cue filter; and a feedback and cue controller connected to the adaptive feedback canceller and the cue filter, wherein the feedback and cue controller is configured to control the cue filter to reduce a difference between an output of the ITE microphone and a combined output that is obtained using at least the cue filter.




Fig. 10

Description**FIELD OF THE INVENTION**

5 [0001] A new hearing aid is provided with improved localization of sound sources with relation to the wearer of the hearing aid.

BACKGROUND

10 [0002] Hearing aid users have been reported to have poorer ability to localize sound sources when wearing their hearing aids than without their hearing aids. This represents a serious problem for the mild-to-moderate hearing impaired population.

15 [0003] Furthermore, hearing aids typically reproduce sound in such a way that the user perceives sound sources to be localized inside the head. The sound is said to be internalized rather than being externalized. A common complaint for hearing aid users when referring to the "hearing speech in noise problem" is that it is very hard to follow anything that is being said even though the signal to noise ratio (SNR) should be sufficient to provide the required speech intelligibility. A significant contributor to this fact is that the hearing aid reproduces an internalized sound field. This adds to the cognitive loading of the hearing aid user and may result in listening fatigue and ultimately that the user removes the hearing aid(s).

20 [0004] Thus, there is a need for a new hearing aid with improved localization of sound sources, i.e. the new hearing aid preserves information of the directions and distances of respective sound sources in the sound environment with relation to the orientation of the head of the wearer of the hearing aid.

25 [0005] Human beings detect and localize sound sources in three-dimensional space by means of the human binaural sound localization capability.

[0006] The input to the hearing consists of two signals, namely the sound pressures at each of the eardrums, in the following termed the binaural sound signals. Thus, if sound pressures at the eardrums that would have been generated by a given spatial sound field are accurately reproduced at the eardrums, the human auditory system will not be able to distinguish the reproduced sound from the actual sound generated by the spatial sound field itself.

30 [0007] It is not fully known how the human auditory system extracts information about distance and direction to a sound source, but it is known that the human auditory system uses a number of cues in this determination. Among the cues are spectral cues, reverberation cues, interaural time differences (ITD), interaural phase differences (IPD) and interaural level differences (ILD).

35 [0008] The transmission of a sound wave from a sound source positioned at a given direction and distance in relation to the left and right ears of the listener is described in terms of two transfer functions, one for the left ear and one for the right ear, that include any linear distortion, such as coloration, interaural time differences and interaural spectral differences. Such a set of two transfer functions, one for the left ear and one for the right ear, is called a Head-Related Transfer Function (HRTF). Each transfer function of the HRTF is defined as the ratio between a sound pressure p generated by a plane wave at a specific point in or close to the appertaining ear canal (p_L in the left ear canal and p_R in the right ear canal) in relation to a reference. The reference traditionally chosen is the sound pressure p_I that would have been generated by a plane wave at a position right in the middle of the head with the listener absent.

40 [0009] The HRTF contains all information relating to the sound transmission to the ears of the listener, including diffraction around the head, reflections from shoulders, reflections in the ear canal, etc., and therefore, the HRTF varies from individual to individual.

45 [0010] In the following, one of the transfer functions of the HRTF will also be termed the HRTF for convenience.

[0011] The hearing aid related transfer function is defined similar to a HRTF, namely as the ratio between a sound pressure p generated by the hearing aid at a specific point in the appertaining ear canal in response to a plane wave and a reference. The reference traditionally chosen is the sound pressure p_I that would have been generated by a plane wave at a position right in the middle of the head with the listener absent.

50 [0012] The HRTF changes with direction and distance of the sound source in relation to the ears of the listener. It is possible to measure the HRTF for any direction and distance and simulate the HRTF, e.g. electronically, e.g. by filters. If such filters are inserted in the signal path between a playback unit, such as a tape recorder, and headphones used by a listener, the listener will achieve the perception that the sounds generated by the headphones originate from a sound source positioned at the distance and in the direction as defined by the transfer functions of the filters simulating the HRTF in question, because of the true reproduction of the sound pressures in the ears.

55 [0013] Binaural processing by the brain, when interpreting the spatially encoded information, results in several positive effects, namely better signal-to-noise ratio (SNR); direction of arrival (DOA) estimation; depth/distance perception and synergy between the visual and auditory systems.

[0014] The complex shape of the ear is a major contributor to the individual spatial-spectral cues (ITD, ILD and spectral

5 cues) of a listener. Devices which pick up sound behind the ear will, hence, be at a disadvantage in reproducing the HRTF since much of the spectral detail will be lost or heavily distorted.

[0015] This is exemplified in Figs. 1 and 2 where the angular frequency spectrum of an open ear, i.e. non-occluded, measurement is shown in Fig. 1 for comparison with Fig. 2 showing the corresponding measurement on the front microphone on a behind the ear device (BTE) using the same ear. The open ear spectrum shown in Fig. 1 is rich in detail whereas the BTE result shown in Fig. 2 is much more blurred and much of the spectral detail is lost.

SUMMARY

10 [0016] It is therefore desirable to position one or more microphones of the hearing aid at position(s) with relation to a user wearing the hearing aid in which spatial cues of sounds arriving at the user is preserved. It is for example advantageous to position a microphone in the outer ear of the user in front of the pinna, for example at the entrance to the ear canal; or, inside the ear canal, in order to preserve spatial cues of sounds arriving at the ear to a much larger extent than what is possible with the microphone behind the ear. A position below the triangular fossa has also proven advantageous with relation to preservation of spatial cues.

15 [0017] Positioning of a microphone at the entrance to the ear canal or inside the ear canal leads to the problem that the microphone is moved close to the sound emitting device of the hearing aid, whereby the risk of feedback generation is increased, which in turn limits the maximum stable gain which can be prescribed with the hearing aid.

20 [0018] The standard way of solving this problem is to completely seal off the ear canal using a custom mould. This, however, introduces the occlusion effect as well as comfort issues with respect to moisture and heat.

25 [0019] For comparison, the maximum stable gain of a BTE hearing aid with front and rear microphones positioned behind the ear, and an In-The-Ear (ITE) hearing aid with an open fitted microphone positioned in the ear canal is shown in Fig. 2. It can be seen that the ITE hearing aid has much lower maximum stable gain (MSG) than the front and rear BTE microphones for nearly all frequencies.

30 [0020] In the new hearing aid, output signals of an arbitrary configuration of microphones undergo signal processing in such a way that spatial cues are preserved and conveyed to the user of the hearing aid. The output signals are filtered with filters that are configured to preserve spatial cues.

35 [0021] The new hearing aid provides improved localization to the user by providing, in addition to conventionally positioned microphones as in a BTE hearing aid, at least one ITE microphone intended to be positioned in the outer ear of the user in front of the pinna, e.g. at the entrance to the ear canal or immediately below the triangular fossa; or, inside the ear canal, when in use in order to record sound arriving at the ear of the user and containing the desired spatial information relating to localization of sound sources in the sound environment.

40 [0022] The processor of the new hearing aid combines an audio signal of the at least one ITE microphone residing in the outer ear of the user with the microphone signal(s) of the conventionally positioned microphone(s) as in a BTE hearing aid in such a way that spatial cues are preserved. An audio signal of the at least one ITE microphone may be formed as a weighted sum of the output signals of each microphone of the at least one ITE microphone. Other forms of signal processing may be included in the formation of the audio signal of the at least one ITE microphone.

45 [0023] Thus, a hearing aid is provided, comprising

a BTE hearing aid housing configured to be worn behind the pinna of a user,
 50 at least one BTE sound input transducer, such as an omni-directional microphone, a directional microphone, a transducer for an implantable hearing aid, a telecoil, a receiver of a digital audio datastream, etc., accommodated in the BTE hearing aid housing, each of which is configured for conversion of sound into a respective audio signal,
 an ITE microphone housing configured to be positioned in the outer ear of the user for fastening and retaining, in its intended position,
 at least one ITE microphone accommodated in the ITE microphone housing, each of which is configured for conversion of acoustic sound into a respective audio signal,
 at least one adaptive cue filter, each of which having

55 an input that is provided with an output signal from a respective one of the at least one BTE sound input transducer, and the filter coefficients of which are adapted so that the difference between an output of the at least one ITE microphone and a combined output of the at least one adaptive cue filter is minimized, or substantially minimized, or reduced,

a processor configured to generate a hearing loss compensated output signal based on a combination of the filtered audio signals output by the at least one cue filter,

an output transducer for conversion of the hearing loss compensated output signal to an auditory output signal that can be received by the human auditory system,

an adaptive feedback canceller for feedback suppression and having

an input connected to an output of the processor for reception of the hearing loss compensated output signal, at least one output modelling the feedback path from the output of the output transducer to the respective at least one BTE microphone and connected to a subtractor for subtraction of the at least one output from the output of the respective at least one BTE microphone and outputting the difference to the respective at least one adaptive cue filter.

5

[0024] The hearing aid further comprises a feedback and cue controller with inputs connected to the at least one output of the adaptive feedback canceller and the output of the at least one adaptive cue filter, and configured to control the at least one adaptive cue filter so that the difference between an output of the at least one ITE microphone and a combined output of the at least one adaptive cue filter is reduced, preferably minimized, taking feedback into account.

10

[0025] The hearing aid may further have

a sound signal transmission member for transmission of a sound signal from a sound output in the BTE hearing aid housing at a first end of the sound signal transmission member to the ear canal of the user at a second end of the sound signal transmission member, and

15

an earpiece configured to be inserted in the ear canal of the user for fastening and retaining the sound signal transmission member in its intended position in the ear canal of the user.

[0026] Throughout the present disclosure, the "output signals of the at least one ITE microphone" may be used to identify any analogue or digital signal forming part of the signal path from the output of the at least one ITE microphone to an input of the processor, including pre-processed output signals of the at least one ITE microphone.

20

[0027] Likewise, the "output signals of the at least one BTE sound input transducer" may be used to identify any analogue or digital signal forming part of the signal path from the at least one BTE sound input transducer to an input of the processor, including pre-processed output signals of the at least one BTE sound input transducer.

25

[0028] In use, the at least one ITE microphone is positioned so that the output signal of the at least one ITE microphone generated in response to the incoming sound has a transfer function that constitutes a good approximation to the HRTFs of the user. For example, the at least one ITE microphone may be constituted by a single microphone positioned at the entrance to the ear canal. The processor conveys the directional information contained in the output signal of the at least one ITE microphone to the resulting hearing loss compensated output signal of the processor so that the hearing loss compensated output signal of the processor also attains a transfer function that constitutes a good approximation to the HRTFs of the user whereby improved localization is provided to the user.

30

[0029] BTE (behind-the-ear) hearings aids are well-known in the art. A BTE hearing aid has a BTE housing that is shaped to be worn behind the pinna of the user. The BTE housing accommodates components for hearing loss compensation. A sound signal transmission member, i.e. a sound tube or an electrical conductor, transmits a signal representing the hearing loss compensated sound from the BTE housing into the ear canal of the user.

35

[0030] In order to position the sound signal transmission member securely and comfortably at the entrance to the ear canal of the user, an earpiece, shell, or earmould may be provided for insertion into the ear canal of the user constituting an open solution. In an open solution, the earpiece, shell, or earmould does not obstruct the ear canal when it is positioned in its intended operational position in the ear canal. Rather, there will be a passageway through the earpiece, shell, or earmould or, between a part of the ear canal wall and a part of the earpiece, shell, or earmould, so that sound waves may escape from behind the earpiece, shell, or earmould between the ear drum and the earpiece, shell, or earmould through the passageway to the surroundings of the user. In this way, the occlusion effect is substantially eliminated.

40

[0031] Typically, the earpiece, shell, or earmould is individually custom manufactured or manufactured in a number of standard sizes to fit the user's ear to sufficiently secure the sound signal transmission member in its intended position in the ear canal and prevent the earpiece from falling out of the ear, e.g., when the user moves the jaw.

45

[0032] The output transducer may be a receiver positioned in the BTE hearing aid housing. In this event, the sound signal transmission member comprises a sound tube for propagation of acoustic sound signals from the receiver positioned in the BTE hearing aid housing and through the sound tube to an earpiece positioned and retained in the ear canal of the user and having an output port for transmission of the acoustic sound signal to the eardrum in the ear canal.

50

[0033] The output transducer may be a receiver positioned in the earpiece. In this event, the sound signal transmission member comprises electrical conductors for propagation of audio signals from the output of a processor in the BTE hearing aid housing through the conductors to a receiver positioned in the earpiece for emission of sound through an output port of the earpiece.

[0034] The ITE microphone housing accommodating at least one ITE microphone may be combined with, or be constituted by, the earpiece so that the at least one microphone is positioned proximate the entrance to the ear canal when the earpiece is fastened in its intended position in the ear canal.

55

[0035] The ITE microphone housing may be connected to the BTE hearing aid housing with an arm, possibly a flexible arm that is intended to be positioned inside the pinna, e.g. around the circumference of the conchae abutting the antihelix and at least partly covered by the antihelix for retaining its position inside the outer ear of the user. The arm may be pre-formed during manufacture, preferably into an arched shape with a curvature slightly larger than the curvature of the antihelix, for easy fitting of the arm into its intended position in the pinna. In one example, the arm has a length and a

shape that facilitate positioning of the at least one ITE microphone in an operating position immediately below the triangular fossa.

[0036] The processor may be accommodated in the BTE hearing aid housing, or in the ear piece, or part of the processor may be accommodated in the BTE hearing aid housing and part of the processor may be accommodated in the ear piece. There is a one-way or two-way communication link between circuitry of the BTE hearing aid housing and circuitry of the earpiece. The link may be wired or wireless.

[0037] Likewise, there is a one-way or two-way communication link between circuitry of the BTE hearing aid housing and the at least one ITE microphone. The link may be wired or wireless.

[0038] The processor operates to perform hearing loss compensation while maintaining spatial information of the sound environment for optimum spatial performance of the hearing aid and while at the same time providing as large maximum stable gain as possible.

[0039] The output signal of the at least one ITE microphone of the earpiece may be a combination of several pre-processed ITE microphone signals or the output signal of a single ITE microphone of the at least one ITE microphone. The short time spectrum for a given time instance of the output signal of the at least one ITE microphone of the earpiece is denoted $S^{IEC}(f, t)$ (IEC = In the Ear Component).

[0040] One or more output signals of the at least one BTE sound input transducers are provided. The spectra of these signals are denoted $S_1^{BTEC}(f, t)$, and $S_2^{BTEC}(f, t)$, etc (BTEC = Behind The Ear Component). The output signals may be pre-processed. Pre-processing may include, without excluding any form of processing; adaptive and/or static feedback suppression, adaptive or fixed beamforming and pre-filtering.

[0041] Adaptive cue filters may be configured to adaptively filter the audio signals of the at least one BTE sound input transducer so that they correspond to the output signal of the at least one ITE microphone as closely as possible. The adaptive cue filters G_1, G_2, \dots, G_n have the respective transfer functions: $G_1(f, t), G_2(f, t), \dots, G_n(f, t)$.

[0042] The at least one ITE microphone may operate as monitor microphone(s) for generation of an audio signal with the desired spatial information of the current sound environment.

[0043] Each output signal of the at least one BTE sound input transducer is filtered with a respective adaptive cue filter, the filter coefficients of which are adapted to provide a combined output signal of the adaptive cue filter(s) that resembles the audio signal provided by the at least one ITE microphone as closely as possible.

[0044] The filter coefficients are adapted to obtain an exact or approximate solution to the following minimization problem:

$$\min_{G_1(f,t) \dots G_n(f,t)} \|S^{IEC}(f, t) - G_1(f, t) S_1^{BTEC}(f, t) - \dots - G_n(f, t) S_n^{BTEC}(f, t)\|^p \quad (1)$$

wherein p is the norm. Preferably p = 2.

[0045] The algorithm controlling the adaption could (without being restricted to) e.g. be based on least mean square (LMS) or recursive least squares (RLS), possibly normalized, optimization methods in which p = 2.

[0046] Various weights may be incorporated into the minimization problems above so that the solution is optimized as specified by the values of the weights. For example, frequency weights W(f) may optimize the solution in certain one or more frequency ranges while information in other frequency ranges may be disregarded. Thus, the minimization problem may be modified into:

$$\min_{G_1(f,t) \dots G_n(f,t)} \|W(f)((S^{IEC}(f, t) - G_1(f, t) S_1^{BTEC}(f, t) - \dots - G_n(f, t) S_n^{BTEC}(f, t))\|^p \quad (2)$$

[0047] Further, in one or more selected frequency ranges, only magnitude of the transfer functions may be taken into account during minimization while phase is disregarded, i.e. in the one or more selected frequency range, the transfer function is substituted by its absolute value.

[0048] Subsequent to the adaptive cue filtering, the combined output signal of the adaptive cue filter(s) is passed on for further hearing loss compensation processing, e.g. with a compressor.

[0049] In this way, only signals from the at least one BTE sound input transducer is possibly amplified as a result of hearing loss compensation while the audio signal of the at least one ITE microphone is not included in the hearing loss compensation processing, whereby possible feedback from the output transducer to the at least one ITE microphone is reduced, preferably minimized, and a large maximum stable gain can be provided.

[0050] For example, in a hearing aid with one ITE microphone, and two BTE microphones constituting the at least

one BTE sound input transducer, and in the event that the incident sound field consist of sound emitted by a single speaker, the emitted sound having the short time spectrum $X(f,t)$; then, under the assumption that no pre-processing is performed with relation to the ITE microphone signal and that the ITE microphone reproduces the actual HRTF perfectly then the following signals are provided:

5

$$S^{IEC}(f,t) = HRTF(f)X(f,t) \quad (3)$$

10

$$S_{1,2}^{BTEC}(f,t) = H_{1,2}(f)X(f,t) \quad (4)$$

where $H_{1,2}(f)$ are the hearing aid related transfer functions of the two BTE microphones.

15 [0051] After sufficient adaptation, the hearing aid impulse response convolved with the resulting adapted filters and summed will be equal the actual HRTF so that

$$\lim_{t \rightarrow \infty} G_1(f,t)H_1(f) + G_2(f,t)H_2(f) = HRTF(f) \quad (5)$$

20

[0052] If the speaker moves and thereby changes the HRTF, the adaptive cue filters, i.e. the algorithm adjusting the filter coefficients, adapt towards the new minimum of minimization problem (2). The time constants of the adaptation are set to appropriately respond to changes of the current sound environment.

25 [0053] Feedback may be taken into account by performing the solution of the minimization problem (2) subject to the condition that the gain of the feedback loops must be less than one, i.e. subject to the condition that

$$\frac{1}{\|G_1^{BTEC}(f,t)H_{FB,1}^{BTEC}(f) + \dots + G_n^{BTEC}(f,t)H_{FB,n}^{BTEC}\|^2} \geq MSG(f) \quad (6)$$

wherein

35 $H_{FB,1}^{BTEC}(f), H_{FB,2}^{BTEC}(f), \dots, H_{FB,n}^{BTEC}(f)$ are the transfer functions of the feedback path associated with the n'th BTE microphone of the at least one BTE microphone, and $MSG(f)$ is the maximum stable gain,

[0054] In this way, it is ensured that a desired maximum stable gain will be available.

[0055] Alternatively, the requirement of spatial cue preservation and feedback cancellation may be balanced by solving:

40

$$\begin{aligned} \min_{G_1^{BTEC}(f,t) \dots G_n^{BTEC}(f,t)} & \|S^{IEC}(f,t) - G_1^{BTEC}(f,t)S_1^{BTEC}(f,t) - \dots - G_n(f,t)S_n^{BTEC}(f,t)\|^p \\ & + \alpha \|G_1^{BTEC}(f,t)H_{FB,1}^{BTEC}(f) + \dots + G_n^{BTEC}(f,t)H_{FB,n}^{BTEC}\|^p \end{aligned} \quad (7)$$

45

wherein

50 p is the norm factor, e.g. $p = 2$, and
 α is a weighting factor balancing spatial cue accuracy and feedback performance. α may be frequency dependent so that in a frequency range with low probability of feedback, α may be of low value, and in a frequency range with high probability of feedback, α may be of high value in order to take feedback appropriately into account in the frequency range in question.

55

[0056] The transfer functions $H_{FB,1}^{BTEC}(f), H_{FB,2}^{BTEC}(f), \dots, H_{FB,n}^{BTEC}(f)$ of the feedback paths may be modelled or ap-

proximated by an adaptive feedback cancellation circuit well-known in the art.

[0057] Various weights may be incorporated into the minimization problems above so that the solution is optimized as specified by the values of the weights. For example, frequency weights $W(f)$ may optimize the solution in certain one or more frequency ranges. Thus, the minimization problem may be modified into:

5

$$\begin{aligned} 10 \quad \text{Min}_{G_1^{BTEC}(f,t) \dots G_n^{BTEC}(f,t)} & \|W(f)(S^{IEC}(f,t) - G_1^{BTEC}(f,t)S_1^{BTEC}(f,t) \\ & - \dots - G_n(f,t)S_n^{BTEC}(f,t))\|^p \end{aligned} \quad (8)$$

subject to the condition that

15

$$\frac{1}{\|G_1^{BTEC}(f,t)H_{FB,1}^{BTEC}(f) + \dots + G_n^{BTEC}(f,t)H_{FB,n}^{BTEC}(f)\|^2} \geq MSG(f) \quad (9)$$

20

or

$$\begin{aligned} 25 \quad \min_{G_1^{BTEC}(f,t) \dots G_n^{BTEC}(f,t)} & \|W(f)(S^{IEC}(f,t) - G_1^{BTEC}(f,t)S_1^{BTEC}(f,t) - \dots - G_n^{BTEC}(f,t)S_n^{BTEC}(f,t))\|^p \\ & + \alpha \|G_1^{BTEC}(f,t)H_{FB,1}^{BTEC}(f) + \dots + G_n^{BTEC}(f,t)H_{FB,n}^{BTEC}(f)\|^p \end{aligned} \quad (10)$$

30

[0058] The target transfer function need not be defined by the HRTF for the various directions I. Any transfer function that includes spatial cues may be used as the target transfer function.

[0059] As used herein, the terms "processor", "signal processor", "controller", "system", etc., are intended to refer to CPU-related entities, either hardware, a combination of hardware and software, software, or software in execution.

35

[0060] For example, a "processor", "signal processor", "controller", "system", etc., may be, but is not limited to being, a process running on a processor, a processor, an object, an executable file, a thread of execution, and/or a program.

[0061] By way of illustration, the terms "processor", "signal processor", "controller", "system", etc., designate both an application running on a processor and a hardware processor.

40

[0062] One or more "processors", "signal processors", "controllers", "systems" and the like, or any combination hereof, may reside within a process and/or thread of execution, and one or more "processors", "signal processors", "controllers", "systems", etc., or any combination hereof, may be localized on one hardware processor, possibly in combination with other hardware circuitry, and/or distributed between two or more hardware processors, possibly in combination with other hardware circuitry.

45

[0063] The hearing aid may be a multi-channel hearing aid in which signals to be processed are divided into a plurality of frequency channels, and wherein signals are processed individually in each of the frequency channels. The adaptive feedback cancellation circuitry may also be divided into the plurality of frequency channels; or, the adaptive feedback cancellation circuitry may still operate in the entire frequency range; or, may be divided into other frequency channels, typically fewer frequency channels, than the other circuitry is divided into.

50

[0064] The processor may be configured for processing the output signals of the at least one ITE microphone and the at least one BTE sound input transducer in such a way that the hearing loss compensated output signal substantially preserves spatial cues in a selected frequency band.

[0065] The selected frequency band may comprise one or more of the frequency channels, or all of the frequency channels. The selected frequency band may be fragmented, i.e. the selected frequency band need not comprise consecutive frequency channels.

55

[0066] The plurality of frequency channels may include warped frequency channels, for example all of the frequency channels may be warped frequency channels.

[0067] Outside the selected frequency band, the at least one ITE microphone may be connected conventionally as an input source to the processor of the hearing aid and may cooperate with the processor of the hearing aid in a well-

known way.

[0068] In this way, the at least one ITE microphone supplies the input to the hearing aid at frequencies where the hearing aid is capable of supplying the desired gain with this configuration. In the selected frequency band, wherein the hearing aid cannot supply the desired gain with this configuration, the microphones of BTE hearing aid housing are included in the signal processing as disclosed above. In this way, the gain can be increased while simultaneously maintain the spatial information about the sound environment provided by the at least one ITE microphone.

[0069] The hearing aid may for example comprise a first filter connected between the processor input and the at least one ITE microphone, and a second complementary filter connected between the processor input and a combined output of the at least one BTE sound input transducer, the filters passing and blocking frequencies in complementary frequency bands so that one of the at least one ITE microphone and the combined output of at least one BTE sound input transducer constitutes the main part of the input signal supplied to the processor input in one frequency band, and the other one of the at least one ITE microphone and the combined output of at least one BTE sound input transducer constitutes the main part of the input signal supplied to the processor input in the complementary frequency band.

[0070] In this way, the at least one ITE microphone may be used as the sole input source to the processor in a frequency band wherein the required gain for hearing loss compensation can be applied to the output signal of the at least one ITE microphone. Outside this frequency band, the combined output signal of the at least one BTE sound input transducer is applied to the processor for provision of the required gain.

[0071] The combination of the signals could e.g. be based on different types of band pass filtering.

20 BRIEF DESCRIPTION OF THE DRAWINGS

[0072] In the following, preferred embodiments of the invention is explained in more detail with reference to the drawing, wherein

- 25 Fig. 1 shows a plot of the angular frequency spectrum of an open ear,
- Fig. 2 shows a plot of the angular frequency spectrum of a BTE front microphone worn at the same ear,
- 30 Fig. 3 shows plots of maximum stable gain of a BTE front and rear microphones and an open fitted ITE microphone positioned in the ear canal,
- Fig. 4 schematically illustrates an exemplary new hearing aid,
- 35 Fig. 5 schematically illustrates another exemplary new hearing aid,
- Fig. 6 shows in perspective a new hearing aid with an ITE-microphone in the outer ear of a user,
- Fig. 7 shows a schematic block diagram of a new hearing aid with adaptive cue filters,
- 40 Fig. 8 shows a schematic block diagram of the hearing aid of Fig. 7 with added feedback cancellation,
- Fig. 9 shows a schematic block diagram of a new hearing aid with an arbitrary number of microphones,
- Fig. 10 shows a schematic block diagram of a new hearing aid,
- 45 Fig. 11 shows a schematic block diagram of the hearing aid of Fig. 10 with added feedback cancellation, and
- Fig. 12 shows a schematic block diagram of the hearing aid of Fig. 11 with added adaptive filtering.

50 DETAILED DESCRIPTION OF THE DRAWINGS

[0073] The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. The invention may, however, be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like reference numerals refer to like elements throughout. Like elements will, thus, not be described in detail with respect to the description of each figure.

[0074] Fig. 4 schematically illustrates a BTE hearing aid 10 comprising a BTE hearing aid housing 12 (not shown -

outer walls have been removed to make internal parts visible) to be worn behind the pinna 100 of a user. The BTE housing 12 accommodates at least one BTE sound input transducer 14, 16 with a front microphone 14 and a rear microphone 16 for conversion of a sound signal into a microphone audio signal, optional pre-filters (not shown) for filtering the respective microphone audio signals, A/D converters (not shown) for conversion of the respective microphone audio signals into respective digital microphone audio signals that are input to a processor 18 configured to generate a hearing loss compensated output signal based on the input digital audio signals.

[0075] The hearing loss compensated output signal is transmitted through electrical wires contained in a sound signal transmission member 20 to a receiver 22 for conversion of the hearing loss compensated output signal to an acoustic output signal for transmission towards the eardrum of a user and contained in an earpiece 24 that is shaped (not shown) to be comfortably positioned in the ear canal of a user for fastening and retaining the sound signal transmission member in its intended position in the ear canal of the user as is well-known in the art of BTE hearing aids.

[0076] The earpiece 24 also holds one ITE microphone 26 that is positioned at the entrance to the ear canal when the earpiece is positioned in its intended position in the ear canal of the user. The ITE microphone 26 is connected to an A/D converter (not shown) and optional to a pre-filter (not shown) in the BTE housing 12, with electrical wires (not visible) contained in the sound transmission member 20.

[0077] The BTE hearing aid 10 is powered by battery 28.

[0078] Various possible functions of the processor 18 are disclosed above and some of these in more detail below.

[0079] Fig. 5 schematically illustrates another BTE hearing aid 10 similar to the hearing aid shown in Fig. 1, except for the difference that in Fig. 5, the receiver 22 is positioned in the hearing aid housing 12 and not in the earpiece 24, so that acoustic sound output by the receiver 22 is transmitted through the sound tube 20 and towards the eardrum of the user when the earpiece 24 is positioned in its intended position in the ear canal of the user.

[0080] The positioning of the ITE microphone 26 proximate the entrance to the ear canal of the user when the BTE hearing aids 10 of Figs. 4 and 5 are used is believed to lead to a good reproduction of the HRTFs of the user.

[0081] Fig. 6 shows a BTE hearing aid 10 in its operating position with the BTE housing 12 behind the ear, i.e. behind the pinna 100, of the user. The illustrated BTE hearing aid 10 is similar to the hearing aids shown in Figs. 4 and 5 except for the fact that the ITE microphone 26 is positioned in the outer ear of the user outside the ear canal at the free end of an arm 30. The arm 30 is flexible and the arm 30 is intended to be positioned inside the pinna 100, e.g. around the circumference of the conchae 102 behind the tragus 104 and antitragus 106 and abutting the antihelix 108 and at least partly covered by the antihelix for retaining its position inside the outer ear of the user. The arm may be pre-formed during manufacture, preferably into an arched shape with a curvature slightly larger than the curvature of the antihelix 104, for easy fitting of the arm 30 into its intended position in the pinna. The arm 30 contains electrical wires (not visible) for interconnection of the ITE microphone 26 with other parts of the BTE hearing aid circuitry.

[0082] In one example, the arm 30 has a length and a shape that facilitate positioning of the ITE microphone 26 in an operating position below the triangular fossa.

[0083] Fig. 7 is a block diagram illustrating one example of signal processing in the new hearing aid 10. The illustrated hearing aid 10 has a front microphone 14 and a rear microphone 16 accommodated in the BTE hearing aid housing configured to be worn behind the pinna of the user, for conversion of sound signals arriving at the microphones 14, 16 into respective audio signals 33, 35. Further, the illustrated hearing aid 10 has an ITE microphone 26 accommodated in an earpiece (not shown) to be positioned in the outer ear of the user, for conversion of sound signals arriving at the microphone 26 into audio signal 31.

[0084] The microphone audio signals 31, 33, 35 are digitized and pre-processed, such as prefiltered, in respective pre-processors 32, 34, 36. The pre-processed audio signals 38, 40 of the front and rear microphones 14, 16 are filtered in respective adaptive cue filters 42, 44, and the adaptively filtered signals 46, 48 are added to each other in adder 50 and the combined signal 52 is input to processor 18 for hearing loss compensation. The hearing loss compensated signal 54 is output to the receiver 22 that converts the signal 54 to an acoustic output signal for transmission towards the ear drum of the user.

[0085] Adaptation of the filter coefficients of adaptive cue filters 42, 44 are controlled by adaptive controller 56 that controls the adaptation of the filter coefficients to reduce, and preferably eventually minimize, the difference 58 between the output 52 of adder 46 and the pre-processed ITE microphone audio signal 60, output by subtractor 62. In this way, the input signal 52 to the processor 18 models the microphone audio signal 60 of the ITE microphone 26, and thus also substantially models the HRTFs of the user.

[0086] The pre-processed output signal 60 of the ITE microphone 26 of the earpiece has a short time spectrum denoted $S^{IEC}(f, t)$ (IEC = In the Ear Component).

[0087] The spectra of the pre-processed audio signals 38, 40 of the front and rear microphones 14, 16 are denoted

$S_1^{BTEC}(f, t)$, and $S_2^{BTEC}(f, t)$ (BTEC = Behind The Ear Component).

[0088] Pre-processing may include, without excluding any form of processing; adaptive and/or static feedback sup-

pression, adaptive or fixed beamforming and pre-filtering.

[0089] The adaptive controller 56 is configured to control the filter coefficients of adaptive cue filters 42, 44 so that their summed output 52 corresponds to the pre-processed output signal 60 of the ITE microphone 26 as closely as possible.

[0090] The adaptive cue filters 42, 44 have the respective transfer functions: $G_1(f, t)$, and $G_2(f, t)$.

[0091] The ITE microphone 26 operates as monitor microphone for generation of an audio signal 60 with the desired spatial information of the current sound environment due to its positioning in the outer ear of the user.

[0092] Thus, the filter coefficients of the adaptive cue filters 34, 36 are adapted to obtain an exact or approximate solution to the minimization problem:

10

$$\min_{G_1(f, t), G_2(f, t)} \|S^{IEC}(f, t) - G_1(f, t) S_1^{BTEC}(f, t) - G_2(f, t) S_2^{BTEC}(f, t)\|^p \quad (11)$$

15

wherein p is the norm-factor, preferably $p = 2$.

[0093] The algorithm controlling the adaption could (without being restricted to) e.g. be based on least mean square (LMS) or recursive least squares (RLS), possibly normalized, optimization methods in which $p = 2$.

[0094] Subsequent to the adaptive cue filtering, the combined output signal 52 of the adaptive cue filters 42, 44 is passed on for further hearing loss compensation processing, e.g. in a compressor. In this way, only signals from the front and rear microphones 14, 16 are possibly amplified as a result of hearing loss compensation while the audio signal 60 of the ITE microphone 26 is not processed in the processor 18 configured for hearing loss processing, whereby possible feedback from the output transducer 22 to the ITE microphone 26 is reduced, preferably minimized, and a large maximum stable gain can be provided.

[0095] For example, in the event that the incident sound field consists of sound emitted by a single speaker, the emitted sound having the short time spectrum $X(f, t)$; then, under the assumption that no pre-processing is performed with relation to the ITE microphone signal 60 and that the ITE microphone 26 reproduces the actual HRTF perfectly then the following signals are provided:

30

$$S^{IEC}(f, t) = HRTF(f)X(f, t) \quad (12)$$

35

$$S_{1,2}^{BTEC}(f, t) = H_{1,2}(f)X(f, t) \quad (13)$$

where $H_{1,2}(f)$ are the hearing aid related transfer functions of the two BTE microphones 14, 16.

[0096] After sufficient adaptation, the hearing aid impulse response convolved with the resulting adapted filters and summed will be equal the actual HRTF so that

45

$$\lim_{t \rightarrow \infty} G_1(f, t) H_1(f) + G_2(f, t) H_2(f) = HRTF(f) \quad (14)$$

[0097] If the speaker moves and thereby changes the actual HRTF, the adaptive cue filters 42, 44, i.e. the adaptive controller 56 by adjusting the filter coefficients, adapt towards the new minimum of the minimization problem (11). The time constants of the adaptation are set to appropriately respond to changes of the current sound environment.

[0098] In the event that feedback occurs in the hearing aid, adaptation may be stopped, i.e. the filter coefficients may be prevented from changing, or the adaptation rate may be slowed down, in order to avoid that feedback is transferred from the audio signal of the at least one ITE microphone to the output signal(s) of the at least one BTE sound input transducer during presence of feedback.

[0099] The filter coefficients of the adaptive cue filters 42, 44 may be predetermined so that a set of filter coefficients is provided for a specific HRTF.

[0100] The sets of filter coefficients, one set for each predetermined HRTF, may be determined using a manikin, such as KEMAR. The filter coefficients are determined for a number of direction of arrivals for the hearing aid as disclosed above; however under controlled conditions and allowing adaptation of long duration. In this way, an approximation to the individual HRTFs is provided that can be of sufficient accuracy for the hearing aid user to maintain sense of direction

when wearing the hearing aid.

[0101] During use, the set of filter coefficients is selected that reduces, and preferably eventually minimizes, the difference between the combined output signal, possibly pre-processed, of the at least one BTE sound input transducer and the output signal, possibly pre-processed, of the at least one ITE microphone. During use, the adaptive cue filter 5 may be allowed to further adapt to the individual HRTF of the user in question. The adaptation may be stopped when the filter coefficients have become stable so that the at least one ITE microphone is no longer used for the HRTF in question.

[0102] The new hearing aid circuitry shown in Fig. 7 may operate in the entire frequency range of the hearing aid 10.

[0103] The hearing aid 10 shown in Fig. 7 may be a multi-channel hearing aid in which microphone audio signals 38, 10 40, 60 to be processed are divided into a plurality of frequency channels, and wherein signals are processed individually in each of the frequency channels.

[0104] For a multi-channel hearing aid 10, Fig. 7 may illustrate the circuitry and signal processing in a single frequency channel. The circuitry and signal processing may be duplicated in a plurality of the frequency channels, e.g. in all of the frequency channels.

[0105] For example, the signal processing illustrated in Fig. 7 may be performed in a selected frequency band, e.g. selected during fitting of the hearing aid to a specific user at a dispenser's office.

[0106] The selected frequency band may comprise one or more of the frequency channels, or all of the frequency channels. The selected frequency band may be fragmented, i.e. the selected frequency band need not comprise consecutive frequency channels.

[0107] The plurality of frequency channels may include warped frequency channels, for example all of the frequency channels may be warped frequency channels.

[0108] Outside the selected frequency band, the ITE microphone 26 may be connected conventionally as an input source to the processor 18 of the hearing aid 10 and may cooperate with the processor 18 of the hearing aid 10 in a well-known way.

[0109] In this way, the ITE microphone supplies the input to the hearing aid at frequencies where the hearing aid is capable of supplying the desired gain with this configuration. In the selected frequency band, wherein the hearing aid cannot supply the desired gain with this configuration, the microphones 14, 16 of BTE hearing aid housing are included in the signal processing as disclosed above. In this way, the gain can be increased while the spatial information of the sound environment as provided by the ITE microphone is simultaneously maintained.

[0110] Fig. 8 is a block diagram illustrating a new hearing aid 10 similar to the hearing aid 10 shown in Fig. 7 except for the fact that adaptive feedback cancellation circuitry has been added, including an adaptive feedback filter 70 with an input 72 connected to the output of the hearing aid processor 18 and with outputs 74-1, 76-1, 76-2, each of which is connected to a respective subtractor 78-1, 80-1, 80-2 for subtraction of each output 74-1, 76-1, 76-2 from a respective microphone output 31, 33, 35 to provide a respective feedback compensated signal 82-1, 84-1, 84-2 as is well-known in the art. Each feedback compensated signal 82-1, 84-1, 84-2 is fed to the corresponding preprocessor 32, 34, 36, and also to the adaptive feedback filter 70 for control of the adaption of the adaptive feedback filter 70. The adaptive feedback filter outputs 74-1,

[0111] 76-1, 76-2 provide signals that constitute approximations of corresponding feedback signals travelling from the output transducer 22 to the respective microphone 14, 16, 26 as is well-known in the art. The outputs 76-1, 76-2 approximating feedback signals of the BTE microphones are further connected to the adaptive controller 56.

[0112] The adaptive controller 56 of Fig. 8 controls adjustment of the filter coefficients of adaptive cue filters 38, 40 by solving minimization problem (11) subject to the condition that

$$45 \quad \frac{1}{\| G_1(f,t)H_{FB,1}^{BTEC}(f) + G_2(f,t)H_{FB,n}^{BTEC} \|^2} \geq MSG(f) \quad (15)$$

or

50 by solving minimization problem

$$55 \quad \begin{aligned} \min_{G_1(f,t) G_2(f,t)} & \| W(f)(S^{IEC}(f,t) - G_1(f,t)S_1^{BTEC}(f,t) - G_2(f,t)S_2^{BTEC}(f,t)) \|^p \\ & + \alpha \| G_1(f,t)H_{FB,1}^{BTEC}(f) + \dots + G_2(f,t)H_{FB,n}^{BTEC} \|^p \end{aligned} \quad (16)$$

[0113] in order to preserve spatial cue and simultaneously take feedback into account.

[0114] Typically $p = 2$, and/or $W(f) = 1$.

[0115] The new hearing aid circuitry shown in Fig. 8 may operate in the entire frequency range of the hearing aid 10.

[0116] The hearing aid 10 shown in Fig. 8 may be a multi-channel hearing aid in which microphone audio signals 38, 40, 60 to be processed are divided into a plurality of frequency channels, and wherein signals are processed individually in each of the frequency channels possibly apart from the adaptive feedback cancellation circuitry 70, 72, 74-1, 74-2, 76-1, 76-2, 78-1, 78-2, 80-1, 80-2, 82-1, 82-2, 84-1, 84-2 that may still operate in the entire frequency range; or, may be divided into other frequency channels, typically fewer frequency channels than the remaining illustrated circuitry.

[0117] For a multi-channel hearing aid 10, the part of Fig. 8 corresponding to the circuitry of Fig. 7 may illustrate the circuitry and signal processing in a single frequency channel, while the adaptive circuitry that may still operate in the entire frequency range; or, may be divided into other frequency channels, typically fewer frequency channels than the remaining illustrated circuitry.

[0118] The circuitry and signal processing may be duplicated in a plurality of the frequency channels, e.g. in all of the frequency channels.

[0119] For example, the signal processing illustrated in Fig. 8 may be performed in a selected frequency band, e.g. selected during fitting of the hearing aid to a specific user at a dispenser's office.

[0120] The selected frequency band may comprise one or more of the frequency channels, or all of the frequency channels. The selected frequency band may be fragmented, i.e. the selected frequency band need not comprise consecutive frequency channels.

[0121] The plurality of frequency channels may include warped frequency channels, for example all of the frequency channels may be warped frequency channels.

[0122] Outside the selected frequency band, the at least one ITE microphone may be connected conventionally as an input source to the processor of the hearing aid and may cooperate with the processor of the hearing aid in a well-known way.

[0123] In this way, the at least one ITE microphone supplies the input to the hearing aid at frequencies where the hearing aid is capable of supplying the desired gain with this configuration. In the selected frequency band, wherein the hearing aid cannot supply the desired gain with this configuration, the microphones of BTE hearing aid housing are included in the signal processing as disclosed above. In this way, the gain can be increased while simultaneously maintain the spatial information about the sound environment provided by the at least one ITE microphone.

[0124] Fig. 9 is a block diagram illustrating a new hearing aid 10 similar to the hearing aid 10 shown in Fig. 7 and operating in a way similar to the hearing aid 10 shown in Fig. 7, except for the fact that the circuit has been generalized to include an arbitrary number N of ITE microphones 26-1, 26-2, ..., 26- N , and an arbitrary number M of BTE microphones 14-1, 14-2, ..., 14- M . In Fig. 7, $N=1$ and $M = 2$. In Fig. 9, N and M can be any non-negative integer.

[0125] The output signals 31-1, 31-2, ..., 31- N from the N ITE microphones 26-1, 26-2, ..., 26- N are delayed by delays 41-1, 41-2, ..., 41- N after pre-processing in pre-processors 32-1, 32-2, ..., 32- N to compensate for the delays of the output signals 33-1, 33-2, ..., 33- M from the M BTE microphones 14-1, 14-2, ..., 14- M , caused by the adaptive cue filters 42-1, 42-2, ..., 42- M . The delays 41-1, 41-2, ..., 41- N may also be used for beamforming. The output signals 31-1, 31-2, ..., 31- N from the N ITE microphones 26-1, 26-2, ..., 26- N are further combined in the signal combiner 64, e.g. as a weighted sum, and the output 60 of the signal combiner 64 is fed to a subtractor 72 as in the circuit shown in Fig. 7.

[0126] Likewise, the output signals 33-1, 33-2, ..., 33- M from the M BTE microphones are pre-processed in pre-processors 34-1, 34-2, ..., 34- M and filtered in the respective adaptive cue filters 42-1, 42-2, ..., 42- M and combined in the signal combiner 50, e.g. as a weighted sum, and the output 52 of the signal combiner 50 is fed to the subtractor 62 and the hearing aid processor 18 as in the circuit of Fig. 7.

[0127] The adaptive controller 56 controls the adaptation of the filter coefficients of adaptive cue filters 42-1, 42-2, ..., 42- M to reduce, and preferably eventually minimize, the difference 58 between the output of BTE signal combiner 50 and ITE signal combiner 64, provided by subtractor 62, e.g. by solving the minimization problem (2) already mentioned above:

$$50 \quad \min_{G_1(f,t) \dots G_m(f,t)} \|W(f)((S^{IEC}(f,t) - G_1(f,t)S_1^{BTEC}(f,t) - \dots - G_m(f,t)S_m^{BTEC}(f,t))\|^p$$

Wherein S^{IEC} is the output signal 60 of signal combiner 64, and $G_1(f,t), G_2(f,t), \dots, G_n(f,t)$ are the transfer functions of the respective adaptive cue filters 42-1, 42-2, ..., 42- M .

[0128] Typically $p = 2$, and/or $W(f) = 1$.

[0129] Possible weights in the signal combination performed by the signal combiner 58 are included in the transfer functions $G_1(f,t), G_2(f,t), \dots, G_n(f,t)$. These weights may be frequency dependent.

[0130] In this way, the output signal 52 of the BTE signal combiner 50 models the combined ITE microphone audio

signal 60 of the ITE microphones 26-1, 26-2, ..., 26-N, and thus also substantially models the HRTFs of the user.

[0131] The new hearing aid circuitry shown in Fig. 9 may operate in the entire frequency range of the hearing aid 10.

[0132] The hearing aid 10 shown in Fig. 9 may be a multi-channel hearing aid in which microphone audio signals 31-1, 31-2, ..., 31-N, 33-1, 33-2, ..., 33-M to be processed are divided into a plurality of frequency channels, and wherein signals are processed individually in each of the frequency channels.

[0133] For a multi-channel hearing aid 10, Fig. 9 may illustrate the circuitry and signal processing in a single frequency channel. The circuitry and signal processing may be duplicated in a plurality of the frequency channels, e.g. in all of the frequency channels. For example, the signal processing illustrated in Fig. 9 may be performed in a selected frequency band, e.g. selected during fitting of the hearing aid to a specific user at a dispenser's office.

[0134] The selected frequency band may comprise one or more of the frequency channels, or all of the frequency channels. The selected frequency band may be fragmented, i.e. the selected frequency band need not comprise consecutive frequency channels.

[0135] The plurality of frequency channels may include warped frequency channels, for example all of the frequency channels may be warped frequency channels.

[0136] Outside the selected frequency band, the at least one ITE microphone 26-1, 26-2, ..., 26-N may be connected conventionally as an input source to the processor 18 of the hearing aid 10 and may cooperate with the processor 18 of the hearing aid 10 in a well-known way.

[0137] In this way, the at least one ITE microphone 26-1, 26-2, ..., 26-N supply the input to the hearing aid at frequencies where the hearing aid is capable of supplying the desired gain with this configuration. In the selected frequency band, wherein the hearing aid cannot supply the desired gain with this configuration, the microphones 14-1, 14-2, ..., 14-M of BTE hearing aid housing are included in the signal processing as disclosed above. In this way, the gain can be increased while simultaneously maintain the spatial information about the sound environment provided by the at least one ITE microphone.

[0138] In the hearing aid 10 shown in Fig. 10, adaptive feedback cancellation has been added to the hearing aid shown in Fig. 9 similar to the way illustrated in Fig. 8 in comparison with Fig. 7, i.e. an adaptive feedback filter 70 is added with an input 72 connected to the output of the hearing aid processor 18 and outputs 74-1, 74-2, ..., 74-N, 76-1, 76-2, ..., 76-M connected to subtractors 78-1, 78-2, ..., 78-N, 80-1, 80-2, ..., 80-M for subtraction of each output from a respective microphone output to provide a feedback compensated signal 82-1, 82-2, ..., 82-N, 84-1, 84-2, ..., 84-M fed to the corresponding pre-processing circuits 32-1, 32-2, ..., 32-N, 34-1, 34-2, ..., 34-M and to the adaptive feedback filter 70 for control of the adaption of the adaptive feedback filter 70. The adaptive feedback filter outputs 74-1, 74-2, ..., 74-N, 76-1, 76-2, ..., 76-M provide signals that constitute approximations of corresponding feedback signals travelling from the output transducer 22 to the respective microphones 26-1, 26-2, ..., 26-N, 14-1, 14-2, ..., 14-M as is well-known in the art.

[0139] Further, the outputs 76-1, 76-2, ..., 76-M approximating feedback signals of the BTE microphones 14-1, 14-2, ..., 14-M are connected to the adaptive controller 56 that controls the filter coefficients of adaptive cue filters 42-1, 42-2, ..., 42-M.

[0140] in accordance with, e.g. equation 1 subject to condition 1, or equation 5, in order to preserve spatial cue and simultaneously take feedback into account.

[0141] The adaptive controller 56 controls the adaptation of the filter coefficients of adaptive cue filters 42-1, 42-2, ..., 42-M to reduce, and preferably eventually minimize, the difference 58 between the output 60 of the ITE signal combiner 64 and the output 52 of BTE signal combiner 50, provided by subtractor 62, e.g. by solving the minimization problem:

$$\begin{aligned}
 & \underset{G_1^{BTEC}(f,t) \dots G_n^{BTEC}(f,t)}{\text{Min}} \|W(f)(S^{IEC}(f,t) - G_1^{BTEC}(f,t)S_1^{BTEC}(f,t) \\
 & \quad - \dots - G_n(f,t)S_n^{BTEC}(f,t))\|^p
 \end{aligned} \tag{8}$$

subject to the condition that

$$\frac{1}{\|G_1^{BTEC}(f,t)H_{FB,1}^{BTEC}(f) + \dots + G_n^{BTEC}(f,t)H_{FB,n}^{BTEC}\|^2} \geq MSG(f) \tag{9}$$

or

$$\begin{aligned}
 & \min_{G_1^{BTEC}(f,t) \dots G_n^{BTEC}(f,t)} \|W(f)(S^{IEC}(f,t) - G_1^{BTEC}(f,t)S_1^{BTEC}(f,t) - \dots - G_n^{BTEC}(f,t)S_n^{BTEC}(f,t))\|^p \\
 & + \alpha \|G_1^{BTEC}(f,t)H_{FB,1}^{BTEC}(f) + \dots + G_n^{BTEC}(f,t)H_{FB,n}^{BTEC}\|^p
 \end{aligned} \tag{10}$$

wherein S^{IEC} is the output signal 60 of signal combiner 64, and $G_1(f,t)$, $G_2(f,t)$, ..., $G_n(f,t)$ are the transfer functions of the respective adaptive cue filters 42-1, 42-2, ..., 42-M.

[0142] Typically $p = 2$, and/or $W(f) = 1$.

[0143] Possible weights in the signal combination performed by the signal combiner 58 are included in the transfer functions $G_1(f,t)$, $G_2(f,t)$, ..., $G_n(f,t)$. These weights may be frequency dependent.

[0144] In this way, the output signal 52 of the BTE signal combiner 50 models the combined ITE microphone audio signal 60 of the ITE microphones 26-1, 26-2, ..., 26-N, and thus also substantially models the HRTFs of the user.

[0145] The new hearing aid circuitry shown in Fig. 10 may operate in the entire frequency range of the hearing aid 10.

[0146] Like the hearing aids shown in Figs. 7 - 9, the hearing aid 10 shown in Fig. 10 may be a multi-channel hearing aid in which microphone audio signals 31-1, 31-2, ..., 31-N, 33-1, 33-2, ..., 33-M to be processed are divided into a plurality of frequency channels, and wherein signals are processed individually in each of the frequency channels, possibly apart from the adaptive feedback cancellation circuitry 70, 72, 74-1, 74-2, ..., 74-N, 76-1, 76-2, ..., 76-M, 78-1, 78-2, ..., 78-N, 80-1, 80-2, ..., 80-M, 82-1, 82-2, ..., 82-N, 84-1, 84-2, ..., 84-M, 86 that may still operate in the entire frequency range; or, may be divided into other frequency channels, typically fewer frequency channels than the remaining illustrated circuitry.

[0147] As in Figs. 7 - 9, Fig. 10 may also illustrate the circuitry and signal processing in a single frequency channel of a multi-channel hearing aid 10. The circuitry and signal processing may be duplicated in a plurality of the frequency channels, e.g. in all of the frequency channels apart from the adaptive circuitry that may still operate in the entire frequency range; or, may be divided into its own frequency channels, typically with fewer frequency channels than the remaining illustrated circuitry.

[0148] For a multi-channel hearing aid 10, the part of Fig. 10 corresponding to the circuitry of Fig. 9 may illustrate the circuitry and signal processing in a single frequency channel, while the adaptive circuitry may still operate in the entire frequency range; or, may be divided into other frequency channels, typically fewer frequency channels than the remaining illustrated circuitry.

[0149] The illustrated circuitry and signal processing may be duplicated in a plurality of the frequency channels, e.g. in all of the frequency channels.

[0150] For example, the signal processing illustrated in Fig. 10 may be performed in a selected frequency band, e.g. selected during fitting of the hearing aid to a specific user at a dispenser's office.

[0151] The selected frequency band may comprise one or more of the frequency channels, or all of the frequency channels. The selected frequency band may be fragmented, i.e. the selected frequency band need not comprise consecutive frequency channels.

[0152] The plurality of frequency channels may include warped frequency channels, for example all of the frequency channels may be warped frequency channels.

[0153] Outside the selected frequency band, the at least one ITE microphone may be connected conventionally as an input source to the processor 18 of the hearing aid and may cooperate with the processor 18 of the hearing aid in a well-known way.

[0154] In this way, the at least one ITE microphone 26-1, 26-2, ..., 26-N supply the input to the hearing aid at frequencies where the hearing aid is capable of supplying the desired gain with this configuration. In the selected frequency band, wherein the hearing aid cannot supply the desired gain with this configuration, the microphones of BTE hearing aid housing are included in the signal processing as disclosed above. In this way, the gain can be increased while simultaneously maintain the spatial information about the sound environment provided by the at least one ITE microphone.

[0155] The hearing aid 10 shown in Fig. 11 is similar to the hearing aid 10 shown in Fig. 10 and operates in the same way, apart from the fact that, in Fig. 11, a signal combiner 66 has been inserted in front of the processor 18. The added signal combiner 66 comprises first filters connected between the processor input and the output 60 of the signal combiner 64 of the at least one ITE microphone 26-1, 26-2, ..., 26-N, and second complementary filters connected between the processor input and the output 52 of the signal combiner 50 of the at least one BTE microphone 14-1, 14-2, ..., 14-M, the filters passing and blocking, respectively, frequencies in complementary frequency bands so that the output 60 of the signal combiner 64 of the at least one ITE microphone 26-1, 26-2, ..., 26-N constitutes the main part of the input signal 68 supplied to the processor input in one or more first frequency bands, and the output 52 of the signal combiner 50 of the at least one BTE microphone 14-1, 14-2, ..., 14-M constitutes the main part of the input signal 68 supplied to the processor input in one or more complementary second frequency bands.

[0156] In this way, the at least one ITE microphone 26-1, 26-2, ..., 26-N may be used as the sole input source to the processor 18 in one or more frequency bands wherein the required gain for hearing loss compensation can be applied to the output signal 60 of the at least one ITE microphone 26-1, 26-2, ..., 26-N. Outside these one or more frequency bands, the combined output signal 52 of the at least one BTE sound input transducer 14-1, 14-2, ..., 14-M is applied to the processor 18 for provision of the required gain.

[0157] The combination of the signals performed in signal combiner 66 could e.g. be based on different types of band pass filtering.

[0158] The hearing aid 10 shown in Fig. 11 may be a multi-channel hearing aid in which microphone audio signals 31-1, 31-2, ..., 31-N, 33-1, 33-2, ..., 33-M to be processed are divided into a plurality of frequency channels, and wherein signals are processed individually in each of the frequency channels possibly apart from the adaptive feedback cancellation circuitry 70, 72, 74-1, 74-2, ..., 74-N, 76-1, 76-2, ..., 76-M, 78-1, 78-2, ..., 78-N, 80-1, 80-2, ..., 80-M, 82-1, 82-2, ..., 82-N, 84-1, 84-2, ..., 84-M, 86 that may still operate in the entire frequency range; or, may be divided into other frequency channels, typically fewer frequency channels than the remaining illustrated circuitry. The signal combiner 66 may connect the audio signal 60 of the at least one ITE microphone 26-1, 26-2, ..., 26-N as the sole input source to the processor 18 in one or more frequency channels in which no feedback is expected, and the combined output signal 52 of the at least one BTE sound input transducer 14-1, 14-2, ..., 14-M in frequency channels with risk of feedback..

[0159] The hearing aid 10 shown in Fig. 12 is similar to the hearing aid 10 shown in Fig. 11 and operates in the same way, apart from the fact that, in Fig. 12, the signal combiner 66 is adaptive, e.g. so that the interconnections of the output 60 of the signal combiner 64 of the at least one ITE microphone 26-1, 26-2, ..., 26-N and the output 52 of the signal combiner 50 of the at least one BTE microphone 14-1, 14-2, ..., 14-M can be changed during operation of the hearing aid 10, e.g. in response to the status of the feedback loops, whereby, the at least one ITE microphone 26-1, 26-2, ..., 26-N may be used as the sole input source to the processor 18 in one or more frequency bands in which no feedback is currently present, whereas in one or more frequency bands in which feedback is evolving, the combined output signal 52 of the at least one BTE sound input transducer 14-1, 14-2, ..., 14-M is applied to the processor 18 for provision of the required gain without feedback.

[0160] The hearing aid 10 shown in Fig. 12 may be a multi-channel hearing aid in which microphone audio signals 31-1, 31-2, ..., 31-N, 33-1, 33-2, ..., 33-M to be processed are divided into a plurality of frequency channels, and wherein signals are processed individually in each of the frequency channels possibly apart from the adaptive feedback cancellation circuitry 70, 72, 74-1, 74-2, ..., 74-N, 76-1, 76-2, ..., 76-M, 78-1, 78-2, ..., 78-N, 80-1, 80-2, ..., 80-M, 82-1, 82-2, ..., 82-N, 84-1, 84-2, ..., 84-M, 86 that may still operate in the entire frequency range; or, may be divided into other frequency channels, typically fewer frequency channels than the remaining illustrated circuitry. The signal combiner 66 may adaptively connect the audio signal 60 of the at least one ITE microphone 26-1, 26-2, ..., 26-N as the sole input source to the processor 18 in one or more frequency channels in which no feedback instability is currently present, and the combined output signal 52 of the at least one BTE sound input transducer 14-1, 14-2, ..., 14-M in frequency channels with current risk of feedback.

Claims

40 1. A hearing aid comprising

a BTE hearing aid housing configured to be worn behind the pinna of a user,
 at least one BTE sound input transducer accommodated in the BTE hearing aid housing, each of which is configured for conversion of acoustic sound into a respective audio signal,
 45 an ITE microphone housing configured to be positioned in the outer ear of the user for fastening and retaining, in its intended position,
 at least one ITE microphone accommodated in the ITE microphone housing, each of which is configured for conversion of acoustic sound into a respective audio signal,
 at least one adaptive cue filter, each of which having

50 an input that is provided with an output signal from a respective one of the at least one BTE sound input transducer, and
 the filter coefficients of which are adapted so that the difference between an output of the at least one ITE microphone and a combined output of the at least one adaptive cue filter is reduced,

55 a processor configured to generate a hearing loss compensated output signal based on a combination of the filtered audio signals output by the at least one cue filter,
 an output transducer for conversion of the hearing loss compensated output signal to an auditory output signal

that can be received by the human auditory system,
an adaptive feedback canceller for feedback suppression and having

5 an input connected to an output of the processor for reception of the hearing loss compensated output signal,
at least one output modelling the feedback path from the output of the output transducer to the respective
at least one BTE microphone and connected to
a subtractor for subtraction of the at least one output from the output of the respective at least one BTE
microphone and outputting the difference to the respective at least one adaptive cue filter,
characterized in that the hearing aid further comprises
10 a feedback and cue controller with inputs connected to the at least one output of the adaptive feedback
canceller and the output of the at least one adaptive cue filter, and configured to control the at least one
adaptive cue filter so that the difference between an output of the at least one ITE microphone and a
combined output of the at least one adaptive cue filter is reduced and so that feedback is reduced.

15 2. A hearing aid according to claim 1, wherein the filter coefficients of the at least one adaptive cue filter are adapted
towards a solution of:

$$20 \min_{G_1^{BTEC}(f,t) \dots G_n^{BTEC}(f,t)} \|W(f)(S^{IEC}(f,t) - G_1^{BTEC}(f,t)S_1^{BTEC}(f,t) - \dots - G_n(f,t)S_n^{BTEC}(f,t))\|^p \\ + \alpha \|G_1^{BTEC}(f,t)H_{FB,1}^{BTEC}(f) + \dots + G_n^{BTEC}(f,t)H_{FB,n}^{BTEC}\|^p$$

25 wherein

25 $S^{IEC}(f, t)$ is the short time spectrum at time t of the output signal of the at least one ITE microphone, and

30 $S_1^{BTEC}(f,t), S_2^{BTEC}(f,t), \dots, S_n^{BTEC}(f,t)$ are the short time spectra at time t of the output signals of the
at least one BTE sound input transducer, and

35 $G_1^{BTEC}(f,t), G_2^{BTEC}(f,t), \dots, G_n^{BTEC}(f,t)$ are the transfer functions of pre-processing filters connected
to respective outputs of the at least one BTE sound input transducer, and

35 $H_{FB,1}^{BTEC}(f), H_{FB,2}^{BTEC}(f), \dots, H_{FB,n}^{BTEC}(f)$ are the transfer functions of the feedback path associated with the n 'th

BTE microphone of the at least one BTE microphone,

α is the norm factor,

$W(f)$ is a frequency dependent weighting factor, and

α is a weighting factor balancing spatial cue accuracy and feedback performance.

40 3. A hearing aid according to claim 1, wherein the filter coefficients of the at least one adaptive cue filter are adapted
towards a solution of:

$$45 \min_{G_1^{BTEC}(f,t) \dots G_n^{BTEC}(f,t)} \|W(f)(S^{IEC}(f,t) - G_1^{BTEC}(f,t)S_1^{BTEC}(f,t) \\ - \dots - G_n(f,t)S_n^{BTEC}(f,t))\|^p$$

50 subject to the condition that

$$55 \frac{1}{\|G_1^{BTEC}(f,t)H_{FB,1}^{BTEC}(f) + \dots + G_n^{BTEC}(f,t)H_{FB,n}^{BTEC}\|^2} \geq MSG(f)$$

wherein

$S^{ITEC}(f, t)$ is the short time spectrum at time t of the output signal of the at least one ITE microphone, and

5 $S_1^{BTEC}(f, t), S_2^{BTEC}(f, t), \dots, S_n^{BTEC}(f, t)$ are the short time spectra at time t of the output signals of the at least one BTE sound input transducer, and

10 $G_1^{BTEC}(f, t), G_2^{BTEC}(f, t), \dots, G_n^{BTEC}(f, t)$ are the transfer functions of pre-processing filters connected to respective outputs of the at least one BTE sound input transducer,

15 $H_{FB,1}^{BTEC}(f), H_{FB,2}^{BTEC}(f), \dots, H_{FB,n}^{BTEC}(f)$ are the transfer functions of the feedback path associated with the n 'th BTE microphone of the at least one BTE microphone,

p is the norm factor, and

$MSG(f)$ is the maximum stable gain,

15 4. A hearing aid according to any of the preceding claims, further comprising a memory for accommodation of sets of filter coefficients of the at least one adaptive cue filter, each set of filter coefficients having been determined for a specific direction of arrival with relation to the hearing aid by the adaptation of the at least one adaptive cue filter for the direction of arrival in question.

20 5. A hearing aid according to claim 4, wherein the at least one adaptive cue filter is loaded with the set of filter coefficients that provides minimum difference between an output of the at least one ITE microphone and a combined output of the at least one adaptive cue filter.

25 6. A hearing aid according to claim 5, wherein the at least one adaptive cue filter is allowed to further adapt after loading.

7. A hearing aid according to any of the preceding claims, wherein the at least one adaptive cue filter is prevented from further adapting when the filter coefficient values have ceased changing significantly.

30 8. A hearing aid according to any of the preceding claims, wherein the audio signals are divided into a plurality of frequency channels, and wherein the at least one adaptive cue filter is configured for individually processing the audio signals in selected frequency channels.

35 9. A hearing aid according to claim 8, wherein the at least one BTE microphone is disconnected from the processor in a selected frequency channel so that hearing loss compensation is based solely on the output of the at least one ITE microphone.

10. A hearing aid according to any of the preceding claims, wherein

40 the at least one BTE sound input transducer is constituted by a first and a second BTE sound input transducer, and the at least one adaptive cue filter is constituted by a first and second adaptive cue filter, wherein

the first adaptive cue filter has an input that is provided with an output signal from the first BTE sound input transducer, and

45 the filter coefficients of the first adaptive cue filter are adapted so that the difference between an output of the at least one ITE microphone and a combined output of the first and second adaptive cue filters is reduced. the second adaptive cue filter has an input that is provided with an output signal from the second BTE sound input transducer, and

50 the filter coefficients of the second adaptive cue filter are adapted so that the difference between an output of the at least one ITE microphone and a combined output of the first and second adaptive cue filters is reduced.

11. A hearing aid according to any of the preceding claims, wherein α is frequency dependent.

12. A hearing aid according to any of the preceding claims, wherein $W(f) = 1$.

55 13. A hearing aid according to any of the preceding claims, wherein $p = 2$.

14. A hearing aid according to any of the preceding claims, comprising a sound signal transmission member for transmission of a sound signal from a sound output in the BTE hearing aid housing at a first end of the sound signal transmission member to the ear canal of the user at a second end of the sound signal transmission member, an earpiece configured to be inserted in the ear canal of the user for fastening and retaining the sound signal transmission member in its intended position in the ear canal of the user.

5

10

15

20

25

30

35

40

45

50

55




Fig. 1




Fig. 2






Fig. 3






Fig. 6





Fig. 7






Fig. 9




Fig. 10




Fig. 11




Fig. 12



EUROPEAN SEARCH REPORT

Application Number
EP 12 19 9761

5

10

15

20

25

30

35

40

45

DOCUMENTS CONSIDERED TO BE RELEVANT			CLASSIFICATION OF THE APPLICATION (IPC)
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	
A	US 2009/097681 A1 (PURIA SUNIL [US] ET AL) 16 April 2009 (2009-04-16) * paragraph [0003] - paragraph [0142] * -----	1-14	INV. H04R25/00
A	US 2010/303267 A1 (PEDERSEN MICHAEL SYSKIND [DK] ET AL) 2 December 2010 (2010-12-02) * paragraph [0001] - paragraph [0086] * -----	1-14	
A	US 2010/092016 A1 (IWANO KENJI [JP] ET AL) 15 April 2010 (2010-04-15) * paragraph [0001] - paragraph [0080] * -----	1-14	
A	US 2012/308057 A1 (EDWARDS BRENT [US] ET AL) 6 December 2012 (2012-12-06) * paragraph [0001] - paragraph [0034] * -----	1-14	
			TECHNICAL FIELDS SEARCHED (IPC)
			H04R
The present search report has been drawn up for all claims			
1	Place of search Munich	Date of completion of the search 27 May 2013	Examiner Peirs, Karel
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			
T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 12 19 9761

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

27-05-2013

10

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2009097681 A1	16-04-2009	EP 2208367 A1	21-07-2010
		US 2009097681 A1	16-04-2009
		WO 2009049320 A1	16-04-2009
<hr/>			
US 2010303267 A1	02-12-2010	AU 2010202218 A1	16-12-2010
		CN 101924979 A	22-12-2010
		EP 2262285 A1	15-12-2010
		US 2010303267 A1	02-12-2010
<hr/>			
US 2010092016 A1	15-04-2010	CN 101772965 A	07-07-2010
		DE 112008002187 T5	04-11-2010
		GB 2466556 A	30-06-2010
		JP 4355359 B1	28-10-2009
		JP 2010011444 A	14-01-2010
		JP 2010124446 A	03-06-2010
		KR 20100011984 A	03-02-2010
		US 2010092016 A1	15-04-2010
		US 2011249851 A1	13-10-2011
		WO 2009144774 A1	03-12-2009
<hr/>			
US 2012308057 A1	06-12-2012	EP 2124483 A2	25-11-2009
		US 2009290739 A1	26-11-2009
		US 2012308057 A1	06-12-2012
<hr/>			
35			
40			
45			
50			
55			

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

55