



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 71, 72

(51) Int Cl.:
E03B 1/02 ^(2006.01) **E03B 7/00** ^(2006.01)
E03B 7/07 ^(2006.01) **G06Q 50/06** ^(2012.01)
E02D 29/12 ^(2006.01)

(48) Corrigendum issued on:
25.02.2015 Bulletin 2015/09

(86) International application number:
PCT/JP2012/066258

(43) Date of publication:
09.07.2014 Bulletin 2014/28

(87) International publication number:
WO 2013/002211 (03.01.2013 Gazette 2013/01)

(21) Application number: **12803949.2**

(22) Date of filing: **26.06.2012**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(72) Inventors:
• **Kurata, Sakuji**
Osaka-shi, Osaka 545-0033 (JP)
• **Kurata, Masako**
Osaka-shi, Osaka 545-0033 (JP)

(30) Priority: **30.06.2011 JP 2011146707**

(71) Applicants:
• **Kurata, Sakuji**
Osaka-shi, Osaka 545-0033 (JP)
• **Kurata, Masako**
Osaka-shi, Osaka 545-0033 (JP)

(74) Representative: **Wood, Graham**
Bailey Walsh & Co LLP
1 York Place
Leeds, LS1 2DR (GB)

(54) **SELF-POWER GENERATION TYPE PIPE SENSOR, DISASTER DETECTION SYSTEM, AND SELF-POWER GENERATION TYPE PIPE ATTACHMENT DEVICE**

(57) [Object] To construct a disaster prevention system in which the trouble and costs of production and installment for providing several types of detection portions and their data acquisition devices can be reduced, and a plurality of sensors are provided for each predetermined section of the pipeline. [Solution] A pair of connection flanges 1 which is flange-connected to a section part dividing a pipeline P in the midst of the same, an inner pipe 2 which connects the section part of the pipeline P in a manner of allowing fluid circulation, a bypass pipe 3 having a flow path branching in a bypassing manner from a position of the inner pipe 2 closer to the upstream side, and merging again in a position of the inner pipe 2 closer to the downstream side, and a rotor 4 provided within the flow path of the bypass pipe 3 about the inner pipe 2 and rotates by the fluid circulation to the bypass pipe 3, an electromotive device 5 which generates electricity by the rotation of the rotor 4, and at least either the detector 6 or power receiving device 8 which is electrically connected with the electromotive device 5 are provided.

Fig. 4

