## 

## (11) **EP 2 784 773 A8**

## (12) CORRECTED EUROPEAN PATENT APPLICATION

published in accordance with Art. 153(4) EPC

(15) Correction information:

Corrected version no 1 (W1 A1) Corrections, see Bibliography INID code(s) 71

(48) Corrigendum issued on: **26.11.2014 Bulletin 2014/48** 

(43) Date of publication: 01.10.2014 Bulletin 2014/40

(21) Application number: 13780683.2

(22) Date of filing: 19.04.2013

(51) Int Cl.: **G10H 1/00** (2006.01) **H04L 12/70** (2013.01)

(86) International application number: **PCT/JP2013/061632** 

(87) International publication number: WO 2013/161706 (31.10.2013 Gazette 2013/44)

(84) Designated Contracting States:

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR


(30) Priority: 25.04.2012 JP 2012099955

(71) Applicant: NTT DOCOMO, INC. Chiyoda-ku Tokyo 100-6150 (JP) (72) Inventors:

- TSUKAMOTO, Masakatsu Tokyo 100-6150 (JP)
- TAGAYA, Masashi Tokyo 100-6150 (JP)
- MORINAGA, Yasuo Tokyo 100-6150 (JP)
- (74) Representative: MERH-IP Matias Erny Reichl Hoffmann Paul-Heyse-Strasse 29 80336 München (DE)

## (54) SERVER AND DATA SYNCHRONIZATION SYSTEM

There is provided a server that enables any piece of mobile equipment on a mobile communication network to synchronously receive data sent from two or more pieces of mobile equipment. The server includes a terminal managing part receiving synchronizing terminal information from each of the pieces of mobile equipment that specifies a group to which the piece of mobile equipment belongs and whether the piece of mobile equipment participates in the group as a session terminal or an audience terminal, a transmission time measuring part measuring the transmission time from each of the pieces of mobile equipment to the server, a route establishing part determining whether to change a route from each of the session terminals belonging to the same group to an alternative route on the basis of whether or not the transmission times from the session terminals are practically equal and establishing a route, a route sending part sending the established route to the session terminal, an SV synchronous data receiving part receiving data sent through the established route, and an SV synchronous data sending part sending the received data to the audience terminal in the same group as the pieces of mobile equipment that have sent the data.



EP 2 784 773 A8