



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 72

(51) Int Cl.:
H04R 9/04 (2006.01) **H04R 31/00** (2006.01)
H04R 7/04 (2006.01) **H04R 7/14** (2006.01)

(48) Corrigendum issued on:
11.02.2015 Bulletin 2015/07

(43) Date of publication:
29.10.2014 Bulletin 2014/44

(21) Application number: **13004359.9**

(22) Date of filing: **05.09.2013**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

- **Kwon, Joong Hak**
609-843 Busan (KR)
- **Lee, Jung Hyung**
642-955 Gyeongsangnam-do (KR)
- **Oh, Hyeon Taek**
636-922 Gyeongsangnam-do (KR)

(30) Priority: **25.04.2013 KR 20130046102**

(74) Representative: **Müller - Hoffmann & Partner**
Patentanwälte
St.-Martin-Strasse 58
81541 München (DE)

(71) Applicant: **Em-tech. Co., Ltd.**
Busan 609-390 (KR)

(72) Inventors:
• **Kim, Ji Hoon**
621-833 Gyeongsangnam-do (KR)

(54) **Bonding structure of diaphragm for microspeaker**

(57) The present invention relates to an assembly structure of a diaphragm for a microspeaker. The present invention discloses a bonding structure of a diaphragm for a microspeaker, the bonding structure comprising: a suspension including a central portion, an outer peripheral portion, and a connecting portion connecting the central portion and the outer peripheral portion; and a side diaphragm including an inner peripheral portion and an outer peripheral portion, which are attached to the central portion and outer peripheral portion of the suspension, respectively, and a dome portion, which projects between the inner peripheral portion and the outer peripheral portion, wherein the suspension and the side diaphragm are attached by thermal compression.

[Fig.2]

