



(11) **EP 2 801 608 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
12.11.2014 Bulletin 2014/46

(51) Int Cl.:
C11D 17/06 ^(2006.01) **C11D 11/02** ^(2006.01)
C11D 3/10 ^(2006.01) **C11D 3/04** ^(2006.01)
C11D 3/37 ^(2006.01) **C11D 11/00** ^(2006.01)
C11D 1/12 ^(2006.01)

(21) Application number: **13166775.0**

(22) Date of filing: **07.05.2013**

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**
Designated Extension States:
BA ME

(71) Applicant: **The Procter & Gamble Company**
Cincinnati, OH 45202 (US)

(72) Inventors:
• **Martinez-Guzman, Andres Arturo**
Newcastle upon Tyne, NE12 9TS (GB)

• **Tantawy, Hossam Hassan**
Newcastle upon Tyne, NE12 9TS (GB)
• **Porter, Adam**
Newcastle upon Tyne, NE12 9TS (GB)

(74) Representative: **Howard, Phillip Jan**
Procter & Gamble
Technical Centres Limited
Whitley Road
Longbenton
Newcastle upon Tyne NE12 9TS (GB)

(54) **Spray-dried detergent powder**

(57) A spray-dried powder comprising (i) from 20 to 80wt% of a first spray-dried particle comprising at least 5wt% of carbonate, silicate, an alkali metal chloride or a combination thereof, anionic deterative surfactant, and

having a bulk density of from 120g/l to 450g/l: and (ii) from 20 to 80wt% of a second spray-dried particle comprising at least 45wt% sulphate and having a bulk density of from 350g/l to 700g/l.

EP 2 801 608 A1

Description

FIELD OF THE INVENTION

5 **[0001]** The present invention relates to a spray-dried detergent powder and a process for making a spray-dried detergent powder.

BACKGROUND OF THE INVENTION

10 **[0002]** Particulate detergent compositions comprise deterative active ingredients. These deterative active ingredients are present on a carrier material such as carbonate, silicate or an alkali metal chloride. But, such particles tend to be 'sticky' due to the presence of the deterative ingredients. This has the effect of making the particles stick together which negatively impacts the flowability of the granular composition and can affect the dissolution in the wash liquor. Therefore, a 'bulking agent' in the form of a separate particle or powder is often added to the granular composition to counteract the stickiness and maintain good flowability.

15 **[0003]** The most preferred bulking agent is sulphate, as this is pH neutral and so does not raise the pH of the wash liquor. A less alkaline wash liquor is preferred as this has the benefit of being less harsh on the skin, especially for fabric hand wash consumers. However, natural sulphate has a high bulk density so upon addition to water it rapidly sinks and forms a sediment at the bottom of the container. Consumers associate this sedimentation with 'poor cleaning as they believe that the composition is not dissolving into the water and so 'not working'. Furthermore, in a fabric hand washing context, the slowly dissolving sediment makes the wash liquor feel 'gritty'. Consumers associate this with 'dirty wash water' and 'lack of cleaning'. In addition, as the sulphate sediments in the wash liquor, it can trap other detergent components and so affect the overall cleaning performance.

20 **[0004]** Thus, there is a need in the art for a granular laundry detergent composition that provides a more consumer acceptable wash liquor but still exhibits consumer acceptable flowability and dissolution. Furthermore, it is preferred that the laundry detergent composition provides a less alkaline wash liquor.

25 **[0005]** The Inventors have surprisingly found that a spray-dried powder comprising (i) from 20 to 80wt% of a first spray-dried particle comprising at least 5wt% of carbonate, silicate, an alkali metal chloride or a combination thereof, anionic deterative surfactant, and having a bulk density of from 120g/l to 450g/l; and (ii) from 20 to 80wt% of a second spray-dried particle comprising at least 45wt% sulphate and having a bulk density of from 350g/l to 700g/l overcame this issue.

SUMMARY OF THE INVENTION

35 **[0006]** A first aspect of the present invention is a spray-dried powder comprising (i) from 20 to 80wt% of a first spray-dried particle comprising at least 5wt% of carbonate, silicate, an alkali metal chloride or a combination thereof, anionic deterative surfactant, and having a bulk density of from 120g/l to 450g/l; and (ii) from 20 to 80wt% of a second spray-dried particle comprising at least 45wt% sulphate and having a bulk density of from 350g/l to 700g/l.

40 **[0007]** A second aspect of the present invention is a process for making the spray-dried powder according to the first aspect.

DETAILED DESCRIPTION OF THE INVENTION

The spray-dried powder

45 **[0008]** The spray dried powder of the present invention comprises (i) from 20 to 80wt% of a first spray-dried particle comprising at least 5wt% of carbonate, silicate, an alkali metal chloride or a combination thereof, anionic deterative surfactant, and having a bulk density of from 120g/l to 450g/l; and (ii) from 20 to 80wt% of a second spray-dried particle comprising at least 45wt% sulphate and having a bulk density of from 350g/l to 700g/l.

50 **[0009]** The first particle can comprise from 50wt% to 80wt%, or even from 60wt% to 80wt% by weight of the spray-dried powder. Alternatively, the first particle can comprise from 20wt% to 50wt% by weight of the spray-dried powder. The second particle can comprise from 50wt% to 80wt%, or even from 60wt% to 80wt% by weight of the spray-dried powder. Alternatively, the second particle can comprise from 20wt% to 50wt% by weight of the spray-dried powder.

55 **[0010]** The spray-dried detergent powder is suitable for any detergent application, for example: laundry, including automatic washing machine laundering and hand laundering, and even bleach and laundry additives; hard surface cleaning; dish washing, especially automatic dish washing; carpet cleaning and freshening. However, highly preferably, the spray-dried detergent powder is a spray-dried laundry detergent powder.

[0011] The spray-dried detergent powder can be a fully formulated detergent product, such as a fully formulated laundry detergent product, or it can be combined with other particles to form a fully formulated detergent product, such as a fully

formulated laundry detergent product. The spray-dried laundry detergent particles may be combined with other particles such as: enzyme particles; perfume particles including agglomerates or extrudates of perfume microcapsules, and perfume encapsulates such as starch encapsulated perfume accord particles; surfactant particles, such as non-ionic
 5 detersive surfactant particles including agglomerates or extrudates, anionic detersive surfactant particles including agglomerates and extrudates, and cationic detersive surfactant particles including agglomerates and extrudates; polymer particles including soil release polymer particles, cellulosic polymer particles; buffer particles including carbonate salt and/or silicate salt particles, preferably a particle comprising carbonate salt and silicate salt such as a sodium carbonate and sodium silicate co-particle, and particles and sodium bicarbonate; other spray-dried particles; fluorescent whitening
 10 particles; aesthetic particles such as coloured noodles or needles or lamellae particles; bleaching particles such as percarbonate particles, especially coated percarbonate particles, including carbonate and/or sulphate coated percarbonate, silicate coated percarbonate, borosilicate coated percarbonate, sodium perborate coated percarbonate; bleach catalyst particles, such as transition metal catalyst bleach particles, and imine bleach boosting particles; preformed peracid particles; hueing dye particles; and any mixture thereof.

[0012] It may also be especially preferred for the spray-dried detergent powder to comprise low levels, or even be
 15 essentially free, of builder. By essentially free of it is typically meant herein to mean: "comprises no deliberately added". In a preferred embodiment, the spray-dried detergent powder comprises no builder.

[0013] The spray-dried particle is typically flowable, typically having a cake strength of from 0 N to 20 N, preferably from 0 N to 15 N, more preferably from 0 N to 10 N, most preferably from 0 N to 5 N. The method to determine the cake strength is described in more detail elsewhere in the description.

[0014] The spray-dried detergent powder comprises a first spray-dried particle and a second spray-dried particle. By
 20 first and second spray-dried particles, we herein mean that the spray-dried detergent powder comprises two distinct particle types, the first spray-dried particle being formed independently of the second spray-dried particle. The first spray-dried particle has a different intra-particulate chemistry to that of the second spray-dried particle.

[0015] The spray-dried powder comprising the first and second spray-dried particles typically comprises from 0wt%
 25 to 7wt%, preferably from 0.5wt% to 5wt%, and preferably from 1wt% to 2wt% water.

First spray-dried particle

[0016] The first spray-dried particle comprises at least 5wt% of carbonate, silicate, an alkali metal chloride or a combination thereof, anionic detersive surfactant, and having a bulk density of from 120g/l to 450g/l.
 30

[0017] The first spray-dried particle may comprise between 5wt% and 30wt% or even between 10wt% and 25wt%, or even between 15wt% and 25wt% of carbonate, silicate, an alkali metal chloride or a combination thereof. In the avoidance of any doubt, if the first particle comprises carbonate, silicate and an alkali metal chloride, then the total weight percentage of the three materials combined is at least 5wt% or even between 5wt% and 30wt% or even between 10wt% and 25wt%,
 35 or even between 15wt% and 25wt%. Suitable carbonates, silicates and alkali metal chlorides are detailed below. The first particle may comprise between 5wt% and 30wt% or even between 10wt% and 25wt%, or even between 15wt% and 25wt% of an alkali metal chloride, preferably sodium chloride. The first particle may comprise less than 40wt%, or even less than 35wt%, or even less than 25wt% carbonate. The first particle may comprise from 1wt%, or even from 2wt% or even from 5wt% to 40wt% or even to 35wt% or even to 25wt% carbonate.

[0018] The first particle may comprise carbonate and an alkali metal chloride. Alternatively the first particle may comprise carbonate and silicate. Alternatively the first particle may comprise an alkali metal chloride and silicate.

[0019] The first spray-dried particle may comprise 0 to 5wt%, preferably 1 to 5wt% polymer, preferably 1.5 to 3wt% polymer. Without wishing to be bound by theory, the presence of the polymer can act to decrease the 'stickiness' of the first particle. This has benefits on the flowability of the spray-dried powder. The polymer in the first particle can be selected
 45 from a polycarboxylate homopolymer or a polycarboxylate copolymer, preferably the polymer is selected from polyacrylate homopolymer or acrylic acid/maleic acid copolymer. Suitable polymers are described in more detail below.

[0020] The first particle may comprise at least 5wt%, or at least 10wt%, or at least 15wt%, or at least 30wt% anionic detersive surfactant. The first particle may comprise at most 50wt%, or at most 40wt%, or at most 30wt%, or at most 20wt% anionic detersive surfactant. Suitable anionic detersive surfactants are described in more detail below. The
 50 anionic detersive surfactant can be alkyl benzene sulphonic acid or salt thereof, alkyl ethoxylated sulphate, or a mixture thereof. The anionic detersive surfactant can be a mixture of alkyl benzene sulphonic acid or salt thereof and alkyl ethoxylated sulphate.

[0021] The first particle may comprise from 0wt%, or from 1wt% or from 2wt% or from 5wt% to 10wt% or to 15wt% or to 20wt%, or to 35wt% or to 40wt% or to 50wt% of carbonate.

[0022] The first particle may comprise sodium hydroxide. The first particle may comprise between 0.5wt% and 5wt%, or even between 1wt% and 4wt% sodium hydroxide.

[0023] The first particle may comprise HEDP, brighteners or a mixture thereof. Brighteners are described in more detail below.

[0024] The first particle may comprise a hydrotrope. Hydrotropes are compounds that aid in the solubilisation of compounds in aqueous solutions. Preferably, the hydrotrope is present at in the first particle at a ratio of hydrotrope to anionic deterative surfactant of between 1:10 to 1:20. Suitable hydrotropes are described in more detail below.

[0025] The first particle may have a mean particle size of between 350 and 500 μ m, preferably between 375 and 425 μ m.

[0026] The first particle may have a bulk density of from 120g/l to 300g/l or from 300g/l to 450g/l.

Second spray-dried particle

[0027] The second spray-dried particle comprises at least 45wt% sulphate and has a bulk density of from 350g/l to 700g/l.

[0028] The sulphate is described in more detail below. The second particle may comprise at least 55wt%, or even 65wt% or even 75wt% sulphate. The second particle may comprise at most 99wt% sulphate, or even 90wt%, or even 85wt% or even 80wt% sulphate.

[0029] The second particle may comprise carbonate. If carbonate is present in the second particle, it may be present at a concentration of from 0wt% or from 1wt% or from 2wt% or from 5wt% to 10wt% or to 20wt% or to 30wt%.

[0030] The second particle may comprise polymer, preferably from 0 to 10wt% polymer, or even 1wt% to 8wt% polymer. Suitable polymers are described in more detail below. The polymer in the second particle can be selected from a polycarboxylate homopolymer or a polycarboxylate copolymer, preferably the polymer is selected from polyacrylate homopolymer or acrylic acid/maleic acid copolymer.

[0031] The second particle may comprise from 0 to 15wt%, or even from 1 to 12wt%, or from 2 to 10wt% anionic deterative surfactant. Suitable anionic deterative surfactants are described in more detail below. The anionic deterative surfactant in the second particle can be linear alkylbenzene sulfonate. Or the anionic deterative surfactant in the second particle can be alkyl ethoxylated sulphate

[0032] The second particle may comprise from 0 to 10wt% silicate, or even between 1 and 10wt% silicate.

[0033] The second particle may comprise sodium hydroxide. The second particle may comprise between 0.1wt% and 5wt%, or even between 0.25wt% and 5wt% or even between 0.5wt% and 5wt%, or even between 0.5wt% and 3.5wt% sodium hydroxide. Without wishing to be bound by theory, the presence of sodium hydroxide results in a more clear wash liquor when the second particle is dissolved in the wash liquor. Consumers prefer clear wash liquors as they perceive this to mean that the wash liquor is 'not dirty' and so providing improved fabric cleaning.

[0034] The second particle may have a mean particle size of between 350 and 500 μ m, preferably between 375 and 425 μ m.

[0035] Without wishing to be bound by theory, the density of the second particle means that it floats in the wash liquor and exhibits reduced sedimentation. The density of the second particle is lower than traditionally used sulphate particles. This is achieved by injecting air into an aqueous slurry which is then spray-dried to produce the second particle. This results in 'air bubbles' in the particle. This increased porosity means that the particle has a higher surface area, and so the particle dissolves faster in the wash liquor. This faster dissolution and lower level of sedimentation means that the wash liquor does not have the same gritty feel as if traditional sulphate particles were used. However, the sulphate (second) particle still acts a bulking agent ensuring excellent flowability of the powder composition.

[0036] The bulk density of the second particle can be from 350g/l to 600g/l, or from 400g/l to 550g/l.

Alkali metal chloride

[0037] The alkali metal chloride may be sodium chloride, potassium chloride or a mixture thereof.

Silicate salt

[0038] A suitable silicate salt is sodium silicate, preferably 1.6R and/or 2.0R sodium silicate.

Sulphate

[0039] The sulphate in the first spray-dried particle and independently in the second spray-dried particle can be any suitable sulphate. It may be sodium sulphate.

Carbonate

[0040] Carbonate can be any suitable carbonate, for example sodium or potassium carbonate, burkeite, sesquicarbonate or crystal modified carbonate such as crystal modified burkeite.

Polymer

[0041] The polymer in the first particle and independently in the second particle can be any suitable polymer. The anionic deterative surfactant can be alkyl benzene sulphonic acid or salt thereof, alkyl ethoxylated sulphate, or a mixture thereof. Preferably, the anionic deterative surfactant is a mixture of alkyl benzene sulphonic acid or salt thereof and alkyl ethoxylated sulphate.

[0042] Suitable polymers include carboxylate polymers, such as polyacrylates, and acrylate/maleate co-polymers and other functionalized polymers such as styrene acrylates. Preferably, the carboxylate polymer is an acrylate/maleate copolymer having an average molecular weight of about 2,000 to about 100,000 and a ratio of acrylate to maleate segments of from about 30:1 to about 1:1.

[0043] One suitable polymer is an amphiphilic graft polymer (AGP). Suitable AGPs are obtainable by grafting a polyalkylene oxide of number average molecular weight from about 2,000 to about 100,000 with vinyl acetate, which may be partially saponified, in a weight ratio of polyalkylene oxide to vinyl acetate of about 1:0.2 to about 1:10. The vinyl acetate may, for example, be saponified to an extent of up to 15%. The polyalkylene oxide may contain units of ethylene oxide, propylene oxide and/or butylene oxide. Selected embodiments comprise ethylene oxide.

[0044] In some embodiments the polyalkylene oxide has a number average molecular weight of from about 4,000 to about 50,000, and the weight ratio of polyalkylene oxide to vinyl acetate is from about 1:0.5 to about 1:6. A material within this definition, based on polyethylene oxide of molecular weight 6,000 (equivalent to 136 ethylene oxide units), containing approximately 3 parts by weight of vinyl acetate units per 1 part by weight of polyethylene oxide, and having itself a molecular weight of about 24,000, is commercially available from BASF as Sokalan HP22.

[0045] Suitable AGPs may be present in the detergent composition at weight percentages of from about 0 to about 5%, preferably from about above 0% to about 4%, or from about 0.5% to about 2%. In some embodiments, the AGP is present at greater than about 1.5wt%. The AGPs are found to provide excellent hydrophobic soil suspension even in the presence of cationic coacervating polymers.

[0046] Preferred AGPs are based on water-soluble polyalkylene oxides as a graft base and side chains formed by polymerization of a vinyl ester component. These polymers having an average of less than or equal to one graft site per 50 alkylene oxide units and mean molar masses (Mw) of from about 3000 to about 100,000.

[0047] Another suitable polymer is polyethylene oxide, preferably substituted or un-substituted.

[0048] Another suitable polymer is cellulosic polymer, preferably selected from alkyl cellulose, alkyl alkoxyalkyl cellulose, carboxylalkyl cellulose, alkyl carboxyalkyl, more preferably selected from carboxymethyl cellulose (CMC) including blocky CMC, methyl cellulose, methyl hydroxyethyl cellulose, methyl carboxymethyl cellulose, and mixtures thereof.

[0049] Other suitable polymers are soil release polymers. Suitable polymers include polyester soil release polymers. Other suitable polymers include terephthalate polymers, polyurethanes, and mixtures thereof. The soil release polymers, such as terephthalate and polyurethane polymers can be hydrophobically modified, for example to give additional benefits such as sudsing.

[0050] Other suitable polymers include polyamines, preferably polyethylene imine polymers, preferably having ethylene oxide and/or propylene oxide functionalized blocks

[0051] Other suitable polymers include synthetic amino containing amphoteric and/or zwitterionic polymers, such as those derived from hexamethylene diamine.


[0052] Another suitable polymer is a polymer that can be co-micellized by surfactants, such as the AGP described in more detail above.

[0053] Other suitable polymers include silicone, including amino-functionalised silicone.

[0054] Suitable polymers can include clay and soil removal/anti-redeposition agents being co-polymers comprising:


- (i) from 50 to less than 98 wt% structural units derived from one or more monomers comprising carboxyl groups;
- (ii) from 1 to less than 49 wt% structural units derived from one or more monomers comprising sulfonate moieties;
- and (iii) from 1 to 49 wt% structural units derived from one or more types of monomers selected from ether bond-containing monomers represented by formulas (I) and (II):

formula (I):



wherein in formula (I), R_0 represents a hydrogen atom or CH_3 group, R represents a CH_2 group, CH_2CH_2 group or single bond, X represents a number 0-5 provided X represents a number 1-5 when R is a single bond, and R_1 is a hydrogen atom or C_1 to C_{20} organic group;

formula (II)



in formula (II), R_0 represents a hydrogen atom or CH_3 group, R represents a CH_2 group, CH_2CH_2 group or single bond, X represents a number 0-5, and R_1 is a hydrogen atom or C_1 to C_{20} organic group.

[0055] Other suitable polymers include polysaccharide polymers such as celluloses, starches, lignins, hemicellulose, and mixtures thereof.

[0056] Other suitable polymers include cationic polymers, such as deposition aid polymers, such as cationically modified cellulose such as cationic hydroxy ethylene cellulose, cationic guar gum, cationic starch, cationic acrylamides and mixtures thereof.

[0057] Mixtures of any of the above described polymers can be used herein.

Anionic deterative surfactant

[0058] Suitable anionic deterative surfactants include sulphate and sulphonate deterative surfactants.

[0059] Preferred sulphonate deterative surfactants include alkyl benzene sulphonate, preferably C_{10-13} alkyl benzene sulphonate. Suitable alkyl benzene sulphonate (LAS) is obtainable, preferably obtained, by sulphonating commercially available linear alkyl benzene (LAB); suitable LAB includes low 2-phenyl LAB, such as those supplied by Sasol under the tradename Isochem® or those supplied by Petresa under the tradename Petrelab®, other suitable LAB include high 2-phenyl LAB, such as those supplied by Sasol under the tradename Hyblene®. A suitable anionic deterative surfactant is alkyl benzene sulphonate that is obtained by DETAL catalyzed process, although other synthesis routes, such as HF, may also be suitable.

[0060] Preferred sulphate deterative surfactants include alkyl sulphate, preferably C_{8-18} alkyl sulphate, or predominantly C_{12} alkyl sulphate.

[0061] Another preferred sulphate deterative surfactant is alkyl alkoxyated sulphate, preferably alkyl ethoxyated sulphate, preferably a C_{8-18} alkyl alkoxyated sulphate, preferably a C_{8-18} alkyl ethoxyated sulphate, preferably the alkyl


alkoxylated sulphate has an average degree of alkoxylation of from 0.5 to 20, preferably from 0.5 to 10, preferably the alkyl alkoxyated sulphate is a C₈₋₁₈ alkyl ethoxylated sulphate having an average degree of ethoxylation of from 0.5 to 10, preferably from 0.5 to 7, more preferably from 0.5 to 5 and most preferably from 0.5 to 3.

[0062] The alkyl sulphate, alkyl alkoxyated sulphate and alkyl benzene sulphonates may be linear or branched, substituted or un-substituted.

Brightener

[0063] Suitable brighteners are stilbenes, such as brightener 15. Other suitable brighteners are hydrophobic brighteners, and brightener 49. The brightener may be in micronized particulate form, having a weight average particle size in the range of from 3 to 30 micrometers, or from 3 micrometers to 20 micrometers, or from 3 to 10 micrometers. The brightener can be alpha or beta crystalline form.

[0064] The detergent composition preferably comprises C.I. fluorescent brightener 260 in alpha-crystalline form having the following structure:



[0065] The C.I. fluorescent brightener 260 is preferably predominantly in alpha-crystalline form. Predominantly in alpha-crystalline form means that preferably at least 50wt%, or at least 75wt%, or even at least 90wt%, or at least 99wt%, or even substantially all, of the C.I. fluorescent brightener 260 is in alpha-crystalline form.

[0066] The brightener is typically in micronized particulate form, having a weight average primary particle size of from 3 to 30 micrometers, preferably from 3 micrometers to 20 micrometers, and most preferably from 3 to 10 micrometers.

[0067] The detergent composition may comprises C.I. fluorescent brightener 260 in beta-crystalline form, and preferably the weight ratio of: (i) C.I. fluorescent brightener 260 in alpha-crystalline form, to (ii) C.I. fluorescent brightener 260 in beta-crystalline form is at least 0.1, preferably at least 0.6.

[0068] BE680847 relates to a process for making C.I. fluorescent brightener 260 in alpha-crystalline form.

Hydrotrope

[0069] The hydrotrope typically has at least one sulphonate group such as found in an alkyl aryl sulphonate or an alkyl aryl sulfonic acid. In an embodiment herein, the alkyl aryl sulphonate includes: sodium, potassium, calcium and ammonium xylene sulphonates; sodium, potassium, calcium and ammonium toluene sulphonates; sodium, potassium, calcium and ammonium cumene sulphonates; sodium, potassium, calcium and ammonium substituted or unsubstituted naphthalene sulphonates; and a mixture thereof. In an embodiment herein, the alkyl aryl sulfonic acid includes: xylene sulfonic acid, toluene sulfonic acid, cumene sulfonic acid, substituted or unsubstituted naphthalene sulfonic acid and a mixture thereof. In an embodiment herein, the hydrotrope is selected from the sodium and potassium salts of cumene sulphonate and toluene sulphonate and a mixture thereof. The salts of p-toluene sulfonate may also be used herein. Contrary to previous thought, the present invention has found that by adding a hydrotrope, the slurry can be thickened so as to improve structuring and increase the retention of gas in the slurry. However, the amount of hydrotrope needs to be cost-effective in the formulation. Such hydrotropes are readily available as commodity items from multiple sources around the world. In an embodiment herein, the hydrotrope has multiple sulphonate groups, such as found in the DOWFAX(TM) series of hydrotropes available from The Dow Chemical Company, Midland Michigan, USA. In an embodiment of the invention, the hydrotrope has two sulphonate groups on a diphenyl oxide backbone, while the hydrophobic portion may be a linear or branched alkyl group of from six to sixteen carbon atoms. A preferred hydrotrope is alkyl diphenyl oxide disulphonate, monoalkoxylated, which is commercially available from the Dow Chemical Company, Midland Michigan, USA as DOW-FAX XD.

Zeolite builder

[0070] Suitable zeolite builder includes include zeolite A, zeolite P and zeolite MAP. Especially suitable is zeolite 4A.

Phosphate builder

[0071] A typical phosphate builder is sodium tri-polyphosphate.

Other detergent ingredients

[0072] The composition typically comprises other detergent ingredients. Suitable detergent ingredients include: transition metal catalysts; imine bleach boosters; enzymes such as amylases, carbohydrases, cellulases, laccases, lipases, bleaching enzymes such as oxidases and peroxidases, proteases, pectate lyases and mannanases; source of peroxygen such as percarbonate salts and/or perborate salts, preferred is sodium percarbonate, the source of peroxygen is preferably at least partially coated, preferably completely coated, by a coating ingredient such as a carbonate salt, a sulphate salt, a silicate salt, borosilicate, or mixtures, including mixed salts, thereof; bleach activator such as tetraacetyl ethylene diamine, oxybenzene sulphonate bleach activators such as nonanoyl oxybenzene sulphonate, caprolactam bleach activators, imide bleach activators such as N-nonanoyl-N-methyl acetamide, preformed peracids such as N,N-phthaloylamino peroxyacetic acid, nonylamido peroxyadipic acid or dibenzoyl peroxide; suds suppressing systems such as silicone based suds suppressors; brighteners; hueing agents; photobleach; fabric-softening agents such as clay, silicone and/or quaternary ammonium compounds; flocculants such as polyethylene oxide; dye transfer inhibitors such as polyvinylpyrrolidone, poly 4-vinylpyridine N-oxide and/or co-polymer of vinylpyrrolidone and vinylimidazole; fabric integrity components such as oligomers produced by the condensation of imidazole and epichlorhydrin; soil dispersants and soil anti-redeposition aids such as alkoxylated polyamines and ethoxylated ethyleneimine polymers; anti-redeposition components such as polyesters and/or terephthalate polymers, polyethylene glycol including polyethylene glycol substituted with vinyl alcohol and/or vinyl acetate pendant groups; perfumes such as perfume microcapsules, polymer assisted perfume delivery systems including Schiff base perfume/polymer complexes, starch encapsulated perfume accords; soap rings; aesthetic particles including coloured noodles and/or needles; dyes; fillers such as sodium sulphate, although it may be preferred for the composition to be substantially free of fillers; carbonate salt including sodium carbonate and/or sodium bicarbonate; silicate salt such as sodium silicate, including 1.6R and 2.0R sodium silicate, or sodium metasilicate; co-polyesters of di-carboxylic acids and diols; cellulosic polymers such as methyl cellulose, carboxymethyl cellulose, hydroxyethoxycellulose, or other alkyl or alkylalkoxy cellulose, and hydrophobically modified cellulose; carboxylic acid and/or salts thereof, including citric acid and/or sodium citrate; and any combination thereof.

Method for measuring cake strength

[0073] A smooth plastic cylinder of internal diameter 6.35 cm and length 15.9 cm is supported on a suitable base plate. A 0.65 cm hole is drilled through the cylinder with the centre of the hole being 9.2cm from the end opposite the base plate.

[0074] A metal pin is inserted through the hole and a smooth plastic sleeve of internal diameter 6.35cm and length 15.25 cm is placed around the inner cylinder such that the sleeve can move freely up and down the cylinder and comes to rest on the metal pin. The space inside the sleeve is then filled (without tapping or excessive vibration) with the spray-dried powder such that the spray-dried powder is level with the top of the sleeve. A lid is placed on top of the sleeve and a 5 kg weight placed on the lid. The pin is then pulled out and the spray-dried powder is allowed to compact for 2 minutes. After 2 minutes the weight is removed, the sleeve is lowered to expose the powder cake with the lid remaining on top of the powder.

[0075] A metal probe is then lowered at 54 cm/min such that it contacts the centre of the lid and breaks the cake. The maximum force required to break the cake is recorded and is the result of the test. A cake strength of 0 N refers to the situation where no cake is formed.

Spray-drying process

[0076] The process for making the spray-dried powder of the present invention comprises the steps of;

- a) preparing a first aqueous slurry comprising anionic surfactant and water;
- b) preparing a second aqueous slurry comprising sulphate and water;
- c) spraying the first aqueous slurry through a first spray nozzle and the second aqueous slurry through a second spray nozzle into a spray-drying tower; and
- d) spray-drying the mixture to form the spray-dried powder.

[0077] Step (a): the first aqueous slurry can be formed by mixing in any suitable vessel, such as a mixer, in the standard manner. Suitable mixers include vertical mixers, slurry mixers, tank agitators, crutcher mixers and the like. The first aqueous slurry may comprise silicate, polymer, sulphate, carbonate or a mixture thereof.

[0078] In one embodiment the anionic deterative surfactant is LAS. The LAS maybe added to the mixing vessel in the neutralized form or may be added in the acid form (linear alkylbenzene sulphononic acid, HLAS). If added as HLAS, neutralization is effected upon contact to a suitable alkaline source in the mixer vessel (in-situ or dry neutralization). Without wishing to be bound by theory, LAS is a highly viscous material. Hence in order to pump the LAS, water is often added to lower the viscosity. However, this means that a large quantity of water needs to be removed during spray-drying which is energy and cost intensive. Hydrotropes can be added to the LAS and water mix which help lower the viscosity and so reduce the amount of water needed. However, it was surprisingly found that the addition of a hydrotrope to the HLAS acts to lower the viscosity even further, so even less water is needed to achieve a suitable viscosity. In one embodiment, the anionic deterative surfactant comprises a hydrotrope. Preferably, the ratio of hydrotrope to anionic deterative surfactant in the slurry is between 1:10 and 1:20. In one embodiment a hydrotrope is added to HLAS, preferably at a ratio of hydrotrope to HLAS of between 1:10 and 1:20. The HLAS and hydrotrope mix is then either neutralized prior to addition to the mixer or is neutralized in-situ in the mixer.

[0079] Step (b): the second aqueous slurry can be formed by mixing in any suitable vessel, such as a mixer, in the standard manner. Suitable mixers include vertical mixers, slurry mixers, tank agitators, crutcher mixers and the like. The second aqueous slurry may comprise silicate, polymer, anionic deterative surfactant, sodium hydroxide or a mixture thereof.

[0080] Step (c): the first aqueous slurry is transferred from the mixer, preferably through at least one pump, to a first spray nozzle. Typically, the first aqueous slurry is transferred in a pipe. The first aqueous slurry is typically transferred through an intermediate storage vessel such as a drop tank, for example when the process is semi-continuous. Alternatively, the process can be a continuous process, in which case no intermediate storage vessel is required. The first aqueous slurry is transferred through at least one pump, preferably at least two, or even at least three or more pumps, although one or two, preferably two pumps may be preferred. Typically, when two or more pumps are used, the first pump is a low pressure pump, such as a pump that is capable of generating a pressure of from 3×10^5 to 1×10^6 Pa, and the second pump is a high pressure pump, such as a pump that is capable of generating a pressure of from 2×10^6 to 1×10^7 Pa. Optionally, the first aqueous slurry is transferred through a disintegrator, such as disintegrators supplied by Hosakawa Micron. The disintegrator can be positioned before the pump, or after the pump. If two or more pumps are present, then the disintegrator can also be positioned between the pumps. Typically, the pumps, disintegrators, intermediate storage vessels, if present, are all in series configuration. However, some equipment may be in a parallel configuration. A suitable spray nozzle is a Spray Systems T4 Nozzle.

[0081] The first aqueous slurry may be made by firstly mixing water and if present, silicate, polymer, carbonate, sulphate, or a mixture thereof. This first aqueous slurry is then pumped along a pipe to the first spray nozzle and the anionic deterative surfactant is injected into the pipe before the first aqueous slurry is sprayed from the first spray nozzle. Preferably, the first aqueous slurry is passed through a first pump prior to addition of the anionic deterative surfactant and then passed through a second pump before passing to the first spray nozzle. A gas may be introduced between the first pump and the second pump. A gas, preferably air, may be pumped into the anionic deterative surfactant, preferably at a pressure of between 0.1 MPa and 2 MPa, prior to it being contacted with the first aqueous slurry. Alternatively, a gas can be injected directly into the slurry at any point before the spray nozzle, preferably between the first and second pumps. By 'nitrogen-rich gas' we herein mean a gas that comprises at least 50wt% nitrogen. By 'air' we herein mean atmospheric air.

[0082] The second aqueous slurry is also transferred from the mixer, preferably through at least one pump, to a second spray nozzle in the same way as detailed above for the first aqueous slurry.

[0083] In a preferred embodiment, the second aqueous slurry is prepared by mixing the sulphate and the water and if present, the anionic surfactant and sodium hydroxide, to form an aqueous premix, the aqueous premix is pumped through a pipe to the second spray nozzle, the silicate and polymer are independently injected into the pipe before the spray nozzle. The premix can be formed by mixing in any suitable vessel, such as a mixer, in the standard manner. Suitable mixers include vertical mixers, slurry mixers, tank agitators, crutcher mixers and the like.

[0084] The independent injection of the silicate and the polymer can be carried out in any position after the mixer and before the spray nozzle. However, preferably injection is carried out after the premix has been transferred through at least one pump, although injection can be carried out before the premix has been transferred through at least one pump. In a preferred embodiment, the premix is transferred through at least two pumps, and injection is carried out after the premix has been transferred through the first pump but before the premix enters the second pump.

[0085] A nitrogen-rich gas, preferably air, may be injected into the slurry at any point before the spray nozzle, preferably between the first and second pumps. Without wishing to be bound by theory injection of nitrogen-rich gas into the slurry introduces gas bubbles into the slurry. These remain in the slurry during spray-drying and so are captured in the spray-dried particles. This provides the particles with a lower bulk density. By 'nitrogen-rich gas' we herein mean a gas comprising

at least 50wt% nitrogen. By 'air' we herein mean atmospheric air.

[0086] Preferably, during step (c) the pipe carrying the first aqueous slurry and separately the pipe carrying the second aqueous slurry and premix are at a pressure between 3×10^5 and 1×10^6 Pa.

[0087] In step (c), it may be preferred that additionally sodium chloride is contacted to the first aqueous slurry, the second aqueous slurry, or both, after the mixer and before the spray nozzle.

[0088] The first aqueous slurry is sprayed through the first spray nozzle into a spray-drying tower, and the second aqueous slurry is independently sprayed through the second spray nozzle into the spray-drying tower. Preferably, the first and second aqueous slurries are independently at a temperature of from 60°C to 130°C when they are sprayed through the spray nozzles into a spray-drying tower. Suitable spray-drying towers are co-current or counter-current spray-drying towers. The slurries are typically sprayed at a pressure of from 3×10^6 Pa to 1×10^7 Pa.

[0089] **Step (d):** the slurries are spray-dried to form a spray-dried powder. Preferably, the exhaust air temperature is in the range of from 60°C to 100°C.

[0090] Preferably when added to the aqueous slurry, the sulphate has a volume average particle size of from 10 micrometers to 50 micrometers, preferably from 20 micrometers, or from 30 micrometers, and preferably to 45 micrometers, or even to 42 micrometers. The volume average particle size of the sulphate can be determined by any conventional means, such as light scattering, for example using a sympatec particle size analyser. The particle size of the inorganic salt can be controlled (i.e. reduced) by any suitable means, such as dry grinding (e.g. using pin mills) or wet grinding (e.g. using colloid mill). Without wishing to be bound by theory, smaller particle size sulphate dissolves more efficiently into the aqueous slurry. It is believed this is due to the larger surface area of the sulphate particles. This improved efficiency of dissolution has the benefit that less sulphate sediments out of the slurry during the manufacturing process. Sedimentation can cause blockages in the apparatus and so negatively affect production. Furthermore, the smaller particle size of the sulphate in the resultant spray-dried particle has the benefit of further reducing the 'gritty' feel within the wash liquor.

[0091] Preferably, the first spray nozzle is at a position higher up the spray drying tower than the second nozzle. Without wishing to be bound by theory, the spray-drying tower is heated from the bottom. Hence the hottest air exists at the bottom of the tower, with cooler air nearer the top of the tower. By introducing the first slurry into the tower at a point higher up, the slurry droplets encounter cooler air. This reduces the likelihood of the first particle being overheated in the tower and so damaging the components of the first particle. The second particle which comprises large quantities of sulphate is more heat resistant, and so can be introduced at a point further down the tower where the hotter air exists.

EXAMPLES

Example 1

[0092] A comparison was made between a spray-dried powder according to the present invention and a spray-dried powder outside of the scope of the present claims.

[0093] A first detergent POWDER A was prepared, comprising 30wt% of a Spray Dried particle 1 (bulk density: 300 g/l), and 70wt% of Sodium Sulphate (bulk density: 1200 g/l), blended in a batch rotating mixer. The composition of the spray dried particle is seen in Table 1.

Table 1.

Component	%w/w Spray Dried Particle
Sodium chloride	14.6
Linear alkyl benzene sulphonate	80.0
Acrylate/maleate copolymer	3.3
Miscellaneous	0.1
Water	2

[0094] The spray dried particle 1 was manufactured via spray drying of an aqueous slurry composed of anionic surfactant, acrylate polymer and sodium chloride. The slurry was prepared at 80°C in a crutcher making vessel and the slurry was pumped through a standard spray system pressure nozzle and atomized into a counter current spray drying tower at an air inlet temperature of 275 °C. The atomized slurry was dried to produce a solid mixture, which was then cooled and sieved to remove oversize material (>1.8mm) to form a spray-dried powder.

[0095] A second detergent POWDER B was prepared comprising 20wt% of spray dried particle 1 (bulk density: 300

EP 2 801 608 A1

g/l), and 80wt% of a second spray-dried particle (bulk density: 400 g/l), blended in a batch rotating mixer. The second spray dried particle was manufactured via spray drying of an aqueous slurry composed of sodium sulphate having a particle size of between 10 and 50 microns, water, anionic surfactant and acrylate/maleate co-polymer. The slurry was prepared in at 80°C in a crutcher making vessel and the slurry was pumped through a standard spray system pressure nozzle and atomized into a counter current spray drying tower at an air inlet temperature of 275 °C. The atomized slurry was dried to produce a solid mixture, which is was then cooled and sieved to remove oversize material (>1.8mm) to form a spray-dried powder. The composition of the second dried particle is seen in Table 2.

Table 2.

Component	%w/w
Sodium silicate salt	10.0
Linear alkyl benzene sulphonate	9.6
Sodium sulphate	73.7
Water	1.0
Acrylate/maleate copolymer	3.4
Total Parts	100.0

[0096] Powder detergent B had a cake strength of 0 N as measured by the method described herein. The overall composition of the POWDER DETERGENTS A & B are shown in Table 3.

Table 3.

Component	%w/w POWDER A	%w/w POWDER B
Sodium silicate salt	0.0	8.0
Linear alkyl benzene sulphonate	23.7	23.7
Acrylate/maleate copolymer	1.0	4.4
Sodium Chloride	4.3	2.9
Sodium carbonate	0.0	0.8
Sodium sulphate	70.4	58.9
Water	0.6	1.2
Total Parts	100.0	100.0

Dissolution Test

[0097] A 5g sample of both DETERGENT A and DETERGENT B were separately dispersed into 1 L aliquots of fresh tap water at 20°C, stirred at 200 RPM, using a magnetic stirrer and hotplate with thermocouple. The powders were left to dissolve for 60 seconds and then the dissolutions were decanted and passed through a cotton fabric filter (black cotton fabric, cut in a 9cm diameter circle). The filters were dried and the mass of the dry filters was recorded before and after the filtration process. The initial and final weights were used to determine the % of undissolved detergent:

$$\% \text{ undissolved detergent} = \frac{m_{\text{filter after filtration}} - m_{\text{filter before filtration}}}{3 \text{ g}} \times 100$$

[0098] The results can be seen in Table 4.

Table 4

	% undissolved detergent
Powder Detergent A	8.77%

(continued)

	% undissolved detergent
Powder Detergent B	2.94%

[0099] As can be seen from Table 4, there was a 66% improvement in dissolution of Detergent B as compared to Detergent A.

[0100] The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as "40 mm" is intended to mean "about 40 mm."

Example 2

[0101] A comparison was made between a spray-dried powder according to the present invention and a spray-dried powder outside of the scope of the present claims.

[0102] A first detergent POWDER C was prepared, comprising 30wt% of a Spray Dried particle 3 (bulk density: 300 g/l), and 70wt% of Sodium Sulphate (bulk density: 1200 g/l), blended in a batch rotating mixer. The composition of the spray dried particle 3 is seen in Table 5.

Table 5.

Component	%w/w Spray Dried Particle
Sodium Carbonate	14.6
Linear alkyl benzene sulphonate	80.0
Acrylate/maleate copolymer	3.3
Miscellaneous	0.1
Water	2

[0103] The spray dried particle 3 was manufactured via spray drying of an aqueous slurry composed of anionic surfactant, acrylate polymer and sodium carbonate. The slurry was prepared at 80°C in a crutcher making vessel and the slurry was pumped through a standard spray system pressure nozzle and atomized into a counter current spray drying tower at an air inlet temperature of 275 °C. The atomized slurry was dried to produce a solid mixture, which was then cooled and sieved to remove oversize material (>1.8mm) to form a spray-dried powder.

[0104] A second detergent POWDER D was prepared comprising 20wt% of spray dried particle 3 (bulk density: 300 g/l), and 80wt% of a second spray-dried particle (bulk density: 400 g/l), blended in a batch rotating mixer. The second spray dried particle was manufactured via spray drying of an aqueous slurry composed of sodium sulphate having a particle size of between 10 and 50 microns, water, anionic surfactant and acrylate/maleate co-polymer. The slurry was prepared in at 80°C in a crutcher making vessel and the slurry was pumped through a standard spray system pressure nozzle and atomized into a counter current spray drying tower at an air inlet temperature of 275 °C. The atomized slurry was dried to produce a solid mixture, which is was then cooled and sieved to remove oversize material (> 1.8mm) to form a spray-dried powder. The composition of the second dried particle is seen in Table 6.

Table 6.

Component	%w/w
Sodium silicate salt	10.0
Linear alkyl benzene sulphonate	9.6
Sodium sulphate	73.7
Water	1.0
Acrylate/maleate copolymer	3.4
Total Parts	100.0

[0105] Powder detergent D had a cake strength of 0 N as measured by the method described herein. The overall composition of the POWDER DETERGENTS C & D are shown in Table 7.

Table 7.

Component	%w/w POWDER C	%w/w POWDER D
Sodium silicate salt	0.0	8.0
Linear alkyl benzene sulphonate	23.7	23.7
Acrylate/maleate copolymer	1.0	4.4
Sodium Chloride	0.0	0.0
Sodium carbonate	4.3	3.7
Sodium sulphate	70.4	58.9
Water	0.6	1.2
Total Parts	100.0	100.0

Dissolution Test

[0106] A 5g sample of both DETERGENT C and DETERGENT D were separately dispersed into 1 L aliquots of fresh tap water at 20°C, stirred at 200 RPM, using a magnetic stirrer and hotplate with thermocouple. The powders were left to dissolve for 60 seconds and then the dissolutions were decanted and passed through a cotton fabric filter (black cotton fabric, cut in a 9cm diameter circle). The filters were dried and the mass of the dry filters was recorded before and after the filtration process. The initial and final weights were used to determine the % of undissolved detergent:

$$\% \text{ undissolved detergent} = \frac{m_{\text{filter after filtration}} - m_{\text{filter before filtration}}}{3 \text{ g}} \times 100$$

[0107] The results can be seen in Table 8.

Table 8

	% undissolved detergent
Powder Detergent A	7.19%
Powder Detergent B	6.55%

[0108] As can be seen from Table 4, there was a 9% improvement in dissolution of Detergent D as compared to Detergent C.

[0109] The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as "40 mm" is intended to mean "about 40 mm."

Claims

1. A spray-dried powder comprising:


- (i) from 20 to 80wt% of a first spray-dried particle comprising at least 5wt% of carbonate, silicate, an alkali metal chloride or a combination thereof, anionic detergent surfactant, and having a bulk density of from 120g/l to 450g/l; and
- (ii) from 20 to 80wt% of a second spray-dried particle comprising at least 45wt% sulphate and having a bulk density of from 350g/l to 700g/l.

2. The spray-dried powder according to claim 1, wherein the first particle comprises carbonate, preferably less than 40wt%, preferably less than 35wt% carbonate, preferably less than 25wt% carbonate.
3. The spray-dried powder according to any preceding claims, wherein the first particle comprises less than 30wt%, preferably between 5wt% and 30wt%, preferably between 15wt% and 25wt% sulphate.
4. The spray-dried powder according to any preceding claims, wherein the first particle comprises an alkali metal chloride, preferably between 1wt% and 40wt%, more preferably between 5wt% and 30wt%, even more preferably between 10wt% and 25wt% of an alkali metal chloride.
5. The spray-dried powder according to any preceding claims, wherein the second particle comprises sodium hydroxide, preferably between 0.5wt% and 5wt% sodium hydroxide.
6. The spray-dried powder according to any preceding claims, wherein the first particle has a mean particle size of between 350µm and 500µm, preferably between 375µm and 425µm, and the second particle has a mean particle size 350µm and 500µm, preferably between 375 µm and 425 µm.
7. The spray-dried powder according to any preceding claims, wherein the first particle, the second particle or both particles comprise a polymer independently selected from the group consisting of:

- (I) polycarboxylate homopolymers, preferably polyacrylate homopolymers;
- (II) polycarboxylate co-polymers, preferably acrylic acid/maleic acid co-polymers;
- (III) co-polymers comprising:


- (i) from 50 to less than 98 wt% structural units derived from one or more monomers comprising carboxyl groups;
- (ii) from 1 to less than 49 wt% structural units derived from one or more monomers comprising sulfonate moieties; and
- (iii) from 1 to 49 wt% structural units derived from one or more types of monomers selected from ether bond-containing monomers represented by formulas (I) and (II):

formula (I):



wherein in formula (I), R_0 represents a hydrogen atom or CH_3 group, R represents a CH_2 group, CH_2CH_2 group or single bond, X represents a number 0-5 provided X represents a number 1-5 when R is a single bond, and R_1 is a hydrogen atom or C_1 to C_{20} organic group;

formula (II)



in formula (II), R_0 represents a hydrogen atom or CH_3 group, R represents a CH_2 group, CH_2CH_2 group or single bond, x represents a number 0-5, and R_1 is a hydrogen atom or C_1 to C_{20} organic group;

(IV) any combination thereof.

8. The spray-dried powder according to any preceding claims wherein the first particle comprises from 0 to 5wt%, preferably from 1.5 to 3wt% polymer.
9. The spray-dried powder according to any preceding claims, wherein the anionic deterative surfactant in the first particle comprises linear alkylbenzene sulfonate, alkyl ethoxylated sulphate or a mixture thereof.
10. The spray-dried powder according to any preceding claims wherein the first particle comprises HEDP, brighteners or a mixture thereof.
11. A laundry detergent composition comprising a spray-dried powder according to any preceding claims.
12. A process for making a spray-dried powder according to any preceding claims comprising the steps of:
 - a) preparing a first aqueous slurry comprising anionic surfactant and water;
 - b) preparing a second aqueous slurry comprising sulphate and water;
 - c) spraying the first aqueous slurry through a first spray nozzle and the second aqueous slurry through a second spray nozzle into a spray-drying tower; and
 - d) spray-drying the mixture to form the spray-dried powder.
13. The process according to claim 12, wherein if present, silicate, polymer, carbonate, sulphate or a mixture thereof and water are mixed together and then pumped along a pipe to the first spray nozzle, and wherein the anionic deterative surfactant is injected into the pipe before the first aqueous slurry is sprayed from the first spray nozzle.
14. The process according to any preceding claims, wherein the sulphate added to the second aqueous slurry has a volume average particle size of from 10 micrometers to 50 micrometers, preferably from 20 micrometers, or from 30 micrometers, and preferably to 45 micrometers, or even to 42 micrometers.
15. The process according to any preceding claims, wherein the first spray nozzle is at a position higher up the spray drying tower than the second nozzle.



EUROPEAN SEARCH REPORT

 Application Number
 EP 13 16 6775

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	EP 1 566 431 A1 (PROCTER & GAMBLE [US]) 24 August 2005 (2005-08-24)	1,2,4,6,7,9-11	INV. C11D17/06
Y	* paragraph [0036]; examples 1, 2 *	5,14	C11D11/02 C11D3/10
X	EP 0 289 311 A2 (UNILEVER PLC [GB]; UNILEVER NV [NL]) 2 November 1988 (1988-11-02)	1,3,7-9,11,12,15	C11D3/04 C11D3/37 C11D11/00
Y	* page 9, lines 19-29; claims 1-4, 10; figure 2; examples 2, 4, 6, 7 * * page 6, lines 9-27; table p.14 *	13,14	C11D1/12
X	EP 2 380 964 A1 (PROCTER & GAMBLE [US]) 26 October 2011 (2011-10-26)	1,11,12	
Y	* paragraphs [0047] - [0053]; claim 1 *	5,13	
X	US 2011/257066 A1 (SOMERVILLE ROBERTS NIGEL PATRICK [GB] ET AL) 20 October 2011 (2011-10-20)	1,2,7-9,11,12	
A	WO 2004/055150 A1 (HENKEL KGAA [DE]; ARTIGA GONZALEZ RENE-ANDRES [DE]; HAMMELSTEIN STEFAN) 1 July 2004 (2004-07-01)	1,6-9,11	TECHNICAL FIELDS SEARCHED (IPC) C11D
A	EP 1 754 779 A1 (PROCTER & GAMBLE [US]) 21 February 2007 (2007-02-21)	1-15	
	* paragraphs [0042] - [0050]; claims 1-8; examples *		
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 4 November 2013	Examiner Loiselet-Taisne, S
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 13 16 6775

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-11-2013

10

15

20

25

30

35

40

45

50

55

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 1566431 A1	24-08-2005	AR 047970 A1	15-03-2006
		AU 2005217631 A1	09-09-2005
		BR PI0507967 A	17-07-2007
		CA 2557194 A1	09-09-2005
		CN 1922299 A	28-02-2007
		EP 1566431 A1	24-08-2005
		JP 2007522336 A	09-08-2007
		KR 20070004644 A	09-01-2007
		US 2005187117 A1	25-08-2005
		WO 2005083048 A1	09-09-2005

EP 0289311 A2	02-11-1988	AU 604113 B2	06-12-1990
		AU 1515788 A	03-11-1988
		BR 8802050 A	29-11-1988
		CA 1315639 C	06-04-1993
		DE 3873145 D1	03-09-1992
		DE 3873145 T2	14-01-1993
		EP 0289311 A2	02-11-1988
		ES 2034211 T3	01-04-1993
		JP H0534398 B2	21-05-1993
		JP S63286495 A	24-11-1988
		NO 881882 A	31-10-1988
		US 4818424 A	04-04-1989
		ZA 8803074 A	27-12-1989

EP 2380964 A1	26-10-2011	EP 2380964 A1	26-10-2011
		US 2011257059 A1	20-10-2011
		WO 2011133460 A1	27-10-2011

US 2011257066 A1	20-10-2011	CN 102858933 A	02-01-2013
		EP 2561054 A1	27-02-2013
		US 2011257066 A1	20-10-2011
		WO 2011133306 A1	27-10-2011

WO 2004055150 A1	01-07-2004	AU 2003303064 A1	09-07-2004
		WO 2004055150 A1	01-07-2004

EP 1754779 A1	21-02-2007	AR 054931 A1	25-07-2007
		BR PI0615177 A2	03-05-2011
		CA 2616744 A1	22-02-2007
		CN 101243173 A	13-08-2008
		EP 1754779 A1	21-02-2007
		JP 2009504835 A	05-02-2009
		US 2007042931 A1	22-02-2007
		WO 2007020606 A1	22-02-2007
		ZA 200800748 A	28-01-2009

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

EP 13 16 6775

10

04-11-2013

Patent document cited in search report	Publication date	Patent family member(s)	Publication date

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82