



(11) **EP 2 818 997 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
31.12.2014 Bulletin 2015/01

(51) Int Cl.:
G06F 3/0488 ^(2013.01) **H04M 1/725** ^(2006.01)
G06F 3/0481 ^(2013.01) **G06F 3/14** ^(2006.01)

(21) Application number: **13174439.3**

(22) Date of filing: **28.06.2013**

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**
Designated Extension States:
BA ME

- **Steeves, Ryan David**
Waterloo, ON N2L 3W8 (CA)
- **Ziegler, Rudolph Ferdinand**
Mississauga, Ontario L4W 0B5 (CA)
- **Pedwyssocki, Alexander James**
Mississauga, Ontario L4W 0B5 (CA)

(71) Applicant: **BlackBerry Limited**
Waterloo, ON N2K 0A7 (CA)

(74) Representative: **Carpmaels & Ransford LLP**
One Southampton Row
London WC1B 5HA (GB)

(72) Inventors:
• **Arbsjö, Jonas Ove**
Malmö 21140 (SE)

(54) **Generating message notifications providing direction actions**

(57) A method and device for generating message notifications at a computing device is provided. The computing device receives a message indicator from a mobile device, the indicator associated with a message received by the mobile device. The computing device generates a first display representation of the received message indicator. Positioning information is determined from an

input component. A second display representation is generated comprising at least a portion of the message received at the mobile device and an action area for performing a direct action in response to the received message when the determined positioning information satisfies a display criteria associated with the second display representation.

EP 2 818 997 A1

Description

TECHNICAL FIELD

[0001] The current description relates to systems, devices and methods for generating message notifications and in particular to generating message notifications at a computing device for messages received at a mobile device.

BACKGROUND

[0002] When messages are received at a mobile device, such as mobile phones smartphone or a tablet, a notification may be presented to indicate to the user that a message has been received. The notification may not present the full message but provide a portion of the message to the user to limit interruption with the current operating context and still provide a notification to the user that a message has been received.

[0003] Users of mobile devices may often use other computing devices, such as a tablet, or desktop computer in conjunction with the mobile device. The additional computing devices may have one or more message applications, which may be associated with the one or more of the messaging applications on the user's mobile device. For example, a user may receive e-mail messages from a work account on both the mobile device and a work desktop computer. The mobile device may receive messages from accounts not associated with their additional computing device, such as a Short Message Service (SMS) text message.

[0004] Mobile devices may connect to additional computing devices used by a user in order to allow messages received at the mobile device to be displayed on the additional computing device. For example, a user on their work desktop may receive a notification of an SMS text message received on their mobile device.

[0005] While it can be advantageous to receive notifications of messages received by a mobile device on a different computing device it may be desirable to provide additional, alternative and/or improved functionality for presenting notifications on a computing device other than the device a message was received by.

SUMMARY

[0006] In accordance with the present disclosure there is provided a method for generating message notifications at a computing device, the method comprising receiving at the computing device a received message indicator from a mobile device, the indicator associated with a message received by the mobile device; generating at the computing device a first display representation of the received message indicator; determining at the computing device positioning information from an input component; and generating a second display representation comprising at least a portion of the message re-

ceived at the mobile device and an action area for performing a direct action in response to the received message when the determined positioning information satisfies a display criteria associated with the second display representation.

[0007] In accordance with the present disclosure there is further provided a computing device comprising a memory for storing instructions; and a processor for executing the instructions stored in memory, the instructions configuring the computing device to perform a method comprising receiving at the computing device a received message indicator from a mobile device, the indicator associated with a message received by the mobile device; generating at the computing device a first display representation of the received message indicator; determining positioning information from an input component; and generating a second display representation comprising at least a portion of the message received at the mobile device and an action area for performing a direct action in response to the received message when the determined positioning information satisfies a display criteria associated with the second display representation.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Further features and advantages of the present disclosure will become apparent from the following detailed description, taken in combination with the appended drawings, in which:

Figure 1 depicts displaying an actionable notification on a mobile device;

Figure 2 depicts the process for generating message notifications at a computing device for messages received at a mobile device;

Figure 3 depicts interacting with a display representation of a message indicator received from a mobile device;

Figures 4A to 4C depicts interacting with a display representation of a message indicator received from a mobile device;

Figure 5A to 5C depicts interacting with a display representation of a message indicator received from a mobile device;

Figure 6A to 6C depicts interacting with a display representation of a message indicator received from a mobile device;

Figure 7A and 7B depicts interacting with a display representation of a message indicator received from a mobile device;

Figure 8A to 8C depicts interacting with a display representation of a message indicator received from a mobile device;

Figure 9A to 9C depicts interacting with a display representation of a message indicator received from a mobile device;

Figure 10 depicts processing notifications received

from a mobile device for display;
 Figure 11 depicts processing notifications received from a mobile device for display;
 Figure 12 further depicts processing notifications received from a mobile device for display;
 Figure 13 further depicts processing notifications received from a mobile device for display;
 Figure 14 depicts a system for generating display representations of notifications received by a mobile device;
 Figure 15 depicts a method for generating message notifications at a computing device; and
 Figure 16 depicts a further method for generating message notifications at a computing device.

DETAILED DESCRIPTION

[0009] Embodiments are described below, by way of example only, with reference to Figs. 1-16. Mobile devices, such as mobile phones, smartphone and tablets, can receive messages from numerous channels such as one or more e-mail accounts, instant messaging applications, short message service (SMS) text messaging applications, as well push notification applications such as stock price applications and sports scores applications. The mobile device can notify a user when a new message is received from one of the communication or messaging channels. As described further herein, the notification displayed on the mobile device may include functionality for facilitating taking an action, such as responding to a message, directly from the notification. As further described herein, a notification of a message received at the mobile device may be displayed on a second device in communication with the mobile device. Control of the notification displayed on the second device may be provided to reduce an intrusiveness of notifications while still providing meaning notifications as well as notifications with direct actions.

[0010] Figure 1 depicts displaying an actionable notification on a mobile device. The mobile device 102 is depicted as a mobile phone although other mobile devices that are capable of sending and receiving messages are contemplated as well. The mobile device 102 comprises a display 104 for displaying a user interface. The display 104 may be a touch sensitive display providing an input component for the mobile device. A user of the mobile device 102 may have one or more applications on the mobile device for receiving messages from different channels. For example, a user may have a number of e-mail accounts setup to receive messages on the mobile device. Additional communication channels may include social media applications such as Twitter®, Facebook® and LinkedIn®. Further communication channels may include instant messaging applications such as Blackberry Messenger BBM®, Skype® Windows Live Messenger® and others. Further communication channels may include applications on the mobile device 102 that receive pushed messages from remote sources such

as applications that push sports scores, news, stock prices or other alerts. Typically, it is possible to specify a notification to be used for informing the user of a new message. For example, a user may select an alert tone or sound to notify the user of a new e-mail. It is often possible to customize the notifications based on the channel the message was received from as well as other message information. For example, a user may select one alert tone for e-mails received from a personal account and a different alert tone for e-mails received from a work account.

[0011] In addition to sound alerts, it is possible to provide visual notifications. For example a blinking light may be used to notify a user of a new message. Further, the notification may be displayed on the display as a pop-up or banner or other similar graphical representation. The pop-up or banner may display a portion of the text of the message and/or other relevant information.

[0012] As depicted in Figure 1, a notification 110 for a received message may be displayed on the mobile device 102. The notification 110 is depicted as a banner displayed at the top of the display 104. When displaying such a banner notification, the banner may be displayed overtop of the currently displayed user interface. Alternatively, the user interface may be displaced downward, or the size of the user interface reduced to allow the banner notification 110 to be displayed without obstructing other visual components of the display. As depicted in Figure 1, a home screen user interface 126 is displaced downwards to allow the notification to be displayed above the home screen. It will be appreciated that a banner type notification may be presented at other locations such as the bottom of the display. Further, the notification may be displayed as a pop-up which can be overlaid over the current user interface.

[0013] The notification 110 may comprise a message section 112 that displays information associated with the received message associated with the notification. The message section 112 may display an icon or graphic 114 associated with a sender of the message or associated with the type of message, as well as a name 116 associated with the sender of the message. The name of the sender may be displayed based on contact information of the sender stored in the mobile device. Additionally, the notification may display text 118 associated with the message. For example, if the notification is for an e-mail, the text 118 may be the subject line of the e-mail and/or a body of the e-mail message.

[0014] In addition to the message section 112, the notification 110 may include a direct action area 120 associated with performing a direct action. The direct action area 120 may vary depend upon the notification, or the message channel associated with the notification. For example, if the message associated with the notification is a text based messaging application, the direct action may be associated with replying to the received message. The direct action area may include a text box area 122 for inputting reply text as well as a reply button

124 for sending the reply. It is contemplated that the reply button may be omitted or replaced with another button. If the reply button 124 is not presented, then the reply text may be sent when the user presses enter, or takes a similar action.

[0015] The notification 110 allows a notification for a message to be displayed along with an associated action that can be performed directly from the notification. When a message is received on the mobile device, a notification providing a direct action can be displayed on the device and as described further below, the message notification may be passed to a second device computing device, such as a tablet or desktop computer or laptop and displayed on the secondary screen.

[0016] Figure 2 depicts the process for generating message notifications at a computing device for messages received at a mobile device. The system 200 comprises a mobile device 102 and a second computer device 206. The mobile device 102 can receive messages and provide notifications on the display 104. The mobile device 102 can connect to a second computer 206, depicted as an all-in-one computer although other types of computing devices are contemplated, and use the display 208 of the second computer to present a notification of the message received on the mobile device 102.

[0017] When the mobile device 102 is in proximity to the second computer 206 a connection may be established 210 between the two devices. The connection can be established using various communication techniques, to create local area networks (LAN) or personal area networks (PAN) including a USB connection, a Bluetooth connection, a Wi-Fi connection, a ZigBee connection or other wired or wireless connections. A message 212 is received at the mobile device. The mobile device can generate a notification for the message as well as a direct action area as described above with regard to Figure 1. If the mobile device 102 has established a connection to the second computer 206, a message indicator can be sent 214 from the mobile device to the second computer. The message indicator can be received at the second computer 216 and a display representation 218 of the message indicator displayed to the user. As depicted, the display representation 218 may be a small graphical icon or other unobtrusive indicator. As described further below, a user of the second computing device 206 may interact with the display representation, which may for example expand the graphical representation to allow the user to take a direct action from the display representation.

[0018] Figures 3A and 3B depicts interacting with a display representation of a message indicator received from a mobile device. As depicted in section (A) of Figure 3, a message indicator has been received at the second computing device 206 from a mobile device 102 and a first display representation 218 of the message indicator is displayed. Positioning information can be received from an input component, which is depicted graphically as pointer 302 in Figure 3.

[0019] The input component, graphically represented as pointer position 302, can be moved toward the graphical representation 218 to a location 306 as depicted by dashed arrow 304 in section (B) of Figure 3. The positioning information associated with the second pointer position 306 is within a display area surrounding the display representation, represented by dashed line 308. When the positioning information 306 is within the display area 308 a second display representation 310 of the message indicator may be presented on the second display. As depicted, the second display representation 310 may comprise a message portion 312 that may display a graphical icon 314 indicative of a sender of the message, or a message channel of the message. The message portion 312 may further comprise a name portion 316 displaying a name associated with the sender of the message as well as a message body 318 displaying at least a portion of the message, such as the body of an e-mail or text message. The display representation 310 also includes a direct action area 320 that allows a user to take a direct action associated with the message, such as replying to the message. The direct action area 320 may comprise a text box 322 for inputting a reply text as well as an action button 324 for carrying out the direct action. Although depicted as a direct action button 324, a button may not be necessary for performing the direct action. For example, sending the reply to the message may occur when a user hits enter. Regardless of if a direct action button is present or not, an input selection is received, such as pressing the direct action button or hitting enter, that causes the associated direct action to occur. Further, although only a single direct action has been described, it is contemplated that a plurality of direct actions may be presented to the user. For example the input selection may also include the ability to share the message with one or more additional contacts. Alternatively, the direct action may also provide the ability to share a message with other contacts and not reply to the message in the instance that notification is broadcast type message. When multiple direct actions are presented, the input selection may select which of the direct actions to perform.

[0020] As depicted in Figure 3, a display representation used to notify a user of a message received on the mobile device may be adjusted based on input, such as mouse movement, from a user. As depicted, a first display representation 218 may provide a small notification that does not distract the user or interfere with work currently being performed. If the user wishes to determine more information associated with the displayed notification, they are able to move a pointer towards the display representation, which will expand to display information associated with the message as well as provide an option for taking a direct action associated with the message of the notification.

[0021] Figures 4A to 4C depicts interacting with a display representation of a message indicator received from a mobile device. The interaction depicted in Figure 4 is

similar to the interaction depicted in Figure 3; however, it includes an additional intermediary display representation of the notification. As depicted in section (A) of Figure 4, a message indicator has been received at the second computing device from a mobile device and a first display representation 218 of the message indicator is displayed. Positioning information can be received from an input component, which is depicted graphically as pointer 302. A user of the second device 206 can use an input component to move the pointer 302 to a second position 402. If the positioning information associated with position 402 is within an intermediary display area, depicted by dashed line 404, the display representation of the notification can be changed to a second display representation 410 of the notification. The second display notification 410 may comprise a message portion 312, as described above, that may display a graphical icon 314 indicative of a sender of the message, or a message channel of the message. The message portion 312 may further comprise a name portion 316 displaying a name associated with the sender of the message as well as a message body 318 displaying at least a portion of the message, such as the body of an e-mail or text message.

[0022] The user may continue moving the pointer toward the display notification from position 402 to position 406. If the position 406 is within a direct action area depicted by dashed line 308, the display representation 310 that includes a direct action area as described above with regard to Figure 3.

[0023] As depicted in Figure 4, a display representation of a notification may initially be small and unobtrusive so as not to distract the user. If the user wishes to see more information associated with the notification, the pointer can be moved toward the display representation, which can change to display additional information. If the user wishes to take a direct action associated with the message, they can continue moving the pointer toward the representation and once the pointer is within an area associated with displaying the direct action, the display representation can be changed to include a direct action area. Accordingly, a user can control the amount of information about a message received at the mobile device that is revealed on a second device.

[0024] Figures 5A to 5C depicts interacting with a display representation of a message indicator received from a mobile device. Depicted, an initial display representation 218 is displayed and a user moves a pointer from a first position 302 to a second position 502. The second position 502 is within the direct action notification area 308 and as such, the display representation 310 is presented on the display. The user may click 504 on the message portion of the display representation 310. Clicking on the message portion causes an application associated with the message to be displayed 506. The message application 506 may display the communication history of a conversation 508 as well as provide an area for sending a new message to the other participants in the conversation.

[0025] As described above, a message can be received at a mobile device, such as a mobile phone, and a notification can be presented on the display of a second device coupled to the mobile device. The amount of information displayed for the notification on the mobile device can be controlled by the user.

[0026] Figures 6A to 6C depicts interacting with a display representation of a message indicator received from a mobile device. The second computing device of Figure 6 is depicted as a tablet type device 602 that includes a touch sensitive display 604 as the input component. A message indicator can be received at the tablet 602 and a display representation 618 presented to the user. As described above with reference to Figures 3 to 5, different display notifications 618, 610 can be displayed. The user may initiate a gesture by touching the screen at a first location 606; the touch-based gesture may comprise dragging or swiping towards a second location 608. The gesture 612 may cause the display notification 618 to expand and display a more detailed display representation of the message, possibly including a direct action area. The gesture 612 may be compared to display criteria, which may include a direction of the gesture, the end location of the gesture, display time threshold, and/or the speed of the gesture in determining if the display representation should be changed. If the swipe gesture 612 causes the display representation 610 to be displayed including a direct action area, ending the gesture by lifting the figure at position 608 may cause the focus to switch to input box 622 allowing a user to input text once the gesture is completed.

[0027] Figure 7 depicts interacting with a display representation of a message indicator received from a mobile device. The depicted interaction is similar to that described above with regard to Figure 6. A notification is received and initially displayed. A gesture 612 starting at a first position 606 and ending at a second location position 608 causes a display representation 610 to be presented. In contrast to Figure 6, in which it is assumed that the user lifts their finger at location 608, Figure 7 depicts a further swipe gesture starting at the location 608 and ending at location 702. The gesture 704 may be considered as the reverse of gesture 612 and causes the display representation to disappear.

[0028] Figures 8A to 8C depicts interacting with a display representation of a message indicator received from a mobile device. The interaction depicted in Figure 8 does not rely upon a swipe gesture. Rather when an initial display representation of the notification is presented 618, the user may tap 802 on the display representation, causing another display representation 610, including message and direct action portions to be presented. Once presented, the focus may be placed on the text input area 622, and a virtual keyboard 804 displayed on screen allowing the user to enter text into the reply area.

[0029] Figures 9A to 9C depicts interacting with a display representation of a message indicator received from a mobile device. The above description has described

using an input component for controlling the display representations associated with a notification. The input component may also be provided by the mobile device 102 itself. The mobile device may include one or more sensors for determining its orientation and movement. Each of the different display representations 218, 310, 410 may be associated with a range of positions of the mobile device.

[0030] As depicted, the mobile device 102 may be rotated from a horizontal position 902 to different positions. When a notification is presented on the display, the display representation to present may be determined based on the position of the mobile device. As depicted if the mobile device 102 is positioned between a horizontal position and a second angular position 904 the display representation 218, which displays a small graphical icon, can be displayed. As the mobile device is rotated between the second angular position 904 and a third angular position 906, a second display representation 410 that presents at least a portion of the associated message is displayed. If the mobile device continues to be rotated past the third angular position 908 to a fourth angular position 908, the display representation 310 may be presented on the display that includes at least a portion of the message as well as a direct action area allowing a user to carry out a direct action associated with the message. It will be appreciated that the particular angles defining the angular positions 902, 904, 906, 908 may vary and may be set by the user of the mobile device.

[0031] The above has described displaying notifications received at a mobile device on a display of a second computing device that is communicatively coupled to the mobile device. The notification may have various display representations, including a display representation that includes a direct action area. By allowing the user to control, through an input component, which of the display representations are presented the presentation of the notifications may be improved.

[0032] As described further below, in addition to controlling when the display representation that includes a direct action area is displayed, it may be desirable to control which of the messages are notified to the user. For example, regardless of the display representation used for the notification on the second device, a message notification received from the mobile device may be processed to determine if it should be displayed based on the current computing context. The current computing context may include various factors, such as what applications are running, what applications are currently displayed, networks the computing device is connected to as well as other factors such as preference settings.

[0033] Figure 10 depicts processing notifications received from a mobile device for display. As depicted in Figure 10, a message 1002 is received for an account, depicted as being a work e-mail account 1004, on the mobile device 102. As described above, the mobile device 102 may send a message indicator 1006 to a second computing device 206. The second computing device

206 is running an e-mail program 1008 for the work account. Accordingly the message that was received at the mobile device is also received at the second computing device and displayed 1010.

[0034] When the message indicator 1006 is received at the computing device 206 the computing device processes the message indicator based on the computing context. In Figure 10, it is contemplated that the computing context includes that the computing device is running an e-mail program for an e-mail account, and the user has set preferences indicating that notifications should not be presented if the message is associated with an e-mail account displayed in a currently running e-mail application. When the message indicator 1006 is received, it is processed and it is determined that the message indicator is associated with a message for the work e-mail account that is displayed by the e-mail application 1006. Accordingly, the received message indicator is not presented to the user.

[0035] Figure 11 depicts processing notifications received from a mobile device for display. The depiction in Figure 11 is similar to that of Figure 10; however, a display representation of the message indicator is presented to the user. A message 1102 is received at the mobile device 102 for a personal e-mail account 1104. The mobile device 102 sends a notification indicator 1106 to a second computing device 206 that is communicatively coupled with the mobile device 102. The message indicator 1106 is processed at the computing device 206, which determines that the message indicator is associated with a message for an account that is not associated with the work e-mail program 1006. Accordingly, the processing determines that a display representation for the notification should be presented to the user and presents the display representation accordingly 1108. The display representation may be displayed and controlled in accordance with the description of the position based action notification described above. Additionally or alternatively, the notification may be a static display representation.

[0036] As described above with reference to Figure 10 and Figure 11, when a message indicator is received that is associated with an account of an application currently running on the second device 206, a display representation of the message indicator is not presented on the display. If however, the message indicator is not associated with an account of a running application, the display representation may be presented to the user on the display.

[0037] Figures 12 and 13 further depict processing notifications received from a mobile device for display. In Figures 11 and 12 a notification for a received SMS message is not displayed when the second computer is connected to a work domain, while a notification for a received SMS message is displayed when the second computing device is not connected to the work domain. As such, the context based display of notifications can allow notifications associated with personal accounts to only be displayed when not at work.

[0038] As depicted in Figure 12, a message 1202 is received for a personal SMS account 1204. The mobile device 102 sends the message indicator 1206 to the second computing device 206 which receives the message indicator and processes it. The second computing device 206 is connected to a work domain 1208, and as such, a display representation of the received message indicator for the personal SMS message is not presented on the display 1210. The determination that the second computing device 206 is connected to the work domain may be determined based upon network characteristics such as Internet Protocol (IP) address, domain registration, logon credentials, and access network or gateway/proxy configuration.

[0039] In contrast to Figure 12, the second computing device 206 of Figure 13 is connected to a home network 1302. As such, when the message indicator 1206 for the personal SMS message is received, display representation of the received message indicator 1302 is presented to the user.

[0040] As described above with regard to Figures 10 - 13, it is possible to control which notifications are displayed on a second computing device based on a current operating context. Rules or preferences may be specified in notification display settings that specify which message notifications should be displayed based on particular operating contexts. The operating context may specify one or more criteria such as what applications are running, currently visible applications, current time, a time of day, a day of the week, a current location of the portable device or computing device, as well as networks connected to the portable device or computing device.

[0041] Although described above as determining what notifications should be displayed on a second device, it is contemplated that the same context-based processing may be used in determining what notifications should be displayed in the mobile device.

[0042] The message indicator sent from the mobile device to the second computing device may comprise various characteristics depending upon the type of message. For example, the characteristics of the message indicators may include information on a sender and receiver of the message, a message subject, a message body, a messaging application, and a time the message was sent and/or received.

[0043] Figure 14 depicts a system for generating display representations of notifications received by a mobile device. The system 1400 comprises a mobile device 206 which may be, for example a cellular phone, smartphone, or tablet and a second computing device 206, which may be a tablet, desktop computer, all-in-one computer as depicted or a laptop computer. The second computing device 206 is generally considered to be a computing device having a larger display than the mobile device 102.

[0044] The mobile device 102 comprises a display screen 1412, which may include a touch screen. The mobile device 102 comprises a processor 1414 for executing instructions that are stored in memory 1416. The

mobile device 102 may further comprise non-volatile storage 1418. The instructions stored in memory 1416, when executed by the processor configure the mobile device 102 to provide secondary device messaging functionality 1420 as well as one or more messaging applications 1422. The secondary messaging functionality 1420 establishes a connection with the secondary computing device in order to send message indicators for messages received at the mobile device. The messaging applications 1422 receive messages from respective notification channels, such as e-mail, SMS and MMS messages, IN messages, push notification messages or other messaging applications.

[0045] The mobile device further comprises an input/output (I/O) component 1424 for connecting one or more components capable of providing input to the device or producing output. The mobile device 102 further comprises one or more sensors 1426 as well as one or more radios 1428 for establishing wireless communication with other computing devices.

[0046] The second computing device 206 comprises a display screen 1432, which may include a touch screen. The display 1432 of the second computing device is generally contemplated to be larger than the display of the mobile device 102. The second computing device 206 comprises a processor 1434 for executing instructions that are stored in a memory 1436. The second computing device 206 may further comprise non-volatile storage 1448. The instructions stored in memory 1436, when executed by the processor configure the second computing device 102 to provide mobile device messaging functionality 1440 as well as message notification generation functionality 1442. The mobile device messaging functionality 1440 establishes a connection with the secondary device messaging functionality 1420 of the mobile device in order to receive message indicators for messages received at the mobile device. The message notification generation functionality 1442 may comprise various functionality for generating notifications as described here. The functionality may comprise positioning based action notification functionality 1444. The position based action notification functionality 1444 allows a display representation of a notification that has a direct action area for carrying out a direct action associated with the message, to be progressively displayed based on positioning information of an input component. The message notification generation functionality 1442 may further comprise context based notification functionality for generating a display representation for a notification based on a current operating context of the computing device.

[0047] The second computing device further comprises an input/output (I/O) component 1448 for connecting one or more components capable of providing input to the computing device or producing output. The second computing device 206 further comprises one or more sensors 1450 as well as one or more radios 1452 for establishing wireless communication with other comput-

ing devices.

[0048] Figure 15 depicts a method for generating message notifications at a computing device. The method 1500 receives at the computing device a received message indicator from a mobile device (1502). The received message indicator is associated with a message received by the mobile device. The received message indicator may be sent from the portable computing device to the computing device over a communication channel established between the two devices. The communication channel may be established over a wired or wireless channel, such as Ethernet, Universal Serial Bus (USB), Wi-Fi, Bluetooth, ZigBee or other communication technologies. Once the received message indicator is received at the computing device a first display representation of the received message indicator is generated at the computing device (1504), and positioning information from an input component is determined (1506). Input component may be a mouse or pointing device connected to the computing device, a touch screen input as well as sensors of the mobile device. A second display representation is generated comprising at least a portion of the message received at the mobile device and an action area for performing a direct action in response to the received message when the determined positioning information satisfies a display criteria associated with the second display representation (1508).

[0049] Figure 16 depicts a further method for generating message notifications at a computing device. The method 1600 receives at the computing device a message indicator from a mobile device (1602). The message indicator is associated with a message received by the mobile device. The method determines a current operating context of the computing device (1604) and generates at the computing device a display representation of the message indicator in accordance with notification display settings associated with the determined current operating context (1606). The notification display settings associated with the determined operating context can provide rules for determining how a received message notification should be displayed including whether it should be a blank display that does not provide a visual notification to the user.

[0050] Although certain methods, apparatus, computer readable memory, and articles of manufacture have been described herein, the scope of coverage of this disclosure is not limited thereto. To the contrary, this disclosure covers all methods, apparatus, computer readable memory, and articles of manufacture fairly falling within the scope of the appended claims either literally or under the doctrine of equivalents.

[0051] Although the following discloses example methods, system and apparatus including, among other components, software executed on hardware, it should be noted that such methods, system and apparatus are merely illustrative and should not be considered as limiting. For example, it is contemplated that any or all of these hardware and software components could be em-

bodied exclusively in hardware, exclusively in software, exclusively in firmware, or in any combination of hardware, software, and/or firmware. Accordingly, while the following describes example methods and apparatus, persons having ordinary skill in the art will readily appreciate that the examples provided are not the only way to implement such methods, system and apparatus.

10 Claims

1. A method for generating message notifications at a computing device (206), the method comprising:

receiving (1502) at the computing device (206) a received message indicator (214) from a mobile device (102), the indicator (214) associated with a message (212) received by the mobile device (102);
generating (1504) at the computing device (206) a first display representation (218) of the received message indicator (214);
determining (1506) at the computing device (206) positioning information from an input component (302); and
generating (1508) a second display representation (310) comprising at least a portion of the message received at the mobile device (102) and an action area (320) for performing a direct action (322) in response to the received message (212) when the determined positioning information satisfies a display criteria associated with the second display representation (310).

2. The method of claim 1, wherein the display criteria defines an area on the display in the area surrounding the first display representation.

3. The method of claims 1 or 2, wherein the display criteria defines a touch-based gesture comprising a drag from a first position towards an area on the display surrounding the first display representation.

4. The method of any one of claims 1 to 3, wherein the message indicator identifies a communication channel the notification was received from and a message body.

5. The method of any one of claims 1 to 4, further comprising determining the direct action associated with the message based on a type of message received.

6. The method of claim 5, wherein the direct action comprises one or more of:

replying to the message;
sharing the message with one or more contacts;
marking the message as read; and

deleting the message.

7. The method of any one of claims 1 to 6, further comprising:

5

receiving an input selection corresponding to the direct action; and
sending the input selection to the mobile device.

8. The method of claim 7, wherein the direct action comprises responding to the message and displaying the action area comprises displaying a text box for receiving reply text. 10

9. The method of claim 8, wherein receiving the input selection corresponding to the direct action comprises: 15

receiving reply text in the text box; and
receiving an indication to send the reply text, 20
wherein sending the direct action comprises
sending the reply text to the mobile device.

10. The method of claim 9, wherein sending the direct action further comprises sending the reply text to the mobile device with an indication of the message indicator received from the mobile device. 25

11. The method of any one of claims 1 to 10, further comprising: 30

hiding the first display representation if the positioning information of the pointing device does not satisfy the display criteria within a display time threshold. 35

12. A computing device (206) comprising:

a memory (1436) for storing instructions; and
a processor (1434) for executing the instructions stored in memory, the instructions configuring the computing device (206) to perform the method according to any one of claims 1 to 11. 40

45

50

55




Figure 1

200




Figure 2




Figure 3




Figure 4







Figure 5



(A)




(B)




(C)

Figure 6




(A)




(B)


Figure 7



(A)



(B)



(C)

Figure 8




Figure 9




Figure 10




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15




Figure 16



EUROPEAN SEARCH REPORT

 Application Number
 EP 13 17 4439

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
Y	US 2012/054683 A1 (SANDS KORT [GB] ET AL) 1 March 2012 (2012-03-01) * paragraphs [0062], [0086] * * paragraph [0109] * * paragraph [0117] - paragraph [0136] * * figures 6A-&C *	1-12	INV. G06F3/0488 H04M1/725 G06F3/0481 G06F3/14
Y	WO 2013/011197 A2 (NOKIA CORP [FI]; BRAKENSIEK JOERG [US]; BOSE RAJA [US]) 24 January 2013 (2013-01-24) * paragraph [0024] - paragraph [0053] * * figures 1-3 *	1-12	
Y	US 2011/319136 A1 (LABOWICZ MICHAEL P [US] ET AL) 29 December 2011 (2011-12-29) * paragraph [0015] - paragraph [0016] * * paragraph [0021] - paragraph [0023] * * paragraph [0036] - paragraph [0039] * * paragraph [0043] * * figures 1-2C *	1-12	
Y	WO 2013/083868 A1 (NOKIA CORP [FI]; PALIN ARTO [FI]; NIKARA JARI [FI]; LIUHA PETRI [FI]) 13 June 2013 (2013-06-13) * paragraph [0042] - paragraph [0063] *	1-12	TECHNICAL FIELDS SEARCHED (IPC) G06F H04M
A	US 2010/281409 A1 (RAINISTO ROOPE [FI] ET AL) 4 November 2010 (2010-11-04) * figures 5-8 * * paragraph [0045] - paragraph [0052] * * paragraph [0064] - paragraph [0068] *	1-12	
A	US 2011/260970 A1 (KUO MARGARET ELIZABETH [CA] ET AL) 27 October 2011 (2011-10-27) * figures 4-6 * * paragraph [0045] - paragraph [0052] * * paragraph [0054] - paragraph [0057] *	1-12	
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 28 November 2013	Examiner Maciejewski, Robert
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P04C01)



EUROPEAN SEARCH REPORT

Application Number
EP 13 17 4439

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	GB 2 491 165 A (REALVNC LTD [GB]) 28 November 2012 (2012-11-28) * the whole document * -----	1-12	
			TECHNICAL FIELDS SEARCHED (IPC)
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 28 November 2013	Examiner Maciejewski, Robert
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

3
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 13 17 4439

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

28-11-2013

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2012054683 A1	01-03-2012	CN 103155529 A	12-06-2013
		DE 202011106798 U1	01-02-2012
		EP 2612229 A1	10-07-2013
		US 2012054683 A1	01-03-2012
		WO 2012029022 A1	08-03-2012
WO 2013011197 A2	24-01-2013	US 2013024777 A1	24-01-2013
		WO 2013011197 A2	24-01-2013
US 2011319136 A1	29-12-2011	US 2011319136 A1	29-12-2011
		WO 2011162875 A2	29-12-2011
WO 2013083868 A1	13-06-2013	NONE	
US 2010281409 A1	04-11-2010	US 2010281409 A1	04-11-2010
		WO 2010125451 A1	04-11-2010
US 2011260970 A1	27-10-2011	CA 2797426 A1	03-11-2011
		EP 2564303 A1	06-03-2013
		US 2011260970 A1	27-10-2011
		WO 2011134078 A1	03-11-2011
GB 2491165 A	28-11-2012	GB 2491165 A	28-11-2012
		WO 2012160384 A1	29-11-2012