



(11)

**EP 2 837 518 A8**

(12)

## CORRECTED EUROPEAN PATENT APPLICATION

published in accordance with Art. 153(4) EPC

(15) Correction information:

**Corrected version no 1 (W1 A1)**

**Corrections, see**

Bibliography INID code(s) 71

(51) Int Cl.:

**B60K 15/04** (2006.01)

(86) International application number:

PCT/JP2012/060043

(48) Corrigendum issued on:

15.04.2015 Bulletin 2015/16

(87) International publication number:

**WO 2013/153658 (17.10.2013 Gazette 2013/42)**

(43) Date of publication:

18.02.2015 Bulletin 2015/08

(21) Application number: **12874071.9**

(22) Date of filing: **12.04.2012**

(84) Designated Contracting States:

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB  
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO  
PL PT RO RS SE SI SK SM TR

Designated Extension States:

BA ME

- **KATAOKA, Chiaki**

**Toyota-shi,  
Aichi-ken, 471-8571 (JP)**

- **AKAGI, Masaki**

**Toyota-shi,  
Aichi-ken, 471-8571 (JP)**

(71) Applicant: **TOYOTA JIDOSHA KABUSHIKI**

**KAISHA**

**Toyota-shi, Aichi-ken, 471-8571 (JP)**

(74) Representative: **Kuhnen & Wacker**

## Patent- und Rechtsanwaltsbüro

**Prinz-Ludwig-Straße 40A**

**85354 Freising (DE)**

(72) Inventors:

- **YAMAMOTO, Satoshi**

**Toyota-shi,**

**Aichi-ken, 471-8571 (JP)**

(54) **STRUCTURE FOR FUEL FILLING SECTION OF FUEL TANK**

(57) To obtain a fuel filler structure for a fuel tank wherein when causing an opening and closing valve to close, it can be ensured that the opening and closing valve does not rapidly rotate to a closed position in which it closes a fuel fill inlet, and when causing the opening and closing valve to open, the opening and closing valve can be opened with a small force.

A fuel filler structure (12) is equipped with a damper (32) on the near side of a flapper valve (20) in the insertion direction of a fuel nozzle (28). When the flapper valve (20) rotates to an open position, the damper (32) does not act on the flapper valve (20), and when the flapper valve (20) rotates to a closed position, the damper (32) acts on the flapper valve (20).

FIG. 2

