



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
04.03.2015 Bulletin 2015/10

(51) Int Cl.:
D06F 39/14 (2006.01)
D06F 58/22 (2006.01)
D06F 58/04 (2006.01)
D06F 58/24 (2006.01)

(21) Application number: **14161141.8**

(22) Date of filing: **21.03.2014**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

(72) Inventors:
• **Contarini, Andrea**
33080 Porcia (PN) (IT)
• **Viero, Massimo**
33080 Porcia (PN) (IT)

(30) Priority: **30.08.2013 EP 13182334**
30.08.2013 EP 13182328
30.08.2013 EP 13182331


(74) Representative: **Maccalli, Marco et al**
Maccalli & Pezzoli S.r.l.
Via Settembrini, 40
20124 Milano (IT)

(71) Applicant: **Electrolux Appliances Aktiebolag**
105 45 Stockholm (SE)

(54) **Laundry drying machine**

(57) A laundry machine (100) adapted to dry laundry by means of a flow of drying air, comprising: a machine cabinet (110) for accommodating components necessary for the operation of the laundry machine (100); inside the cabinet, a laundry treatment chamber (105) adapted to contain the laundry to be dried; a cabinet top element (125) incorporating at least part of a drying air circuit in fluid communication with the laundry treating chamber through a drying air inlet opening (210) and through a drying air outlet opening (215) formed in the cabinet top element, the cabinet top element comprising a bottom base element (205) and a top cover (240) and, defined in an interspace between the base element and the top cover, a drying air path for the flow of drying air between said drying air inlet opening (210) and said drying air outlet opening (215), said drying air path including a moisture condensing arrangement (225,230). The drying air inlet opening (210) is formed in a wall (217a) extending within the interspace between the base element (205) of the top element (125) and the top cover (240) thereof.

FIG.4



Description

Background of the invention

Field of the invention

[0001] The present invention relates to laundry treatment appliances or machines. In more detail, the present invention refers to appliances for drying laundry (laundry drying machines), both for domestic and professional use, and particularly to a laundry washing machine also having a laundry drying functionality (laundry washing/drying machines).

Overview of the related art

[0002] Laundry drying and laundry washing/drying machines - which will be referred to simply as laundry machines in the following - typically comprise a casing substantially parallelepiped-shaped forming a machine cabinet. The cabinet accommodates therein a laundry treating chamber, comprising a drum, generally rotatable, apt to contain the laundry to be dried. In laundry washing/drying machines, the drum is rotatably contained in a washing tub, adapted to contain the laundry washing liquid when the machine is operated in laundry washing mode. A front panel of the cabinet has a loading opening to access the treating chamber, for loading/unloading the laundry, and a door is hinged to the cabinet front panel for closing the loading opening, particularly during the laundry machine operation.

[0003] The cabinet also accommodates the electrical, electronic, electro-mechanical, mechanical, and hydraulic components necessary for the operation of the laundry machine. Particularly, laundry machines features an air circuit (comprising, for example, fans, air ducts, a moisture condensing unit, a heating unit, *etc.*) adapted to heat air, blow it into the drum where it removes moisture from the laundry, suck out from the drum the moisturized air, de-moisturize the air and reiterate such actions thereby performing a laundry drying cycle.

[0004] In a known type of laundry machines, also referred to as "condenser dryer", the drying air flow is typically caused to pass through the drum, exiting therefrom from the drum front access opening, then the moisture-laden drying air flow passes through a moisture condensing system, where the humid air is at least partially dehydrated, dried, and the dried drying air flow is heated up by means of a heating arrangement, like an electrical resistance; the heated drying air flow then passes again through the drum, and repeats the cycle.

[0005] The condensing system may be an air-air heat exchanger, exploiting air taken in from the outside.

[0006] Other known laundry machines exploit a heat pump to dehydrate the drying air flow. In these laundry machines, the function of the heating arrangement may be performed by the heat pump itself, and the electrical resistance may thus not be provided for.

[0007] For some household appliance manufacturers, it might be interesting to exploit the already existing design of a laundry washing machine for producing and offering to the customers a laundry washer/dryer. The addition of those components and parts, that are necessary for the laundry drying function, should have as low as possible impact on the already existing design; in particular, the additional components should be housed within the already existing laundry washing machine cabinet.

[0008] EP 2270274 discloses a top adapted to match and close from above a cabinet of a laundry drying appliance, the top being formed as a ready-to-mount part ready to be mounted to the cabinet and forming a moisture condensing module for dehydrating drying air used to dry laundry within a drying drum of the laundry drying appliance. The top has a drying air inlet, a drying air outlet, fluid passageways defined therein from said drying air inlet to said drying air outlet for the passage of the drying air to be dehydrated and moisture condensing means arranged inside said fluid passageways.

[0009] The top disclosed in EP 2270274, once assembled, forms a unit that is ready to be mounted to the machine cabinet, simply by placing the top in the correct alignment, so that the drying air inlet opening and the drying air outlet opening match an outlet of a drying air return duct and, respectively, an intake of a drying air circulation fan, both of which are fixed, rigidly connected to the machine cabinet. In such a way, the outlet of the return air duct and the air intake of the air circulation fan act as automatic positioning and centering means for the top, simplifying the mounting thereof: the operation of mounting of the top onto the cabinet simply consists in laying the top on the cabinet properly positioning it with the help of the self-centering action achieved by the matching of the openings provided in the top with the outlet and air intake; in this way, all the necessary connections for the drying air circulation circuit are completed, and there is no necessity to perform any additional connection.

Summary of the invention

[0010] The Applicant believes that while the top disclosed in EP 2270274 is advantageous under several respects, has some drawbacks.

[0011] In particular, a disadvantage of the top disclosed in EP 2270274 consists in that possible leakage of drying air (process air) may occur after the top has been assembled to the machine cabinet. In fact, the positioning of the top is the only occasion for coupling the drying air circuit portion located within the top with the remaining drying air circuit portion placed under the top, i.e. in a lower volume of the machine cabinet. Once the top is assembled to the cabinet, the drying conduit cannot be reached anymore. Since a leakage of process air reduces the performance of a drying process, it would be desirable to improve the fixation of the drying air circuit

portions and its verification by an assembler, to avoid any risk of drying air leakage during a drying process.

[0012] One aspect of the present invention proposes a laundry machine adapted to dry laundry by means of a flow of drying air. The laundry machine comprises a cabinet for accommodating components necessary for the operation of the laundry machine. Inside the cabinet, a laundry treating chamber adapted to contain the laundry to be dried. A cabinet top element is provided incorporating at least part of a drying air circuit in fluid communication with the laundry treating chamber through a drying air inlet opening and through a drying air outlet opening formed in the cabinet top element. The cabinet top element comprises a bottom base element and a top cover. A drying air path for the flow of drying air between said drying air inlet opening and said drying air outlet opening is defined in an interspace between the base element and the top cover, and said drying air path includes a moisture condensing arrangement for demisting the drying air. The drying air inlet opening is formed in a wall extending within the interspace between the base element of the top element and the top cover thereof.

[0013] Preferred features of the present invention are set in the dependent claims.

[0014] For example, the base element advantageously comprises an aperture adjacent to the drying air inlet opening. The machine may comprise a return drying air hose coupled at one end thereof to the drying air inlet opening and, at another end, to a drying air outlet of the laundry treatment chamber. The drying air inlet opening is preferably surrounded by a projecting collar arranged in said interspace between the base element and the top cover and the return drying air hose is coupled to the collar. Said wall preferably extends substantially perpendicularly to the base element and the top cover. Advantageously, said wall is formed integrally with the top base element. The end of the return drying air hose that is coupled to the drying air inlet opening may be secured to the projecting collar by means of a hose clamp. Also the end of the return drying air hose that is coupled to the drying air outlet of the laundry treatment chamber may be secured thereto by means of a hose clamp. Advantageously, the return drying air hose may be provided, proximate to the end thereof that is coupled to the drying air inlet opening, with an annular seat for accommodating the first hose clamp. Similarly, the return drying air hose may be provided, proximate to the end thereof that is coupled to the drying air outlet of the laundry treatment chamber, with an annular seat for accommodating the hose clamp.

[0015] Advantageously, the moisture condensing arrangement comprises heat-exchanging units part of a heat pump arranged for exchange of heat between the drying air and a heat pump refrigerant fluid, the heat pump further comprising a refrigerant fluid compressor expediently installed inside the laundry machine cabinet at a bottom part of the laundry machine, particularly attached

to a laundry machine basement.

[0016] Preferably, the refrigerant fluid compressor is in fluid communication with said heat-exchanging units in the top through flexible refrigerant fluid conduits running along a vertical corner of the machine cabinet.

[0017] A refrigerant fluid compressor cooling fan is preferably provided, arranged inside the machine cabinet at the bottom of the laundry machine, preferably attached to the laundry machine basement.

[0018] Thanks to the present invention, it is easier for the machine assembler to ensure that the portion of the drying air circuit outside the cabinet top is connected in an air-tight manner to the portion of the drying air circuit formed within the top.

Brief description of the drawings

[0019] These, and others, features and advantages of the solution according to the present invention will be better understood with reference to the following detailed description of some embodiments thereof, provided for illustrative and not restrictive purposes, to be read in conjunction with the attached drawings. In this regard, it is expressly intended that the drawings are not necessarily to scale and that, unless specified otherwise, they simply aim to conceptually illustrate the structures and procedures. In particular:

Figure 1 is a perspective view of a laundry machine according to an embodiment of the present invention;

Figure 2 is a perspective view of the laundry machine of **Figure 1**, showing a cabinet top thereof in exploded view;

Figure 3 is a perspective view of a base element of the top of the laundry machine according to an embodiment of the present invention;

Figure 4 shows, in perspective exploded view, the cabinet top with a drying air return hose coupled to top and to a drying air outlet of a laundry treatment chamber of the laundry machine;

Figure 5A shows in perspective view the cabinet top with the drying air return hose uncoupled from the top;

Figure 5B is a perspective view from below of a detail of **Figure 5A**;

Figure 6 shows the drying air return hose, and

Figure 7 is a perspective view from the rear of the laundry machine with dismounted cabinet panels.

Detailed description of embodiments of the invention

[0020] With reference to the drawings, **Figure 1** is a perspective view of a laundry machine, globally denoted as **100**, according to an embodiment of the present invention.

[0021] The laundry machine **100** comprises a laundry treatment chamber **105** for accommodating the items to

be dried or washed and dried, such as clothes, garments, linen, and similar laundry items. Preferably, the laundry treatment chamber **105** includes a drum (not shown in the figures) rotatably mounted inside a machine casing or cabinet **110**, and in case the laundry machine **100** is a washing/drying laundry machine the drum is arranged within a tub (the tub is not shown in **Figure 1**; it is shown in **Figure 4**) housed in the machine casing or cabinet **110**.

[0022] The cabinet **110** generally accommodates all the electrical, electronic, mechanical, and hydraulic components necessary for the operation of the laundry machine. The cabinet **110** has generically a parallelepiped shape, with a front wall **115**, two side walls **120** (only one visible in **Figure 1**), a rear wall (not visible), a basement and a top **125**. The front wall **115** of the cabinet **110** is provided with an access opening for accessing the drum and with an associated door **117**, hinged to the front wall **115**, for closing the access opening. In the upper part of the front wall **115**, a machine control panel **130** is located, and, aside the control panel **130**, a drawer **135** is provided, which is part of a washing treatment products dispensing arrangement, for loading laundry washing treatment products like detergents and softeners. The top **125** closes the cabinet **110** from above, and defines a work-top.

[0023] In one embodiment of the invention, a de-fluff filter (aesthetic) cover **140** is exposed on the control panel **130** on the front wall **115**, e.g. above the drawer **135**, and flush therewith.

[0024] Reference is now made to **Figures 2** and **3**, which are, respectively, a perspective view of the laundry machine **100** with its top **125** in exploded view and a perspective view of a base element **205** of the top **125** with some parts removed.

[0025] In one embodiment of the invention, the top **125** is formed as a ready-to-mount part ready to be mounted to the cabinet. The top **125** integrates part of a drying air circuit adapted to circulate drying air across the laundry treating chamber **105** for drying the laundry stored therein. In particular, the top **105** forms a moisture condensing module for dehydrating drying air used to dry laundry within a drying drum of the laundry drying appliance. As described hereinafter, the top has a drying air inlet, a drying air outlet, and fluid passageways defined therein-side from said drying air inlet to said drying air outlet for the passage of the drying air to be dehydrated. Moisture condensing means are arranged inside said fluid passageways.

[0026] In greater detail, according to an embodiment of the present invention, the top **125** comprises the base element **205**, e.g. made of plastic, which has a drying air inlet opening **210** and a drying air outlet opening **215**. The drying air inlet opening **210** is in fluid communication (as described in greater detail afterwards) with the laundry treatment chamber **105** through a chamber drying air outlet. The drying air outlet opening **215** is in fluid communication with a blowing arrangement **216**.

[0027] The blowing arrangement **216** comprises a fan

and a corresponding fan duct. The fan blows the drying air inside the air circuit by sucking drying air from the air outlet opening **215** and blowing the drying air into the laundry treatment chamber **105**, the air outlet opening **215** and the laundry treatment chamber **105** being both fluidly connected to the blowing arrangement **216**.

[0028] In a region of the base element **205**, preferably near the front-left corner thereof, a de-fluff filter housing **217** is provided suitable to house a de-fluff filter **218**. The filter housing **217** has for example (but not limitatively) roughly a right trapezoid outline in plan view (e.g., similar to a grand piano), with a shorter sidewall **217a** (corresponding to a lesser base of the right trapezoid) in which the drying air inlet opening **210** is formed, and a larger sidewall **217b** (opposite to the shorter sidewall **217a**, and corresponding to a greater base of the right trapezoid) that has a housing aperture **219** opened on the machine front wall **115** for example above the drawer **135** for allowing the insertion of the de-fluff filter **218**. The filter housing **217** further comprises a right sidewall **217c** substantially corresponding to a portion of a lateral sidewall of the base element **205** of the top **125** (and corresponding to the right leg of the right trapezoid) and a transversal opened side **217d**, preferably inclined (opposite to the right sidewall **217c** and corresponding to the inclined leg of the right trapezoid). The sidewalls of the filter housing **217**, particularly the shorter sidewall **217a**, projects substantially orthogonally from a base plane of the top base element **205**. In alternative embodiments the sidewall **217a**, may form an angle α with a base plane of the top base element **205** such that $0^\circ < \alpha \leq 90^\circ$.

[0029] In one embodiment of the present invention, the drying air inlet opening **210** is fluidly connected to an adapter element **212**, which is provided to fluidly connect the drying air inlet opening **210** with the filter housing **217** and the de-fluff filter **218** (when inserted in the filter housing **217**). Preferably, but not limitatively, the adapter element **212** may be a parallelepiped-shape element adapted to be coupled to the base element **205**, with conical or cylindrical passage(s) provided therein with two opposite apertures to fluidly connect the drying air inlet opening **210** with the de-fluff filter **218**. The adapter element **212** may be made of any suitable material, e.g. a polymeric material, and is coupled to the base element **205** by means of any suitable coupling arrangement, e.g. by tightly fitting a rear portion of the filter housing **217** (adjacent to the shorter sidewall **217a**).

[0030] In a preferred embodiment of the invention, the aperture facing the filter housing **217** of the adapter element **212** is surrounded by a gasket element **212a** which protrudes towards the inside of the filter housing **217**. In alternative embodiments of the present invention in which the adapter element **212** is not provided, an alternative gasket element may be directly provided around the inlet opening **210**.

[0031] In one embodiment of the present invention, the transversal opened side **217d** of the filter housing **217** comprises a frame **220** that defines a plurality of side

windows **220a** separated one from the other by separating elements, such as for example mullion elements **220b**, preferably prism-shaped. Advantageously, a plurality of flap elements **222** may be provided, protruding from the frame **220** opposite to the filter housing **217** in order to direct the drying air flow exiting the transversal opened side **217d** towards the remaining of the air circuit defined in the top **125**.

[0032] In an embodiment of the present invention, a heat pump is used for condensing the moisture of, i.e. de-hydrating, the drying air and for heating the drying air after the de-hydration.

[0033] In particular, in the central region of the base element **205**, there is accommodated a first heat-exchanging unit of the heat pump, forming a moisture condensing element **225**, for example comprising a refrigerant fluid evaporator of the heat pump. The moisture condensing element **225** is adjacent to the transversal opened side **217d** of the filter housing **217**, so as to receive the drying air after the latter has passed through the de-fluff filter **218**. Next to the moisture condensing element **225**, opposite to the filter housing **217**, there is provided a second heat-exchanging unit, forming a drying air heating element **230**, for example comprising a condenser of the refrigerant fluid of the heat pump. The moisture condensing element **225** has the function of de-hydrating the drying air, by cooling it down. The drying air heating element **230** has instead the function of heating the dehydrated drying air.

[0034] The first and second heat-exchanging units **225** and **230** are parts of a refrigerant fluid circuit of the heat pump. The refrigerant fluid circuit further comprises a lamination device (e.g. a refrigerant fluid expansion valve) between the first and second heat-exchanging units **225** and **230**, and a refrigerant fluid compressor. In an embodiment of the present invention, visible in **Figure 7**, the refrigerant fluid compressor **705** is located at the bottom of the cabinet **110**, e.g. attached to a basement **710** of the laundry machine **100**, and is fluidly connected to the heat-exchanging units **225** and **230** accommodated in the top **125** by means of refrigerant fluid pipes **715** that preferably run along a rear corner of the cabinet **110** or along the laundry treatment chamber **105** of the laundry machine **100**. Preferably, the refrigerant fluid pipes **715** are flexible pipes: this facilitates the machine assembling operations, particularly the fluid connection of the compressor **705** mounted to the machine basement **710** to the heat pump heat-exchanging elements **225** and **230** in the cabinet top **125**.

[0035] In alternative embodiments of the present invention, the refrigerant fluid compressor may be attached to the underside of the base element **205** of the top **125**, e.g. in correspondence of the front-right corner thereof, the body of the compressor hanging in such a case from below the base element **205**. However, the installation of the compressor **705** at the bottom of the cabinet **110**, attached to the machine basement **710**, may be preferable because at the bottom of the cabinet **110** there is

usually more room than at the top, the machine basement **710** is rigid and resistant, and the compressor cooling is better than at the top of the machine. The existence of more room at the machine bottom also facilitates the provision of a compressor cooling fan **720**, for promoting the compressor cooling. Preferably the cooling fan is attached to the machine basement **710**.

[0036] In different embodiments of the present invention, the laundry machine **100** may comprise an air-air or an air-water heat exchanger apparatus and an electric heater instead of the heat pump. The air-air or air-water heat exchanger apparatus and, possibly, the electric heater are advantageously accommodated inside the top **125**.

[0037] The base element **205** of the top **125** is covered by an inner panel **235**, that covers essentially the first and second heat-exchanging units **225** and **230** and the de-fluff filter **218**. The top **125** is completed by an outer (aesthetic) panel **240** that can be secured to the top based element **205** e.g. by screwing. The base element **205** and the inner panel **235** define an air-path that conveys the moisture-laden air coming from the laundry treatment chamber **105** (through the drying air inlet opening **210**) towards the de-fluff filter **218**, preventing the moisture-laden air from entering directly (i.e., before being filtered by the de-fluff filter **217**) the moisture condensing element **225** or the drying air heating element **230**, and then the drying air flow follows the air path from the de-fluff filter **218** to the heating element **230**, passing through the moisture condensing element **225**, eventually reaching the drying air outlet opening **215**, where the de-hydrated and heat drying air is sucked by the fan and blown into the laundry treatment chamber **105**.

[0038] As mentioned in the foregoing, the top **125**, once assembled, forms a unit that is ready to be mounted to the cabinet **110**, simply by placing it in the correct alignment, particularly with the drying air outlet opening **215** matching the intake of the blowing arrangement **216**. The top **125** may be secured to the cabinet **110** by conventional means (e.g., by means of gluing, screwing or other connecting means).

[0039] According to the present invention, for the fluid connection of the drying air inlet opening **210** provided in the top **125** to the drying air outlet of the laundry treatment chamber **105**, a drying air return hose **405** is used. The hose **405** is shown per-se in **Figure 6**, while in **Figures 4** and **5A, 5B** there is shown the coupling of the hose **405** to the drying air inlet opening **210** of the top **125** (and to a drying air outlet of the laundry treatment chamber **105**, e.g. of the tub of a laundry washer/dryer).

[0040] The hose **405** is elbow-shaped, having a roughly "S" shape and is preferably flexible and collapsible/extendible to a certain extent. To this purpose, the hose **405** is, at least partly, corrugated: for example, in the example shown in **Figure 6** the hose **405** has a corrugated portion **605**.

[0041] Preferably, the drying air inlet opening **210** is surrounded by a projecting collar **410**, projecting from

the sidewall **217a** of the de-fluff filter housing **217** opposite to the filter housing **217**, i.e. the collar **410** projects towards the rear of the top **125**. For example, the sidewall **217a** is generally perpendicular to a base plane of the top base element **205**, and the collar **410** extends substantially orthogonally to the sidewall **217a**, so that the collar **410** has an axis that is substantially parallel to the base plane of the top base element **205** and both the sidewall **217a** and the collar **410** extend in an interspace between the top base element **205** and the top outer panel **240**. For allowing the coupling of the hose **405** to the collar **410** surrounding the drying air inlet opening **210**, an aperture **250** is formed in the top base element **205**, in the shown example in the region thereof near the rear left corner of the top base element **205**.

[0042] The hose **405** has two open extremities, **610-1** and **610-2**, respectively for the coupling to drying air outlet of the laundry treatment chamber **105** and for coupling to the drying air inlet opening **210** formed in top **125**. Preferably, one or both of the hose extremities **610-1**, **610-2** are flanged.

[0043] The hose extremity **610-2** has an inner diameter slightly greater than the external diameter of the collar **410**. The hose extremity **610-2** is slipped on the collar **410**, and then, for securing the hose **405** to the collar **410**, a hose clamp **415** is used, that is tightened around the portion of the hose **405** near the extremity **610-2** slipped on the collar **410**. Preferably, a projecting ring **417** is formed externally on the hose **405** near the extremity **610-2** thereof, so as to define, together with the flange at the extremity **610-2**, an annular seat **419** for accommodating and keeping in place the hose clamp **415**.

[0044] Preferably, the drying air outlet of the laundry treatment chamber **105** is formed in the cylindrical wall of the tub, as shown in **Figure 4**.

[0045] Similarly to the drying air inlet opening **210** formed in the top **125**, a collar is provided around the drying air outlet of the laundry treatment chamber **105**. The hose extremity **610-1** has an inner diameter slightly greater than the external diameter of the collar surrounding the drying air outlet of the laundry treatment chamber **105**, so the hose extremity **610-1** can be slipped on the collar, and then, for securing the hose **405** to the collar, a hose clamp **420** is used, that is tightened around the portion of the hose **405** near the extremity **610-1** slipped on the collar. Similarly to the hose extremity **610-2**, a projecting ring **430** is preferably formed externally on the hose **405** near the extremity **610-1** thereof, so as to define, together with the flange at the extremity **610-1**, an annular seat for accommodating and keeping in place the hose clamp **420**.

[0046] Thus, the portion of the drying air circuit outside the top **125**, comprising the drying air return hose **405**, accesses the portion of the drying air circuit formed within the top **125** through the aperture **250** formed in the top base element **205**. The portion of the drying air circuit outside the top **125**, particularly the drying air return hose

405, connects to the portion of the drying air circuit formed within the top **125** via the drying air inlet opening **210** formed in the sidewall **217a**.

[0047] In the laundry machine **100**, when operated in dryer mode (i.e., for drying items stored in the drum), drying air (i.e., warm and dry air) is typically caused to flow through the drum **105** inside the laundry treating chamber **105**, where the items to be dried are contained. The drying air binds to moisture particles from the laundry and/or dispersed within the laundry treating chamber **105** and carries them away. The drying air may also carry away fluff (e.g., generated from the laundry during laundry treating processes) from the laundry together with moisture particles. After exiting the drum through the chamber outlet, the flow of now moisture-laden drying air passes through the de-fluff filter **218** where substantially any fluff carried by the drying air flow together with moisture particles is caught and remains trapped. Instead, the moisture-laden drying air is conveyed towards the moisture condensing element **225**, where the moisture-laden drying air is at least partially dried, i.e. dehydrated, and such dehydrated drying air flow is then heated by the air heating element **230** through which the drying air flows, which heats the drying air up to a drying temperature (e.g., set by a user through the control panel **130** via the selection of a drying program). Then the drying air is sucked by the fan through the fan intake and is caused to pass again through the drum **105** drying the laundry therein stored and then repeating the cycle just described.

Claims

1. A laundry machine (**100**) adapted to dry laundry by means of a flow of drying air, comprising:

a machine cabinet (**110**) for accommodating components necessary for the operation of the laundry machine (**100**);
inside the cabinet, a laundry treatment chamber (**105**) adapted to contain the laundry to be dried;
a cabinet top element (**125**) incorporating at least part of a drying air circuit in fluid communication with the laundry treating chamber through a drying air inlet opening (**210**) and through a drying air outlet opening (**215**) formed in the cabinet top element, the cabinet top element comprising a bottom base element (**205**) and a top cover (**240**) and, defined in an interspace between the base element and the top cover, a drying air path for the flow of drying air between said drying air inlet opening (**210**) and said drying air outlet opening (**215**), said drying air path including a moisture condensing arrangement (**225,230**),

characterized in that

the drying air inlet opening (210) is formed in a wall (217a) extending within the interspace between the base element (205) of the top element (125) and the top cover (240) thereof.

2. The laundry machine (100) of claim 1, wherein the base element (205) comprises an aperture (250) adjacent to the drying air inlet opening (210). 5
3. The laundry machine (100) of claim 1 or 2, comprising a return drying air hose (405) coupled at one end (610-2) thereof to the drying air inlet opening (210) and, at another end (610-1), to a drying air outlet of the laundry treatment chamber (105). 10
4. The laundry machine (100) of claim 3, wherein the drying air inlet opening (210) is surrounded by a projecting collar (410) arranged in said interspace between the base element and the top cover and the return drying air hose (405) is coupled to the collar (410). 15
5. The laundry machine (100) of any one of the preceding claims, wherein the wall (217a) extends substantially perpendicularly to the base element (205) and the top cover (240). 20
6. The laundry machine (100) of any one of the preceding claims, wherein the wall (217a) is formed integrally with the base element (205). 25
7. The laundry machine (100) of any one of claims 4 to 6 when depending from claim 3, wherein the end (610-2) of the return drying air hose (405) coupled to the drying air inlet opening (210) is secured to the projecting collar (410) by means of a first hose clamp (415). 30
8. The laundry machine (100) of any one of claims 3 to 7 when depending from claim 3, wherein the end (610-1) of the return drying air hose (405) coupled to the drying air outlet of the laundry treatment chamber (105) is secured thereto by means of a second hose clamp (420). 35
9. The laundry machine (100) of claim 7 or 8, wherein the return drying air hose (405) is provided, proximate to the end (610-2) of the return drying air hose (405) coupled to the drying air inlet opening (210), with an annular seat (419) for accommodating the first hose clamp (415). 40
10. The laundry machine (100) of claim 9 when depending from claim 8, wherein the return drying air hose (405) is provided, proximate to the end (610-1) of the return drying air hose (405) coupled to the drying air outlet of the laundry treatment chamber (105), with a further annular seat for accommodating the 45

second hose clamp (420).

11. The laundry machine (100) of any one of the preceding claims, wherein said moisture condensing arrangement (225,230) comprises heat-exchanging units part of a heat pump arranged for exchange of heat between the drying air and a heat pump refrigerant fluid, the heat pump further comprising a refrigerant fluid compressor (705) installed inside the laundry machine cabinet (110) at a bottom part of the laundry machine, particularly attached to a laundry machine basement (710). 50
12. The laundry machine (100) of claim 11, wherein the refrigerant fluid compressor (705) is in fluid communication with said heat-exchanging units (225,230) in the top (125) through flexible refrigerant fluid conduits (715), preferably running along a vertical corner of the machine cabinet (110). 55
13. The laundry machine (100) of claim 11, further comprising a refrigerant fluid compressor cooling fan (720) arranged inside the machine cabinet (110) at the bottom of the laundry machine, preferably attached to the laundry machine basement (710).




FIG.1




FIG.2







FIG.3

FIG.4








FIG. 6




FIG. 7



EUROPEAN SEARCH REPORT

Application Number
EP 14 16 1141

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X,D	EP 2 270 274 A1 (ELECTROLUX HOME PROD CORP [BE]) 5 January 2011 (2011-01-05) * the whole document *	1-13	INV. D06F39/14 D06F58/04 D06F58/22 D06F58/24
A	EP 2 385 163 A1 (ELECTROLUX HOME PROD CORP [BE]) 9 November 2011 (2011-11-09) * the whole document *	1-13	
			TECHNICAL FIELDS SEARCHED (IPC)
			D06F
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 14 January 2015	Examiner Spitzer, Bettina
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

1
EPO FORM 1503 03.82 (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 14 16 1141

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

14-01-2015

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 2270274 A1	05-01-2011	CN 102686792 A	19-09-2012
		EP 2270274 A1	05-01-2011
		EP 2660381 A1	06-11-2013
		EP 2660382 A1	06-11-2013
		EP 2660383 A1	06-11-2013
		RU 2012102983 A	10-08-2013
		US 2012159800 A1	28-06-2012
EP 2385163 A1	09-11-2011	WO 2011000760 A1	06-01-2011
		BR P11102068 A2	30-10-2012
		EP 2385163 A1	09-11-2011
		US 2011265523 A1	03-11-2011

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- EP 2270274 A [0008] [0009] [0010] [0011]