



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 71

(51) Int Cl.:
F04B 43/12 ^(2006.01) **A61M 5/142** ^(2006.01)

(86) International application number:
PCT/JP2013/080765

(48) Corrigendum issued on:
25.11.2015 Bulletin 2015/48

(87) International publication number:
WO 2014/077308 (22.05.2014 Gazette 2014/21)

(43) Date of publication:
30.09.2015 Bulletin 2015/40

(21) Application number: **13855928.1**

(22) Date of filing: **14.11.2013**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

(72) Inventors:
• **KOYAMA Masahiro**
Tokyo 123-8511 (JP)
• **NAKAMURA Shouta**
Tokyo 123-8511 (JP)
• **KASHIWAGI Makoto**
Tokyo 123-8511 (JP)
• **KOGURE Hiroyuki**
Tokyo 123-8511 (JP)
• **TAJIMA Hiroyuki**
Tokyo 123-8511 (JP)

(30) Priority: **14.11.2012 JP 2012250349**

(74) Representative: **Prinz & Partner mbB**
Patent- und Rechtsanwälte
Rundfunkplatz 2
80335 München (DE)

(71) Applicants:
• **Namiki Seimitsu Houseki Kabushiki Kaisha**
Tokyo 123-8511 (JP)
• **Namiki Precision Singapore Pte. Ltd.**
Singapore 068804 (SG)

(54) **TUBING PUMP**

(57) **PROBLEM:** To improve opening and closing operability of a door.

SOLUTION: A tubing pump for transferring a fluid in a detachably attached tube 30 by a pump mechanism 50, the tubing pump is equipped with: a pump body 10 having a base 11 to and from which the tube 30 can be attached and detached; a door 20 pivotally supported to be rotatable with respect to the pump body 10, so as to open or close the base 11; switching urging unit A for urging the door 20 in an opening direction in a first rotation range R1 on a completely opened side and switching an urging direction to a closing direction in a second rotation range R2 on a completely closed side; and closing suppression unit B for suppressing an urging force in the closing direction by the switching urging unit A in the second rotation range R2.

FIG. 5

