



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Abstract

(51) Int Cl.:
G06F 3/0488 ^(2013.01) **G06F 3/023** ^(2006.01)
G06F 3/041 ^(2006.01) **H03M 11/04** ^(2006.01)
H04M 1/00 ^(2006.01)

(48) Corrigendum issued on:
06.01.2016 Bulletin 2016/01

(86) International application number:
PCT/JP2013/079356

(43) Date of publication:
21.10.2015 Bulletin 2015/43

(87) International publication number:
WO 2014/069504 (08.05.2014 Gazette 2014/19)

(21) Application number: **13851150.6**

(22) Date of filing: **30.10.2013**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

- **KOBAYASHI, Shigeko**
Tokyo 100-6150 (JP)
- **TSUKAMOTO, Masakatsu**
Tokyo 100-6150 (JP)
- **AOYAGI, Sadanori**
Tokyo 100-6150 (JP)
- **MORINAGA, Yasuo**
Tokyo 100-6150 (JP)

(30) Priority: **05.11.2012 JP 2012243783**

(71) Applicant: **NTT DOCOMO, INC.**
Chiyoda-ku
Tokyo 100-6150 (JP)

(74) Representative: **MERH-IP Matias Erny Reichl**
Hoffmann
Patentanwälte PartG mbB
Paul-Heyse-Strasse 29
80336 München (DE)

(72) Inventors:
• **TAGAYA, Masashi**
Tokyo 100-6150 (JP)

(54) **TERMINAL DEVICE, SCREEN DISPLAY METHOD, HOVER LOCATION CORRECTION METHOD, AND RECORDING MEDIUM**

(57) A terminal device is provided which is capable of making a key display with which a user makes an input easily. A hover position detection unit measures a distribution of a physical quantity indicating a degree of approach of an operation finger to a touch panel, and detects a hover position from the distribution of the physical quantity. A target key identification unit identifies, as a target key, a key corresponding to a display region including coordinates of the hover position. A user assistance display control unit generates a display control signal indicating that an assistance display that represents the target key is to be displayed at a different position from a display position of the target key. A display makes a screen display in accordance with the display control signal.

FIG. 9

