



(11) **EP 2 993 052 A1**

(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
09.03.2016 Bulletin 2016/10

(51) Int Cl.:
B41M 3/12 ^(2006.01) **B41C 1/16** ^(2006.01)
G03C 11/12 ^(2006.01)

(21) Application number: **14791329.7**

(86) International application number:
PCT/ES2014/000065

(22) Date of filing: **29.04.2014**

(87) International publication number:
WO 2014/177732 (06.11.2014 Gazette 2014/45)

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**
Designated Extension States:
BA ME

(72) Inventor: **Gomez Portela, Julio**
08003 Barcelona (ES)

(30) Priority: **30.04.2013 ES 201330634**

(74) Representative: **Juncosa Miro, Jaime et al**
Torner, Juncosa i Associates, S.L.
Gran Via de les Corts
Catalanes, 669 bis, 1^o, 2^a
08013 Barcelona (ES)

(71) Applicant: **Gomez Portela, Julio**
08003 Barcelona (ES)

(54) **MULTILAYER LAMINAR ELEMENT AND METHOD FOR TRANSFERRING IMAGES TO A THREE-DIMENSIONAL SURFACE**

(57) The multilayer laminar element comprises: a first gelatin layer with a humidity content less than 10%, which, when moistened, becomes soft and elastic; and a second layer providing a transparent cover that is elastic and printable so that it can receive the printed image to be transferred. An adhesive is applied to the outer face

of said cover, which allows attaching the laminar element to a three-dimensional surface with the cover facing and in contact with said three-dimensional surface, and following the positioning of the laminar element on said three-dimensional surface, the aforementioned first gelatin layer is removed in the moistened state.

EP 2 993 052 A1

Description

Technical Field

[0001] The invention relates to a multilayer laminar element conceived for making it easy to transfer or apply images to a body, object or surface, particularly a three-dimensional surface, with primarily decorative functions, by superimposing and attaching one of the laminar layers of the multilayer laminar element integrating a printed image on said three-dimensional surface and eliminating another layer or layers.

[0002] The invention also relates to a method for transferring images to a body using the mentioned multilayer laminar element.

[0003] The reference made to "image" in the present specification must be understood as being extensive to any graphic composition, with images or a mixed composite with text and images.

Background of the Invention

[0004] Patent document EP 1 102 122 B1, belonging to the same inventor as the present invention, discloses a method for transferring an image to a three-dimensional body using a gelatin sheet. This invention proposes the steps of:

- providing an unsupported gelatin sheet;
- printing an image onto the gelatin sheet when it is in the solid state (with a water content less than 10%);
- moistening the sheet such that it becomes soft and flexible, and
- applying the sheet in this soft and flexible state on a three-dimensional surface or body, where, taking advantage of the elasticity and of the fact that it is adhesive in this state, it is fixed by said application to said three-dimensional surface or body, providing the printed image and being applied in situ.

[0005] Printing on the sheet is advantageously performed by means of ink-jet printing.

[0006] In a preferred embodiment, the sheet is subjected to heating at a temperature in the order of 35 to 45°C, during the step of applying it to said three-dimensional surface or body.

[0007] The printed image is generally not on the contact surface of the gelatin sheet and the three-dimensional body/object or surface, but the sheet can also be attached on a surface such that the image is on contact face with said surface. In this case, if the ink of the image is impermeable the, contact face of said surface must be impregnated with an adhesive.

[0008] Although the described method has been shown to be very useful, it suffers from the drawback derived from the dimensional instability of gelatin taking into account that the gelatin sheet must be attached at all times to the three-dimensional surface, as a support

for the transferred printed image. Said instability is particularly due to changes and/or variations that may be experienced in relative humidity and temperature of the environment surrounding the sheet over time, which can compromise the fixing thereof to the three-dimensional surface and deteriorate the image it supports.

[0009] For this reason, the invention proposes an alternative laminar element and a method for transferring images to a three-dimensional surface using said multilayer laminar element.

Description of the invention

[0010] For that purpose, the invention proposes a multilayer laminar element for transferring images to a three-dimensional body or surface comprising in a basic embodiment:

- a first gelatin layer in the solid state (water content less than 10%), and
- a second layer (or several layers) superimposed on the preceding layer, integrating a transparent, elastic (or one that acquires elasticity due to moistening) and printable (advantageously by means of an ink-jet printer) cover for thus receiving the image to be transferred.

[0011] The mentioned first layer, when moistened, becomes soft and elastic as explained in the European patent mentioned as a background document, which allows, particularly by means of the use of an adhesive arranged on the second layer or cover, after printing thereof with the image to be transferred, applying the composition to said three-dimensional surface with the printed face of the cover facing and in contact with said surface. Then, the aforementioned first gelatin layer, in the moistened state, can be readily separated from the cover, the image accompanying it then being completely integrated on the three-dimensional surface of interest.

[0012] It is obvious that the mentioned adhesive for fixing the proposed multilayer laminar element could be deposited on the three-dimensional surface to which it must be attached, placing the mentioned cover against the surface with adhesive.

[0013] In other words, in the present invention the gelatin sheet is used as a support for the second layer or cover which is where the image will be printed and which will be applied to the three-dimensional surface or body.

[0014] In the event that more than one of the layer or layers could be used, as a cover they have the feature of being transparent and printable. With respect to being elastic, this will be due to the nature of the material of the sheet or it is the result of the humidity provided to the gelatin sheet prior to or during the operation of applying the multilayer element on the three-dimensional surface for transferring the image

[0015] The transparent cover can have various compositions, such as a polyurethane, an acrylic copolymer

and mixtures thereof. Some conditions relating to the material used will be indicated below, depending on the ink used in the printing process.

[0016] Generally the cover has a thickness that is much less than that of the gelatin layer, which is from 60 to 70 microns, whereas said cover can be from 3 to 40 microns, and generally between 3 and 20 microns. Said reduced thickness results in applying the printed image with minimal alteration of the features of the three-dimensional surface on which it is fixed through the mentioned cover, leading to full integration printing of the image on said outer surface.

[0017] Efforts will be made so that with the humidity provided in the process of application, the gelatin sheet will readily detach from the cover. In an alternative embodiment, it is envisaged as having an intermediate layer that is soluble with the humidity, selected from, for example, acacia gum or polyvinyl alcohol.

[0018] An important aspect to be taken into account is based on the ink used for the ink-jet printing process.

[0019] Three fundamental types of ink have been identified and tested for said (ink-jet) printing process to implement this invention:

- Ultraviolet-curable inks, which adhere perfectly in a wide range of materials, which allows using a polyurethane, an acrylic copolymer, a vinyl resin or mixtures thereof as a cover.
- Solvent and eco-solvent inks. Polyurethanes, acrylic resins as well as mixtures of both can be used to assure correct printing.
- Aqueous inks. There are a number of formulations in the state of the art which allow for correct printing. The cover on which the image is printed has to be water-absorbent in this case and it must also absorb other components present in the ink. Suitable formulations can comprise polyvinyl alcohol (PVA) or some polyurethanes.

[0020] In the case of aqueous inks and given that the ink-receiving layer (the cover) must necessarily be water-absorbent, are proposed two configurations:

- The adhesive used, which is superimposed on the cover, is aqueous, such that it will transmit humidity to the set of layers, making it elastic and adherent in this process.
- The adhesive used is an aqueous adhesive, but an impermeable layer is arranged between the image-receiving layer (cover) and the gelatin sheet. This impermeable interposed layer will provide features of impermeability, transparency and elasticity. An acrylic copolymer can be used for said impermeable layer.

[0021] Furthermore and to improve the rate of absorption of the aqueous inks, permeable covers (microporous or nanoporous), which would be applied on the cover

before printing, have been described.

[0022] If the adhesive is not aqueous, the multilayer composition will be taken, in a rigid state, to the object to which it would be adhered superficially, subsequently moistening the gelatin layer to make it elastic and then pressing the laminar element against the three-dimensional surface where the cover must be attached, finally proceeding to detach the gelatin layer.

[0023] On the other hand, the adhesive used can be different types of adhesives:

- ultraviolet-curable (UV-curable) adhesive;
- polyvinyl acetate,
- pressure-sensitive adhesive

[0024] The proposed method for transferring images comprises performing the following steps:

- preparing a multilayer laminar element by applying a cover of a transparent, elastic (or one that acquires elasticity due to pressure-sensitive) and printable material on a gelatin layer in the solid state (humidity content less than 10%);
- printing said cover advantageously by means of an ink-jet printing process;
- applying an adhesive (which can be provided by the surface on which the laminar element is applied);
- moistening said multilayer laminar element (if it was not moistened by the applied adhesive);
- applying the moistened and elastic laminar element on a three-dimensional surface or body with said cover facing and in contact with said three-dimensional surface or body; and
- removing said gelatin layer, separating it from the cover which remains adhered to said three-dimensional surface or body.

[0025] Once the cover has been printed, the method for transferring the multilayer element to a three-dimensional surface can be carried out in several ways according to the nature of the layer or layers constituting said multilayer laminar element.

[0026] If the cover is permeable, an aqueous adhesive is applied so that when the multilayer composition receives humidity, it becomes elastic and readily adheres to the three-dimensional surface of a body or object.

[0027] If the multilayer laminar element integrates an impermeable and elastic layer, which is either the actual cover receiving the printing or an additional layer, interposed between said cover and the gelatin layer, the composition is superficially adhered to the irregular surface or object by means of an adhesive arranged on said cover; humidity is subsequently applied to the gelatin layer so it becomes elastic; the multilayer element is then pressed against the three-dimensional surface and is adhered to same; and the gelatin layer is finally removed as a result of the humidity.

[0028] In the case of aqueous inks, the cover can be-

come adhesive when it is moistened, which would allow applying said cover on the three-dimensional surface without requiring additional adhesives. The moistened gelatin layer would finally be removed as explained above.

[0029] In particular embodiment, the multilayer laminar element is applied to a three-dimensional object using to that end a mold envisaged for shaping said object. In this case, the printed and moistened multilayer laminar element is fitted to the walls of a mold, arranging the gelatin layer in contact with the inner wall of the mold. A material is then deposited inside the mold and said mold is optionally closed. When, due to the molding process, the material has set, it is removed from the mold, with the multilayer laminar element adhered by the cover layer thereof to the outer surface of the molded body. Finally, the gelatin layer is removed from the multilayer laminar element, and the body is decorated with a printed image.

[0030] The features of the invention are described in the following claims.

Claims

1. A multilayer laminar element for transferring images to a three-dimensional surface, comprising:

- a first gelatin layer with a humidity content less than 10%, which, when moistened, becomes soft and elastic, and
- at least a second layer providing a transparent cover of said first layer, said transparent cover being elastic or being able to become elastic due to humidity, and intended for being printed on so that it can receive the printed image to be transferred,
- said multilayer laminar element being able to be adhered to a three-dimensional surface by means of an adhesive, with the transparent cover facing and in contact with said three-dimensional surface and said first gelatin layer being removable in the moistened state, after applying the multilayer laminar element to a three-dimensional surface.

2. The multilayer laminar element according to claim 1, **characterized in that** said first gelatin layer has a thickness of between 60 to 70 microns, whereas said cover has a thickness of 3 to 20 microns.
3. The multilayer laminar element according to claim 1, **characterized in that** said printing is ink-jet printing.
4. The multilayer laminar element according to claim 3, **characterized in that** said printing ink is selected from an ultraviolet-curable ink, a solvent or eco-solvent ink or an aqueous ink.

5. The multilayer laminar element according to claim 3, **characterized in that** the printing ink is an ultra-violet-curable ink and the cover is a polyurethane, an acrylic copolymer, a vinyl resin or the mixtures thereof.

6. The multilayer laminar element according to claim 3, **characterized in that** the printing ink is a solvent or eco-solvent ink and the cover is a polyurethane, an acrylic resin or a mixture of both.

7. The multilayer laminar element according to claim 3, **characterized in that** the printing ink is an aqueous ink and the cover is water-absorbent and selected from polyvinyl alcohol, polyvinylpyrrolidone or a polyurethane.

8. The multilayer laminar element according to claim 7, **characterized in that** the adhesive used is aqueous.

9. The multilayer laminar element according to claim 7, **characterized in that** said second layer incorporates a permeable cover selected from a microporous or nanoporous cover.

10. The multilayer laminar element according to claim 7, **characterized in that** it further comprises an impermeable, transparent and elastic layer between said cover-forming second layer, which is at least one in number, and said first gelatin layer.

11. The multilayer laminar element according to claim 1, **characterized in that** said adhesive is selected from a UV-curable adhesive, a vinyl adhesive or a pressure-sensitive adhesive.

12. The multilayer laminar element according to claim 1, **characterized in that** it integrates an impermeable and elastic layer, which is either the actual cover receiving the printing or an additional layer, interposed between said cover and the gelatin layer.

13. A method for transferring images to a three-dimensional surface, **characterized in that** it comprises

- preparing a multilayer laminar element by applying a cover of a transparent, elastic and printable material on a gelatin layer in the solid state (with a humidity content less than 10%);
- printing said cover with the image to be transferred;
- moistening said multilayer laminar element;
- applying the moistened multilayer laminar element on a three-dimensional surface by arranging the mentioned cover in contact with said three-dimensional surface and fixed thereto with the aid of an adhesive, and

- removing said gelatin layer, separating it from the cover which remains adhered to said three-dimensional surface or body.

14. The method according to claim 13, **characterized in that** said adhesive is added to said cover or applied on the three-dimensional surface to be decorated. 5

15. The method according to claim 13, **characterized in that:** 10

- said multilayer laminar element is applied, printed and moistened, to the inner walls of a mold for molding an object, with the gelatin layer in contact with the inner wall of the mold; 15
- a material is deposited for forming the object inside the mold;
- once it has set, the molded object is taken out together with the laminar element attached to its outer surface; and 20
- the gelatin layer is removed from the laminar element.

16. The method according to claim 13, **characterized in that** said printing on the mentioned cover is performed by means of ink-jet printing and said ink is selected from an ultraviolet-curable ink, a solvent or eco-solvent ink, or an aqueous ink. 25

17. The method according to claim 13, **characterized in that** the multilayer laminar element furthermore integrates an impermeable and elastic layer, which is either the actual cover receiving the printing or an additional layer, interposed between said cover and the gelatin layer, and **in that** the composition is superficially adhered to the irregular surface or object by means of an adhesive arranged on said impermeable and elastic layer, the gelatin layer is moistened, so it becomes elastic; the multilayer element is pressed against the three-dimensional surface in order to be adhered to same, and the moistened gelatin layer is finally removed. 30 35 40 45

45

50

55

INTERNATIONAL SEARCH REPORT

International application No.
PCT/ES2014/000065

A. CLASSIFICATION OF SUBJECT MATTER

See extra sheet

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

B41M, B44C, G03C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, INVENES, WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 1498285 A2 (TODESCHINI DANILO) 19/01/2005, the whole document.	1-17
A	EP 1102122 A1 (GOMEZ PORTELA JULIO) 23/05/2001, the whole document.	1-17
A	EP 0937584 A2 (TODESCHINI DANILO) 25/08/1999, the whole document.	1-17
A	GB 323724 A (WILLIAM HENRY STEELE) 16/01/1930, the whole document.	1, 13
A	ES 2156555 A1 (GOMEZ PORTELA JULIO) 16/06/2001, column 4, line 43 - column 8, line 17.	1, 13

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance.	
"E" earlier document but published on or after the international filing date	
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"O" document referring to an oral disclosure use, exhibition, or other means.	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other documents, such combination being obvious to a person skilled in the art
"P" document published prior to the international filing date but later than the priority date claimed	"&" document member of the same patent family

Date of the actual completion of the international search
14/08/2014

Date of mailing of the international search report
(19/08/2014)

Name and mailing address of the ISA/

Authorized officer
R. Reyes Lizcano

OFICINA ESPAÑOLA DE PATENTES Y MARCAS
Paseo de la Castellana, 75 - 28071 Madrid (España)
Facsimile No.: 91 349 53 04

Telephone No. 91 3495527

Form PCT/ISA/210 (second sheet) (July 2009)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/ES2014/000065

Information on patent family members

Patent document cited in the search report	Publication date	Patent family member(s)	Publication date
EP0937584 A2	25.08.1999	ITMI980334 A1 IT1298430 B1	20.08.1999 10.01.2000
----- EP1102122 A1	----- 23.05.2001	----- US6576347 B1 JP2002508263 A WO9949364 A1 ES2338075T T3 CN1293771 A CN1210617C C CA2323498 A1 CA2323498 C BR9908907 A BR9908907 B1 AU2837499 A ES2144948 A1 ES2144948 B1	----- 10.06.2003 19.03.2002 30.09.1999 03.05.2010 02.05.2001 13.07.2005 30.09.1999 06.01.2009 21.11.2000 18.11.2008 18.10.1999 16.06.2000 01.03.2001
----- EP1498285 A2	----- 19.01.2005	----- ITMI20031404 A1	----- 10.01.2005
----- GB323724 A	----- 16.01.1930	----- NONE	-----
----- ES2156555 A1	----- 16.06.2001	----- NONE	-----
-----	-----	-----	-----

Form PCT/ISA/210 (patent family annex) (July 2009)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/ES2014/000065

5
10
15
20
25
30
35
40
45
50
55

CLASSIFICATION OF SUBJECT MATTER

B41M3/12 (2006.01)

B44C1/16 (2006.01)

G03C11/12 (2006.01)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- EP 1102122 B1 [0004]