



(11) **EP 3 021 188 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:  
**Corrected version no 1 (W1 A1)**  
**Corrections, see**  
**Bibliography INID code(s) 71**

(51) Int Cl.:  
**G05D 16/02 (2006.01) G05D 16/10 (2006.01)**

(48) Corrigendum issued on:  
**10.08.2016 Bulletin 2016/32**

(43) Date of publication:  
**18.05.2016 Bulletin 2016/20**

(21) Application number: **15193908.9**

(22) Date of filing: **10.11.2015**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB**  
**GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO**  
**PL PT RO RS SE SI SK SM TR**  
Designated Extension States:  
**BA ME**  
Designated Validation States:  
**MA MD**

(30) Priority: **13.11.2014 JP 2014230453**

(71) Applicants:  
• **TOYOTA JIDOSHA KABUSHIKI KAISHA**  
**Toyota-shi, Aichi-ken, 471-8571 (JP)**  
• **JTEKT Corporation**  
**Osaka-shi, Osaka 542-8502 (JP)**

(72) Inventors:  
• **SAITO, Norihiko**  
**Toyota-shi, Aichi-ken, 471-8571 (JP)**

• **GOTO, Sogo**  
**Toyota-shi, Aichi-ken, 471-8571 (JP)**  
• **KONDO, Masaaki**  
**Toyota-shi, Aichi-ken, 471-8571 (JP)**  
• **YAMASHITA, Akira**  
**Toyota-shi, Aichi-ken, 471-8571 (JP)**  
• **OKAWACHI, Eiji**  
**Toyota-shi, Aichi-ken, 471-8571 (JP)**  
• **KUROYANAGI, Munetoshi**  
**Osaka-shi, Osaka 542-8502 (JP)**  
• **KUBO, Toshikatsu**  
**Osaka-shi, Osaka 542-8502 (JP)**  
• **IWAGUCHI, Takashi**  
**Osaka-shi, Osaka 542-8502 (JP)**

(74) Representative: **Kuhnen & Wacker**  
**Patent- und Rechtsanwaltsbüro**  
**Prinz-Ludwig-Straße 40A**  
**85354 Freising (DE)**

(54) **PRESSURE REDUCTION VALVE AND GAS SUPPLY DEVICE**

(57) The pressure reduction valve includes: a cylindrical portion, a piston and a spring. The cylindrical portion includes an inlet communicating with the primary side flow path and an outlet communicating with the secondary side flow path. The piston fitted into the cylindrical portion is slidable along an axis direction of the cylindrical portion within the cylindrical portion, and defines, within the cylindrical portion, a space communicating with the inlet and the outlet. The spring applies, to the piston, a force acting toward the space. The outlet is displaced in one direction from the center of the piston when seen in the axis direction. The force applied to the piston by the spring is distributed so as to deviate from the center of the piston to the side of the outlet.

Fig.4

