

(19)



(11)

EP 3 029 133 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

08.06.2016 Bulletin 2016/23

(51) Int Cl.:

C10M 141/02 (2006.01)

C10M 169/04 (2006.01)

C10N 10/04 (2006.01)

C10N 30/04 (2006.01)

C10N 40/25 (2006.01)

(21) Application number: **15195322.1**

(22) Date of filing: **19.11.2015**

(84) Designated Contracting States:

**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

Designated Extension States:

BA ME

Designated Validation States:

MA MD

(30) Priority: **04.12.2014 US 201414560231**

03.02.2015 EP 15153647

27.10.2015 US 201514923535

(71) Applicant: **Infineum International Limited**

Abingdon,

Oxfordshire OX13 6BB (GB)

(72) Inventors:

• **Bera, Tushar**
Linden, NJ 07036 (US)

• **Tundel, Rachel**
Linden, NJ 07036 (US)

• **Gregory, Laura**
Abingdon, Oxfordshire OX13 6BB (GB)

• **Wright, Peter**
Abingdon, Oxfordshire OX13 6BB (GB)

(74) Representative: **Lewis, Pauline Therese et al**

PO Box 1

Milton Hill

Abingdon

Oxfordshire OX13 6BB (GB)

(54) **MARINE ENGINE LUBRICATION**

(57) A trunk piston marine engine lubricant comprises in respective minor amounts (A) an overbased metal hydrocarbyl-substituted hydroxybenzoate detergent system, and (B) a hydrocarbyl-substituted succinic acid anhydride, preferably made by halogen- or radical-assisted functionalization processes, where the ratio of succinic

anhydride to hydrocarbyl chains is in the range of 1.4 to 4. The lubricant, when used to lubricate such an engine fuelled by heavy fuel oil, exhibits improved control of asphaltene precipitation and deposition on engine surfaces.

EP 3 029 133 A1

Description**FIELD OF THE INVENTION**

5 **[0001]** This invention relates to trunk piston marine engine lubrication for a medium-speed four-stroke compression-ignited (diesel) marine engine.

BACKGROUND OF THE INVENTION

10 **[0002]** Marine trunk piston engines generally use Heavy Fuel Oil ('HFO') for offshore running. Heavy Fuel Oil is the heaviest fraction of petroleum distillate and comprises a complex mixture of molecules including up to 15% of asphaltenes, defined as the fraction of petroleum distillate that is insoluble in an excess of aliphatic hydrocarbon (e.g. heptane) but which is soluble in aromatic solvents (e.g. toluene) as measured by ASTM D6560. Asphaltenes can enter the engine lubricant as contaminants either via the cylinder or the fuel pumps and injectors, and asphaltene precipitation can then
 15 occur, manifested in 'black paint' or 'black sludge' in the engine. The presence of such carbonaceous deposits on a piston surface can act as an insulating layer which can result in the formation of cracks that then propagate through the piston. If a crack travels through the piston, hot combustion gases can enter the crankcase, possibly resulting in a crankcase explosion.

[0003] It is therefore highly desirable that trunk piston engine oils ('TPEO's) prevent or inhibit asphaltene precipitation, a problem which becomes more acute when the oil of lubricating viscosity has a higher saturates content. The prior art describes ways of doing this by use of metal carboxylate detergents in combination with a polyalkenyl-substituted carboxylic acid anhydride. WO 2010/115594 ('594) and WO 2010/115595 ('595) describe use, in trunk piston marine engine (TPEO) lubricating oil compositions that contain 50 mass % or more of a Group II basestock, of respective minor amounts of a calcium salicylate detergent and of a polyalkenyl-substituted carboxylic acid anhydride. The data therein
 20 shows that the combination gives rise to improved asphaltene dispersency. EP-A-2644687 ('687) describes use of a combination of defined calcium salicylates and defined polyalkenyl-substituted carboxylic acid anhydrides in a TPEO lubricant comprising a major amount of an oil of lubricating viscosity containing 50 mass % or more of a Group I basestock. This achieves good asphaltene dispersency at lower and hence more economical levels of soap.

[0004] The art does not, however, concern itself with the influence of the succination ratio of the anhydride in such combinations on the problem of asphaltene precipitation such as at higher saturate levels in the oil of lubricating viscosity
 25 in a TPEO. Component (B) in the examples of '594 is stated to be a PIBSA derived from a polyisobutene of number average molecular weight 950; its succination ratio is not stated.

SUMMARY OF THE INVENTION

35 **[0005]** It is now surprisingly found that, when a polyalkenyl carboxylic acid anhydride additive of defined succination ratio, preferably made by a specific process, is used in a TPEO that includes a hydroxybenzoate detergent additive, improved control of asphaltene precipitation and deposition on engine surfaces is achieved, particularly when the oil of lubricating viscosity in the TPEO is a high saturates content oil. The anhydride additive boosts the performance of the detergent additive.
 40

[0006] Thus, a first aspect of the invention is a trunk piston marine engine lubricating oil composition for improving asphaltene handling in use thereof, in operation of such engine when fuelled by a heavy fuel oil, which composition comprises, or is made by admixing, a major amount of an oil of lubricating viscosity and, in respective minor amounts:

45 (A) an overbased metal hydrocarbyl-substituted hydroxybenzoate detergent system, and

(B) a hydrocarbyl-substituted succinic acid anhydride, preferably made using halogen- or radical-assisted functionalization processes, where the ratio of succinic anhydride groups per substituted hydrocarbyl moiety is in the range of 1.4 to 4.

50 **[0007]** A second aspect of the invention is a method of preparing a trunk piston marine engine lubricating oil composition for a medium-speed compression-ignited marine engine comprising blending (A) and (B) with the oil of lubricating viscosity, each defined as in the first aspect of the invention.

[0008] A third aspect of the invention is a trunk piston marine engine lubricating oil composition for a medium-speed four-stroke compression-ignited marine engine obtainable by the method of the second aspect of the invention.

55 **[0009]** A fourth aspect of the invention is a method of operating a trunk piston medium-speed compression-ignited marine engine comprising:

(i) fuelling the engine with a heavy fuel oil; and

(ii) lubricating the engine with a composition as defined in the first aspect of the invention.

[0010] A fifth aspect of the invention is a method of dispersing asphaltenes in trunk piston marine lubricating oil composition during its lubrication of surfaces of a medium-speed compression-ignited marine engine and operation of the engine, which comprises:

(i) providing a composition as defined in the first aspect of the invention;

(ii) providing the composition to the engine;

(iii) providing heavy fuel oil to the engine; and

(iv) combusting the fuel oil.

[0011] A sixth aspect of the invention is the use of detergent system (A) as defined in, the first aspect of the invention in combination with anhydride (B) as defined in the first aspect of the invention in a trunk piston marine lubricating oil composition for a medium-speed compression-ignited marine engine, to improve asphaltene handling during operation of the engine which is fueled by a heavy fuel oil.

[0012] A seventh aspect of the invention is the use of detergent system (A) as defined in, the first aspect of the invention in combination with anhydride (B) as defined in the first aspect of the invention in a trunk piston marine lubricating oil composition for a medium-speed compression-ignited marine engine, to improve asphaltene handling during operation of the engine, fueled by a heavy fuel oil, in comparison with analogous operation where anhydride (B) has a ratio different from that defined in the first aspect of the invention.

[0013] In this specification, the following words and expressions, if and when used, have the meanings ascribed below:

"Succination ratio" in relation to component (B) means the number of groups derived from succinic anhydride for each substituted hydrocarbyl moiety. The "succinic ratio" or "succination ratio" refers to the ratio calculated in accordance with the procedure and mathematical equation set forth in columns 5 and 6 of U.S. Pat. No. 5,334,321. The calculation is asserted to represent the average number of succinic groups in an alkenyl or alkylsuccinic anhydride per substituted alkenyl or alkyl chain.

"active ingredients" or "(a.i.)" refers to additive material that is not diluent, solvent or unreacted hydrocarbyl moiety;

"comprising" or any cognate word specifies the presence of stated features, steps, or integers or components, but does not preclude the presence or addition of one or more other features, steps, integers, components or groups thereof; the expressions "consists of" or "consists essentially of" or cognates may be embraced within "comprises" or cognates, wherein "consists essentially of" permits inclusion of substances not materially affecting the characteristics of the composition to which it applies;

"major amount" means 50 or more, preferably 60 or more, more preferably 70 or more, and even more preferably 80 or more, mass % of a composition;

"minor amount" means less than 50, preferably less than 40, even more preferably less than 30 and most preferably less than 20, mass % of a composition;

"TBN" means total base number as measured by ASTM D2896.

[0014] Furthermore in this specification:

"calcium content" is as measured by ASTM 4951;

"phosphorus content" is as measured by ASTM D5185;

"sulphated ash content" is as measured by ASTM D874;

"sulphur content" is as measured by ASTM D2622;

"KV100" means kinematic viscosity at 100°C as measured by ASTM D445.

[0015] Also, it will be understood that various components used, essential as well as optimal and customary, may react under conditions of formulation, storage or use and that the invention also provides the product obtainable or obtained as a result of any such reaction.

[0016] Further, it is understood that any upper and lower quantity, range and ratio limits set forth herein may be independently combined.

DETAILED DESCRIPTION OF THE INVENTION

[0017] The features of the invention in its various aspects, if and where applicable, will now be discussed in more detail below.

OIL OF LUBRICATING VISCOSITY

[0018] The lubricating oils may range in viscosity from light distillate mineral oils to heavy lubricating oils. Generally, the viscosity of the oil ranges from 2 to 40 mm²/sec, as measured at 100°C.

[0019] Natural oils include animal oils and vegetable oils (e.g., castor oil, lard oil); liquid petroleum oils and hydrorefined, solvent-treated or acid-treated mineral oils of the paraffinic, naphthenic and mixed paraffinic-naphthenic types. Oils of lubricating viscosity derived from coal or shale also serve as useful base oils.

[0020] Synthetic lubricating oils include hydrocarbon oils and halo-substituted hydrocarbon oils such as polymerized and interpolymers of olefins (e.g., polybutylenes, polypropylenes, propylene-isobutylene copolymers, chlorinated polybutylenes, poly(1-hexenes), poly(1-octenes), poly(1-decenes)); alkybenzenes (e.g., dodecylbenzenes, tetradecylbenzenes, dinonylbenzenes, di(2-ethylhexyl)benzenes); polyphenyls (e.g., biphenyls, terphenyls, alkylated polyphenols); alkylated naphthalenes; and alkylated diphenyl ethers and alkylated diphenyl sulphides and derivative, analogs and homologs thereof.

[0021] Alkylene oxide polymers and interpolymers and derivatives thereof where the terminal hydroxyl groups have been modified by esterification, etherification, etc., constitute another class of known synthetic lubricating oils. These are exemplified by polyoxyalkylene polymers prepared by polymerization of ethylene oxide or propylene oxide, and the alkyl and aryl ethers of polyoxyalkylene polymers (e.g., methyl-polyiso-propylene glycol ether having a molecular weight of 1000 or diphenyl ether of poly-ethylene glycol having a molecular weight of 1000 to 1500); and mono- and polycarboxylic esters thereof, for example, the acetic acid esters, mixed C₃-C₈ fatty acid esters and C₁₃ Oxo acid diester of tetraethylene glycol.

[0022] Another suitable class of synthetic lubricating oils comprises the esters of dicarboxylic acids (e.g., phthalic acid, succinic acid, alkyl succinic acids and alkenyl succinic acids, maleic acid, azelaic acid, suberic acid, sebacic acid, fumaric acid, adipic acid, linoleic acid dimer, malonic acid, alkylmalonic acids, alkenyl malonic acids) with a variety of alcohols (e.g., butyl alcohol, hexyl alcohol, dodecyl alcohol, 2-ethylhexyl alcohol, ethylene glycol, diethylene glycol monoether, propylene glycol). Specific examples of such esters includes dibutyl adipate, di(2-ethylhexyl) sebacate, di-n-hexyl fumarate, dioctyl sebacate, diisooctyl azelate, diisodecyl azelate, dioctyl phthalate, didecyl phthalate, dieicosyl sebacate, the 2-ethylhexyl diester of linoleic acid dimer, and the complex ester formed by reacting one mole of sebacic acid with two moles of tetraethylene glycol and two moles of 2-ethylhexanoic acid.

[0023] Esters useful as synthetic oils also include those made from C₅ to C₁₂ monocarboxylic acids and polyols and polyol esters such as neopentyl glycol, trimethylolpropane, pentaerythritol, dipentaerythritol and tripentaerythritol.

[0024] Silicon-based oils such as the polyalkyl-, polyaryl-, polyalkoxy- or polyaryloxysilicone oils and silicate oils comprise another useful class of synthetic lubricants; such oils include tetraethyl silicate, tetraisopropyl silicate, tetra-(2-ethylhexyl)silicate, tetra-(4-methyl-2-ethylhexyl)silicate, tetra-(p-tert-butyl-phenyl) silicate, hexa-(4-methyl-2-ethylhexyl)disiloxane, poly(methyl)siloxanes and poly(methylphenyl)siloxanes. Other synthetic lubricating oils include liquid esters of phosphorous-containing acids (e.g., tricresyl phosphate, trioctyl phosphate, diethyl ester of decylphosphonic acid) and polymeric tetrahydrofurans.

[0025] Unrefined, refined and re-refined oils can be used in lubricants of the present invention. Unrefined oils are those obtained directly from a natural or synthetic source without further purification treatment. For example, a shale oil obtained directly from retorting operations; petroleum oil obtained directly from distillation; or ester oil obtained directly from an esterification and used without further treatment would be an unrefined oil. Refined oils are similar to unrefined oils except that the oil is further treated in one or more purification steps to improve one or more properties. Many such purification techniques, such as distillation, solvent extraction, acid or base extraction, filtration and percolation are known to those skilled in the art. Re-refined oils are obtained by processes similar to those used to provide refined oils but begin with oil that has already been used in service. Such re-refined oils are also known as reclaimed or reprocessed oils and are often subjected to additional processing using techniques for removing spent additives and oil breakdown

products.

[0026] The American Petroleum Institute (API) publication "Engine Oil Licensing and Certification System", Industry Services Department, Fourteenth Edition, December 1996, Addendum 1, December 1998 categorizes base stocks as follows:

a) Group I base stocks contain less than 90 percent saturates and/or greater than 0.03 percent sulphur and have a viscosity index greater than or equal to 80 and less than 120 using the test methods specified in Table E-1.

b) Group II base stocks contain greater than or equal to 90 percent saturates and less than or equal to 0.03 percent sulphur and have a viscosity index greater than or equal to 80 and less than 120 using the test methods specified in Table E-1.

c) Group III base stocks contain greater than or equal to 90 percent saturates and less than or equal to 0.03 percent sulphur and have a viscosity index greater than or equal to 120 using the test methods specified in Table E-1.

d) Group IV base stocks are polyalphaolefins (PAO).

e) Group V base stocks include all other base stocks not included in Group I, II, III, or IV.

[0027] Analytical Methods for Base Stock are tabulated below (Table E-1):

PROPERTY	TEST METHOD
Saturates	ASTM D 2007
Viscosity Index	ASTM D 2270
Sulphur	ASTM D 2622
	ASTM D 4294
	ASTM D 4927
	ASTM D 3120

[0028] The present invention particularly embraces those of the above oils containing greater than or equal to 90% saturates and less than or equal to 0.03% sulphur as the oil of lubricating viscosity, eg Group II, III, IV or V. They also include basestocks derived from hydrocarbons synthesised by the Fischer-Tropsch process. In the Fischer-Tropsch process, synthesis gas containing carbon monoxide and hydrogen (or 'syngas') is first generated and then converted to hydrocarbons using a Fischer-Tropsch catalyst. These hydrocarbons typically require further processing in order to be useful as a base oil. For example, they may, by methods known in the art, be hydroisomerized; hydrocracked and hydroisomerized; dewaxed; or hydroisomerized and dewaxed. The syngas may, for example, be made from gas such as natural gas or other gaseous hydrocarbons by steam reforming, when the basestock may be referred to as gas-to-liquid ("GTL") base oil; or from gasification of biomass, when the basestock may be referred to as biomass-to-liquid ("BTL" or "BMTL") base oil; or from gasification of coal, when the basestock may be referred to as coal-to-liquid ("CTL") base oil.

[0029] Preferably, the oil of lubricating viscosity in this invention contains 30, such as 50, mass % or more said basestocks. It may contain 60, such as 70, 80 or 90, mass % or more of said basestock or a mixture thereof. The oil of lubricating viscosity may be substantially all of said basestock or a mixture thereof.

[0030] It may be desirable, although not essential, to prepare one or more additive packages or concentrates comprising additives, whereby additives (A) and (B) can be added simultaneously to the oil of lubricating viscosity to form the TPEO.

[0031] The final formulations as a trunk piston engine oil may typically contain up to 30, preferably 10 to 28, more preferably 12 to 24, mass % of the additive package(s), the remainder being the oil of lubricating viscosity. The trunk piston engine oil may have a compositional TBN (using ASTM D2896) of 20 to 60, preferably 30 to 55. Even more preferably, it may be 40 to 55 or 35 to 50.


[0032] The combined treat rate of additives (A) and (B) contained in the lubricating oil composition may for example be in the range of 5 to 30, preferably 10 to 28, more preferably 12 to 24, mass %.

OVERBASED METAL DETERGENT ADDITIVE (A)

[0033] A metal detergent is an additive based on so-called metal "soaps", that is metal salts of acidic organic compounds, sometimes referred to as surfactants. They generally comprise a polar head with a long hydrophobic tail. Overbased metal detergents, which comprise neutralized metal detergents as the outer layer of a metal base (e.g. carbonate) micelle, may be provided by including large amounts of metal base by reacting an excess of a metal base, such as an oxide or hydroxide, with an acidic gas such as carbon dioxide.

[0034] In the present invention, overbased metal detergents (A) are overbased metal hydrocarbyl-substituted hydroxybenzoate, preferably hydrocarbyl-substituted salicylate, detergents.

[0035] "Hydrocarbyl" means a group or radical that contains carbon and hydrogen atoms and that is bonded to the remainder of the molecule via a carbon atom. It may contain hetero atoms, i.e. atoms other than carbon and hydrogen, provided they do not alter the essentially hydrocarbon nature and characteristics of the group. As examples of hydrocarbyl, there may be mentioned alkyl and alkenyl. The overbased metal hydrocarbyl-substituted hydroxybenzoate typically has the structure shown:



wherein R is a linear or branched aliphatic hydrocarbyl group, and more preferably an alkyl group, including straight- or branched-chain alkyl groups. There may be more than one R group attached to the benzene ring. M is an alkali metal (e.g. lithium, sodium or potassium) or alkaline earth metal (e.g. calcium, magnesium barium or strontium). Calcium or magnesium is preferred; calcium is especially preferred. The COOM group can be in the ortho, meta or para position with respect to the hydroxyl group; the ortho position is preferred. The R group can be in the ortho, meta or para position with respect to the hydroxyl group. When M is polyvalent, it is represented fractionally in the above formula.

[0036] Hydroxybenzoic acids are typically prepared by the carboxylation, by the Kolbe-Schmitt process, of phenoxides, and in that case, will generally be obtained (normally in a diluent) in admixture with uncarboxylated phenol. Hydroxybenzoic acids may be non-sulphurized or sulphurized, and may be chemically modified and/or contain additional substituents. Processes for sulphurizing a hydrocarbyl-substituted hydroxybenzoic acid are well known to those skilled in the art and are described, for example, in US 2007/0027057.

[0037] In hydrocarbyl-substituted hydroxybenzoic acids, the hydrocarbyl group is preferably alkyl (including straight- or branched-chain alkyl groups), and the alkyl groups advantageously contain 5 to 100, preferably 9 to 30, especially 14 to 24, carbon atoms.

[0038] The term "overbased" is generally used to describe metal detergents in which the ratio of the number of equivalents of the metal moiety to the number of equivalents of the acid moiety is greater than one. The term "low-based" is used to describe metal detergents in which the equivalent ratio of metal moiety to acid moiety is greater than 1, and up to about 2.

[0039] By an "overbased calcium salt of surfactants" is meant an overbased detergent in which the metal cations of the oil-insoluble metal salt are essentially calcium cations. Small amounts of other cations may be present in the oil-insoluble metal salt, but typically at least 80, more typically at least 90, for example at least 95, mole % of the cations in the oil-insoluble metal salt are calcium ions. Cations other than calcium may be derived, for example, from the use in the manufacture of the overbased detergent of a surfactant salt in which the cation is a metal other than calcium. Preferably, the metal salt of the surfactant is also calcium.

[0040] Carbonated overbased metal detergents typically comprise amorphous nanoparticles. Additionally, there are disclosures of nanoparticulate materials comprising carbonate in the crystalline calcite and vaterite forms.

[0041] The basicity of the detergents may be expressed as a total base number (TBN). A total base number is the amount of acid needed to neutralize all of the basicity of the overbased material. The TBN may be measured using ASTM standard D2896 or an equivalent procedure. The detergent may have a low TBN (i.e. a TBN of less than 50), a medium TBN (i.e. a TBN of 50 to 150) or a high TBN (i.e. a TBN of greater than 150, such as 150-500). In this invention, Basicity Index is used. Basicity Index is the molar ratio of total base to total soap in the overbased detergent. The Basicity Index of the detergent (A) in the invention is preferably in the range of 1 to 8, more preferably 3 to 8, such as 3 to 7,

such as 3 to 6. The Basicity Index may for example be greater than 3.

[0042] Overbased metal hydrocarbyl-substituted hydroxybenzoates can be prepared by any of the techniques employed in the art. A general method is as follows:

1. Neutralisation of hydrocarbyl-substituted hydroxybenzoic acid with a molar excess of metallic base to produce a slightly overbased metal hydrocarbyl-substituted hydroxybenzoate complex, in a solvent mixture consisting of a volatile hydrocarbon, an alcohol and water;
2. Carbonation to produce colloiddally-dispersed metal carbonate followed by a post-reaction period;
3. Removal of residual solids that are not colloiddally dispersed; and
4. Stripping to remove process solvents.

[0043] Overbased metal hydrocarbyl-substituted hydroxybenzoates can be made by either a batch or a continuous overbasing process.

[0044] Metal base (e.g. metal hydroxide, metal oxide or metal alkoxide), preferably lime (calcium hydroxide), may be charged in one or more stages. The charges may be equal or may differ, as may the carbon dioxide charges which follow them. When adding a further calcium hydroxide charge, the carbon dioxide treatment of the previous stage need not be complete. As carbonation proceeds, dissolved hydroxide is converted into colloidal carbonate particles dispersed in the mixture of volatile hydrocarbon solvent and non-volatile hydrocarbon oil.

[0045] Carbonation may be effected in one or more stages over a range of temperatures up to the reflux temperature of the alcohol promoters. Addition temperatures may be similar, or different, or may vary during each addition stage. Phases in which temperatures are raised, and optionally then reduced, may precede further carbonation steps.

[0046] The volatile hydrocarbon solvent of the reaction mixture is preferably a normally liquid aromatic hydrocarbon having a boiling point not greater than about 150°C. Aromatic hydrocarbons have been found to offer certain benefits, e.g. improved filtration rates, and examples of suitable solvents are toluene, xylene, and ethyl benzene.

[0047] The alkanol is preferably methanol although other alcohols such as ethanol can be used. Correct choice of the ratio of alkanol to hydrocarbon solvents, and the water content of the initial reaction mixture, are important to obtain the desired product.

[0048] Oil may be added to the reaction mixture; if so, suitable oils include hydrocarbon oils, particularly those of mineral origin. Oils which have viscosities of 15 to 30 mm²/sec at 38°C are very suitable.

[0049] After the final treatment with carbon dioxide, the reaction mixture is typically heated to an elevated temperature, e.g. above 130°C, to remove volatile materials (water and any remaining alkanol and hydrocarbon solvent). When the synthesis is complete, the raw product is hazy as a result of the presence of suspended sediments. It is clarified by, for example, filtration or centrifugation. These measures may be used before, or at an intermediate point, or after solvent removal.

[0050] The products are used as a diluent (or oil) dispersion. If the reaction mixture contains insufficient oil to retain an oil solution after removal of the volatiles, further oil should be added. This may occur before, or at an intermediate point, or after solvent removal.

[0051] Preferably, the diluent used for (A) comprises a basestock containing greater than or equal to 90% saturates and less than or equal to 0.03% sulphur. (A) may contain up to 20, 30, 40, 50, 60, 70, 80 or 90, mass% or more (such as all) of said basestock. An example of said basestock is a Group II basestock.

HYDROCARBYL-SUBSTITUTED SUCCINIC ACID ANHYDRIDE (B)

[0052] The anhydride may constitute at least 0.1 to 10, preferably 0.5 to 8.5, even more preferably 1 to 7, and most preferably 1.5 to 5, mass %, on an active ingredient basis, of the lubricating oil composition. Preferably it constitutes 2 to 5, more preferably 2.5 to 4, mass %.

[0053] The hydrocarbyl group is preferably a polyalkenyl group and preferably has from 36 to 216, more preferably 56 to 108, carbon atoms. It may have a number average molecular weight in the range of 500 to 3,000; preferably 700 to 2,300, even more preferably 800 to 1,500.

[0054] The succination ratio is, as stated, in the range of 1.4 to 4, preferably 1.4 to 3; more preferably it is in the range of 1.50 to 2.20, even more preferably 1.50 to 2.00, and most preferably 1.60 to 2.00.

[0055] Suitable hydrocarbons or polymers employed in the formation of the anhydrides of the present invention to generate the polyalkenyl moieties include homopolymers, interpolymers or lower molecular weight hydrocarbons. One family of such polymers comprise polymers of ethylene and/or at least one C₃ to C₂₈ alpha-olefin having the formula H₂C=CHR¹ wherein R¹ is straight or branched chain alkyl radical comprising 1 to 26 carbon atoms and wherein the polymer contains carbon-to-carbon unsaturation, such as with a high degree of terminal ethenylidene unsaturation. Preferably, such polymers comprise interpolymers of ethylene and at least one alpha-olefin of the above formula, wherein R¹ is alkyl of from 1 to 18 carbon atoms, and more preferably is alkyl of from 1 to 8 carbon atoms, and more preferably

still of from 1 to 2 carbon atoms. Therefore, useful alpha-olefin monomers and comonomers include, for example, propylene, butene-1, hexene-1, octene-1, 4-methylpentene-1, decene-1, dodecene-1, tridecene-1, tetradecene-1, pentadecene-1, hexadecene-1, heptadecene-1, octadecene-1, nonadecene-1, and mixtures thereof (e.g., mixtures of propylene and butene-1, and the like). Exemplary of such polymers are propylene homopolymers, butene-1 homopolymers, ethylene-propylene copolymers, ethylene-butene-1 copolymers, propylene-butene copolymers and the like, wherein the polymer contains at least some terminal and/or internal unsaturation. Possible polymers are unsaturated copolymers of ethylene and propylene and ethylene and butene-1. The interpolymers may contain a minor amount, e.g. 0.5 to 5 mole % of a C₄ to C₁₈ nonconjugated diolefin comonomer. However, it is preferred that the polymers comprise only alpha-olefin homopolymers, interpolymers of alpha-olefin comonomers and interpolymers of ethylene and alpha-olefin comonomers. The molar ethylene content of the polymers employed is preferably in the range of 0 to 80 %, and more preferably 0 to 60 %. When propylene and/or butene-1 are employed as comonomer(s) with ethylene, the ethylene content of such copolymers is most preferably between 15 and 50 %, although higher or lower ethylene contents may be present.

[0056] These polymers may be prepared by polymerizing alpha-olefin monomer, or mixtures of alpha-olefin monomers, or mixtures comprising ethylene and at least one C₃ to C₂₈ alpha-olefin monomer, in the presence of a catalyst system comprising at least one metallocene (e.g., a cyclopentadienyl-transition metal compound) and an alumoxane compound. Using this process, a polymer in which 95 % or more of the polymer chains possess terminal ethenylidene-type unsaturation can be provided. The percentage of polymer chains exhibiting terminal ethenylidene unsaturation may be determined by FTIR spectroscopic analysis, titration, or C¹³ NMR. Interpolymers of this latter type may be characterized by the formula POLY-C(R¹)=CH₂ wherein R¹ is C₁ to C₂₆ alkyl, preferably C₁ to C₁₈ alkyl, more preferably C₁ to C₈ alkyl, and most preferably C₁ to C₂ alkyl, (e.g., methyl or ethyl) and wherein POLY represents the polymer chain. The chain length of the R¹ alkyl group will vary depending on the comonomer(s) selected for use in the polymerization. A minor amount of the polymer chains can contain terminal ethenyl, i.e., vinyl, unsaturation, i.e. POLY-CH=CH₂, and a portion of the polymers can contain internal monounsaturations, e.g. POLY-CH=CH(R¹), wherein R¹ is as defined above. These terminally-unsaturated interpolymers may be prepared by known metallocene chemistry and may also be prepared as described in U.S. Patent Nos. 5,498,809; 5,663,130; 5,705,577; 5,814,715; 6,022,929 and 6,030,930.

[0057] Another useful class of polymer constitutes those polymers prepared by cationic polymerization of isobutene, styrene, and the like. Common polymers from this class include polyisobutenes obtained by polymerization of a C₄ refinery stream having a butene content of about 35 to about 75 mass %, and an isobutene content of about 30 to about 60 mass %, in the presence of a Lewis acid catalyst, such as aluminum trichloride or boron trifluoride. A preferred source of monomer for making poly-n-butenes is petroleum feedstreams such as Raffinate II. These feedstocks are disclosed in the art such as in U.S. Patent No. 4,952,739. Polyisobutylene is a most preferred backbone of the present invention because it is readily available by cationic polymerization from butene streams (e.g., using AlCl₃ or BF₃ catalysts). Such polyisobutenes generally contain residual unsaturation in amounts of about one ethylenic double bond per polymer chain, positioned along the chain. One embodiment utilizes polyisobutylene prepared from a pure isobutylene stream or a Raffinate I stream to prepare reactive isobutylene polymers with terminal vinylidene olefins. These polymers, referred to as highly reactive polyisobutylene (HR-PIB), may have a terminal vinylidene content of at least 65%. The preparation of such polymers is described, for example, in U.S. Patent No. 4,152,499. HR-PIB is known and HR-PIB is commercially available under the tradenames Glissopal™ (from BASF) and Ultravis™ (from BP-Amoco).

[0058] Polyisobutylene polymers that may be employed are generally based on a hydrocarbon chain of from 400 to 3000. Methods for making polyisobutylene are known. Polyisobutylene can be functionalized by halogenation (e.g. chlorination), the thermal "ene" reaction, or by free radical grafting using a catalyst (e.g. peroxide), as described below.

[0059] To produce (B), the hydrocarbon or polymer backbone may be functionalized, with carboxylic anhydride-producing moieties selectively at sites of carbon-to-carbon unsaturation on the polymer or hydrocarbon chains, or randomly along chains using one or more of the three processes mentioned above or combinations thereof, in any sequence.

[0060] Processes for reacting polymeric hydrocarbons with unsaturated carboxylic, anhydrides and the preparation of derivatives from such compounds are disclosed in U.S. Patent Nos. 3,087,936; 3,172,892; 3,215,707; 3,231,587; 3,272,746; 3,275,554; 3,381,022; 3,442,808; 3,565,804; 3,912,764; 4,110,349; 4,234,435; 5,777,025; 5,891,953; as well as EP 0 382 450 B1; CA-1,335,895 and GB-A-1,440,219. The polymer or hydrocarbon may be functionalized, with carboxylic acid anhydride moieties by reacting the polymer or hydrocarbon under conditions that result in the addition of functional moieties or agents, i.e., acid, anhydride, onto the polymer or hydrocarbon chains primarily at sites of carbon-to-carbon unsaturation (also referred to as ethylenic or olefinic unsaturation) using the halogen- or radical-assisted functionalization (e.g. chlorination) processes, such as chloro or radical maleation.

[0061] Functionalization is preferably accomplished by halogenating, e.g., chlorinating or brominating the unsaturated alpha-olefin polymer to about 1 to 8 mass %, preferably 3 to 7 mass % chlorine, or bromine, based on the weight of polymer or hydrocarbon, by passing the chlorine or bromine through the polymer at a temperature of 60 to 250°C, preferably 130 to 220°C, e.g., 140 to 190°C, for about 0.5 to 10, preferably 1 to 7 hours. The halogenated polymer or hydrocarbon (hereinafter backbone) is then reacted with sufficient monounsaturated reactant capable of adding the required number of functional moieties to the backbone, e.g., monounsaturated carboxylic reactant, at 100 to 250°C, usually about 140°C

to 220°C, for about 0.5 to 10, e.g., 3 to 8 hours, such that the product obtained will contain the desired number of moles of the monounsaturated carboxylic reactant per mole of the halogenated backbones. Alternatively, the backbone and the monounsaturated carboxylic reactant are mixed and heated while adding chlorine to the hot material.

[0062] US 4,234,435 (above-mentioned) describes PIBSA's made by the chloro-route (Diels-Alder process). Its abstract states "carboxylic acid acylating agents are derived from polyalkenes such as polybutenes, and a dibasic, carboxylic reactant such as maleic or fumaric acid or certain derivatives thereof. These acylating agents are characterized in that the polyalkenes from which they are derived have a Mn value of about 1300 to about 5000 and a Mw/Mn value of about 1.5 to about 4. The acylating agents are further characterized by the presence within their structure of at least 1.3 groups derived from the dibasic, carboxylic reactant for each equivalent weight of the groups derived from the polyalkene. The acylating agents can be reacted with a further reactant subject to being acylated such as polyethylene polyamines and polyols (e.g., pentaerythritol) to produce derivatives useful per se as lubricant additives or as intermediates to be subjected to post-treatment with various other chemical compounds and compositions, such as epoxides, to produce still other derivatives useful as lubricant additives."

[0063] CA 2,471,534 describes PIBSA's made by the ene-reaction (falling outside the present invention). Its abstract relates to "a process for forming an ene reaction product wherein an enophile, such as maleic anhydride, is reacted with reactive polyalkene having a terminal vinylidene content of at least 30 mol%, at high temperature in the presence of a free radical inhibitor. The polyalkenyl acylating agents are useful per se as additives in lubricating oils, functional fluids, and fuels and also serve as intermediates in the preparation of other products (e.g., succinimides) useful as additives in lubricating oils, functional fluids, and fuels. The presence of the free radical inhibitor during the high temperature reaction results in a reaction product that is low, or substantially free from sediment."

[0064] It is believed that the Diels-Adler process produces a dicyclic two bond attachment of the succinic group to the polybutene. This is structurally rather rigid and keeps the succinic group limited to an imide structure when reacted with a functionalising agent such as a polyamine. On the other hand an ene-reaction (1,5 hydrogen shift reaction) PIBSA has a single bond link between the succinic group and polybutene, and as such will allow rotation and opening of the succinic group (to dicarboxylic acid) to allow di-amide formation in the right energy conditions (low temperature) and amine excess.

[0065] The hydrocarbon or polymer backbone can be functionalized by random attachment of functional moieties along the polymer chains by a variety of methods. For example, the polymer, in solution or in solid form, may be grafted with the monounsaturated carboxylic reactant, as described above, in the presence of a free-radical initiator. When performed in solution, the grafting takes place at an elevated temperature in the range of about 100 to 260°C, preferably 120 to 240°C. Preferably, free-radical initiated grafting would be accomplished in a mineral lubricating oil solution containing, e.g., 1 to 50 mass %, preferably 5 to 30 mass %, polymer based on the initial total oil solution.

[0066] The free-radical initiators that may be used are peroxides, hydroperoxides, and azo compounds, preferably those that have a boiling point greater than about 100°C and decompose thermally within the grafting temperature range to provide free-radicals. Representative of these free-radical initiators are azobutyronitrile, 2, 5-dimethylhex-3-ene-2, 5-bis-tertiary-butyl peroxide and dicumene peroxide. The initiator, when used, typically is used in an amount of between 0.005% and 2% by weight based on the weight of the reaction mixture solution. Typically, the aforesaid monounsaturated carboxylic reactant material and free-radical initiator are used in a weight ratio range of from about 1.0:1 to 30:1, preferably 3:1 to 6:1. The grafting is preferably carried out in an inert atmosphere, such as under nitrogen blanketing. The resulting grafted polymer is characterized by having carboxylic acid (or derivative) moieties randomly attached along the polymer chains: it being understood, of course, that some of the polymer chains remain ungrafted. The free radical grafting described above can be used for the other polymers and hydrocarbons of the present invention.

[0067] To provide the required functionality, the monounsaturated carboxylic reactant, preferably maleic anhydride, typically will be used in an amount ranging from about equimolar amount to about 100 mass % excess, preferably 5 to 50 mass % excess, based on the moles of polymer or hydrocarbon. Unreacted excess monounsaturated carboxylic reactant can be removed from the final dispersant product by, for example, stripping, usually under vacuum, if required.

CO-ADDITIVES

[0068] The lubricating oil composition of the invention may comprise further additives, different from and additional to (A) and (B). Such additional additives may, for example include ashless dispersants, other metal detergents, anti-wear agents such as zinc dihydrocarbyl dithiophosphates, anti-oxidants and demulsifiers.

[0069] The following examples illustrate but in no way limit the invention.

EXAMPLES**COMPONENTS**

[0070] The following compounds were used:

Oil of lubricating viscosity

[0071] An API Group II 600R basestock from Chevron

(A) Detergents

(1) a 225BN Ca alkyl salicylate (alkyl = C14-18)

(2) a 350BN Ca alkyl salicylate (alkyl = C14-18)

(B) A set of polyisobutene succinic anhydrides ("PIBSA") derived from a polyisobutene and made by a chloro-(Diels-Alder) process. The properties of each PIBSA are shown in the table in the RESULTS section below.

(C) A zinc dihydrocarbyl dithiophosphate at 0.5%.

Heavy Fuel Oil 1S0-F-RMG 380**LUBRICANTS**

[0072] Selections of the above components were blended with the oil of lubricating viscosity to give a range of trunk piston marine engine lubricants. Some of the lubricants were examples of the invention; others were reference examples for comparison purposes. Each lubricant contained the same combination of detergents in (A) to give a lubricating oil with a TBN of 40mgKOH/g and a different PIBSA at a treat rate of 2-6 mass %.

TESTINGLight Scattering

[0073] Test lubricants were evaluated for asphaltene dispersancy using light scattering according to the Focused Beam Reflectance Method ("FBRM"), which predicts asphaltene agglomeration and hence 'black sludge' formation.

[0074] The FBRM test method was disclosed at the 7th International Symposium on Marine Engineering, Tokyo, 24th - 28th October 2005, and was published in 'The Benefits of Salicylate Detergents in TPEO Applications with a Variety of Base Stocks', in the Conference Proceedings. Further details were disclosed at the CIMAC Congress, Vienna, 21st -24th May 2007 and published in "Meeting the Challenge of New Base Fluids for the Lubrication of Medium Speed Marine Engines - An Additive Approach" in the Congress Proceedings. In the latter paper it is disclosed that by using the FBRM method it is possible to obtain quantitative results for asphaltene dispersancy that predict performance for lubricant systems based on base stocks containing greater than or less than 90% saturates, and greater than or less than 0.03% sulphur. The predictions of relative performance obtained from FBRM were confirmed by engine tests in marine diesel engines.

[0075] The FBRM probe contains fibre optic cables through which laser light travels to reach the probe tip. At the tip, an optic focuses the laser light to a small spot. The optic is rotated so that the focussed beam scans a circular path between the window of the probe and the sample. As particles flow past the window, they intersect the scanning path, giving backscattered light from the individual particles.

[0076] The scanning laser beam travels much faster than the particles; this means that the particles are effectively stationary. As the focussed beam reaches one edge of the particle the amount of backscattered light increases; the amount will decrease when the focussed beam reaches the other edge of the particle.

[0077] The instrument measures the time of the increased backscatter. The time period of backscatter from one particle is multiplied by the scan speed and the result is a distance or chord length. A chord length is a straight line between any two points on the edge of a particle. This is represented as a chord length distribution, a graph of numbers of chord lengths (particles) measured as a function of the chord length dimensions in microns. As the measurements are performed in real time, the statistics of a distribution can be calculated and tracked. FBRM typically measures tens of thousands of chords per second, resulting in a robust number-by-chord length distribution. The method gives an absolute measure of the particle size distribution of the asphaltene particles.

[0078] The Focused beam Reflectance Probe (FBRM), model Lasentec D600L, was supplied by Mettler Toledo, Leicester, UK. The instrument was used in a configuration to give a particle size resolution of 1 μm to 1 mm. Data from FBRM can be presented in several ways. Studies have suggested that the average counts per second can be used as a quantitative determination of asphaltene dispersancy. This value is a function of both the average size and level of agglomerate. In this application, the average count rate (over the entire size range) was monitored using a measurement time of 1 second per sample.

[0079] The test lubricant formulations were heated to 60°C and stirred at 400 rpm. An aliquot of heavy fuel oil (16% w/w) was introduced into the lubricant formulation under stirring using a four-blade stirrer (at 400 rpm) and at 60°C. This mixture was stirred overnight. With the temperature at 60°C the FBRM probe was inserted into the sample- A value for the average counts per second was taken when the count rate had reached an equilibrium value (typically after 30 minutes equilibration time).

RESULTS

[0080] Response curves were generated showing the number of particle counts against active ingredient treat rate of the PIBSA. Results are presented as active ingredient treat rate required to deliver particle counts equivalent to a reference oil. Thus, lower active ingredient treat rate values indicate a better performance.

[0081] In the table below, the properties shown (Succination Ratio and M_n) are of the PIBSA used in each of the test lubricants.

Table 1

Examples	Maleation process	Succination Ratio	PIB M_n / g mol ⁻¹	Active ingredient Treat rate required to reach normalised count=1 / wt%
Comparative example 1	Chloro	1.17	1331	4.50
Comparative Example 2	Chloro	1.19	950	4.93
Comparative Example 3	Chloro	1.27	2225	4.10
Comparative Example 4	Chloro	1.31	1600	4.70
Example 1	Chloro	1.41	1331	2.58
Example 2	Chloro	1.62	1331	3.10
Example 3	Chloro	1.64	950	1.60
Example 4	Chloro	1.88	950	1.70
Example 5	Chloro	1.91	1331	1.83
Example 6	Chloro	2.06	950	2.09
Example 7	Chloro	2.17	2225	2.67
Example 8	Chloro	2.20	2225	2.44
Example 9	Chloro	2.67	950	2.41
Example 10	Chloro	3.10	1331	2.01
Example 11	Chloro	3.94	950	2.35

[0082] The table shows that much better results are achieved at higher succination ratios i.e. 1.41 to 3.94, as indicated below the bar. Although good results are achievable at higher PIB molecular weights, PIBSA's made therefrom have very high viscosities. They therefore have to be diluted much more than PIBSA's of lower PIB molecular weight. PIBSA's of PIB M_n 1,331 and 950 g mol⁻¹ are therefore preferred. Very high succination ratios or high polymer molecular weights leads to high viscosities; therefore a PIB M_n range of 700-1500 g mol⁻¹ and an SR range 1.50-2.00, preferably 1.70 or 1.65 - 2.00, are preferred.

[0083] The anhydride additives of the invention have been shown to boost the performance of salicylates to improve

their asphaltene dispersancy. Conventionally, PIBSAPAM-type dispersants are used to disperse contaminants in lubricating oils. Therefore, a comparison was made with two such PIBSAPAM-type dispersants (see table below). In combination with salicylates it can be seen that PIBSAPAM-type dispersants are not able to reach equivalent performance to the anhydride additives, which reach a normalised counts of '1' (i.e. equivalent performance) at much lower active ingredient treat rates.

Example	Description	Active ingredient Treat rate / wt%	Normalised counts
Comparative Example 5	Low molecular weight, low SR, chloro PIBSAPAM type dispersant ¹	3	9.0
Comparative Example 6	High molecular weight chloro, low SR, PIBSAPAM type dispersant ¹	3.3	4.17
¹ As described in US-A-3,219,666 (low molecular weight PIBSAPAM) and US-A-6,127,321 (high molecular weight PIBSAPAM).			

[0084] The materials of the invention do not work in the absence of salicylate detergents to affect asphaltene dispersancy. In the table below, the two PIBSAs were tested in the absence of salicylates and were unable to reach equivalent performance to any of the PIBSA/salicylate combinations of the invention. Even at significantly increased treat rates, no further improvements were observed.

Example	Material	SR	Active ingredient Treat / wt%	Normalised counts
Comparative Example 7	PIBSA from Example 4	1.18	3.58	6.4
Comparative Example 8	Example 2	1.62	3.78	7.16

[0085] Furthermore, PIBSAs synthesised by a 'thermal-ene' approach were ineffective compared with the PIBSAs of the invention derived from a chloro or radical maleation approach. These were tested in combination with salicylates.

Example	Process	SR	PIB M _n / g mol ⁻¹	Active ingredient Treat rate required to reach normalised count=1 / wt%
Comparative Example 9	Thermal	1.18	450	4.72
Comparative Example 10	Thermal	1.05	700	4.84
Comparative Example 11	Thermal	1.05	950	4.8
Comparative Example 12	Thermal	1.6	1300	6.8

Claims

1. A trunk piston marine engine lubricating oil composition for improving asphaltene handling in use thereof, in operation of such engine when fuelled by a heavy fuel oil, which composition comprises, or is made by admixing, an oil of lubricating viscosity and, in respective minor amounts:

(A) an overbased metal hydrocarbyl-substituted hydroxybenzoate detergent system, and
 (B) a hydrocarbyl-substituted succinic acid anhydride, preferably made by halogen- or radical-assisted functionalization processes, where the ratio of succinic anhydride groups per substituted hydrocarbyl moiety is in the range of 1.4 to 4, preferably 1.4 to 3.

2. The composition of claim 1 where, in (B), the hydrocarbyl group has a number average molecular weight in the range of 500 to 3,000.

3. The composition of claim 2 where the number average molecular weight is in the range of 700 to 2,300, preferably 800 to 1,500.
4. The composition of any of claims 1 to 3 where, in (B), the ratio is in the range of 1.50 to 2.20, preferably 1.50 to 2.00, more preferably 1.60 to 2.00.
5. The composition of any of claims 1 to 4 where, in (B), the hydrocarbyl group is a polyalkenyl group, such as a polyisobutylene group.
6. The composition of any of claims 1 to 5 where (B) is made by a chloro-maleation process.
7. The composition of any of claims 1 to 6 where the oil of lubricating viscosity comprises a Group II, III, IV or V basestock.
8. The composition of any of claims 1 to 7 where the oil of lubricating viscosity contains 30, such as 50, mass % or more of a basestock containing greater than or equal to 90 % saturates and less than or equal to 0.03 % sulphur or a mixture thereof.
9. The composition of any of claims 1 to 8 having a TBN in the range of 20 to 60, such as 30 to 55.
10. The composition of any of claims 1 to 9 where detergent system (A) comprises a calcium alkyl salicylate detergent system.
11. The composition of any one of the preceding claims, wherein the anhydride (B) constitutes at least 0.1 to 10, preferably 0.5 to 8.5, even more preferably 1 to 7, and most preferably 1.5 to 5, mass %, on an active ingredient basis, of the lubricating oil composition.
12. A method of operating a trunk piston medium-speed compression-ignited marine engine comprising:
 - (i) fuelling the engine with a heavy fuel oil; and
 - (ii) lubricating the engine with a composition as defined in any of claims 1 to 11.
13. A method of dispersing asphaltenes in trunk piston marine lubricating oil composition during its lubrication of surfaces of a medium-speed compression-ignited marine engine and operation of the engine, which comprises:
 - (i) providing a composition as defined in any of claims 1 to 11;
 - (ii) providing the composition to the engine;
 - (iii) providing heavy fuel oil to the engine; and
 - (iv) combusting the fuel oil.
14. The use of detergent system (A) as defined in claim 1 in combination with anhydride (B) as defined in claim 1 in a trunk piston marine lubricating oil composition for a medium-speed compression-ignited marine engine, to improve asphaltene handling during operation of the engine, fueled by a heavy fuel oil.
15. A concentrate suitable for blending into a composition of any of claims 1 to 9 comprising (A) and (B) as defined in any of claims 1 to 6 and 10.



EUROPEAN SEARCH REPORT

Application Number
EP 15 19 5322

5

10

15

20

25

30

35

40

45

50

55

1

EPO FORM 1503 03.82 (P04C01)

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	WO 2010/115594 A1 (INFINEUM INT LTD [GB]; GARNER TERRY [GB]; GREGORY LAURA [GB]; HARTLEY) 14 October 2010 (2010-10-14) * the whole document *	1-15	INV. C10M141/02 C10M169/04
A	EP 2 765 179 A1 (INFINEUM INT LTD [GB]) 13 August 2014 (2014-08-13) * the whole document *	1-15	ADD. C10N10/04 C10N30/04 C10N40/25
A	EP 2 644 687 A1 (INFINEUM INT LTD [GB]) 2 October 2013 (2013-10-02) * the whole document *	1-15	
A	EP 2 735 603 A1 (INFINEUM INT LTD [GB]) 28 May 2014 (2014-05-28) * the whole document *	1-15	
A	EP 2 123 739 A1 (INFINEUM INT LTD [GB]) 25 November 2009 (2009-11-25) * paragraphs [0001], [0003], [0041]; claims 1,7; examples *	1-15	
			TECHNICAL FIELDS SEARCHED (IPC)
			C10M
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 18 March 2016	Examiner Renoth, Heinz
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 15 19 5322

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-03-2016

10

15

20

25

30

35

40

45

50

55

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 2010115594 A1	14-10-2010	AU 2010234299 A1	27-10-2011	
		AU 2010234300 A1	27-10-2011	
		CA 2755308 A1	14-10-2010	
		CA 2755815 A1	14-10-2010	
		CN 102365352 A	29-02-2012	
		CN 102365353 A	29-02-2012	
		CN 104277894 A	14-01-2015	
		EP 2417233 A1	15-02-2012	
		EP 2417234 A1	15-02-2012	
		ES 2425957 T3	18-10-2013	
		ES 2428237 T3	06-11-2013	
		JP 5698728 B2	08-04-2015	
		JP 5698729 B2	08-04-2015	
		JP 2012522878 A	27-09-2012	
		JP 2012522879 A	27-09-2012	
		KR 20120006995 A	19-01-2012	
		KR 20120027208 A	21-03-2012	
		SG 174925 A1	28-11-2011	
		SG 175117 A1	28-11-2011	
		US 2012028521 A1	02-02-2012	
		US 2012028522 A1	02-02-2012	
		WO 2010115594 A1	14-10-2010	
		WO 2010115595 A1	14-10-2010	

EP 2765179 A1	13-08-2014	AU 2014200673 A1	21-08-2014	
		CA 2842081 A1	07-08-2014	
		CN 103980980 A	13-08-2014	
		EP 2765179 A1	13-08-2014	
		JP 2014152334 A	25-08-2014	
		KR 20140100905 A	18-08-2014	
		SG 2014008759 A	26-09-2014	
		US 2014221261 A1	07-08-2014	

EP 2644687 A1	02-10-2013	AU 2013202144 A1	17-10-2013	
		CA 2810720 A1	29-09-2013	
		CN 103361147 A	23-10-2013	
		EP 2644687 A1	02-10-2013	
		JP 2013204040 A	07-10-2013	
		KR 20130111393 A	10-10-2013	
		SG 193762 A1	30-10-2013	
		US 2013281334 A1	24-10-2013	

EP 2735603 A1	28-05-2014	AU 2013260695 A1	05-06-2014	
		CA 2833977 A1	21-05-2014	
		CN 103834458 A	04-06-2014	
		EP 2735603 A1	28-05-2014	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 15 19 5322

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-03-2016

10

15

20

25

30

35

40

45

50

55

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
				JP 2014101513 A	05-06-2014
				KR 20140065350 A	29-05-2014
				SG 2013085915 A	27-06-2014
				US 2014165943 A1	19-06-2014

EP 2123739	A1	25-11-2009	AU	2009201996 A1	10-12-2009
			CA	2666092 A1	20-11-2009
			CN	101586050 A	25-11-2009
			EP	2123739 A1	25-11-2009
			JP	5366653 B2	11-12-2013
			JP	2009280816 A	03-12-2009
			SG	157322 A1	29-12-2009
			US	2009291869 A1	26-11-2009

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 2010115594 A [0003]
- WO 2010115595 A [0003]
- EP 2644687 A [0003]
- US 5334321 A [0013]
- US 20070027057 A [0036]
- US 5498809 A [0056]
- US 5663130 A [0056]
- US 5705577 A [0056]
- US 5814715 A [0056]
- US 6022929 A [0056]
- US 6030930 A [0056]
- US 4952739 A [0057]
- US 4152499 A [0057]
- US 3087936 A [0060]
- US 3172892 A [0060]
- US 3215707 A [0060]
- US 3231587 A [0060]
- US 3272746 A [0060]
- US 3275554 A [0060]
- US 3381022 A [0060]
- US 3442808 A [0060]
- US 3565804 A [0060]
- US 3912764 A [0060]
- US 4110349 A [0060]
- US 4234435 A [0060] [0062]
- US 5777025 A [0060]
- US 5891953 A [0060]
- EP 0382450 B1 [0060]
- CA 1335895 [0060]
- GB 1440219 A [0060]
- CA 2471534 [0063]
- US 3219666 A [0083]
- US 6127321 A [0083]

Non-patent literature cited in the description

- Engine Oil Licensing and Certification System. The American Petroleum Institute (API), December 1996 [0026]
- The Benefits of Salicylate Detergents in TPEO Applications with a Variety of Base Stocks. *7th International Symposium on Marine Engineering, Tokyo*, 24 October 2005 [0074]
- Meeting the Challenge of New Base Fluids for the Lubrication of Medium Speed Marine Engines - An Additive Approach. *CIMAC Congress, Vienna*, 21 May 2007 [0074]