



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Abstract

(51) Int Cl.:
A47L 15/42 (2006.01) **A47L 15/44** (2006.01)

(86) International application number:
PCT/KR2013/009651

(48) Corrigendum issued on:
05.10.2016 Bulletin 2016/40

(87) International publication number:
WO 2015/020268 (12.02.2015 Gazette 2015/06)

(43) Date of publication:
15.06.2016 Bulletin 2016/24

(21) Application number: **13891333.0**

(22) Date of filing: **29.10.2013**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

(71) Applicant: **Daeun Global Solution Co., Ltd.**
Bupyeong-gu, Incheon 403-911 (KR)

(72) Inventor: **SHIN, Kyung-sub**
Incheon 403-020 (KR)

(74) Representative: **Ruzzu, Giammario**
Via Gulli, 5
40068 San Lazzaro di Savena (BO) (IT)

(30) Priority: **05.08.2013 KR 20130092525**

(54) **CASE FOR DISHWASHER-USE WASHING BALLS**

(57) The present invention relates to a washing ball case for a dishwasher, used to wash dishes by washing balls of a ceramic material and washing water without using any detergents and, more particularly, to a washing ball case for a dishwasher, wherein a case body (100) is formed by thermally bonding a top plate (10) and a bottom plate (20) and has through holes (120) formed in an outer side portion thereof so as to completely drain the washing water at the time of washing dishes such that the washing balls can be maintained in a dried state through the complete draining of the washing water and the washing efficiency of the washing balls can be maximized in next dish-washing, and through holes (120) and reference grooves (130) are provided to the outer portions of the top plate (10) and the bottom plate (20) such that, at the time of the thermal bonding, the top plate (10) and the bottom plate (20) can be bonded to each other at uniform positions in a fixed state without movement by the through holes (120) and the reference grooves (130) so as to prevent the conventional bonding defects.

Fig.1

