



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:
Corrected version no 1 (W1 A2)
Corrections, see
Bibliography INID code(s) 30

(51) Int Cl.:
G01N 29/22 (2006.01)

(48) Corrigendum issued on:
29.03.2017 Bulletin 2017/13

(43) Date of publication:
15.02.2017 Bulletin 2017/07

(21) Application number: **15200592.2**

(22) Date of filing: **16.12.2015**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
MA MD

- **TOPCZEWSKI, Lukasz**
03-984 Warszawa (PL)
- **MIKOLAJEWSKI, Pawel**
71-471 Szczecin (PL)
- **ADAMSKI, Pawel**
59-300 Lubin (PL)
- **LUBEK, Slawomir**
71-220 Bezzecze (PL)
- **MARKOWSKI, Zenon**
70-744 Szczecin (PL)
- **MOTYLINSKI, Marcin**
71-677 Szczecin (PL)
- **MALECKI, Mariusz**
80-175 Gdansk (PL)

(30) Priority: **10.08.2015 PL 41349615**

(71) Applicants:
• **Instytut Badawczy Dróg I Mostów**
03-302 Warszawa (PL)
• **Escort Sp. z o.o.**
70-103 Szczecin (PL)

(72) Inventors:
• **CIESLA, Juliusz**
02-106 Warszawa (PL)

(74) Representative: **Adamczyk, Piotr**
Kancelaria Patentowa Piotr Adamczyk
Ul. Wilcza 70/8
00-670 Warszawa (PL)

(54) **APPARATUS FOR FIXING OF MEASURING DEVICE FOR MONITORING BOTTOM SHAPE NEAR BRIDGE SUPPORT TO BRIDGE STRUCTURE, METHOD FOR FIXING SUCH APPARATUS TO BRIDGE STRUCTURE AND SLING FOR SUCH FIXING**

(57) The apparatus contains a boom (4), at the end of which there is a measuring device (5). The boom (4) is affixed to a multi-section clamp (3) with adjustable length, which is mounted on a sling (1) affixed to a bridge support (2). The boom (4) consists of a guide (18) mounted slidably and rotatably in a sleeve (19), with the option to stabilize a specific position of this guide (18) with respect to the sleeve (19). One guide (18) end is connected to the cover (6) of the measuring device (5). The sleeve (19) of the boom (4) is affixed to the lower part (10) of the clamp (3).

