



(11) **EP 3 144 631 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 54

(51) Int Cl.:
G01B 3/00 (2006.01) **G01B 3/22** (2006.01)
G01B 3/18 (2006.01) **G01B 3/20** (2006.01)
G01D 7/06 (2006.01) **G01B 7/02** (2006.01)
G01B 11/02 (2006.01)

(48) Corrigendum issued on:
08.11.2017 Bulletin 2017/45

(43) Date of publication:
22.03.2017 Bulletin 2017/12

(21) Application number: **16002212.5**

(22) Date of filing: **05.09.2012**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR

- **SHIRAISHI, Yoshiaki**
Kanagawa 213-8533 (JP)
- **HAYASHIDA, Shuji**
Kanagawa 213-8533 (JP)
- **KIWADA, Takefumi**
Gifu 509-9132 (JP)

(30) Priority: **05.09.2011 JP 2011192931**
23.08.2012 JP 2012184384

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
13004587.5 / 2 693 162
12006264.1 / 2 565 577

(74) Representative: **Müller-Boré & Partner**
Patentanwälte PartG mbB
Friedenheimer Brücke 21
80639 München (DE)

(71) Applicant: **Mitutoyo Corporation**
Kawasaki-shi, Kanagawa 213-8533 (JP)

Remarks:

This application was filed on 14-10-2016 as a divisional application to the application mentioned under INID code 62.

(72) Inventors:

- **HAYASHI, Nobuyuki**
Kanagawa 213-8533 (JP)

(54) **ORGANIC ELECTROLUMINESCENT DOT-MATRIX DISPLAY FOR A MEASURING INSTRUMENT AND MEASURING INSTRUMENT WITH SUCH DISPLAY**

(57) A measuring instrument comprising a display (50) on which measurements are displayed, wherein the display (50) is provided by an organic electroluminescent display device (50A) comprising an assembly of organic electroluminescence devices or an electronic paper, the display (50) is a dot-matrix type in which display elements are arranged in a matrix, the display (50) is provided with a scale-segment image display area (82) that displays a plurality of scale-seg-

ment images arranged in a circle and a reversed image display area (83) that reversely displays the scale segment image corresponding to an angular area in accordance with the measurements, and the measuring instrument is provided with a scale-interval switch (60) that switches an interval between the scale segment images in accordance with a display resolution.

EP 3 144 631 A8

FIG. 5

