



(11) **EP 3 156 535 A1**

(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
19.04.2017 Bulletin 2017/16

(51) Int Cl.:
D06F 23/02 ^(2006.01) **D06F 23/06** ^(2006.01)
D06F 37/40 ^(2006.01)

(21) Application number: **15806510.2**

(86) International application number:
PCT/CN2015/079426

(22) Date of filing: **21.05.2015**

(87) International publication number:
WO 2015/188683 (17.12.2015 Gazette 2015/50)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
MA

• **Qingdao Haier Washing Machine Co., Ltd.**
Laoshan District
Qingdao,
Shandong 266101 (CN)

(30) Priority: **12.06.2014 JP 2014121778**

(72) Inventors:
• **TSUJI, Takahiro**
Tokyo 100-0005 (JP)
• **TANAKA, Hiroyuki**
Tokyo 100-0005 (JP)

(71) Applicants:
• **Haier Asia Co., Ltd**
Tokyo 100-0005 (JP)

(74) Representative: **Zacco Sweden AB**
P.O. Box 5581
114 85 Stockholm (SE)

(54) **DRUM TYPE WASHING MACHINE**

(57) Disclosed is a drum type washing machine which can carry out switching of a driving form of a driving part through a clutch mechanism part (600) in good precision. A driving unit (30) includes a driving motor (100) and the clutch mechanism part (600), where the clutch mechanism part (600) switches a driving form of the driving unit (30) between a first-shaft driving form and a second-shaft driving form, the first-shaft driving form is a form that enables a wing shaft (200) for transmitting rotation to a stirring body (24) and a drum shaft (300) for transmitting rotation to a drum (22) to integrally rotate at a same rotation speed, and the second-shaft driving form is a form that enables the wing shaft (200) and the drum shaft (300) to respectively rotate at different rotation speeds. By moving a clutch body (610) of the clutch mechanism part (600) to a first position so as to engage an engaging flange part (613) at the first position with an engaged recess (114) that rotates along with rotation of the driving motor (100), the driving form is switched to the first-shaft driving form. A control part (701) executes first-shaft switching treatment, where the first-shaft switching treatment is treatment that enables the clutch mechanism part (600) to work to move the clutch body (610) to the first position and then enables the driving motor (100) to rotate to engage the unengaged engaging flange part (613) with the engaged recess (114).

First-shaft switching treatment




FIG.9

EP 3 156 535 A1

Description**TECHNICAL FIELD**

[0001] The present invention relates to a drum type washing machine, which can not only continuously operate from washing to drying, but also carry out washing without drying.

BACKGROUND

[0002] Previously, a drum type washing machine stores water in an outer tank at the bottom to enable a transverse-shaft type drum to rotate, washings are lifted up and dropped down by baffles arranged in the drum, and the washings are thrown to the inner circumferential surface of the drum to be washed (with reference to a patent document 1).

[0003] In this way, in a structure of stirring the washings by the baffle, the washings are difficult to twine or rub against each other. Therefore, compared with an automatic washing machine which washes the washings through rotation of a pulsator in a washing and dewatering tank, the drum type washing machine has mechanical force, acting on the washings, easy to get small, , and has detergency easy to lower.

[0004] Therefore, in the drum type washing machine, in order to improve the detergency, a structure that a stirring body is arranged on the rear surface of the drum may be adopted, so that the drum and the stirring body can rotate at different rotation speeds when in washing and rinsing.

Current Technical Literature

Patent Literature

[0005] Patent Literature 1: Japanese Laid-Open Patent Publication No. 2013-240577

SUMMARY

Problems to be solved by the invention

[0006] In a drum type washing machine with the above structure, a drum and a stirring body need to integrally rotate at a same rotation speed when in dewatering. Therefore, a clutch mechanism part is arranged at a driving part of the drum and the stirring body, so that a driving form of the driving part can be switched between a first-shaft driving form that enables the drum and the stirring body to integrally rotate at the same rotation speed and a second-shaft driving form that enables the drum and the stirring body to respectively rotate at different rotation speeds.

[0007] Under such condition that the driving form is switched by the clutch mechanism part, if switching is carried out in poor precision, the situation that the drum

and the stirring body incorrectly work to lose the expected performance occurs, causing lowered reliability.

[0008] The present invention is completed in view of the problems and aims at providing a drum type washing machine which can realize switching of the driving form of the driving part through the clutch mechanism part in good precision.

Solution for solving the problems

[0009] The drum type washing machine in a main manner of the present invention includes: an outer tank, configured in a housing; a drum, configured in the outer tank and is capable of rotating by using a horizontal axis or an inclination axis inclining relative to a horizontal direction as a center; a rotating body, configured at a rear part of the drum and provided, on a surface of the rotating body, with a protruding part in contact with washings; a driving part, configured to enable the drum and the rotating body to rotate; and a control part, configured to control working of the driving part. Herein, the driving part includes: a driving motor; a first rotation shaft which transmits rotation of the driving motor to the rotating body; a second rotation shaft which transmits rotation of the driving motor to the drum; and a clutch mechanism part which enables a driving form of the driving part to be switched between a first-shaft driving form and a second-shaft driving form, wherein the first-shaft driving form is a form that enables the first rotation shaft and the second rotation shaft to integrally rotate at a same rotation speed, and the second-shaft driving form is a form that enables the first rotation shaft and the second rotation shaft to respectively rotate at different rotation speeds. In addition, the clutch mechanism part includes a clutch body provided with a first engaging part, where by moving the clutch body to a first position so as to engage the first engaging part at the first position with a first engaged part that rotates with rotation of the driving motor, the driving form is switched to the first-shaft driving form. In order to carry out switching from the second-shaft driving form to the first-shaft driving form, the control part executes first-shaft switching treatment, wherein the first-shaft switching treatment is treatment that enables the driving motor to rotate to engage the unengaged first engaging part with the first engaged part after enabling the clutch mechanism part to work to move the clutch body to the first position.

[0010] According to the above structure, even if dislocation between the first engaging part and the first engaged part is generated when the clutch mechanism part is operated to move the clutch body to the first position, the dislocation can be eliminated, so that the first engaging part is engaged with the first engaged part. Therefore, switching from the second-shaft driving form to the first-shaft driving form can be carried out in good precision.

[0011] In the drum type washing machine in the manner, for the first-shaft switching treatment, the control part may adopt a structure that the driving motor rotates with

a driving current lower than a driving current enabling the driving motor to rotate under the first-shaft driving form after the first-shaft switching treatment.

[0012] According to the above structure, for the first-shaft switching treatment, as the driving motor can slowly rotate, the first engaging part is easily engaged with the first engaged part, thereby improving switching precision.

[0013] The drum type washing machine in the manner may adopt a structure below, namely, the driving part further includes a planetary gear mechanism, wherein the planetary gear mechanism is provided with: a sun gear which rotates along with rotation of the motor; an annular internal gear which surrounds the sun gear; a plurality of planetary gears which are arranged between the sun gear and the internal gear; and a planetary gear carrier which holds the planetary gears in a free manner, wherein one of the planetary gear carrier and the internal gear is fixed on the second rotation shaft. Under such condition, the drum type washing machine in the manner may adopt a structure below, namely, the clutch body is provided with a second engaging part and is connected with the other one of the planetary gear carrier and the internal gear in a state of limiting rotation relative to the other one of the planetary gear carrier and the internal gear toward a circumferential direction and allowing movement along an axial direction of the second rotation shaft. Through such structures, the driving part enables the clutch body to move to a second position, the second engaging part is engaged with a second engaged part that does not rotate along with rotation of the driving motor at the second position, and the other one of the planetary gear carrier and the internal gear is in a non-rotation state, so that the driving form is switched to the second-shaft driving form. Even if the clutch mechanism part works to enable the clutch body to move to the second position, the other one of the planetary gear carrier and the internal gear can also rotate along with rotation of the driving motor when the second engaging part is not engaged with the second engaged part, thereby causing rotation of the clutch body. In order to carry out switching from the second-shaft driving form to the first-shaft driving form, the control part executes second-shaft switching treatment, wherein the second-shaft switching treatment is treatment that enables the driving motor to rotate to engage the unengaged second engaging part with the second engaged part after enabling the clutch mechanism part to work to move the clutch body to the second position.

[0014] According to the above structure, even if dislocation between the second engaging part and the second engaged part is generated when the clutch mechanism part is operated to move the clutch body to the second position, the dislocation can be eliminated, so that the second engaging part is engaged with the second engaged part. Therefore, switching from the first-shaft driving form to the second-shaft driving form can be carried out in good precision.

[0015] Under a situation of adopting the above struc-

ture, further, for the second-shaft switching treatment, the control part may adopt a structure that the driving motor rotates with a driving current lower than a driving current enabling the driving motor to rotate under the second-shaft driving form after the second-shaft switching treatment.

[0016] As long as such structure is adopted, for the second-shaft switching treatment, as the driving motor can slowly rotate, the second engaging part is easily engaged with the second engaged part, thereby improving switching precision.

[0017] Under a situation of adopting the above structure, the drum type washing machine is further provided with a clutch driving apparatus configured to enable the clutch body to move. Under such condition, the clutch driving apparatus includes: a working body which can be transferred to a first working state enabling the clutch body to move to the first position and a second working state enabling the clutch body to move to the second position; and a state detection part which detects a working state of the working body. For the first-shaft switching treatment, the control part enables the clutch driving apparatus to work according to a detection result of the state detection part so as to enable the working body to be transferred to the first working state; and for the second-shaft switching treatment, the control part enables the clutch driving apparatus to work according to a detection result of the state detection part so as to enable the working body to be transferred to the second working state.

[0018] As long as such structure is adopted, as the position of the clutch body is indirectly detected by detecting the working state of the working body, the driving form of the driving part can be switched with no need of using a sensor and the like configured to directly detect the position of the clutch body.

Effects of the invention

[0019] According to the present invention, the drum type washing machine can be provided, which can realize switching of the driving form of the driving part through the clutch mechanism part in good precision.

[0020] The effects and the significance of the present invention may be further defined through the description of an implementation manner shown below. However, the implementation manner below is only one illustration when the present invention is implemented, and the present invention is not limited by a technical solution described by the implementation manner below.

BRIEF DESCRIPTION OF DRAWINGS

[0021]

Fig. 1 is a side sectional view illustrating a structure of a drum type washing machine involved in an implementation manner;

Fig. 2 is a sectional view illustrating a structure of a driving unit involved in an implementation manner; Fig. 3 is a sectional view illustrating a structure of a driving unit involved in an implementation manner; Fig. 4 is a front view illustrating a rotor and a rotor structure of a driving motor involved in an implementation manner;

Fig. 5 is an enlarged stereoscopic view illustrating a rear part of a bearing unit formed with a rack involved in an implementation manner;

Fig. 6 is a diagram illustrating a structure of a clutch body of a clutch mechanism part involved in an implementation manner;

Fig. 7 is a block diagram illustrating a structure of the drum type washing machine involved in an implementation manner;

Fig. 8 is a diagram illustrating a state that an engaging flange part of the clutch body and an engaged recess of the rotor generate dislocation involved in an implementation manner;

Fig. 9 is a flow chart illustrating first-shaft switching treatment involved in an implementation manner;

Fig. 10 is a flow chart illustrating second-shaft switching treatment involved in an implementation manner;

Fig. 11 is a diagram illustrating a structure of a driving unit involved in a changed example.

DETAILED DESCRIPTION

[0022] A drum type washing machine without a drying function as an implementation manner of a drum type washing machine of the present invention is described below with reference to the drawings.

[0023] Fig. 1 is a side sectional view illustrating a structure of a drum type washing machine 1.

[0024] The drum type washing machine 1 is provided with a housing 10 forming an appearance. A front surface 10a of the housing 10 inclines from the central part to the upper part, a throwing opening 11 of washings is formed on the inclined surface, and the throwing opening 11 is covered by a freely opened/closed door 12.

[0025] An outer tank 20 is elastically supported by a plurality of shock absorbers in the housing 10. A drum 22 is configured in the outer tank 20 in a free rotation way. The outer tank 20 and the drum 22 incline in a manner that the rear surface sides become lower relative to a horizontal direction. Therefore, the drum 22 rotates by using an inclined shaft inclining relative to the horizontal direction as the center. The inclination angles of the outer tank 20 and the drum 22 are set as about 10-20 degrees. An opening part 20a of the front surface of the outer tank 20 and an opening part 22a of the front surface of the drum 2 are opposite to the throwing opening 11 and are closed by the door 12 together with the throwing opening 11. A plurality of dewatering holes 22b are formed in the inner circumferential surface of the drum 22. Then, three baffles 23 are arranged on the inner circumferential surface of the drum 22 along a circumferential direction at

almost equal intervals.

[0026] A stirring body 24 is configured at the rear part of the drum 22 in a free rotation way and is in an approximate disc shape. A plurality of blades 24a radially extending from the central part are formed on the surface of the stirring body 24. The stirring body 24 and the drum 22 coaxially rotate. The stirring body 24 is equivalent to a rotating body of the present invention, and the blades 24 are equivalent to protrusion parts of the present invention.

[0027] A driving unit 30 generating a torque for driving the drum 22 and the stirring body 24 is configured to behind the outer tank 20 and is equivalent to a driving part of the present invention. The driving unit 30 enables the drum 22 and the stirring body 24 to rotate along the same direction at different rotation speeds in a washing process and a rinsing process. Specifically, the driving unit 30 enables the drum 22 to rotate at a rotation speed with the centrifugal force exerted on the washings in the drum 22 less than the gravity and enables the stirring body 24 to rotate at a rotation speed higher than that of the drum 22. In another aspect, the driving unit 30 enables the drum 22 and the stirring body 24 to integrally rotate at a rotation speed with the centrifugal force exerted on the washings in the drum 22 far more than the gravity in a dewatering process. The detailed structure of the driving unit 30 is described subsequently.

[0028] A water outlet part 20b is formed at the bottom of the outer tank 20. A drainage valve 40 is arranged in the water outlet part 20b and is connected with a drainage hose 41. Water stored in the outer tank 20 is discharged out of the machine through the drainage hose 41 when the drainage valve 40 is opened.

[0029] A detergent box 50 is configured at the front upper part in the housing 10. A detergent container 50a containing a detergent, which can be freely drawn out from the front of the detergent box 50, is contained in the detergent box 50. The detergent box 50 is connected with a water-feeding valve 51 configured to at the rear upper part in the housing 10 through a water-feeding hose 52. In addition, the detergent box 50 is connected with the upper part of the outer tank 20 through a water injection pipe 53. Tap water from a faucet is supplied into the outer tank 20 through the water-feeding hose 52, the detergent box 50 and the water injection pipe 53 when the water-feeding valve 51 is opened. At this moment, the detergent contained in the detergent container 50a is supplied into the outer tank 20 along with a water flow.

[0030] Next, the structure of the driving unit 30 is described in detail.

[0031] Fig. 2 and Fig. 3 are sectional views illustrating the structure of the driving unit 30. Fig. 2 is a sectional view illustrating a state that a driving form of the driving unit 30 is switched to a second-shaft driving form, and Fig. 3 is a sectional view illustrating a state that the driving form of the driving unit 30 is switched to a first-shaft driving form. Fig. 4 is a front view illustrating a structure of a rotor 110 of a driving motor 100. Fig. 5 is an enlarged

stereoscopic view illustrating a rear part of a bearing unit 500, on which a rack 514 is formed. Figs. 6(a)-6(c) are diagrams illustrating a structure of a clutch body 610 of a clutch mechanism part 600 and are respectively a front view, a right view and a rear view of the clutch body 610.

[0032] The driving unit 30 includes: the driving motor 100, a wing shaft 200, a drum shaft 300, a planetary gear mechanism 400, the bearing unit 500 and the clutch mechanism part 600. The driving motor 100 generates the torque used for driving the stirring body 24 and the drum 22. The wing shaft 200 rotates through the torque of the driving motor 100 and transmits rotation to the stirring body 24. The wing shaft 200 is equivalent to a first rotation shaft of the present invention. The planetary gear mechanism 400 slows down rotation of the wing shaft 200, i.e. rotation of the rotor 110 of the driving motor 100, and transmits rotation to the drum shaft 300. The drum shaft 300 coaxially rotates with the wing shaft 200 at a rotation speed after being slowed down by the planetary gear mechanism 400 and transmits rotation to the drum 22. The drum shaft 300 is equivalent to a second rotation shaft of the present invention. The bearing unit 500 supports the wing shaft 200 and the drum shaft 300 in a free rotation way. The clutch mechanism part 600 switches a driving form of the driving motor 100 between the second-shaft driving form and the first-shaft driving form, wherein the second-shaft driving form is a form that enables the stirring body 24, i.e. the wing shaft 200, to rotate at a rotation speed that is equal to that of the driving motor 100 and enables the drum 22, i.e. the drum shaft 300, to rotate at a rotation speed after being slowed down by the planetary gear mechanism 400; and the first-shaft driving form is a form that enables the stirring body 24 and the drum 22, i.e. the wing shaft 200 and the drum shaft 300, and the planetary gear mechanism 400 to integrally rotate at a rotation speed that is equal to that of the driving motor 100.

[0033] The driving motor 100 is an outer rotor type DC (Direct Current) brushless motor and includes the rotor 110 and a stator 120. The rotor 110 is in a cylindrical shape with a bottom, and permanent magnets 111 are arranged on the inner circumferential surface and the whole circumference of the rotor 110. As shown in Fig. 4, a round shaft sleeve part 112 is formed at the central part of the rotor 110. A shaft sleeve hole 113 configured to fix the wing shaft 200 is formed in the shaft sleeve part 112, and an annular engaged recess 114 is formed on the outer circumference of the shaft sleeve hole 113. Concave-convex parts 114a are arranged at the outer circumferential part and the whole circumference of the engaged recess 114. The engaged recess 114 is equivalent to a first engaged part of the present invention.

[0034] A coil 121 is arranged at the outer circumferential part of the stator 120. The rotor 110 rotates when an after-mentioned motor driving part supplies driving current to the coil 121 of the stator 120.

[0035] The drum shaft 300 is in a hollow shape, and the wing shaft 200 and the planetary gear mechanism

400 are wrapped inside the drum shaft 300. The central part of the drum shaft 300 is bulged toward the outer side, and the bulging part forms a containing part of the planetary gear mechanism 400.

[0036] The planetary gear mechanism 400 includes: a sun gear 410, an annular internal gear 420 which surrounds the sun gear 410, a plurality of groups of planetary gears 430 which are arranged between the sun gear 410 and the internal gear 420 and a planetary gear carrier 440 which holds the planetary gears 430 in a free rotation manner.

[0037] The sun gear 410 is fixed on the wing shaft 200, and the internal gear 420 is fixed on the drum shaft 300. One group of planetary gears 430 includes a first gear and a second gear which are engaged with each other and rotate in reverse directions. The planetary gear carrier 440 includes a gear carrier shaft 441 extending backward. The gear carrier shaft 441 is coaxial with the drum shaft 300, and a hollow part is formed in the gear carrier shaft 441, so as to insert the wing shaft 200.

[0038] The rear end part of the wing shaft 200 protrudes backward from the gear carrier shaft 441 and is fixed in the shaft sleeve hole 113 on the rotor 110.

[0039] A cylindrical bearing part 510 is arranged at the central part of the bearing unit 500. In the bearing part 510, a roller 511 and a roller 512 are respectively arranged at the front part and the rear part, and a mechanical sealing element 513 is arranged at the front end part. The outer circumferential surface of the drum shaft 300 is supported by the rollers 511 and 512, and the drum shaft 300 smoothly rotates in the bearing part 510. In addition, the mechanical sealing element 513 prevents water from invading between the bearing part 510 and the drum shaft 300. As shown in Fig. 5, racks 514 are formed on the inner surface and the whole circumference of the rear end part of the bearing part 510. The racks 514 are equivalent to second engaged parts of the present invention.

[0040] In the bearing unit 500, a fixed flange part 520 is formed at the circumference of the bearing part 510. A mounting boss 521 is formed at the lower end part of the fixed flange part 520.

[0041] In the fixed flange part 520, the bearing unit 500 is fixed on the rear surface of the outer tank 20 by a fixing method of screw fastening and the like. In a state that the driving unit 30 is installed in the outer tank 20, the wing shaft 200 and the drum shaft 300 are faced with the inner part of the outer tank 20. The drum 22 is fixed on the drum shaft 300, and the stirring body 24 is fixed on the wing shaft 200.

[0042] The clutch mechanism part 600 includes: the clutch body 610, a clutch spring 620, a clutch lever 630, a lever supporting part 640, a clutch driving apparatus 650, a jointing rod 660 and a mounting plate 670.

[0043] As shown in Figs. 6(a)-6(c), the clutch body 610 is in an approximate disc shape. An annular rack 611 is formed on the outer circumferential surface of the front end part of the clutch body 610. The rack 611 is formed

in a manner of being engaged with the rack 514 of the bearing unit 500. In addition, on the outer circumferential surface of the clutch body 610, a flange part 612 is formed behind the rack 611. Further, an annular engaging flange part 613 is formed at the rear end part on the clutch body 610. The engaging flange part 613 is in a shape the same as that of the engaged recess 114 of the rotor 110, and concave-convex parts 613a are arranged on the outer circumferential part and the whole circumference of the engaging flange part 613. The concave-convex parts 613a are engaged with each other when the engaging flange part 613 is inserted into the engaged recess 114. The engaging flange part 613 is equivalent to a first engaging part of the present invention, and the racks 611 are equivalent to second engaging parts of the present invention.

[0044] The gear carrier shaft 441 is inserted into a shaft hole 614 of the clutch body 610. A rack 614a formed on the inner circumferential surface of the shaft hole 614 is engaged with a rack 441a formed on the outer circumferential surface of the gear carrier shaft 441. Therefore, the clutch body 610 becomes a state of allowing movement back and forth and limiting rotation in a circumferential direction relative to the gear carrier shaft 441.

[0045] On the clutch body 610, an annular containing tank 615 is formed on the outer side of the shaft hole 614, and the clutch spring 620 is contained in the containing tank 615. One end of the clutch spring 620 is connected with the rear end part of the bearing part 510, and the other end of the clutch spring 620 is connected with the bottom surface of the containing tank 615.

[0046] A pressing part 631 which is in contact with the rear surface of the flange part 612 of the clutch body 610 and pushes the flange part 612 forward is formed at the upper end part of the clutch lever 630. The clutch lever 630 is supported by a supporting shaft 641 arranged on the lever supporting part 640 in a free rotation way. A mounting shaft 632 is formed at the lower end part of the clutch lever 630.

[0047] The clutch driving apparatus 650 is configured under the clutch lever 630. The clutch driving apparatus 650 includes a torque motor 651 and a disc-shaped cam 652 that rotates around a horizontal axis through a torque of the torque motor 651. A cam shaft 653 is arranged at the outer circumferential part on the cam 652. The rotating center of the cam 652 is the same as the center of the mounting shaft 632 of the clutch lever 630 in the forward-and-backward direction. The cam 652 is equivalent to a working body of the present invention.

[0048] The jointing rod 660 extends in the up-and-down direction and is configured to connect the clutch lever 630 and the cam 652. The upper end part of the jointing rod 660 is installed on the mounting shaft 632 of the clutch lever 630, and the lower end part of the jointing rod 660 is installed on the cam shaft 653 of the cam 652. A spring 661 is integrally formed at the middle position of the jointing rod 660 and is an extension spring.

[0049] The lever supporting part 640 and the clutch

driving apparatus 650 are fixed on the mounting plate 670 by a fixing method of screw fastening and the like. The mounting plate 670 is fixed on the mounting boss 521 of the bearing unit 500 by screws.

[0050] Under a situation of switching the driving form of the driving unit 30 from the first-shaft driving form to the second-shaft driving form, as shown in Fig. 2, the cam 652 rotates through the torque motor 651 to enable the cam shaft 653 to be located at the lowest position. Along with rotation of the cam 652, the lower end part of the clutch lever 630 is pulled to the lower part by the jointing rod 660. The clutch lever 630 rotates forward by using the supporting shaft 641 as the center, and the pressing part 631 pushes the clutch body 610 forward. The clutch body 610 moves forward against the elasticity of the clutch spring 620, and the rack 611 of the clutch body 610 is engaged with the rack 514 of the bearing unit 500.

[0051] The rack 611 arrives at the position where the rack 611 is engaged with the rack 514 when the cam shaft 653 of the clutch body 610 moves to the assigned central position. At this moment, the spring 661 of the jointing rod 660 is in a natural length state. Since the clutch body 610 does not move to the position more forward than the engaging position, when the cam shaft 653 moves to the lowest position from the specified position, as shown in Fig. 2, the spring 661 extends to the lower part. In this way, since the clutch lever 630 is pulled by the spring 661 in a forward rotation manner, the pressing part 631 exerts pressing force onto the clutch body 610 positioned at the engaging position, so that the rack 611 is tightly engaged with the rack 514.

[0052] In addition, the position of the clutch body 610, at which the rack 611 is engaged with the rack 514, is called a second position below. In addition, the working state of the cam 652 when the cam shaft 653 is positioned at the lowest position is called a second working state below.

[0053] When the rack 611 is engaged with the rack 514, since rotation of the clutch body 610 relative to the bearing unit 500 in a circumferential direction is limited and the clutch body 610 becomes a non-rotation state, the gear carrier shaft 441 of the planetary gear mechanism 400, namely, the planetary gear carrier 440, becomes a state of being fixed in a non-rotation manner. Under such state, when the rotor 110 rotates, the wing shaft 200 rotates at a rotation speed that is equal to that of the rotor 110, and the stirring body 24 connected with the wing shaft 200 also rotates at a rotation speed that is equal to that of the rotor 110. The sun gear 410 in the planetary gear mechanism 400 rotates along with rotation of the wing shaft 200. As described above, since the planetary gear carrier 440 is in the state of being fixed, the first gears and the second gears of the planet gears 430 respectively rotate in the same direction and in the reverse direction with the sun gear 410, and the internal gear 420 and the sun gear 410 rotate in the same direction. Therefore, the drum shaft 300 fixed on the internal

gear 420 rotates in the same direction as the wing shaft 200 and at a rotation speed slower than that of the wing shaft 200, and the drum 22 fixed on the drum shaft 300 rotates at a rotation speed slower than that of the stirring body 24 and in the same direction as the stirring body 24. In other words, the stirring body 24 rotates at a rotation speed higher than that of the drum 22 in the same direction as the drum 22.

[0054] In another aspect, under a situation of switching the form of the driving unit 30 from the second-shaft driving form to the first-shaft driving form, as shown in Fig. 3, the cam 652 rotates through the torque motor 651 to enable the cam shaft 653 to be position at the highest part. When the cam 652 rotates, and the cam shaft 653 moves upward, firstly, the spring 661 is contracted. After the spring 661 restores to the natural length, the jointing rod 660 moves upward along with movement of the cam shaft 653, and the lower end part of the clutch lever 630 is pushed by the jointing rod 660 to move upward. The clutch lever 630 rotates backward by using the supporting shaft 641 as the center, and the pressing part 631 is separated from the flange part 612 of the clutch body 610. The clutch body 610 moves backward through the elasticity of the clutch spring 620, and the engaging flange part 613 of the clutch body 610 is engaged with the engaged recess 114 of the rotor 110.

[0055] In addition, the position of the clutch body 610, at which the engaging flange part 613 is engaged with the engaged recess 114, is called a first position below. In addition, the working state of the cam 652 when the cam shaft 653 is positioned at the highest part is called a first working state below.

[0056] When the engaging flange part 613 is engaged with the engaged recess 114, rotation relative to the rotor 110 toward a circumferential direction of the clutch body 610 is limited, and the clutch body 610 and the rotor 110 become a rotatable state. Under such state, the wing shaft 200 and the clutch body 610 rotate at a rotate speed that is equal to that of the rotor 110 when the rotor 110 rotates. At this moment, the sun gear 410 and the planetary gear carrier 440 rotate at a rotation speed that is equal to that of the rotor 110 in the planetary gear mechanism 400. Therefore, the internal gear 420 rotates at a rotation speed that is equal to that of the sun gear 410 and the planetary gear carrier 440, and the drum shaft 300 fixed on the internal gear 420 rotates at a rotation speed that is equal to that of the rotor 110. Namely, the wing shaft 200, the planetary gear mechanism 400 and the drum shaft 300 integrally rotate in the driving unit 30, so that the drum 22 and the stirring body 24 integrally rotate.

[0057] Fig. 7 is a block diagram illustrating the structure of the drum type washing machine 1.

[0058] In addition to the above structure, the drum type washing machine 1 is further provided with: a control part 701, a storage part 702, an operation part 703, a water level sensor 704, the motor driving part 705, a water-feeding driving part 706, a drainage driving part 707, a

clutch driving part 708 and a door locking apparatus 709.

[0059] The operation part 703 includes: a power button 703a, a start button 703b and a program selection button 703c. The power button 703a is a button configured to switch on and off a power supply of the drum type washing machine 1. The start button 703b is a button configured to start rotation. The mode selection button 703c is a button configured to select any running program from a plurality of running programs related to washing running. The operation part 703 outputs an input signal corresponding to the button operated by a user to the control part 701.

[0060] The water level sensor 704 detects a water level in the outer tank 20 and outputs a water level detection signal corresponding to the detected water level to the control part 701.

[0061] The motor driving part 705 supplies the driving current to the driving motor 100 according to a control signal from the control part 701. The motor driving part 705 is provided with a speed sensor for detecting rotation speed of the driving motor 100, an inverter circuit and the like, and adjusts the driving current to enable the driving motor 100 to rotate at a rotation speed set by the control part 701.

[0062] The water-feeding driving part 706 supplies the driving current to the water-feeding valve 51 according to the control signal from the control part 701. The drainage driving part 707 supplies the driving current to the drainage valve 40 according to the control signal from the control part 701.

[0063] The clutch driving apparatus 650 includes a first detection sensor 654 and a second detection sensor 655. The first detection sensor 654 and the second detection sensor 655 form a state detection part of the present invention. The first detection sensor 654 detects that the cam 652 becomes a first working state and outputs a detection signal to the control part 701. The second detection sensor 655 detects that the cam 652 becomes second working state and outputs a detection signal to the control part 701. The clutch driving part 708 supplies the driving current to the torque motor 651 according to the detection signals from the first detection sensor 654 and the second detection sensor 655 as well as the control signal output by the control part 701.

[0064] The door locking apparatus 709 locks and unlocks the door 12 according to the control signal from the control part 701.

[0065] The storage part 702 includes an EEPROM (Electrically Erasable Programmable Read-Only Memory), an RAM (Random Access Memory) and the like. A program used for executing the washing running in a variety of washing running programs is stored in the storage part 702. In addition, a variety of parameters and a variety of control marks used for executing the programs are stored in the storage part 702.

[0066] The control part 701 controls the motor driving part 705, the water-feeding driving part 706, the drainage driving part 707, the clutch driving part 708, the door lock-

ing apparatus 709 and the like according to the programs stored in the storage part 702 and based on various signals from the operation part 703, the water level sensor 704 and the like.

[0067] The drum type washing machine 1 carries out the washing running in the variety of washing running programs according to a selection operation of the user carried out by the program selection button 703c. A washing process, a middle dewatering process, a rinsing process and a final dewatering process are sequentially carried out in the washing running. In addition, sometimes, the middle dewatering process and the rinsing process can be carried out for more than two times according to the running program.

[0068] The driving form of the driving unit 30 is switched to the second-shaft driving form in the washing process and the rinsing process. Water is stored in the outer tank 20 at the specified water level lower than the lower edge of the throwing opening 11 to enable the washings in the drum 22 to be immersed into the water, and under such state, the driving motor 100 alternatively rotates in the forward direction and in the reverse direction. Therefore, the drum 22 and the stirring body 24 alternatively rotate in the forward direction and in the reverse direction in a state that rotation speed of the stirring body 24 is higher than that of the drum 22. At this moment, the drum 22 rotates at a rotation speed with the centrifugal force acted on the washings less than the gravity.

[0069] The washings in the drum 22 are lifted up and dropped down by the baffles and are thrown to the inner circumferential surface of the drum 22. Besides, at the rear part of the drum 22, the washings are in contact with the blades 24a of the rotating stirring body 24, and rubbed and stirred by the blades 24a. Therefore, the washings are washed or rinsed.

[0070] In the middle dewatering process and the final dewatering process, the driving form of the driving unit 30 is switched to the first-shaft driving form. The driving motor 100, namely, the drum 22 and the stirring body 24, rotates at a rotation speed with the centrifugal force acted on the washings in the drum 22 far more than the gravity. The washings are pressed on the inner circumferential surface through the action of the centrifugal force and are dewatered.

[0071] So, when switching is carried out from the second-shaft driving form to the first-shaft driving form, and the clutch body 610 is moved to the first position through the elasticity of the clutch spring 620, as shown in Fig. 8, sometimes, the concave-convex parts 613a and 114a are dislocated from each other toward rotation direction of the rotor 110, i.e. the driving motor 100. In addition, in Fig. 8, the clutch body 610 is expressed by a dot-and-dash line for the purpose of convenience.

[0072] Under a situation that the concave-convex parts 613a and 114a are dislocated from each other, the clutch body 610 does not move to the first position, and the engaging flange part 613 is not engaged with the engaged recess 114. Under such state, since rotation of

the driving motor 100 is accelerated more quickly under the situation that the driving motor 100 formally rotates for dewatering, a hidden danger exists that rotation of the driving motor 100 is still accelerated to a rotation speed used for dewatering under a state that the engaging flange part 613 cannot be engaged with the engaged recess 114. In this way, since rotation of the driving motor 100 is incorrectly transmitted to the drum shaft 300, a hidden danger of incorrect dewatering of the washings exists as the drum 22 incorrectly rotates.

[0073] Additionally, when switching is carried out from the first-shaft driving form to the second-shaft driving form, and the clutch body 610 is pushed by the clutch lever 630 to move to the second position, all teeth of the rack 611 and all teeth of the rack 514 are sometimes dislocated toward a circumferential direction of the clutch body 610. Under such situation, the clutch body 610 does not move to the second position, and the racks 611 and 514 cannot be engaged with each other. Therefore, in washing and rinsing, when the driving motor 100 formally rotates in a state that the racks 611 and 514 are not engaged with each other, a hidden danger of incorrect washing and rinsing of the washings exists as the drum 22 incorrectly rotates.

[0074] Therefore, in the implementation manner, the control part 701 executes first-shaft switching treatment used for carrying out switching from the second-shaft driving form to the first-shaft driving form in good precision and executes second-shaft switching treatment used for carrying out switching from the first-shaft driving form to the second-shaft driving form in good precision. The first-shaft switching treatment and the second-shaft switching treatment are described in detail below.

[0075] Fig. 9 is a flow chart illustrating the first-shaft switching treatment.

[0076] Before the first-shaft switching treatment is started, the driving form of the driving unit 30 is the second-shaft driving form, and the cam 652 of the clutch driving apparatus 650 is in the second working state.

[0077] The control part 701 enables the torque motor 651 to rotate (S101) when the first-shaft switching treatment is started. The control part 701 judges whether the detection signal is output by the first detection sensor 654 (S102). The control part 701 enables the torque motor 651 to stop (S103) when the detection signal is output by the first detection sensor 654 (S102: YES) in a way that the cam 652 rotates until the cam shaft 653 is positioned at the highest position. As described above, the clutch body 610 arrives at the first position under a situation that the concave-convex parts 613a and 114a are not dislocated from each other and the engaging flange part 613 is engaged with the engaged recess 114. In another aspect, the clutch body 610 does not arrive at the first position under a situation that the concave-convex parts 613a and 114a are dislocated from each other and the engaging flange part 613 is not engaged with the engaged recess 114.

[0078] When the torque motor 651 is stopped, the con-

trol part 701 sets rotation speed of the driving motor 100 as a specified pre-rotation speed and supplies driving current corresponding to the pre-rotation speed to the driving motor 100 to enable the driving motor 100 to pre-rotate (S104). The pre-rotation speed is set as rotation speed slower than that when the driving motor 100 is enabled to formally rotate under the first-shaft driving form, for example, rotation speed is about 20rpm-30rpm. Therefore, the driving current supplied to the driving motor 100 when in pre-rotation is less than that of the driving motor 100 when in formal rotation.

[0079] The rotor 110 of the driving motor 100 slowly rotates. Under a situation that the concave-convex parts 613a and 114a are dislocated from each other, when the engaged recess 114 rotates along with rotation of the rotor 110 until the concave-convex parts 613a and 114a are at the consistent position, the engaging flange part 613 is engaged with the engaged recess 114. The clutch body 610 arrives at the first position.

[0080] The control part 701 stops the driving motor 100 (S106) after the specified pre-rotation time (S105). The pre-rotation time is set as time that enables the rotor 110 of the driving motor 100 to rotate for many times from a half time through rotation at the pre-rotation speed. Since rotation angle of the rotor 110 of the driving motor 100 is larger than an angle R corresponding to an interval of the concave-convex part 114a of the engaged recess 114 shown in Fig. 8, even if dislocation of almost an interval is generated between the concave-convex part 613a of the engaging flange part 613 and the concave-convex part 114a of the engaged recess 114, the engaging flange part 613 is also engaged with the engaged recess 114.

[0081] So, the first-shaft switching treatment is ended. Then, the control part 701 enables the driving motor 100 to formally rotate. For example, under the situation of performing the dewatering process under the first-shaft driving form, the control part 701 supplies driving current corresponding to a rotation speed used for dewatering to the driving motor 100, so as to enable the driving motor 100 to rotate.

[0082] Fig. 10 is a flow chart illustrating the second-shaft switching treatment.

[0083] Before the second-shaft switching treatment is started, the driving form of the driving unit 30 is the first-shaft driving form, and the cam 652 of the clutch driving apparatus 650 is in the first working state.

[0084] The control part 701 enables the torque motor 651 to rotate (S201) when the second-shaft switching treatment is started. The control part 701 judges whether the detection signal is output by the second detection sensor 655 (S202). The control part 701 enables the torque motor 651 to stop (S203) when the detection signal is output by the second detection sensor 655 (S202: YES) in a way that the cam 652 rotates until the cam shaft 653 is positioned at the lowest position. As described above, the clutch body 610 arrives at the second position under a situation that the racks 611 and 514 are

engaged with each other. In another aspect, the clutch body 610 does not arrive at the second position under a situation that the racks 611 and 514 are dislocated from each other and are not engaged with each other.

5 **[0085]** When the torque motor 651 is stopped, the control part 701 sets rotation speed of the driving motor 100 as a specified pre-rotation speed and supplies driving current corresponding to the pre-rotation speed to the driving motor 100 to enable the driving motor 100 to pre-rotate (S204). The pre-rotation speed is set as rotation speed slower than that when the driving motor 100 is enabled to formally rotate according to the second-shaft driving form. Therefore, the driving current supplied to the driving motor 100 when in pre-rotation is less than that of the driving motor 100 when in formal rotation. The pre-rotation speed set according to the second-shaft switching treatment can not only be equal to that set according to the first-shaft switching treatment, but also be different from that set according to the first-shaft switching treatment.

10 **[0086]** The rotor 110 of the driving motor 100 slowly rotates. The wing shaft 200 rotates along with rotation of the rotor 110. Therefore, the planetary gears 430 rotate when the sun gear 410 rotates. Under a situation that the racks 611 and 514 are not engaged with each other, both the internal gear 420 and the planetary gear carrier 440 are in a rotation state; but since the internal gear 420 is connected with the drum 22 and the planetary gear carrier 440 is connected with the clutch body 610, a torque required by rotation is smaller, namely, the planetary gear carrier 440 rotates along with rotation of the planetary gears 430. The dislocated racks 611 and 514 are engaged with each other when the clutch body 610 rotates along with rotation of the planetary gear carrier 440. The clutch body 610 arrives at the first position.

15 **[0087]** The control part 701 stops the driving motor 100 (S206) after the specified pre-rotation time (S205). The pre-rotation time is set as time that enables the rotor 110 of the driving motor 100 to rotate for many times from a half time through rotation at the pre-rotation speed. The pre-rotation time of the second-shaft switching treatment can not only be equal to that of the first-shaft switching treatment, but also be different from that of the first-shaft switching treatment.

20 **[0088]** So, the second-shaft switching treatment is ended. Then, the control part 701 enables the driving motor 100 to formally rotate. For example, under the situation of performing the washing process according to the second-shaft driving form, the control part 701 supplies driving current corresponding to a rotation speed used for washing to the driving motor 100, so as to enable the driving motor 100 to rotate. Or, for example, under the situation of performing the rinsing process according to the second-shaft driving form, the control part 701 supplies driving current corresponding to a rotation speed used for rinsing to the driving motor 100, so as to enable the driving motor 100 to rotate.

<Effects of the implementation manner>

[0089] As described above, according to the described implementation manner, in order to realize switching from the second-shaft driving form to the first-shaft driving form, the first-shaft switching treatment is executed after the clutch mechanism part 600 is operated to move the clutch body 610 to the first position, and the first-shaft treatment enables the driving motor 100 to rotate to engage the unengaged engaging flange part 613 with the engaged recess 114. Therefore, when the clutch mechanism part 600 is operated to move the clutch body 610 to the first position, even if the dislocation between the engaging flange part 613 and the engaged recess 114 is generated, the dislocation can be eliminated, so that the engaging flange part 613 is engaged with the engaged recess 114. Therefore, since switching from the second-shaft driving form to the first-shaft driving form can be carried out in good precision, rotation of the drum 22 and the stirring body 24 is correctly carried out under the first-shaft driving form, so as to carry out correct dewatering.

[0090] Further, according to the implementation manner, since the machine is designed into the first-shaft switching treatment, the driving motor 100 is enabled to rotate through the driving current lower than that when the driving motor 100 rotates under the first-shaft driving form after the first-shaft switching treatment, thereby enabling the driving motor 100 to slowly rotate. Therefore, the engaging flange part 613 is easily engaged with the engaged recess 114, so as to improve switching precision.

[0091] Further, according to the implementation manner, in order to realize switching from the first-shaft driving form to the second-shaft driving form, the second-shaft switching treatment is executed after the clutch mechanism part 600 is operated to move the clutch body 610 to the second position, and the second-shaft switching treatment enables the driving motor 100 to rotate to engage the unengaged racks 611 and 514. Therefore, when the clutch mechanism part 600 is operated to move the clutch body 610 to the second position, even if the dislocation between the racks 611 and 514 is generated, the dislocation can be eliminated, so that the racks 611 and 514 are engaged with each other. Therefore, since switching from the first-shaft driving form to the second-shaft driving form can be carried out in good precision, rotation of the drum 22 and the stirring body 24 is correctly carried according to the second-shaft driving form, so as to carry out correct washing or rinsing.

[0092] Further, according to the implementation manner, since the machine is designed into the second-shaft switching treatment, the driving motor 100 rotates through the driving current lower than that when the driving motor 100 rotates according to the second-shaft driving form after the second-shaft switching treatment, thereby enabling the driving motor 100 to slowly rotate. Therefore, the racks 611 and 514 are easily engaged

with each other, so as to improve switching precision.

[0093] Further, according to the implementation manner, since the machine is designed to detect the working state of the cam 652 by the first detection sensor 654 and the second detection sensor 655, the position of the clutch body 610 is indirectly detected. Therefore, the driving form of the driving unit 30 can be switched with no need of the sensors for directly detecting the position of the clutch body 610 and the like.

<Change example>

[0094] Although the implementation manner of the present invention is described above, the present invention is not limited by the above implementation manner. In addition, various changes can also be made to the implementation manner of the present invention in addition to the above description.

[0095] For example, in the above implementation manner, the engaging flange part 613 is formed on the clutch body 610 and is taken as the first engaging part, and the engaged recess 114 is formed on the rotor 110 of the driving motor 100 and is taken as the first engaged part. But, as long as the clutch body 610 and the rotor 110 are engaged with each other, the clutch body 610 and the rotor 110 can be fixed in a circumferential direction, regardless of the structures of the first engaging part and the first engaged part. In addition, in the above implementation manner, the rack 611 is formed on the clutch body 610 and is taken as the second engaging part, and the rack 514 is formed on the bearing part 510 of the bearing unit 500 and is taken as the second engaged part. However, as long as the clutch body 610 and the bearing part 510 are engaged with each other, the clutch body 610 and the rotor 110 can be fixed in a circumferential direction through engagement, regardless of the structures of the second engaging part and the second engaged part.

[0096] Further, in the above implementation manner, for the first-shaft switching treatment and the second-shaft switching treatment, the driving motor 100 is stopped after the pre-rotation time. But, the pro-rotation may also be transferred to rotation used for dewatering and washing without stopping the driving motor 100 after the pre-rotation time.

[0097] Further, in the above implementation manner, the drum shaft 300 is fixed on the internal gear 420, and the planetary carrier shaft 441, i.e. the planetary gear carrier 440, is connected with the clutch body 610. Therefore, in the second-shaft driving form, when the wing shaft 200 rotates under a state that the planetary gear carrier 440 is fixed by the clutch body 610, the planetary gears 430 rotate around the own axis along with rotation of the sun gear 410, and the internal gear 420 rotates at a rotation speed slower than that of the sun gear 410. But, as shown in Fig. 11, a structure that the drum shaft 300 is fixed on the planetary gear carrier 440 may also be adopted. Under such situation, a shaft part 425, which

protrudes backward from the drum shaft 300, of a top end part 425a is arranged on the internal gear 420. Moreover, the clutch body 610 is connected with the shaft part 425. Namely, the clutch body 610 is connected with the internal gear 420 through the shaft part 425. Further, the planetary gears 430 are changed to only be provided with the first gear. In the second-shaft driving form, when the wing shaft 200 rotates under a state that the internal gear 420 is fixed by the clutch body 610, the planetary gears 430 rotate around the own axis and revolve along with rotation of the sun gear 410, and the planetary gear carrier 440 rotates at a rotation speed slower than that of the sun gear 410. Therefore, the drum shaft 300 fixed on the planetary gear carrier 440 rotates.

[0098] Further, since the space between the teeth of the racks 611 and 514 is small, compared with the situation of switching from the second-shaft driving form to the first-shaft driving form, the situation that the racks 611 and 514 are not engaged with each other is difficult to generate. Therefore, as long as the precision of engagement of the racks 611 and 514 is high, for the second-shaft switching treatment, the treatment from the step S204 to the step S206 used for enabling the driving motor 100 to pre-rotate may also be omitted.

[0099] Further, in the above implementation manner, the drum 22 rotates by using the inclination axis inclining relative to the horizontal direction as the center. But, the drum type washing machine 1 may also adopt a structure that the drum 22 rotates by using the horizontal axis as the center.

[0100] Further, although the drum type washing machine 1 of the above implementation manner does not have the drying function, the present invention can also be used for a drum type washing machine with the drying function, i.e. a drum type washing and drying machine.

[0101] Additionally, various changes can be appropriately made to the implementation manner of the present invention within the scope of the technological idea expressed within the scope of the claims.

Reference signs:

[0102] 10: housing; 20: outer tank; 22: drum; 24: stirring body (rotating body); 24a: blade (protruding part); 30: driving unit (driving part); 100: driving motor; 110: rotor; 114: engaged recess (first engaged part); 200: wing shaft (first rotation shaft); 300: drum shaft (second rotation shaft); 400: planetary gear mechanism; 410: sun gear; 420: internal gear; 430: planetary gear; 440: planetary gear carrier; 500: bearing unit; 510: bearing part; 514: rack (second engaged part); 600: clutch mechanism part; 610: clutch body; 611: rack (second engaging part); 613: engaging flange part (first engaging part); 650: clutch driving apparatus; 652: cam (working body); 654: first detection sensor (state detection part); 655: second detection sensor (state detection part); 701: control part.

Claims

1. A drum type washing machine, provided with:

5 an outer tank, configured in a housing;
a drum, configured in the outer tank and is capable of rotating by using a horizontal axis or an inclination axis inclining relative to a horizontal direction as a center;
10 a rotating body, configured at a rear part of the drum and provided, on a surface of the rotating body, with a protruding part in contact with washings;
a driving part, configured to enable the drum and the rotating body to rotate; and
15 a control part, configured to control working of the driving part, wherein the driving part comprises:

20 a driving motor;
a first rotation shaft, configured to transmit rotation of the driving motor to the rotating body;

25 a second rotation shaft, configured to transmit rotation of the driving motor to the drum; and

30 a clutch mechanism part, configured to switch a driving form of the driving part between a first-shaft driving form and a second-shaft driving form, wherein the first-shaft driving form is a form that enables the first rotation shaft and the second rotation shaft to integrally rotate at a same rotation speed, and the second-shaft driving form is a form that enables the first rotation shaft and the second rotation shaft to respectively rotate at different rotation speeds, wherein the clutch mechanism part comprises: a clutch body provided with a first engaging part, wherein

35 by moving the clutch body to a first position so as to engage the first engaging part at the first position with a first engaged part that rotates with rotation of the driving motor, the driving form is switched to the first-shaft driving form;

40 the control part executes first-shaft switching treatment to carry out switching from the second-shaft driving form to the first-shaft driving form, wherein the first-shaft switching treatment is treatment that enables the clutch mechanism part to work to move the clutch body to the first position and then enables the driving motor to rotate to engage the unengaged first engaging part and the first engaged part.

2. The drum type washing machine according to claim

1, wherein
 for the first-shaft switching treatment, the control part enables the driving motor to rotate with a driving current lower than a driving current enabling the driving motor to rotate under the first-shaft driving form after the first-shaft switching treatment.

3. The drum type washing machine according to claim 1 or 2, wherein
 the driving part further comprises a planetary gear mechanism, wherein the planetary gear mechanism is provided with: a sun gear which rotates along with rotation of the motor; an annular internal gear which surrounds the sun gear; a plurality of planetary gears which are arranged between the sun gear and the internal gear; and a planetary gear carrier which holds the planetary gears in a free rotation manner, wherein one of the planetary gear carrier and the internal gear is fixed on the second rotation shaft; the clutch body is provided with a second engaging part and is connected with the other one of the planetary gear carrier and the internal gear in a state of limiting rotation relative to the other one of the planetary gear carrier and the internal gear toward a circumferential direction and allowing movement along an axial direction of the second rotation shaft; by moving the clutch body to a second position so as to engage the second engaging part at the second position with a second engaged part that does not rotate along with rotation of the driving motor and become a non-rotation state for the other one of the planetary gear carrier and the internal gear, the driving form is switched to the second-shaft driving form; even if the clutch mechanism part works to enable the clutch body to move to the second position, the second engaging part is not engaged with the second engaged part, and at this moment, the other one of the planetary gear carrier and the internal gear rotates along with rotation of the driving motor, so that the clutch body rotates; and
 the control part executes second-shaft switching treatment to carry out switching from the second-shaft driving form to the first-shaft driving form, wherein the second-shaft switching treatment is treatment that enables the clutch mechanism part to work to move the clutch body to the second position and then enables the driving motor to rotate to engage the unengaged second engaging part with the second engaged part.

4. The drum type washing machine according to claim 3, wherein
 for the second-shaft switching treatment, the control part enables the driving motor to rotate with a driving current lower than a driving current enabling the driving motor to rotate under the second-shaft driving form after the second-shaft switching treatment.

5. The drum type washing machine according to claim 3 or 4, further comprising a clutch driving apparatus configured to enable the clutch body to move, wherein
 the clutch driving apparatus comprises:

a working body, capable of being transferred to a first working state enabling the clutch body to move to the first position and a second working state enabling the clutch body to move to the second position; and
 a state detection part, configured to detect a working state of the working body, wherein
 for the first-shaft switching treatment, the control part enables the clutch driving apparatus to work according to a detection result of the state detection part so as to enable the working body to be transferred to the first working state; and
 for the second-shaft switching treatment, the control part enables the clutch driving apparatus to work according to a detection result of the state detection part so as to enable the working body to be transferred to the second working state.




FIG.1




FIG. 2




FIG.3




FIG.4




FIG.5




FIG. 6




FIG.7




FIG. 8

First-shaft switching treatment




FIG.9

Second-shaft switching treatment




FIG.10




FIG.11

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2015/079426

5	A. CLASSIFICATION OF SUBJECT MATTER		
	D06F 23/02 (2006.01) i; D06F 23/06 (2006.01) i; D06F 37/40 (2006.01) i According to International Patent Classification (IPC) or to both national classification and IPC		
10	B. FIELDS SEARCHED		
	Minimum documentation searched (classification system followed by classification symbols) D06F		
15	Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
	Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) CNABS; VEN; CNKI: impeller, WASHING W MACHINE, WASHER, ROLLER, DRUM, CYLINDER, STIRRER, PULSATOR, AGITATOR, DRIVE, FORCE, CLUTCH, SWITCH		
20	C. DOCUMENTS CONSIDERED TO BE RELEVANT		
	Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
25	A	CN 1517473 A (LG ELECTRONICS INC.), 04 August 2004 (04.08.2004), description, page 6, line 10 to page 9, line 2, and figures 4 and 5	1-5
	A	CN 1888193 A (LG ELECTRONICS (TIANJIN) APPLIANCES CO., LTD.), 03 January 2007 (03.01.2007), the whole document	1-5
	A	CN 1453416 A (HAIER ELECTRONICS GROUP CO., LTD. et al.), 05 November 2003 (05.11.2003), the whole document	1-5
30	A	CN 2450240 Y (ZHANG, Xiangzhu), 26 September 2001 (26.09.2001), the whole document	1-5
35	<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
	* Special categories of cited documents:	“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	
40	“A” document defining the general state of the art which is not considered to be of particular relevance	“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	
	“E” earlier application or patent but published on or after the international filing date	“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	
45	“L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	“&” document member of the same patent family	
	“O” document referring to an oral disclosure, use, exhibition or other means		
	“P” document published prior to the international filing date but later than the priority date claimed		
50	Date of the actual completion of the international search 18 August 2015 (18.08.2015)	Date of mailing of the international search report 28 August 2015 (28.08.2015)	
55	Name and mailing address of the ISA/CN: State Intellectual Property Office of the P. R. China No. 6, Xitucheng Road, Jimenqiao Haidian District, Beijing 100088, China Facsimile No.: (86-10) 62019451	Authorized officer FU, Guixin Telephone No.: (86-10) 62084564	

Form PCT/ISA/210 (second sheet) (July 2009)

INTERNATIONAL SEARCH REPORT
 Information on patent family members

International application No.
PCT/CN2015/079426

5
10
15
20
25
30
35
40
45
50
55

Patent Documents referred in the Report	Publication Date	Patent Family	Publication Date
CN 1517473 A	04 August 2004	KR 20040065839 A	23 July 2004
		EP 1439255 A1	21 July 2004
		CN 1517473 B	18 April 2012
		US 2004139768 A1	22 July 2004
CN 1888193 A	03 January 2007	None	
CN 1453416 A	05 November 2003	None	
CN 2450240 Y	26 September 2001	None	

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 2013240577 A [0005]