

(19)



(11)

EP 3 176 294 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
07.06.2017 Bulletin 2017/23

(51) Int Cl.:
D01H 5/88 (2006.01)

(21) Application number: **16194717.1**

(22) Date of filing: **20.10.2016**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
MA MD

(72) Inventors:
• **SHODA, Yuichi**
Kyoto, 612-8686 (JP)
• **OKA, Masaki**
Kyoto, 612-8686 (JP)
• **MATSUI, Toshihiro**
Kyoto, 612-8686 (JP)

(30) Priority: **11.11.2015 JP 2015221340**

(74) Representative: **Weickmann & Weickmann**
PartmbB
Postfach 860 820
81635 München (DE)


(71) Applicant: **Murata Machinery, Ltd.**
Minami-ku
Kyoto-shi
Kyoto 601-8326 (JP)

(54) TENSOR, DRAFT DEVICE, AND SPINNING MACHINE

(57) A tensor (40) includes a main body section (50) extending in a rotation axis direction of a bottom roller (16a), and a supporting member (54b) arranged in the main body section (50) and adapted to support a bottom belt (18a) to set a first nip position (P2) of a fiber bundle (S) by a top belt (18b) arranged on a top roller (16b) and

the bottom belt (18a). The supporting member (54b) is arranged at a position where the first nip position (P2) is within a range of 11 mm or more and 22 mm or less from a second nip position (P1) of the fiber bundle (S) by the bottom roller (16a) and the top roller (16b).

FIG. 6

**EP 3 176 294 A1**

Description

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates to a tensor, a draft device, and a spinning machine.

2. Description of the Related Art

[0002] There is known a spinning machine including a draft device adapted to draft a fiber bundle, and a spinning device adapted to twist the drafted fiber bundle to produce a spun yarn. The draft device includes a plurality of pairs of rollers in a draft direction of the fiber bundle. An apron belt adapted to grip (nip) and draft the fiber bundle is stretched between a bottom roller of a pair of rollers and a tensor (tensor bar).

[0003] DE102005000990A describes a draft device including a tensor (belt bridge) in which five rotatable rollers are arranged. According to the tensor of DE102005000990A, friction between the tensor and the apron belt when the apron belt is rotated can be reduced.

[0004] In such a draft device, a gripping position (nip position) and a gripping force of the fiber bundle by the apron belt affect quality of the yarn. The fiber bundle has a different effective fiber length depending on its type. Thus, when the effective fiber length is short, for example, the fibers may be pulled following the fibers travelling ahead, the fibers may travel in a bent state with respect to the draft direction, and the like if the gripping position of the fiber bundle is not appropriately set, and hence the movement of the fibers may be difficult to control. Thus, the thickness of the fiber bundle may vary, and the yarn quality may be lowered.

BRIEF SUMMARY OF THE INVENTION

[0005] It is an object of the present invention to provide a tensor, a draft device, and a spinning machine that can improve yarn quality.

[0006] A tensor according to the present invention is a tensor which is provided in a draft device adapted to draft a fiber bundle by a pair of rollers including a bottom roller and a top roller, the tensor adapted to adjust a tension of a bottom belt, the bottom belt being stretched between the tensor and the bottom roller, the tensor including a main body section extending in a rotation axis direction of the bottom roller; and a supporting member arranged in the main body section and adapted to support the bottom belt to set a first nip position of the fiber bundle by a top belt arranged in the top roller and the bottom belt, wherein the supporting member is arranged at a position where a distance between the first nip position and a second nip position of the fiber bundle by the bottom roller and the top roller is within a range of 11 mm or more and 22 mm or less.

[0007] In such a tensor, the supporting member is arranged at a position where the distance between the first nip position and the second nip position is within a range of 11 mm or more and 22 mm or less. Thus, even if the fiber bundle of different effective fiber lengths is to be drafted, by setting the first nip position and the second nip position in the above range, the fiber bundle, even short fibers, for example, can be appropriately sandwiched, and the movement of the fibers can be suppressed. Therefore, variation and the like in the thickness of the fiber bundle can be suppressed from occurring. As a result, the yarn quality can be enhanced. In particular, since the distance between the first nip position and the second nip position is smaller than an average fiber length (25 mm or more) of cotton, it is effective for suppressing the movement of the cotton fibers.

[0008] A tensor according to another aspect of the present invention is a tensor which is provided in a draft device adapted to draft a fiber bundle by a pair of rollers including a bottom roller and a top roller, the tensor adapted to adjust a tension of a bottom belt, the bottom belt being stretched between the tensor and the bottom roller, the tensor including a main body section extending in a rotation axis direction of the bottom roller; and a supporting member arranged in the main body section and adapted to support the bottom belt to set a first nip position of the fiber bundle by a top belt arranged in the top roller and the bottom belt. The supporting member is arranged at a position where the distance between the first nip position and the second nip position of the fiber bundle by the bottom roller and the top roller is in a range equal to or larger than half the average fiber length of the fiber bundle to be drafted and smaller than the average fiber length.

[0009] According to such a tensor, not only the fiber bundle of 100% cotton fibers and the fiber bundle in which the cotton fibers and the fibers other than the cotton fibers are mixed, but also, for example, the fiber bundle of 100% synthetic fibers cut to a predetermined length (e.g., 38 mm) and the fiber bundle of chemical fibers in which the average fiber length is intentionally cut to an uneven length may be appropriately sandwiched, and the yarn quality can be enhanced. There is a case where the synthetic fibers are intended to be aligned and cut to a predetermined length (e.g., 38 mm) but unintentionally became an uneven length, or a case where part of chemical fibers are bent at the time of drafting, but the fiber bundle can be appropriately sandwiched even in such cases and the yarn quality can be enhanced.

[0010] In one embodiment, the supporting member may be arranged such that the distance between the first nip position and the second nip position can be adjusted to be within a range of 11 mm or more and 22 mm or less (or within a range equal to or larger than half the average fiber length of the fiber bundle to be drafted and smaller than the average fiber length). Thus, the supporting member can be configured such that the distance between the first nip position and the second nip position

can be adjusted (changed) within a range of 11 mm or more and 22 mm or less (or within a range equal to or larger than half the average fiber length of the fiber bundle to be drafted and smaller than the average fiber length). Therefore, the first nip position can be changed according to the type of fiber bundle, and the movement of the fibers can be effectively controlled.

[0011] In one embodiment, the supporting member may be a roller that can rotate with the rotation axis extending in the same direction as the extending direction of the main body section as the center. According to the tensor having such a configuration, the friction between the tensor and the apron belt when the apron belt is rotated can be reduced.

[0012] In one embodiment, the tensor further includes a replacement member in which positioning portions adapted to detachably position the supporting member are arranged in one direction, wherein the main body section may detachably fix the replacement member so that the positioning portions are arranged along a draft direction of the fiber bundle. In this configuration, the first nip position can be changed by changing the positioning portion for attaching the supporting member. Furthermore, for example, the position of the supporting member in the arrangement direction can be easily changed by replacing with the replacement member, in which the positions of the positioning portions in the arrangement direction differ from each other. In other words, the first nip position can be easily adjusted.

[0013] A draft device according to the present invention includes a pair of rollers including a bottom roller and a top roller; the tensor described above; and an apron belt stretched across the bottom roller and the tensor.

[0014] In such a draft device, the movement of the fibers can be controlled and drafted even in the fiber bundle of different effective fiber lengths. Thus, the variation and the like in the thickness of the fiber bundle can be suppressed from occurring, and the yarn quality can be enhanced.

[0015] A spinning machine according to the present invention includes the draft device described above; a pneumatic spinning device adapted to twist the fiber bundle drafted by the draft device to produce a yarn; and a winding device adapted to wind the yarn produced by the pneumatic spinning device into a package.

[0016] In such a spinning machine, the movement of the fibers can be controlled and drafted in the draft device even in the fiber bundle of different effective fiber lengths. Thus, the pneumatic spinning device produces a yarn with the fiber bundle without variation and the like in the thickness, whereby the yarn of high quality can be produced.

[0017] According to the present invention, the yarn quality is enhanced.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018]

FIG. 1 is a front view illustrating a spinning machine including a draft device according to one embodiment;

FIG. 2 is a side view illustrating a spinning unit of the spinning machine of FIG. 1;

FIG. 3 is a plan view illustrating the draft device of the spinning unit of FIG. 2;

FIG. 4 is a side view illustrating the draft device of the spinning unit of FIG. 2;

FIG. 5 is a perspective view illustrating a pair of middle rollers;

FIG. 6 is a cross-sectional view illustrating the pair of middle rollers;

FIG. 7 is a perspective view illustrating a tensor;

FIG. 8 is a perspective view illustrating the tensor where illustration of the roller is omitted;

FIG. 9 is an exploded perspective view of a main body and a supporting body illustrated in FIG. 8;

FIG. 10 is an exploded perspective view illustrating a supporting body in which positions of bearings are different;

FIG. 11 is a perspective view illustrating a tensor in which the roller is arranged on the supporting body of FIG. 10;

FIG. 12 is a perspective view illustrating a tensor according to another embodiment;

FIG. 13 is a cross-sectional view taken along line a-a in FIG. 12; and

FIG. 14 is a perspective view illustrating a tensor according to another embodiment.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0019] Preferred embodiments of the present invention will be hereinafter described in detail with reference to the accompanying drawings. The same or corresponding components are denoted with the same reference numerals in the description of the drawings, and the redundant description will be omitted.

[0020] As illustrated in FIG. 1, a spinning machine 1 includes a plurality of spinning units 2, a yarn joining cart 3, a doffing cart (not illustrated), a first end frame 4, and a second end frame 5. The plurality of the spinning units 2 are arranged in a row. Each of the spinning units 2 is adapted to produce a yarn Y and to wind the yarn Y into a package P. The yarn joining cart 3 is adapted to perform a yarn joining operation in a spinning unit 2 after the yarn Y is cut, or is broken for some reason in such a spinning unit 2. The doffing cart is adapted to doff the package P and to supply a new bobbin B to the spinning unit 2 when the package P is fully-wound in a spinning unit 2.

[0021] The first end frame 4 accommodates, for example, a collecting device adapted to collect a fiber waste, a yarn waste, and the like generated in the spinning units 2. The second end frame 5 accommodates an air supplying section adapted to adjust air pressure of compressed air (air) to be supplied to the spinning machine

1 and to supply the air to each section of the spinning machine 1, a drive motor adapted to supply power to each section of the spinning unit 2, and the like. The second end frame 5 is provided with a machine control device 100, a display screen 102, and input keys 104. The machine control device 100 is adapted to intensively manage and control each section of the spinning machine 1. The display screen 102 is capable of displaying information relating to set contents and/or status of the spinning units 2, or the like. An operator can perform an appropriate operation using the input keys 104 to carry out a setting operation of the spinning units 2. The display screen 102 may be a touch panel display, and the touch panel display may be operated instead of the input keys 104.

[0022] As illustrated in FIGS. 1 and 2, each spinning unit 2 includes a draft device 6, a pneumatic spinning device 7, a yarn monitoring device 8, a tension sensor 9, a yarn storage device 11, a waxing device 12, and a winding device 13 in this order from upstream in a travelling direction of the yarn Y. A unit controller 10 is provided for every predetermined number of spinning units 2 and is adapted to control operations of the spinning units 2.

[0023] The draft device 6 is adapted to draft a sliver (fiber bundle) S. The draft device 6 includes a pair of back rollers 14, a pair of third rollers 15, a pair of middle rollers 16, and a pair of front rollers 17 in this order from upstream in a travelling direction of the sliver S. Each pair of rollers 14, 15, 16, and 17 includes a bottom roller and a top roller. The bottom roller is rotationally driven by a drive motor provided in the second end frame 5 or by a drive motor provided in each spinning unit 2. An apron belt (bottom belt) 18a is provided with respect to the bottom roller of the middle rollers 16. An apron belt (top belt) 18b is provided with respect to the top roller of the middle rollers 16.

[0024] The pneumatic spinning device 7 is adapted to produce the yarn Y by twisting a fiber bundle F, which has been drafted by the draft device 6, with a whirling airflow. More specifically (however, not illustrated), the pneumatic spinning device 7 includes a spinning chamber, a fiber guiding section, a whirling airflow generating nozzle, and a hollow guide shaft body. The fiber guiding section is adapted to guide the fiber bundle F supplied from the upstream draft device 6 into the spinning chamber. The whirling airflow generating nozzle is arranged at a periphery of a path where the fiber bundle F travels. A whirling airflow is generated in the spinning chamber by injecting air from the whirling airflow generating nozzle. With the whirling airflow, each fiber end of a plurality of fibers that form the fiber bundle F is reversed and whirled. The hollow guide shaft body is adapted to guide the yarn Y from the spinning chamber to an outside of the pneumatic spinning device 7.

[0025] The yarn monitoring device 8 is adapted to monitor information on the travelling yarn Y between the pneumatic spinning device 7 and the yarn storage device 11,

and to detect presence or absence of a yarn defect based on the information acquired by the monitoring. When detecting the yarn defect, the yarn monitoring device 8 transmits a yarn defect detection signal to a unit controller 10. The yarn monitoring device 8 detects a thickness abnormality of the yarn Y and/or a foreign substance included in the yarn Y, for example, as the yarn defect. The yarn monitoring device 8 also detects a yarn breakage or the like. The tension sensor 9 is adapted to measure tension of the travelling yarn Y between the pneumatic spinning device 7 and the yarn storage device 11, and to transmit a tension measurement signal to the unit controller 10. When the unit controller 10 determines presence of an abnormality based on a detection result of the yarn monitoring device 8 and/or the tension sensor 9, the yarn Y is cut in the spinning unit 2. Specifically, by stopping air supply to the pneumatic spinning device 7 to interrupt the production of the yarn Y, the yarn Y is cut. Alternatively, the yarn Y may be cut with a separately provided cutter.

[0026] The waxing device 12 is adapted to apply wax to the yarn Y between the yarn storage device 11 and the winding device 13.

[0027] The yarn storage device 11 is adapted to eliminate a slack of the yarn Y between the pneumatic spinning device 7 and the winding device 13. The yarn storage device 11 has a function of stably pulling out the yarn Y from the pneumatic spinning device 7, a function of preventing the yarn Y from slackening by accumulating the yarn Y fed from the pneumatic spinning device 7 at the time of the yarn joining operation or the like by the yarn joining cart 3, and a function of preventing variation in the tension of the yarn Y at downstream of the yarn storage device 11 from being propagated to the pneumatic spinning device 7.

[0028] The winding device 13 is adapted to wind the yarn Y around a bobbin B to form a package P. The winding device 13 includes a cradle arm 21, a winding drum 22, and a traverse guide 23. The cradle arm 21 is adapted to rotatably support the bobbin B. The cradle arm 21 is swingably supported by a support shaft 24 and is adapted to bring a surface of the bobbin B or a surface of the package P into contact with a surface of the winding drum 22 under appropriate pressure. A drive motor (not illustrated) provided in the second end frame 5 is adapted to simultaneously drive the winding drums 22 each provided in the plurality of the spinning units 2. Accordingly, in each spinning unit 2, the bobbin B or the package P is rotated in a winding direction. The traverse guide 23 of each spinning unit 2 is provided on a shaft 25 shared by the plurality of the spinning units 2. By the drive motor in the second end frame 5 driving the shaft 25 to reciprocate in a direction of a rotational axis of the winding drum 22, the traverse guide 23 traverses the yarn Y in a predetermined width with respect to the rotating bobbin B or package P.

[0029] After the yarn Y is cut, or is broken for some reason in a spinning unit 2, the yarn joining cart 3 travels

to such a spinning unit 2 to perform the yarn joining operation. The yarn joining cart 3 includes a yarn joining device 26, a suction pipe 27, and a suction mouth 28. The suction pipe 27 is swingably supported by a support shaft 31, and is adapted to catch the yarn Y from the pneumatic spinning device 7 and to guide the caught yarn Y to the yarn joining device 26. The suction mouth 28 is swingably supported by a support shaft 32, and is adapted to catch the yarn Y from the winding device 13 and to guide the caught yarn Y to the yarn joining device 26. The yarn joining device 26 is adapted to join the guided yarns Y together. The yarn joining device 26 is a splicer using the compressed air, a knotter adapted to join the yarns Y together in a mechanical manner, or the like.

[0030] When the yarn joining cart 3 performs the yarn joining operation, the package P is rotated in an unwinding direction (reversely rotated). At this time, the cradle arm 21 is moved by an air cylinder (not illustrated) such that the package P is located away from the winding drum 22, and the package P is reversely rotated by a reversely-rotating roller (not illustrated) provided in the yarn joining cart 3.

[0031] The draft device 6 described above will be more specifically described.

[0032] As illustrated in FIGS. 3 and 4, the pair of back rollers 14 includes a back bottom roller 14a and a back top roller 14b facing each other with a travelling path R, where the sliver S travels, therebetween. The pair of third rollers 15 includes a third bottom roller 15a and a third top roller 15b facing each other with the travelling path R therebetween. The pair of middle rollers 16 includes a middle bottom roller 16a and a middle top roller 16b facing each other with the travelling path R therebetween. The pair of front rollers 17 includes a front bottom roller 17a and a front top roller 17b facing each other with the travelling path R therebetween. Each of the plurality of pairs of rollers 14, 15, 16, 17 feeds the sliver S supplied from a can (not illustrated) and guided by a fiber bundle guide 77 from the upstream toward the downstream while drafting.

[0033] The back bottom roller 14a is rotatably supported by a back roller housing 66. The third bottom roller 15a is rotatably supported by a third roller housing 67. The middle bottom roller 16a is rotatably supported by a middle roller housing 68. The front bottom roller 17a is rotatably supported by a front roller housing 69. Each of the bottom rollers 14a, 15a, 16a, 17a is rotated at a rotation speed different from each other so as to be faster toward the downstream by the power from the second end frame 5. At least part of or all of the bottom rollers 14a, 15a, 16a, 17a may be rotated by the drive motor provided in each spinning unit 2.

[0034] The back top roller 14b, the third top roller 15b, the middle top roller 16b, and the front top roller 17b are rotatably supported by a draft cradle 71. Each top roller 14b, 15b, 16b, 17b is brought into contact with each bottom roller 14a, 15a, 16a, 17a at a predetermined pressure to be driven and rotated.

[0035] The draft cradle 71 can be swung with a support shaft 72 as a center to a position where each top roller 14b, 15b, 16b, 17b is brought into contact with each bottom roller 14a, 15a, 16a, 17a at a predetermined pressure, and a position where each top roller 14b, 15b, 16b, 17b is separated from each bottom roller 14a, 15a, 16a, 17a. The draft cradle 71 is swung using a handle (not illustrated) provided in the draft cradle 71. The draft cradle 71 rotatably supports each top roller 14b, 15b, 16b, 17b of the draft devices 6 arranged in each of the pair of adjacent spinning units 2. That is, the draft cradle 71 is shared by the draft devices 6 arranged in each of the pair of adjacent spinning units 2.

[0036] A regulating section 74 referred to as a sliver guide or a capacitor, for example, is arranged between the pair of third rollers 15 and the pair of middle rollers 16. A through-hole 74a, through which the sliver S is passed, is formed in the regulating section 74. The width of the sliver S in a direction (hereinafter referred to as "rotation axis direction") in which the rotation axis of each roller 14a, 14b, 15a, 15b, 16a, 16b, 17a, 17b extends is regulated to the width of the through-hole 74a in the rotation axis direction. Thus, the regulating section 74 regulates the path, where the sliver S travels, on the travelling path R, and regulates the width of the sliver S in the rotation axis direction to the width of the through-hole 74a in the rotation axis direction. The regulating section 74 is supported by a supporting section 75. The supporting section 75 is located on a lower side of the travelling path R in a machine height direction, and is attached to a middle roller housing 68 adapted to rotatably support the middle bottom roller 16a. The position of the regulating section 74 with respect to the pair of middle rollers 16 is thereby fixed. In FIGS. 1 and 2, the regulating section 74 and the supporting section 75 are omitted.

[0037] As illustrated in FIGS. 5 and 6, the apron belt 18a is stretched across the middle bottom roller 16a and a tensor 40. The apron belt 18a is driven by the rotation of the middle bottom roller 16a. The apron belt 18b is stretched across the middle top roller 16b and an apron tensioner 42. The apron tensioner 42 is supported by the draft cradle 71. The apron belt 18b is driven by the rotation of the top roller 16b that rotates accompanying the rotation of the middle bottom roller 16a.

[0038] In the pair of middle rollers 16, the apron belt 18a is pressed by the tensor 40 and the apron belt 18b is pressed by the apron tensioner 42, so that the sliver S is nipped (sandwiched) by the apron belt 18a and the apron belt 18b while pressure is applied.

[0039] Next, a description will be made in detail on the tensor 40. As illustrated in any of FIGS. 5 to 9, the tensor 40 includes a main body section 50, a supporting body (replacement member) 52, and rollers (supporting members) 54a, 54b, 54c, 54d.

[0040] The main body section 50 is a member that extends in one direction and that has a predetermined thickness. The main body section 50 is, for example, made of a material such as metal. As illustrated in FIG. 4, the

main body section 50 is arranged downstream (on the front bottom roller 17a side) of the middle bottom roller 16a in the travelling path R of the sliver S. As illustrated in FIG. 3, the main body section 50 is arranged to extend in the same direction as the extending direction (direction in which the spinning units 2 are arranged) of the bottom roller 16a. In other words, the main body section 50 is arranged to extend in the same direction as the direction in which the rotation axis of the bottom roller 16a extends. The main body section 50 is provided commonly for the draft devices 6 of the two adjacent spinning units 2. One main body section 50 may be provided for one spinning unit 2. The main body section 50 is supported by a supporting mechanism (not illustrated). As illustrated in FIG. 9, the main body section 50 includes a recess 51. The recess 51 is formed, for example, by partially cutting out the main body section 50 in the thickness direction.

[0041] The supporting body 52 rotatably supports the rollers 54a to 54d (see FIG. 6). The supporting body 52 is made of, for example, a material such as resin. As illustrated in FIG. 9, the supporting body 52 is detachably provided on the main body section 50. The supporting body 52 is arranged and held in the recess 51 of the main body section 50. The supporting body 52 is fixed to the main body section 50 with, for example, a fixture (not illustrated) such as a screw.

[0042] The supporting body 52 includes a main body portion 52a, a first end 52b, and a second end 52c. The main body portion 52a, the first end 52b, and the second end 52c are, for example, integrally molded. The main body portion 52a is a plate-shaped member presenting a substantially rectangular shape.

[0043] The first end 52b and the second end 52c are each arranged at an end in a longitudinal direction of the main body portion 52a, and are provided along a width direction of the main body portion 52a. The first end 52b and the second end 52c each project out from the surface of the main body portion 52a. In other words, the thicknesses of the first end 52b and the second end 52c are larger than the thickness of the main body portion 52a. Thus, the supporting body 52 presents a substantially recessed shape when seen from a direction along the surface of the main body portion 52a.

[0044] The first end 52b is provided with bearings (positioning portions) 56a, 56b, 56c, 56d. At the first end 52b, the bearings 56a to 56d are arranged in this order from one end toward the other end in the longitudinal direction of the first end 52b (width direction of the main body portion 52a). The second end 52c is provided with bearings (positioning portions) 58a, 58b, 58c, 58d. At the second end 52c, the bearings 58a to 58d are arranged in this order from one end toward the other end in the longitudinal direction of the second end 52c. The bearing 56a and the bearing 58a are arranged at positions facing each other with the main body portion 52a therebetween. Similarly, the bearing 56b and the bearing 58b, the bearing 56c and the bearing 58c, and the bearing 56d and the bearing 58d are respectively arranged at positions

facing each other with the main body portion 52a therebetween.

[0045] The bearings 56b, 56c and the bearings 58b, 58c are grooves formed in each of the first end 52b and the second end 52c. The bearings 56a, 56d and the bearings 58a, 58d are cutouts formed in each of the first end 52b and the second end 52c. A contacting surface with the rollers 54a to 54d in the bearings 56a to 56d and the bearings 58a to 58d presents a shape corresponding to the outer shape of the rollers 54a to 54d (curved shape in the present embodiment). The shape of each of the bearings 58a to 58d may be formed in a U-shape or a V-shape when seen in the axial direction.

[0046] The bearings 56a to 56d and the bearings 58a to 58d detachably support the rollers 54a to 54d. Specifically, the bearing 56a and the bearing 58a are provided with the roller 54a to rotatably support the roller 54a. The bearing 56b and the bearing 58b are provided with the roller 54b to rotatably support the roller 54b. The bearing 56c and the bearing 58c are provided with the roller 54c to rotatably support the roller 54c. The bearing 56d and the bearing 58d are provided with the roller 54d to rotatably support the roller 54d.

[0047] The rollers 54a to 54d are rotatably supported by the supporting body 52. The rollers 54a to 54d present a circular column shape. In the present embodiment, the cross-section of the rollers 54a to 54d presents a true circular shape, as illustrated in FIG. 6. The rollers 54a to 54d are, for example, made of a material having abrasion resistance. The rollers 54a to 54d may be in a mode in which a material having abrasion resistance is applied on the surface. The surface of the rollers 54a to 54d may be in a state (smooth state) without almost any bumps, or may be subjected to mirror-like finish, pearskin finish, grain finish, groove finish, or the like.

[0048] The diameters of the rollers 54a to 54d may be appropriately set according to design between, for example, 3 mm and 7 mm. In the present embodiment, the diameters of the roller 54b and the roller 54c are set to 3 mm. The diameters of the roller 54a and the roller 54d are set to 4 mm. The axial lengths (hereinafter simply referred to as "lengths") of the rollers 54a to 54d are appropriately set according to the width of the apron belt 18a within a range where the rigidity can be ensured. Specifically, the lengths of the rollers 54a to 54d merely need to be equal to or larger than the width of the apron belt 18a. That is, the lengths of the rollers 54a to 54d may be the same as the width of the apron belt 18a, or may be larger than the width of the apron belt 18a. In FIG. 5, a mode in which the lengths of the rollers 54a to 54d are larger than the width of the apron belt 18a is illustrated by way of example. An identifiable mark may be given to each of the rollers 54a to 54d and/or the supporting body 52. Examples of the mark include an engraved mark, a color coding, and a sticker.

[0049] As illustrated in FIGS. 7 and 8, the roller 54a has its ends supported by the bearing 56a and the bearing 58a. The roller 54b has its ends supported by the

bearing 56b and the bearing 58b. The roller 54c has its ends supported by the bearing 56c and the bearing 58c. The roller 54d has its ends supported by the bearing 56d and the bearing 58d. According to such a configuration, the rollers 54a to 54d are arranged in this order from the upstream toward the downstream in the draft direction in the present embodiment. Both ends of the rollers 54a to 54d make contact with the side surfaces of the recess 51 of the main body section 50. The axial movement of the rollers 54a to 54d is thereby restricted.

[0050] The rollers 54a to 54d in the width direction of the main body portion 52a may be arranged at equal intervals or at unequal intervals. In the present embodiment, the rollers 54a to 54d are arranged at an interval (gap) with each other along the width direction of the main body portion 52a, but may be arranged with almost no interval (with no gap).

[0051] The apron belt 18a is stretched across the bottom roller 16a and the tensor 40. Specifically, the apron belt 18a is stretched across the bottom roller 16a and the roller 54d of the tensor 40. The apron belt 18a is rotated accompanying the rotation of the bottom roller 16a rotated by the drive section (not illustrated). The upper part of each of the rollers 54a to 54d is pressed toward the lower side by the apron belt 18a. The vertical position of each of the rollers 54a to 54d is thereby restricted. The rollers 54a to 54d are rotated accompanying the rotation of the apron belt 18a.

[0052] As described above, the rollers 54a to 54d are detachably supported by the bearings 56a to 56d and the bearings 58a to 58d, and hence the supporting body 52 may be attached to the main body section 50 in a state where the roller 54c is removed from the bearing 56c and the bearing 58c, for example. The rollers 54a, 54b, 54c, 54d can be removed from the bearings 56a to 56d and the bearings 58a to 58d like the roller 54c. Thus, the nip position P2 (see FIG. 6) in the width direction (direction in which the rollers 54a to 54d are arranged) of the main body portion 52a can be adjusted. In the present embodiment, at least the roller 54b and the roller 54d need to be attached. The interval between the rollers 54a to 54d is appropriately set according to the type of the sliver S.

[0053] The method for adjusting the nip position P2 in the width direction of the main body section 50 is not limited to the method described above. For example, the supporting body 52 fixed to the main body section 50 may be replaced with a supporting body 152 as illustrated in FIG. 10. In the supporting body 152, the positions of the bearings 56a to 56d and the bearings 58a to 58d in the width direction of the main body section 50 are different from those in the supporting body 52. As illustrated in FIG. 11, the nip position P2 in the width direction of the main body section 50 can be adjusted by fixing the rollers 54a to 54d held by such a supporting body 152 to the main body section 50. An identifiable mark may be given to each of the rollers 54a to 54d and/or the supporting body 152. Examples of the mark include an engraved mark, a color coding, and a sticker.

[0054] Furthermore, the supporting body may be replaced with the supporting body 152 in which not only the positions of the bearings 56a to 56d and the bearings 58a to 58d in the width direction of the main body section 50 are different from those of the supporting body 52, but also the shapes of the bearings 56a to 56d and the bearings 58a to 58d are different. In such a case, in addition to adjustment of the nip position in the width direction of the main body section 50, replacement can also be made to rollers (supporting members) in which the projection amount from the supporting body 52, 152 differs from each other, or replacement can be made to rollers (supporting members) in which the contacting area with the apron belt 18a differ from each other. Thus, the nip force of the sliver S by the apron belt 18a can be easily adjusted.

[0055] As illustrated in FIG. 6, the roller 54b is arranged at a position where the distance D1 between the nip position (second nip position) P1 of the sliver S by the middle bottom roller 16a and the middle top roller 16b and the nip position (first nip position) P2 of the sliver S by the apron belt 18a and the apron belt 18b by the roller 54b is in a range of 11 mm or more and 22 mm or less. That is, the bearing 56b and the bearing 58b are arranged at positions to support the roller 54b where the distance D1 between the nip position P1 and the nip position P2 is in a range of 11 mm or more and 22 mm or less. In the present embodiment, the distance D1 is, for example, set between 16 mm and 17 mm.

[0056] The roller 54d is arranged at a position where a distance D2 between the nip position P1 and the end on the front bottom roller 17a side of the roller 54d is, for example, 35 mm. A linear distance between the nip position P1 and the nip position of the sliver S by the front bottom roller 17a and the front top roller 17b is, for example, 47 mm.

[0057] As illustrated in FIG. 6, a height position of the contacting point of the roller 54b and the apron belt 18a is higher than height positions of the contacting points of the other rollers 54a, 54c, 54d and the apron belt 18a. In other words, the roller 54b projects farther out toward the upper side than the rollers 54a, 54c, 54d. The contacting point of the roller 54b and the apron belt 18a is located above a line connecting the contacting point of the roller 54a and the apron belt 18a and the contacting point of the roller 54d and the apron belt 18a. The contacting point of the roller 54a and the apron belt 18a and the contacting point of the roller 54d and the apron belt 18a may be at the same height position, or may be at different height positions. The contacting point of the roller 54c and the apron belt 18a is located above the line connecting the contacting point of the roller 54a and the apron belt 18a and the contacting point of the roller 54d and the apron belt 18a, and located below the contacting point of the roller 54b and the apron belt 18a.

[0058] As described above, in the tensor 40 according to the present embodiment, the roller 54b is arranged at a position where the distance D1 of the nip position P1

of the sliver S by the middle bottom roller 16a and the middle top roller 16b and the nip position P2 of the sliver S by the apron belt 18a and the apron belt 18b by the roller 54b is in a range of 11 mm or more and 22 mm or less. In other words, the roller 54b is arranged such that the nip position P2 where the sliver S is stronger nipped than in other positions (position in the draft direction of the sliver S in the range where the apron belt 18a and the apron belt 18b makes contact) is set at a position located at a distance of 11 mm or more and 22 mm or less from the nip position P1. Thus, even if the sliver S of different effective fiber lengths is drafted, the movement of the fibers of the sliver S can be suppressed by setting the nip position P1 and the nip position P2 in the above range. Specifically, for example, the movement of the fibers can be suppressed even with the sliver S having an effective fiber length of 25 mm or less. Therefore, variation and the like in the thickness of the sliver S can be suppressed from occurring. As a result, the yarn quality can be enhanced. In particular, since the distance D1 is smaller than the average fiber length (25 mm or more) of cotton, it is effective for suppressing the movement of the cotton fibers.

[0059] In the present embodiment, the supporting member adapted to support the apron belt 18a corresponds to the rollers 54a to 54d that can rotate with the rotation axis extending in the same direction as the extending direction of the main body section 50 as the center. According to the tensor 40 having such a configuration, the friction between the tensor 40 and the apron belt 18a when the apron belt 18a is rotated can be reduced.

[0060] In the present embodiment, the tensor 40 includes the supporting body 52 in which the bearings 56a to 56d and the bearings 58a to 58d for detachably positioning the rollers 54a to 54d are arranged in one direction. The main body section 50 detachably fixes the supporting body 52 so as to arrange the bearings 56a to 56d and the bearings 58a to 58d along the draft direction of the sliver S. In this configuration, the nip position P2 can be changed by changing the bearings 56a to 56d and the bearings 58a to 58d for attaching the rollers 54a to 54d. Furthermore, for example, the positions of the rollers 54a to 54d in the arrangement direction can be easily changed by replacement with the supporting body 52 in which the positions of the bearings 56a to 56d and the bearings 58a to 58d in the arrangement direction differ from each other. In other words, the nip position P2 can be easily adjusted.

[0061] In the tensor 40 of the embodiment described above, the supporting body 52, 152 and/or the rollers 54a to 54d are appropriately replaced by the operator according to the yarn type. An identifiable mark is given to the supporting body 52, 152 and/or the rollers 54a to 54d. Thus, the operator can, for example, easily replace the supporting body and/or the rollers with the supporting body and/or the rollers adapted to the yarn type by looking at the instruction manual (table) and the like. Therefore, each of the rollers 54a to 54d can be easily and accurately

arranged in the supporting body 52, 152 according to the type of sliver S.

[0062] One embodiment of the present invention has been described above, but the present invention is not limited to the above embodiment.

[0063] In the embodiment described above, a mode in which the supporting member is a roller has been described by way of example. However, the supporting member is not limited to the roller. In summary, the supporting member may be any member as long as it has a configuration of supporting the apron belt 18a such that the nip position is set between the apron belt 18a and the apron belt 18b.

[0064] In the embodiment described above, a mode in which the roller 54b is arranged at a position where the distance D1 between the nip position P1 and the nip position P2 is in a range of 11 mm or more and 22 mm or less has been described by way of example. However, one of the rollers 54a to 54d merely needs to be arranged at a position where the distance D1 between the nip position P1 and the nip position P2 is in a range of 11 mm or more and 22 mm or less.

[0065] In the embodiment described above, a mode in which a plurality of rollers 54a to 54d is provided to the supporting body 52, 152 has been described by way of example, but at least one roller merely needs to be arranged. In summary, the roller (supporting member) merely needs to be arranged at a position where the distance D1 between the nip position P1 and the nip position P2 is in a range of 11 mm or more and 22 mm or less. The roller (supporting member) merely needs to be arranged at a position where the distance D1 between the nip position P1 and the nip position P2 is in a range equal to or larger than half the average fiber length of the fiber bundle to be drafted and smaller than the average fiber length.

[0066] In the embodiment described above, a mode in which the rollers 54a to 54d are detachably arranged on the supporting body 52, 152 has been described by way of example. However, the supporting member adapted to support the apron belt 18a may be fixed to the main body section 50. In other words, the supporting body may not be provided.

[0067] In the embodiment described above, an example in which the nip position in the width direction of the main body section 50 can be easily adjusted by adjusting the attachment/non-attachment of the rollers 54a to 54d with respect to the bearings 56a to 56d and the bearings 58a to 58d of the supporting body 52, 152 has been described, but the present invention is not limited thereto. For example, as illustrated in FIGS. 12 and 13, a stepped roller 59a to 59d in which diameters of shaft portions 59aa to 59da and diameters of roller portions supporting the apron belt 18a differ (may be large or small) may be removably and rotatably arranged with respect to the bearings 53a to 53d of the supporting body 153. Thus, even if the diameters of the shaft portions 59aa to 59da are the same with respect to each other, the rollers in which

the projection amount from the supporting body 153 differ from each other may be held, or the rollers in which the contacting area with the apron belt 18a differ from each other may be held by replacing the rollers with the stepped rollers in which the diameter of the roller portion differ from each other. Thus, the nip force of the sliver S by the apron belt 18a can be easily adjusted.

[0068] In the embodiment described above or the alternative embodiment described above, an example in which the rollers 54a to 54d are rotatably held with respect to the bearings 56a to 56d and the bearings 58a to 58d of the supporting body 52, 152 has been described, but a configuration in which the rollers 54a to 54d are held so as not to rotate may be adopted.

[0069] In the embodiment described above or the alternative embodiment described above, the roller that can rotate with the rotation axis as the center has been described as an example of the supporting member for supporting the apron belt 18a, but the present invention is not limited thereto. For example, a supporting member 154 in which only the portion to be brought into contact with the apron belt 18a is formed in a circular arc shape may be adopted, as illustrated in FIG. 14. A groove 154a may be formed at the portion to be brought into contact with the apron belt 18a. In such a case, the friction between the tensor 40 and the apron belt 18a when the apron belt 18a is rotated can be reduced.

[0070] In the embodiment described above, a mode in which the cross-section of the roller 54a to 54d presents a true circular shape has been described by way of example. However, the cross-section of the roller may present an elliptical shape.

[0071] In the embodiment described above, an example in which the rollers 54a to 54d are fixed to the supporting body 52, 152 by inserting the rollers 54a to 54d from the upper side with respect to the bearings 56a to 56d and the bearings 58a to 58d has been described, but the present invention is not limited thereto. For example, the bearings may be formed as circular hole portions, and the rollers 54a to 54d may be inserted while being sled in the axial direction with respect to the bearings to fix the rollers to the supporting body.

[0072] In the embodiment described above, a mode in which the rollers 54a to 54d serving as the supporting member are detachably arranged on the supporting body 52, and the rollers 54a to 54d having different diameters are arranged on the supporting body 52 to adjust the projection amount from the supporting body 53 has been described by way of example. However, a mode in which the supporting member is adjusted by the drive section may be adopted. Specifically, a drive section for vertically moving the supporting member may be arranged, and the supporting member may be vertically moved by operation of the drive section to adjust the projection amount of the supporting member from the supporting body. There may be adopted a mode in which a drive section for moving the supporting member along the draft direction in the supporting body may be arranged, and the

position in the draft direction of the supporting member is adjusted by operation of the drive section.

[0073] In the embodiment described above, a mode in which the contacting point of the roller 54b and the apron belt 18a is at a position higher than the contacting points of the other rollers 54a, 54c, 54d and the apron belt 18a has been described by way of example. However, the height positions of the contacting points of the rollers 54a to 54d and the apron belt 18a may be the same in the draft direction.

[0074] The spinning machine may be other than the spinning machine 1 including the pneumatic spinning device 7, and for example, may be a ring spinning machine.

Claims

1. A tensor (40) which is provided in a draft device (6) adapted to draft a fiber bundle (S) by a pair of rollers (16) including a bottom roller (16a) and a top roller (16b), the tensor (40) adapted to adjust a tension of a bottom belt (18a), the bottom belt (18a) being stretched between the tensor (40) and the bottom roller (16a), the tensor (40) comprising:

a main body section (50) extending in a rotation axis direction of the bottom roller (16a); and
a supporting member (54b) arranged in the main body section (50) and adapted to support the bottom belt (18a) to set a first nip position (P2) of the fiber bundle (S) by a top belt (18b) arranged in the top roller (16b) and the bottom belt (18a),

characterized in that the supporting member (54b) is arranged at a position where a distance (D1) between the first nip position (P2) and a second nip position (P1) of the fiber bundle (S) by the bottom roller (16a) and the top roller (16b) is within a range of 11 mm or more and 22 mm or less.

2. The tensor (40) according to claim 1, **characterized in that** the supporting member (54b) is set so that the distance (D1) between the first nip position (P2) and the second nip position (P1) is adjustable within the range of 11 mm or more and 22 mm or less.
3. The tensor (40) according to claim 1 or 2, **characterized in that** the supporting member (54b) is a roller which is rotatable with a rotation axis extending in a same direction as an extending direction of the main body section (50) as a center.
4. The tensor (40) according to any one of claims 1 to 3, further comprising a replacement member (52; 152) in which positioning portions (56a to 56d, 58a to 58d) adapted to detachably position the supporting member (54b) are arranged in one direction,

characterized in that the main body section (50) detachably fixes the replacement member (52; 152) so that the positioning portions (56a to 56d, 58a to 58d) are arranged along a draft direction of the fiber bundle (S).

5

5. A draft device (6) comprising:

a pair of rollers (16) including a bottom roller (16a) and a top roller (16b);
the tensor (40) according to any one of claims 1 to 4; and
an apron belt (18a) stretched across the bottom roller (16a) and the tensor (40).

10

15

6. A spinning machine (1) comprising:

the draft device (6) according to claim 5;
a pneumatic spinning device (7) adapted to twist the fiber bundle (S) drafted by the draft device (6) to produce a yarn (Y); and
a winding device (13) adapted to wind the yarn (Y) produced by the pneumatic spinning device (7) into a package (P).

20

25

30

35

40

45

50

55

THH




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13





FIG. 14





EUROPEAN SEARCH REPORT

 Application Number
 EP 16 19 4717

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	WO 2015/068005 A1 (RIETER AG MASCHF [CH]) 14 May 2015 (2015-05-14)	1,2	INV. D01H5/88
Y	* page 14, line 4 - page 15, line 1 * * figures 2,3,4 * * abstract *	3-6	
Y	FR 1 382 701 A (ZINSER TEXTILMASCHINEN GMBH) 18 December 1964 (1964-12-18) * column 1, line 1 - line 2 * * column 1, line 9 - line 14 * * column 2, line 11 - line 17 * * column 2, line 21 - line 23 * * column 2, line 28 - line 30 * * column 4, line 6 - line 20 * * figures 1-7 *	3-5	
Y,D	DE 10 2005 000990 A1 (SAURER GMBH & CO KG [DE]) 20 July 2006 (2006-07-20) * abstract *	6	
A	US 2 953 822 A (SCHILTKNECHT ADOLF DIPL ING [CH]) 27 September 1960 (1960-09-27) * claims 1-11; figures 1,2 *	1,5	TECHNICAL FIELDS SEARCHED (IPC)
A	WO 86/03793 A1 (PLATT SACO LOWELL CORP [US]) 3 July 1986 (1986-07-03) * abstract * * page 1, line 5 - line 8 * * page 1, line 19 - line 28 * * page 1, line 36 - page 2, line 6 * * page 4, line 17 - line 23 * * figures 2-4 *	1,5	D01H
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 13 April 2017	Examiner Humbert, Thomas
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 16 19 4717

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-04-2017

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2015068005 A1	14-05-2015	CH 708812 A1	15-05-2015
		CN 105683429 A	15-06-2016
		EP 3066241 A1	14-09-2016
		WO 2015068005 A1	14-05-2015
FR 1382701 A	18-12-1964	NONE	
DE 102005000990 A1	20-07-2006	NONE	
US 2953822 A	27-09-1960	CH 347746 A	15-07-1960
		DE 1033563 B	03-07-1958
		FR 1168392 A	08-12-1958
		GB 832603 A	13-04-1960
		US 2953822 A	27-09-1960
WO 8603793 A1	03-07-1986	DE 3573623 D1	16-11-1989
		EP 0205573 A1	30-12-1986
		ES 8603597 A1	16-04-1986
		US 4727626 A	01-03-1988
		WO 8603793 A1	03-07-1986

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- DE 102005000990 A [0003]