



(11)

EP 3 199 612 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
02.08.2017 Bulletin 2017/31

(51) Int Cl.:
C10M 135/30 ^(2006.01) **C10M 169/04** ^(2006.01)
C10M 177/00 ^(2006.01) **C10M 159/22** ^(2006.01)
C10N 10/04 ^(2006.01) **C10N 40/25** ^(2006.01)

(21) Application number: **16206178.2**

(22) Date of filing: **22.12.2016**

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**
Designated Extension States:
BA ME
Designated Validation States:
MA MD

(30) Priority: **26.01.2016 US 201615006219**
15.02.2016 EP 16155672

(71) Applicant: **Infineum International Limited**
Abingdon
Oxfordshire OX13 6BB (GB)

(72) Inventors:
• **Schwaebisch, Dirk**
Abingdon, Oxfordshire OX13 6BB (GB)
• **Musmacher, Jamie**
Linden, NJ New Jersey 07036 (US)
• **Cant, Alastair**
Abingdon, Oxfordshire OX13 6BB (GB)

(74) Representative: **Lewis, Pauline Therese et al**
PO Box 1
Milton Hill
Abingdon
Oxfordshire OX13 6BB (GB)

(54) **METAL DETERGENTS**

(57) Sulfurised calcium phenate detergents having a reduced unsulfurised alkyl-substituted phenol content are made by:

(A) providing, made from an unsulfurised alkyl-substituted phenol, a sulfurised calcium phenate detergent that, optionally, may have been further reacted with carbon dioxide;

(B) adding to the detergent from 1 to 100 mass % , based on the mass of the detergent, of an organic solvent that has a boiling point of above 100°C and below the boiling point of the unsulfurised alkyl-substituted phenol; and
(C) removing the organic solvent from the detergent thereby to reduce the unsulfurised alkyl-substituted phenol content.

EP 3 199 612 A1

Description**FIELD OF THE INVENTION**

5 **[0001]** This invention relates to a process for preparing sulfurized calcium phenate detergents having a reduced alkylphenol content.

BACKGROUND OF THE INVENTION

10 **[0002]** Sulfurized calcium alkyl phenate detergents are well-known additive components for internal combustion engine lubricating oil compositions (or lubricants). Unreacted alkylphenol used in their manufacture may be present in the detergents. Such alkylphenols have undesirable properties such as giving rise to corrosion, and certain alkylphenols (e.g. nonylphenol and tetrapropenylphenol) are classified as reproductive toxins.

15 **[0003]** The art describes ways of overcoming this problem, a recent example being US 8,772,209 B2 ('209), which describes protonating a phenate detergent with an acidic compound followed by removing unreacted alkylphenol and protonated unsulfurised salt such as by distillation. A problem with this approach is that acid salts (e.g. Ca stearate) that are formed are neutralised to release organic acid into the lubricant, such acid being detrimental to the engine.

20 **[0004]** WO 2015/153160 A1 ('160) describes preparing an overbased sulfurised alkaline earth metal alkylphenate composition in oil. The composition is heated and subjected to steam stripping followed by filtration. The resulting product is stated to exhibit an improved rate and efficiency of filtration, but further states, without exemplification, that the product may also have a reduced level of free monomeric alkylphenate or alkylphenol (e.g. tetrapropenyl phenol (TPP)) than materials prepared by conventional means without the steam-stripping step. WO 2015/153160 A1 makes no mention of solvent addition to the resulting product before carrying out the stripping step.

25 **[0005]** US 2014/0142015A describes a method for preparing a salt of a sulfurized alkyl-substituted hydroxyaromatic composition having a reduced content of unsulfurized alkyl-substituted hydroxyaromatic compound and its unsulfurized metal salt. The process involves the addition of an immiscible solvent such as a low molecular weight alcohol (e.g. methanol and ethanol), followed by extraction using a separatory funnel. The solvent needs to be immiscible with the sulfurized alkyl-substituted hydroxyaromatic composition so that separate layers form. One disadvantage of this process is that extra equipment is required in the manufacturing plant (i.e. equipment not previously used in phenate manufacturing plants) to carry out the separation. Also, a solvent not previously used in the manufacturing process needs to be available for use and needs to be stored in a separate storage tank. Furthermore, methanol and ethanol, as used in the specific examples in US 2014/0142015, are toxic solvents.

SUMMARY OF THE INVENTION

35 **[0006]** This invention overcomes the problem by adding to the detergent defined proportions of a solvent having a lower boiling point than the alkylphenol as an aid to distillation of the alkylphenol from the detergent without generating species detrimental to the engine.

40 **[0007]** Thus, in a first aspect, the invention provides a process for preparing sulfurised calcium phenate detergent having a reduced content of unsulfurised alkyl-substituted phenol comprising the steps of:

(A) providing, made from an unsulfurised alkyl-substituted phenol, a sulfurised calcium phenate detergent that, optionally, may have been further reacted with carbon dioxide;

45 (B) adding to the detergent from 1 to 100, preferably 5 to 40, more preferably 5 to 30, mass %, based on the mass of the detergent, of an organic solvent that has a boiling point of above 100°C and below the boiling point of the unsulfurised alkyl-substituted phenol; and

(C) distilling the organic solvent from the detergent thereby to reduce the content of the unsulfurised alkyl-substituted phenol.

50 **[0008]** In a second aspect, the invention provides a detergent obtained or obtainable by the process of the above first aspect.

[0009] In a third aspect, the invention provides a lubricating oil composition comprising an oil of lubricating viscosity in a major amount and a detergent of the second aspect of the invention in a minor amount.

55 **[0010]** The organic solvent is preferably miscible with the sulfurized calcium phenate detergent so that excessive mixing is not required.

[0011] One advantage of our invention is that distillation is normally used in phenate detergent manufacturing plants so the equipment is readily available. Another advantage of this invention is that solvents already used in the manufacture of sulfurized calcium phenate detergents can be used as the organic solvent having a boiling point about 100°C, such

as, for example, isodecanol.

[0012] The examples of the invention below demonstrate the surprising advantages thereof.

Definitions

[0013] In this specification, the following words and expressions, if and when used, have the meanings ascribed below:

"Active ingredients" or "(a.i.)" refers to additive material that is not diluent or solvent;

"comprising" or any cognate word specifies the presence of stated features, steps, or integers or components, but does not preclude the presence or addition of one or more other features, steps, integers, components or groups thereof; the expressions "consists of" or "consists essentially of" or cognates may be embraced within "comprises" or cognates, wherein "consists essentially of" permits inclusion of substances not materially affecting the characteristics of the composition to which it applies;

"major amount" means 50 mass % or more, preferably 60 mass % or more, more preferably 70 mass % or more, and most preferably 80 % or more, of a composition;

"minor amount" means less than 50 mass %, preferably less than 40 mass %, more preferably less than 30 mass % and most preferably less than 20 mass %, of a composition;

"TBN" means total base number as measured by ASTM D2896.

[0014] Furthermore in this specification, if and when used:

"calcium content" is as measured by ASTM D4951;

"phosphorus content" is as measured by ASTM D5185;

"sulphated ash content" is as measured by ASTM D874;

"sulphur content" is as measured by ASTM D2622;

"KV100" means kinematic viscosity at 100°C as measured by ASTM D445.

[0015] Also, it will be understood that various components used, essential as well as optimal and customary, may react under conditions of formulation, storage or use and that the invention also provides the product obtainable or obtained as a result of any such reaction.

[0016] Further, it is understood that any upper and lower quantity, range and ratio limits set forth herein may be independently combined.

DETAILED DESCRIPTION OF THE INVENTION

[0017] The features of the invention relating, where appropriate, to one or more aspects of the invention, will now be discussed in more detail below.

Step (A)

[0018] As examples of the phenate additives, there may be mentioned those of TBN in the range of 50 - 400. The alkyl groups may be those having 9-100, preferably 9-70, most preferably 9-50, carbon atoms.

[0019] As examples of alkylphenol starting materials, there may be mentioned those prepared via the alkylation of phenol with propylene-based alkenes; these may be characterized by branched-chain para-alkyl substitution where attachment of the chain to the benzene ring is via C-2 or C-3 carbon atoms. A notable example is tetrapropenylphenol ("TPP").

[0020] The art describes preparation of phenate detergents from alkylphenols. The phenates of this invention may, optionally, have been carbonated by reaction with carbon dioxide to give rise to overbased phenates. Specific examples are given in the EXAMPLES section of this specification.

Step (B)

[0021] Examples of organic solvents that may be used include alkanols and aromatic hydrocarbons. Isodecanol is preferred: it has a boiling point of 220°C, cf 313°C for TPP. It should be noted that the Ca phenate starting material may contain small amounts of organic solvent; amounts given in this specification are those added as in step (B).

Step (C)

[0022] All or most of the organic solvent is removed in step (C). Preferably, after step (B) and before step (C), a base oil is added; this cuts back the phenate before distillation rather than after and appears to give rise to a viscosity benefit.

[0023] Steps (B) and (C) may be carried out in a sequence of repeated steps, or carried out in single steps (one step (B) followed by one step (C) so that each of steps (B) and (C) is carried out once only).

[0024] If further reduction of the alkylphenol content is required, phenolic functional groups in the product in the product of step (C) may be oxyalkylated such as by reaction with ethylene carbonate, propylene carbonate or butylene carbonate, for example as described in EP-A-2682451.

Lubricating Oil Composition

[0025] This, as indicated above, is an aspect of the invention.

[0026] The oil of lubricating viscosity (sometimes referred to as base oil or lubricating oil) provides a major proportion of the composition and may be any oil suitable for lubricating an internal combustion engine.

[0027] It may range in viscosity from light distillate mineral oils to heavy lubricating oils. Generally, the viscosity of the oil ranges from 2 to 40 mm²/sec, as measured at 100°C.

[0028] Natural oils include animal oils and vegetable oils (e.g., castor oil, lard oil); liquid petroleum oils and hydrorefined, solvent-treated or acid-treated mineral oils of the paraffinic, naphthenic and mixed paraffinic-naphthenic types. Oils of lubricating viscosity derived from coal or shale also serve as useful base oils.

[0029] Synthetic lubricating oils include hydrocarbon oils and halo-substituted hydrocarbon oils such as polymerized and interpolymerized olefins (e.g., polybutylenes, polypropylenes, propylene-isobutylene copolymers, chlorinated polybutylenes, poly(1-hexenes), poly(1-octenes), poly(1-decenes)); alkylbenzenes (e.g., dodecylbenzenes, tetradecylbenzenes, dinonylbenzenes, di(2-ethylhexyl)benzenes); polyphenyls (e.g., biphenyls, terphenyls, alkylated polyphenols); and alkylated diphenyl ethers and alkylated diphenyl sulphides and derivative, analogues and homologues thereof.

[0030] Alkylene oxide polymers and interpolymers and derivatives thereof where the terminal hydroxyl groups have been modified by esterification, etherification, etc., constitute another class of known synthetic lubricating oils. These may be exemplified by polyoxyalkylene polymers prepared by polymerization of ethylene oxide or propylene oxide, and the alkyl and aryl ethers of polyoxyalkylene polymers (e.g., methyl-polyiso-propylene glycol ether having a molecular weight of 1000 or diphenyl ether of poly-ethylene glycol having a molecular weight of 1000 to 1500); and mono- and polycarboxylic esters thereof, for example, the acetic acid esters, mixed C3-C8 fatty acid esters and C 13 oxo acid diester of tetraethylene glycol.

[0031] Another suitable class of synthetic lubricating oils comprises the esters of dicarboxylic acids (e.g., phthalic acid, succinic acid, alkyl succinic acids and alkenyl succinic acids, maleic acid, azelaic acid, suberic acid, sebacic acid, fumaric acid, adipic acid, linoleic acid dimer, malonic acid, alkylmalonic acids, alkenyl malonic acids) with a variety of alcohols (e.g., butyl alcohol, hexyl alcohol, dodecyl alcohol, 2-ethylhexyl alcohol, ethylene glycol, diethylene glycol monoether, propylene glycol). Specific examples of such esters includes dibutyl adipate, di(2-ethylhexyl) sebacate, di-n-hexyl fumarate, dioctyl sebacate, diisooctyl azelate, diisodecyl azelate, dioctyl phthalate, didecyl phthalate, dieicosyl sebacate, the 2-ethylhexyl diester of linoleic acid dimer, and the complex ester formed by reacting one mole of sebacic acid with two moles of tetraethylene glycol and two moles of 2-ethylhexanoic acid.

[0032] Esters useful as synthetic oils also include those made from C5 to C12 monocarboxylic acids and polyols and polyol esters such as neopentyl glycol, trimethylolpropane, pentaerythritol, dipentaerythritol and tripentaerythritol.

[0033] Silicon-based oils such as the polyalkyl-, polyaryl-, polyalkoxy- or polyaryloxysilicone oils and silicate oils comprise another useful class of synthetic lubricants; such oils include tetraethyl silicate, tetraisopropyl silicate, tetra-(2-ethylhexyl)silicate, tetra-(4-methyl-2-ethylhexyl)silicate, tetra-(p-tert-butyl-phenyl) silicate, hexa-(4-methyl-2-ethylhexyl)disiloxane, poly(methyl)siloxanes and poly(methylphenyl)siloxanes. Other synthetic lubricating oils include liquid esters of phosphorus-containing acids (e.g., tricresyl phosphate, trioctyl phosphate, diethyl ester of decylphosphonic acid) and polymeric tetrahydrofurans.

[0034] Unrefined, refined and re-refined oils can be used in lubricants of the present invention. Unrefined oils are those obtained directly from a natural or synthetic source without further purification treatment. For example, a shale oil obtained directly from retorting operations; petroleum oil obtained directly from distillation; or ester oil obtained directly from esterification and used without further treatment, are unrefined oils. Refined oils are similar to unrefined oils except that the oil is further treated in one or more purification steps to improve one or more properties. Many such purification techniques, such as distillation, solvent extraction, acid or base extraction, filtration and percolation, are known to those skilled in the art. Re-refined oils are obtained by processes similar to those used to provide refined oils but begin with oil that has already been used in service. Such re-refined oils are also known as reclaimed or reprocessed oils and are often subjected to additional processing using techniques for removing spent additives and oil breakdown products.

[0035] The American Petroleum Institute (API) publication "Engine Oil Licensing and Certification System", Industry

Services Department, Fourteenth Edition, December 1996, Addendum 1, December 1998 categorizes groups of base stocks. As an example of an oil of lubricating viscosity that may be used in a lubricating oil composition of the present invention, there may be mentioned an oil containing 50 mass % or more of a basestock containing greater than or equal to 90 % saturates and less than or equal to 0.03% sulphur or a mixture thereof. Preferably, it contains 60, such as 70, 80 or 90, mass % or more of said basestock or a mixture thereof. The oil of lubricating viscosity may consist or substantially consist of said basestock or a mixture thereof.

[0036] Oil of lubricating viscosity may provide 50 mass % or more of the composition. Preferably, it provides 60, such as 70, 80 or 90, mass % or more of the composition.

[0037] The composition may comprise, in addition to the detergent additive of the invention, one or more additive components, different from the additive of the invention, selected from one or more ashless dispersants, detergents, corrosion inhibitors, antioxidants, pour point depressants, antiwear agents, friction modifiers, demulsifiers, antifoaming agents and viscosity modifiers.

Engines

[0038] The detergent additives of the invention may be used in lubricants for a range of internal combustion engines (spark-ignited or compression ignited) such as motor vehicle engines and marine engines. Of the latter, there may be mentioned two-stroke marine diesel cross-head engines and marine trunk piston engines.

EXAMPLES

[0039] The present invention is illustrated by but in no way limited to the following examples.

Example 1

(A) Ca Phenate Detergents

[0040] Two detergents were made, each from tetrapropenylphenol ('TPP'), one in a low TBN variant, and one in a high TBN variant. The following procedure was used:

- Tetrapropenylphenol, isodecanol (reaction solvent), ethylene glycol and an antifoam agent were charged to a reactor and heated to 50°C.
- This mixture was heated up to 90°C during which, elemental sulphur and calcium oxide were charged to the mixture.
- Once at 90°C, further ethylene glycol and base oil were charged as required and the temperature increased to 115°C.
- CO₂ addition was started at 115°C and added for between 6 and 8 hours as the temperature was raised to between 190 and 215°C.
- Once carbonation was complete, the reaction mixture was heated to, or held at, 210-215°C and vacuum applied to remove reaction solvents and water.

(B) The high TBN Ca phenate (500g) and isodecanol (IDA; 210.9g) were added to a reactor flask

(C) The product was subjected to the following heat-treatment regime

[0041]

Time (mins)	Temperature (°C)
30	ambient - 90
30	90-150
60	150-190
30	190-210

and then vacuum stripped at < 30 mbar for 40 mins, compressed air cooled over 15 minutes and cooled overnight to ambient temperature.

Reference Example

[0042] The high TBN Ca phenate (200g), without addition of IDA, was subject to an extensive sequence of heat treatment and vacuum distillation. Samples were taken after each of the first, second and third distillation treatments.

Results

	% TPP (mass%)	Viscosity (KV100; mm ² /s)
Ca phenate Starting material	14.6	265
Example 1	5.3	592
Reference Example	3.4	4590

[0043] The results show that Example 1 (of the invention) reduced the %TPP of the Ca phenate starting material and also gave rise to a considerably lower viscosity product than the reference example. The viscosity measurement for the Reference Example is an order of magnitude too high for it to be useable.

Example 2

[0044]

(A) The high TBN Ca phenate of Example 1 was used.

(B) and (C) IDA (10 mass %) was charged to the Ca phenate and the mixture subjected to the vacuum distillation treatment described in Example 1. The % TPP of the product was measured. The process step was repeated twice more, i.e. on each occasion, addition of 10 % IDA, vacuum distillation and % TPP measurements were carried out. Thus, % TPP measurements were obtained for 0, 10, 20 and 30 % IDA-charged products as set out below. They are the mass % content of C10, C11, C12+ alkylphenols determined by reverse phase high performance liquid chromatography (HPLC) using a UV detector.

Results

IDA charge (total; mass%)	% TPP (mass %)
0	14.66
10	8.46
20	7.12
30	5.65

[0045] The results show the benefits of multiple rounds of solvent addition and subsequent removal by distillation.

Claims

1. A process for preparing a sulfurised calcium phenate detergent having a reduced content of unsulfurised alkyl-substituted phenol comprising the steps of:

(A) providing, made from an unsulfurised alkyl-substituted phenol, a sulfurised calcium phenate detergent that, optionally, may have been further reacted with carbon dioxide;

(B) adding to the detergent from 1 to 100, preferably from 5 to 40, more preferably from 5 to 30, mass %, based on the mass of the detergent, of an organic solvent that has a boiling point of above 100°C and below the boiling point of the unsulfurised alkyl-substituted phenol; and

(C) distilling the solvent from the detergent thereby to reduce the content of the unsulfurised alkyl-substituted phenol.

2. The process of claim 1 where the organic solvent is miscible with the sulfurised calcium phenate detergent.

3. The process of claims 1 or 2 where the organic solvent is an alkanol or an aromatic solvent.
4. The process of claim 1 where the organic solvent is isodecanol.
- 5 5. The process of claim 1 where the alkylphenol is tetrapropenylphenol.
6. The process of claim 1 wherein, after step (B) and before step (C), base oil is added.
7. The process of claim 1 where steps (B) and (C) are carried out in a sequence of repeated steps.
- 10 8. The process of claim 1 where steps (B) and (C) are each carried out singly.
9. The process of claim 1 where phenolic functional groups in the product of step (C) are oxyalkylated.
- 15 10. The process of claim 9 where oxyalkylation is carried out by reaction with ethylene carbonate, propylene carbonate or butylene carbonate.
11. A sulfurised calcium phenate detergent obtained by the process of claim 1.
- 20 12. A lubricating oil composition comprising, or made by mixing, an oil of lubricating viscosity in a major amount and a detergent as claimed in claim 11.
13. The process of claim 1, wherein, in step (B), said organic solvent is added to said detergent in an amount of from 5 to 40 mass %, based on the mass of the detergent.
- 25 14. The process of claim 13, wherein said organic solvent is added to said detergent in an amount of from 5 to 30 mass %, based on the mass of the detergent.

30

35

40

45

50

55



EUROPEAN SEARCH REPORT

Application Number
EP 16 20 6178

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X,D	US 2014/142015 A1 (MAHIEUX CEDRICK [US] ET AL) 22 May 2014 (2014-05-22)	1-14	INV. C10M135/30
Y	* paragraphs [0003], [0010], [0016], [0017], [0058], [0077], [0079], [0081]; claims 1-5,15,18,19; examples; tables 1,2 *	1-14	C10M169/04 C10M177/00 C10M159/22
A,D	US 2014/142347 A1 (MAHIEUX CEDRICK [US] ET AL) 22 May 2014 (2014-05-22) * the whole document *	1-14	ADD. C10N10/04 C10N40/25
Y	EP 2 065 367 A1 (CHEVRON ORONITE CO [US]) 3 June 2009 (2009-06-03) * Comparative Example 1; paragraphs [0001], [0005]; claims; examples *	1-14	
			TECHNICAL FIELDS SEARCHED (IPC)
			C10M
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 24 January 2017	Examiner Renoth, Heinz
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 16 20 6178

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

24-01-2017

10

Patent document
cited in search report

Publication
date

Patent family
member(s)

Publication
date

15

US 2014142015 A1 22-05-2014 CA 2887233 A1 30-05-2014
CN 104736684 A 24-06-2015
EP 2922934 A1 30-09-2015
JP 2016503423 A 04-02-2016
KR 20150086242 A 27-07-2015
SG 11201502789S A 28-05-2015
US 2014142015 A1 22-05-2014
WO 2014081624 A1 30-05-2014

20

US 2014142347 A1 22-05-2014 CA 2886810 A1 30-05-2014
CN 104736509 A 24-06-2015
EP 2922812 A1 30-09-2015
JP 2015535009 A 07-12-2015
KR 20150084796 A 22-07-2015
SG 11201502785U A 28-05-2015
US 2014142347 A1 22-05-2014
WO 2014081538 A1 30-05-2014

25

EP 2065367 A1 03-06-2009 CA 2644252 A1 29-05-2009
EP 2065367 A1 03-06-2009
JP 5492404 B2 14-05-2014
JP 2009132719 A 18-06-2009
SG 153025 A1 29-06-2009
SG 172651 A1 28-07-2011
US 2009143264 A1 04-06-2009

30

35

40

45

50

55

ORM P0459

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 8772209 B2 [0003]
- WO 2015153160 A1 [0004]
- US 20140142015 A [0005]
- EP 2682451 A [0024]

Non-patent literature cited in the description

- Engine Oil Licensing and Certification System. Industry Services Department. The American Petroleum Institute (API), December 1996 [0035]