



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Abstract

(51) Int Cl.:
A61M 25/10 (2013.01) **A61M 25/00** (2006.01)
A61M 25/01 (2006.01)

(48) Corrigendum issued on:
11.10.2017 Bulletin 2017/41

(86) International application number:
PCT/JP2015/080334

(43) Date of publication:
06.09.2017 Bulletin 2017/36

(87) International publication number:
WO 2016/068167 (06.05.2016 Gazette 2016/18)

(21) Application number: **15855569.8**

(22) Date of filing: **28.10.2015**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
MA

- **MIYAKE Takamasa**
Seto-shi
Aichi 489-0976 (JP)
- **OGAWA Tomokazu**
Seto-shi
Aichi 489-0976 (JP)
- **OGAWA Keisuke**
Seto-shi
Aichi 489-0976 (JP)
- **FUJISAWA Soichiro**
Seto-shi
Aichi 489-0976 (JP)
- **OTA Mitsuhiro**
Seto-shi
Aichi 489-0976 (JP)

(30) Priority: **30.10.2014 JP 2014221134**

(71) Applicant: **Goodman Co., Ltd.**
Aichi 460-0008 (JP)

(72) Inventors:
• **IWANO Kenshi**
Seto-shi
Aichi 489-0976 (JP)

(74) Representative: **Epping - Hermann - Fischer**
Patentanwalts-gesellschaft mbH
Schloßschmidstraße 5
80639 München (DE)

(54) **BALLOON CATHETER**

(57) A balloon catheter is provided that is capable of suppressing warping of a balloon. A balloon catheter 10 is provided with an outer shaft 11, an inner shaft 12, and a balloon 14. The inner shaft 12 is inserted inside the outer shaft 11 and a part of the inner shaft 12 extends from a leading end of the outer shaft 12. The balloon 14 includes a base end side joint portion 21 and a leading end side joint portion 22. The base end side joint portion 21 is a portion joined to the outer shaft 11. The leading end side joint portion 22 is a portion joined to the inner shaft 12. The inner shaft 12 has an extension portion. The extension portion is configured to extend and retract in an axial line direction.

FIG. 2

