



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
20.12.2017 Bulletin 2017/51

(51) Int Cl.:
A61M 35/00 (2006.01)

(21) Application number: **17171599.8**

(22) Date of filing: **17.05.2017**

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**
Designated Extension States:
BA ME
Designated Validation States:
MA MD

(71) Applicant: **Taylor, John Richard**
Tyler, TX 75713 (US)

(72) Inventor: **Taylor, John Richard**
Tyler, TX 75713 (US)

(74) Representative: **Abraham, Richard et al**
Maguire Boss
24 East Street
St. Ives, Cambridgeshire PE27 5PD (GB)

(30) Priority: **17.06.2016 US 201662351830 P**
28.04.2017 US 201715581919

(54) **FACE SOAKING DEVICE**

(57) Face soaking devices (devices 100) and methods of use are described and disclosed. In some embodiments the device (100) may comprise a vessel (120) and a vessel neck gasket (500). The vessel (120) may be configured to hold a liquid to submerge a face of a user or a portion thereof. The vessel neck gasket (500) may be (removably) joined to the vessel (120). The vessel neck gasket (500) may be configured to comfortably accommodate a portion of the user's neck. In some embodiments, the device (100) may comprise a breathing apparatus (160) that may be in removable contact with: the vessel (120), with a head rest subassembly (140), and/or with the user. The breathing apparatus (160) may be configured to permit the user to breathe while the user's face may be submerged within the liquid. When the vessel (120) may be filled with the liquid to at least a sufficient level, the user may soak the face or the portion thereof, such that the skin being soaked receives a benefit.




FIG. 1

Description

PRIORITY NOTICE

[0001] The present application claims priority under 35 U.S.C. §119(e) to U.S. provisional patent application, application number 62/351,830 filed on June 17, 2016, the disclosure of which is incorporated herein by reference in its entirety.

[0002] The present patent application is a continuation-in-part (CIP) of U.S. non-provisional patent applications: application number 14/877,856 filed on October 7, 2015; and application number 14/964,552 filed on December 9, 2015; wherein this present patent application claims priority to both said U.S. non-provisional patent applications under 35 U.S.C. §120. The above-identified parent U.S. non-provisional patent applications are incorporated herein by reference in their entirety as if fully set forth below.

[0003] The present patent application is a continuation-in-part (CIP) of patent application, application number PCT/US15/54576, filed on October 7, 2015; wherein this present patent application claims priority to said PCT non-provisional patent application.

CROSS REFERENCE TO RELATED PATENT APPLICATIONS

[0004] The present application is related to presently pending filed patent application, application number PCT/US15/54576, filed on October 7, 2015; wherein said presently pending PCT patent application is incorporated by reference in its entirety.

TECHNICAL FIELD OF THE INVENTION

[0005] The present invention relates in general to skin soaking devices and more specifically to face soaking devices.

COPYRIGHT AND TRADEMARK NOTICE

[0006] A portion of the disclosure of this patent application may contain material that is subject to copyright protection. The owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyrights whatsoever.

[0007] Certain marks referenced herein may be common law or registered trademarks of third parties affiliated or unaffiliated with the applicant or the assignee. Use of these marks is by way of example and should not be construed as descriptive or to limit the scope of this invention to material associated only with such marks.

BACKGROUND OF THE INVENTION

[0008] The skin (epidermis) of humans (and of terrestrial vertebrates) may suffer from a number of problems, such as: acne; wrinkles, including age spots; infections; physical damage; various rashes, including pityriasis rosea, acne rosacea; and the like. Each of these skin problems may be briefly discussed below.

[0009] Acne may result from clogged skin pores, which may be visible as pustules or pimples - *i.e.*, what are commonly called blackheads and whiteheads. Such visible acne may be both visually unpleasant and painful. Severe acne may also result in scarring from the physical damage associated with ruptures of follicle walls, which may also form deep cysts under the skin. The clogged skin pores visible as acne may result from an overproduction of sebum oil, keratin, and/or metabolic byproducts of skin pore bacteria, as well as from the cells of skin pore bacteria. A common skin pore bacterium is *Propionibacterium acnes* (*P. acnes*).

[0010] Undesirable wrinkles on the skin may result from age, environmental factors, genetic factors, and repeated facial expressions. Age may be a factor in wrinkle formation because as skin ages, it may lose elasticity, in part due to accumulated gravitational pull over time and changes in connective tissues. Additionally with age, sebum production may slow (from the sebaceous glands), which may contribute to skin dryness with age, wherein such skin dryness may enhance visibility of wrinkles. Environmental factors may include sun and wind exposure as well as exposure to smoke, which over time may also contribute to wrinkles. Further, consistent facial expressions over time such as squinting, smiling, and even thinking can result in skin wrinkles. And in addition to wrinkles, age spots, such as liver spots and solar lentigines may also appear on the skin as the skin ages and is exposed to various environmental factors over time.

[0011] Additionally, various microorganisms, which may include bacteria, fungi, protozoans, and even some small invertebrates may infect skin, both on the surface and within the skin tissue, with varying levels of severity. For example, the mere presence of some such microorganisms, whether dead or alive, may act as an irritant, causing inflammation. Some microorganism metabolic byproducts may also act as irritants; whereas, some byproducts may actually be toxic. And some microorganisms may actually feed on the skin itself and/or the natural secretions of the skin, such as sebum. Such microorganisms may also infect open wounds on the skin and use such open wounds to gain entry to the body, and pose a larger bodily infectious threat.

[0012] Additionally, viruses may cause contagious, painful, and/or unpleasant looking lesions and blisters, *e.g.*, cold sores. Such lesions and blisters if ruptured may result in physical damage to the skin, as well as pain. Such viruses may include herpes and herpes like viruses.

[0013] With respect to physical damage to the skin, this may include: various wounds, cuts, abrasions, burns,

lesions, blisters, ruptures, and the like. Such physical damage to the skin may result in scarring as the skin heals and prior to healing may increase chances for various microorganism infection.

[0014] Such skin problems, particularly when occurring on the face, because of the inherent visibility to others of the face, may result in collateral detrimental effects, such as to one's psychological, social, and occupational wellbeing.

[0015] Pityriasis rosea may be a type of skin rash. Often, pityriasis rosea may begin with a single "herald patch" an oval red lesion of 2 to 10 centimeters (cm), followed in one or two weeks by a generalized body rash of many small (5 to 10 millimeter (mm)) patches of pink and/or red, flaky, oval shaped lesions, which often appear on the torso, but may also appear on the cheeks and/or at the hairline.

[0016] Acne rosacea or just rosacea may be a chronic skin rash condition characterized by facial erythema (redness) and sometimes pimples. Rosacea may affect all ages. Rosacea may typically begin as redness on the central face across the cheeks, nose, or forehead, but may also affect the neck, chest, ears, and/or scalp. In some cases, additional signs, such as semi-permanent redness, telangiectasia (dilation of superficial blood vessels on the face), red domed papules (small bumps) and pustules, red gritty eyes, burning and stinging sensations, and in some advanced cases, a red lobulated nose (rhinophyma), may be present.

[0017] The prior state of the art has responded to such problems with a diversity of technologies. For example, there may be a plethora of various topical ointments and creams for treating various skin problems. However, relevant here, may be the application of soaking the affected skin in an immersion liquid. Regardless of explanation, the prior state of art has shown a positive correlation with improvements to the above noted skin problems with soaking the skin in an appropriate immersion liquid. For example, such a treatment modality may be known in the art generally as hydrotherapy when the immersion liquid in question may be predominantly water. However, such hydrotherapy principles may be applied to other such immersion liquids, such as various oils, various paraffin waxes (typically heated), and oil water mixtures (emulsions). As used herein, hydrotherapy may be a means of treating various skin problems, by immersing the skin in a particular immersion liquid, wherein the immersion liquid may be predominantly water or some other liquid, such as an oil in liquid form at room temperature or an appropriate temperature, such as paraffin wax in liquid form when appropriately heated, or an oil and water mixture.

[0018] Such hydrotherapy may involve soaking a target region of skin within the immersion liquid. The immersion liquid may comprise various properties. For example, the immersion liquid may contain various dissolved salts, wherein such a liquid may be known herein as a saline solution. For example, the immersion liquid may

contain released oxygen, either as dissolved oxygen and/or as gas bubbles within the immersion liquid. For example, the immersion liquid may contain an increased or decreased temperature with respect to room temperature. And for example, the immersion liquid may be directed via one or more jets, such that a stream of liquid pressure may be directed at the target region of skin.

[0019] With respect to saline solutions as the immersion liquid, saline and salts as used herein may refer not only to solutions of sodium chloride, but may also refer to other minerals in solution, e.g. potassium and/or magnesium, that may be dissolved in a solvent, such as predominantly water. Various negative ions, such as chloride, may also be present in solution with the positive mineral ions. For example, sodium and potassium salt solutions may be present with chloride ions and magnesium may be present with sulfate ions, as in Epsom salt. An immersion liquid using various salts may promote different benefits. For example, some such saline solutions may soften the skin and/or others may tend to moisturize the soaked skin.

[0020] Benefits to the skin from soaking the skin in saline solutions may predominantly function by osmosis. Osmosis is a random movement of water molecules across partially-permeable membranes (such as cellular membranes, including skin cells), from an area of high water concentration (e.g. within a cell) to an area of low water concentration (e.g. the saline solution). Thus osmosis will function to draw water out of cells, including skin cells, when the saline solution has a salinity that is greater than the salinity within the cells. For example, human blood has an average salinity of about 0.85% by weight, which is often rounded to 0.9%. Thus if the saline solution that the skin may be soaking in is greater than 0.9% by weight, there will be osmotic flow of water molecules from the skin cells into the saline solution.

[0021] However, it is from this flow of water molecules across cell membranes that several benefits may result for treating and/or improving the various skin problems noted above.

[0022] For example, with respect to acne, skin with acne that is exposed to saline solutions may see a reduction in acne. Such reduction may result from the saline solution reducing sebum oil within pores, by the saline solution reducing the population of skin pore bacteria, and/or by the saline solution encouraging a reduction in skin pore size. The saline solution may help to loosen sebum oil from pores. With respect to skin pore bacteria, which may be adapted for non-saline environments, such bacteria may not be adapted to cope with the osmotic flow of water molecules out of the bacterial cells. Such saline solutions may hinder reproduction of such bacterial cells. Such saline solutions may actually kill such bacterial cells. With respect to the reduction in skin pore size, this may also result from osmotic flow of water molecules.

[0023] With respect to a reduction in wrinkles, the saline solution may reduce wrinkles by softening the wrinkled skin tissue and by stimulating the sebaceous glands

to produce sebum oil which may combat age associated skin dryness. For example, exposing a face to warm water may soften facial skin in preparation and aiding in shaving whiskers (stubble) from that face. Additionally, depending upon the salinity of the given saline solution, the saline solution may have a hydrating effect upon the immersed skin.

[0024] With respect to mitigating against microorganism infection of the skin, as noted above, those microorganisms which may be predominantly present on the skin are not typically adapted to withstand osmotic flow of water molecules from within the bacterial cells. Immersion of skin in such saline solutions may result in microorganism population reduction.

[0025] With respect to improving a rate of healing damaged skin, skin immersed into saline solutions may experience an improved rate of healing by reducing the populations of microorganisms which may interfere with healing. And the osmotic flow may also aid healing damaged skin by aiding transport of nutrients and repair proteins from within the cells and tissues below the surface skin to the damaged skin site.

[0026] Thus immersion of skin into a saline solution which may have a salinity greater than the skin tissue being immersed, may result in a plurality of benefits to the immersed skin.

[0027] Now turning to oxygen treatments for the skin and how oxygen may reduce some of the skin problems identified above. Again, regardless of explanation, the state of the prior art shows a positive correlation with exposing skin to oxygen and improvements in the skin.

[0028] Molecular oxygen (atmospheric oxygen), *i.e.* O₂, may be essential for cellular respiration and the basis for how each vertebrate cell derives energy via the Krebs Cycle (Citric Acid Cycle). Without a sufficient supply of consistent oxygen to any vertebrate cell, that cell may be hypoxic and may have a diminished capacity to operate normal cellular activities, including a diminished capacity to reproduce, to fight infection, and/or to heal. By providing oxygen in sufficient concentration directly to the skin, such exposed skin may obtain some of its needed oxygen directly, instead of relying largely upon delivery of oxygen via hemoglobin in red blood cells. Such skin cells having a steady available source of oxygen may allow such skin cells a full range of normal cellular activities. Additionally, immune system cells (*e.g.* macrophages and phagocytes) which target and kill infectious microorganisms better perform when such cells have an adequate supply of oxygen. And a second mechanism of oxygen reducing infectious microorganism population may be by oxygen's oxidation properties and ability to form reactive oxygen species that may then oxidize bacterial cellular machinery, such as interfering with bacterial cell walls.

[0029] Now oxygen may be applied to the skin in gaseous form and/or released as a dissolved gas and/or as gas bubbles within a liquid, including the immersion liquid. For example, atmospheric air will contain atmospheric oxygen, *e.g.* at approximately 20.95%. A delivered con-

centration of gaseous oxygen may be increased over the atmospheric percentage by using pure oxygen as a supply source. However, use of gaseous oxygen directed at skin may have the drawback of being difficult to control and manipulate due to the gasses' inherent ability to more freely and disperse. Whereas, release of oxygen in a liquid may provide for better control as the target area of skin may be immersed in the liquid, which then may have oxygen from air or pure oxygen released into the liquid.

[0030] The benefits of oxygen and saline solutions may be combined into the same immersion liquid. For example, air (which includes oxygen) and/or oxygen may be pumped or released into an appropriate saline solution. Additionally, such an oxygenated saline solution may be combined with the benefits of controlling a temperature of the oxygenated saline solution.

[0031] For example, increasing a temperature of the immersion liquid above room temperature but less than a temperature which may be harmful (*e.g.* painful), allows for an increase in chemical reactions (kinetics). Thus increasing the immersion liquids temperature in such a range will tend to increase the effectiveness of saline solutions as well as the effectiveness of oxygenation of the skin. Additionally, such increased temperature of the immersion liquid may result in an environment that may be soothing and relaxing to a user. Such a soothing and relaxing result may then release stress and mitigate against headaches. Release of stress may promote lowering of blood pressure, healing of damaged skin, and a stronger immune system. Thus, increasing the temperature of the immersion liquid not only may provide direct improvements to how the saline and the oxygen functions to improve the skin, but by creating the soothing and relaxing environment, a collateral benefit of stress release may be achieved, which may also then include a cascade of additional benefits.

[0032] Further, increasing the immersion liquids temperature above room temperature may then permit the immersion liquid to be used for heat therapy. Heat therapy may be used to treat not only skin problems, but also other ailments, such as, but not limited to, arthritis, osteoarthritis, fibromyalgia, joint stiffness, bursitis, tendonitis, sprains and pulled muscles. The heat and immersion liquid which may convey the heat, may increase blood flow, improve joint stiffness and reduce pain. For example, heated paraffin waxes as the immersion liquid may be utilized. Such heated paraffin wax may soften hardened skin caused by scleroderma, a disease in which collagen accumulates on the body.

[0033] In addition or alternatively, decreasing the immersion liquids temperature below room temperature may then permit the immersion liquid to be used for cold therapy. Chilling the liquid by use of a chiller, chilling equipment, and/or by introduction of ice, may then permit various cold therapies to be used to treat the face or other body part which may be removably immersed into the chilled liquid. Additionally or alternatively, heat therapy may be alternated with cold therapy; wherein such alter-

nation of warmth and cold may aid in increasing blood flow, facilitating removal of cellular toxins (e.g., but not limited to, lactic acid), and/or promoting healing of burned or traumatized tissue.

[0034] Additionally, liquid jets, for example water jets, when directed at the immersed skin may also result in an environment that is soothing and relaxing to the user. Such water jets also may have their benefit increased when the immersion temperature is increased as noted per above.

[0035] Light therapy may also be used to impart various benefits to the exposed skin and/or body in general. Light therapy may involve directing a source of light at skin. Some wavelengths of light have found to increase healing rates of damaged skin, such as including cuts, scrapes, bruising, lacerations, lesions, and the like. Light such as ultraviolet (UV) light may also be used for skin tanning purposes. However, both existing oxygen therapy and existing light therapy are conducted in a treatment environment of atmospheric air, i.e., not with an article to be treated (e.g. a region of skin) submerged within an immersion liquid.

[0036] Additionally, it may be desirable to expand beyond just oxygen, air, or air enriched with oxygen, as treatment gasses for skin.

[0037] Additionally, current light therapy devices generally are directed at emitting only a very narrow range of wavelengths, generally within the visible light spectrum, near infrared (IR), and near ultraviolet (UV). It would be desirable to have expanded devices that may be capable of emitting electromagnetic (EM) radiation in various wavelengths that may encompass regions of the entire EM spectrum, i.e. not necessarily a single device capable of emitting across the entire EM spectrum (since different technologies may be required to produce a given range of wavelengths), but rather a multitude of EM emitting devices where each different device may be capable of emitting a particular range of wavelengths, such that these different EM emitting devices may collectively be able to cover the entire EM spectrum.

[0038] Conducting oxygen therapy and/or light therapy or other EM therapy within the immersion liquid may be desirable for several reasons. Because the liquid is more dense than atmospheric air, more control over directing oxygen (or other gas) to a target region on the article (e.g., immersed skin region) may be achieved over conducting oxygen therapy in atmospheric air, where expelled oxygen quickly dissipates into the atmospheric air. By using the immersion liquid to removably submerge the target region of the article, useful properties of the liquid may be tailored for specific applications with respect to the target region of the article. For example, liquid water, such as saline solutions, may soften the skin and make such softened skin better able to benefit from exposure to oxygen and/or various wavelengths of light. The additives in the liquid may be used to heal, cleanse, rejuvenate, sanitize, sterilize, and the like. Likewise, controlling a temperature of the liquid may then be able to

impart heat or withdraw heat from the target region of the article in a much greater efficiency than may be possible where the treatment environment is atmospheric air and not the liquid. Additionally, controlling the temperature (up, down, or maintaining) of the liquid may increase or decrease the efficacy of the additives, e.g., from a kinetics perspective.

[0039] Furthermore, it has been discovered that conducting light therapy or other EM therapy may be enhanced when the EM radiation may be emitted through a plurality of bubbles within the immersion liquid, by providing an increased coverage of the target region of the article receiving EM radiation in comparison to if there were no bubbles. The emitted EM radiation and the bubbles produce an optical chain reaction (OCR) phenomena that provides this enhancement.

[0040] However, as noted above, with respect to such skin problems on the face, these problems are exacerbated because the high visibility of the face. Additionally, these skin problems on the face are exacerbated because the current state of the art does not provide a means by which the user may immerse the face to receive hydrotherapy, wherein the hydrotherapy immersion liquid may comprise saline solutions, delivery of oxygen (and/or other gasses), heating means for increasing and/or decreasing immersion liquid temperature, and/or use of liquid jets. The problem that the prior state of the art has failed to address, until this invention, results from two biological facts. One, terrestrial vertebrates breathe from their nose and/or mouth located on the face and thus a hydrotherapy means for the face needs to provide a means by which the user may breathe while the user's face is immersed. Otherwise immersion of the face is limited to how long the user can hold their breath. And two, all pre-existing vessels have no means to accommodate a neck region of the user, particularly the soft tissue regions of the neck (front and sides of the neck), so if the user were to submerge the user's face into a pre-existing vessel, a rim of that vessel would press into the neck region causing discomfort rendering the prior state of the art ineffective for hydrotherapy of the face. Or the user would have to angle their head into the prior art vessel and attempt to hold their head at an uncomfortable angle to soak their face, which if is prolonged may result in neck pain. Additionally, it may be desirable if such a device might, in at least some embodiments, comfortably support the head region of the user, particularly the forehead, to promote facial immersion that may be comfortable and not strain the neck; wherein the user may soak their face, in comfort, for extended periods of time.

[0041] There is a need in the art for devices and/or methods that permit treating specifically targeted regions of the articles (e.g., skin) to be removably submerged in the immersion liquid and then treated with various gas bubbles, such as oxygen, treated with various wavelengths of EM radiation, such as visible light, and/or providing for an enhanced EM radiation coverage of the

treated region by a synergistic combination of EM radiation and bubbles that may result from directing EM radiation through bubbles in the liquid.

[0042] There then is a need in the art for a device which may promote comfortable face immersion into the immersion liquid that both allows the user to breathe while the face is immersed and that may be comfortable to the neck of the user.

[0043] It is to these ends that the present invention has been developed.

BRIEF SUMMARY OF THE INVENTION

[0044] To minimize the limitations in the prior art, and to minimize other limitations that will be apparent upon reading and understanding the present specification, one or more embodiments of the present invention may describe a face soaking device.

[0045] Some embodiments may provide for a device which may be used to place and hold a person's face into a liquid for an extended time while the person conveniently and/or comfortably breathes through a breathing tube (e.g., a breathing apparatus). While the person has his or her face immersed in the liquid, the device may aerate the liquid (with various gasses). In some embodiments, the device may be designed to minimize or prevent the spillage of liquid onto the person's clothing or the immediate area around the device.

[0046] In some embodiments the face soaking device may comprise a vessel and a vessel neck gasket. The vessel may be configured to hold a liquid to submerge a face of a user or a portion thereof. The vessel neck gasket may be removably joined to the vessel. The vessel neck gasket may be configured to comfortably accommodate a portion of the user's neck. In some embodiments, the face soaking device may also comprise a breathing apparatus that may be in removable contact with: the vessel, with a head support, and/or with the user. The breathing apparatus may be configured to permit the user to breathe while the user's face (in whole or in part) may be submerged within the liquid. When the vessel may be filled with the liquid to at least a sufficient level, the user may soak the face or the portion thereof, such that skin being soaked receives a benefit.

[0047] It is an objective of the present invention to provide a face soaking device that may be used to reduce severity of facial acne by immersing the face within the immersion liquid.

[0048] It is another objective of the present invention to provide the face soaking device that may be used to reduce severity of facial wrinkles and/or facial age spots by immersing the face within the immersion liquid.

[0049] It is another objective of the present invention to provide the face soaking device that may be used to reduce severity of microorganism infection, including, but not limited to viral, bacterial, and/or fungal infections, of facial skin by immersing the face within the immersion liquid.

[0050] It is another objective of the present invention to provide the face soaking device that may be used to reduce severity of physical damage to facial skin by immersing the face within the immersion liquid.

[0051] It is another objective of the present invention to provide the face soaking device that may permit a user to submerge the user's face within the immersion liquid by the face soaking device comprising a vessel which may be configured to hold the immersion liquid.

[0052] It is another objective of the present invention to provide the face soaking device that may permit the user to breath while the user's face may be immersed in the immersion liquid.

[0053] It is another objective of the present invention to provide the face soaking device that may permit the user to immerse the user's face within the immersion liquid while maintaining comfort to the neck where the neck may contact the face soaking device, particularly where the soft tissue of the neck may contact the face soaking device.

[0054] It is another objective of the present invention to provide the face soaking device that may minimize immersion liquid spillage around the user's neck when the user's face may be immersed within the immersion liquid.

[0055] It is another objective of the present invention to provide the face soaking device that may catch spilled immersion liquid from a main vessel (e.g., the vessel) holding the immersion liquid.

[0056] It is another objective of the present invention to provide the face soaking device that may permit the user to immerse the user's face within the immersion liquid while maintaining comfort to the neck and mitigating against neck strain, by supporting a portion of the user's head that may be within the vessel, particularly that of the forehead.

[0057] It is another objective of the present invention to provide the face soaking device, wherein a head support (e.g., a head rest subassembly) may be adjustable; wherein such adjustments may be in a vertical direction (height direction) and/or in a forwards-backwards direction.

[0058] It is another objective of the present invention to provide the face soaking device wherein the immersion liquid may receive various gasses into the immersion liquid.

[0059] It is another objective of the present invention to provide the face soaking device wherein the immersion liquid may be oxygenated by a release of air and/or oxygen within the immersion liquid.

[0060] It is another objective of the present invention to provide the face soaking device wherein a temperature of the immersion liquid may be increased or decreased with respect to a room temperature of the face soaking device.

[0061] It is another objective of the present invention to provide the face soaking device wherein the vessel may be insulated to help control the temperature of the

immersion liquid.

[0062] It is another objective of the present invention to provide the face soaking device wherein the face soaking device may be used for heat therapy and/or for cold therapy.

[0063] It is another objective of the present invention to provide the face soaking device wherein the face soaking device may be used for heat therapy and/or for cold therapy, wherein the heat therapy and/or the cold therapy may be used to treat not only skin problems, but also other ailments, such as, but not limited to, arthritis, osteoarthritis, fibromyalgia, joint stiffness, bursitis, tendonitis, sprains, pulled muscles, and the like.

[0064] It is another objective of the present invention to provide the face soaking device wherein the face soaking device may be used for heat therapy and/or for cold therapy, wherein the heat therapy and/or the cold therapy may increase blood flow, improve joint stiffness, reduce pain, and the like.

[0065] It is another objective of the present invention to provide the face soaking device wherein the face soaking device may be used for cold therapy, wherein the cold therapy may increase blood flow, improve joint stiffness, reduce pain, reduce swelling, and the like.

[0066] It is another objective of the present invention to provide the face soaking device wherein the face soaking device may be used for alternating between heat therapy and cold therapy, wherein the alternating heat and cold therapy may increase blood flow, improve joint stiffness, reduce pain, reduce swelling, improve healing, aid in removing cellular toxins, and the like.

[0067] It is another objective of the present invention to provide the face soaking device wherein the face soaking device may be used for soaking facial skin for at least a purpose of softening such facial skin and/or for softening facial hair (e.g., whiskers and/or stubble). For example, such skin softening may be beneficial for facial shaving.

[0068] It is another objective of the present invention to provide the face soaking device wherein the face soaking device may be used for treating burns, external and/or internal.

[0069] It is another objective of the present invention to provide the face soaking device wherein the face soaking device may be used for lightening skin shading.

[0070] It is another objective of the present invention to provide the face soaking device wherein the face soaking device may be used for darkening skin shading (e.g., skin tone or skin hue).

[0071] It is another objective of the present invention to provide the face soaking device wherein the immersion liquid may be paraffin wax.

[0072] It is another objective of the present invention to provide the face soaking device wherein interior surface of the vessel may be smooth to facilitate draining of the immersion liquid and to facilitate cleaning and sanitation of the face soaking device.

[0073] It is another objective of the present invention

to provide the face soaking device that may be portable and that may be carried by a single adult user.

[0074] It is another objective of the present invention to provide the face soaking device wherein interior surfaces of the vessel may comprise one or more jet nozzles, one or more intakes, and a means for pumping the immersion liquid from the intakes and through the jet nozzles such that a pressure of immersion liquid may be directed to portions of the immersed face.

[0075] It is another objective of the present invention to provide the face soaking device wherein jet nozzle positioning may be adjustable.

[0076] It is another objective of the present invention to provide the face soaking device wherein facial immersion within the immersion liquid within the vessel may be soothing and relaxing to the user, such stress may be reduced.

[0077] It is another objective of the present invention that such a stress releasing use of the face soaking device may result in further collateral benefits such as promoting lowering of blood pressure, mitigation against headache severity, and/or strengthening the user's immune system.

[0078] It is yet another objective of the present invention to provide a face soaking device that may utilize, quality and reliable manufacturing methods, but that may also be efficient and less expensive manufacturing methods.

[0079] These and other advantages and features of the present invention are described herein with specificity so as to make the present invention understandable to one of ordinary skill in the art, both with respect to how to practice the present invention and how to make the present invention.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0080] Elements in the figures have not necessarily been drawn to scale in order to enhance their clarity and improve understanding of these various elements and embodiments of the invention. Furthermore, elements that are known to be common and well understood to those in the industry are not depicted in order to provide a clear view of the various embodiments of the invention.

FIG. 1 may depict an embodiment of an overall assembled face soaking device, shown from a top perspective view.

FIG. 2A may depict a close up of a front and a top portion of the face soaking device of **FIG. 1**.

FIG. 2B may depict a front view of the face soaking device of **FIG. 2A**. **FIG. 2B** also includes **sectional-line 7-7**.

FIG. 2C may depict a top view of a front portion of the face soaking device of **FIG. 2A**.

FIG. 2D may depict a back view of a front portion of the face soaking device of **FIG. 2A**.

FIG. 3A may depict a partial exploded view of a front portion of the face soaking device of **FIG. 2A**, shown from a top front perspective view.

FIG. 3B may depict a partial exploded view of a front portion of the face soaking device of **FIG. 2A**, shown from a top back perspective view.

FIG. 4A may depict a close up of a front and a top portion of the face soaking device of **FIG. 2A**, but with a vessel neck gasket and a clamp removed, so a neck-gasket-accommodator may be visible.

FIG. 4B may depict a front view of the face soaking device of **FIG. 4A**.

FIG. 4C may depict a top view of a front portion of the face soaking device of **FIG. 4A**.

FIG. 4D may depict a back view of a front portion of the face soaking device of **FIG. 4A**.

FIG. 5A may depict an exploded view of a vessel neck gasket; wherein a carrier may be separated from a flexible member, shown from a top front perspective view.

FIG. 5B may depict the assembled vessel neck gasket of **FIG. 5A**, shown from a top front perspective view.

FIG. 5C may depict the assembled vessel neck gasket of **FIG. 5A**, shown from a front view.

FIG. 5D may depict the assembled vessel neck gasket of **FIG. 5A**, shown from a back view.

FIG. 5E may depict the assembled vessel neck gasket of **FIG. 5A**, shown from a top view.

FIG. 5F may depict the assembled vessel neck gasket of **FIG. 5A**, shown from a bottom view.

FIG. 5G may depict the assembled vessel neck gasket of **FIG. 5A**, shown from a left side view. (A right side view may be a mirror image of **FIG. 5G**.)

FIG. 6A may depict a clamp, shown from a top front perspective view.

FIG. 6B may depict the clamp of **FIG. 6A**, shown from a front view.

FIG. 6C may depict the clamp of **FIG. 6A**, shown from a back view.

FIG. 6D may depict the clamp of **FIG. 6A**, shown from a top view.

FIG. 6E may depict the clamp of **FIG. 6A**, shown from a bottom view.

FIG. 6F may depict the clamp of **FIG. 6A**, shown from a side view.

FIG. 6G may depict a close up of one end (a left end) of the clamp of **FIG. 6A**, shown from a top front perspective view.

FIG. 7 may depict a cross-sectional view along **sectional-line 7-7** that is shown in **FIG. 2B**.

FIG. 8 may depict a cross-sectional view of the neck-gasket-accommodator, the vessel neck gasket, and an additional embodiment of the clamp.

FIG. 9 may depict a cross-sectional view of the neck-gasket-accommodator, the vessel neck gasket, and an additional embodiment of the clamp.

FIG. 10 may depict a cross-sectional view of the

neck-gasket-accommodator, the vessel neck gasket, and an additional embodiment of the clamp.

FIG. 11 may depict a cross-sectional view of the neck-gasket-accommodator, the vessel neck gasket, and an additional embodiment of the clamp.

FIG. 12A may show that a clamp embodiment may resemble a letter "f" in cross-section.

FIG. 12B may show that a clamp embodiment may resemble a letter "L" in cross-section.

FIG. 12C may show that a clamp embodiment may resemble a letter "J" in cross-section.

FIG. 12D may show that a clamp embodiment may resemble a letter "C" in cross-section.

FIG. 12E may depict a cross-sectional view of a neck-gasket-accommodator.

REFERENCE NUMERAL SCHEDULE

[0081]

100	face soaking device 100
120	vessel 120
121	at least one wall 121
122	rim 122
125	at least one base 125
130	breathing apparatus 130
140	head rest subassembly 140
150	heater subassembly 150
160	aerator 160
170	controls 170
400	neck-gasket-accommodator 400
402	contour 402
404	horizontal width 404
406	maximum vertical length 406
408	receiving-channel 408
410	two opposing opening wall-edges 410
412	pocket 412
500	vessel neck gasket 500
501	mating edge 501
503	top edge 503
505	flexible member 505
507	internal surface 507
509	external surface 509
511	carrier 511
600	clamp 600
601	terminal end 601
603	mating-wall-edge 603
605	snap latch 605
800	clamp 800
811	finger-pull 811
813	chamfer 813
815	tab 815
900	clamp 900
911	finger-pull 911
1000	clamp 1000
1011	finger-pull 1011
1100	clamp 1100

DETAILED DESCRIPTION OF THE INVENTION

[0082] In the following discussion that addresses a number of embodiments and applications of the present invention, reference is made to the accompanying drawings that form a part thereof, where depictions are made, by way of illustration, of specific embodiments in which the invention may be practiced. It is to be understood that other embodiments may be utilized and changes may be made without departing from the scope of the invention.

[0083] FIG. 1 may depict an embodiment of an overall assembled face soaking device 100, shown from a top perspective view. In some exemplary embodiments, as may be depicted in FIG. 1, face soaking device 100 may comprise: a vessel 120, a vessel neck gasket 500, and a breathing apparatus 130.

[0084] Continuing discussing FIG. 1, in some embodiments, vessel 120 may be hold a liquid in a sufficient volume to submerge a whole face of a user or a portion thereof. It is obvious to one of ordinary skill in the art, that vessel 120 may be configured to hold the liquid at a sufficient level to permit the user to submerge (immerse) the whole of their face, or a portion thereof within the liquid, while the liquid may be held within vessel 120. This sufficient level may be a liquid level where when the user inserts their face into an internal volume of vessel 120 and rests a first portion of their neck upon a vessel neck gasket 500, such that their face may be completely immersed in the liquid. The maximum liquid level of vessel 120 may be greater (higher) than this sufficient level.

[0085] In some embodiments, vessel 120 may comprise at least one wall 121 and at least one base 125. At least one wall 121 and at least one base 125 may be in physical contact with each other. At least one wall 121 may comprise a neck-gasket-accommodator 400. (See e.g., FIG. 4A for neck-gasket-accommodator 400.) Neck-gasket-accommodator 400 may be configured to accommodate vessel neck gasket 500. In some embodiments, neck-gasket-accommodator 400 may be formed as a cut-out into a region of at least one wall 121, from a top of vessel 120. In some embodiments, neck-gasket-accommodator 400 may be formed as an integral molded structure of a region of at least one wall 121. Vessel neck gasket 500 may be removably joined to vessel 120. Where vessel neck gasket 500 may join vessel 120, i.e., along such surfaces of physical contact, a primary water tight seal may be formed in or at the vicinity of neck-gasket-accommodator 400. For example, and without limiting the scope of the present invention, in some embodiments, this "vicinity" of neck-gasket-accommodator 400 may be two inches or less from structure of neck-gasket-accommodator 400. In other embodiments, other distances may be used for the "vicinity" of neck-gasket-accommodator 400. Vessel neck gasket 500 may receive a first portion of a neck region of the user when the whole face or the first portion thereof may be submerged in the liquid within the internal volume of vessel 120. The first portion of the neck region of the user may be where their

neck physically contacts vessel neck gasket 500. Note, the nature of the physical contact between the first portion of the neck region of the user and vessel neck gasket 500 may be removable. When vessel neck gasket 500 may receive the first portion of the neck region of the user, a secondary water tight seal may be formed between this first portion of the neck region and vessel neck gasket 500.

[0086] In some embodiments, vessel 120 may be double hulled.

[0087] In some embodiments, breathing apparatus 130 may be in physical contact with vessel 120, as may be shown in FIG. 1. In some embodiments, a breathing apparatus embodiment may be in physical contact with a head rest subassembly. In both such embodiments, the nature of the physical contact between breathing apparatus embodiments (e.g., 130) and vessel 120; or between breathing embodiments and the given head rest subassembly, may be removable in some embodiments; while non-removable in other embodiments. In some embodiments, the user may be able to breathe using breathing apparatus 130 when a mouth of the user may be holding a mouth piece of breathing apparatus 130.

[0088] When vessel 120 may be filled with the liquid to a level at or less than a maximum liquid level of vessel 120, the user may soak their whole face or the portion thereof for a time period. The skin being soaked in the liquid for this time period may receive a health, an aesthetic, and/or a soothing benefit.

[0089] In some embodiments, the benefit may comprise one or more of a reduction in acne, a reduction in wrinkle severity, a softening of skin, moisturizing of skin, promotion of relaxation, promotion of healing of damaged skin, promotion of healing of infected skin, reduction in rash severity, reduction and/or elimination of headaches (including migraine), promotion of healing of traumatized tissue (including burned tissue), lightening skin shades, darkening skin shades (tone, hue), reduction in swelling, and the like. Such benefits may derive from facial skin exposure to the liquid where characteristics of the liquid may comprise one or more of the liquid being a saline solution, the liquid being a saline solution with a salt concentration greater than 0.9% by weight, presence of air and/or oxygen within the liquid, temperature of the liquid being less than or greater than ambient room temperature, circulation of the liquid within vessel 120, and/or the liquid being directed against a portion of the skin in the form of stream or jet of the liquid pressure.

[0090] In some embodiments, face soaking device 100 may further comprise a head rest subassembly 140. In some embodiments, at least some portion of head rest subassembly 140 may be attached to vessel 120. See e.g., FIG. 1. In some embodiments, the at least some portion of head rest subassembly 140 may be removably attached to vessel 120. In some embodiments, head rest subassembly 140 may comprise a support member or a strap. In some embodiments, at least some portion of the support member or at least some portion of the strap may

be located in the internal volume of vessel **120**. In some embodiments, the support member or the strap physically supports a portion of the head (e.g., a forehead) of the user when the whole face or portion thereof is removably located in the internal volume of vessel **120**. See e.g., **FIG. 1**.

[0091] In some embodiments, face soaking device **100** may further comprise a heater subassembly **150**. In some embodiments, at least a portion of heater subassembly **150** may be attached to vessel **120**. See e.g., **FIG. 1**. In some embodiments, heater subassembly **150** may comprise a heating element that heats at least a portion of the liquid within the internal volume of vessel **120**. In some embodiments, heater subassembly **150** may provide heating and/or cooling to the at least the portion of the liquid within the internal volume of vessel **120**.

[0092] In some embodiments, face soaking device **100** may further comprise an aerator **160**. See e.g., **FIG. 1**. In some embodiments, aerator **160** may comprise a gas diffuser and a gas source in physical communication with the gas diffuser. In some embodiments, the gas diffuser may be attached to vessel **120**. In some embodiments, the gas diffuser may be removably attached to vessel **120**. In some embodiments, the gas source provides gas to the gas diffuser. In some embodiments, the gas diffuser releases at least some of the gas received through a porous structure of the gas diffuser into the internal volume of vessel **120**; such that bubbles may be released into at least some of the liquid in the internal volume of vessel **120**.

[0093] In some embodiments, face soaking device **100** may further comprise at least one electromagnetic (EM) emitter. In some embodiments, the at least one EM emitter emits electromagnetic radiation at predetermined wavelengths. In some embodiments, at least some portion of the at least one EM emitter may be attached to vessel **120**. In some embodiments, at least some of emitted electromagnetic radiation is emitted into the internal volume of vessel **120**. For example, and without limiting the scope of the present invention, in some embodiments, the at least one EM emitter may comprise at least one light source, such as, but limited to a LED (light emitting diode) or one or more banks of LEDs.

[0094] In some embodiments, face soaking device **100** may further comprise controls **170** for controlling electronics and/or electro-mechanical components of face soaking device **100**. Such electronic and electro-mechanical components may comprise one or more: heater subassembly **150**, aerator **160**, and/or the at least one electromagnetic emitter. See e.g., **FIG. 1**.

[0095] A **FIG. 2** series of figures may comprise **FIG. 2A** through **FIG. 2D**. These **FIG. 2** series figures may depict vessel neck gasket **500** removably attached to vessel **120**. In contrast, a **FIG. 3** series of figures (**FIG. 3A** and **FIG. 3B**) may show vessel neck gasket **500** exploded away from vessel **120**, i.e., vessel neck gasket **500** removably detached from vessel **120**; a **FIG. 4** series may focus on showing neck-gasket-accommodator **400**

of vessel **120**, i.e., where vessel neck gasket **500** removably attaches to vessel **120**; a **FIG. 5** series of figures may focus on showing just vessel neck gasket **500**; a **FIG. 6** series may focus on showing just a clamp **600**, which in some embodiments, may help to removably secure vessel neck gasket **500** to neck-gasket-accommodator **400**; **FIG. 7** may show a cross-sectional view of the configuration where vessel neck gasket **500** is removably attached to neck-gasket-accommodator **400**.

[0096] Turning back to the **FIG. 2** series of figures, **FIG. 2A** may depict a close up of a front and a top portion of face soaking device **100** showing vessel neck gasket **500** removably attached to vessel **120**. **FIG. 2B** may depict a front view of face soaking device **100** of **FIG. 2A**. **FIG. 2C** may depict a top view of a front portion of face soaking device **100** of **FIG. 2A**. **FIG. 2D** may depict a back view of a front portion of face soaking device **100** of **FIG. 2A**.

[0097] Notes: front views may also be known as a vessel neck gasket view, at least when vessel neck gasket **500** may be attached to vessel **120**; a left side view may be with respect to an observer looking upon the front view, wherein the left side view may be with respect to the observer's left, i.e., the left side of face soaking device **100** (or component thereof) when viewed from the front view.

[0098] The **FIG. 3** series of figures may comprise **FIG. 3A** and **FIG. 3B**. **FIG. 3A** may depict a partial exploded view of a front portion of face soaking device **100** of **FIG. 2A**, shown from a top front perspective view. **FIG. 3B** may depict a partial exploded view of a front portion of face soaking device **100** of **FIG. 2A**, shown from a top back perspective view. In both **FIG. 3A** and in **FIG. 3B**, vessel neck gasket **500** may be shown removed away from vessel **120**. In both **FIG. 3A** and in **FIG. 3B**, portions of neck-gasket-accommodator **400** may be shown as vessel neck gasket **500** may be shown removed away from vessel **120**. In both **FIG. 3A** and in **FIG. 3B**, clamp **600** may also be shown removed away from vessel **120**.

[0099] In some embodiments vessel neck gasket **500** may be attached to neck-gasket-accommodator **400** by use of clamp **600**. See e.g., **FIG. 3A**, **FIG. 3B**, and **FIG. 7**.

[0100] The **FIG. 4** series of figures may comprise **FIG. 4A** through **FIG. 4D**. As noted, these **FIG. 4** series may focus on showing neck-gasket-accommodator **400** of vessel **120**, i.e., where vessel neck gasket **500** removably attaches to vessel **120**. Note, vessel neck gasket **500** may not be shown in the **FIG. 4** series of figures. Note, vessel neck gasket **500** may not be shown in the **FIG. 4** series of figures. Note, clamp **600** may not be shown in the **FIG. 4** series of figures. **FIG. 4A** may depict a close up of a front and a top portion of face soaking device **100** of **FIG. 2A**. **FIG. 4B** may depict a front view of face soaking device **100** of **FIG. 4A**. **FIG. 4C** may depict a top view of a front portion of face soaking device **100** of **FIG. 4A**. **FIG. 4D** may depict a back view of a front portion of face soaking device **100** of **FIG. 4A**. **FIG. 4A** may correspond to **FIG. 2A**, **FIG. 4B** may correspond to **FIG. 2B**, **FIG. 4C** may correspond to **FIG. 2C**, and **FIG. 4D** may correspond

to FIG. 2D; but in these FIG. 4 series of figures vessel neck gasket 500 and clamp 600 may be removed from vessel 120, so neck-gasket-accommodator 400 may be visible.

[0101] The FIG. 5 series of figures may comprise FIG. 5A through FIG. 5G. As noted, these FIG. 5 series of figures may focus on showing just vessel neck gasket 500. FIG. 5A may depict an exploded view of vessel neck gasket 500; wherein a carrier 511 may be separated from a flexible member 505, shown from a top front perspective view. FIG. 5B may depict the assembled vessel neck gasket 500, shown from a top front perspective view. FIG. 5C may depict the assembled vessel neck gasket 500, shown from a front view. FIG. 5D may depict the assembled vessel neck gasket 500, shown from a back view. FIG. 5E may depict the assembled vessel neck gasket 500, shown from a top view. FIG. 5F may depict the assembled vessel neck gasket 500, shown from a bottom view. FIG. 5G may depict the assembled vessel neck gasket 500, shown from a left side view. (A right side view may be a mirror image of FIG. 5G.)

[0102] The FIG. 6 series of figures may comprise FIG. 6A through FIG. 6G. As noted, these FIG. 6 series of figures may focus on showing just clamp 600. FIG. 6A may depict clamp 600, shown from a top front perspective view. FIG. 6B may depict clamp 600, shown from a front view. FIG. 6C may depict clamp 600, shown from a back view. FIG. 6D may depict clamp 600, shown from a top view. FIG. 6E may depict clamp 600, shown from a bottom view. FIG. 6F may depict clamp 600, shown from a side view. FIG. 6G may depict a close up of one end (a left end) of clamp 600, shown from a top front perspective view.

[0103] FIG. 7 may depict a cross-sectional view along sectional-line 7-7, that is shown in FIG. 2B. Transverse width cross-sections of neck-gasket-accommodator 400, clamp 600, vessel neck gasket 500 may be seen in FIG. 7, all in their assembled configuration wherein clamp 600 may be assisting in the removable attachment of vessel neck gasket 500 to neck-gasket-accommodator 400 of vessel 120.

[0104] In some embodiments, neck-gasket-accommodator 400, vessel neck gasket 500, and clamp 600 may all communicate together forming the primary water tight seal. Compare FIG. 2A against FIG. 3A. In FIG. 2A the primary water tight seal may be intact; whereas, FIG. 3A may show how the primary water tight seal may be formed or is unformed.

[0105] In some embodiments, components for forming the primary water tight seal may comprise: neck-gasket-accommodator 400, vessel neck gasket 500, and clamp 600 (or clamp 800, clamp 900, clamp 1000, or clamp 1100). In some embodiments, neck-gasket-accommodator 400 may be a structural member located on a side wall (e.g., wall 121) of vessel 120. In some embodiments, neck-gasket-accommodator 400 may have a contour 402. In some embodiments, contour 402 may track an open path that may be below a top rim 122 of the vessel

120. In some embodiments, this open path may be continuous. In some embodiments, extending into the contour 402 may be a receiving-channel 408. See e.g., FIG. 4A. In some embodiments, vessel neck gasket 500 may comprise a mating edge 501. See e.g., FIG. 5A. In some embodiments, at least portions of mating edge 501 may fit within receiving-channel 408. See e.g., FIG. 3A, FIG. 7, FIG. 8, FIG. 9, FIG. 10, and FIG. 11. In some embodiments, the clamp (e.g., 600, 800, 900, 1000, or 1100) may also be a structural member. In some embodiments, the clamp (e.g., 600, 800, 900, 1000, or 1100) may comprise a mating-wall-edge 603. See e.g., FIG. 6A. In some embodiments, at least portions of mating-wall-edge 603 may fit within receiving-channel 408. See e.g., FIG. 3A, FIG. 7, FIG. 8, FIG. 9, FIG. 10, and FIG. 11. In some embodiments, a width of a portion of the clamp (e.g., 600, 800, 900, 1000, or 1100), a width of vessel neck gasket 500, and a width of the receiving-channel 408 may be sized such that when the at least portions of mating-wall-edge 603 and the at least portions of mating edge 501 may be received into receiving-channel 408, the primary water tight seal is formed between a portion of receiving-channel 408 and some portions of vessel neck gasket 500. See e.g., FIG. 3A, FIG. 7, FIG. 8, FIG. 9, FIG. 10, and FIG. 11. In some embodiments, clamp 600 (and other disclosed clamps herein) and vessel neck gasket 500 may be removable from receiving-channel 408. See e.g., FIG. 3A.

[0106] In some embodiments, in at least one wall 121 of vessel 120 may be neck-gasket-accommodator 400. In some embodiments, at least one wall 121 of vessel 120 may comprise neck-gasket-accommodator 400. Many figures show neck-gasket-accommodator 400 located in a front wall of face soaking device 100. In some embodiments, neck-gasket-accommodator 400 may be formed in the front wall of vessel 120. See e.g., the FIG. 4 series of figures, such as, FIG. 4A and FIG. 4C.

[0107] In some embodiments, neck-gasket-accommodator 400 may comprise contour 402. Contour 402 may generally track an overall shape of neck-gasket-accommodator 400. Contour 402 may comprise one or more surfaces. In some embodiments, such surfaces may face one or more of: each other, face the front of a face soaking device, face the back of a face soaking device, and/or face away from an upper surface of a bottom interior surface of vessel 120. See e.g., FIG. 4A and FIG. 4B.

[0108] In some embodiments, neck-gasket-accommodator 400 may comprise contour 402 in at least one wall 121 that runs below rim 122 of vessel 120. In some embodiments, contour 402 begins where a surface of neck-gasket-accommodator 400 first runs below rim 122 and contour 402 continues until ending where the surface of neck-gasket-accommodator 400 runs back up to rim 122. In some embodiments, where contour 402 begins and where contour 402 ends may be separated by horizontal width 404. In some embodiments, contour 338 has maximum vertical length 406 from a height of rim 122 to a lowest point on contour 402. See e.g., FIG. 4B.

[0109] In some embodiments, horizontal width **404** may be greater than or equal to a diameter of a neck of the user. In some embodiments, maximum vertical length **406** may be greater than or equal to half of a diameter of the neck of the user. For example, some large adult men may have a neck circumference of about 21 inches, which results in a neck diameter of about 6.69 inches. For example, and without limiting the scope of the present invention, in some embodiments, horizontal width **404** may be 7 to 11 inches. For example, and without limiting the scope of the present invention, in some embodiments, maximum vertical length **406** may be 3.5 to 7 inches.

[0110] Neck-gasket-accommodator **400** may comprise a maximum vertical length **406** greater than a second portion of the neck region of the user extending from rim **122** towards at least one base **125** of vessel **120**, extending to a bottom most portion of neck-gasket-accommodator **400**. See e.g., FIG. 4B. The second portion of the neck region may be a vertical area of a front of the user's neck, i.e. the soft tissue side of the neck, where the neck may contact vessel neck gasket **500**. Neck-gasket-accommodator **400** may have a horizontal width **404** greater than a third portion of the neck region of the user centered in a horizontal width (e.g., transverse-width or from right to left) of vessel **120**, extending from rim **122** to opposing rim **122** across an opening that neck-gasket-accommodator **400** creates. See e.g., FIG. 4B. The third portion of the neck region may be a horizontal area of a front of the user's neck, i.e. the soft tissue side of the neck, where the neck may contact vessel neck gasket **500**.

[0111] Note with respect, to the first portion, the second portion, and the third portion of the neck region of the user, the first portion may comprise the second portion and the third portion. That is, the second portion may define a vertical dimension of the first portion and the third portion may define a horizontal dimension of the first portion. For example, and without limiting the scope of the present invention, this first portion of the neck region may be a portion of the neck what may correspond to where an Adam's Apple of a neck may be located; and including up two inches from that Adam's Apple region or a corresponding region on a neck with no Adam's Apple.

[0112] In some embodiments, an overall shape of neck-gasket-accommodator **400**, with respect to at least one base **125** (see FIG. 1 for at least one base **125**) or as viewed from a front of wall **121** that has neck-gasket-accommodator **400**, may be shaped suitable to receive vessel neck gasket **500** and the first portion of the neck region of the user when in use in a given face soaking device embodiment (e.g., face soaking device **100**). See e.g., FIG. 4B wherein the overall shape of contour **402** of neck-gasket-accommodator **400** may be: curved; rounded; semicircular; semi-elliptical; U-shaped; horseshoe shaped, semi-oval; an arc of a partial circle; an arc of a partial ellipse; an arc of a partial oval; one third to

three thirds of a circle; one third to three thirds of an oval; one third to three thirds of an ellipse; and/or the like; e.g., when viewed from the front of face soaking device **100**.

[0113] In some embodiments, a shape (i.e., the overall shape) of contour **402** as viewed from a front of face soaking device **100** may be selected from the group comprising: curved; rounded; semicircular; semi-elliptical; U-shaped; horseshoe shaped, semi-oval; an arc of a partial circle; an arc of a partial ellipse; an arc of a partial oval; one third to three thirds of a circle; one third to three thirds of an oval; one third to three thirds of an ellipse; a shape approximating an open-ended polygon; and/or the like. See e.g., FIG. 4B.

[0114] In some embodiments, the open path of contour **402** may be substantially (i.e., not geometrically perfectly) shaped, as viewed from a front of the side wall, as one of the following: curved; rounded; semicircular; semi-elliptical; U-shaped; horseshoe shaped, semi-oval; an arc of a partial circle; an arc of a partial ellipse; an arc of a partial oval; one third to three thirds of a circle; one third to three thirds of an oval; one third to three thirds of an ellipse; a shape approximating an open-ended polygon; and/or the like.

[0115] In some embodiments, the open path of contour **402** may be a regular or an irregular polygon that is not closed (i.e., an open shape) or semi-polygon suitable to that is not closed (i.e., an open shape) suitable to receive bottom portions of vessel neck gasket **500** (e.g., mating edge **501**) and the first portion of the neck region of the user when in use. This embodiment is not shown in the figures; however, it should be obvious to one of ordinary skill in the art that the overall shape semi-circular neck-gasket-accommodator **400** shown FIG. 4B may be modified into the open regular or the open irregular polygon or the open semi-polygon of contour **402** and that such a contour may continue to be within the scope of this invention.

[0116] Note, in some embodiments, neck-gasket-accommodator **400** may be termed a "gasket-accommodator."

[0117] In some embodiments, contour **402** may comprise at least one surface facing away from an upper surface of a bottom interior surface of vessel **120**. In some embodiments, along a length of contour **402** may be a receiving-channel **408**. See e.g., FIG. 4A and FIG. 7 for a cross-sectional view of this receiving-channel **408**. Receiving-channel **408** may be channel or groove cut into contour **402**, substantially along a length of contour **402**. See e.g., FIG. 4A. A width of receiving-channel **408** may be sized to frictionally fit widths of one or more of: vessel neck gasket **500** (e.g., flexible member **505** plus carrier **511**), and/or clamp **600**; such that the primary water tight seal is formed. See e.g., FIG. 7.

[0118] In some embodiments, a cross-section of the receiving-channel **408** may be substantially (i.e., not geometrically perfectly) shaped as one of the following: curved; rounded; semi-circular; semi-elliptical; U-shaped; horseshoe shaped, semi-oval; an arc of a partial

circle; an arc of a partial ellipse; an arc of a partial oval; one third to three thirds of a circle; one third to three thirds of an oval; one third to three thirds of an ellipse; or a shape approximating an open-ended polygon. See e.g., FIG. 7, FIG. 8, FIG. 9, FIG. 10, and FIG. 11.

[0119] In some embodiments, a direction that receiving-channel 408 extends into contour 402 may be substantially parallel with a major plane of side wall 121. See e.g., FIG. 7, FIG. 8, FIG. 9, FIG. 10, FIG. 11, and FIG. 12E. In some embodiments, the direction that receiving-channel 408 extends into contour 402 may not be perpendicular (nor substantially perpendicular) with the major plane of side wall 121. The major plane of side wall 121 may be substantially collinear with an external surface of side wall 121.

[0120] In some embodiments, bottom portions of vessel neck gasket 500 may be configured to fit to (e.g., mate to) contour 402 of neck-gasket-accommodator 400 in at least one wall 121 of vessel 120. In some embodiments, bottom portions of vessel neck gasket 500 may be configured to fit to (e.g., mate to) receiving-channel 408 in contour 402 of neck-gasket-accommodator 400 in at least one wall 121 of vessel 120. See e.g., FIG. 3A, FIG. 4A, FIG. 5A, and FIG. 7. Surface area of mating edge 501 of vessel neck gasket 500 may be equal to, greater than, or less than, as compared against surface area of neck-gasket-accommodator 400. Vessel neck gasket 500 may comprise a mating edge 501 complimentary to at least some surfaces of contour 402 of neck-gasket-accommodator 400 in at least one wall 121 of vessel 120. Vessel neck gasket 500 may comprise a top edge 503. In some embodiments, top edge 503 and mating edge 501 together may define a perimeter of vessel neck gasket 500. In some embodiments, top edge 503 and mating edge 501 may together circumscribe and define a closed shape for vessel neck gasket 500. In some embodiments, top edge 503 and mating edge 501 may each curve for at least some portion of the given edge. In some embodiments, a radius of curvature for top edge 503 may be different for a radius of curvature for edge 501. See e.g., FIG. 5A. In some embodiments, top edge 503 may be accommodative to receiving the first portion of the neck region of the user. In some embodiments, when vessel neck gasket 500 may be attached to neck-gasket-accommodator 400, e.g., as in the FIG. 2 series of figures (e.g., FIG. 2A), some portions of top edge 503 may extend above rim 122 (e.g., FIG. 2B). In some embodiments, mating edge 501 of vessel neck gasket 500 may be attached to contour 402 of neck-gasket-accommodator 400 by a vessel neck gasket attachment means. In some embodiments, mating edge 501 of vessel neck gasket 500 may be received into receiving-channel 408 of contour 402.

[0121] In some embodiments, the vessel neck gasket attachment means may comprise clamp 600. Or in some embodiments, mating edge 501 of vessel neck gasket 500 may be attached to either an exterior wall surface or an interior wall surface of at least one wall 121, at a fixed

distance from contour 402 of neck-gasket-accommodator 400 by the vessel neck gasket attachment means. For example, and without limiting the scope of the present invention, in some embodiments, the fixed distance may be one inch or less. In other embodiments, the fixed distance may be other distances.

[0122] In some embodiments, vessel neck gasket 500 may be removable from vessel 120. In some embodiments, vessel neck gasket 500 may be removable from neck-gasket-accommodator 400. Such embodiments may facilitate switching out vessel neck gasket 500 in the event of wear and tear and/or damage to an installed vessel neck gasket 500. In some other embodiments, vessel neck gasket 500 may not be removed from vessel 120 once installed.

[0123] In some embodiments, vessel neck gasket 500 may be a subassembly comprising two parts: a flexible member 505 and a carrier 511. In some embodiments, vessel neck gasket 500 may comprise flexible member 505 and carrier 511. In some embodiments, flexible member 505 and carrier 511 may be attached to each other. See e.g., FIG. 5A.

[0124] In some embodiments, flexible member 505 may be substantially planar with an internal surface 507 (see FIG. 5D) and an external surface 509 (see FIG. 5A) disposed opposite of internal surface 507. Portions of either external surface 509 or internal surface 507 may form the secondary water tight seal with the neck region, when the user rests their neck against portions of vessel neck gasket 500. In some embodiments, a portion of internal surface 507 may physically contact some of the liquid when the liquid may be held within the internal volume of vessel 120.

[0125] In some embodiments, flexible member 505 may be a flexible sheet. In some embodiments, this flexible sheet may be shaped generally with mating edge 501 that is complimentary to cover portions (e.g., receiving-channel 408) of neck-gasket-accommodator 400 of vessel 120. In some embodiments, this flexible sheet may be shaped generally with mating edge 501 that is complimentary to cover portions of receiving-channel 408. In some embodiments, this flexible sheet may comprise a gasket along the bottom of the sheet. In some embodiments, this gasket may be mating edge 501. See e.g., FIG. 5A and FIG. 5F.

[0126] In some embodiments, flexible member 505 may be substantially constructed of one or more materials (i.e., materials of construction) suitable for forming water tight seals against human skin (or against an exterior portion of a terrestrial vertebrates body) and/or against the vessel (e.g. vessel 120), and/or suitable for being comfortable when touching human skin. In some embodiments, flexible member 505 may be constructed of one or more of elastomers comprising silicone, rubber, neoprene, nitrile, vinyl, polyethylene, polypropylene, and/or any other material suitable for forming water tight seals against human skin and/or against the vessel (e.g. vessel 120), and/or suitable for being comfortable when

touching human skin. In some embodiments, the rubber may be natural rubber. In some embodiments, the rubber may be synthetic, including latex free. In some embodiments, flexible member **505** may be compressible. For example, and without limiting the scope of the present invention, when vessel neck gasket **500** may be attached to neck-gasket-accommodator **400**, portions of internal surface **507** and external surface **509** that may be residing within receiving-channel **408** of neck-gasket-accommodator **400**, may be compressed; see e.g., **FIG. 7**. Such compression of portions of flexible member **505** within receiving-channel **408** may aid in forming the primary water tight seal. Compare, **FIG. 5F** and **FIG. 5G** may show flexible member **505** in a non-compressed state. In some embodiments, portions of flexible member **505** may be compressed by 5% to 95% as compared to non-compressed states of flexible member **505**.

[0127] In some embodiments, a shape (e.g., an overall shape) of receiving-channel **408** as viewed in a cross-section may be selected from the group comprising: one third to three thirds of a circle; one third to three thirds of an oval; one third to three thirds of an ellipse; a "U" shape, a horseshoe shape; a regular polygon open at a top (with or without rounded corners), an irregular polygon open at a top (with or without rounded corners); a semi-polygon open at a top (with or without rounded corners); and/or the like; with an arc of the partial circle, partial oval, partial ellipse, or the horseshoe shape oriented downwards towards at least one base **125**. See e.g., **FIG. 7**, **FIG. 8**, **FIG. 9**, **FIG. 10**, and **FIG. 11**.

[0128] In some embodiments, internal surface **507** and external surface **509** may be constructed of different elastomers. That is, flexible member **505** may be a laminate or comprised of planar layers. Internal surface **507** may be constructed of an elastomer with a focus on water impermeability. External surface **509** may be constructed of an elastomer with a focus on comfort to the user, i.e., an elastomer with a soft outer surface and/or a non-tacky outer surface. Such two different elastomers may be joined into a single flexible composite member of flexible member **505**. The means for joining internal surface **507** to external surface **509** may be by solvent bonding, heat welding, ultrasonic welding, chemical adhesive/sealant, mechanical fasteners (e.g., stitching and/or staples, or the like), and/or the like.

[0129] In some embodiments, flexible member **505** may be manufactured by die cutting, stamping, molding, and/or 3D printing.

[0130] In some embodiments, carrier **511** may be attached to flexible member **505**. The means for joining carrier **511** to flexible member **505** may be by solvent bonding, heat welding, ultrasonic welding, chemical adhesive/sealant, mechanical fasteners (e.g., stitching and/or staples, or the like), and/or the like. See e.g., **FIG. 5A** and **FIG. 5B**. In some embodiments, carrier **511** may be integral with flexible member **505**. In some embodiments, carrier **511** may be a structural member. In some embodiments, carrier **511** may be rigid to semi-rigid. In

some embodiments, carrier **511** may be substantially constructed from one or more thermoformed plastics, metal, wood, composite, laminate, and/or the like. In some embodiments, carrier **511** may have a higher durometer as compared against a durometer of flexible member **505**. In some embodiments, carrier **511** may impart structural rigidity to bottom portions of flexible member **505**, which may facilitate loading or feeding of bottom portions of vessel neck gasket **500** into neck-gasket-accommodator **400** receiving-channel **408**. See e.g., **FIG. 3A** and **FIG. 3B**. In some embodiments, carrier **511** may have a shape that is complimentary to bottom surfaces of flexible member **505**, such as mating edge **501**. In some embodiments, both carrier **511** and flexible member **505** may share mating edge **501**. See e.g., **FIG. 3A**, **FIG. 5A**, **FIG. 5B**, **FIG. 7**, **FIG. 8**, **FIG. 9**, **FIG. 10**, and **FIG. 11**.

[0131] In some embodiments, carrier **511** may be shaped complimentary to a shape of the open path of contour **402**. In some embodiments, mating edge **501** may be shaped complimentary to a shape of receiving-channel **408**. See e.g., **FIG. 3A**, **FIG. 7**, **FIG. 8**, **FIG. 9**, **FIG. 10**, and **FIG. 11**.

[0132] In some embodiments, carrier **511** may be manufactured by die cutting, stamping, molding, extrusion, and/or 3D printing.

[0133] In some embodiments, the vessel neck gasket attachment means may be selected from one or more of: a friction fit, heat welding, ultrasonic welding, solvent bonding, chemical adhesives and/or sealants, mechanical fasteners, and/or the like. Use of clamp **600** may be an example of a frictional fit and/or a type of mechanical fastener. Recall, the vessel neck gasket attachment means may be how vessel neck gasket **500** may be attached to neck-gasket-accommodator **400**.

[0134] In some embodiments, an embodiment of face soaking device **100** may comprise at least these elements: vessel neck gasket **500**, clamp **600**, and vessel **120** with neck-gasket-accommodator **400** of at least one wall **121** of vessel **120**. In some embodiments, a vessel neck gasket subassembly may comprise at least these parts: vessel neck gasket **500**, clamp **600**, and neck-gasket-accommodator **400**. Neck-gasket-accommodator **400** may be a portion or region of a given vessel embodiment, such as vessel **120** embodiments.

[0135] In some embodiments vessel neck gasket **500** may be attached to neck-gasket-accommodator **400** by use of clamp **600**. See e.g., **FIG. 3A**, **FIG. 3B**, and **FIG. 7**. In some embodiments such an attachment may form the primary water tight seal. In some embodiments clamp **600** may be shaped to complimentary fit to neck-gasket-accommodator **400**, with a portion of vessel neck gasket **500** sandwiched between clamp **240** and contour **402** of neck-gasket-accommodator **400**, forming the primary water tight seal. See e.g., **FIG. 3A**, **FIG. 3B**, and **FIG. 7**. In some embodiments, contour **402** may comprise at least one surface facing away from an upper surface of a bottom interior surface of vessel **120**. The Bottom in-

terior surface may be an interior surface of vessel **120**. A width of receiving-channel **408** (of neck-gasket-accommodator **400**) may be sized to frictionally fit widths of one or more of: vessel neck gasket **500** (*i.e.*, flexible member **505** plus carrier **511**), and/or clamp **600**; such that the primary water tight seal is formed. See *e.g.*, **FIG. 7**.

[0136] In some embodiments, clamp **600** fit attachment to contour **402** of neck-gasket-accommodator **400** may be removable. In some embodiments, at least some portions of clamp **600** may fit into portions of receiving-channel **408**. In some embodiments, clamp **600** fit attachment to contour **402** of neck-gasket-accommodator **400** may be a frictional fit. In some embodiments, clamp **600** fit attachment to contour **402** of neck-gasket-accommodator **400** may be from one or more snap fits.

[0137] In some embodiments, clamp **600** may be constructed (or substantially) of a semi-rigid to rigid material of construction. For example, and without limiting the scope of the present invention, clamp **600** may be substantially constructed of one or more of a thermoformed plastic, metal, wood, composite, laminate, and/or the like. In some embodiments, clamp **600** and carrier **511** may be substantially constructed of the same types of materials. In some embodiments, clamp **600** may be manufactured via die cutting, stamping, molding (*e.g.*, injection molding), extrusion, and/or 3D printing. In some embodiments, at least some of the above characteristics (*e.g.*, rigidity and/or materials of construction) of clamp **600** may be shared with clamps **800**, **900**, **1000**, and **1100**. However, as show, clamps **800**, **900**, **1000**, and **1100** may have different geometry and/or structures from clamp **600**.

[0138] A **FIG. 6A** and **FIG. 6G** may depict snap latch structure illustrating how clamp **600** (of the **FIG. 3** series) may removably couple with neck-gasket-accommodator **400**. Such snap latch connections may work to assist in removably coupling clamp **600** to neck-gasket-accommodator **400**.

[0139] In some embodiments, neck-gasket-accommodator **400** may comprises two opposing opening wall-edges **410**. In some embodiments, the two opposing opening wall-edges **410** may define where neck-gasket-accommodator **400** begins. See *e.g.*, **FIG. 4A** and **FIG. 4C**. In some embodiments, each opening wall-edge **410** (*e.g.*, left and right) may be separated from the other by at least the at least horizontal width **404** of neck-gasket-accommodator **400** (see *e.g.*, **FIG. 4B** for horizontal width **404**). In some embodiments, each opening wall-edge **410** may descend downwards in a direction towards at least one base **125** from rim **122**. In some embodiments, each opening wall-edge **410** may be substantially flat (*i.e.*, a substantially flat surface). See *e.g.*, **FIG. 4A** and **FIG. 4C**.

[0140] In some embodiments, clamp **600** may comprise two terminal ends **601** disposed opposite of each other. See *e.g.*, **FIG. 6A**, **FIG. 6B**, and **FIG. 6C**. In some embodiments, each terminal end **601** may comprise a mating-wall-edge **603**. In some embodiments, clamp **600**

may comprise mating-wall-edges **603**. In some embodiments, at least some portion of a given mating-wall-edge **603** may be located below and/or proximate (*e.g.*, within three inches in some embodiments) to a given terminal end **601**. See *e.g.*, **FIG. 6A** which may depict one such mating-wall-edge **603**; *e.g.*, a right mating-wall-edge **603** from the perspective of the user looking at the front of face soaking device **100**; wherein a right mating-wall-edge **603** may be a mirror image of the left mating-wall-edge **603**.

[0141] In some embodiments, each mating-wall-edge **603** may be paired with a respective opening wall-edge **410**, such that mating-wall-edge **603** paired to a given opening wall-edge **410** may be complimentary to each other, when clamp **600** may be removably coupled to neck-gasket-accommodator **400**. See *e.g.*, **FIG. 3A** and **FIG. 3B**. In some embodiments, each mating-wall-edge **603** may be paired with a respective opening wall-edge **410**, such that mating-wall-edge **603** paired to the respective opening wall-edge **410** may be substantially parallel to each other, when clamp **600** may be removably coupled to neck-gasket-accommodator **400**. For example, and without limiting the scope of the present invention, left opening wall-edge **410** may be paired with left mating-wall-edge **603**. For example, and without limiting the scope of the present invention, right opening wall-edge **410** may be paired with right mating-wall-edge **603**. In some embodiments, each mating-wall-edge **603** may be substantially flat to compliment a substantially flat region on corresponding (paired) opening wall-edge **410**. See *e.g.*, **FIG. 3A** and **FIG. 3B**.

[0142] In some embodiments, when left opening wall-edge **410** may be paired with left mating-wall-edge **603** and right opening wall-edge **410** may be paired with right mating-wall-edge **603** each respective pairing may be a friction fit between the paired and complimentary surfaces.

[0143] In some embodiments, each mating-wall-edge **603** may terminate in a snap latch **605**. See *e.g.*, **FIG. 6A**, **FIG. 6B**, and **FIG. 6G**. In some embodiments, each opening wall-edge **410** may comprise a pocket **412**, which may be an indenture extending into the given opening wall-edge **410**. Each such pocket **412** may be sized to removably fit a respective snap latch **605**. In some embodiments, each snap latch **605** may be paired with a respective pocket **412** such that the paired snap latch **605** may removably snap into paired pocket **412** to form a removable snap latch connection at each of the two respective pairings. See *e.g.*, **FIG. 3A** and **FIG. 3B**. In some embodiments, a paired snap latch **605** may comprise a protrusion that may be removably engage the paired pocket **412**. See *e.g.*, **FIG. 3A** and **FIG. 3B**.

[0144] In some embodiments, release of each removable snap latch connection (left and right) may be accomplished by the user squeezing each terminal end **601** towards each other, which may disengage a given paired snap latch **605** from the paired pocket **412**. In some embodiments, release of clamp **600** from neck-gasket-ac-

commodator **400** may also require the user to pull clamp **600** upwards or away from neck-gasket-accommodator **400**. In some embodiments, there may be structure located proximate (e.g., within three inches) to each terminal end **601**; wherein such structure may aid or may facilitate removal (i.e., release) of clamp **600** from neck-gasket-accommodator **400**. For example, and without limiting the scope of the present invention, in some embodiments, this structure may be indentures, such as, divots, to removably receive a tool for pushing the two terminal ends **601** towards each other. See e.g., **FIG. 6A**, **FIG. 6B**, **FIG. 6C**, **FIG. 6G**, **FIG. 2A**, **FIG. 2B**, **FIG. 2D**, **FIG. 3A**, and **FIG. 3B**. For example, and without limiting the scope of the present invention, in some embodiments, this structure may be removably engage pressing fingers from the user for pushing (e.g., squeezing) the two terminal ends **601** towards each other.

[0145] Some embodiments may be characterized as a "flexible detachable vessel cover" that may comprise: (1) vessel **120** having a top opening and capable of holding the liquid; wherein vessel **120** has neck-gasket-accommodator **400**; and (2) a flexible sheet (e.g., vessel neck gasket **500**); wherein the flexible sheet that may be shaped generally to cover gasket-accommodator **400** of vessel **120**; wherein the flexible sheet has a gasket (e.g., mating edge **501**) along the bottom of the flexible sheet; and wherein the bottom of the gasket and a top of gasket-accommodator **400** of vessel **120** are arranged to mate tightly with one another to form the primary water tight seal.

[0146] **FIG. 8**, **FIG. 9**, **FIG. 10**, and **FIG. 11** may depict views and embodiments comparable against those shown in **FIG. 7**. **FIG. 8**, **FIG. 9**, **FIG. 10**, and **FIG. 11** may depict additional embodiments of the clamp, i.e., of clamp **800**, clamp **900**, clamp **1000**, and clamp **1100**, respectively, wherein such clamps may frictionally and removably snap onto an exterior vertical portion of neck-gasket-accommodator **400**. See e.g., **FIG. 8**, **FIG. 9**, **FIG. 10**, and **FIG. 11**. Compare the clamps of **FIG. 8**, **FIG. 9**, **FIG. 10**, and **FIG. 11** against clamp **600** of **FIG. 7**.

[0147] In some embodiments of face soaking device **100**, the clamp may be selected from: clamp **600**, clamp **800**, clamp **900**, clamp **1000**, clamp **1100**, or the like.

[0148] In **FIG. 8**, clamp **800** may removably and frictionally snap around the exterior vertical portion of neck-gasket-accommodator **400**. In some embodiments, to assist with this removable and frictional snap lock, clamp **800** may comprise a relatively short protrusion, tab **815**, which may protrude substantially perpendicularly from a vertical direction of clamp **800**, such that tab **815** may removably engage a bottom and outward edge of neck-gasket-accommodator **400**. In some embodiments, tab **815** may extend from the given clamp (e.g., clamp **800**) in a direction that may be substantially perpendicular from the major plane of side wall **121**. In some embodiments, tab **815** may snap onto a corner of the neck-gasket-accommodator **400**. In some embodiments, when a given clamp (e.g., clamp **800**) may be attached to neck-

gasket-accommodator **400**, tab **815** may protrude towards vessel **120**. See e.g., **FIG. 8**. Tab **815** may have a length that is less than the vertical lengths of clamp **800**. Tab **815** may be an integral structure of clamp **800**. In some embodiments, clamp **1000** and clamp **1100** may also comprise such a tab **815**. See e.g., **FIG. 10** and **FIG. 11**.

[0149] Continuing discussing **FIG. 8**, in some embodiments, clamp **800** may also comprise finger-pull **811**. Finger-pull **811** may be a vertically oriented finger pull, allowing the user to lift under finger-pull **811** when removing clamp **800** from neck-gasket-accommodator **400**. In some embodiments, finger-pull **811** may be a vertical extension of clamp **800**, extending below and beyond tab **815**, and below where neck-gasket-accommodator **400** ends. Finger-pull **811** may be an integral structure of clamp **800**. In cross-section as shown in **FIG. 8**, clamp **800** may resemble a stylized letter "f"; wherein the terminal of the ascender curves around to point towards receiving-channel **408**; the stem descends into finger-pull **811**; and there may only one arm being that of tab **815**.

[0150] Clamp **900** (shown in **FIG. 9**) and clamp **1000** (shown in **FIG. 10**) may each also comprise similar finger pulls, finger-pull **911** and finger-pull **1011**, respectively. Each of finger-pull **911** and finger-pull **1011**, may extend substantially perpendicularly away from wall **121** shown in **FIG. 9** and in **FIG. 10**, respectively. See e.g., **FIG. 9** and **FIG. 10**. A cross-section of clamp **900** may be "L" shaped, where one leg of the "L" is for removable insertion into receiving-channel **408** and the other leg of the "L" is finger-pull **911**. See **FIG. 9**. A cross-section of clamp **1000** may resemble an upside down letter "J." With clamp **1000**, finger-pull **1011** and tab **815** may be collinear but extending in opposite directions of each other, with finger-pull **1011** extending away from vessel **120** and with tab **815** extending towards vessel **120**. See **FIG. 10**.

[0151] Although all three finger pulls (e.g., finger-pull **811**, finger-pull **911**, and, finger-pull **1011**) may be structurally different, each may serve a similar or same purpose, in aiding the user in removing the given clamp from neck-gasket-accommodator **400**, by providing explicit structure to be engaged by fingers for pulling upwards and away from vessel **120**.

[0152] Additionally, clamp **800** may comprise chamfer **813**, which may be located a terminal portion of clamp **800** that is removably retained in receiving-channel **408**. Chamfer **813** may be a chamfer and may aid in inserting clamp **800** into receiving-channel **408** and against portions of vessel neck gasket **500** that also may removably reside within receiving-channel **408**. Clamp **600**, clamp **900**, clamp **1000**, and clamp **1100** may also comprise such a chamfer **813**. Chamfer **813** may also aid use of a given finger pull (e.g., finger-pull **811**, finger-pull **911**, and, finger-pull **1011**), by providing a small region of void space within receiving-channel **408**, such that when the user pulls on the given finger pull, the terminal end of the clamp within receiving-channel **408** may articulate (i.e.,

pivot) into this void region of the given receiving-channel 408.

[0153] Note, with respect to various clamps disclosed herein, such as, but not limited to, clamp 600, clamp 800, clamp 900, clamp 1000, and clamp 1100, these clamps may function technically as a wedge, when portions of such clamps may be removably inserted in receiving-channel 408, creating opposing lateral compression forces against portions of vessel neck gasket 500 (e.g., carrier 511 and flexible member 505) within receiving-channel 408, as well as against wall(s) of receiving-channel 408, which may be surfaces of contour 402. These lateral compression forces may compress portions of flexible member 505 as noted herein, which may aid in creating the primary water tight seal. See e.g., FIG. 7, FIG. 8, FIG. 9, FIG. 10, and FIG. 11. Additionally, portions of these clamps (e.g., clamp 600, clamp 800, clamp 900, clamp 1000, and clamp 1100), e.g., mating-wall-edge 603, which may be structure present on each of these clamps, may press against portions of receiving-channel 408, such as opposing opening wall-edge 410; and in this functional capacity these clamps may be acting as a clamp (as in a device that presses together so as to hold firmly) and/or as a wedge. That is, when any of these clamps may be inserted into receiving-channel 408, receiving-channel 408 and the portions of the clamp may be pressing against each other.

[0154] FIG. 12A through FIG. 12D may depict cross-sectional views of various clamps, such as clamp 800 in FIG. 12A; clamp 900 in FIG. 12B; clamp 1000 in FIG. 12C; and clamp 1100 in FIG. 12D. FIG. 12E may depict a cross-sectional view of neck-gasket-accommodator 400; which may comprise receiving-channel 408 that may receive portions (e.g., portions with chamfer 813) of the various clamps. FIG. 12A may show that clamp 800 may resemble a letter "I" in cross-section. FIG. 12B may show that clamp 900 may resemble a letter "L" in cross-section. FIG. 12C may show that clamp 1000 may resemble a letter "J" in cross-section. FIG. 12D may show that clamp 1100 may resemble a letter "C" in cross-section.

[0155] In some embodiments, a region comprising neck-gasket-accommodator 400 and comprising where neck-gasket-accommodator joins the side wall 121; wherein this region, in cross-section, resembles an Arabic number "4." See e.g., FIG. 12E, FIG. 7, FIG. 8, FIG. 9, FIG. 10, and FIG. 11.

[0156] In some embodiments, some face soaking device 100 component parts may be substantially constructed of one or more thermoplastics suitable for injection molding and/or 3D printing. For example, and without limiting the scope of the present invention, some face soaking device 100 component parts may be substantially constructed of one or more materials of acrylonitrile-butadiene styrene (ABS), polyvinyl chloride (PVC), polycarbonate, nylon, polypropylene, polyethylene (e.g., HDPE), elastomers, rubbers, silicones, fiberglass, and/or the like.

[0157] Note with respect to the materials of construction, it is not desired nor intended to thereby unnecessarily limit the present invention by reason of such disclosure.

[0158] Note, in some embodiments, such component parts as flexible member 505, carrier 511, and/or the various clamps (e.g., clamp 600 and clamp 900) may be manufactured with reliable and quality manufacturing methods of die cutting (stamping) which may be considerably less expensive as compared against creating the tooling for molds of such parts. And other clamp embodiments (e.g., clamp 600, clamp 800, clamp 900, clamp 1000, and clamp 1100), may be manufacturing by custom extrusion with cuts at appropriate lengths, which may be a reliable and quality manufacturing method that is less expensive than creating the tooling for molds of such parts.

[0159] Face soaking devices have been described. The foregoing description of the various exemplary embodiments of the invention has been presented for the purposes of illustration and disclosure. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching without departing from the spirit of the invention.

[0160] While the invention has been described in connection with what is presently considered to be the most practical and preferred embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

Claims

1. Components for forming a primary water tight seal comprising:

a neck-gasket-accommodator that is a first structural member located on a side wall of a vessel; wherein the neck-gasket-accommodator has a contour that tracks an open path that is below a top rim of the vessel; wherein extending into the contour is a receiving-channel; a vessel neck gasket with a mating edge; wherein at least portions of the mating edge fit within the receiving-channel; and a clamp that is a second structural member with a mating-wall-edge; wherein at least portions of the mating-wall-edge fit within the receiving-channel; wherein a width of a portion of the clamp, a width of vessel neck gasket, and a width of the receiving-channel are sized such that when the at least portions of the mating-wall-edge and the at least portions of the mating edge are received into the receiving-channel, the primary water tight seal

is formed between a portion of the receiving-channel and some portions of the vessel neck gasket.

2. The components for forming the primary water tight seal according to claim 1, wherein the open path of the contour is continuous. 5
3. The components for forming the primary water tight seal according to claim 1, wherein the open path of the contour is substantially shaped, as viewed from a front of the side wall, as one of the following: curved; rounded; semicircular; semi-elliptical; U-shaped; horseshoe shaped, semi-oval; an arc of a partial circle; an arc of a partial ellipse; an arc of a partial oval; one third to three thirds of a circle; one third to three thirds of an oval; one third to three thirds of an ellipse; or a shape approximating an open-ended polygon. 10
4. The components for forming the primary water tight seal according to claim 1, wherein a cross-section of the receiving-channel is substantially shaped as one of the following: curved; rounded; semicircular; semi-elliptical; U-shaped; horseshoe shaped, semi-oval; an arc of a partial circle; an arc of a partial ellipse; an arc of a partial oval; one third to three thirds of a circle; one third to three thirds of an oval; one third to three thirds of an ellipse; or a shape approximating an open-ended polygon. 15
5. The components for forming the primary water tight seal according to claim 1, wherein a direction that the receiving-channel extends into the contour is substantially parallel with a major plane of the side wall. 20
6. The components for forming the primary water tight seal according to claim 1, wherein a region comprising the neck-gasket-accommodator and comprising where the neck-gasket-accommodator joins the side wall; wherein this region, in cross-section, resembles an Arabic number "4." 25
7. The components for forming the primary water tight seal according to claim 1, wherein the vessel neck gasket comprises a flexible member and a carrier; wherein the flexible member is flexible and substantially planar; wherein the carrier is a third structural member that provides some rigidity to the flexible member; wherein the carrier is attached to the flexible member; wherein both the carrier and the flexible member share the mating edge. 30
8. The components for forming the primary water tight seal according to claim 7, wherein the flexible member is substantially elastomeric. 35
9. The components for forming the primary water tight seal according to claim 8, wherein when the at least portions of the mating-wall-edge and the at least portions of the mating edge are received into the receiving-channel, portions of the flexible-member within the receiving-channel are compressed which contributes to forming the primary water tight seal. 40
10. The components for forming the primary water tight seal according to claim 7, wherein the flexible member comprises a top edge wherein at least a portion of the top edge extends beyond the top rim of the vessel when the vessel neck gasket is attached to the receiving-channel; wherein the top edge and the mating edge of the flexible member define a closed shape for the flexible member. 45
11. The components for forming the primary water tight seal according to claim 7, wherein the carrier is rigid to semi-rigid. 50
12. The components for forming the primary water tight seal according to claim 7, wherein the carrier is shaped complimentary to a shape of the open path of the contour. 55
13. The components for forming the primary water tight seal according to claim 1, wherein the mating edge is shaped complimentary to a shape of the receiving-channel.
14. The components for forming the primary water tight seal according to claim 1, wherein the mating-wall-edge of the clamp has a chamfer to facilitate insertion into the receiving-channel.
15. The components for forming the primary water tight seal according to claim 1, wherein the clamp terminates in a finger-pull that is engageable by a finger of a user to remove the clamp from the receiving-channel.
16. The components for forming the primary water tight seal according to claim 1, wherein the clamp has a tab that extends from the clamp that is substantially perpendicular from a major plane of the side wall; wherein the tab snaps onto a corner of the neck-gasket-accommodator.
17. The components for forming the primary water tight seal according to claim 1, wherein the clamp is rigid to semi-rigid.
18. The components for forming the primary water tight seal according to claim 1, wherein a cross-section of the clamp resembles: a closed polygon; a letter "F"; a letter "L"; a letter "J"; or a letter "C".
19. The components for forming the primary water tight seal according to claim 1, wherein the clamp is rigid to semi-rigid.

seal according to claim 8, wherein when the at least portions of the mating-wall-edge and the at least portions of the mating edge are received into the receiving-channel, portions of the flexible-member within the receiving-channel are compressed which contributes to forming the primary water tight seal.

10. The components for forming the primary water tight seal according to claim 7, wherein the flexible member comprises a top edge wherein at least a portion of the top edge extends beyond the top rim of the vessel when the vessel neck gasket is attached to the receiving-channel; wherein the top edge and the mating edge of the flexible member define a closed shape for the flexible member.
11. The components for forming the primary water tight seal according to claim 7, wherein the carrier is rigid to semi-rigid.
12. The components for forming the primary water tight seal according to claim 7, wherein the carrier is shaped complimentary to a shape of the open path of the contour.
13. The components for forming the primary water tight seal according to claim 1, wherein the mating edge is shaped complimentary to a shape of the receiving-channel.
14. The components for forming the primary water tight seal according to claim 1, wherein the mating-wall-edge of the clamp has a chamfer to facilitate insertion into the receiving-channel.
15. The components for forming the primary water tight seal according to claim 1, wherein the clamp terminates in a finger-pull that is engageable by a finger of a user to remove the clamp from the receiving-channel.
16. The components for forming the primary water tight seal according to claim 1, wherein the clamp has a tab that extends from the clamp that is substantially perpendicular from a major plane of the side wall; wherein the tab snaps onto a corner of the neck-gasket-accommodator.
17. The components for forming the primary water tight seal according to claim 1, wherein the clamp is rigid to semi-rigid.
18. The components for forming the primary water tight seal according to claim 1, wherein a cross-section of the clamp resembles: a closed polygon; a letter "F"; a letter "L"; a letter "J"; or a letter "C".
19. The components for forming the primary water tight seal according to claim 1, wherein the clamp is rigid to semi-rigid.

seal according to claim 1, wherein the clamp and the vessel neck gasket are removable from the receiving-channel.

5

10

15

20

25

30

35

40

45

50

55




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F




FIG. 5G




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 6F




FIG. 6G




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D




FIG. 12E



EUROPEAN SEARCH REPORT

 Application Number
 EP 17 17 1599

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
Y	US 2016/096042 A1 (TAYLOR JOHN RICHARD [US]) 7 April 2016 (2016-04-07) * paragraphs [0054] - [0724]; figures 3C-3H *	1-19	INV. A61M35/00
Y	US 7 448 093 B1 (RUECK KLAUS-MICHAEL [DE]) 11 November 2008 (2008-11-11) * column 2, line 43 - column 3, line 15 *	1-19	
A	US 6 328 031 B1 (TISCHER MICHAEL SCOTT [US] ET AL) 11 December 2001 (2001-12-11) * columns 5-6; figures 7-9 *	1-19	
A	EP 2 868 218 A1 (SI TECH AB [SE]) 6 May 2015 (2015-05-06) * paragraphs [0057] - [0064]; figures 1b, 3b *	1-19	
			TECHNICAL FIELDS SEARCHED (IPC)
			A61M A61H A41D
The present search report has been drawn up for all claims			
Place of search Berlin		Date of completion of the search 13 November 2017	Examiner Dydenko, Igor
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

 1
 EPO FORM 1503 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 17 17 1599

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-11-2017

10

15

20

25

30

35

40

45

50

55

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2016096042	A1	07-04-2016	CA 2963664 A1	14-04-2016
			EP 3203971 A1	16-08-2017
			KR 20170067828 A	16-06-2017
			US 2016096042 A1	07-04-2016
			WO 2016057729 A1	14-04-2016

US 7448093	B1	11-11-2008	DE 102005045820 B3	14-09-2006
			GB 2430971 A	11-04-2007
			SE 0601155 A	25-03-2007
			US 7448093 B1	11-11-2008

US 6328031	B1	11-12-2001	US 6328031 B1	11-12-2001
			US 2002046752 A1	25-04-2002

EP 2868218	A1	06-05-2015	CA 2928607 A1	07-05-2015
			DK 2868218 T3	05-09-2016
			EP 2868218 A1	06-05-2015
			US 2016249689 A1	01-09-2016
			WO 2015062963 A1	07-05-2015

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 62351830 A [0001]
- US 87785615 A [0002]
- US 14964552 B [0002]
- US 1554576 W [0003] [0004]