



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**07.03.2018 Bulletin 2018/10**

(51) Int Cl.:  
**F21K 9/90 (2016.01) F21K 9/23 (2016.01)**

(21) Application number: **16187181.9**

(22) Date of filing: **05.09.2016**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB  
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO  
PL PT RO RS SE SI SK SM TR**  
Designated Extension States:  
**BA ME**  
Designated Validation States:  
**MA MD**

(71) Applicant: **Double Good Co.**  
**Hsinchu County (TW)**


(72) Inventor: **Fan, Szu-Min**  
**Hsinchu County (TW)**

(74) Representative: **Becker Kurig Straus**  
**Patentanwälte**  
**Bavariastrasse 7**  
**80336 München (DE)**

(54) **LED LIGHT BULB AND FABRICATION METHOD THEREOF**

(57) An LED light bulb (1) and a fabrication method thereof are provided. A plurality of power wires (111,112) for supplying electricity to an LED filament (12) are fixed to form a power wire supporting structure for supporting and fixing the LED filament (12) in position, without using a stem of a conventional LED light bulb, thereby simpli-

fying fabrication processes of the LED light bulb (1) and reducing fabrication costs thereof. Moreover, the LED light bulb does not require an internal space for accommodating the stem, and thus its length can be effectively reduced to ideally become a small-size light bulb.



**FIG. 4-5**

## Description

### BACKGROUND OF THE INVENTION

#### Field of the Invention

[0001] The invention relates to lighting fields, and more particularly, to an LED light bulb and a fabrication method thereof.

#### Descriptions of the Related Art

[0002] It is known that light-emitting diode (LED) light bulbs have many advantages such as lasting longer, more energy-efficient, more environmental friendly and reacting more rapidly, which make LED lighting gradually replace traditional lighting.

[0003] A fabrication method of a conventional LED light bulb is shown in Figure 1. First in step S21, a stem 21, an LED filament 22 and two power wires 23 shown in Figure 2-1 are provided. The stem 21 is used to support the LED filament 22. The stem 21 includes an exhaust tube 211 and a horn-shaped tube 212, wherein the exhaust tube 211 and the two power wires 23 pass through the horn-shaped tube 22. Then in step S22, as shown in Figure 2-2, two ends of the LED filament 22 are soldered to the two power wires 23 passing through the stem 21 to form a semi-finished LED light bulb 24. Then in step S23, as shown in Figure 2-3, a glass envelope 25 is provided to cover and protect a head part of the semi-finished LED light bulb 24. Then in step S24, as shown in Figure 2-4, a sealer is used to seal the glass envelope 25, and an exhausting machine is used to discharge redundant gas from the glass envelope 25 through the exhaust tube 211. Then in step S25, any unnecessary portion of the exhaust tube 211 is removed, and a screw base 26 is provided, making the two power wires 23 electrically connected to the screw base 26 respectively, thereby forming a finished LED light bulb 2 shown in Figure 2-5.

[0004] Therefore in the conventional LED light bulb 2, the stem 21 must be provided to support the LED filament 22, making the fabrication method of the LED light bulb 2 complicated and not cost-effective. As shown in Figure 2-5, the LED light bulb 2 also requires an internal space 22 for accommodating a front end 213 of the stem 21, such that the LED light bulb 2 cannot be significantly reduced in length and cannot replace all the small-size traditional light bulbs.

### SUMMARY OF THE INVENTION

[0005] In view of the shortages of prior technologies mentioned above, the invention provides an LED light bulb, including: a power wire support set, an LED filament, a glass envelope and a screw base. The power wire support set includes a first power wire, a second power wire and at least one fixed block. The fixed block fixes the first and second power wires to make them form

a power wire supporting structure. An LED filament having two ends respectively soldered to a first end of the first power wire and a first end of the second power wire, making the LED filament supported by the power wire supporting structure; a glass envelope including a head part having a receiving space for receiving the LED filament, and a tail part tapered to clamp and fix second ends of the first and second power wires in position; and a screw base electrically connected to the second ends of the first and second power wires.

[0006] Optionally, the LED light bulb has a plurality of fixed blocks. The fixed block is made of glass. The first and second power wires are dumet wires. The screw base is soldered to the second ends of the first and second power wires.

[0007] Moreover, the invention further provides A fabrication method of an LED light bulb, including the steps of: providing an LED filament and a power wire support set, wherein the power wire support set includes a first power wire, a second power wire and at least one fixed block, and the fixed block fixes the first and second power wires to make them form a power wire supporting structure; soldering two ends of the LED filament to a first end of the first power wire and a first end of the second power wire respectively to form a semi-finished LED light bulb; providing a glass envelope, wherein the glass envelope has a receiving space in a head part thereof and a passage in a tail part thereof, allowing the LED filament to pass through the passage to be received in the receiving space; tapering the tail part of the glass envelope and sealing the passage to clamp second ends of the first and second power wires; and providing a screw base, and electrically connecting the second ends of the first and second power wires respectively to the screw base, to form a finished LED light bulb.

[0008] Optionally, the fabrication method further includes the step of: discharging redundant gas from the receiving space through the passage. Removing an unnecessary portion of the tail part of the glass envelope.

[0009] Compared to the conventional technology, the invention provides an LED light bulb and a fabrication method thereof, wherein two power wires for supplying electricity are used in place of the stem in the conventional LED light bulb. The power wires support and fix an LED filament in position. Besides eliminating the need of making the stem, the invention desirably simplifies fabrication processes of the LED light bulb and thereby reduces its fabrication costs. Moreover, the LED light bulb of the invention does not require an internal space for accommodating the stem, and thus its length may be significantly reduced, making the LED light bulb ideally used as a small-size light bulb.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The above and other aspects, features and other advantages of the present invention will be more clearly understood from the following detailed description tak-

en in conjunction with the accompanying drawings, in which:

Figure 1 is a flowchart showing a fabrication method of a conventional LED light bulb.

Figures 2-1 to 2-5 are schematic diagrams showing an embodiment of the LED light bulb fabricated by the steps shown in Figure 1.

Figure 3 is a flowchart showing a fabrication method of an LED light bulb according to the invention.

Figures 4-1 to 4-5 are schematic diagrams showing an embodiment of the LED light bulb fabricated by the steps shown in Figure 3.

#### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

[0011] Embodiments of the present invention will now be described in detail with reference to the accompanying drawings. The invention may, however, be embodied in many different forms and should not be construed as being limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. In the drawings, the shapes and dimensions of elements may be exaggerated for clarity, and the same reference numerals will be used throughout to designate the same or like components.

[0012] An embodiment of an LED light bulb according to the invention and a fabrication method thereof are disclosed with reference to Figures 3 to 4-5.

[0013] The fabrication method of the LED light bulb according to the invention includes the following steps shown in Figure 3.

[0014] In step S11, as shown in Figure 4-1, an LED filament 12 and a power wire support set 11 are provided. The power wire support set 11 includes a first power wire 111, a second power wire 112 and at least one fixed block 113. The first and second power wires 111, 112 are electrical conductors and can be dumet wires. There may be provided one or more fixed blocks 13, which can be made of glass. The fixed block 13 is used to fix the first and second power wires 111, 112 to integrally combine them to form a power wire supporting structure.

[0015] In step S12, as shown in Figure 4-2, the LED filament 12 has two ends thereof respectively soldered to a first end E1 of the first power wire 111 and a first end E1 of the second wire 112, such that the LED filament 12 may obtain electricity through the first and second power wires 111, 112 and support from the power wire supporting structure to be properly fixed in position. This forms a semi-finished LED light bulb 15.

[0016] In step S13, as shown in Figure 4-3, a glass envelope 13 is provided, wherein a head part 131 of the glass envelope 13 has a receiving space 1311, and a tail part 132 of the glass envelope 13 has a passage 1321 connected to the receiving space 1311. The LED filament

12 and the fixed block 113 may pass through the passage 1321 to be received in the receiving space 1311 and thus be protected by the glass envelope 13.

[0017] In step S14, as shown in Figure 4-4, redundant gas in the receiving space 1311 is discharged through the passage 1321 so as to prevent moisture from staying in the operating environment of the LED filament 12. Then the tail part 132 of the glass envelope 13 is tapered and the passage 1321 is sealed in a manner to clamp second ends E2 of the first and second power wires 111, 112. Any unnecessary portion of the tail part 132 of the glass envelope 13 is removed.

[0018] In step S15, as shown in Figure 4-5, a screw base 14 is provided. The second ends E2 of the first and second power wires 111, 112 are electrically connected to the screw base 14 respectively, thereby forming a finished LED light bulb 16.

[0019] Figure 4-5 also shows the structure of the LED light bulb according to the invention. The LED light bulb 1 includes: a power wire support set 11, an LED filament 12, a glass envelope 13 and a screw base 14. The LED filament 12 has an operating voltage of from 8V to 240V. The power wire support set 11 includes a first power wire 111, a second power wire 112 and at least one fixed block 113. The first and second power wires 111, 112 provide a path of electricity to the LED filament 12. The screw base 14 is used to electrically connect an external power source. The first and second power wires 111, 112 may be made of dumet wires. The first and second power wires 111, 112 have first ends E1 thereof being soldered to two ends of the LED filament 12 respectively and have second ends E2 thereof being electrically connected to the screw base 14 respectively.

[0020] The fixed block 113 may be, for example, a glass ball, for fixing the first and second power wires 111, 112 to make them form a power wire supporting structure, which is used to provide support for the LED filament 12. The fixed block 113 can have a ball shape or any other shape that is easily made. A head part 131 of the glass envelope 13 has a receiving space 1311 where the LED filament 12 and the fixed block 113 are received. The receiving space 1311 may be filled with inert gas. A tail part 132 of the glass envelope 13 is tapered to clamp the second ends E2 of the first and second power wires 111, 112 so as to properly fix the first and second power wires 111, 112 in position and keep the receiving space 1311 intact.

[0021] Therefore, the invention provides an LED light bulb and a fabrication method thereof, wherein power wires for supplying electricity to an LED filament are used to support and fix the LED filament in position, such that a stem used in a conventional LED light bulb is not needed. This desirably simplifies fabrication processes of the LED light bulb and thereby reduces its fabrication costs. Moreover, the LED light bulb of the invention does not require an internal space for accommodating the stem, and thus its length may be significantly reduced, making the LED light bulb ideally used as a small-size light bulb.

**[0022]** The examples above are only illustrative to explain principles and effects of the invention, but not to limit the invention. It will be apparent to those skilled in the art that modifications and variations can be made without departing from the scope of the invention. Therefore, the protection range of the rights of the invention should be as defined by the appended claims.

## Claims

### 1. An LED light bulb (1), including:

a power wire support set (11) including a first power wire (111), a second power wire (112) and at least one fixed block (113), wherein the fixed block (113) fixes the first and second power wires (111, 112) to make them form a power wire supporting structure;  
 an LED filament (12) having two ends respectively soldered to a first end (E1) of the first power wire (111) and a first end (E1) of the second power wire (112), making the LED filament (12) supported by the power wire supporting structure;  
 a glass envelope (13) including a head part (131) having a receiving space (1311) for receiving the LED filament (12) and the fixed block (113), and a tail part (132) tapered to clamp and fix second ends (E2) of the first and second power wires (111, 112) in position; and  
 a screw base (14) electrically connected to the second ends (E2) of the first and second power wires (111, 112).

2. The LED light bulb (1) according to claim 1, wherein the LED light bulb (1) has a plurality of fixed blocks (113).

3. The LED light bulb (1) according to claim 1, wherein the fixed block (113) is made of glass.

4. The LED light bulb (1) according to claim 1, wherein the first and second power wires (111, 112) are dumet wires.

5. The LED light bulb (1) according to claim 1, wherein the screw base (14) is soldered to the second ends (E2) of the first and second power wires (111, 112).

6. A fabrication method of an LED light bulb (1), including the steps of:

providing an LED filament (12) and a power wire support set (11), wherein the power wire support set (11) includes a first power wire (111), a second power wire (112) and at least one fixed block (113), and the fixed block (113) fixes the first

and second power wires (111, 112) to make them form a power wire supporting structure; soldering two ends of the LED filament (12) to a first end (E1) of the first power wire (111) and a first end (E1) of the second power wire (112) respectively to form a semi-finished LED light bulb (15);

providing a glass envelope (13), wherein the glass envelope (13) has a receiving space (1311) in a head part (131) thereof and a passage (1321) in a tail part (132) thereof, allowing the LED filament (12) and the fixed block (113) to pass through the passage (1321) to be received in the receiving space (1311);

tapering the tail part (132) of the glass envelope (13) and sealing the passage (1321) to clamp second ends (E2) of the first and second power wires (111, 112); and

providing a screw base (14), and electrically connecting the second ends (E2) of the first and second power wires (111, 112) respectively to the screw base (14), to form a finished LED light bulb (16).

7. The fabrication method according to claim 6, further including the step of: discharging redundant gas from the receiving space (1311) through the passage (1321).

8. The fabrication method according to claim 6, further including the step of: removing an unnecessary portion of the tail part (132) of the glass envelope (13).




FIG . 1(Prior Art)




FIG.2-1(Prior Art)




FIG.2-2(Prior Art)




FIG.2-3(Prior Art)




FIG.2-4(Prior Art)

2




FIG.2-5(Prior Art)






FIG . 3




FIG . 4-1




FIG . 4-2




FIG . 4-3




FIG . 4-4




FIG . 4-5



## EUROPEAN SEARCH REPORT

Application Number  
EP 16 18 7181

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 2015/069442 A1 (LIU HONG-ZHI [TW] ET AL) 12 March 2015 (2015-03-12) * figure 6 *	1,2,6	INV. F21K9/90 F21K9/23
X	----- CN 203 907 532 U (HUIZHOU VERY LIGHT SOURCE TECHNOLOGY CO LTD; HUARUI OPTOELECTRONICS HU) 29 October 2014 (2014-10-29) * figures 4,5 *	1,6	
X	----- US 2013/155683 A1 (MATSUDA TSUGIHIRO [JP] ET AL) 20 June 2013 (2013-06-20) * figures 13-15 *	1-8	
X	----- WO 2013/014821 A1 (PANASONIC CORP [JP]; SETOMOTO TATSUMI; MATSUDA TSUGIHIRO; MIKI MASAHIR) 31 January 2013 (2013-01-31) * figure 48 *	1-3,6-8	
X	----- CN 101 968 181 A (SHICHAO GE) 9 February 2011 (2011-02-09) * figures 3,4 *	1,6	TECHNICAL FIELDS SEARCHED (IPC)
X	----- CN 102 980 054 B (WANG YUANCHENG) 22 October 2014 (2014-10-22) * figure 2 *	1,2,5-8	F21K
A	----- US 2012/098429 A1 (LIANG CHING-LONG [TW]) 26 April 2012 (2012-04-26) * figure 1 *	1,6	
A	----- EP 2 108 880 A2 (LIQUIDLEDS LIGHTING CORP [KY]) 14 October 2009 (2009-10-14) * figures 1-9 *	1,6	
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 18 October 2016	Examiner Kebemou, Augustin
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 16 18 7181

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-10-2016

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2015069442 A1	12-03-2015	CN 104425476 A	18-03-2015
		JP 2015056667 A	23-03-2015
		TW 201510440 A	16-03-2015
		US 2015069442 A1	12-03-2015
-----			
CN 203907532 U	29-10-2014	NONE	
-----			
US 2013155683 A1	20-06-2013	CN 103080632 A	01-05-2013
		EP 2636939 A1	11-09-2013
		JP 5511977 B2	04-06-2014
		US 2013155683 A1	20-06-2013
		WO 2012060058 A1	10-05-2012
-----			
WO 2013014821 A1	31-01-2013	JP 5129413 B1	30-01-2013
		JP 5491601 B2	14-05-2014
		JP 2013048106 A	07-03-2013
		JP WO2013014821 A1	23-02-2015
		WO 2013014821 A1	31-01-2013
-----			
CN 101968181 A	09-02-2011	NONE	
-----			
CN 102980054 B	22-10-2014	NONE	
-----			
US 2012098429 A1	26-04-2012	NONE	
-----			
EP 2108880 A2	14-10-2009	EP 2108880 A2	14-10-2009
		JP 2009231276 A	08-10-2009
		KR 20090101082 A	24-09-2009
		TW 200940897 A	01-10-2009
		US 2009236992 A1	24-09-2009
		US 2012212137 A1	23-08-2012
-----			