



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 71

(51) Int Cl.:
H01R 12/57 (2011.01) H01R 13/24 (2006.01)

(86) International application number:
PCT/KR2016/003980

(48) Corrigendum issued on:
01.08.2018 Bulletin 2018/31

(87) International publication number:
WO 2017/026625 (16.02.2017 Gazette 2017/07)

(43) Date of publication:
13.06.2018 Bulletin 2018/24

(21) Application number: **16834165.9**

(22) Date of filing: **18.04.2016**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
MA MD

(72) Inventors:
• **KIM, Sun-Ki**
Gunpo-si
Gyeonggi-do 15823 (KR)
• **PARK, Kee-Han**
Ansan-si
Gyeonggi-do 15613 (KR)

(30) Priority: **07.08.2015 KR 20150111612**
02.09.2015 KR 20150124490
16.09.2015 KR 20150131270

(74) Representative: **Kuhnen & Wacker**
Patent- und Rechtsanwaltsbüro PartG mbB
Prinz-Ludwig-Straße 40A
85354 Freising (DE)

(71) Applicant: **Joinset Co., Ltd**
Ansan-si, Gyeonggi-do 15613 (KR)

(54) **ELECTRICAL CONNECTING TERMINAL**

(57) Disclosed is an electric connecting terminal, which is intervened between electric conductive objects to electrically connect the objects to each other, the electric connecting terminal including a spring of a metallic material, and a contact part having electric conductivity, which is formed by being adhered to at least one end of the spring and configured to electrically contact the object, wherein the contact part is formed by that the electric conductive material in which a liquid polymer resin is mixed with metallic power surrounds the end of the spring to be cured or flows into an end hole of the spring to be cured.

FIG. 1

