



Europäisches  
Patentamt  
European  
Patent Office  
Office européen  
des brevets



(11)

EP 3 513 854 A1

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
24.07.2019 Bulletin 2019/30

(51) Int Cl.:  
**B01D 17/04** (2006.01)      **B01D 17/06** (2006.01)

(21) Application number: 18204461.0

(22) Date of filing: 07.06.2013

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB  
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO  
PL PT RO RS SE SI SK SM TR**

(30) Priority: 08.06.2012 US 201213491890

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:  
**13729236.3 / 2 858 732**

(71) Applicant: **Cameron International Corporation**  
**Houston, TX 77027 (US)**

(72) Inventors:  
• **SAMS, Gary W.**  
**Spring, Texas 77379 (US)**

- **WALLACE, Harry G.**  
Tulsa, Oklahoma 74137 (US)
- **TAGGART, Davis L.**  
Houston, Texas 77041 (US)
- **MANEN, David R**  
Okemah, Oklahoma 74859 (US)
- **TREVAS, David A.**  
Houston, Texas 77096 (US)

(74) Representative: **Schlumberger Intellectual Property Department**  
**Parkstraat 83**  
**2514 JG Den Haag (NL)**

### Remarks:

This application was filed on 05-11-2018 as a divisional application to the application mentioned under INID code 62.

### (54) HIGH VELOCITY ELECTROSTATIC COALESCING OIL/WATER SEPARATOR

(57) An apparatus and method for separating water from an oil-and-water mixture includes at least two elongated separator vessels (64, 66) oriented at an incline and connected to one another so that an upwardly flowing oil predominant fluid passes from the first separator vessel (64) to the second separator vessel (66) where further electrostatic separation of water from the oil predominant fluid occurs. Each vessel has an electrode (60) at its upper end preferably connected to a different voltage

source. The inlet to each vessel is located relative to the electrode (60) to provide an up flow or a down flow vessel. Additionally, the first vessel (64) may be at a different elevation than the second vessel. An additional vessel may be included with output from the first vessel bypassing the additional vessel, the second vessel, or both. Baffles (134) may be added in the water collection portion (138) of each vessel to reduce turbulence and settling distance.




Fig. 4

**Description****FIELD OF THE INVENTION**

5 [0001] This invention is in the field of electrostatic coalescence of immiscible components of a mixture, and is particularly related to the separation of water from a water-and-oil mixture.

**BACKGROUND OF THE INVENTION**

10 [0002] One of the world's most useful sources of energy is crude oil, derived from subterranean formations. When crude oil arrives at the earth's surface it is typically in the form of a water-and-oil mixture. That is, crude oil invariably has associated water that must be separated before the oil component can be efficiently refined into useful commercially acceptable products.

15 [0003] A common technique for improving the effectiveness of oil/water separation is by use of coalescence - that is a technique of joining together smaller into larger water droplets that are more readily separated from the mixture. As water droplet size increases, the dynamics of gravitational separation improve. One method of augmenting coalescence of water droplets is by subjecting the mixture to an electric field. Oil, being a non-polar fluid, acts as a dielectric and water droplets, being polar, when subjected to an electric field are coalesced. Coalescence is usually practiced by establishing an electric field between electrodes and passing an oil-in-water mixture through the electric field. Since 20 water is slightly polar, water droplets become polarized by the electric field. Polarized droplets are attracted to each other and move into and coalesce with each other. Larger droplets tend to gravitate downwardly within the mixture and the oil, having portions of the water removed therefrom, tend to gravitate upwardly within the mixture.

25 [0004] Much work has been done in the area of electrostatic coalescence of a mixture to augment separation of oil and water components. Background information relating to the inventive subject matter contained herein can be obtained from the following United States patents:

Patent Number	Inventor	Title
1,116,299	Laird et al.	Process of treating petroleum emulsions
1,276,387	McKibben	Method of separating associated liquids
1,838,931	Fisher	Apparatus for converting commercial frequency circuits into high frequency circuits
2,120,932	Dillon	High frequency induction dehydrator
2,849,395	Wintermute	Method and apparatus for electrical separation of emulsions
3,772,180	Prestridge	Electric treater
3,839,176	McCoy	Method and apparatus for removing contaminants from liquids
3,847,775	Prestridge	Process for electrical coalescing of water
4,126,537	Prestridge	Method and apparatus for separation of fluids with an electric field
4,161,439	Warren et al.	Apparatus for application of electrostatic fields to mixing and separating fluids
4,200,516	Pope	Electrostatic coalescing system
4,204,934	Warren et al.	Process for application of electrostatic fields to mixing and separating fluids
4,224,124	Pope	Electrostatic coalescing system
4,283,290	Davies	Purification utilizing liquid membrane with electrostatic coalescence
4,290,882	Dempsey	Electrostatic separation of impurities phase from liquid-liquid extraction
4,308,127	Prestridge	Separation of emulsions with electric field
4,400,253	Prestridge	Voltage control system for electrostatic oil treater
4,415,426	Hsu et al.	Electrodes for electrical coalescence of liquid emulsions
4,417,971	Ferrin et al.	Circuit for maintaining the strength of an electrostatic field generated in a fluid mixture of varying dielectric strength

(continued)

Patent Number	Inventor	Title
4,469,582	Sublette et al.	Electrically enhanced inclined plate separator
4,479,161	Henrich et al.	Switching type driver circuit for fuel injector
4,581,119	Rajani et al.	Apparatus for separating a dispersed liquid phase from a continuous liquid phase by electrostatic coalescence
4,581,120	Sublette	Method and apparatus for separating oilfield emulsions
4,601,834	Bailes et al.	Settling of liquid dispersions
4,606,801	Prestridge et al.	Electrostatic mixer/separator
4,702,815	Prestridge et al.	Distributed charge composition electrodes and desalting system
4,747,921	Bailes	Liquid-liquid contacting
4,767,515	Scott et al.	Surface area generation and droplet size control in solvent extraction systems utilizing high intensity electric fields
4,804,453	Sublette et al.	Resolution of emulsions with multiple electric fields
5,147,045	Chi et al.	Particulate separations by electrostatic coalescence
5,411,651	Yamaguchi et al.	Method for electrostatic liquid/liquid contactor
5,421,972	Hickey et al.	Process and apparatus for removing soluble contaminants from hydrocarbon streams
5,464,522	Mac Edmondson	Electrostatic oil emulsion treating method and apparatus
5,543,027	Yamaguchi et al.	Apparatus for electrostatic liquid/liquid contactor
5,565,078	Sams et al.	Apparatus for augmenting the coalescence of water in a water-in-oil emulsion
5,575,896	Sams et al.	Method and apparatus for oil/water separation using a dual electrode centrifugal coalescer
5,643,431	Sams et al.	Method for augmenting the coalescence of water in a water-in-oil emulsion
5,824,203	Remo	Method and means for changing characteristics of substances
6,010,634	Sams et al.	System and method for separating mingled heavier and lighter components of a liquid stream
6,113,765	Wagner et al.	Methods for enhanced resolution of hydrocarbon continuous emulsions or dispersions with conductivity modifiers
6,860,979	Sams	Dual Frequency Electrostatic Coalescence

## BRIEF SUMMARY OF THE INVENTION

[0005] This invention provides a method and apparatus for separating water from a water-and-oil mixture. The invention is particularly useful for separating water from crude oil. A great deal of the energy consumed on the earth today is derived from crude oil that is found in subterranean deposits and brought to the earth's surface by wells. When the crude oil reaches the earth's surface it invariably is in the form of a water-and-oil mixture. That is, crude oil is usually found associated with water. In order to successfully and economically transport, refine and make use of crude oil, one of the first requirements after the crude oil is brought to the earth's surface is to separate out and properly dispose of the water content. Methods and various systems for accomplishing this are illustrated and described herein.

[0006] One embodiment of this invention includes an elongated inlet vessel having a lower outlet end and an upper inlet end. The elongated inlet vessel can typically be in the form of a pipe, the diameter of which will be determined by the quantity of crude oil to be processed. While the pipe is an example of a readily available elongated vessel, the cross-section of the elongated vessel can be square, rectangular or other shape but for all practical purposes a pipe functions completely satisfactory and is readily available and inexpensive.

[0007] A second element making up the apparatus of this invention is a separation vessel that has an upper oil outlet,

a lower water outlet and an intermediate inlet passageway. As with the inlet vessel, the separation vessel can, by example, be a length of pipe having a circular cross-section and the diameter of the separation vessel can typically be the same or substantially the same as the diameter of the inlet vessel. The separation vessel typically is elongated with respect to the diameter and may typically be about the same in length as the inlet vessel.

**[0008]** At least one electrode is positioned with the inlet vessel by which a mixture flowing therethrough is subjected to an electric field. The electrode may be, as an example, in the form of a coil conductor that receives the voltage applied through an insulator in the wall of the inlet vessel. The voltage may be applied between the electrode and the inlet vessel itself when the inlet vessel is a metallic conductor. The electrode may be insulated or in appropriate applications may be bare, that is in electrical contact with the mixture liquid flowing through the inlet.

**[0009]** The separator functions by providing short liquid flow paths. A mixture, after being subjected to an electric field within an inlet vessel is immediately passed to a separation vessel where passageways are provided for downward flow of separated water and upward flow of oil having a substantial portion of the water extracted therefrom.

**[0010]** The apparatus for separating water from a water-and-oil mixture may be arranged in series relationship whereby the percentage of water removed from the mixture is increased or may be arranged in a parallel relationship to adjust for varying quantities of crude oil being treated.

**[0011]** Another embodiment of this invention includes a first and a second elongated separator vessel both oriented on an incline and connected to one another so that the oil predominant flow exiting the outlet of the first vessel enters the inlet of the second vessel, where it is once again exposed to an electric field. Substantially dry oil then exits the second vessel. The water-and-oil mixture preferably enters the first vessel below the electrode but above the water level control in the lower end or water collection portion of the vessel. At least one of the separator vessels includes a plurality of baffles arranged parallel one another in the water collection portion of the vessel. The baffles may be horizontal, vertical, or, preferably, angled.

**[0012]** The first vessel may be arranged so that it is at the same elevation as that of the second vessel or at a different elevation. The inlet of the first or second vessel may be located below the electrode and above the water level control or it may be located at its upper end, thereby making the vessel a down flow vessel. A pretreatment or degasser unit may be connected to the inlet of the first elongated separator vessel.

**[0013]** The first vessel can run a bare electrode in circuit relationship to an AC voltage source at a lower potential. The ability to use a bare electrode is one advantage of the first vessel being an upflow vessel, the flow being pre-treated in the AC field. The moderate water fraction of the mixture exiting the first vessel and entering the second vessel, which can be an upflow or downflow vessel, allows for the use of an insulated electrode which may be in circuit relationship to a DC voltage source at a higher potential. The voltage source may include reactance. The second vessel could also use a bare electrode when configured as an upflow vessel.

**[0014]** A method of separating water from the water-and-oil mixture includes the steps of:

- 35 (a) flowing the water-and-oil mixture into an inlet of a first elongated separator vessel, the first elongated separator vessel being oriented on an incline and having an outlet and an electrode located toward its upper end;
- (b) passing the mixture through an electric field of the first elongated separator vessel whereby water in the water-and-oil mixture coalesces and a first water predominant fluid flows downward;
- 40 (c) flowing a portion of the first oil predominant fluid out of the outlet of the first elongated separator vessel and into an inlet of a second elongated separator vessel, the second elongated separator vessel being oriented on an incline and having an electrode located toward its upper end;
- (d) passing the portion of the first oil predominant fluid through an electric field of the second elongated separator vessel whereby water in the oil predominant fluid coalesces and a second water predominant fluid flows downward.

**[0015]** The inlet of each separator vessel is preferably arranged relative to the electrode of the vessel to provide for a desired direction of flow, either an up flow or a down flow, for the passing steps (b) and (d). A portion of the first oil predominant fluid flowing out of the outlet of the first elongated separator vessel and into the inlet of a second or third elongated separator vessel may be a wet oil or a medium-wet oil portion. A second portion of the first oil predominant fluid may also be passed through an outlet and along a path which bypasses the second (or other subsequent) elongated separator vessels.

**[0016]** A better understanding of the invention will be obtained from the following detailed description of the preferred embodiments taken in conjunction with the drawings and the attached claims.

## 55 BRIEF DESCRIPTION OF THE DRAWINGS

**[0017]** Preferred embodiments of the invention will now be described in further detail. Other features, aspects, and advantages of the present invention will become better understood with regard to the following detailed description,

appended claims, and accompanying drawings (which are not to scale) where:

Figure 1 is an elevational view of a basic system for practicing the essence of the invention.

5 Figure 2 is an alternate view of a basic system of the invention herein. Figure 2 shows a tubular inlet vessel having an electrode therein by which a mixture is subjected to an electrostatic field and divergent water collection and oil collection portions in communication with oil treatment process and water treatment process vessels.

Figure 3 is another alternate embodiment of the basic concept of the invention wherein the separation vessel is vertical with an upper product outlet and a lower water outlet.

10 Figure 4 is an elevational view of an embodiment of the invention showing how basic systems used to practice the invention may be placed in series to achieve greater completeness of separation of water from the mixture. Further, Figure 4 illustrates an inlet manifold and an outlet manifold that can be used so that the system extending between the manifold may be repeated in parallel to thereby adapt the system for increase volume applications.

Figure 5 shows a desalter embodiment of the invention wherein a separation system is used in an application for extraction of salt from a mixture.

15 Figure 6 shows another desalter system and illustrates how two of the basic separation systems of the invention may be employed in a network to provide more thorough water separation and salt removal.

Figure 7 is a diagrammatic view showing how the basic arrangement of Figure 2 may be repeated multiple times as necessary depending upon the level of dehydration required of the system. As an example, Figure 4 illustrates two basic systems in sequence whereas Figure 7 shows diagrammatically three basic systems in sequence.

20 Figure 8 illustrates another embodiment of the invention wherein the basic separation system of the invention follows an inlet structure particularly useful in extracting gas from the inlet mixture and wherein two basic separation systems, the first like Figure 2 and the second like Figure 1, are employed in series.

Figure 9 illustrates another embodiment of the invention wherein the separation vessel is oriented at about 22.5° relative to horizontal.

25 Figures 10, 11 and 12 provide cross-sectional views of alternate embodiments of the electrode. Figure 10 illustrates a rod-type electrode configuration. Figure 11 illustrates a coil-type electrode configuration. Figure 12 illustrates a plate-type electrode configuration.

Figure 13 is an alternate embodiment of the basic system for practicing the invention as first disclosed in Figure 1. This embodiment employs a horizontal transition section between the inlet vessel and the oil collection portion to

30 reduce turbulence where the flow of separated water diverges from the flow of separated oil.

Figure 14 is an alternate embodiment of a system for separating water from a water-and-oil mixture. Two up flow stages are arranged one above the other, each having the wet oil inlet located below the electrode.

35 Figures 15 to 15B illustrate another alternate embodiment in which two up flow stages are arranged next to (or horizontal with) one another. Similar to the system of Figure 14, the wet oil inlet to each stage is located below the electrode.

Figure 16 illustrates the system of Figure 14 equipped with an optional degasser/pretreatment unit connected to the inlet of the first up flow stage.

Figure 17 is a partial cross-section view of the water leg portion of each stage of Figure 15 illustrating a plurality of baffles designed to improve water quality.

40 Figure 18 illustrates the system of Figure 15 equipped with an optional degasser/pretreatment unit connected to the inlet of the first up flow stage.

Figures 19 to 21 provide cross-sectional views of various baffle arrangements that may be provided in the water leg portion of the up flow stages of Figure 14 and 15.

45 Figure 22 is yet another alternate embodiment of a system for separating water from a water-and-oil mixture. The first stage is an up flow stage. The second stage is a down flow stage.

Figure 23 is a view of the embodiment illustrated in Figure 22 and taken along section line 23-23 of Figure 22.

Figure 24A is another alternate embodiment of a system for separating water from a water-and-oil mixture. Two down flow stages are preceded by degasser/pretreatment unit connected to the inlet of the first down flow stage.

50 Figure 24B is an alternate embodiment of the system of Figure 24A. Because of the relatively low pressure drop experienced across the stages, the separator vessels are plumbed to a single header and controlled with a single level control.

Figure 25 is a schematic illustrating yet another alternate embodiment of a system made according to this invention for separating water from a water-and-oil mixture. An additional outlet is provided to the first stage which allows oil that is dry enough to meet a user's requirements to bypass the second stage.

55 Figure 26 is a schematic illustrating another alternate embodiment in which an additional outlet is provided at the first and second stages to allow dry oil to bypass a subsequent stage.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0018] It is to be understood that the invention that is now to be described is not limited in its application to the details of the construction and arrangement of the parts illustrated in the accompanying drawings. The invention is capable of other embodiments and of being practiced or carried out in a variety of ways. The phraseology and terminology employed herein are for purposes of description and not limitation.

[0019] Elements shown by the drawings are identified by the following numbers:

10	10	Inlet vessel	78	Third separation system
	12	Lower outlet end	80	T-fitting
	14	Upper inlet end	82	Wash water inlet
	16	Electrode	84	Outlet
	18	Separation vessel	86	Mixing valve
15	20	Upper oil outlet end	88	Inlet
	22	Lower water outlet end	90	Desalter vessel
	24	Inlet passageway	92	Water outlet
	26	Inlet flange fitting	94	Oil outlet
20	28	Outlet flange fitting	96	Inlet
	30	Pipe outlet fitting	98	Preliminary separator
	32	Inlet longitudinal axis	100	Gas outlet
	34	Separation vessel longitudinal axis	102	Valve
	36	Water collection portion	104	3 phase voltage
25	38	Water level	106	Rectifier
	40	Water level control	108	DC Bus
	42	Oil collection portion	110	Modulator
	44	Voltage source	112	Conductors
	46	Conductor	114	Chopper
30	48	Conductor	116	Primary
	50	Insulator	118	Transformer
	52	Water inlet	120	Secondary
	54	Water treatment process vessel	122	Ground
35	56	Oil outlet	124	Conductor
	58	Oil treatment process vessel	124	Horizontal transition vessel
	60	Second electrode	128	Tee fitting
	62	Inlet manifold	130	First separation system/vessel
	64	First separation system	132	Second separation system/vessel
40	66	Second separation system	134	Baffle
	68	Outlet manifold	136	Degassifier or pretreatment unit
	70	Gas outlet	138	Water collection portion
	72	Piping	140	Third separation system/vessel
45	74	First separation system	142	Dry oil path
	76	Second separation system	144	Medium oil path

[0020] The basic concept of the invention is illustrated in its simplest embodiment in Figure 1. Basically the invention includes an elongated inlet vessel 10 having a lower outlet end 12 and an upper inlet end 14. Positioned within inlet vessel 10 is an electrode 16 that provides an electrostatic field through which inlet liquid, identified in Figure 1 as "feed", flows. In Figure 1 electrode 16, shown in dotted outline, is positioned within vessel 10 in which the vessel 10 is of conductive material, that is metal, so that the electrostatic field is established between electrode 16 and the wall of vessel 10.

[0021] Inlet vessel 10 is elongated, that is, it has a length measured from the upper inlet end 14 to the lower outlet end 12 that is a multiple of the largest vessel cross-sectional dimension. In the illustrated arrangement of Figure 1 the inlet vessel 10 is in the form of a pipe, that is, a vessel that, in cross-section, is round. The length of vessel 10 should preferably be about twice the vessel diameter, however the precise length is not a critical essence of the invention except that it is important that the vessel 10 be elongated so that fluid flowing therethrough is exposed for a minimum length of

time to the electrostatic field established by electrode 16.

[0022] A second basic element of the apparatus of Figure 1 is a separation vessel 18. Vessel 18 has an upper oil outlet end 20 and a lower water outlet end 22. Further, separation vessel 18 has an intermediate inlet passageway 24 that communicates with the inlet vessel lower outlet end 12.

[0023] As the invention is illustrated in Figure 1, an inlet flange fitting 26 is secured to the upper inlet end of inlet vessel 10 and a similar outlet flange fitting 28 is secured to the upper oil outlet end 20 of separation vessel 18. Flange fittings 26 and 28 provide convenient devices for connecting the system of Figure 1 to piping but are not otherwise involved in the performance of the system. In like manner, the lower water outlet end 22 of separation vessel 18 is provided with a pipe fitting 30 by which water separated by the system may be carried away for disposal or further treatment.

[0024] In the embodiment of the invention as revealed in Figure 1, a mixture of oil and water, designated as "feed" enters the system by way of inlet flange fitting 26 where it passes into inlet vessel 10. The mixture flows through the elongated inlet vessel that is preferably downwardly sloped as indicated. Sloping the inlet vessel helps allow a high liquid flux past the electrodes. Within the inlet vessel the mixture is exposed to an electrostatic field. If electrode 16 within the inlet vessel is covered with insulation then electricity is not directly conducted from the electrode 16 to the mixture but instead only an electrostatic field is maintained within vessel 10 to which the mixture is exposed. By the use of an insulated electrode 16 the voltage between the electrode and the wall of vessel 10 can be significant so that an electrostatic field is applied to the inlet mixture. The electrostatic field causes water droplets within the mixture to rapidly coalesce. The mixture, with a significant portion of the water therein coalesced into large droplets immediately passes directly into separator vessel 18 that preferably is at an angle perpendicular to the longitudinal axis of inlet vessel 10. In Figure 1 the longitudinal axis of inlet vessel 10 is indicated by the numeral 32 while the longitudinal axis of separation vessel 18 is indicated by the numeral 34.

[0025] The mixture having been subjected to an electrostatic field and therefore having passed through an environment in which the water is rapidly coalesced enters perpendicularly into separation vessel 18. Within separation vessel 18 the inwardly flowing mixture is offered an immediate opportunity to separate into heavier and lighter components. The heavier component separates from the mixture and flows downwardly within the sloped separation vessel 18 into a water collection portion 36 which is the portion of vessel 18 below inlet passageway 24. Water within water collection portion 36 is maintained at a selected level 38 by means of a water level control 40. The water level control 40 is illustrated diagrammatically since such devices are frequently and customarily used in oil/water separation and are well known to any practitioner in the art. A typical water level control system is illustrated in and will subsequently be described with reference to Figure 8. Basically, the water level control 40 operates a valve (not seen) connected to the pipe fitting 30 to drain water as it accumulates within the vessel lower portion 36 so that the level 38 stays at a pre-selected height within water collection portion 36.

[0026] The mixture flowing out of inlet vessel 10 through lower outlet end 12 separates and the lighter component is carried upwardly into an oil collection portion 42 of separation vessel 18. The oil component of the feed mixture having at least a substantial portion of the water extracted therefrom flows through upper oil outlet end 20 of inlet vessel 10 and through outlet flange fitting 28 for transportation to a pipeline where it may be moved to a refinery, or is conveyed to a facility for storage or further processing.

[0027] The system for separating water from a water-in-oil mixture of Figure 1 is of ultimate simplicity compared to most oil/water separation equipment in use today and yet is arranged to provide improved performance. Specifically, a unique aspect of the separation system of Figure 1 is that an oil/water mixture is subjected to an electrostatic field and immediately thereafter passes for separation with the water component flowing in one direction and the oil component flowing in an opposite direction. Further, the sloped arrangements of inlet vessel 10 and separation vessel 18 provide immediate gravity-assisted separation of a water-in-oil mixture after exposure to an electrostatic field. The apparatus of Figure 1 provides the most immediate and effective separation of oil and water in the simplest possible flow arrangement as compared with other known systems.

[0028] In Figure 1 the rudiments of the method of applying an electrostatic field to the mixture within inlet vessel 10 is illustrated. A voltage source 44 provides a voltage output between conductors 46 and 48. Conductor 48 is secured to the sidewall of inlet vessel 10 while conductor 46 is fed through an insulator 50 that extends through the sidewall of vessel 10 to electrode 16. Voltage across conductors 46 and 48 may be an AC voltage, a DC voltage, a pulsing DC voltage or a dual frequency voltage. The particular voltage applied to create an electrostatic field within the inlet vessel is not a critical element of the invention since much work has been done to define the advantages and disadvantages of various voltage systems used to augment coalescence of water in a water-in-oil mixture. As an example, United States Patent No. 6,860,979 teaches a dual frequency electrostatic coalescence system that may be applied to the apparatus of Figure 1. Such a dual frequency system is better illustrated and will be discussed with reference to Figure 6.

[0029] The basic system of the invention illustrated in Figure 1 is susceptible of a variety of modifications. Figure 2 shows one example of a modification of Figure 1 in which the inlet vessel 10, lower outlet 12, upper inlet 14, and electrode 16 all have the same element number and same purpose as described with reference to Figure 1.

[0030] Inlet vessel lower end 12 is connected in a straight line with a water collection portion 36A that has a water

level control 40 to maintain a water level 38 as described with reference to Figure 1. The lower water outlet end 22 of the water collection portion in Figure 2 connects to the inlet 52 of a water treatment process vessel 54 that is illustrative of any system that provides for treating and/or disposing of water extracted from the inlet mixture. The water treatment process 54 may include simply a disposal of the water extracted from the inlet water/oil mixture or it may represent further treatment to remove any residuary oil carried over from the inlet mixture, such as a hydrocyclone, a centrifugal force separator, a gravity separator, a corrugated plate separator, a flotation cell or a filter.

**[0031]** In the arrangement of Figure 2 the inlet mixture flowing into the system through inlet flange 26 is subjected to an electric field provided by electrode 16 that functions to cause the water portion of the inlet mixture to coalesce. The coalesced water continues to flow downwardly into water collection portion 36A. Oil that separates out of the mixture and therefore that remains above the water level 38 turns upwardly and flows into oil collection portion 42A. Separated oil flows out of the collection portion 42A through upper oil outlet end 20 and through an oil outlet 56 into an oil treatment process area indicated by vessel 58. Oil treatment process vessel 58 is emblematic of any system for further handling, transports, treatment or storage of oil separated by the system of Figure 2. Typically the oil treatment process 58 can be a storage facility where crude oil having a substantial portion of the water extracted therefrom is stored prior to being transported for further use, such as to a refinery for processing.

**[0032]** Comparing Figure 2 with Figure 1 shows two distinct differences. First, Figure 2 illustrates water treatment process vessel 54 and oil treatment vessel 58 as emblematic of further treatment of separated oil and water exiting from the systems. Second, Figure 2 compared to Figure 1 shows a different geometrical arrangement of the flow paths of oil and water that have been separated from an inlet oil-in-water mixture. In both Figure 1 and Figure 2 separated oil changes directions and moves upwardly at an angle relative to the flow path of the inlet mixture. However, in Figure 2, compared to Figure 1, separated water continues in the same flow path of the inlet vessel. Irrespective of these differences the basic function of the systems of Figures 1 and 2 is the same. That is, an inlet mixture of oil-in-water flows in a downward direction through an elongated inlet vessel during which time it is subjected to an electrostatic field and a separation vessel has an inlet passageway in communication with the inlet vessel lower outlet end. Figure 2 shows an arrangement wherein an inlet mixture of oil-in-water is subject to an electrostatic field and immediately thereafter separate passageways are provided by which the separated water and oil flows in different directions.

**[0033]** Figure 3 shows another alternate embodiment of the system of this invention. In Figure 3 inlet vessel 10 is elongated and downwardly sloped, the same as shown in Figures 1 and 2. However, in Figure 3 the oil collection portion 42B is vertically upward. The longitudinal axis 32 intersects the separation vessel longitudinal axis 34 at an angle of about 45°. In Figure 3 the mixture after having passed through the electrostatic field established by electrode 16 within inlet vessel 10 turns and enters horizontally into oil collection portion 42B that is in vertical alignment with water collection portion 36B. Separated water from the mixture coalesced by action of the electrode 16 immediately turns downwardly into the water collection portion 36B and the separated lighter oil component immediately turns upwardly into oil collection portion 42B and flows out upper oil outlet 20. Thus as with Figures 1 and 2, the inlet mixture is subjected to an electrostatic field and immediately thereafter the flow from the inlet mixture enters a divergent path in which separated water can flow in a direction divergent from the separated oil. In the case of Figure 3 the separated water component immediately diverges into a downward path into water collection portion 36B while the separated oil component flows in the opposite direction, that is, upwardly into oil collection portion 42. Thus, Figure 3 provides the same unique concept as Figures 1 and 2, that is, a mixture inlet through an elongated vessel in which the mixture is subject to an electrostatic field followed immediately by divergent flow pathways for the separated water and oil components.

**[0034]** Figure 9 shows another alternate embodiment of the system of this invention. The inlet vessel 10, lower outlet 12, upper inlet 14, and electrode 16 all have the same element number and same purpose as described with reference to Figures 1, 2 and 3. Inlet vessel 10 is elongated and downwardly sloped but with flange fitting 26 oriented to receive a vertical feed. Both the water collection portion 36C and the oil collection portion 42C of the separator vessel 18 are aligned along the separation vessel longitudinal axis 34 and oriented at an angle of about 22.5° relative to the horizontal. The inlet vessel longitudinal axis 32 is perpendicular to the separation vessel longitudinal axis 34. The mixture separates, after having passed through the electrostatic field established by electrode 16 within inlet vessel 10, and the separated water turns angularly downward into the water collection portion 36C and the separated lighter oil component turns angularly upward into the oil collection portion 42C and flows out upper oil outlet 20. The outlet flange fitting 28 is oriented such that it can connect to a vertically oriented oil treatment process area. Thus as with Figures 1, 2 and 3 the inlet mixture is subjected to an electrostatic field and immediately thereafter the flow from the inlet mixture enters a divergent path in which separated water can flow in a direction divergent from the separated oil. As suggested by Figures 1, 2, 3 and 9, the angle of inlet vessel 10 can range from 0° to 45° relative to vertical and the angle of the separation vessel 18 can range from 0° to 45° relative to horizontal.

**[0035]** Figures 1, 2, 3 and 9 each make use of plural electrostatic fields. In each of Figures 1, 2, 3 and 9, in addition to electrode 16 positioned within the inlet vessel 10, a second electrode 60 is positioned within the oil collection portion 42, that is, there is a second electrode 60 within oil collection portion 42 of Figure 1, within oil collection 42A of Figure 2, within oil collection 42B of Figure 3, and within oil collection 42C of Figure 9. Each of the second electrodes provide

electrostatic fields in the same way as the primary electrode 16 in each embodiment and serves to further aid in the coalescence of any water remaining in the separated oil after first separation has taken place. The secondary electrodes 60 may be insulated or if the percentage of water remaining in the mixture within the oil collection portion of the apparatus has diminished sufficiently then the secondary electrodes 60 may be bare electrodes operating at lower voltages.

**[0036]** Figure 4 shows how the basic separation system of this invention may be used in series to more completely separate water from a water-in-oil mixture. Figure 4 shows an inlet manifold 62 by which a water-in-oil mixture is fed into a first separation system generally indicated by the numeral 64 that has the components with the same numerical identification as Figure 1. Outlet flange 28 of first separation system 64 connects to an inlet flange 26A of a second separation system 66. The outlet flange 28A of separation system 66 communicates with an outlet manifold 68 whereby the oil component of the mixture that flows in inlet manifold 62 is collected. Thus the first separation system 64 and second separation system 66 each function identically as has been described with reference to Figure 1 in that each has an inlet vessel 10, a water collection portion 36 and an oil collection portion 42. Each inlet vessel has an electrode 16 and each water collection portion 36 has a pipe fitting by which water separated from the feed mixture is conveyed away from the separation system. Further, there is a second electrode 60 in both separation systems 64 and 66.

**[0037]** One difference in Figure 4 compared to Figure 1 is that a gas outlet is illustrated in communication with each of the inlet vessels 10 and 10A. Each gas outlet 70 and 70A is connected by piping 72 by which gas separated from the system can be carried away, such as to a gas collection facility, a flare or so forth.

**[0038]** Figure 7 is a diagrammatic illustration of how the separation system of Figure 2 can be connected in series. Figure 7 diagrammatically shows a separation system 74 that functions as illustrated and described with reference to Figure 2 and identical separation systems 76 and 78 connected in series. This is illustrative of the fact that separation systems as described herein may be connected in series with as many as necessary substantially identical separation systems connected in series to achieve the level of separation required.

**[0039]** Referring back to Figure 4, this view suggests that the separation systems of this invention can easily be placed in parallel. Figure 4 shows two separation systems 64 and 66 extending in series from an inlet manifold 62 to an outlet manifold 68. It is easy to see that any number of the systems illustrated in Figure 4 can be placed side-by-side, in parallel, each extending from inlet manifold 62 to outlet manifold 68. In like manner the system of Figure 7 could easily be placed in parallel with as many separation systems as required according to the volume of a water-in-oil mixture to be treated.

**[0040]** Figure 5 illustrates how a separation system of this invention may be employed in a desalter system. In Figure 5 a first separation system 64 as is described with reference to Figure 1 functions to provide separated oil at outlet flange fitting 28 that is connected to a T-fitting 80 having a wash water inlet 82. The separated oil flowing from outlet flange 28 mixes with wash water in T-fitting 80, and the mixture passes out of the T-fitting through outlet 84, through a mixing valve 86 and through an inlet 88 pipe to a desalter vessel 90. In vessel 90 a quiet zone is provided allowing the oil and water to separate. The water introduced through wash water inlet 82 absorbs salt content in the oil discharged from first separator system 64. From desalter vessel 90 water passes out through outlet 92 and oil having substantially all the water and substantially all the salt removed therefrom flows out through oil outlet 94.

**[0041]** The basic concepts of the desalter of Figure 5 are known, that is the step of using wash water to mix with oil having salt therein is known and is not the essence of the invention. The significance of Figure 5 is that it shows how a separation system 64 of this invention can be used in a desalter to improve the efficiency and effectiveness of the desalter system.

**[0042]** Figure 6 shows a further illustration of how the separation systems of this invention may be used in a desalting arrangement. A first separation system 64, as illustrated and described with reference to Figure 1, provides separated oil through outlet flange 24 into a T-fitting 80 having a water inlet 82 as described in Figure 5. The mixture passes through mixing valve 86 as described and into another inlet flange fitting 26 of a second separation system 66 that again is the same as the basic separation system of Figure 1. The separated oil flowing through outlet fitting 28A enters a desalter vessel 90 where the water and oil components of the mixture separate by gravitation with the water having dissolved salt therein and relatively salt-free oil passing upwardly and out of the desalter through oil outlet 94.

**[0043]** Figure 6 shows more details of circuitry by which a voltage may be applied to an electrode within a separation system to which reference will be made subsequently.

**[0044]** Figure 8 shows one way in which separation systems of this invention can be added in series. In Figure 8 an oil/water mixture enters through an inlet 96 into a preliminary separator 98 that is in the form of a vertical vessel having a gas outlet 100 at the top. Liquid passes downwardly in preliminary separator 98 with easily separated water component settling to the bottom into a water level 38 maintained by a water level control 40. The control 40 operates a water discharge valve 102 so that the level 38 is maintained within vessel 98. A pipe outlet fitting 30 provides for conveying water away from preliminary separator 98. The mixture having gas and easily separated water removed therefrom flows into a first separator system 74 like that described in Figure 2.

**[0045]** As water is separated from the oil content of the mixture within separation system 74 it flows downwardly into water collection portion 36A and ultimately is drained out pipe outlet fitting 30. Oil from the mixture moves upwardly through oil collection portion 42 where it is again exposed to an electrostatic field by second electrode 60. The separated

oil moves through oil outlet 56 and into a second separation system 64 and through downwardly inclined inlet vessel 10 having an electrode 16 therein. In the separation system 64 the mixture is treated as has been described with reference to Figure 1, that is, in a basic separation system of this invention. From inlet vessel 10, the mixture, after being subjected to the electrostatic field provided by electrode 16, flows into separation vessel 18, the water being channeled downwardly into the water collection portion 36 where it mixes with water draining out of water collection portions 36A of separation system 74 and passes out of the system through a pipe outlet 30. The oil passing out of inlet vessel 10 is channeled upwardly through oil collection portion 42 and out through outlet flange fitting 28, all in the manner as described with reference to Figure 1.

**[0046]** Figure 8 is an illustration of how the unique separation system of this invention lends itself to a variety of combinations, all achieved with the basic concepts as revealed in Figure 1. In the system of Figure 8 the mixture is subjected to electrostatic field provided by four (4) electrodes. To achieve highly effective separation of water from the oil contained in the mixture, the strength of the electrostatic field of successive electrodes can be increased since each is in a portion of the system wherein the water content of the mixture has been reduced. As an example, while electrodes 16 and 60 of separation system 74 may be insulated, electrodes 16 and 60 of separation system 64 may be uninsulated, that is bare. Additionally, as shown by Figures 10, 11 and 12, different electrode configurations may be used for electrodes 16 and 60 in order to achieve the desired electrostatic field. For example, in Figure 10 electrodes 16A are in the form of parallel plates. In Figure 11 the electrodes 16B are in the form of concentric cylindrical members 16B, while in Figure 12 a coaxial electrode 16C is in the shape of a rod surrounded by a concentric cylindrical member 16D. Second electrode 60 may have any of the cross-sectional arrangements shown in Figures 10, 11 and 12.

**[0047]** As mentioned with reference to Figure 1, each of the electrodes employed in the separation systems described herein is supplied by a voltage potential which may be an AC voltage, a DC voltage, a rectified AC voltage or an AC voltage having selected frequencies and wave forms. An effective voltage format for use with the electrostatic separator systems of this invention is a dual frequency voltage as described in detail in United States Patent No. 6,860,979 entitled "Dual Frequency Electrostatic Coalescence." This patent issued on May 1, 2005, and is incorporated herein by reference. Figure 6 shows a basic circuit revealed in this patent by which a dual frequency voltage is applied to electrode 16 of separation system 64. In this dual frequency circuit a three-phase voltage source 104 is applied to a rectifier 106 to produce a voltage on a DC bus 108. Voltage from DC bus 108 supplies a modulator 110 that, by signals fed on conductors 112, controls a chopper 114 that provides an AC voltage of selectable frequency to the primary 116 of a transformer 118. The secondary 120 of transformer 118 applies voltage between ground 122 and a conductor 124 that supply voltage passing through insulator 50 to electrode 16. The circuit of Figure 6 provides a method of augmenting the separation of the oil and water components of a mixture flowing through inlet vessel 10 by providing an AC voltage source of a readily selectable frequency F1 that is modulated in intensity at a selected frequency F2.

**[0048]** Figure 13 illustrates an alternate embodiment of the invention as compared to the basic embodiment of Figure 1. In Figure 13 a horizontal transition vessel 126, typically in the form, as illustrated, of a length of pipe, interconnects oil collection vessel 42 with inlet vessel 10. A tee fitting 128, extends from the bottom of horizontal transition vessel 126 and connects to the inlet of water collection vessel 36. Thus water separating in inlet vessel 10 and oil collection vessel 42 settles to the bottom of horizontal transition vessel 126 and drains out through tee fitting 128 into water collection vessel 36 while encountering reduced turbulence.

**[0049]** In the drawings the basic configurations of the separator of this invention is illustrated in Figures 1, 2, 3, 9 and 13. Different systems by which this separator system can be applied are illustrated in Figures 4, 5, 6, 7 and 8. Figures 5 and 6 illustrate specifically how the separator system herein can be employed in a desalting system in which wash water is utilized. It is important to emphasize that the illustrations of how the separator system of this invention can be modified into various configurations, as exemplified in Figures 4 through 8, are examples only and by no means are illustrated as the only arrangements by which the separator system can be employed.

**[0050]** Referring now to Figure 14, a first separation vessel 130 and a second separation vessel 132 are arranged one above the other, each vessel 130 being an upflow leg or stage that has the wet oil inlet 14 located below the electrode 16 but above the water level control 40 (and therefore above the water level 38). The orientation of the vessels 130, 132 may vary from vertical to horizontal (see Figures 15 to 15B) relative to one another. A vertical orientation has logistical advantages and a horizontal orientation has fluid flow advantages. Varying between the two orientations blends the advantages of both orientations.

**[0051]** As the wet oil enters through inlet 14 of the first vessel 130 below the electrode 16, the wet oil is substantially immediately affected by the electric field. The largest water droplets coalesce and flow downward into the water collection portion 26 before the wet oil encounters the electrode 16. The angle of the vessel 130 relative to horizontal (see e.g., Figure 15) allows the expedited countercurrent removal of the coalesced water to the water collection portion 26. As the drier oil flows upward to the oil collection portion 42 of the vessel 130, smaller water droplets coalesce and separate into the countercurrent flow. The drier oil passes from the outlet 20 of the first vessel 130 and enters the inlet 14 of second vessel 132 below the electrode 16, where the above separation process is repeated. Each vessel 130, 132 is equipped with a gas outlet 70 by which gas separated from the system can be carried away, such as to a gas collection

facility, a flare or so forth.

[0052] A plurality of baffles 134 that are arranged parallel to one another may be provided in the water collection portion 26 of each vessel 130, 132. The baffles 134, which are preferably oriented parallel to the axis of the vessel 130, 132 may be vertical, horizontal, or angled baffles (see Figures 19 to 21). A vertical baffle decreases the Reynolds Number and, therefore, system turbulence. A horizontal baffle decreases the Reynolds Number and settling distance. However, a horizontal configuration increases the number of surfaces on which sand may accumulate. Additionally, the separated oil droplets must cross the water flow in order to travel upward and recombine with the continuous oil phase. An angled baffle—that is, a baffle oriented between 0 and 90 degrees—has the potential to combine the advantages of vertical and horizontal baffles, providing shorter settling distances and an increased angle of repose for the sand. The separated oil droplets cross the water flow at the wall where flow velocity is a minimum.

[0053] As illustrated in Figures 16, 18, and 24A & B a degasser or pretreatment unit 136 may be connected to the inlet 14 of the first separator vessel 130. Pretreatment prevents excessive gas from entering into vessel 130 (and 132) and reduces the inlet water volume by initiating water removal. In a preferred embodiment, the pretreatment unit 136 is a PORTA-TEST WHIRLYSCRUB® V™ vertical centrifugal separator (Cameron Corp. Process Systems, formerly National Tank Company Corp., Houston, Texas) or CONSEPT ICD™ centrifugal separator (also Cameron Corp. Process Systems, formerly National Tank Company Corp., Houston, Texas). The tangential inlet on these particular centrifugal separators promotes free-gas removal and initiates free-water coalescence by creating a high-g environment. As illustrated in Figures 24A & B, pretreatment unit 136 may include a water collection portion 138.

[0054] Experiments by the inventors on various configurations of a compact electrostatic separator made according to this invention have provided insights into what works best. Different performance characteristics depend on whether the oil-water flow is upward or downward. For example, the oil-water flow in the arrangement of Figures 24A & B is a downward flow in each of the separator vessels, 130, 132 (with the pretreatment unit 136 and vessels 130, 132 being connected to a single header in Figure 24B and controlled by a single level control). With respect to inlet water fraction, for high water fractions (about 30-70% BS&W), up flow yields superior results whereas for moderate water fractions (about 5-10% BS&W) down flow performs better. With respect to outlet water fractions, the up flow configuration has a limit on the amount of water that can be removed. The drag of the upward flowing oil prevents small amounts of water from falling into the water collection portion 36 of the vessel 130, 132, and this configuration can dry oil only to moderate fractions. However, with moderate inlet water fractions, a down flow configuration can yield oil with a low (< 1%) water fraction.

[0055] With respect to the electrostatic technique, AC is the only appropriate technique in up flow configurations given very wet oil inlet flows. Furthermore, the electrode 16 is preferably a bare electrode when the wet oil has a high water fraction. Because the flow coming into a down flow configuration is moderately wet, there is a possibility to use AC as well as dual polarity and dual frequency techniques to achieve very dry outlet oils. As discussed previously in connection with Figure 6, an effective voltage format for use with the electrostatic separator systems of this invention is a dual frequency voltage as described in detail in United States Patent No. 6,860,979 entitled "Dual Frequency Electrostatic Coalescence" and incorporated herein by reference. The moderately wet inflow also provides an opportunity to use an insulated electrode 16.

[0056] Referring now to Figures 22 and 23, a compact electrostatic separator is illustrated that combines the most advantageous features of an up flow and a down flow configuration. Wet oil enters the inlet 14 of a first separator vessel 130, which is in an up flow configuration, below the electrode 16 and above the water level control 40. Because of the high water fraction of the wet oil, first stage electrode 16 is a bare electrode used in combination with AC technology. Electrode 16 causes water droplets to coalesce and fall out of the oil-water mixture into the water collection portion 36. Because of the high density of the water relative to the oil and its low viscosity, most of the water can fall out of the mixture into the water collection portion 36. However, at some point, the drag force of the upwardly moving oil-water mixture exceeds the remaining water's ability to move downward. With much of the water exiting the lower water outlet end 22 of the first vessel 130, a moderately dry oil exits the upper oil outlet end 20 of vessel 130 and enters the inlet 14 to a second separator vessel 132, which is in a down flow configuration.

[0057] The moderately dry oil enters the second vessel 132 about even with the electrode 60. Second stage electrode 60 performs the same function as that of the first stage electrode 16. Electrode 60 may be an insulated electrode and used in combination with AC or with dual polarity and dual frequency techniques. With the momentum of the water and the mixture being in the same direction, the drag on the oil-water mixture is reduced and much more of the remaining water can fall out into the water collection portion 36 of the second vessel 132. This water exits at the lower water outlet end 22 and nearly dry oil exits from the upper oil outlet end 20. Note that because upper oil outlet end 20 of the first vessel 130 and the inlet 14 of the second vessel 132 are both at the upper ends of the vessels 130, 132, this configuration occupies less space than the systems illustrated, for example, in Figures 14 and 15.

[0058] Laboratory studies demonstrate that the addition for reactance to the transformer 118 (see Figure 6) is beneficial. From preliminary lab data, when the reactance is absorbing about 5 to 70% of the input voltage, it is performing two functions. First, it limits both the number and length of arcing short circuits. This tends to increase the applied voltage

on the electrode 16 and produce more coalescence. Second, the voltage adjustments caused by the arc response induce a voltage modulation. This voltage modulation enhances the coalescence of water droplets of varying size, which leads to improved separation. The combination of these two properties improves the quality of both the oil and water (see Tables 1 and 2).

5

**Table 1. Effect of Added Reactance on the Quality of Oil and Water.**

2000 Volts 1st Electrode; 5000 Volts 2nd Electrode ~100 °F 2000 B/D psf, 32-34% H <sub>2</sub> O						
Amps 1st	Amps 2nd	Added Reactance MHY	% H <sub>2</sub> O Dry Oil Out	Angle of Baffle	PPM Oil 1st Water Outlet	% Oil 2nd Water Outlet
1.4	0.4	0	5.6*	0	160	36*
1.4	0.4	0	5.6*	45	179	36*
1.4	0.4	0	5.6*	90	261	36*
0.5	0.4	35	5.2	45	58	1.7
0.5	0.4	47	5.6	45	123	2.7
0.5	0.4	59	5.5	45	120	2.3
0.6 <sup>†</sup>	0.6	59	4.9	45	94	0.5

\* Values averaged † One sample only 3000 Volts and 7500 Volts

**Table 2. Effect of Added Reactance and No Baffles in the Second Separator Vessel on the Quality of Oil and Water.**

~100 °F 2000 B/D psf, 32-34% H <sub>2</sub> O								
Amps 1st	KVoltage In/Out	Amps 2nd	KVoltage In/Out	Added Reactance MHY	% H <sub>2</sub> O Dry Oil Out	Angle of Baffle	PPM Oil 1st Water Outlet Baffled	PPM Oil 2nd Water Outlet Not Baffled
0.6	4.0/1.7	0.6	8.0/7.6	56	5	45	49	10K
0.6	4.0/1.7	0.9	9.1/8.2	56	4.6	45	57	5K
0.6	4.0/1.7	1.3	11.0/9.1	56	4.3	45	51	220

**[0059]** Referring now to Figures 25 and 26, an additional oil outlet 20a is provided that routes oil dry enough to meet a user's requirements on a dry oil path 142 that bypasses the second separator vessel 132. In Figure 25, wet oil (about 30-70% H<sub>2</sub>O) enters inlet 14<sub>(1)</sub> of the first separator vessel 130 and dry oil (about < 1% H<sub>2</sub>O) exits at the top end of the vessel 130 through outlet 20a. The balance of the medium-wet or moderately dry oil (about 5-10% H<sub>2</sub>O) exits outlet 20<sub>B</sub> and enters the inlet 14<sub>(2)</sub> of the second separator vessel 132. Dry oil then exits the second vessel 132 through outlet 20<sub>D</sub> and along dry oil path 142. Preferably, the flow through outlet 20<sub>A</sub> is controlled to ensure that any oil that exceeds the user's requirements is not routed through the outlet 20<sub>A</sub> (thereby bypassing the second vessel 132). The same holds true for outlet 20<sub>D</sub>.

**[0060]** In Figure 26, the first separator vessel 130, which is an up flow vessel, includes two additional outlets 20<sub>A</sub> and 20<sub>B</sub>. Preferably, outlet 20<sub>B</sub> is located in close proximity to the wet oil inlet 14. As wet oil passes through inlet 14<sub>(1)</sub> and enters the first separator vessel 130, a portion of the wet oil is diverted to outlet 20<sub>B</sub> and into inlet 14<sub>(2)</sub> of the second separator vessel 132, which is also an up flow vessel. Dry oil that meets the user's requirements exits through additional outlet 20<sub>A</sub> located at the top end of vessel 130 and travels along path 142.

**[0061]** The second separator vessel 132 converts the wet oil from the first vessel 130 to a medium-wet oil, which exits the second vessel 132 through outlet 20<sub>D</sub> and travels along medium-wet oil path 144 to the inlet 14<sub>(3B)</sub> of an additional or third separator vessel 140. Vessel 240 is a down flow vessel substantially similar in structure to that of vessels 130, 132 as illustrated in, for example, Figures 24A & B. Medium- or moderately wet oil which passes through outlet 20<sub>C</sub> of the first vessel 130 also travels along medium-wet oil path 144 to the inlet 14<sub>(3A)</sub> of a third vessel 140. Dry oil then exits through outlet 20<sub>E</sub> of the third vessel 140 and travels along dry oil path 142.

**[0062]** While the invention has been described with a certain degree of particularity, it is manifest that many changes may be made in the details of construction and the arrangement of components without departing from the spirit and

scope of this disclosure. It is understood that the invention is not limited to the embodiments set forth herein for purposes of exemplification, but is to be limited only by the scope of the attached claims, including the full range of equivalency to which each element thereof is entitled.

[0063] The following are particularly preferred aspects according to the present disclosure:

5

Numbered clause 1. An apparatus for separating water from a water-and-oil mixture, comprising:

10

a first (64) and a second (66) elongated separator vessel, each said first and second elongated separator vessel having at its upper end an oil collection portion (42) including an electrode (60) and at its lower end a water collection portion (36);  
 each said first (64) and second (66) elongated separator vessel having an inlet being located relative to the electrode of the elongated separator vessel to provide a predetermined direction of flow within the elongated separator vessel of a water-and-oil mixture entering the elongated separator vessel;  
 15 said first (64) and second (66) elongated separator vessels each being oriented at an incline relative to a horizontal plane;  
 the water-and-oil mixture entering each said first (64) and second (66) elongated separator vessels is subjected to an electric field.

15

20

Numbered clause 2. An apparatus according to clause 1, said first elongated separator is at a different elevation than that of said second elongated separator vessel.

25

Numbered clause 3. An apparatus according to clause 1, the predetermined flow direction within said first elongated separator vessel is different than that within said second elongated separator vessel.

30

Numbered clause 4. An apparatus according to clause 1 further comprising the electrode in at least one of said first and second elongated separator vessels being in circuit relationship to an AC voltage source.

35

Numbered clause 5. An apparatus according to clause 1 further comprising the electrode in said first elongated separator vessel being in circuit relationship to a voltage source at lower potential than a voltage source in circuit relationship to the electrode in said second elongated separator vessel.

40

Numbered clause 6. An apparatus according to clause 1 further comprising a voltage source in circuit relationship to at least one of the electrodes includes reactance.

45

Numbered clause 7. An apparatus according to clause 1 further comprising the electrode in said first elongated separator vessel being a different type of electrode than the electrode in said second elongated separator vessel.

50

Numbered clause 8. An apparatus according to clause 1 further comprising at least one of said first and second elongated separator vessels including a plurality of baffles arranged parallel to one another in the lower water collection portion of the elongated separator vessel.

Numbered clause 9. An apparatus according to clause 8 further comprising each baffle in said plurality of baffles being a baffle selected from the group consisting of a horizontal baffle, a vertical baffle, and an angled baffle.

55

Numbered clause 11. An apparatus according to clause 1 further comprising a degasser unit connected to the inlet of said first elongated separator vessel.

Numbered clause 12. A method of separating water from a water-and-oil mixture, the method comprising the steps of:

60

(a) flowing a water-and-oil mixture into an inlet of a first elongated separator vessel, the first elongated separator vessel being oriented on an incline and having an electrode located toward its upper end;  
 (b) passing the water-and-oil mixture through an electric field of the first elongated separator vessel whereby water in the water-and-oil mixture coalesces and a first water predominant fluid flows downward;  
 (c) flowing a portion of a first oil predominant fluid out of an outlet of the first elongated separator vessel and into an inlet of a second elongated separator vessel, the second elongated separator vessel being oriented on an incline and having an electrode located toward its upper end; and  
 (d) passing the portion of the first oil predominant fluid through an electric field of the second elongated separator vessel whereby water in the portion of the first oil predominant fluid coalesces and a second water predominant

fluid flows downward.

5 Numbered clause 13. A method according to clause 12, the inlet to the first elongated separator vessel and the second elongated separator vessel is located relative to the electrode to provide for a predetermined direction of flow of the water-and-oil mixture as the water-and-oil mixture enters the separator vessel, the direction of flow being a direction of flow selected from the group consisting of an upward direction of flow and a downward direction of flow.

10 Numbered clause 14. A method according to clause 12, the portion of the first oil predominant fluid flowing out of the outlet of the first elongated separator vessel and into the inlet of the second elongated separator vessel is a portion selected from the group consisting of a wet oil portion and a medium-wet oil portion.

15 Numbered clause 15. A method according to clause 12 further comprising the step of:

(e) allowing a second portion of the first oil predominant fluid to exit an outlet of the first elongated separator vessel and bypass the second elongated separator vessel.

20 Numbered clause 16. A method according to clause 12 further comprising the steps of:

(f) after said step (a), allowing a portion of the water-and-oil mixture to substantially immediately exit an outlet of the first elongated separator vessel and flow into an inlet of an additional elongated separator vessel, the additional elongated separator vessel being oriented on an incline and having an electrode located toward its upper end; and

(g) passing the portion of the water-and-oil mixture through an electric field of the additional elongated separator vessel whereby water in the portion of the water-and-oil mixture coalesces and a third water predominant fluid flows downward.

25 Numbered clause 17. A method according to clause 17, the inlet to the additional elongated separator vessel is located relative to the electrode to provide for a predetermined direction of flow of the water-and-oil mixture as the water-and-oil mixture enters the additional elongated separator vessel, the direction of flow being a direction of flow selected from the group consisting of an upward direction of flow and a downward direction of flow.

30 Numbered clause 18. A method according to clause 17 further comprising the step of:

(h) flowing a portion of a third oil predominant fluid out of an outlet of the additional elongated separator vessel and into an inlet of the second elongated separator vessel.

35 Numbered clause 19. A method according to clause 12 further comprising the step of flowing the water-and-oil mixture to a pre-separation unit prior to said step (a).

40 Numbered clause 20. A method according to clause 12, at least one of the first water predominant flow and the second water predominant flow passes through a plurality of baffles.

45 Numbered clause 21. A method according to clause 12, the electrode of the first and second elongated separator vessels is each in circuit relationship to a voltage source at a different potential than the other voltage source.

## 45 **Claims**

1. An apparatus for separating water from a water-and-oil mixture, comprising:

50 a first (64) and a second (66) elongated separator vessel, each said first and second elongated separator vessel having at its upper end an oil collection portion (42) including a single electrode portion (16) and at its lower end a water collection portion (36);

55 each said first (64) and second (66) elongated separator vessel having an inlet (14) being located below the electrode of the elongated separator vessel, the inlet (14) arranged to provide a predetermined direction of flow within the elongated separator vessel of a water-and-oil mixture entering the elongated separator vessel; said first (64) and second (66) elongated separator vessels each being oriented at an incline relative to a horizontal plane; and wherein

the electrode (16) is arranged to subject a water-and-oil mixture exiting the inlet and entering the elongated separator vessel to an electric field.

2. An apparatus according to claim 1 further comprising an oil outlet (20) having a portion located opposite a lower end of the electrode portion (16), preferably wherein a portion of the oil outlet (2) is located diametrically opposite a lower end of the electrode portion (16).

5 3. An apparatus according to any preceding claim wherein said first elongated separator is at a different elevation than that of said second elongated separator vessel and/or wherein the predetermined flow direction within said first elongated separator vessel is different than that within said second elongated separator vessel.

10 4. An apparatus according to any preceding claim wherein the electrode portion in said first and second elongated separator vessels is in circuit relationship to an AC voltage source, and/or wherein the electrode portion in said first elongated separator vessel is in circuit relationship to a voltage source at lower potential than a voltage source in circuit relationship to the electrode portion in said second elongated separator vessel and/or

15 wherein the electrode portion in said first elongated separator vessel is a different type of electrode than the electrode portion in said second elongated separator vessel.

20 5. An apparatus according to any preceding claim further comprising a voltage source in circuit relationship to at least one of the electrodes portion includes reactance and/or further comprising a degasser unit connected to the inlet of said first elongated separator vessel.

25 6. An apparatus according to any preceding claim further comprising at least one of said first and second elongated separator vessels including a plurality of baffles arranged parallel to one another in the lower water collection portion of the elongated separator vessel preferably wherein each baffle in said plurality of baffles being a baffle selected from the group consisting of a horizontal baffle, a vertical baffle, and an angled baffle.

30 7. A method of separating water from a water-and-oil mixture, the method comprising the steps of:

(a) flowing a water-and-oil mixture into an inlet of a first elongated separator vessel, the first elongated separator vessel being oriented on an incline and having a single electrode portion located toward its upper end, the inlet of the first elongated separator vessel located below the electrode portion;

35 (b) passing the water-and-oil mixture through an electric field of the first elongated separator vessel whereby water in the water-and-oil mixture coalesces and a first water predominant fluid flows downward;

(c) flowing a portion of a first oil predominant fluid out of an outlet of the first elongated separator vessel and into an inlet of a second elongated separator vessel, the second elongated separator vessel being oriented on an incline and having a single electrode portion located toward its upper end, the inlet of the second elongated separator vessel located below the electrode portion; and

40 (d) passing the portion of the first oil predominant fluid through an electric field of the second elongated separator vessel whereby water in the portion of the first oil predominant fluid coalesces and a second water predominant fluid flows downward.

45 8. A method according to claim 7 wherein the first and second separator vessels comprises an oil outlet having a portion located opposite a lower end of the electrode portion, preferably wherein a portion of the oil outlet (2) is located diametrically opposite a lower end of the electrode portion (16).

50 9. A method according to Claim 7 or 8, the inlet to the first elongated separator vessel and the second elongated separator vessel is located relative to the electrode portion to provide for a predetermined direction of flow of the water-and-oil mixture as the water-and-oil mixture enters the separator vessel, the direction of flow being a direction of flow selected from the group consisting of an upward direction of flow and a downward direction of flow.

55 10. A method according to any of Claims 7 to 9, the portion of the first oil predominant fluid flowing out of the outlet of the first elongated separator vessel and into the inlet of the second elongated separator vessel is a portion selected from the group consisting of a wet oil portion and a medium-wet oil portion.

11. A method according to any of claims 7 to 10 further comprising the step of:

(e) allowing a second portion of the first oil predominant fluid to exit an outlet of the first elongated separator vessel and bypass the second elongated separator vessel.

12. A method according to any of claims 7 to 11 further comprising the steps of:

5 (f) after said step (a), allowing a portion of the water-and-oil mixture to substantially immediately exit an outlet of the first elongated separator vessel and flow into an inlet of an additional elongated separator vessel, the additional elongated separator vessel being oriented on an incline and having an electrode portion located toward its upper end; and  
10 (g) passing the portion of the water-and-oil mixture through an electric field of the additional elongated separator vessel whereby water in the portion of the water-and-oil mixture coalesces and a third water predominant fluid flows downward.

15 13. A method according to Claim 12, the inlet to the additional elongated separator vessel is located relative to the electrode portion to provide for a predetermined direction of flow of the water-and-oil mixture as the water-and-oil mixture enters the additional elongated separator vessel, the direction of flow being a direction of flow selected from the group consisting of an upward direction of flow and a downward direction of flow.

14. A method according to Claim 12 or 13 further comprising the step of:

(h) flowing a portion of a third oil predominant fluid out of an outlet of the additional elongated separator vessel and into an inlet of the second elongated separator vessel.

20 15. A method according to any of claims 7 to 14 further comprising the step of flowing the water-and-oil mixture to a pre-separation unit prior to said step (a) and/or  
wherein at least one of the first water predominant flow and the second water predominant flow passes through a plurality of baffles and/or  
wherein the electrode portion of the first and second elongated separator vessels is each in circuit relationship to a voltage source at a different potential than the other voltage source.

30

35

40

45

50

55




Fig. 1




Fig. 7




Fig. 3




Fig. 2




Fig. 4




Fig. 5





Fig. 6






Fig. 9




Fig. 10




Fig. 11





Fig. 12

Fig. 13






Fig. 14




Fig. 15





Fig. 15A

15B



*Fig. 15B*




Fig. 16

17B




Fig. 17A




Fig. 17B





Fig. 18A



132





Fig. 21

Fig. 21




Fig. 22




Fig. 23




Fig. 24A




Fig. 24B




Fig. 25




Fig. 26



## EUROPEAN SEARCH REPORT

Application Number  
EP 18 20 4461

5

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
10 X	US 2008/257739 A1 (SAMS GARY W [US] ET AL) 23 October 2008 (2008-10-23) * paragraphs [0087] - [0097], [0103], [0104]; claim 14; figures 4,6,8 *	1-15	INV. B01D17/04 B01D17/06
15 A	US 2 825 686 A (GREENE ROBERT L ET AL) 4 March 1958 (1958-03-04) * figures 1-2 *	1-15	
20 A	US 3 597 346 A (WATERMAN LOGAN C) 3 August 1971 (1971-08-03) * figures 1-2 *	1-15	
25 A	US 3 148 134 A (STENZEL RICHARD W) 8 September 1964 (1964-09-08) * figure 1 *	1-15	
30 A,D	US 6 860 979 B2 (SAMS GARY W [US]) 1 March 2005 (2005-03-01) * figure 8 *	1-15	
35			TECHNICAL FIELDS SEARCHED (IPC)
40			B01D
45			
50 1	The present search report has been drawn up for all claims		
55	Place of search The Hague	Date of completion of the search 1 April 2019	Examiner Weber, Christian
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.

EP 18 20 4461

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-04-2019

10	Patent document cited in search report	Publication date		Patent family member(s)	Publication date
15	US 2008257739 A1	23-10-2008	CA EP JP	2683761 A1 2139575 A1 5060615 B2	23-10-2008 06-01-2010 31-10-2012
20	US 2008257739 A1	23-10-2008	JP	2010524666 A	22-07-2010
25	US 2014034504 A1	06-02-2014	US	2008257739 A1	23-10-2008
30	US 2008127932 A1	23-10-2008	WO	2008127932 A1	23-10-2008
35	US 2825686 A	04-03-1958		NONE	
40	US 3597346 A	03-08-1971		NONE	
45	US 3148134 A	08-09-1964		NONE	
50	US 6860979 B2	01-03-2005	AU BR CA GB GB JP JP MX US WO	2003261393 A1 0306194 A 2494813 A1 2407999 A 2419305 A 4999271 B2 2005534494 A PA05001482 A 2004094421 A1 2004014512 A2	25-02-2004 19-10-2004 19-02-2004 18-05-2005 26-04-2006 15-08-2012 17-11-2005 06-06-2005 20-05-2004 19-02-2004
55	-----				

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**REFERENCES CITED IN THE DESCRIPTION**

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

**Patent documents cited in the description**

- US 6860979 B [0028] [0047] [0055]