



(12) **CORRECTED EUROPEAN PATENT APPLICATION**  
published in accordance with Art. 153(4) EPC

(15) Correction information:  
**Corrected version no 2 (W2 A1)**  
**Corrections, see**  
**Abstract**

(51) Int Cl.:  
**A61F 13/49** <sup>(2006.01)</sup> **A61F 13/496** <sup>(2006.01)</sup>

(86) International application number:  
**PCT/JP2017/037312**

(48) Corrigendum issued on:  
**17.06.2020 Bulletin 2020/25**

(87) International publication number:  
**WO 2018/074398 (26.04.2018 Gazette 2018/17)**

(43) Date of publication:  
**28.08.2019 Bulletin 2019/35**

(21) Application number: **17861729.6**

(22) Date of filing: **16.10.2017**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB**  
**GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO**  
**PL PT RO RS SE SI SK SM TR**

(72) Inventors:  
• **IDE, Aya**  
**Shikokuchuo-shi**  
**Ehime 799-0431 (JP)**  
• **MORI, Yosuke**  
**Shikokuchuo-shi**  
**Ehime 799-0431 (JP)**

(30) Priority: **21.10.2016 JP 2016206862**

(71) Applicant: **Daio Paper Corporation**  
**Ehime 799-0492 (JP)**

(74) Representative: **Williams Powell**  
**11 Staple Inn**  
**London WC1V 7QH (GB)**

(54) **UNDERPANTS-TYPE DISPOSABLE DIAPER**

(57) Problem is to prevent appearance from deteriorating due to a conspicuous corner of a side edge of a gluteal cover portion on a side of a leg opening in an outer member separated type underpants-type disposable diaper.

The above-mentioned problem is solved by an underpants-type disposable diaper separately having a front side outer member 12F and a back side outer member 12B, the front side outer member 12F and the back side outer member 12B being spaced apart in a front-back direction LD in a middle in the front-back direction LD, in which the back side outer member 12B has a gluteal cover portion C extending to a center side of the side seal portions 12A in the front-back direction, and a front-back direction dimension of a side edge of the gluteal cover portion C is 0.9 to 1.1 times a width direction dimension W3 from a side edge of the back side outer member 12B to a side edge of a center side of the side seal portions 12A in the width direction.

FIGURE 1

