



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
11.09.2019 Bulletin 2019/37

(51) Int Cl.:
F28F 7/02 (2006.01)

(21) Application number: **18160938.9**

(22) Date of filing: **09.03.2018**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
KH MA MD TN

(72) Inventor: **The designation of the inventor has not yet been filed**

(74) Representative: **BAE SYSTEMS plc**
Group IP Department
Farnborough Aerospace Centre
Farnborough
Hampshire GU14 6YU (GB)


(71) Applicant: **BAE SYSTEMS plc**
London SW1Y 5AD (GB)

(54) **HEAT EXCHANGER**

(57) There is disclosed a heat exchanger comprising a first channel, for communicating between a first channel inlet and a first channel outlet, a second channel for communicating between a second channel inlet and a second channel outlet, a third channel for communicating be-

tween a third channel inlet and a third channel outlet, a first conduit interconnecting the first channel and the third channel, and thereby defining a first group of interconnected channels, the first conduit extending through the second channel.

Figure 1



Description

[0001] According to the present invention there is provided a heat exchanger.

[0002] It is known, for example from WO2014/135844 (BAE Systems plc), to provide a heat exchanger with a plurality of channels for a working fluid, these channels being interleaved amongst a plurality of channels for coolant fluid.

[0003] It is also known to introduce baffles into channels to affect flow and heat transfer. Baffles can improve the heat transfer efficiency of a heat exchanger, but can tend to raise the pressure drop across the exchanger.

[0004] According to a first aspect of the invention there is provided a heat exchanger comprising: a first channel, for communicating between a first channel inlet and a first channel outlet, a second channel for communicating between a second channel inlet and a second channel outlet, a third channel for communicating between a third channel inlet and a third channel outlet, a first conduit interconnecting the first channel and the third channel, and thereby defining a first group of interconnected channels, the first conduit extending through the second channel.

[0005] The provision of a conduit extending through the second channel presents a further surface area which may be exploited for heat transfer, whilst encouraging inter channel mixing. This can tend to increase the heat transfer efficiency between fluids in the heat exchanger.

[0006] There may be provided a plurality of first conduits interconnecting the first channel and the third channel, the plurality of first conduits extending through the second channel.

[0007] As such the surface areas and inter-channel mixing can tend to be further increased.

[0008] The plurality of first conduits may be spaced apart at regular intervals.

[0009] As such an even mixing between channels may be achievable.

[0010] The plurality of first conduits are arranged in adjacent pairs where one conduit per pair is arranged to promote inter-channel flow from the third channel to the first channel, and the other conduit per pair is arranged to promote inter-channel flow from the first channel to the third channel.

[0011] Such pairing of conduits enables the provision of a repeating unit which can be used to build up a heat exchanger core. It also helps to provide a functionally flexible core where each channel group is suitable for flow in either direction and the core is deployable in either counter flow or co-flow configurations.

[0012] The heat exchanger may further comprise a fourth channel, for communicating between a fourth channel inlet and a fourth channel outlet, a second conduit interconnecting the second channel and the fourth channel and thereby defining a second group of interconnected channels, the second conduit extending through the third channel. Further, such a heat exchanger

may further comprise a plurality of second conduits interconnecting the second channel and the fourth channel, each of the second conduits extending through the third channel. Still further, such a heat exchanger may provide a plurality of second conduits arranged in adjacent pairs where one conduit per pair is arranged to promote inter-channel flow from the fourth channel to the second, and the other conduit per pair is arranged to promote inter-channel flow from the second channel to the fourth.

[0013] Such a provision can tend to further promote even mixing of fluids between channels, and thereby improve the efficiency of the heat exchanger. Such improved mixing can in turn be associated with an increase in heat transfer.

[0014] Where first and second conduit pairs are provided, the first conduit pairs and the second conduit pairs occupy an equivalent position in the second and third channel respectively.

[0015] As such a more regular structure can be provided which can tend to apply more consistent mixing and transfer.

[0016] In some examples, the first conduit is, or the plurality of first conduits are, inclined relative to a central axis defined by the first channel and thereby arranged to promote inter-channel flow.

[0017] In heat exchangers provided with a second conduit or a plurality of second conduits, the second conduit or the plurality of second conduits can be inclined relative to a central axis defined by the second channel.

[0018] Such conduit inclination can bias certain flows and thereby can tend to mitigate the increases in pressure drop across the exchanger which could otherwise be encountered from the conduits.

[0019] The heat exchanger may comprise a top plate and plurality of base plates mounted between a pair of side walls, wherein the first channel is defined between the top plate, a first base plate and a portion of the side walls, the second channel is defined between the first base plate, the second base plate and a portion of the side walls, the third channel is defined between the second base plate, the third base plate and a portion of the side walls, and The fourth channel is defined between the third base plate, a fourth base plate and a portion of the side walls.

[0020] The first and third channels, being in fluid communication, may be arranged to transport a first fluid in a first flow direction, and the second and fourth channels, being in fluid communication are arranged to transport a second fluid in a second flow direction. The first and second flow directions can be generally opposite to provide a counter-flow heat exchanger.

[0021] As such a counter-flow arrangement be provided, tending to provide efficient cooling.

[0022] The heat exchanger may further comprise towards a first end: a first fluid ingress manifold connecting the inlets of the first and third channels to a common first fluid inlet port, a second fluid ingress manifold connecting

the outlets of the second and fourth channels to a common second fluid outlet port; and towards a second end: a first fluid egress manifold connecting the outlets of the first and third channels to a common first fluid outlet port, a second fluid egress manifold connecting the inlets of the second and fourth channels to a common second fluid outlet port.

[0023] According to a second aspect of the invention there is provided a method of heat exchange comprising providing a heat exchanger according to the first aspect, causing a coolant fluid to flow through the first and second channel, causing a working fluid to flow through the third channel.

[0024] So that the invention may be well understood, exemplary embodiments are herein described with reference to the following figures, of which:

Figure 1 shows a schematic cross-section of a first example heat exchanger;

Figure 2 shows a three-dimensional representation of a first example portion of a heat exchanger core;

Figure 3 shows a three-dimensional representation of a second example portion of a heat exchanger core;

Figure 4 shows a schematic layout of a fourth example portion of a heat exchanger core;

Figure 5 shows a three-dimensional representation of a the first example heat exchanger;

Figure 6 shows a three-dimensional representation of a second heat exchanger; and

Figure 7 shows a flow diagram for arranging a heat exchanger.

[0025] It will be appreciated that relative terms such as horizontal and vertical, top and bottom, above and below, left and right, front/fore and back/aft, near and far, and so on, are used below merely for ease of reference to the Figures, and these terms are not limiting as such, and any two differing directions or positions and so on may be implemented rather than truly horizontal and vertical, top and bottom, and so on.

[0026] With reference to Figures 1 and 5, a first heat exchanger is shown generally at 100 which comprises a first manifold 2, a core 3, and a second manifold 4.

[0027] The heat exchanger 100 is arranged for counter-flow where a first fluid, hot fluid H (which may alternatively be referred to as a working fluid), passes in the opposite direction to a second fluid, cold fluid C (which may alternatively be referred to as a coolant fluid). As shown in Figure 1, the hot fluid H passes through the core from right-to-left, whilst the cold fluid C passes through the core left-to-right.

[0028] In alternative heat exchangers contemplated, the hot fluid H and the cold fluid C could be arranged for co-flow (where the fluids run in the same direction, e.g. both right-to-left) or cross-flow (where fluids run perpendicular to each other).

[0029] The core 3 comprises a plurality of channels. These channels are configured as two groups, the first group for transporting the first fluid, the second group for transporting the second fluid. Channels alternate by group so that an interleaved arrangement is provided, with channels separated by base plates. A multi-layer stack is thus provided. The first group of channels, corresponding with the odd-numbered channels pass fluid in a first direction. The second group of channels, corresponding with the even-numbered channels, pass the fluid in a second direction.

[0030] In particular, a first channel 10 is defined between a top plate 6 and a first base plate 16, and extends between a pair of first channel ports. These ports are configured for a right-to-left (as shown in Figure 1) flow direction and as such represent a first inlet 12 communicating with the second manifold 4 and a first outlet 14 communicating with the first manifold 2.

[0031] A second channel 20 is defined between the first base plate 16 and a second base plate 26, and extends between a pair of second channel ports. These ports are configured for a left-to-right (as shown in Figure 1) flow direction and as such represent a second inlet 22 communicating with the first manifold 2 and a second outlet 24 communicating with the second manifold 4.

[0032] A third channel 30 is defined between the second base plate 26 and a third base plate 36, and extends between a pair of third channel ports. These ports are configured for a right-to-left (as shown in Figure 1) flow direction and as such represent a third inlet 32 communicating with the second manifold 4 and a third outlet 34 communicating with the first manifold 2.

[0033] A fourth channel 40 is defined between the third base plate 36 and the fourth base plate 46, and extends between a pair of fourth channel ports. These ports are configured for to a left-to-right (as shown in Figure 1) flow direction and as such represent a fourth inlet 42 communicating with the first manifold 2 and a fourth outlet 44 communicating with the second manifold 4.

[0034] Further, there is equivalently provided: a fifth, sixth and seventh channel (50, 60 and 70 respectively); a fifth and sixth base plate (not numbered so as to reduce visual clutter in the figure), and a bottom plate 7, and their respective inlets and outlets (not numbered).

[0035] With additional reference to Figure 5, the channels are further defined by side walls 5.

[0036] Thus a first group of channels, the odd channels, comprises the first, third, fourth, fifth and seventh channels. These odd channels can pass a common fluid in a common direction, in this example they pass hot fluid H right to left. In other examples they could pass fluid left to right.

[0037] A second group of channels, the even channels,

comprises the second, fourth and sixth channels. These even channels can pass a common fluid in a common direction, in this example they pass a cold fluid C from left to right. In other examples they could pass fluid right to left.

[0038] Thus in the core 3 there are four channels in the first group and three channels in the second group. Providing an unequal number of channels in an interleaved stack tends to result in channels from a particular group being at the outermost (top and bottom) layers of the stack. In the core 3, channels 10 and 70 provide such outermost layers. In the Figure 1 configuration, by passing hot fluid through the first group, hot fluid channels pass through these peripheral layers.

[0039] In alternatively configured cores, such as shown in Figures 5 and 6, the cold fluid may be passed through a first group of channels providing the peripheral layers of the stack, whilst the hot fluid is passed through a second group of channels interleaved with the first group. Such alternative arrangements can tend to less heat being lost to the surroundings, tending to raise the efficiency of the exchanger.

[0040] In addition to the channels, the core 3 comprises a plurality of conduits which interconnect channels from the same group.

[0041] As such, a plurality of first conduits 8 provides inter-channel connections between odd-numbered channels. As such a fluid can flow between the interconnected channels. Each conduit 8 extends through an even channel but does not fully occlude that even channel.

[0042] For example, a plurality of conduits 8 are provided, each of which interconnects the first channel 10 and the third channel 30, passing through the second channel 20.

[0043] Some conduits 8 are substantially perpendicular to the channels. Some conduits are inclined to the channels.

[0044] In the first example, the odd conduits extend only between neighbouring odd channels; however in alternative examples, some odd conduits could extend between other odd channel combinations. For example, an odd conduit could connect a first channel 10 and a fifth channel 50, passing through the second 20, third 30, and fourth 40 channels.

[0045] A plurality of second conduits 9 provides inter-channel connections between even-numbered channels. As such a fluid can flow between the interconnected channels. Each of the second conduits 9 extends through at least one odd channel but does not fully occlude it or them.

[0046] The first manifold 2 comprises, given the counter-flow configuration, an odd channel egress manifold collocated with an even channel ingress manifold. The odd channel egress manifold connects the odd outlets to a common odd outlet C_{out} . The even channel ingress manifold connects the even inlets to a common even inlet, H_{in} . As such, a first fluid can pass from the odd channels

to the common odd outlet. As such a second fluid can pass from the common even inlet to the even channels.

[0047] The second manifold 4 comprises, in reciprocity with the first manifold 2, an even channel egress manifold collocated with an odd channel ingress manifold. The even channel egress manifold connects the even outlets to a common even outlet. The odd channel ingress manifold connects the odd inlets to a common odd inlet C_{in} . As such, a first fluid can pass from the even channels to the common even outlet H_{out} . As such a second fluid can be transported from the common odd inlet C_{in} to the odd channels.

[0048] With reference to Figure 2, there is shown a three-dimensional portion 200 of a heat exchanger core which could be used in the heat exchanger 100. The portion 200 is shown in the context of three mutually orthogonal reference axes, x, y, and z. As shown on the page, the y-dimension corresponds to height (up/down), the x-dimension corresponds to width (fore/aft, or alternatively right/left) and the z-dimension corresponds to depth (near/far).

[0049] The portion 200 corresponds to a portion of the third, fourth and fifth channels of the core 3.

[0050] The portion 200 is comprised by a set of repeating units R (shown as the shaded components in the top left of Figure 2).

[0051] A repeating unit R comprises a base plate section 216 which has a rectangular planar form, which is parallel with the zx plane.

[0052] Formed in the base plate section 216 is a pair of openings 218a and 218b and a pair of linear conduits 208a, 208b. The openings and conduits are arranged such that their footprints in the plate 216 define a rectangle, with conduit footprints positioned diagonally opposite on another.

[0053] The conduits 208a and b extend in or parallel to the yx plane out from the plate 216 and are inclined to the plate 216 by approximately 45 degrees. More particularly the near conduit 208a extends from a foremost and nearest footprint in a backwards direction (-45 degrees), and the far conduit 208b extends from an aftwards and farthest footprint in a forwards direction (+45 degrees).

[0054] As such, given that the base plate 216 defines an axis P which extends perpendicularly through the centroid of the plate 216, the openings 218a 218b and the conduits 208a 208b are arranged such that they exhibit rotational symmetry, order 2, about the base plate axis P.

[0055] The extension of the conduits is such that the near conduit 208a meets the near opening of the plate 226 below, whilst the far conduit meets the far opening of the plate 226 below.

[0056] Whilst only a section 200 of a core 3 has been described, it will be appreciated that any size of core 3 could be populated with repeating units R by forming multiple repeating units in the x, y, and z directions. In effect this would form a number of continuous base plates interconnected by a plurality of conduit pairs.

[0057] With all conduits of the portion 200 extending parallel to the same plane, the yx plane, such cores would be suitable for co-flow and counter-flow arrangements.

[0058] With reference to Figure 3, there is shown a portion 300 for a heat exchanger core which would be suitable for a cross-flow arrangement.

[0059] The portion 300 shown comprises three channels 320, 340 and 360 interleaved in that order. The channels 320 and 360 are for passing a first fluid, H, in the x-direction (that is to say from aft to fore) and the channel 340 is for transporting a second fluid, C, in the z-direction (i.e. from near to far).

[0060] Each of a plurality of conduits 308 extends between the H channels 320 and 360, and through the C channel 340, in or parallel to the yx plane. Thus the channels 320 and 360 are in fluid communication.

[0061] Each of a plurality of conduits 309 extends between the C channel 340 and the next upwards C channel, passing through the H channel 320, in or parallel to the yz plane.

[0062] The portion 300 for the heat exchanger core can be seen as a combination of the repeating unit R discussed in connection with portion 200 and Figure 2, with a further repeating unit. As shown in Figure 3, two R-type units are present in one layer, and these are sandwiched between further layers, each further layer having two further repeating units. As such the R-type layers alternate with further-type layers.

[0063] Each further repeating unit is the mirror image of the unit R, reflected in an yz plane, and rotated by 90 degrees, about its plate axis P.

[0064] With reference to Figure 4, there is shown schematically a further example of a portion, indicated generally at 400, of a heat exchanger core.

[0065] The portion 400 is comprised from a number of repeating units Q, each of which, as with repeating units R, tessellates with other repeating units. The units Q comprise a hexagonal base plate 416, in which is provided six regularly spaced footprints, arranged symmetrical about the axis defined by the plate 416. Three of the footprints correspond with openings 418a-c, three of the footprints correspond with conduits 408a-c which extend upwardly from the base plate in the yx plane. Two of the conduits, the nearest 408a and farthest 408c extend aftwards. The other conduit, middle/aftmost conduit 408b, extends forwards.

[0066] Figure 6 shows a monolithic multi-channel heat exchanger 600 where three first fluid channels 620, 640 and 660 are interleaved with 2 second fluid channels 630 and 650. A first integrated manifold 602 communicates with the channels at a first side of the exchanger 600. A second integrated manifold 604 communicates with the channels at a second side of the exchanger 600.

[0067] The first manifold 602 comprises a first common port 602a for working fluid H and a second common port 602b for coolant C.

[0068] The first common port 602a is generally cylindrical and communicates with three branches (one of

which 622 is visible) each of which meets a respective taper section (624) which tapers out to meet a respective channel (620).

[0069] The second common port 602b is generally cylindrical and communicates with two branches 621, 623 each of which meets a respective taper section 625, 627 which tapers out to meet a respective channel 630, 650.

[0070] For illustrative purposes, heat exchanger 600 is shown in cut-away, at a point in the core equivalent to the cross section WW shown in Figure 2.

[0071] In the heat exchanger 600, for a given plate, the separation between each opening and the outer diameter of the relevant neighbouring conduit is negligible. In other words and with respect to Figure 2, the separation S is zero. Such a provision tends to promote smooth flow from the channel into the conduit.

[0072] For either the heat exchanger 100 or 600, in operation, a first, or cold fluid C, is put under pressure and thereby caused to flow into the common cold fluid inlet of first manifold, then through the first manifold, then into and through the even channels and then into the second manifold, and then out of the second manifold at the common cold outlet.

[0073] Whilst flowing through the first manifold, the cold fluid splits into separate flows, each one associated with a particular even channel. As the fluid flows through a given even channel, it may be further diverted by the conduits 9, which bleed off some of the fluid into neighbouring even channels. Meanwhile, some of the fluid flowing through neighbouring even channels will be bled off into the given even channel.

[0074] Whilst flowing within the given even channel, the fluid will flow around the odd conduits 8 which extend through the given channel.

[0075] An equivalent flow occurs as the second, or hot fluid, is introduced to heat exchanger at the second manifold, whereupon it flows into and through the odd channels, and into first manifold where it leaves the heat exchanger.

[0076] No mixing of the first and second fluids is permitted.

[0077] The base plates and conduits are formed from a thermally conductive material. Thus there is provided a surface area at the boundaries between hot and cold fluids which enable the transfer of thermal energy from the hot fluid to the cold fluid.

[0078] The inclination of the conduits 9, 8 promotes bleeding off and inter-channel fluid mixing. In particular, the conduits that extend from a given channel in the opposite general direction to the flow (e.g. at -45 degrees), will tend to bleed fluid into the given channel from neighbouring same-fluid channels. Further, conduits extending from a given channel in the same general direction to the flow (e.g. at +45 degrees) will tend to bleed fluid out of the given channel into neighbouring same-fluid channels.

[0079] The interconnecting conduits 8 and 9 are generally inclined at 45 degrees and as such are biased to

promote the inter-channel flow. Such an angle can be achieved using an additive layer manufacturing process, providing a sufficiently robust structure without requiring supports or buttressing. In alternative examples, a range of angles may be suitable for this inclination. For example inclinations in the range of 30 to 60 degrees or 40 to 50 degrees may be suitable, with additional supporting structures provided as appropriate.

[0080] In other alternative examples of the heat exchanger, the conduits could extend perpendicularly from the base plate and thereby achieve promote inter-channel fluid mixing; such an arrangement may lead to a greater pressure drop across the core as compared with the inclined conduits.

[0081] Alternatively, conduits could be fitted with a one-way valve to promote certain flow characteristics.

[0082] For cross-flow heat exchanger examples, it may not be straightforward to collocate the first fluid ingress manifold and the second fluid egress manifold (and vice versa) at a single integrated manifold 2 (or 4). Thus in cross-flow configurations, there could be four separate manifolds.

[0083] The heat exchangers provided for can be formed from a heat-conducting material having the structural integrity to retain complex forms. Metals for example would be suitable.

[0084] The heat exchangers provided for can be manufactured using additive layer manufacturing techniques (also known as additive manufacturing, or 3D printing). For example, a selective laser melting (SLM) process may be used to form the heat exchanger. SLM uses a high power-density laser to melt and fuse metallic powders together.

[0085] Thus, in accord with these properties, the heat exchanger may be formed from any of a number of suitable materials which would be apparent to the skilled person, including but not limited to an Inconel alloy, titanium or an alloy thereof, aluminium or an alloy thereof, or a stainless steel.

[0086] With reference to Figure 7, a method of forming a heat exchanger structure is shown as involving a first step 702 of defining a repeating unit, a second step 704 of defining an operational characteristic set for a heat exchanger structure, a third step 706 of determining the parameters of the repeating units which satisfy the operational characteristic set, and at a fourth step 708, forming the structure according to the parameters.

[0087] At step 702, defining the repeating unit includes providing the definition of the repeating unit R having a set of variable parameters including but not limited to: base plate size, base plate thickness, base plate shape, conduit upward extension (i.e. channel height), opening/conduit bore, conduit wall thickness, conduit inclination, footprint location, and in-channel orientation (i.e. which plane the conduits align with for a channel, determining counter flow or co flow).

[0088] At step 704, the operational characteristic set may define a number of constraints including but not limited to:

a desired thermal transfer rate, a working fluid combination (e.g. air and air, oil and fuel, air and glycol), a given space into which the exchanger should fit, a channel height, and an allowable pressure drop across the heat exchanger.

[0089] At step 706, the determination of the parameters of the unit R could be carried out, in light of the operational characteristics from step 704, using a number of fluid dynamic simulations of the heat exchanger. These simulations could be carried out iteratively, for example in combination with a genetic algorithm, to arrive at a solution. The output of such determinations would be a data file defining a suitable heat exchanger, the definition including the parameters for the unit R, and the number of R units along each of the three orthogonal axes (for example referring back to figure 6, it can be seen that there are four units along the fore to aft axis, and five along the bottom to top axis, with the near to far number being hidden from view).

[0090] At step 708, the heat exchanger could be formed by issuing the data file to an additive layer manufacturing station.

[0091] In certain examples a manifold, corresponding to the heat exchanger core, could be generated by the process. A data file defining such a manifold could thereby be issued to an additive manufacturing station, alongside the heat exchanger data file, to enable the entire heat exchanger to be formed.

[0092] In general, the examples given so far have been in the form of multi-layer heat exchangers. In other examples, the heat exchanger may comprise channels in the form of a tubular cluster. Within this cluster, a first group of tubes (odd tubes) would carry a first fluid, and a second group of tubes (even tubes) would carry a second fluid. A first set of conduits would provide interconnections between the odd tubes, with interconnecting conduits passing through an even tube. A second set of conduits would interconnect the even tubes, with interconnecting conduits passing through an odd tube. As a further alternative, such tubular clusters could comprise linear tubes arranged in parallel. Such tubular clusters could comprise nested spirals of tubes.

[0093] In general, the example cores given so far have been in the form of planar or substantially planar layers and channels, formed by planar base plates stacked in parallel. In alternative examples, the core may be provided by a plurality of curved channels which may be of a predetermined shape or curvature so as to be conformal with a further device. The further device could be a substantially cylindrical engine. Within such cores, channels could be substantially conformal with one another, so as to maintain an inter-plate separation.

[0094] All of the features disclosed in this specification (including any accompanying claims, abstract and drawings), and/or all of the steps of any method or process so disclosed, may be combined in any combination, except combinations where at least some of such features and/or steps are mutually exclusive.

[0095] Each feature disclosed in this specification (including any accompanying claims, abstract and drawings) may be replaced by alternative features serving the same, equivalent or similar purpose, unless expressly stated otherwise. Thus, unless expressly stated otherwise, each feature disclosed is one example only of a generic series of equivalent or similar features.

[0096] The invention is not restricted to the details of the foregoing embodiment(s). The invention extends to any novel one, or any novel combination, of the features disclosed in this specification (including any accompanying claims, abstract and drawings), or to any novel one, or any novel combination, of the steps of any method or process so disclosed.

Claims

1. A heat exchanger comprising:

A first channel, for communicating between a first channel inlet and a first channel outlet;
A second channel for communicating between a second channel inlet and a second channel outlet;
A third channel for communicating between a third channel inlet and a third channel outlet; and
A first conduit interconnecting the first channel and the third channel, and thereby defining a first group of interconnected channels, the first conduit extending through the second channel.

2. A heat exchanger according to claim 1 wherein the first conduit is inclined relative to a central axis defined by the first channel and thereby arranged to promote inter-channel flow.

3. A heat exchanger according to claim 1 or 2 comprising a plurality of first conduits interconnecting the first channel and the third channel, the plurality of first conduits extending through the second channel.

4. A heat exchanger according to claim 3 wherein the plurality of first conduits are spaced apart at regular intervals.

5. A heat exchanger according to claim 3 or 4 wherein the plurality of first conduits are arranged in adjacent pairs where one conduit per pair is arranged to promote inter-channel flow from the third channel to the first channel, and the other conduit per pair is arranged to promote inter-channel flow from the first channel to the third channel.

6. A heat exchanger according to any of the previous claims further comprising:

A fourth channel, for communicating between a

fourth channel inlet and a fourth channel outlet, A second conduit interconnecting the second channel and the fourth channel and thereby defining a second group of interconnected channels, the second conduit extending through the third channel.

7. A heat exchanger according to claim 6 wherein the second conduit is inclined relative to a central axis defined by the second channel.

8. A heat exchanger according to claim 6 or 7 comprising a plurality of second conduits interconnecting the second channel and the fourth channel, each of the second conduits extending through the third channel.

9. A heat exchanger according to claim 8 wherein the plurality of second conduits are arranged in adjacent pairs where one conduit per pair is arranged to promote inter-channel flow from the fourth channel to the second, and the other conduit per pair is arranged to promote inter-channel flow from the second channel to the fourth.

10. A heat exchanger according to claim 9 when dependent on claim 5 wherein the first conduit pairs and the second conduit pairs occupy an equivalent position in the second and third channel respectively.

11. A heat exchanger according to any of claims 6 to 10 comprising a top plate and plurality of base plates mounted between a pair of side walls, wherein

The first channel is defined between the top plate, a first base plate and a portion of the side walls

The second channel is defined between the first base plate, the second base plate and a portion of the side walls,

The third channel is defined between the second base plate, the third base plate and a portion of the side walls, and

The fourth channel is defined between the third base plate, a fourth base plate and a portion of the side walls.

12. A heat exchanger according to claim 11 wherein the first and third channels, being in fluid communication, are arranged to transport a first fluid in a first flow direction, and the second and fourth channels, being in fluid communication are arranged to transport a second fluid in a second flow direction.

13. A heat exchanger according to claim 12 wherein the first and second flow directions can be generally opposite to provide a counter-flow heat exchanger.

14. A heat exchanger according to claim 13 further comprising, towards a first end:

A first fluid ingress manifold connecting the inlets of the first and third channels to a common first fluid inlet port, and 5

A second fluid ingress manifold connecting the outlets of the second and fourth channels to a common second fluid outlet port;

10

And towards a second end:

A first fluid egress manifold connecting the outlets of the first and third channels to a common first fluid outlet port, and 15

A second fluid egress manifold connecting the inlets of the second and fourth channels to a common second fluid outlet port.

15. A method of heat exchange comprising 20

Providing a heat exchanger according to any of the preceding claims, Causing a coolant fluid to flow through the first and second channels
Causing a working fluid to flow through the third channel. 25

30

35

40

45

50

55

Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6





Figure 7





EUROPEAN SEARCH REPORT

 Application Number
EP 18 16 0938

5

10

15

20

25

30

35

40

45

50

55

2

EPO FORM 1503 03.02 (P04C01)

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	GB 1 506 721 A (LORRAINE CARBONE) 12 April 1978 (1978-04-12) * figure 1 *	1-15	INV. F28F7/02
A	US 2009/101313 A1 (HOFMANN WILFRIED [DE]) 23 April 2009 (2009-04-23) * figures 1-5 *	1-15	
X	WO 2008/139651 A1 (KANKEN TECHNO CO LTD [JP]; IMAMURA HIROSHI [JP]) 20 November 2008 (2008-11-20) * figure 1 *	1,15	
			TECHNICAL FIELDS SEARCHED (IPC)
			F28F
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 18 July 2018	Examiner Martínez Rico, Celia
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 18 16 0938

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-07-2018

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 1506721 A	12-04-1978	DE 2508867 A1	04-09-1975
		FR 2262550 A1	26-09-1975
		GB 1506721 A	12-04-1978

US 2009101313 A1	23-04-2009	DE 102006018709 B3	11-10-2007
		DE 102006035552 A1	31-01-2008
		EP 2010853 A1	07-01-2009
		JP 2009534817 A	24-09-2009
		US 2009101313 A1	23-04-2009
		WO 2007121925 A1	01-11-2007

WO 2008139651 A1	20-11-2008	JP 5095729 B2	12-12-2012
		JP WO2008136217 A1	29-07-2010
		WO 2008139651 A1	20-11-2008

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 2014135844 A [0002]