

(19)



(11)

**EP 3 604 129 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**05.02.2020 Bulletin 2020/06**

(51) Int Cl.:  
**B64C 29/00** <sup>(2006.01)</sup> **B64C 39/00** <sup>(2006.01)</sup>  
**B64C 39/02** <sup>(2006.01)</sup>

(21) Application number: **18382588.4**

(22) Date of filing: **03.08.2018**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**  
Designated Extension States:  
**BA ME**  
Designated Validation States:  
**KH MA MD TN**

(72) Inventors:  
• **CASTELLANO ALDAVE, Jesus Carlos**  
**31512 Fontellas (Navarra) (ES)**  
• **VILLADANGOS ALONSO, Jesus**  
**31621 Sarriguren (Navarra) (ES)**  
• **ASTRAIN ESCOLA, Jose Javier**  
**31010 Barañain (Navarra) (ES)**

(71) Applicant: **Fuvex Civil, SL**  
**31621 Sarriguren (Navarra) (ES)**


(74) Representative: **Juncosa Miró, Jaime**  
**Torner, Juncosa i Associats, S.L.**  
**Gran Via de les Corts**  
**Catalanes, 669 bis, 1<sup>o</sup>, 2<sup>a</sup>**  
**08013 Barcelona (ES)**

**(54) UNMANNED AERIAL VEHICLE WITH DIFFERENT FLIGHT MODES**

(57) An unmanned aerial vehicle, UAV, comprising a fuselage (1) with at least one rotating shaft (2) and one wing (3) positioned on said rotating shaft (2), protruding from either side of said fuselage (1). Preferably, the UAV has at least one rotor propeller (4) arranged on each rotating shaft (2), on either side of said fuselage (1), comprising one or more rotor blades (4a) and a housing (4b) which includes an actuator.

The UAV is capable of shifting between a first flight

mode using rotatable wings which rotate freely around the rotating shaft (2) only due to a direction and strength of wind impinging against a surface of the wings (3) and a downstream flow generated by the rotor propellers (4), and a second flight mode using fixed wings, kept in a predetermined position by means of a wing-locking mechanism, preferably a substantially horizontal position.

**Fig. 1**

## Description

### Technical field

**[0001]** The present invention discloses a convertible unmanned aerial vehicle, also used in the abbreviated form UAV, with tilt-rotor and tilt-wing characteristics, where the term unmanned aerial vehicle is also known commonly as a drone or an unmanned aircraft.

**[0002]** Moreover, the present invention discloses a UAV capable of modifying its flight mode configuration between a first flight mode using rotor propellers to generate lift whilst keeping the wings free to rotate, tilt or revolve around their own longitudinal axis (transversal to the vehicle fuselage) and, a second flight mode using propellers to push the aircraft forward in a horizontal direction while the main wings remain fixed in a lift generation position, also known as convertiplane.

### State of the Art

**[0003]** The concept of a tilt-rotor aircraft arose initially in the first decades of the 1900s and refers to aircraft capable of repositioning the rotor propellers or proprotors arranged on wings, usually fixed wings, allowing the aircraft to manoeuvre in a horizontal or vertical (hovering) direction, as well as also being suitable for vertical take-off and landing (VTOL). The first modern prototypes and models were produced during the 1950s and 1960s applied to manned aircraft vehicles, especially military aircraft.

**[0004]** US patent application 2015/136,897 discloses a fixed wing unmanned aerial vehicle comprising a plurality of propellers, arranged on the cited wing, which can be pivoted between a vertical and horizontal position through the use of a pivoting mechanism

**[0005]** On the other hand, the term tilt-wing is used to describe aircraft capable of rotating its wings, in a similar manner as the rotor propellers in a tilt-rotor aircraft, so that the aircraft is capable of conventional forward flight or hovering, as well as conventional or vertical take-off and landing. As is the case with the first tilt-rotor aircrafts, the first modern prototypes and models were also produced during the 1950s and 1960s applied to manned aircraft, especially military aircraft.

**[0006]** US patent n<sup>o</sup> 2,708,081 discloses an aircraft comprising a fuselage, a wing on either side of the fuselage with propellers and power units arranged on the outer ends of the wings and means for rotating the wings around an axis relative to the fuselage.

**[0007]** However, tilt-wing aircraft vehicles designed for either manned or unmanned navigation, present a serious drawback in their design when the fixed wings are positioned vertically in a hover mode as well as during vertical take-off and landing, as the surface area of the wing is at its maximum exposure to crossover winds which reduces the aerodynamic properties of the aircraft and increases the drag effect, therefore reducing the lift

effect.

**[0008]** These concepts, initially applied to manned aircraft vehicles, have been adjusted and extrapolated to unmanned aerial vehicles, such as drones, and therefore there is a wide range of tilt-rotor and tilt-wing UAVs available in the market.

**[0009]** Patent application WO2016/120,833 discloses a tilt-rotor drone which comprises a fuselage, a couple of wings connected to the fuselage having a longitudinal axis "X", so that each wing rotates around the longitudinal axis "X" with respect to the fuselage. The drone includes multiple rotors, each rotor connected to a wing and configured to rotate around longitudinal axis "X", and each rotor comprising at least one blade rotating around a rotation axis "Y", substantially orthogonal to longitudinal axis "X". However, this document doesn't solve the issue regarding crossover winds colliding or impacting against wings in a vertical position.

**[0010]** The present invention aims to overcome the cited problems, as well as providing a UAV which is readily stored or assembled due to the particular design of the different components.

### Brief description of the invention

**[0011]** The present invention discloses an aircraft, specifically an unmanned aerial vehicle (hereafter UAV or drone) capable of shifting between a first flight mode using rotary wings, and a second flight mode using fixed wings, the UAV comprising a fuselage, which defines a longitudinal axis "Y" along the centre of gravity of the UAV and parallel to said fuselage, with one or more rotating shafts protruding from two opposite sides of the fuselage along a transversal longitudinal axis "X", perpendicular to longitudinal axis "Y", with one or more wings on either side of the fuselage arranged on the rotating shaft, so that the wings rotate with regards to the fuselage around the rotating shaft defined by the longitudinal axis "X".

**[0012]** Rotor propellers are arranged on either side of the fuselage on the one or more rotating shafts, preferably with at least one rotor propeller per wing. Each rotor propeller comprises a plurality of rotating blades powered by an engine, or an alternative power source, enclosed in a casing mounted on the rotor shaft. Propeller blades are usually made of wood, metal or polymeric composites, wherein the latter may or may not include reinforcements such as carbon fibres.

**[0013]** The wings of the UAV, disclosed herein, are characterised in that they have a particular design. Each one of the wings is made up of a front detachable component and a rear detachable component, both of them mounted around the at least one rotating shaft, so that the front detachable component defines a leading edge of each wing and the rear detachable component defines a trailing edge of each wing. It should be noted that the front detachable component, the rear detachable component or both of them may be made up of one or more

parts. When the components of each wing are assembled together, they include at least one cut-out portion, suitable for adequately surrounding the casing of the rotor propeller arranged on the rotating shaft, as well as allowing each of the rotor propellers to rotate freely in conjunction with the rotation of the rotating shaft on which it has been installed or arranged between said first and second flight modes, without risk of collision with the wings.

**[0014]** The front and rear detachable components are assembled together, in a particular embodiment, by means of opposing rows of magnets arranged on opposite adjacent surfaces of the front and rear detachable components, wherein said opposing rows of magnets have opposing poles. However, other suitable assembling mechanisms may be used in alternative embodiments such as:

- a combination of one or more rows of evenly distributed inserts protruding from at least one surface of either one or both of the components which are inserted into orifices arranged collinearly on an opposite adjacent surface of the other detachable component,
- a tongue-and-groove configuration in which the detachable components are assembled or disassembled by laterally sliding them together,
- one or more clasping elements arranged along at least one section of the wing where the detachable components are in contact with one another, or
- joining both detachable components through the use of multiple screws or bolts in combination with an equal number of nuts or other similar retaining elements, which are accessible from the outside through retractable panels installed on both components.

**[0015]** Other suitable mechanisms, not disclosed herein but which are known in the current state of the art and the use of which would be obvious to an expert, may also be used.

**[0016]** Furthermore, the front and rear detachable components may or may not be proportional in size, so that in a particular embodiments of the invention the rear detachable component is considerably larger than its counterpart, the front detachable component, or vice versa or they are both approximately the same size.

**[0017]** Due to the fact that the wings of the UAV are detachable, this allows the UAV to be easily assembled or disassembled, and therefore improves its transportability as it may be stored as independent components when it isn't being used.

**[0018]** In view of the wing configuration previously disclosed, the UAV is also characterised in that it is able to shift between a first flight mode and a second flight mode, so that in the first flight mode, each wing is assembled

and arranged so that it can rotate freely around the rotating shaft onto which it has been assembled and having attached to it the rotor propeller, wherein the rotating shaft only serves as a guiding element and doesn't produce or cause any rotational movement which affects the rotation of the wing itself. In this first flight mode the wing is positioned or oriented according to a direction and strength of the wind (crossover wind) impinging against the surface area of the wing, as well as a downstream flow generated by the rotor propeller, which produces a rotary movement along the transversal longitudinal axis "X", and therefore the wings on either side of the fuselage may rotate independently from one another, around the rotating shaft on which they are assembled.

**[0019]** By allowing the wings to rotate freely around their rotating shaft, only due to a crossover wind impinging against the surface area of each wing and the downstream flow generated by the rotor propellers reduces the drag effect generated in conventional tilt-wing aircraft when the wing is rotated and left in a fixed position. By adjusting the angle of the rotor propellers, the UAV can determine an optimum flight course during hovering mode or vertical take-off and landing, also known as VTOL.

**[0020]** With regards to the second flight mode, each wing remains in a predetermined fixed position, for example in a transversal horizontal plane by means of a wing-locking mechanism, providing the UAV with a conventional lift drive caused in conventional forward flight. The cited wing-locking mechanism affords the wings a limited freedom of movement so that each wing may independently adjust their pitch angle around the longitudinal axis "X", transversal to the vehicle fuselage also known as the pitch axis, in order to:

- stabilise the aircraft, by simulating and achieving a similar effect caused by the presence of flight control surfaces included in the wings such as flaps and/or ailerons, which are not present in the disclosed invention, therefore simplifying the design of the wings used in the UAV and improving the aerodynamic properties of the wings by not disrupting their geometry;
- generate a rotational moment around the longitudinal axis "Y", also known as the roll axis of the aircraft, which affects the turning or change of direction of the UAV by banking or inclining towards the inside of a turning movement of the UAV, by increasing the lift of the one or more wings on one side of the fuselage with regards to the one or more wings on the other side of the fuselage; and/or
- modify an angle of a plane surface in relation to a horizontal stabiliser of an empennage or tail of the UAV, in order to further stabilise the UAV.

**[0021]** The wing-locking mechanism used in the sec-

ond flight mode is preferably selected from a group comprising:

- an adjustable buffer positioned on either side of the fuselage, for each wing, which limits and retains the trailing edge of the rear detachable component of each wing, limiting the elevation of the wing due to a negative angular momentum generated by a lift effect;
- one or more magnetic limiting elements arranged along a path on the fuselage equivalent to the path done by the trailing edge of each wing, with a magnet of an opposite pole arranged on the trailing edge of the wing adjacent to the fuselage; or
- a mechanical retainer such as a pin, a bolt or an equivalent element which is optionally adjustable in height which is inserted into a cavity of a surface of the wing adjacent to the fuselage, near the trailing edge, so that when the mechanical retainer is inserted in the cavity it retains the wing in position at a fixed or a variable angle, the latter being the preferred option, due to the geometry of the cavity which may be slot shaped affording the mechanical retainer a certain freedom of movement.

**[0022]** However, other equivalent mechanisms which provide the same effect, not disclosed herein, may be used and should be considered equivalent.

**[0023]** In different embodiments of the present invention, each one of the at least one rotating shaft protruding from the fuselage has at least one port rotating shaft, and one starboard rotating shaft, so that a rotating shaft of the UAV is made up of either one port rotating shaft and one starboard rotating shaft forming one transversal rotating shaft, or so that the at least one port rotating shaft and said at least one starboard rotating shaft are independent from one another.

**[0024]** Furthermore, each one of the rotating shafts arranged on a particular embodiment of the UAV may be powered by either one actuator, or multiple independent actuators, so that each one of the independent actuators is associated with one rotating shaft or a port rotating shaft and a starboard rotating shaft which together form a rotating shaft with two different actuators.

**[0025]** The rotating shafts made up of one port rotating shaft and one starboard rotating shaft may be arranged either co-aligned or non-aligned on either side of the fuselage, and are arranged along the longitudinal axis "Y", or roll axis, along the centre of gravity of the UAV.

**[0026]** It should be noted that in different embodiments of the present invention, the rotor propellers on either side of the fuselage may rotate independently from one another according to the rotation of the rotating shaft on which they are installed, as well as if they are arranged on either the same rotating shaft or independent rotating shafts. Regardless of whether the rotor propellers of the

UAV rotate independently from one another or not, they rotate between 0° and 90° with regards to a horizontal plane defined by the position of the wings in the second flight mode, where they are substantially horizontal and parallel to the ground.

**[0027]** It will be understood that references to geometric position, such as parallel, perpendicular, tangent, etc. allow deviations up to  $\pm 5^\circ$  from the theoretical position defined by this nomenclature.

**[0028]** It will also be understood that any range of values given may not be optimal in extreme values and may require adaptations of the invention to these extreme values are applicable, such adaptations being within reach of a skilled person.

**[0029]** Other features of the invention appear from the following detailed description of an embodiment.

#### Brief description of the Figures

**[0030]** The foregoing and other advantages and features will be more fully understood from the following detailed description of an embodiment with reference to the accompanying drawings, to be taken in an illustrative and not limitative, in which:

- **FIG. 1** is an exploded view of a port wing, illustrating the different components of a particular embodiment of a wing,
- **FIG. 2** illustrates a wing, as seen in **FIG. 1**, in a second flight mode, as a fixed wing,
- **FIG. 3a** to **FIG. 3c** illustrate different wing positions of a port wing, as seen in **FIG. 1**, when the UAV is in a first flight mode, as a rotary wing, and
- **FIG. 4a** and **FIG. 4b** illustrate, respectively, a particular embodiment of a UAV in a second flight mode and in a first flight mode in which the UAV has two wings on either side of the fuselage.

#### Detailed description of an embodiment

**[0031]** The foregoing and other advantages and features will be more fully understood from the following detailed description of an embodiment with reference to the accompanying drawings, to be taken in an illustrative and non-limitative manner, in which:

**FIG. 1** illustrates the different components which together form a wing 3, specifically the port wing, in a particular embodiment of the UAV. The wing 3 is made up of a front detachable component 3a which defines a leading edge 30a of the wing 3, comprising two separate parts, and a rear detachable component 3b which defines a trailing edge 30b of the wing 3, comprising a single part. The two components, 3a and 3b, are assembled together around a rotating shaft 2, coaxial to a longitudinal axis "X" that is transversal to the aircraft fuselage 1, by means of op-

posing rows of magnets 6 arranged on opposite adjacent surfaces of the front and rear detachable components 3a, 3b, the opposing rows of magnets 6 having opposing poles. Furthermore, the front and rear detachable components 3a, 3b are assembled together leaving a cut-out portion or space 3c, so that a rotor propeller housing 4b of the rotor propeller 4 may rotate freely according to the rotation of the rotating shaft 2 on which it has been attached without risk of collision with the wing, 3, itself.

**[0032]** The rotor propeller 4 comprises a plurality of rotor blades 4a and a housing 4b or encasement installed on the rotating shaft 2 which includes the actuating means to power the rotor propeller 4, specifically the rotor blades 4a.

**[0033]** This description is also valid for the starboard wing, in this particular embodiment of the UAV.

**[0034]** **FIG. 2** and **FIGs. 3a to 3c** show a wing 3 of the UAV, according to the description included in **FIG. 1**, in different positions according to a second flight mode and a first flight mode of the UAV, respectively.

**[0035]** **FIG. 2** shows a wing 3 positioned in the second flight mode of the UAV, wherein the wing 3 of the UAV is fixed at a predetermined angular position due to a wing-locking mechanism (not shown in this figure as the fuselage 1 of the UAV isn't visible). In the second flight mode, the rotor propellers 4 are positioned in a substantially horizontal position, 0°, and therefore the UAV flies in a similar manner to a conventional forward flight aircraft.

**[0036]** However, the wing positions illustrated in **FIGs. 3a to 3c**, are relevant to the first flight mode in which each wing 3 is arranged so as to rotate, tilt or revolve freely around the rotating shaft 2 wherein:

- in **FIG. 3a** the wing 3 is positioned in such a manner due to a direction of the crossover or flow of wind (direction indicated with the arrow) impinging against the surface area of the wing 3, and therefore the wing 3 is pushed and repositioned after rotating around the transversal longitudinal axis "X", also known as pitch axis;
- in **FIG. 3b** the wing 3 remains in place as the crossover or flow of wind which impinges against the surface area of the wing 3 is negligible and therefore doesn't affect the natural position of the wing in the first flight mode; and
- in **FIG. 3c**, the wing 3 is positioned according to the description of **FIG. 3a**, but in the opposite sense due to the direction, indicated with the arrow, of the crossover or flow of wind impinging against the surface area of the wing 3.

**[0037]** The rotor propellers 4 shown in **FIGs. 3a to 3c**, are positioned with the rotating blades 4a parallel to the ground, with the housing 4b at an angle of approximately 90°, therefore allowing the UAV to hover as well as vertical take-off and landing (VTOL).

**[0038]** Both **FIG. 4a** and **FIG. 4b** illustrate a particular embodiment of a UAV, according to the information disclosed previously, in which the UAV has two wings 3 on either side of the fuselage 2, with the housing 4b of the rotor propeller 4, containing the driving means or actuator of the propeller 4, is arranged on the rotating shaft 2 of each wing 3.

**[0039]** In **FIG. 4a** this particular embodiment of the UAV is in the second flight mode, therefore the wings 3 are in a locked position in a substantially horizontal plane parallel to the ground, due to the wing-locking mechanism integrated in the fuselage 2, preferably in an area near the trailing edge 30b of the rear detachable components 3b of each wing 3. The rotor propellers 4 of each wing 3 are facing forwards, and are arranged in such a manner so that the downstream flow generated by the blades 4a of the rotor propellers 4 in the forward wings 3 does not substantially affect the rear wings 3.

**[0040]** On the other hand, **FIG. 4b** the UAV is in the first flight mode, and therefore the wings 3 are substantially perpendicular to the ground in a vertical disposition, due to negligible crossover winds, and the rotor propellers 4 are in hover mode. The position of the wings 3 may vary, as seen and described in **FIGs. 3a to 3c**, according to the direction and strength of the wind which strikes a surface area of the wings 3 as well as the downstream flow generated by the rotor blades 4a of the rotor propeller 4.

**[0041]** The unmanned aerial vehicle (UAV) or drone disclosed herein may be powered by means of one or more fuel cells, one or more batteries (preferably Lithium polymer batteries), or other alternative power sources which supply energy to one or more actuators, such as an electric motor or an electromechanical motor, installed in the fuselage 2.

**[0042]** The fuselage 2 may have any suitable aerodynamic shape and it may optionally include an empennage (also known as tail or tail assembly) at rear section of the fuselage 2 in order to further provide more stability to the UAV. The empennage may include one or more of either a vertical stabilising surface, a horizontal stabilising surface or both, which provide further control of the flight dynamics of the UAV, specifically yaw and pitch of the UAV.

**[0043]** Furthermore, for any particular embodiment of the present invention, the UAV may be configured to modify, switch or transition from the first flight mode to the second flight mode, or vice versa, either manually or automatically.

**[0044]** If the transition between the two flight modes is manual, the UAV pilot or UAV controller decides when the wings 3 are in an optimum position to be retained by the wing-locking mechanism, when the wings 3 are initially in the first flight mode arranged to rotate freely around a rotating shaft 2. The UAV pilot controls the tilt angle of the rotor propellers 4 by the one or more rotating shafts 2 protruding transversally from the fuselage 1, evaluates flight parameters and conditions and then de-

cides if the wings 3 are positioned adequately to activate the wing-locking mechanism and retain the wings 3 in a substantially horizontal disposition, in the second flight mode. The UAV pilot can then determine when the UAV must transition from the second flight mode back to the first flight mode, and therefore deactivate the wing-locking mechanism.

**[0045]** However, if the transition between the two flight modes is automatic, thus the UAV is currently in an auto-pilot configuration, the transition between flight modes begins by tilting or modifying the angle of the rotor propellers 4 by rotating the one or more rotating shafts 2 and at the same time measuring and/or determining the speed of the UAV in relation to the wind as well as ensuring the performance of the UAV is still inside the performance envelope (also referred to as flight envelope) of the UAV. Once a minimum speed, associated to each flight mode, has been attained the rotor propellers 4 are ultimately positioned according to either the first flight mode or the second flight mode according to the flight transition that is taking place. The wings 3 are positioned due to a momentum/lift effect which modifies their position in the first flight mode, until they are at a substantially horizontal position in which the wing-locking mechanism is activated and the UAV has transitioned to the second flight mode.

**[0046]** It will be understood that various parts of one embodiment of the invention can be freely combined with parts described in other embodiments, even being said combination not explicitly described, provided there is no harm in such combination.

## Claims

1. An unmanned aerial vehicle, UAV, comprising:

- a fuselage (1),
- at least one rotating shaft (2) protruding from both sides of said fuselage (1),
- at least one wing (3) on either side of the fuselage (1) positioned on said rotating shaft (2), and
- at least one rotor propeller (4), comprising one or more rotor blades (4a) and a housing (4b) arranged on said rotating shaft (2) on either side of said fuselage (1),

wherein the UAV is configured to shift between a first flight mode using rotatable wings, and a second flight mode using fixed wings,

**characterised in that** in the first flight mode, each wing (3) is arranged so as to rotate freely around the at least one rotating shaft (2), and the wing (3) is oriented due to a direction and strength of the wind impinging against a surface area of the wing (3) as well as a downstream flow generated by the rotor propeller (4), **and in that** in the second flight mode, each wing (3) remains in a predetermined fixed po-

sition by means of a wing-locking mechanism.

2. UAV according to claim 1, wherein the wings (3) are each made up of front and rear detachable components (3a, 3b) mounted around said at least one rotating shaft (2), wherein said assembled wings (3) include a cut-out portion (3c) allowing each rotor propeller housing (4b) to rotate freely in conjunction with the rotation of the at least one rotating shaft (2) between said first and second flight modes.
3. UAV according to claim 1, wherein in the first flight mode the wings on either side of the fuselage (1) rotate independently from one another, around the at least one rotating shaft (2).
4. UAV according to claim 1, wherein in the second flight mode each wing (3) may independently adjust a pitch angle in order to:
  - stabilise the aircraft,
  - stabilise a bank angle around a longitudinal axis "Y", and/or
  - modify an angle of a plane surface in relation to a horizontal stabiliser of an empennage.
5. UAV according to claim 1, wherein the at least one rotating shaft (2) protruding from the fuselage (1) has at least, one port rotating shaft, and one starboard rotating shaft, wherein said at least one port rotating shaft and said at least one starboard rotating shaft are independent from one another.
6. UAV according to claim 5, wherein the at least one port rotating shaft and the at least one starboard rotating shaft are powered by:
  - one actuator, or
  - multiple independent actuators, wherein each independent actuator is associated with one rotating shaft.
7. UAV according to claim 5, wherein the at least one port and the at least one starboard rotating shafts are arranged either co-aligned or non-aligned on either side of the fuselage (1), and are arranged on or proximal to the centre of gravity of the UAV.
8. UAV according to claim 1, wherein the at least one rotating shafts are either co-aligned or non-aligned on either side of the fuselage (1), and are arranged on or proximal to the centre of gravity of the UAV.
9. UAV according to claim 1, wherein said front and rear detachable components are assembled together by means of opposing rows of magnets arranged on opposite adjacent surfaces of the front and rear detachable components, wherein said opposing


rows of magnets have opposing poles.

10. UAV according to claim 1, wherein the rotor propellers on either side of the fuselage (1) rotate independently from one another. 5
11. UAV according to claim 1 or 10, wherein the rotor propellers rotate between 0° and 90° with regards to a plane defined by said predetermined position of each wing in the second flight mode. 10
12. UAV according to claim 1, wherein the front detachable component defines a leading edge of each wing and the rear detachable component defines a trailing edge of each wing. 15
13. UAV according to claim 12, wherein the detachable components are not proportional in size.
14. UAV according to claim 1, wherein said wing-locking mechanism used in the second flight mode is selected from a group comprising: 20
  - an adjustable buffer positioned on either side of the fuselage (1), for each wing, which limits and retains the trailing edge of the rear detachable component of each wing, limiting the elevation of the wing due to a negative angular momentum generated by a lift effect; 25
  - one or more magnetic limiting elements arranged along a path on the fuselage (1) equivalent to the path done by the trailing edge of each wing, with a magnet of an opposite pole arranged on the trailing edge of the wing adjacent to the fuselage (1); or 30
  - a slidable mechanical retainer which is inserted into a cavity of a surface of the wing adjacent to the fuselage (1), retaining each wing in a predetermined position at a fixed or a variable angle. 3540


45

50

55








**Fig. 1**



**Fig. 2**









## EUROPEAN SEARCH REPORT

Application Number  
EP 18 38 2588

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	WO 2016/035068 A2 (AMIT REGEV [IL]) 10 March 2016 (2016-03-10)	1,3-5,7,8,10,14	INV. B64C29/00
Y	* page 3, lines 11-14; figures * -----	6,11	B64C39/00
Y,D	WO 2016/120833 A1 (STEFANUTTI LEOPOLDO [IT]) 4 August 2016 (2016-08-04)	6,11	ADD. B64C39/02
A	* figures * -----	1-5,7-10,12-14	
A	CN 104 925 247 A (LI HONGSHENG) 23 September 2015 (2015-09-23) * figures *	1-14	
A	CN 204 979 219 U (HONGHE COLLEGE) 20 January 2016 (2016-01-20) * figures * -----	1-14	
			TECHNICAL FIELDS SEARCHED (IPC)
			B64C
The present search report has been drawn up for all claims			
Place of search <b>Munich</b>		Date of completion of the search <b>7 January 2019</b>	Examiner <b>Douhet, Hervé</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 18 38 2588

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

07-01-2019

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2016035068 A2	10-03-2016	AU 2015310490 A1	20-04-2017
		BR 112017004139 A2	12-12-2017
		CA 2996481 A1	10-03-2016
		CN 107074352 A	18-08-2017
		EP 3188966 A2	12-07-2017
		JP 2017525621 A	07-09-2017
		RU 2017110703 A	03-10-2018
		US 2018086442 A1	29-03-2018
		WO 2016035068 A2	10-03-2016
-----			
WO 2016120833 A1	04-08-2016	NONE	
-----			
CN 104925247 A	23-09-2015	NONE	
-----			
CN 204979219 U	20-01-2016	NONE	
-----			

**REFERENCES CITED IN THE DESCRIPTION**

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

**Patent documents cited in the description**

- US 2015136897 A [0004]
- US 2708081 A [0006]
- WO 2016120833 A [0009]