



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
08.04.2020 Bulletin 2020/15

(51) Int Cl.:
F16G 13/16 ^(2006.01)

(21) Application number: **19210645.8**

(22) Date of filing: **09.04.2018**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(30) Priority: **10.05.2017 US 201715591916**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
18166296.6 / 3 401 570

(71) Applicant: **The Boeing Company**
Chicago, IL 60606-1596 (US)

(72) Inventors:
• **GALETTI, Ralph R.**
Chicago, IL Illinois 60606-1596 (US)
• **LAZARRO, Anthony A.**
Chicago, IL Illinois 60606-1596 (US)

(74) Representative: **Duxbury, Stephen**
Arnold & Siedsma
Bavariaring 17
80336 München (DE)

Remarks:

This application was filed on 21-11-2019 as a divisional application to the application mentioned under INID code 62.

(54) **APPARATUS FOR CONNECTING COMPONENTS**

(57) An example apparatus includes a cable track that includes a first side and a second side that is opposite the first side. The apparatus further includes two or more spacers. The two or more spacers include respective first ends that are attached to the first side of the cable track and respective second ends that are opposite the respective first ends. The two or more spacers further include respective first surfaces between the respective first ends

and the respective second ends and respective second surfaces that are opposite the respective first surfaces. The apparatus further includes two or more pins attached proximately to the respective second ends of the two or more spacers. The two or more pins protrude from the respective first surfaces of the two or more spacers and/or protrude from the respective second surfaces of the two or more spacers.




FIG. 1

Description

FIELD

[0001] The present disclosure generally relates to cable tracks, and more specifically to cable tracks with features that can lessen the probability that the cable track snags on itself as one section of the cable track moves over another section.

BACKGROUND

[0002] In various applications, it may be necessary to provide an electrical communication or power connection between two machine components, and/or fluid or pneumatic flow between two machine components. Difficulties may arise if at least one of the components is movable during operation of the machine. For example, the two components might move relative to each other such that electrical cables, flexible tubing, or similar means connecting the two components may become pinched, bent, or ruptured. Additionally, such movement may cause damage to electrical cables or flexible tubing as they are dragged over other components of the machine.

[0003] Cable tracks are generally designed to facilitate movement of components that are connected via electrical cables or flexible tubing, and to protect such cables or tubing from damage caused by the movement. A cable track typically takes the form of a flexible, elongated plastic or metal linkage having a protective interior region in which the cables and/or tubing can be placed. Springs or other means for storing mechanical energy may be used to help prevent the cable track from snagging on itself as one section of the cable track moves over another. But, such mechanical means may increase the stiffness and internal friction of the cable track, which may limit how quickly the cable track can move and/or increase the amount of energy required to cause movement. Accordingly, the snag-reducing features of some cable tracks may cause some degree of reduced mobility and may require increased energy input for movement.

SUMMARY

[0004] In one example, an apparatus for connecting components that move relative to each other is provided. The apparatus includes a cable track that includes a first side and a second side that is opposite the first side. The apparatus further includes two or more spacers. The two or more spacers include respective first ends that are attached to the first side of the cable track and respective second ends that are opposite the respective first ends. The two or more spacers further include respective first surfaces between the respective first ends and the respective second ends and respective second surfaces that are opposite the respective first surfaces. The apparatus further includes two or more pins attached proximately to the respective second ends of the two or more

spacers. The two or more pins protrude from the respective first surfaces of the two or more spacers and/or protrude from the respective second surfaces of the two or more spacers.

[0005] In another example, an apparatus for connecting components that move relative to each other is provided. The apparatus includes a cable track comprising a first side and a second side that is opposite the first side. The apparatus further includes two or more first spacers. The two or more first spacers include respective first ends that are attached to the first side of the cable track and respective second ends that are opposite the respective first ends. The two or more first spacers further include respective first surfaces between the respective first ends and the respective second ends and respective second surfaces that are opposite the respective first surfaces. The apparatus further includes two or more first pins attached proximately to the respective second ends of the two or more first spacers. The two or more first pins protrude from the respective first surfaces of the two or more first spacers and/or protrude from the respective second surfaces of the two or more first spacers. The apparatus further includes two or more second spacers. The two or more second spacers include respective first ends that are attached to the second side of the cable track and respective second ends that are opposite the respective first ends of the two or more second spacers. The two or more second spacers further include respective first surfaces between the respective first ends of the two or more second spacers and the respective second ends of the two or more second spacers and respective second surfaces that are opposite the respective first surfaces of the two or more second spacers. The apparatus further includes two or more second pins attached proximately to the respective second ends of the two or more second spacers. The two or more second pins protrude from the respective first surfaces of the two or more second spacers and/or protrude from the respective second surfaces of the two or more second spacers.

[0006] In yet another example, an apparatus for connecting components that move relative to each other is provided. The apparatus includes a plurality of links forming a cable track that includes a first side and a second side that is opposite the first side. The plurality of links includes respective first sides and respective second sides that are opposite the respective first sides of the plurality of links. The apparatus further includes a plurality of separators. The plurality of separators includes respective spacers attached to the respective first sides of the plurality of links at respective first ends of the respective spacers. The plurality of separators further includes respective pins attached proximately to respective second ends of the respective spacers that are opposite the respective first ends. The plurality of separators are operable to maintain a minimum distance between a first section of the first side of the cable track and a second section of the first side of the cable track as the cable track is flexed such that the first section faces the second

section.

[0007] The disclosure also includes the following clauses:

1. An apparatus (100) for connecting components (103, 105) that moves relative to each other, the apparatus comprising:
 - a cable track (102) comprising a first side (104) and a second side (106) that is opposite the first side;
 - two or more spacers (108) comprising:
 - respective first ends (110) that are attached to the first side of the cable track;
 - respective second ends (112) that are opposite the respective first ends;
 - respective first surfaces (114) between the respective first ends and the respective second ends; and
 - respective second surfaces (116) that are opposite the respective first surfaces; and
 - two or more pins (118) attached proximately to the respective second ends of the two or more spacers, wherein the two or more pins protrude from the respective first surfaces of the two or more spacers and/or protrude from the respective second surfaces of the two or more spacers.
2. The apparatus (100) of clause 1, wherein the two or more spacers (108) and the two or more pins (118) are operable to maintain a minimum distance (132) between a first section (134) of the first side (104) of the cable track (102) and a second section (136) of the first side of the cable track as the cable track is flexed such that the first section faces the second section.
3. The apparatus (100) of clause 1 or 2, wherein each spacer (108) of the two or more spacers is overlapped by at least one adjacent spacer (108) of the two or more spacers.
4. The apparatus (100) of any one of clauses 1 to 3,
 - wherein the first surfaces (114) and the second surfaces (116) are parallel to a longitudinal axis (138) of the cable track (102), and
 - wherein a distance (153) between a first spacer (142) of the two or more spacers (108) and the longitudinal axis is unequal to a distance (157) between a second spacer (146) of the two or more spacers and the longitudinal axis, preferably wherein the first spacer is adjacent to the second spacer.
5. The apparatus (100) of any one of clauses 1 to 4, wherein respective distances (115) between the first end (110) and the second end (112) of each spacer

(108) of the two or more spacers are less than a minimum bending radius of the cable track (102).

6. The apparatus (100) of any one of clauses 1 to 5, wherein the first surfaces (114) and the second surfaces (116) are parallel to a longitudinal axis (138) of the cable track (102), and wherein respective lengths (155) of the two or more spacers parallel to the longitudinal axis are less than a minimum bending radius of the cable track.

7. The apparatus (100) of any one of clauses 1 to 6, wherein the two or more spacers (108) further comprise respective holes (120) proximate to the respective second ends (112) of the two or more spacers, and

wherein the two or more pins (118) are inserted into the respective holes in the two or more spacers.

8. The apparatus (100) of any one of clauses 1 to 6, wherein the first surfaces (114) of one or more first spacers (154, 172, 174) of the two or more spacers (108) comprise respective first notches (122) proximate to the respective second ends (112) of the one or more first spacers,

wherein the second surfaces (116) of one or more second spacers (150, 154, 172) of the two or more spacers comprise respective second notches (124) proximate to the respective second ends (112) of the one or more second spacers, and

wherein the two or more pins (118) comprise respective first sections (126) inserted into the respective first notches and/or respective second sections (128) inserted into the respective second notches.

9. The apparatus (100) of any one of clauses 1 to 8, wherein the cable track (102) comprises two or more links (130) that form a chain structure.

10. The apparatus (100) of any one of clauses 1 to 9, wherein the two or more spacers (108) comprise a friction reducing material.

11. The apparatus (100) of any one of clauses 1 to 10, wherein the first surfaces (114) and the second surfaces (116) are parallel to a longitudinal axis (138) of the cable track (102),

wherein the two or more spacers (108) comprise a first group of spacers (148) comprising:

- a first spacer (150) separated from the longitudinal axis by a first distance (152); and
- a second spacer (154) separated from the longitudinal axis by a second distance (156),

wherein the second spacer is adjacent to the first spacer, and wherein the first distance is unequal to the second distance,

wherein the two or more spacers comprise a second group of spacers (158) that is adjacent to the first group of spacers, the second group of spacers comprising:

- a third spacer (142) separated from the longitu-

dinal axis by a distance (153) that is equal to the first distance; and
a fourth spacer (146) separated from the longitudinal axis by a distance (157) that is equal to the second distance, wherein the fourth spacer is adjacent to the third spacer.

12. The apparatus (100) of any one of clauses 1 to 11, wherein the first surfaces (114) and the second surfaces (116) are parallel to a longitudinal axis (138) of the cable track (102), and wherein the two or more pins (118) comprise:

respective first ends (160) that protrude from the respective first surfaces of the two or more spacers (108), wherein the respective first ends of the two or more pins extend further from the longitudinal axis than any of the two or more spacers; and/or
respective second ends (162) that protrude from the respective second surfaces of the two or more spacers, wherein the respective second ends of the two or more pins extend further from the longitudinal axis than any of the two or more spacers.

13. The apparatus (100) of any one of clauses 1 to 12, wherein the two or more pins (118) comprise one or more rollers.

14. The apparatus (100) of any one of clauses 1 to 13, wherein the two or more pins (118) comprise a friction reducing material.

15. The apparatus (100) of any one of clauses 1 to 14, further comprising two or more second spacers (209) comprising:

respective first ends (211) that are attached to the second side (106) of the cable track (102);
respective second ends (213) that are opposite the respective first ends of the two or more second spacers;
respective first surfaces (215) between the respective first ends of the two or more second spacers and the respective second ends of the two or more second spacers;
respective second surfaces (217) that are opposite the respective first surfaces of the two or more second spacers; and
two or more second pins (219) attached proximately to the respective second ends of the two or more second spacers, wherein the two or more second pins protrude from the respective first surfaces of the two or more second spacers and/or protrude from the respective second surfaces of the two or more second spacers.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008]

Figure 1 is a front view of a system, according to the present disclosure.
Figure 2 is a front view of the system of Figure 1 in a different operating position.
Figure 3 is a perspective front view of an apparatus for use with the system shown in Figures 1 and 2.
Figure 4 is a top view of spacers and pins for use with the apparatus shown in Figures 1 to 3.
Figure 5 is a front view of a spacer for use with the apparatus shown in Figures 1 to 3.
Figure 6 is a front view and a rear view of an alternative spacer for use with the apparatus shown in Figures 1 to 3.
Figure 7 is a front perspective view of an apparatus for use with the system shown in Figures 1 and 2, according to another example.
Figure 8 is a front perspective view of an apparatus for use with the system shown in Figures 1 and 2, according to another example.
Figure 9 is a top view of spacers and pins for use with the apparatus shown in Figure 8.

DETAILED DESCRIPTION

[0009] A cable management device having the cable track(s) (e.g., flexible cable tracks) described herein can protect cables or flexible tubing and facilitate movement of the cable track over itself with less mechanical complexity and with less required input energy. An example cable track has a first side and a second side that is opposite the first side. Electrical cables and/or flexible tubing may be routed through an interior region formed between the first and second sides of the cable track. The electrical cables or flexible tubing may be connected to a first component at a first end and to a second component at a second end. During operation of a system (e.g., a machine), the first component may move relative to the second component (or vice versa). As such, the cable track may provide protection for the cables or flexible tubing as the first and second components move relative to each other.

[0010] The cable management device includes additional features that may reduce the probability that one section of the cable track will snag against a second section of the cable track as the first and second sections move over each other. For example, the cable management device further includes two or more spacers having respective first ends that are attached to the first side of the cable track and respective second ends that are opposite the respective first ends. The two or more spacers further include respective first surfaces between the respective first ends and the respective second ends and respective second surfaces that are opposite the respective first surfaces. In some examples, the two or more

spacers resemble flat "teeth" or plate-like structures that slightly overlap each other along a longitudinal axis of the cable track. The two or more spacers may also be staggered (e.g., periodically) with respect to the longitudinal axis.

[0011] The cable management device further includes two or more pins attached proximally to the respective second ends of the two or more spacers. The two or more pins protrude from the respective first surfaces of the two or more spacers and/or protrude from the respective second surfaces of the two or more spacers. When the cable track is flexed so that a first section is on top of a second section, spacers of the first section will generally impact the pins attached to spacers of the second section. This may help maintain a minimum distance between the first and second sections to prevent the first and second sections from snagging on each other during movement. In some examples, the spacers and pins may be coated with or otherwise include friction reducing materials. Using spacers and pins in this manner may prevent the cable track from snagging on itself during movement, without significantly increasing friction within the cable track or increasing levels of energy required to move one section of the cable track relative to another.

[0012] Figures 1 and 2 are front views of an example system 111, such as a machine. The system 111 includes a first component 103, a second component 105, and an apparatus 100 (also referred to herein as a "cable management device") for connecting the components 103 and 105 to each other. For example, the apparatus 100 connects to the first component 103 and the second component 105 of the system 111. An enclosure 101 is defined between the first component 103 and the second component 105, and the apparatus 100 is positioned in the enclosure 101. Figures 1 and 2 show a cross-section of the enclosure 101, which takes the form of a spherical or a cylindrical shell, but the enclosure 101 can have any suitable cross-sectional shape and the apparatus 100 is configured to move within enclosures having any suitable shape.

[0013] The system 111 includes the first component 103 and the second component 105 that move relative to each other during operation of the system 111. A first end 188 of the apparatus 100 is coupled to the first component 103, and a second end 189 of the apparatus 100 is coupled to the second component 105. The ends 188 and 189 of the apparatus 100 can be coupled to the respective component 103 or 105 via, for example, an electrical cable, conduit, and/or flexible tubing. Preferably, the apparatus 100 is a separate component that is positioned in the enclosure 101 and coupled to the first component 103 and the second component 105.

[0014] Electrical cables, conduits, and/or flexible tubing connecting the first component 103 to the second component 105 may be routed through the apparatus 100. The first component 103 may be an electrical power source and the second component 105 may be an optical sensor, for example, and electrical cables routed within

the apparatus 100 may carry electrical current flowing between the first component 103 and the second component 105. In another example, the first component 103 is a processor, and electrical cables or fiber optic cables routed within the apparatus 100 may transmit optical data collected by the second component 105 to the first component 103. In yet another example, the first component 103 is an outlet for pressurized air or another pressurized fluid and the second component 105 may be powered pneumatically via flexible tubing routed within the apparatus 100. Figure 1 depicts the second component 105 in a position 107 along the enclosure that is ninety degrees clockwise with respect to the first component 103. As shown, a first section 119 of a first side 104 of the apparatus 100 faces a second section 121 of the first side 104 due to flexing of the apparatus 100.

[0015] Figure 2 is a front view of the system 111 in a different operating condition within the enclosure 101. Figure 2 depicts the second component 105 in a position 109 along the enclosure 101 that is ninety degrees counter-clockwise with respect to the first component 103. In Figure 2, a third section 123 of the first side 104 faces a fourth section 125 of the first side 104 due to the flexing of the apparatus 100 at a position that differs from the position at which the apparatus 100 is flexed in Figure 1. The apparatus 100 is configured to facilitate movement of the second component 105 between the positional extremes shown respectively in Figures 1 and 2. In other examples, the apparatus 100 may facilitate 360-degree movement of the second component 105. In yet other examples, the apparatus 100 may facilitate movement of the second component 105 in directions that correspond to any number of possible shapes of the enclosure 101. Other examples are possible as well.

[0016] Figure 3 is a perspective front view of the apparatus 100. The apparatus 100 includes a cable track 102 having the first side 104 and a second side 106 that is opposite the first side 104. The apparatus 100 further includes two or more spacers 108. The two or more spacers 108 include respective first ends 110 that are attached to the first side 104 of the cable track 102 and respective second ends 112 that are opposite the respective first ends 110. The two or more spacers 108 also include respective first surfaces 114 between the respective first ends 110 and the respective second ends 112 and respective second surfaces 116 that are opposite the respective first surfaces 114. The apparatus 100 further includes two or more pins 118 attached proximally to the respective second ends 112 of the two or more spacers 108. The two or more pins 118 protrude from the respective first surfaces 114 of the two or more spacers 108 and/or protrude from the respective second surfaces 116 of the two or more spacers 108.

[0017] The cable track 102 is composed of two or more interconnected links 130 that are made of plastic, carbon fiber, and/or metal, but other examples are possible. The links 130 form a chain structure (e.g., two or more links form a chain structure). The cable track 102 defines a

longitudinal axis 138 and an interior region 199. Electrical cables and/or flexible tubing may be routed through the interior region 199, from an end 197 to an end 198 or vice versa. Such electrical cables or flexible tubing may connect the first component 103 to the second component 105.

[0018] The two or more spacers 108 may be composed of or be coated by a friction-reducing material. For example, the two or more spacers 108 can be made of or coated by a polytetrafluoroethylene (PTFE) material, such as TEFLON® ("Teflon" is a registered trademark of The Chemours Company of Wilmington, Delaware, USA.). The two or more spacers 108 resemble flat "teeth" or plate-like structures that slightly overlap each other along the longitudinal axis 138. That is, each spacer 108 of the two or more spacers 108 is overlapped by at least one adjacent spacer 108 of the two or more spacers 108 when viewed from an angle that is perpendicular to the longitudinal axis 138. The two or more spacers 108 are staggered (e.g., arranged periodically) with respect to the longitudinal axis 138. That is, the distance of each spacer 108 from the longitudinal axis 138 is based on a periodic distance sequence with respect to position along the longitudinal axis 138. The first surfaces 114 and the second surfaces 116 of the two or more spacers 108 are parallel to the longitudinal axis 138 of the cable track 102.

[0019] Respective distances 115 between the first end 110 and the second end 112 of each spacer of the two or more spacers 108 are less than or equal to a minimum bending radius of the cable track 102. Respective lengths 155 of the two or more spacers 108 parallel to the longitudinal axis 138 are greater than or equal to the respective lengths of the links 130 in the direction of the longitudinal axis 138. Respective lengths 155 of the two or more spacers 108 parallel to the longitudinal axis 138 are less than a minimum bending radius of the cable track 102.

[0020] Within examples, the two or more pins 118 are attached proximately to the respective second ends 112 of the two or more spacers 108. In this context, the phrase "attached proximately" indicates that the pins 118 are closer to the second ends 112 than the first ends 110. In other examples, the phrase "attached proximately" indicates that the pins 118 are attached flush with the second ends 112 or at least ten times closer to the ends 112 than to the ends 110, but other examples are possible.

[0021] The two or more pins 118 protrude from the respective first surfaces 114 and/or protrude from the respective second surfaces 116 of the two or more spacers 108. For example, a pin 183 attached to a spacer 173 protrudes from both the first surface 114 and the second surface 116 of the spacer 173. The pin 183 extends from each surface 114 and 116 of the spacer 173 because the spacer 173 is displaced a shorter distance from the longitudinal axis 138 in the direction 191 when compared to at least one other spacer 108. A pin 181 attached to a spacer 171 may protrude only from the first surface 114 of the spacer 171 but not from the second surface 116

of the spacer 171. The pin 181 may extend only from one surface 114 because the spacer 171 is displaced from the longitudinal axis 138 in the direction 192 at least as far as any of the other spacers 108. A pin 179 attached to a spacer 169 may protrude only from the second surface 116 of the spacer 169 but not from the first surface 114 of the spacer 169. The pin 179 may extend only from one surface 116 because the spacer 169 is displaced from the longitudinal axis 138 in the direction 191 at least as far as any of the other spacers 108. In Figures 3 and 4, various portions of the pins 118 are illustrated with dashed lines, which denotes that those pins are typically omitted from the apparatus 100, but could optionally be included as part of the apparatus 100.

[0022] The two or more pins 118 may be composed of or be coated with a friction-reducing material such as a polytetrafluoroethylene (PTFE) material (e.g., a TEFLON® material ("Teflon" is a registered trademark of The Chemours Company of Wilmington, Delaware, USA.)).

[0023] The two or more spacers 108 and the two or more pins 118 are operable to maintain a minimum distance 132 between a first section 134 of the first side 104 of the cable track 102 and a second section 136 of the first side 104 of the cable track 102 as the cable track 102 is flexed such that the first section 134 faces the second section 136. When the cable track 102 is flexed so that the first section 134 overlaps the second section 136, spacers 108 of the first section 134 will generally contact pins 118 attached to the spacers 108 of the second section 136. Additionally or alternatively, spacers 108 of the second section 136 may impact pins 118 attached to spacers 108 of the first section 134.

[0024] This arrangement may maintain the minimum distance 132 between the first section 134 and the second section 136 to prevent the first section 134 and the second section 136 from snagging on each other during movement of the apparatus 100. The apparatus 100 may function without significantly increasing friction within the cable track 102 or increasing levels of energy required to move one section of the cable track 102 relative to another.

[0025] Figure 4 is a top view of spacers and pins for use with the apparatus 100 as the two or more spacers 108 and the two or more pins 118. For example, the two or more spacers 108 include at least spacers 150, 154, 142, and 146. The distances of the spacers 150, 154, 142, and 146 from the longitudinal axis 138 are illustrated in Figure 4. For instance, a distance 153 between the spacer 142 and the longitudinal axis 138 is unequal to a distance 157 between the spacer 146 and the longitudinal axis 138. As shown in Figure 4, the spacer 142 is adjacent to the spacer 146 and the distance 153 is larger than the distance 157.

[0026] Figure 5 is a front view of a spacer 108 for use with the apparatus 100. In the embodiment shown in Figure 5, the spacer 108 includes a hole 120 proximate to the second end 112 of the spacer 108. The two or more

pins 118 may be inserted into the respective holes 120 in the two or more spacers 108 and be secured to the two or more spacers 108 such that the two or more pins 118 protrude from the respective first surfaces 114 and/or the respective second surfaces 116. The two or more pins 118 may include or take the form of one or more rollers that spin freely within the respective holes 120.

[0027] Figure 6 is a front view and a rear view of an alternative spacer 108 for use with the apparatus 100. The spacer 108 shown in Figure 6 is similar to the spacer 108 shown in Figure 5, except that in Figure 6 the spacer 108 includes a notch 122 and/or a notch 124 instead of a hole 120. In Figure 6, the first surface 114 of the spacer 108 includes a first notch 122 proximate to the second end 112 of the spacer 108. The second surface 116 of the spacer 108 may also include a second notch 124 proximate to the second end 112 of the spacer 108. As shown in Figure 3, the two or more pins 118 may include respective first sections 126 that are inserted into the first notches 122 and/or respective second sections 128 that are inserted into the second notches 124.

[0028] Referring to Figure 4, the two or more spacers 108 may include a first group 148 of spacers 108 that includes a spacer 150 separated from the longitudinal axis 138 by a first distance 152 and a spacer 154 separated from the longitudinal axis 138 by a second distance 156. The spacer 154 is adjacent to the spacer 150 and the first distance 152 is unequal to the second distance 156 as shown in Figure 4.

[0029] The two or more spacers 108 may also include a second group 158 of spacers 108 that is adjacent to the first group 148 of spacers 108. The second group 158 of spacers 108 includes a spacer 142 separated from the longitudinal axis 138 by a distance 153 that is equal to the first distance 152 and a spacer 146 separated from the longitudinal axis 138 by a distance 157 that is equal to the second distance 156. The spacer 146 is adjacent to the spacer 142.

[0030] The two or more pins 118 may include respective first ends 160 that protrude from the respective first surfaces 114 of the two or more spacers 108. The respective first ends 160 may extend further from the longitudinal axis 138 than any of the spacers 108. In addition to or as an alternative to the first ends 160, the pins 118 may also include respective second ends 162 that protrude from the respective second surfaces 116 of the two or more spacers 108. The respective second ends 162 of the pins 118 may extend further from the longitudinal axis 138 than any of the two or more spacers 108.

[0031] Figure 7 is a front perspective view of an example apparatus 200 (also referred to herein as a "cable management device"). The apparatus 200 includes features similar to the apparatus 100, except apparatus 200 includes spacers 209 coupled to the second side 106 of the cable track 102 in addition to the spacers 108 coupled to the first side 104 of the cable track 102. Components that are common to both apparatus 100 and 200 maintain the reference numbers used above and include the same

features described with respect to apparatus 100, unless stated otherwise. More specifically, the apparatus 200 may include any of the features of the apparatus 100 described above, in addition to any other features described herein. Notably, the apparatus 200 differs from the apparatus 100 in that the apparatus 200 includes the two or more second spacers 209 and the two or more second pins 219 on the second side 106 of the cable track 102 in addition to the two or more first spacers 108 and two or more first pins 118 on the first side 104 of the cable track 102. The two or more second spacers 209 and the two or more second pins 219 may function similarly to the two or more first spacers 108 and the two or more first pins 118 when two sections of the second side 106 of the cable track 102 face each other. The two or more second spacers 209 and the two or more second pins 219 may also have structural features that are similar to the two or more first spacers 108 and the two or more first pins 118.

[0032] The two or more second spacers 209 are similar to the spacers 108 except the spacers 209 oppose the spacers 108 with respect to the cable track 102. Each spacer 209 includes a first end 211 that is attached to the second side 106 of the cable track 102 and a second end 213 that is opposite the respective first end 211. The spacers 209 also each include a first surface 215 between the respective first end 211 and the respective second end 213 and a second surface 217 that is opposite the respective first surface 215.

[0033] The apparatus 200 further includes two or more second pins 219 attached proximately to the respective second ends 213 of the two or more second spacers 209. The two or more second pins 219 protrude from the respective first surfaces 215 of the two or more second spacers 209 and/or protrude from the respective second surfaces 217 of the two or more second spacers 209. The two or more second pins 219 may include any of the features of the two or more first pins 118.

[0034] In Figure 7, various portions of the two or more first pins 118 and the two or more second pins 219 are illustrated with dashed lines, which denotes that those pins are typically omitted, but could optionally be included as part of the apparatus 200.

[0035] Figure 8 is a front perspective view of an example apparatus 300 (also referred to herein as a "cable management device"). The apparatus 300 may include any of the features of the apparatus 100 or 200 described above, in addition to the features described below. Components of the apparatus 300 that are common to apparatus 100 or 200 maintain the reference numbers used above and include the same features described with respect to apparatus 100 or 200, unless stated otherwise.

[0036] The apparatus 300 can be used for connecting components that move relative to each other. The apparatus 300 includes the plurality of links 130 forming the cable track 102. Each of the links 130 includes a first side 305 and a second side 307 that is opposite the first side 305.

[0037] The apparatus 300 further includes a plurality of separators 311. Each separator 311 includes a spacer 108 attached to the first side 305 of the respective link 130 at a first end 110 of the spacer 108. Each separator 311 further includes a respective pin 118 attached proximately to the second end 112 of the respective spacer 108. The plurality of separators 311 are operable to maintain a minimum distance 332 between a first section 334 of the first side 104 of the cable track 102 and a second section 336 of the first side 104 of the cable track 102 as the cable track 102 is flexed such that the first section 334 faces the second section 336.

[0038] The spacers 108 may be oriented perpendicularly to the respective first sides 305 of the plurality of links 130. The spacers 108 may be oriented parallel to a longitudinal axis 338 of the cable track 102.

[0039] The plurality of separators 311 may be operable to prevent the first section 334 of the first side 104 of the cable track 102 from being obstructed by the second section 336 of the first side 104 of the cable track 102 as the first section 334 moves past the second section 336.

[0040] Figure 9 is a top view of spacers and pins for use with the apparatus 300. The plurality of separators 311 may include a first group of separators 348 and a second group of separators 358. The first group 348 includes a first separator 350 and a second separator 354 that is adjacent to the first separator 350. The first separator 350 and the second separator 354 are staggered to facilitate the first separator 350 moving past the second separator 354 in response to flexing of the cable track 102. The second group 358 includes a first separator 342 and a second separator 346 that is adjacent to the first separator 342. The first separator 342 and the second separator 346 are staggered to facilitate the first separator 342 moving past the second separator 346 in response to flexing of the cable track 102.

[0041] In Figures 7-8, various portions of the pins 118 are illustrated with dashed lines, which denotes that those pins are typically omitted, but could optionally be included as part of the apparatus 300.

[0042] The present disclosure can thus relate to one of the enumerated example embodiment (EEEs) listed below.

EEE 1 is an apparatus for connecting components that move relative to each other. The apparatus includes a cable track that includes a first side and a second side that is opposite the first side. The apparatus further includes two or more spacers. The two or more spacers include respective first ends that are attached to the first side of the cable track; respective second ends that are opposite the respective first ends; respective first surfaces between the respective first ends and the respective second ends; and respective second surfaces that are opposite the respective first surfaces. The apparatus further includes two or more pins attached proximately to the respective second ends of the two or

more spacers, wherein the two or more pins protrude from the respective first surfaces of the two or more spacers and/or protrude from the respective second surfaces of the two or more spacers.

EEE 2 is the apparatus of EEE 1, wherein the two or more spacers and the two or more pins are operable to maintain a minimum distance between a first section of the first side of the cable track and a second section of the first side of the cable track as the cable track is flexed such that the first section faces the second section.

EEE 3 is the apparatus of EEE 1 or 2, wherein each spacer of the two or more spacers is overlapped by at least one adjacent spacer of the two or more spacers.

EEE 4 is the apparatus of any of EEEs 1-3, wherein the first surfaces and the second surfaces are parallel to a longitudinal axis of the cable track, and wherein a distance between a first spacer of the two or more spacers and the longitudinal axis is unequal to a distance between a second spacer of the two or more spacers and the longitudinal axis.

EEE 5 is the apparatus of EEE 4, wherein the first spacer is adjacent to the second spacer.

EEE 6 is the apparatus of any of EEEs 1-5, wherein respective distances between the first end and the second end of each spacer of the two or more spacers are less than a minimum bending radius of the cable track.

EEE 7 is the apparatus of any of EEEs 1-6, wherein the first surfaces and the second surfaces are parallel to a longitudinal axis of the cable track, and wherein respective lengths of the two or more spacers parallel to the longitudinal axis are less than a minimum bending radius of the cable track.

EEE 8 is the apparatus of any of EEEs 1-7, wherein the two or more spacers further comprise respective holes proximate to the respective second ends of the two or more spacers, and wherein the two or more pins are inserted into the respective holes in the two or more spacers.

EEE 9 is the apparatus of any of EEEs 1-7, wherein the first surfaces of one or more first spacers of the two or more spacers comprise respective first notches proximate to the respective second ends of the one or more first spacers, wherein the second surfaces of one or more second spacers of the two or more spacers comprise respective second notches proximate to the respective second ends of the one or more second spacers, and wherein the two or more pins comprise respective first sections inserted into the respective first notches and/or respective second sections inserted into the respective second notches.

EEE 10 is the apparatus of any of EEEs 1-9, wherein the cable track comprises two or more links that form a chain structure.

EEE 11 is the apparatus of any of EEEs 1-10, where-

in the two or more spacers comprise a friction reducing material.

EEE 12 is the apparatus of any of EEEs 1-11, wherein the first surfaces and the second surfaces are parallel to a longitudinal axis of the cable track, wherein the two or more spacers comprise a first group of spacers comprising: a first spacer separated from the longitudinal axis by a first distance; and a second spacer separated from the longitudinal axis by a second distance, wherein the second spacer is adjacent to the first spacer, and wherein the first distance is unequal to the second distance, wherein the two or more spacers comprise a second group of spacers that is adjacent to the first group of spacers, the second group of spacers comprising: a third spacer separated from the longitudinal axis by a distance that is equal to the first distance; and a fourth spacer separated from the longitudinal axis by a distance that is equal to the second distance, wherein the fourth spacer is adjacent to the third spacer.

EEE 13 is the apparatus of any of EEEs 1-12, wherein the first surfaces and the second surfaces are parallel to a longitudinal axis of the cable track, and wherein the two or more pins comprise: respective first ends that protrude from the respective first surfaces of the two or more spacers, wherein the respective first ends of the two or more pins extend further from the longitudinal axis than any of the two or more spacers; and/or respective second ends that protrude from the respective second surfaces of the two or more spacers, wherein the respective second ends of the two or more pins extend further from the longitudinal axis than any of the two or more spacers.

EEE 14 is the apparatus of any of EEEs 1-13, wherein the two or more pins comprise one or more rollers.

EEE 15 is the apparatus of any of EEEs 1-14, wherein the two or more pins comprise a friction reducing material.

EEE 16 is an apparatus for connecting components that move relative to each other, the apparatus comprising: a cable track comprising a first side and a second side that is opposite the first side; two or more first spacers comprising: respective first ends that are attached to the first side of the cable track; respective second ends that are opposite the respective first ends; respective first surfaces between the respective first ends and the respective second ends; and respective second surfaces that are opposite the respective first surfaces. The apparatus further comprises: two or more first pins attached proximately to the respective second ends of the two or more first spacers, wherein the two or more first pins protrude from the respective first surfaces of the two or more first spacers and/or protrude from the respective second surfaces of the two or more first spacers; two or more second spacers comprising: respective first ends that are attached to the second side of the cable track; respective second ends that

are opposite the respective first ends of the two or more second spacers; respective first surfaces between the respective first ends of the two or more second spacers and the respective second ends of the two or more second spacers; and respective second surfaces that are opposite the respective first surfaces of the two or more second spacers. The apparatus further comprises two or more second pins attached proximately to the respective second ends of the two or more second spacers, wherein the two or more second pins protrude from the respective first surfaces of the two or more second spacers and/or protrude from the respective second surfaces of the two or more second spacers.

EEE 17 is an apparatus for connecting components that move relative to each other, the apparatus comprising: a plurality of links forming a cable track comprising a first side and a second side that is opposite the first side, wherein the plurality of links comprises respective first sides and respective second sides that are opposite the respective first sides of the plurality of links; and a plurality of separators comprising: respective spacers attached to the respective first sides of the plurality of links at respective first ends of the respective spacers; and respective pins attached proximately to respective second ends of the respective spacers that are opposite the respective first ends, wherein the plurality of separators are operable to maintain a minimum distance between a first section of the first side of the cable track and a second section of the first side of the cable track as the cable track is flexed such that the first section faces the second section.

EEE 18 is the apparatus of EEE 17, wherein the spacers are attached orthogonally to the respective first sides of the plurality of links, and wherein the spacers are oriented parallel to a longitudinal axis of the cable track.

EEE 19 is the apparatus of EEEs 17 or 18, wherein the plurality of separators comprise two or more groups of separators, wherein the two or more groups of separators each comprise a first separator and a second separator that is adjacent to the first separator, and wherein the first separator and the second separator of each group of the two or more groups of separators are staggered to facilitate the first separator moving past the second separator in response to flexing of the cable track.

EEE 20 is the apparatus of any of EEEs 17-19, wherein the plurality of separators are operable to prevent the first section of the first side of the cable track from being obstructed by the second section of the first side of the cable track as the first section moves past the second section.

EEE 21 is the apparatus of any of EEEs 1-15, further comprising two or more second spacers comprising: respective first ends that are attached to the second side of the cable track; respective second ends that

are opposite the respective first ends of the two or more second spacers; respective first surfaces between the respective first ends of the two or more second spacers and the respective second ends of the two or more second spacers; and respective second surfaces that are opposite the respective first surfaces of the two or more second spacers; and two or more second pins attached proximately to the respective second ends of the two or more second spacers, wherein the two or more second pins protrude from the respective first surfaces of the two or more second spacers and/or protrude from the respective second surfaces of the two or more second spacers.

[0043] By the term "about" or "substantially" with reference to amounts or measurement values described herein, it is meant that the recited characteristic, parameter, or value need not be achieved exactly, but that deviations or variations, including for example, tolerances, measurement error, measurement accuracy limitations and other factors known to those of skill in the art, may occur in amounts that do not preclude the effect the characteristic was intended to provide.

[0044] The description of the different advantageous arrangements has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different advantageous embodiments may describe different advantages as compared to other advantageous embodiments. The embodiment or embodiments selected are chosen and described in order to explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

Claims


1. An apparatus for connecting components that move relative to each other, the apparatus comprising: a cable track comprising a first side and a second side that is opposite the first side; two or more first spacers comprising: respective first ends that are attached to the first side of the cable track; respective second ends that are opposite the respective first ends; respective first surfaces between the respective first ends and the respective second ends; and respective second surfaces that are opposite the respective first surfaces.
2. The apparatus of claim 1, further comprising: two or more first pins attached proximately to the respective second ends of the two or more first spacers, wherein the two or more first pins protrude from the respective

first surfaces of the two or more first spacers and/or protrude from the respective second surfaces of the two or more first spacers; two or more second spacers comprising: respective first ends that are attached to the second side of the cable track; respective second ends that are opposite the respective first ends of the two or more second spacers; respective first surfaces between the respective first ends of the two or more second spacers and the respective second ends of the two or more second spacers; and respective second surfaces that are opposite the respective first surfaces of the two or more second spacers.

3. The apparatus of claim 1 or 2, further comprising two or more second pins attached proximately to the respective second ends of the two or more second spacers, wherein the two or more second pins protrude from the respective first surfaces of the two or more second spacers and/or protrude from the respective second surfaces of the two or more second spacers.
4. An apparatus for connecting components that move relative to each other, the apparatus comprising: a plurality of links forming a cable track comprising a first side and a second side that is opposite the first side, wherein the plurality of links comprises respective first sides and respective second sides that are opposite the respective first sides of the plurality of links; and a plurality of separators comprising: respective spacers attached to the respective first sides of the plurality of links at respective first ends of the respective spacers; and respective pins attached proximately to respective second ends of the respective spacers that are opposite the respective first ends, wherein the plurality of separators are operable to maintain a minimum distance between a first section of the first side of the cable track and a second section of the first side of the cable track as the cable track is flexed such that the first section faces the second section.
5. The apparatus of claim 4, wherein the spacers are attached orthogonally to the respective first sides of the plurality of links, and wherein the spacers are oriented parallel to a longitudinal axis of the cable track.
6. The apparatus of claims 4 or 5, wherein the plurality of separators comprise two or more groups of separators, wherein the two or more groups of separators each comprise a first separator and a second separator that is adjacent to the first separator, and wherein the first separator and the second separator of each group of the two or more groups of separators are staggered to facilitate the first separator moving past the second separator in response to flexing of

the cable track.

7. The apparatus of any of the claims 4-6, wherein the plurality of separators are operable to prevent the first section of the first side of the cable track from being obstructed by the second section of the first side of the cable track as the first section moves past the second section. 5
8. An apparatus for connecting components that move relative to each other, comprising a cable track that includes a first side and a second side that is opposite the first side; two or more spacers having respective first ends that are attached to the first side of the cable track; respective second ends that are opposite the respective first ends; respective first surfaces between the respective first ends and the respective second ends; and respective second surfaces that are opposite the respective first surfaces, the apparatus further comprising two or more pins attached proximately to the respective second ends of the two or more spacers, wherein the two or more pins protrude from the respective first surfaces of the two or more spacers and/or protrude from the respective second surfaces of the two or more spacers, further comprising two or more second spacers comprising: respective first ends that are attached to the second side of the cable track; respective second ends that are opposite the respective first ends of the two or more second spacers; respective first surfaces between the respective first ends of the two or more second spacers and the respective second ends of the two or more second spacers; and respective second surfaces that are opposite the respective first surfaces of the two or more second spacers; and two or more second pins attached proximately to the respective second ends of the two or more second spacers, wherein the two or more second pins protrude from the respective first surfaces of the two or more second spacers and/or protrude from the respective second surfaces of the two or more second spacers. 10 15 20 25 30 35 40
9. The apparatus according to claim 8, wherein the two or more spacers and the two or more pins are operable to maintain a minimum distance between a first section of the first side of the cable track and a second section of the first side of the cable track as the cable track is flexed such that the first section faces the second section. 45 50
10. The apparatus according to claim 8 or 9, wherein the first surfaces and the second surfaces are parallel to a longitudinal axis of the cable track, and wherein a distance between a first spacer of the two or more spacers and the longitudinal axis is unequal to a distance between a second spacer of the two or more spacers and the longitudinal axis. 55
11. The apparatus according to any of the claims 8-10, wherein respective distances between the first end and the second end of each spacer of the two or more spacers are less than a minimum bending radius of the cable track.
12. The apparatus according to any of the claims 8-11, wherein the first surfaces and the second surfaces are parallel to a longitudinal axis of the cable track, and wherein respective lengths of the two or more spacers parallel to the longitudinal axis are less than a minimum bending radius of the cable track.
13. The apparatus according to any of the claims 8-12, wherein the first surfaces of one or more first spacers of the two or more spacers comprise respective first notches proximate to the respective second ends of the one or more first spacers, wherein the second surfaces of one or more second spacers of the two or more spacers comprise respective second notches proximate to the respective second ends of the one or more second spacers, and wherein the two or more pins comprise respective first sections inserted into the respective first notches and/or respective second sections inserted into the respective second notches.
14. The apparatus according to any of the claims 8-13, wherein the cable track comprises two or more links that form a chain structure.
15. The apparatus according to any of the claims 8-14, wherein the two or more spacers comprise a friction reducing material.



1
G
E




FIG. 2




FIG. 3




FIG. 4




FIG. 5






FIG. 6





7.6.4




FIG. 8




FIG. 9



EUROPEAN SEARCH REPORT

Application Number
EP 19 21 0645

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	EP 0 456 537 A1 (KABELSCHLEPP FRANCE [FR]) 13 November 1991 (1991-11-13)	1,3,5,7	INV. F16G13/16
A	* column 2, line 46 - line 50 * * column 3, line 39 - column 4, line 2; claim 2; figures 1,3,4 *	2,4,6, 9-15	
X	US 3 590 854 A (CORK GORDON H) 6 July 1971 (1971-07-06)	1,3,5,7	
A	* column 6, line 4 - line 39; figures 17-20 *	2,4,6, 9-15	
A	EP 0 693 638 A1 (ZINDEL CONSULTING [CH]) 24 January 1996 (1996-01-24) * column 5, line 1 - line 11; figures 2,7 *	1-15	TECHNICAL FIELDS SEARCHED (IPC) F16G
X	DE 20 2012 104869 U1 (TSUBAKI KABELSCHLEPP GMBH [DE]) 28 February 2013 (2013-02-28)	1,3,5,7	
A	* paragraphs [0045], [0046], [0050], [0059], [0060]; figures 10,11,12 *	2,4,6, 9-15	
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 10 December 2019	Examiner Afanasiev, Andrey
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 19 21 0645

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

10-12-2019

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0456537 A1	13-11-1991	EP 0456537 A1	13-11-1991
		FR 2661728 A1	08-11-1991
US 3590854 A	06-07-1971	CA 918766 A	09-01-1973
		GB 1249018 A	06-10-1971
		US 3590854 A	06-07-1971
EP 0693638 A1	24-01-1996	AT 180046 T	15-05-1999
		DE 59505884 D1	17-06-1999
		EP 0693638 A1	24-01-1996
DE 202012104869 U1	28-02-2013	NONE	