## 

## (11) **EP 3 656 942 A8**

## (12) CORRECTED EUROPEAN PATENT APPLICATION

(15) Correction information:

Corrected version no 1 (W1 A1) Corrections, see

Bibliography INID code(s) 71

(48) Corrigendum issued on:

19.08.2020 Bulletin 2020/34

(43) Date of publication:

27.05.2020 Bulletin 2020/22

(21) Application number: 19205067.2

(22) Date of filing: 24.10.2019

(84) Designated Contracting States:

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

**Designated Extension States:** 

**BA ME** 

**Designated Validation States:** 

KH MA MD TN

(30) Priority: 20.11.2018 CN 201811407484


(71) Applicants:

 Hebei Huiyuan Building Materials Co., Ltd Chendge City, Hebei Province (CN) (51) Int Cl.: **E04B** 1/94 (2006.01)

- Chifeng Huiyuan Building Materials Co., Ltd Chifeng City (CN)
- (72) Inventor: QIN, Haishan
  Chengde City (industrial park), Hebei Province
  (CN)
- (74) Representative: Baudler, Ron
  Canzler & Bergmeier
  Patentanwälte Partnerschaft mbB
  Friedrich-Ebert-Straße 84
  85055 Ingolstadt (DE)

## (54) STRUCTURE AND METHOD FOR CONNECTING A COMPOSITE INSULATION EXTERIOR WALL PANEL AND A STEEL STRUCTURAL BEAM-COLUMN

(57)The present invention discloses a structure for connecting a composite insulation exterior wall panel and a steel structural beam-column, including a steel structural beam and a steel structural column; the steel structural beam and the steel structural column respectively include a steel structural body; a filling insulation layer is provided at a gap of the steel structural body; a composite insulation panel connecting assembly is wrapped at a junction between the steel structural beam and the steel structural column; the composite insulation panel connecting assembly is connected to a horizontal composite insulation panel assembly, via a staggered seam, in a horizontal direction; the composite insulation panel connecting assembly is connected to a vertical composite insulation panel assembly, via a staggered seam, in a vertical direction; and the horizontal composite insulation panel assembly and the vertical composite insulation panel assembly are connected to a composite insulation exterior wall panel via a staggered seam to form a whole without a continuous seam. In the present invention, an inside and an outside of a steel structural body are connected to an insulation panel to implement flexible connection and prevent a junction from cracking; and composite insulated wall boards are connected via a staggered seam to eliminate a continuous seam and improve the insulation effect.



EP 3 656 942 A8