



(11)

**EP 3 699 345 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**26.08.2020 Bulletin 2020/35**

(51) Int Cl.:  
**D04H 1/49 (2012.01) D04H 1/558 (2012.01)**

(21) Application number: **19382116.2**

(22) Date of filing: **19.02.2019**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**  
Designated Extension States:  
**BA ME**  
Designated Validation States:  
**KH MA MD TN**

- **ROSALES CALDERON, Sergio**  
**08036 BARCELONA (ES)**
- **MONGES, Sebastien, Laurent**  
**08036 BARCELONA (ES)**
- **RODRÍGUEZ RODRÍGUEZ, Andrés**  
**08036 BARCELONA (ES)**
- **AGUILERA COBOS, Gustavo**  
**08036 BARCELONA (ES)**

(71) Applicant: **BC Nonwovens, S.L.**  
**08036 Barcelona (ES)**

(74) Representative: **Herrero & Asociados, S.L.**  
**Cedaceros, 1**  
**28014 Madrid (ES)**

(72) Inventors:  
• **ETAYO SANCHO, Jesus, Maria**  
**08036 BARCELONA (ES)**

(54) **METHOD FOR MANUFACTURING A NONWOVEN FABRIC AND NONWOVEN FABRIC MANUFACTURED BY SAID METHOD**

(57) The method for manufacturing a nonwoven fabric comprises a fiber carding step and a fiber hydroentangling step for forming a web, wherein it also comprises a calendering step of said web.

The nonwoven fabric manufactured by said method comprises fibers forming substantially parallel stripes.

This nonwoven fabric resulting from the method according to the present invention is adaptable to irregular surfaces. Moreover, and opposite to the calender bonded nonwoven fabrics, the cost of the method according to the present invention is low, since the fibers are water jet bonded.

**EP 3 699 345 A1**

**Description**

**[0001]** The present invention refers to a method for manufacturing a nonwoven fabric and to a nonwoven fabric manufactured by said method.

**Background of the invention**

**[0002]** Several technologies to manufacture nonwoven fabrics are known. Basically, these techniques differ in the web formation method (raw material feeding and preparation) and/or the web bonding method.

**[0003]** Therefore, the raw material to produce nonwovens can be continuous yarn, staple fibers or pulp.

**[0004]** In the case of staple fibers, the web formation method consists of carding the fibers and a web bonding step that can be carried out mechanically by hydroentangling (the fibers are sewed by high pressure water jet spray) or needle-punching (the fibers are sewed by needles); chemically (by adding a polymeric bonding agent in order to bind the fibers); or thermally (the fibers are bonded under heating with air or calendering).

**[0005]** The main applications of the nonwoven fabrics are in the hygiene, medical, industrial and geotextiles markets.

**[0006]** The nonwoven fabric spunlace manufacturing method combines the staple fibers carding and hydroentangling steps.

**[0007]** It is known that the spunlace nonwoven method and the resulting fabrics present the following advantages with regards to the other nonwoven technologies mentioned above:

- Free of Chemical Additives: the spunlace is the most suitable method to produce materials with final use in contact with the skin, since no chemical substance is added on the fabric.
- Low Cost: higher production output than the needle-punching method and there is no need to subject the web to long drying times to bond the fibers
- No Change of the Fiber Structure during web bonding. As a result, the intrinsic properties of the fibers are preserved in the spunlace fabric.
- Textile Hand Feel: opposite to the thermally and chemically point-bonded nonwovens, the spunlace fabric show a uniform bonding, which results in a textile hand feel, like a towel.
- High Conformability: due to staple fiber entanglement, the spunlace products present good adaptability to irregular surfaces.
- High Liquid Absorption: opposite to the continuous yarn containing nonwoven products (spunbonded or meltblown nonwoven fabrics), the spunlace products present high liquid absorption, due to the resulting capillarity when making the nonwovens with staple fibers.
- Softness and Bulkiness, as a result of the carding and hydroentangling method steps.

**[0008]** Anyway, there are certain applications that require very thin (not bulky) nonwovens, so a standard spunlace nonwoven fabric does not meet the demanded specifications.

**[0009]** The nonwoven fabrics thickness or caliper is measured according to the EDANA Test Method NWSP 120.6.R0 (15) and it is expressed in mm.

**[0010]** Even though the nonwoven fabrics caliper depends on the material basis weight ( $\text{g/m}^2$ ), the thickness of a standard spunlace product is higher than 0,20 mm.

**[0011]** So, the current nonwoven manufacturing methods to achieve nonwoven fabrics thinner than 0,20mm are the spunbond, meltblown and calender bonded technologies.

**[0012]** However, these technologies present the following limitations:

The spunbonded and meltblown nonwoven fabrics are made of filaments (instead of staple fibers), which results in very rigid fabrics that are not adaptable to irregular surfaces.

**[0013]** In addition, the continuous yarn containing nonwoven products (spunbonded or meltblown nonwoven fabrics), present low capillarity, which results in a low liquid absorption and, consequently, poor compatibility with liquids, such as water, but also liquid resins or waxes.

**[0014]** On the other hand, the calender bonded products present good adaptability, since they are made of staple fibers, but the calender bonding production costs are high, due to the low speed needed to fix the fibers by heat transfer.

**[0015]** Therefore, the objective of the following invention is to provide a nonwoven fabric produced by carding and hydroentangling and, subsequently, calendering, so the resulting nonwoven fabric presents a low caliper.

**[0016]** In addition, and opposite to the spunbonded and meltblown nonwovens, this nonwoven fabric resulting from the method is adaptable to irregular surfaces.

**[0017]** Moreover, and opposite to the calender bonded nonwoven fabrics, the cost of the method according to the present invention is low, since the fibers are water jet bonded.

## Description of the invention

**[0018]** With the nonwoven fabric and the method according to the present invention it is possible to solve said drawbacks, providing other advantages that are described below.

**[0019]** According to a first aspect, the present invention refers to a method for manufacturing a nonwoven fabric, comprising a fiber carding step and a fiber hydroentangling step for forming a web, wherein the method also comprises a calendering step of said web.

**[0020]** Preferably, said calendering step is carried out at a temperature from 60 °C and 280 °C and applying a pressure from 40 N/mm and 300 N/mm.

**[0021]** According to a preferred embodiment, said fibers are staple fibers, being natural fibers, synthetic fibers or a mixture of natural and synthetic fibers.

**[0022]** According to second aspect, the present invention refers to a nonwoven fabric manufactured by the method described previously, the nonwoven fabric comprising fibers forming substantially parallel stripes.

**[0023]** According to a preferred embodiment, said stripes have a width from 0.05 mm and 1.0 mm.

**[0024]** Said fibers are natural fibers, synthetic fibers, or a mixture of natural and synthetic fibers.

**[0025]** As stated previously, the resulting nonwoven fabric according to the present invention, manufactured by the method according to the present invention presents a low caliper, e.g. lower than 0.20 mm.

**[0026]** In addition, this nonwoven fabric resulting from the method according to the present invention is adaptable to irregular surfaces.

**[0027]** Moreover, and opposite to the calender bonded nonwoven fabrics, the cost of the method according to the present invention is low, since the fibers are water jet bonded.

## Brief description of the drawings

**[0028]** For a better understanding the above explanation and for the sole purpose of providing an example, some non-limiting drawings are included that schematically depict a practical embodiment.

**[0029]** Figure 1 is a diagrammatical plan view of the nonwoven fabric according to the present invention, showing the substantially parallel stripes.

## Description of preferred embodiments

**[0030]** Firstly, the present invention refers to a nonwoven fabric resulting of spunlacing (carding and hydroentangling) a plurality of staple fibers forming a web and, subsequently, calendering said web.

**[0031]** In this case, the calendering step is not carried out to bond the fibers, but to reduce the fabric thickness.

**[0032]** So, the spunlace nonwoven fabric obtained presents a significantly thinner caliper than the standard spunlace materials.

**[0033]** Anyway, the spunlace nonwoven obtained with the method according to the present invention preserves the good adaptability of the fabric to irregular surfaces.

**[0034]** In addition, as a result of the water jet fiber bonding, the nonwoven fabric of the invention shows a uniform bonding, which can be appreciated by visual analysis under an optical microscope.

**[0035]** In fact, the water jet uniform bonding results in 0.05 - 1.0 mm wide parallel stripes in machine direction separated between 0.5 - 1.5 mm, which differentiate a hydroentangled nonwoven fabric from other technologies, such as calender bonded, thermal bonded or chemical bonded.

**[0036]** These wide parallel stripes are shown in Fig. 1.

**[0037]** Regarding the feedstock, the fibers source can be natural (such as Viscose, Lyocell or PLA), synthetic (like PET, PP, PE or bi-component fibers) or a blend of natural source fibers and synthetic fibers.

**[0038]** Moreover, the spunlace nonwoven fabric of the invention presents a basis weight between 25 and 90 g/m<sup>2</sup>.

**[0039]** The nonwoven manufacturing method according to the present invention comprises the following steps:

- Web forming by staple fibers carding;
- Web bonding by staple carded fibers hydroentanglement;
- Calendering of the hydroentangled web.

**[0040]** So, according to the present invention, the spunlace nonwoven manufacturing method comprises an additional calendering final treatment of the hydroentangled web, which differentiates it from the standard spunlace production method.

**[0041]** In addition, and opposite to the calender bonding technology, the method of the invention is a low-cost method, since the fibers are water jet bonded.

**[0042]** This additional calendering step of the spunlaced web is carried out preferably at a temperature between 60 and 280 °C and a nip pressure between 40 N/mm and 300 N/mm.

- Examples

**[0043]** In the following table, two examples of nonwoven fabrics of the present invention are shown and the resulting caliper is compared to similar composition and basis weight standard spunlace materials (references):

5  
10  
15  
20  
25  
30  
35  
40  
45  
50  
55

5  
10  
15  
20  
25  
30  
35  
40  
45  
50  
55

EXAMPLE	NONWOVEN FABRIC COMPOSITION			PRODUCTION PROCESS STEPS				Caliper (mm)
	Basis Weight (g/m <sup>2</sup> )	Type and % Natural source Fibers	Type and % Synthetic Fibers	Carding	Hydro- entanglement	Calendering		
						Pressure (N/mm)	Temperature (°C)	
Example 1	35	-	100% Polyester	YES	YES	110	230	0.08
Reference (Standard spunlace fabric)	35	-	100% Polyester	YES	YES	NO		0.58


EXAMPLE	NONWOVEN FABRIC COMPOSITION			NONWOVEN FABRIC COMPOSITION				Caliper (mm)
	Basis Weight (g/m²)	Type and % Natural source Fibers	Type and % Synthetic Fibers	Carding	Hydroen tanglement	Calendering		
						Pressure (N/mm)	Temperature (°C)	
Example 2	50	70% Viscose	30% Polyester	YES	YES	200	80	0,17
Reference (Standard spunlace fabric)	50	70% Viscose	30% Polyester	YES	YES	NO		0,66

**[0044]** Even though reference has been made to a specific embodiment of the invention, it is obvious for a person skilled in the art that the method and the nonwoven fabric described herein are susceptible to numerous variations and modifications, and that all of the details mentioned can be substituted for other technically equivalent ones without departing from the scope of protection defined by the attached claims.

#### Claims

- Method for manufacturing a nonwoven fabric, comprising a fiber carding step and a fiber hydroentangling step for forming a web, **characterized in that** it also comprises a calendering step of said web.
- Method for manufacturing a nonwoven fabric according to claim 1, wherein said calendering step is carried out at a temperature from 60 °C and 280 °C.
- Method for manufacturing a nonwoven fabric according to claim 1 or, wherein said calendering step is carried out applying a pressure from 40 N/mm and 300 N/mm.
- Method for manufacturing a nonwoven fabric according to claim 1, wherein said fibers are staple fibers.
- Method for manufacturing a nonwoven fabric according to claim 1 or 4, wherein said fibers are natural fibers.
- Method for manufacturing a nonwoven fabric according to claim 1 or 4, wherein said fibers are synthetic fibers.
- Method for manufacturing a nonwoven fabric according to claim 1 or 4, wherein said fibers are a mixture of natural and synthetic fibers.
- Nonwoven fabric manufactured by the method according to anyone of the previous claims, **characterized in that** the nonwoven fabric comprising fibers forming substantially parallel stripes.
- Nonwoven fabric according to claim 8, wherein said stripes have a width from 0.05 mm and 1.0 mm.
- Nonwoven fabric according to claim 8, wherein said fibers are natural fibers.
- Nonwoven fabric according to claim 8, wherein said fibers are synthetic fibers.
- Nonwoven fabric according to claim 8, wherein said fibers are a mixture of natural and synthetic fibers.

**FIG. 1**





## EUROPEAN SEARCH REPORT

Application Number  
EP 19 38 2116

5

10

15

20

25

30

35

40

45

50

55

1

EPO FORM 1503 03.82 (P04C01)

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 2018/105965 A1 (POURDEYHIMI BEHNAM [US] ET AL) 19 April 2018 (2018-04-19) * paragraph [0065]; figure 1 * -----	1-12	INV. D04H1/49 D04H1/558
X	US 2003/024092 A1 (ORLANDI VITTORIO [IT]) 6 February 2003 (2003-02-06) * paragraph [0006]; figure 1 * -----	1-7	
A		8-12	
A	DATABASE WPI Week 201571 Thomson Scientific, London, GB; AN 2015-61528H XP002792399, -& JP 2015 180789 A (DAIWABO HOLDINGS CO LTD) 15 October 2015 (2015-10-15) * abstract; figures 1, 2, 7, 8 * -----	1-12	
A	EP 2 692 924 A1 (SUOMINEN CORP [FI]) 5 February 2014 (2014-02-05) * abstract *	1-12	
A	WO 2006/044295 A1 (PROCTER & GAMBLE [US]; GORLEY RONALD THOMAS [US] ET AL.) 27 April 2006 (2006-04-27) * claim 8; example 2 * -----	1-12	TECHNICAL FIELDS SEARCHED (IPC) D04H
The present search report has been drawn up for all claims			
Place of search <b>Munich</b>		Date of completion of the search <b>26 June 2019</b>	Examiner <b>Saunders, Thomas</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			



**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 19 38 2116

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-06-2019

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2018105965 A1	19-04-2018	NONE	
US 2003024092 A1	06-02-2003	AT 279559 T BR 0108687 A CA 2400813 A1 CN 1404540 A DE 10008746 A1 DE 50104106 D1 DK 1266058 T3 EA 200200901 A1 EP 1266058 A1 ES 2231455 T3 IL 151088 A JP 3740420 B2 JP 2004500494 A US 2003024092 A1 US 2005066490 A1 WO 0163032 A1	15-10-2004 12-11-2002 30-08-2001 19-03-2003 30-08-2001 18-11-2004 14-02-2005 27-02-2003 18-12-2002 16-05-2005 15-06-2009 01-02-2006 08-01-2004 06-02-2003 31-03-2005 30-08-2001
JP 2015180789 A	15-10-2015	JP 5525179 B2 JP 5542194 B2 JP 5746737 B2 JP 6080319 B2 JP 2009287158 A JP 2013064226 A JP 2013241724 A JP 2015180789 A	18-06-2014 09-07-2014 08-07-2015 15-02-2017 10-12-2009 11-04-2013 05-12-2013 15-10-2015
EP 2692924 A1	05-02-2014	EP 2692924 A1 ES 2662147 T3 US 2014037906 A1	05-02-2014 05-04-2018 06-02-2014
WO 2006044295 A1	27-04-2006	EP 1799366 A1 JP 2008516672 A US 2005133174 A1 WO 2006044295 A1	27-06-2007 22-05-2008 23-06-2005 27-04-2006

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82