



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 71, 72

(51) Int Cl.:
A43B 13/18 (2006.01) A43B 13/26 (2006.01)

(86) International application number:
PCT/KR2019/000934

(48) Corrigendum issued on:
07.04.2021 Bulletin 2021/14

(87) International publication number:
WO 2020/153511 (30.07.2020 Gazette 2020/31)

(43) Date of publication:
09.09.2020 Bulletin 2020/37

(21) Application number: **19722494.2**

(22) Date of filing: **23.01.2019**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
KH MA MD TN

(72) Inventors:
• **KIM, Sung Sim**
Dongnae-gu, Busan 47866 (KR)
• **CHOI, Choon Geun**
Dongnae-gu, Busan 47866 (KR)
• **CHOI, Do Kyung**
Buk-gu, Busan 46536 (KR)

(74) Representative: **Viering, Jentschura & Partner mbB**
Patent- und Rechtsanwälte
Am Brauhaus 8
01099 Dresden (DE)

(71) Applicant: **Shinwon Chemical Products Co., Ltd.**
Gimhae-si Gyeongsangnam-do 50807 (KR)

(54) **SHOCK-ABSORBING AND SLIP-PREVENTING SHOE**

(57) Provided is a non-skid shoe capable of absorbing shock including: an outsole; a plurality of accommodation grooves formed on the outsole, the accommodation groove including a groove portion, and a penetrated portion extending from a center of a bottom surface of the groove portion and penetrating a bottom surface of the outsole; a support member which is accommodated in the respective accommodation grooves, and includes a support portion disposed in the groove portion, a first guide portion formed at a center of the support portion, and a second guide portion extending from a center of a bottom surface of the first guide portion and penetrating a bottom surface of a center of the support portion; a movable member which is disposed in the respective support members, and includes a latch portion and a protruding portion; a pressing member which is engaged to an upper portion of the first guide portion to seal the upper portion; a resilient member which is disposed in the first guide portion; and a midsole engaged to the top surface of the outsole.

[Fig. 2]

