



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
23.09.2020 Bulletin 2020/39

(51) Int Cl.:
B65D 5/42 (2006.01) **B65D 5/68 (2006.01)**

(21) Application number: **19020211.9**

(22) Date of filing: **22.03.2019**

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**
Designated Extension States:
BA ME
Designated Validation States:
KH MA MD TN

(72) Inventors:
• **FERRIE, Kate**
Speke, Liverpool L24 9HP (GB)
• **MURRAY, Samantha**
Speke, Liverpool L24 9HP (GB)

(74) Representative: **Mewburn Ellis LLP**
Aurora Building
Counterslip
Bristol BS1 6BX (GB)

(71) Applicant: **NERUDIA LIMITED**
Liverpool Merseyside L24 9HP (GB)

(54) **PACKAGING FOR A SMOKING SUBSTITUTE DEVICE**

(57) A packaging (1000) for a smoking substitute system comprising: a cover (1002); and a tray (1001) comprising a cavity (1003) for receiving the smoking substitute system, wherein the tray is configured to be periph-

erally received in the cover and thereby defining an air flow channel therebetween; wherein the air flow channel is configured to provide fluid communication between the cavity and an external environment.




FIG 1B

Description

TECHNICAL FIELD

[0001] The present invention relates to a packing for a smoking substitute device and particularly, although not exclusively, to a smoking substitute system comprising a smoking substitute device and a packaging for the device.

BACKGROUND

[0002] The smoking of tobacco is generally considered to expose a smoker to potentially harmful substances. It is generally thought that a significant amount of the potentially harmful substances are generated through the heat caused by the burning and/or combustion of the tobacco and the constituents of the burnt tobacco in the tobacco smoke itself.

[0003] Conventional combustible smoking articles, such as cigarettes, typically comprise a cylindrical rod of tobacco comprising shreds of tobacco which is surrounded by a wrapper, and usually also a cylindrical filter axially aligned in an abutting relationship with the wrapped tobacco rod. The filter typically comprises a filtration material which is circumscribed by a plug wrap. The wrapped tobacco rod and the filter are joined together by a wrapped band of tipping paper that circumscribes the entire length of the filter and an adjacent portion of the wrapped tobacco rod. A conventional cigarette of this type is used by lighting the end opposite to the filter, and burning the tobacco rod. The smoker receives mainstream smoke into their mouth by drawing on the mouth end or filter end of the cigarette.

[0004] Combustion of organic material such as tobacco is known to produce tar and other potentially harmful by-products. There have been proposed various smoking substitute systems (or "substitute smoking systems") in order to avoid the smoking of tobacco.

[0005] Such smoking substitute systems can form part of nicotine replacement therapies aimed at people who wish to stop smoking and overcome a dependence on nicotine.

[0006] Smoking substitute systems include electronic systems that permit a user to simulate the act of smoking by producing an aerosol (also referred to as a "vapour") that is drawn into the lungs through the mouth (inhaled) and then exhaled. The inhaled aerosol typically bears nicotine and/or flavourings without, or with fewer of, the odour and health risks associated with traditional smoking.

[0007] In general, smoking substitute systems are intended to provide a substitute for the rituals of smoking, whilst providing the user with a similar experience and satisfaction to those experienced with traditional smoking and with combustible tobacco products. Some smoking substitute systems use smoking substitute articles (also referred to as a "consumables") that are designed to re-

semble a traditional cigarette and are cylindrical in form with a mouthpiece at one end.

[0008] The popularity and use of smoking substitute systems has grown rapidly in the past few years. Although originally marketed as an aid to assist habitual smokers wishing to quit tobacco smoking, consumers are increasingly viewing smoking substitute systems as desirable lifestyle accessories.

[0009] There are a number of different categories of smoking substitute systems, each utilising a different smoking substitute approach.

[0010] One approach for a smoking substitute system is the so-called Heated Tobacco ("HT") approach in which tobacco (rather than an "e-liquid") is heated or warmed to release vapour. HT is also known as "heat not burn" ("HNB"). The tobacco may be leaf tobacco or reconstituted tobacco. The vapour may contain nicotine and/or flavourings. In the HT approach the intention is that the tobacco is heated but not burned, i.e. the tobacco does not undergo combustion.

[0011] A typical HT smoking substitute system may include a device and consumable. The consumable may include the tobacco material. The device and consumable may be configured to be physically coupled together. In use, heat may be imparted to the tobacco material by a heating element of the device, wherein airflow through the tobacco material causes components in the tobacco material to be released as vapour. A vapour may also be formed from a carrier in the tobacco material (this carrier may for example include propylene glycol and/or vegetable glycerine) and additionally volatile compounds released from the tobacco. The released vapour may be entrained in the airflow drawn through the tobacco.

[0012] As the vapour passes through the consumable (entrained in the airflow) from the location of vaporisation to an outlet of the consumable (e.g. a mouthpiece), the vapour cools and condenses to form an aerosol for inhalation by the user. The aerosol will normally contain the volatile compounds.

[0013] In HT smoking substitute systems, heating as opposed to burning the tobacco material is believed to cause fewer, or smaller quantities, of the more harmful compounds ordinarily produced during smoking. Consequently, the HT approach may reduce the odour and/or health risks that can arise through the burning, combustion and pyrolytic degradation of tobacco.

[0014] Generally, an HT device is packaged in a standard rigid box such as a cardboard box. The box, as known commonly in the art, is usually rectangular in shape and includes a bottom or tray. The tray has a cavity to accommodate the device and/or any other components. The tray is receivable in a lid or cover to secure the top side of the tray. In an aspect, the cover has a construction similar to an inverted tray so as to correspond with the shape of the tray. The tray may be partially or completely receivable in the cover.

[0015] A major shortcoming associated with these conventional packaging is that a negative pressure may build

up between the tray and the cover during the removal of the tray. Furthermore, there is usually no provision to aid a user gripping onto of the tray. As a result, a user may have to hold and shake the cover of the box to detach the tray under its own weight. Consequently, there is a risk that the tray may accidentally or unexpectedly drop out of the cover during such shaking and thereby damaging the device and content stored therein. Further, during an assembling process, the cavity may be pressurised as the tray is inserted into the cover. As a result, the cover may not be able to securely fit onto the tray.

[0016] Therefore, there is a need for improved design of smoking substitute systems, in particular a packaging for an HT device, to enhance the user experience and to overcome the one or more shortcomings associated with the prior art.

[0017] The present disclosure has been devised in the light of the above considerations.

SUMMARY OF THE INVENTION

[0018] At its most general, the present invention relates to packaging for a smoking substitute system. The packaging comprises an air flow channel to provide fluid communication between the cavity and the external environment, and thereby it may equalise the pressure in the cavity with atmospheric pressure. As a result, such arrangement may allow the tray to be removed from the cover with better efficiency.

[0019] According to a first aspect of the present invention, there is provided a packaging for a smoking substitute system. The packaging comprises a cover and a tray. The tray comprises a cavity for receiving the smoking substitute system. The tray is configured to be peripherally received in the cover such that an air flow channel is defined therebetween. The air flow channel is configured to provide fluid communication between the cavity and an external environment.

[0020] The smoking substitute system may comprise a smoking substitute device, and optionally an aerosol-forming article for use the smoking substitute device. The smoking substitute system may comprises other accessories for the device, such as a cleaning tool, a power source and a user manual.

[0021] For example, the air flow channel may allow an airflow to enter into the cavity when the tray is being removed the cover by a user, or to purge from the cavity when the tray is being received into the cover during an assembly process. Advantageously, the air flow channel may equalise the pressure in the cavity with atmospheric pressure.

[0022] The tray may be peripherally received in the cover. For example, the tray may engage with the cover with an interference fit. Such arrangement may allow the cover to be securely mounted on the tray.

[0023] By providing a packaging comprising a cover and a tray comprising an air flow channel in between, the packaging may advantageously allow the tray from the

cover in an efficient and convenient manner because the tray and the cover may no longer be hold back from each other by a negative pressure or partial vacuum.

[0024] Optional features will now be set out. These are applicable singly or in any combination with any aspect.

[0025] Optionally, at least a portion of a sidewall of the tray is configured to space from an adjacent portion of a sidewall of the cover when said tray is received in the cover, so as to define the air flow channel. For example, a gap may be present in between a portion of corresponding sidewalls of the cover and the tray. Advantageously, such arrangement may allow an airflow to flow between the gap and thereby enter or exit the cavity.

[0026] Optionally, the sidewalls of the cover and the tray are configured to space from each other by one or more protrusions extending from respective sidewalls of the cover and/or the tray, wherein said air flow channel is defined around the one or more protrusions. For example, one or more protrusions may extend from a sidewall of the cover and about the corresponding sidewall of the tray, or one or more protrusions may extend from a sidewall of the tray and about the corresponding sidewall of the cover, or one or more protrusions may extend from the sidewalls of each of the cover and the tray and about the corresponding sidewalls of the other one of the tray and cover. Advantageously, such arrangement may allow a continuous airflow into the cavity as the user removes the tray from the cover.

[0027] Optionally, the sidewalls of the cover and the tray are configured to space from each other by one or more grooves formed on respective sidewalls of the cover and/or the tray, wherein said air flow channel is defined along the one or more grooves. For example, one or more grooves may form on a sidewall of the cover facing a corresponding sidewall of the tray, or one or more grooves may form on a sidewall of the tray and facing a corresponding sidewall of the cover, or one or grooves may form on the sidewalls of each of the cover and the tray and facing the corresponding sidewalls of the other one of the tray and cover. Optionally, the one or grooves may form along the depth of the respective sidewalls. Advantageously, such arrangement may allow a continuous airflow into the cavity as the user removes the tray from the cover.

[0028] Optionally, one or more sidewalls of the cover and/or the tray comprises a corrugated surface having the grooves defined thereon. For example, such corrugated surface may form from a corrugated cardboard having its top liner removed. Advantageously, such arrangement may result in a simplified manufacturing process.

[0029] Optionally, one or more corners of the tray is truncated to define the air flow channel. For example, one or more of edges that adjoins adjacent sidewalls of the tray are truncated so as to define the airflow channels, along the truncated edges, towards the corners of the tray. Advantageously, such arrangement may result in a simplified manufacturing process.

[0030] Optionally, the airflow channel may comprise one or more vents opened on respective sidewalls of the cover and/or the tray. Optionally, the one or more vents comprises apertures opened on respective sidewalls of the cover and/or the tray. Optionally, the one or more vents may open to other airflow channels as described, e.g. as defined around protrusions, along the grooves or along the truncated corners. Advantageously, such arrangement may provide additional air passage and therefore the tray may be removed from the cover more efficiently.

[0031] Optionally, the one or more vents opened on a sidewall of the cover aligns with corresponding one or more vents opened on the tray when the tray is received in the cover. For example, the cavity of the tray may be exposed through one or more vents when the tray and the cover are mutually engaged. When separating of the tray from the cover, the one or more vents may allow an airflow to enter the cavity so as to equalise a negative pressure therein. This allows the tray to be separated from the cover in a more efficient manner. Advantageously, such arrangement may result in a simplified manufacturing process. Optionally, the one or more vent each comprises an air permeable valve or membrane for preventing liquid ingress to the cavity. The valve may be a two way valve, such as a flap, that only opens when there is an airflow entering or exiting the cavity. Advantageously, this may provide additional protection against damage to the device resulting from liquid ingress. Optionally, the one or more vents each comprises a one way valve to allow an airflow to enter into the cavity. This ensures the contents stored in the cavity, e.g. volatiles originating from the consumables or aerosol-forming articles, does not escape from the cavity.

[0032] The packaging may comprises a cover and a tray. The tray may comprise a cavity for receiving the smoking substitute device. The tray may configured to be peripherally received in the cover such that an air flow channel is defined therebetween. The air flow channel may be configured to allow an air flow to enter the cavity. One or both of an internal surface of the cover and an external surface of the tray may include an embossment or protrusion to maintain the external and internal surfaces offset from one another when the tray and cover are engaged. In an aspect, the airflow channel may be configured with one or more vents. The one or more vents may be configured to allow airflow into the cavity during removal or receipt of the tray in the cover. In one embodiment either of the cover and the tray may include at least one vent. In another embodiment, each the cover and tray may include at least one vent. In a further embodiment, the vent may be an aperture through a side wall of the cover and/or tray. The vent may be configured to accommodate a two-way valve or air permeable valve, or an air permeable sheet or a membrane.

[0033] The device may comprise an elongate body. An end of the elongate body may be configured for engagement with an aerosol-forming article. For example, the

body may be configured for engagement with a heated tobacco (HT) consumable (or heat-not-burn (HNB) consumable). The terms "heated tobacco" and "heat-not-burn" are used interchangeably herein to describe a consumable that is of the type that is heated rather than combusted (or are used interchangeably to describe a device for use with such a consumable). The device may comprise a cavity that is configured for receipt of at least a portion of the consumable (i.e. for engagement with the consumable). The aerosol-forming article may be of the type that comprises an aerosol former (e.g. carried by an aerosol-forming substrate).

[0034] The device may comprise a heater for heating the aerosol-forming article. The heater may comprise a heating element, which may be in the form of a rod that extends from the body of the device. The heating element may extend from the end of the body that is configured for engagement with the aerosol-forming article.

[0035] The heater (and thus the heating element) may be rigidly mounted to the body. The heating element may be elongate so as to define a longitudinal axis and may, for example, have a transverse profile (i.e. transverse to a longitudinal axis of the heating element) that is substantially circular (i.e. the heating element may be generally cylindrical). Alternatively, the heating element may have a transverse profile that is rectangular (i.e. the heater may be a "blade heater"). The heating element may alternatively be in the shape of a tube (i.e. the heater may be a "tube heater"). The heating element may take other forms (e.g. the heating element may have an elliptical transverse profile). The shape and/or size (e.g. diameter) of the transverse profile of the heating element may be generally consistent for the entire length (or substantially the entire length) of the heating element.

[0036] The heating element may be between 15 mm and 25 mm long, e.g. between 18 mm and 20 mm long, e.g. around 19 mm long. The heating element may have a diameter of between 1.5 mm and 2.5 mm, e.g. a diameter between 2 mm and 2.3 mm, e.g. a diameter of around 2.15 mm.

[0037] The heating element may be formed of ceramic. The heating element may comprise a core (e.g. a ceramic core) comprising Al₂O₃. The core of the heating element may have a diameter of 1.8 mm to 2.1 mm, e.g. between 1.9 mm and 2 mm. The heating element may comprise an outer layer (e.g. an outer ceramic layer) comprising Al₂O₃. The thickness of the outer layer may be between 160 μm and 220 μm, e.g. between 170 μm and 190 μm, e.g. around 180 μm. The heating element may comprise a heating track, which may extend longitudinally along the heating element. The heating track may be sandwiched between the outer layer and the core of the heating element. The heating track may comprise tungsten and/or rhenium. The heating track may have a thickness of around 20 μm.

[0038] The heating element may be located in the cavity (of the device), and may extend (e.g. along a longitudinal axis) from an internal base of the cavity towards an

opening of the cavity. The length of the heating element (i.e. along the longitudinal axis of the heater) may be less than the depth of the cavity. Hence, the heating element may extend for only a portion of the length of the cavity. That is, the heating element may not extend through (or beyond) the opening of the cavity.

[0039] The heating element may be configured for insertion into an aerosol-forming article (e.g. a HT consumable) when an aerosol-forming article is received in the cavity. In that respect, a distal end (i.e. distal from a base of the heating element where it is mounted to the device) of the heating element may comprise a tapered portion, which may facilitate insertion of the heating element into the aerosol-forming article. The heating element may fully penetrate an aerosol-forming article when the aerosol-forming article is received in the cavity. That is, the entire length, or substantially the entire length, of the heating element may be received in the aerosol-forming article.

[0040] The heating element may have a length that is less than, or substantially the same as, an axial length of an aerosol-forming substrate forming part of an aerosol-forming article (e.g. a HT consumable). Thus, when such an aerosol-forming article is engaged with the device, the heating element may only penetrate the aerosol-forming substrate, rather than other components of the aerosol-forming article. The heating element may penetrate the aerosol-forming substrate for substantially the entire axial length of the aerosol-forming-substrate of the aerosol-forming article. Thus, heat may be transferred from (e.g. an outer circumferential surface of) the heating element to the surrounding aerosol-forming substrate, when penetrated by the heating element. That is, heat may be transferred radially outwardly (in the case of a cylindrical heating element) or e.g. radially inwardly (in the case of a tube heater).

[0041] Where the heater is a tube heater, the heating element of the tube heater may surround at least a portion of the cavity. When the portion of the aerosol-forming article is received in the cavity, the heating element may surround a portion of the aerosol-forming article (i.e. so as to heat that portion of the aerosol-forming article). In particular, the heating element may surround an aerosol-forming substrate of the aerosol-forming article. That is, when an aerosol-forming article is engaged with the device, the aerosol-forming substrate of the aerosol-forming article may be located adjacent an inner surface of the (tubular) heating element. When the heating element is activated, heat may be transferred radially inwardly from the inner surface of the heating element to heat the aerosol-forming substrate.

[0042] The cavity may comprise a (e.g. circumferential) wall (or walls) and the (tubular) heating element may extend around at least a portion of the wall(s). In this way, the wall may be located between the inner surface of the heating element and an outer surface of the aerosol-forming article. The wall (or walls) of the cavity may be formed from a thermally conductive material (e.g. a metal) to allow heat conduction from the heating element to

the aerosol-forming article. Thus, heat may be conducted from the heating element, through the cavity wall (or walls), to the aerosol-forming substrate of an aerosol-forming article received in the cavity.

[0043] In some embodiments the heater may form part of an aerosol-forming article for use with the device. In such cases the device may not comprise a heater. Rather, the aerosol-forming article may comprise a heater. Such arrangements may, for example, be suited to e-cigarette systems in which the aerosol-forming article comprises a tank containing an aerosol former (e.g. in liquid form). In such embodiments, the device may comprise means for connecting the device the heater of an aerosol-forming article engaged with the device. For example, the device may comprise one or more device connectors for (e.g. electrically) connecting the device to a corresponding heater connector of the aerosol-forming article. The connectors (i.e. of both the device and the aerosol-forming article) may be in the form of electrically conductive elements (e.g. plates) that contact when the aerosol-forming article is engaged with the device.

[0044] In some embodiments the device may comprise a cap disposed at the end of the body that is configured for engagement with an aerosol-forming article. Where the device comprises a heater having a heating element, the cap may at least partially enclose the heating element. The cap may be moveable between an open position in which access is provided to the heating element, and a closed position in which the cap at least partially encloses the heating element. The cap may be slideably engaged with the body of the device, and may be slideable between the open and closed positions.

[0045] The cap may define at least a portion of the cavity of the device. That is, the cavity may be fully defined by the cap, or each of the cap and body may define a portion of the cavity. Where the cap fully defines the cavity, the cap may comprise an aperture for receipt of the heating element into the cavity (when the cap is in the closed position). The cap may comprise an opening to the cavity. The opening may be configured for receipt of at least a portion of an aerosol-forming article. That is, an aerosol-forming article may be inserted through the opening and into the cavity (so as to be engaged with the device).

[0046] The cap may be configured such that when an aerosol-forming article is engaged with the device (e.g. received in the cavity), only a portion of the aerosol-forming article is received in the cavity. That is, a portion of the aerosol-forming article (not received in the cavity) may protrude from (i.e. extend beyond) the opening. This (protruding) portion of the aerosol-forming article may be a terminal (e.g. mouth) end of the aerosol-forming article, which may be received in a user's mouth for the purpose of inhaling aerosol formed by the device.

[0047] The device may comprise a power source or may be connectable to a power source (e.g. a power source separate to the device). The power source may be electrically connectable to the heater. In that respect,

altering (e.g. toggling) the electrical connection of the power source to the heater may affect a state of the heater. For example, toggling the electrical connection of the power source to the heater may toggle the heater between an on state and an off state. The power source may be a power store. For example, the power source may be a battery or rechargeable battery (e.g. a lithium ion battery).

[0048] The device may comprise an input connection (e.g. a USB port, Micro USB port, USB-C port, etc.). The input connection may be configured for connection to an external source of electrical power, such as a mains electrical supply outlet. The input connection may, in some cases, be used as a substitute for an internal power source (e.g. battery or rechargeable battery). That is, the input connection may be electrically connectable to the heater (for providing power to the heater). Hence, in some forms, the input connection may form at least part of the power source of the device.

[0049] Where the power source comprises a rechargeable power source (such as a rechargeable battery), the input connection may be used to charge and recharge the power source.

[0050] The device may comprise a user interface (UI). In some embodiments the UI may include input means to receive operative commands from the user. The input means of the UI may allow the user to control at least one aspect of the operation of the device. In some embodiments the input means may comprise a power button to switch the device between an on state and an off state.

[0051] In some embodiments the UI may additionally or alternatively comprise output means to convey information to the user. In some embodiments the output means may comprise a light to indicate a condition of the device (and/or the aerosol-forming article) to the user. The condition of the device (and/or aerosol-forming article) indicated to the user may comprise a condition indicative of the operation of the heater. For example, the condition may comprise whether the heater is in an off state or an on state. In some embodiments, the UI unit may comprise at least one of a button, a display, a touchscreen, a switch, a light, and the like. For example, the output means may comprise one or more (e.g. two, three, four, etc.) light-emitting diodes ("LEDs") that may be located on the body of the device.

[0052] The device may further comprise a puff sensor (e.g. airflow sensor), which form part of the input means of the UI. The puff sensor may be configured to detect a user drawing on an end (i.e. a terminal (mouth) end) of the aerosol-forming article. The puff sensor may, for example, be a pressure sensor or a microphone. The puff sensor may be configured to produce a signal indicative of a puff state. The signal may be indicative of the user drawing (an aerosol from the aerosol-forming article) such that it is e.g. in the form of a binary signal. Alternatively, or additionally, the signal may be indicative of a characteristic of the draw (e.g. a flow rate of the draw, length of time of the draw, etc.).

[0053] The device may comprise a controller, or may be connectable to a controller that may be configured to control at least one function of the device. The controller may comprise a microcontroller that may e.g. be mounted on a printed circuit board (PCB). The controller may also comprise a memory, e.g. non-volatile memory. The memory may include instructions, which, when implemented, may cause the controller to perform certain tasks or steps of a method. Where the device comprises an input connection, the controller may be connected to the input connection.

[0054] The controller may be configured to control the operation of the heater (and e.g. the heating element). Thus, the controller may be configured to control vaporisation of an aerosol forming part of an aerosol-forming article engaged with the device. The controller may be configured to control the voltage applied by power source to the heater. For example, the controller may be configured to toggle between applying a full output voltage (of the power source) to the heater and applying no voltage to the heater. Alternatively, or additionally, the control unit may implement a more complex heater control protocol.

[0055] The device may further comprise a voltage regulator to regulate the output voltage supplied by the power source to form a regulated voltage. The regulated voltage may subsequently be applied to the heater.

[0056] In some embodiments, where the device comprises a UI, the controller may be operatively connected to one or more components of the UI. The controller may be configured to receive command signals from an input means of the UI. The controller may be configured to control the heater in response to the command signals. For example, the controller may be configured to receive "on" and "off command signals from the UI and, in response, may control the heater so as to be in a corresponding on or off state.

[0057] The controller may be configured to send output signals to a component of the UI. The UI may be configured to convey information to a user, via an output means, in response to such output signals (received from the controller). For example, where the device comprises one or more LEDs, the LEDs may be operatively connected to the controller. Hence, the controller may be configured to control the illumination of the LEDs (e.g. in response to an output signal). For example, the controller may be configured to control the illumination of the LEDs according to (e.g. an on or off) state of the heater.

[0058] Where the device comprises a sensor (e.g. a puff/airflow sensor), the controller may be operatively connected to the sensor. The controller may be configured to receive a signal from the sensor (e.g. indicative of a condition of the device and/or engaged aerosol-forming article). The controller may be configured to control the heater, or an aspect of the output means, based on the signal from the sensor.

[0059] The device may comprise a wireless interface configured to communicate wirelessly (e.g. via Bluetooth

(e.g. a Bluetooth low-energy connection) or WiFi) with an external device. Similarly, the input connection may be configured for wired connection to an external device so as to provide communication between the device and the external device.

[0060] The external device may be a mobile device. For example, the external device may be a smart phone, tablet, smart watch, or smart car. An application (e.g. app) may be installed on the external device (e.g. mobile device). The application may facilitate communication between the device and the external device via the wired or wireless connection.

[0061] The wireless or wired interface may be configured to transfer signals between the external device and the controller of the device. In this respect, the controller may control an aspect of the device in response to a signal received from an external device. Alternatively, or additionally, an external device may respond to a signal received from the device (e.g. from the controller of the device).

[0062] In a second aspect, there is provided a smoking substitute system comprising the packaging of the first aspect, and a smoking substitute device configured to be received in the cavity of the packaging. Optionally, the system further comprises an aerosol-forming article. The aerosol-forming article may comprise an aerosol-forming substrate at an upstream end of the aerosol-forming article. The article may be in the form of a smoking substitute article, e.g. heated tobacco (HT) consumable (also known as a heat-not-burn (HNB) consumable). The smoking substitute system, including the packaging, may also be referred to as a smoking substitute product.

[0063] As used herein, the terms "upstream" and "downstream" are intended to refer to the flow direction of the vapour/aerosol i.e. with the downstream end of the article/consumable being the mouth end or outlet where the aerosol exits the consumable for inhalation by the user. The upstream end of the article/consumable is the opposing end to the downstream end.

[0064] The aerosol-forming substrate is capable of being heated to release at least one volatile compound that can form an aerosol. The aerosol-forming substrate may be located at the upstream end of the article/consumable.

[0065] In order to generate an aerosol, the aerosol-forming substrate comprises at least one volatile compound that is intended to be vaporised/aerosolised and that may provide the user with a recreational and/or medicinal effect when inhaled. Suitable chemical and/or physiologically active volatile compounds include the group consisting of: nicotine, cocaine, caffeine, opiates and opioids, cathine and cathinone, kavalactones, mysticin, beta-carboline alkaloids, salvinorin A together with any combinations, functional equivalents to, and/or synthetic alternatives of the foregoing.

[0066] The aerosol-forming substrate may comprise plant material. The plant material may comprise least one plant material selected from the list including *Amaranthus dubius*, *Arctostaphylos uva-ursi* (Bearberry), *Argemone*

mexicana, *Amica*, *Artemisia vulgaris*, Yellow Tees, *Galea zacatechichi*, *Canavalia maritima* (Baybean), *Cecropia mexicana* (Guamora), *Cestrum nocturnum*, *Cynoglossum virginianum* (wild comfrey), *Cytisus scoparius*, *Damiana*, *Entada rheedii*, *Eschscholzia californica* (California Poppy), *Fittonia albivenis*, *Hippobroma longiflora*, *Humulus japonica* (Japanese Hops), *Humulus lupulus* (Hops), *Lactuca virosa* (Lettuce Opium), *Lagdera alata*, *Leonotis leonurus*, *Leonurus cardiaca* (Motherwort), *Leonurus sibiricus* (Honeyweed), *Lobelia cardinalis*, *Lobelia inflata* (Indian-tobacco), *Lobelia siphilitica*, *Nepeta cataria* (Catnip), *Nicotiana species* (Tobacco), *Nymphaea alba* (White Lily), *Nymphaea caerulea* (Blue Lily), Opium poppy, *Passiflora incarnata* (Passionflower), *Pedicularis densiflora* (Indian Warrior), *Pedicularis groenlandica* (Elephant's Head), *Salvia divinorum*, *Salvia dorrii* (Tobacco Sage), *Salvia species* (Sage), *Scutellaria galericulata*, *Scutellaria lateriflora*, *Scutellaria nana*, *Scutellaria species* (Skullcap), *Sida acuta* (Wireweed), *Sida rhombifolia*, *Silene capensis*, *Syzygium aromaticum* (Clove), *Tagetes lucida* (Mexican Tarragon), *Tarhnanthus camphoratus*, *Tumera diffusa* (Damiana), *Verbascum* (Mullein), *Zamia latifolia* (Maconha Brava) together with any combinations, functional equivalents to, and/or synthetic alternatives of the foregoing.

[0067] The plant material may be tobacco. Any type of tobacco may be used. This includes, but is not limited to, flue-cured tobacco, burley tobacco, Maryland Tobacco, dark-air cured tobacco, oriental tobacco, dark-fired tobacco, perique tobacco and rustica tobacco. This also includes blends of the above mentioned tobaccos.

[0068] The tobacco may comprise one or more of leaf tobacco, stem tobacco, tobacco powder, tobacco dust, tobacco derivatives, expanded tobacco, homogenised tobacco, shredded tobacco, extruded tobacco, cut rag tobacco and/or reconstituted tobacco (e.g. slurry recon or paper recon).

[0069] The aerosol-forming substrate may comprise a gathered sheet of homogenised (e.g. paper/slurry recon) tobacco or gathered shreds/strips formed from such a sheet.

[0070] The aerosol-forming substrate may comprise one or more additives selected from humectants, flavourants, fillers, aqueous/non-aqueous solvents and binders.

[0071] The flavourant may be provided in solid or liquid form. It may include menthol, liquorice, chocolate, fruit flavour (including e.g. citrus, cherry etc.), vanilla, spice (e.g. ginger, cinnamon) and tobacco flavour. The flavourant may be evenly dispersed throughout the aerosol-forming substrate or may be provided in isolated locations and/or varying concentrations throughout the aerosol-forming substrate.

[0072] The aerosol-forming substrate may be formed in a substantially cylindrical shape such that the article/consumable resembles a conventional cigarette. It may have a diameter of between 5 and 10mm e.g. between 6 and 9mm or 6 and 8mm e.g. around 7 mm. It may have an axial length of between 10 and 15mm e.g.

between 11 and 14mm such as around 12 or 13mm.

[0073] The article/consumable may comprise at least one filter element. There may be a terminal filter element at the downstream/mouth end of the article/consumable.

[0074] The or at least one of the filter element(s) (e.g. the terminal filter element) may be comprised of cellulose acetate or polypropylene tow. The at least one filter element (e.g. the terminal filter element) may be comprised of activated charcoal. The at least one filter element (e.g. the terminal element) may be comprised of paper. The or each filter element may be at least partly (e.g. entirely) circumscribed with a plug wrap e.g. a paper plug wrap.

[0075] The terminal filter element (at the downstream end of the article/consumable) may be joined to the upstream elements forming the article/consumable by a circumscribing tipping layer e.g. a tipping paper layer. The tipping paper may have an axial length longer than the axial length of the terminal filter element such that the tipping paper completely circumscribes the terminal filter element plus the wrapping layer surrounding any adjacent upstream element.

[0076] In some embodiments, the article/consumable may comprise an aerosol-cooling element which is adapted to cool the aerosol generated from the aerosol-forming substrate (by heat exchange) before being inhaled by the user.

[0077] The article/consumable may comprise a spacer element that defines a space or cavity between the aerosol-forming substrate and the downstream end of the consumable. The spacer element may comprise a cardboard tube. The spacer element may be circumscribed by the (paper) wrapping layer.

[0078] In some embodiments the system may be in the form of an e-cigarette system (i.e. rather than a heated tobacco system as described above). In such a system, the consumable may be in the form of an e-cigarette consumable. The e-cigarette system may be configured such that the consumable can be received and retained in the cavity of the device (i.e. so as to be engaged with the device). The consumable may be retained by way of e.g. an interference fit, screwing one onto (or onto) the other, a bayonet fitting, or by way of a snap engagement mechanism.

[0079] The consumable may comprise a tank, which may define a reservoir for the storage of an aerosol former. The aerosol former may be in the form of an e-liquid (stored in the reservoir).

[0080] The consumable may be a "single-use" consumable. That is, upon exhausting the e-liquid in the tank, the intention may be that the user disposes of the entire consumable. Alternatively, the e-liquid may be the only part of the system that is truly "single-use". For example, the tank may be refillable with e-liquid or another component of the system (internal to the device or external to the device e.g. a refillable cartomizer) may define a reservoir for the e-liquid.

[0081] As set forth above, the consumable may comprise a heater (i.e. instead of the heater forming part of

the device) configured to heat and vaporise the e-liquid. The consumable may comprise a porous wick that conveys e-liquid from the tank to a heating element of the heater. The heating element may be a heating filament that is wound (e.g. helically) around at least a portion of the porous wick, such that when the heating element is heated (e.g. by the action of electrical current passing through the heating element), heat may be transferred from the heating element to the e-liquid conveyed by the wick. This transfer of heat may vaporise the e-liquid and the resultant vapour may be entrained in an airflow passing through the consumable.

[0082] The consumable may further comprise one or more heater connectors for connecting the heater (of the consumable) to the device. The heater connectors may be in the form of electrically conductive element or contacts (e.g. metal plates) and may be disposed on an in-use device-facing surface of the consumable. The heater connectors may be electrically connected to the heater of the consumable, such that electricity supplied via the heater connectors may pass to the heater. In other words, a voltage applied across the heater connectors may generally correspond to a voltage applied across the heating element of the heater.

[0083] The heater connectors may be arranged such that they contact corresponding device connectors of the device when the consumable is engaged with the device. The device connectors may be connected (e.g. electrically) to a power source (e.g. battery) of the device. Thus, electricity may be supplied from the power source to the heating element, via in-contact heater and device connectors. In this way, the heater forming part of the consumable may operate (and interact with e.g. a controller) as otherwise described above with respect to a heater forming part of the device.

[0084] According to an aspect of the present invention, there is provided a method of using the system according to the method comprising inserting the aerosol-forming article into the device; and heating the article using the heater of the device.

[0085] In some embodiments the method may comprise inserting the article into a cavity within a body of the device and penetrating the article with the heating element of the device upon insertion of the article.

[0086] The invention includes the combination of the aspects and preferred features described except where such a combination is clearly impermissible or expressly avoided.

[0087] The skilled person will appreciate that except where mutually exclusive, a feature or parameter described in relation to any one of the above aspects may be applied to any other aspect. Furthermore, except where mutually exclusive, any feature or parameter described herein may be applied to any aspect and/or combined with any other feature or parameter described herein.

SUMMARY OF THE FIGURES

[0088] So that the invention may be understood, and so that further aspects and features thereof may be appreciated, embodiments illustrating the principles of the invention will now be discussed in further detail with reference to the accompanying figures, in which:

Figure 1A is a perspective view of a packaging for a smoking substitute device

Figure 1B is a perspective view a cover and a tray forming the packaging of Figure 1A

Figure 2A is a schematic of a smoking substitute system;

Figure 2B is a schematic of a variation of the smoking substitute system of Figure 2A;

Figure 3A is a front view of a first embodiment of a smoking substitute system with the consumable engaged with the device;

Figure 3B is a front view of the first embodiment of the smoking substitute system with the consumable disengaged from the device;

Figure 3C is a section view of the consumable of the first embodiment of the smoking substitute system;

Figure 3D is a detailed view of an end of the device of the first embodiment of the smoking substitute system;

Figure 3E is a section view of the first embodiment of the smoking substitute system;

Figure 4A is a front view of a second embodiment of a smoking substitute system with the consumable engaged with the device; and

Figure 4B is a front view of a second embodiment of the smoking substitute system with the consumable disengaged from the device.

DETAILED DESCRIPTION OF THE INVENTION

[0089] Aspects and embodiments of the present invention will now be discussed with reference to the accompanying figures. Further aspects and embodiments will be apparent to those skilled in the art. All documents mentioned in this text are incorporated herein by reference.

[0090] Figure 1A is a schematic providing a general overview of a packaging 1000 for a smoking substitute device. In the illustrated embodiment, the packaging 1000 has a rectangular cross sectional shape and has

an external profile generally resembling a cuboid. However, the shape, external profile and dimensional configuration may vary in other embodiments.

[0091] As depicted in Figure 1A, the packaging 1000 comprises a tray 1001 and a cover 1002. In the present embodiment as shown in Figure 1B, the tray 1001 comprises a cavity 1003 defined between tray side walls 1004 and a floor 1010. The cavity 1003 is configured to receive the smoking substitute device and one or more components associated with the device. In some embodiments, the smoking substitute device may be secured in an additional product tray, which in turn is fully received in the cavity of the tray 1001. The tray 1001 is open from a top side.

[0092] The cover 1002 has a rectangular cross sectional profile corresponding to the cross sectional profile of the tray 1001. The cover 1002 comprises a void defined between cover side walls 1006 and a ceiling 1012. The void of the cover 1002 is adapted to receive the tray 1001 from an opening of the void. In different embodiments, the tray 1001 may be received peripherally in the cover 1002, partially or completely.

[0093] When the tray 1001 is engaged with the cover 1002, at least one air flow channel 1010 is defined between the interface between the tray side walls 1004 the cover side walls 1006. The air flow channel 1010 is configured to allow fluid communication between the cavity 1003 and an external environment. More specifically, the air flow channel 1010 allows an airflow to enter into and leave from the cavity 1003 when the tray 1001 is engaged with the cover 1002.

[0094] When the tray 1001 is received in the cover 1002, at least a portion of the tray side walls 1004 is configured to space from an adjacent portion of the cover side wall 1006 and thereby forms said air flow channel 1010. In one example, a plurality of protrusions (not shown) may form on the internal surface of the cover side walls 1006 and thereby when the tray is received in the cover 1002, air channels are defined through the gap in between each of the protrusions. Advantageously, because the protrusions are formed on an internal surface of the cover side walls 1006, they are concealed from sight. In other embodiments, the protrusions may additionally or alternatively forms on the external surface of the tray side walls 1004.

[0095] Other forms of air flow channels may be defined on either or both of the internal surface of the cover side walls 1006 and the external surface of the tray side walls 1004. For example, one or more grooves may form on the internal surface of the cover side walls 1006 and extend substantially along the depth of the void of the cover, and/or they may form on the external surface of the tray side walls 1004 and extend substantially along the depth of the cavity 1003 of the tray 1001.

[0096] Alternatively, either or both of the internal surface of the cover side walls 1006 and the external surface of the tray side walls 1004 may have a corrugated finish to form a plurality of airflow channels 1010, e.g. said side

walls may form from corrugated cardboard.

[0097] In other embodiments, one or more of edges that adjoins adjacent sidewalls of the tray 1001 are truncated so as to define the airflow channels, along the truncated edges, towards the corners of the tray 1001. That is, one or more corners of the tray 1001 are truncated. When the tray 1001 is received in the cover 1002 such truncation is concealed in the cover 1002

[0098] In the illustrated embodiment as shown in Figures 1A and 1B, a plurality of vents 1011 form the air flow channels. In other embodiments, the one or more airflow channels 1010 is configured to be in fluid communication with a plurality of vents 1011. The one or more vents 1010 are configured to allow fluid communication, directly or through the corresponding airflow channels, between the cavity 1003 and the external environment when the tray 1001 is being inserted into or removed from the cover 1002. In one embodiment either of the tray 1001 or the cover 1002 include the one or more vents 1011. In another embodiment, each of the tray 1001 and the cover 1002 include the one or more vents 1011.

[0099] As shown in Figures 1A and 1B, the one or more vents are in the form of an aperture through a side wall of the cover 1002 and/or tray 1001. The cavity 1003 of the tray is exposed through one or more vents 1011 when the tray 1001 and the cover 1002 are mutually engaged. When separating the tray 1001 from the cover 1002, the one or more vents 1011 allow an airflow to enter the cavity 1003 so as to equalise a negative pressure therein. This allows the tray 1001 to be separated from the cover 1002 in a more efficient manner.

[0100] Furthermore, the one or more vents 1011 further comprises air flow control members such as, but not limited to, two-way valves and/or membranes such as air permeable sheets. The two-way valve, such as a flap, is normally closed, except when opened by the action of removing and/or inserting the tray from/into the cover. This prevents fluid ingress, through the plurality of vents 1011, into the cavity during transport and storage of the packaging 1000.

[0101] Figure 2A is a schematic providing a general overview of a smoking substitute system 100. The system 100 includes a substitute smoking device 101 and an aerosol-forming article in the form of a consumable 102, which comprises an aerosol former 103. The system is configured to vaporise the aerosol former by heating the aerosol former 103 (so as to form a vapour/aerosol for inhalation by a user).

[0102] In the illustrated system, the heater 104 forms part of the consumable 102 and is configured to heat the aerosol former 103. In this variation, the heater 104 is electrically connectable to the power source 105, for example, when the consumable 102 is engaged with the device 101. Heat from the heater 104 vaporises the aerosol former 103 to produce a vapour. The vapour subsequently condenses to form an aerosol, which is ultimately inhaled by the user.

[0103] The system 100 further comprises a power

source 105 that forms part of the device 101. In other embodiments the power source 105 may be external to (but connectable to) the device 101. The power source 105 is electrically connectable to the heater 104 such that it is able to supply power to the heater 104 (i.e. for the purpose of heating the aerosol former 103). Thus, control of the electrical connection of the power source 105 to the heater 104 provides control of the state of the heater 104. The power source 105 may be a power store, for example a battery or rechargeable battery (e.g. a lithium ion battery).

[0104] The system 100 further comprises an I/O module comprising a connector 106 (e.g. in the form of a USB port, Micro USB port, USB-C port, etc.). The connector 106 is configured for connection to an external source of electrical power, e.g. a mains electrical supply outlet. The connector 106 may be used in substitution for the power source 105. That is the connector 106 may be electrically connectable to the heater 104 so as to supply electricity to the heater 104. In such embodiments, the device may not include a power source, and the power source of the system may instead comprise the connector 106 and an external source of electrical power (to which the connector 106 provides electrical connection).

[0105] In some embodiments, the connector 106 may be used to charge and recharge the power source 105 where the power source 105 includes a rechargeable battery.

[0106] The system 100 also comprises a user interface (UI) 107. Although not shown, the UI 107 may include input means to receive commands from a user. The input means of the UI 107 allows the user to control at least one aspect of the operation of the system 100. The input means may, for example, be in the form of a button, touch-screen, switch, microphone, etc.

[0107] The UI 107 also comprises output means to convey information to the user. The output means may, for example, comprise lights (e.g. LEDs), a display screen, speaker, vibration generator, etc.

[0108] The system 100 further comprises a controller 108 that is configured to control at least one function of the device 101. In the illustrated embodiment, the controller 108 is a component of the device 101, but in other embodiments may be separate from (but connectable to) the device 101. The controller 108 is configured to control the operation of the heater 104 and, for example, may be configured to control the voltage applied from the power source 105 to the heater 104. The controller 108 may be configured to toggle the supply of power to the heater 104 between an on state, in which the full output voltage of the power source 105 is applied to the heater 104, and an off state, in which the no voltage is applied to the heater 104.

[0109] Although not shown, the system 100 may also comprise a voltage regulator to regulate the output voltage from the power source 105 to form a regulated voltage. The regulated voltage may then be applied to the heater 104.

[0110] In addition to being connected to the heater 104, the controller 108 is operatively connected to the UI 107. Thus, the controller 108 may receive an input signal from the input means of the UI 107. Similarly, the controller 108 may transmit output signals to the UI 107. In response, the output means of the UI 107 may convey information, based on the output signals, to a user. The controller also comprises a memory 109, which is a non-volatile memory. The memory 109 includes instructions, which, when implemented, cause the controller to perform certain tasks or steps of a method.

[0111] Figure 2B is a schematic showing a variation of the system 100 of Figure 2A. In the system 100' of Figure 2B, the heater 104 forms part of the device 101, rather than the consumable 102. In this variation, the heater 104 is electrically connected to the power source 105.

[0112] The systems 100, 100' of Figures 1A and 1B may be implemented as one of two broad categories of system, each in accordance with the present invention: a heated tobacco (HT) system or an e-cigarette system. A description of each category of system follows.

[0113] Figures 3A and 3B illustrate a heated-tobacco (HT) smoking substitute system 200. The system 200 is an example of the systems 100, 100' described in relation to Figures 2A or 2B. System 200 includes an HT device 201 and an HT consumable 202. The description of Figures 2A and 2B above is applicable to the system 200 of Figures 3A and 3B, and will thus not be repeated.

[0114] The device 201 and the consumable 202 are configured such that the consumable 202 can be engaged with the device 201. Figure 3A shows the device 201 and the consumable 202 in an engaged state, whilst Figure 3B shows the device 201 and the consumable 202 in a disengaged state.

[0115] The device 201 comprises a body 209 and cap 210. In use the cap 210 is engaged at an end of the body 209. Although not apparent from the figures, the cap 210 is moveable relative to the body 209. In particular, the cap 210 is slideable and can slide along a longitudinal axis of the body 209.

[0116] The device 201 comprises an output means (forming part of the UI of the device 201) in the form of a plurality of light-emitting diodes (LEDs) 211 arranged linearly along the longitudinal axis of the device 201 and on an outer surface of the body 209 of the device 201. A button 212 is also arranged on an outer surface of the body 209 of the device 201 and is axially spaced (i.e. along the longitudinal axis) from the plurality of LEDs 211.

[0117] Figure 3C show a detailed section view of the consumable 202 of the system 200. The consumable 202 generally resembles a cigarette. In that respect, the consumable 202 has a generally cylindrical form with a diameter of 7 mm and an axial length of 70 mm. The consumable 202 comprises an aerosol forming substrate 213, a terminal filter element 214, an upstream filter element 215 and a spacer element 216. In other embodiments, the consumable may further comprise a cooling element. A cooling element may exchange heat with va-

pour that is formed by the aerosol-forming substrate 213 in order to cool the vapour so as to facilitate condensation of the vapour.

[0118] The aerosol-forming substrate 213 is substantially cylindrical and is located at an upstream end 217 of the consumable 202, and comprises the aerosol former of the system 200. In that respect, the aerosol forming substrate 213 is configured to be heated by the device 201 to release a vapour. The released vapour is subsequently entrained in an airflow flowing through the aerosol-forming substrate 213. The airflow is produced by the action of the user drawing on a downstream 218 (i.e. terminal or mouth) end of the consumable 202.

[0119] In the present embodiment, the aerosol forming substrate 213 comprises tobacco material that may, for example, include any suitable parts of the tobacco plant (e.g. leaves, stems, roots, bark, seeds and flowers). The tobacco may comprise one or more of leaf tobacco, stem tobacco, tobacco powder, tobacco dust, tobacco derivatives, expanded tobacco, homogenised tobacco, shredded tobacco, extruded tobacco, cut rag tobacco and/or reconstituted tobacco (e.g. slurry recon or paper recon). For example, the aerosol-forming substrate 213 may comprise a gathered sheet of homogenised (e.g. paper/slurry recon) tobacco or gathered shreds/strips formed from such a sheet.

[0120] In order to generate an aerosol, the aerosol forming substrate 213 comprises at least one volatile compound that is intended to be vaporised/aerosolised and that may provide the user with a recreational and/or medicinal effect when inhaled. The aerosol-forming substrate 213 may further comprise one or more additives. For example, such additives may be in the form of humectants (e.g. propylene glycol and/or vegetable glycerine), flavourants, fillers, aqueous/non-aqueous solvents and/or binders.

[0121] The terminal filter element 214 is also substantially cylindrical and is located downstream of the aerosol forming substrate 213 at the downstream end 218 of the consumable 202. The terminal filter element 214 is in the form of a hollow bore filter element having a bore 219 (e.g. for airflow) formed therethrough. The diameter of the bore 219 is 2 mm. The terminal filter element 214 is formed of a porous (e.g. monoacetate) filter material. As set forth above, the downstream end 218 of the consumable 202 (i.e. where the terminal filter 214 is located) forms a mouthpiece portion of the consumable 202 upon which the user draws. Airflow is drawn from the upstream end 217, through the components of the consumable 202, and out of the downstream end 218. The airflow is driven by the user drawing on the downstream end 218 (i.e. the mouthpiece portion) of the consumable 202.

[0122] The upstream filter element 215 is located axially adjacent to the aerosol-forming substrate 213, between the aerosol-forming substrate 213 and the terminal filter element 214. Like the terminal filter 214, the upstream filter element 215 is in the form of a hollow bore filter element, such that it has a bore 220 extending axially

therethrough. In this way, the upstream filter 215 may act as an airflow restrictor. The upstream filter element 215 is formed of a porous (e.g. monoacetate) filter material. The bore 220 of the upstream filter element 215 has a larger diameter (3 mm) than the terminal filter element 214.

[0123] The spacer 216 is in the form of a cardboard tube, which defines a cavity or chamber between the upstream filter element 215 and the terminal filter element 214. The spacer 216 acts to allow both cooling and mixing of the vapour/aerosol from the aerosol-forming substrate 213. The spacer has an external diameter of 7 mm and an axial length of 14mm.

[0124] Although not apparent from the figure, the aerosol-forming substrate 213, upstream filter 215 and spacer 216 are circumscribed by a paper wrapping layer. The terminal filter 214 is circumscribed by a tipping layer that also circumscribes a portion of the paper wrapping layer (so as to connect the terminal filter 214 to the remaining components of the consumable 202). The upstream filter 215 and terminal filter 214 are circumscribed by further wrapping layers in the form of plug wraps.

[0125] Returning now to the device 201, Figure 3D illustrates a detailed view of the end of the device 201 that is configured to engage with the consumable 202. The cap 210 of the device 201 includes an opening 221 to an internal cavity 222 (more apparent from Figure 3D) defined by the cap 210. The opening 221 and the cavity 222 are formed so as to receive at least a portion of the consumable 202. During engagement of the consumable 202 with the device 201, a portion of the consumable 202 is received through the opening 221 and into the cavity 222. After engagement (see Figure 3B), the downstream end 218 of the consumable 202 protrudes from the opening 221 and thus also protrudes from the device 201. The opening 221 includes laterally disposed notches 226. When a consumable 202 is received in the opening 221, these notches 226 remain open and could, for example, be used for retaining a cover in order to cover the end of the device 201.

[0126] Figure 3E shows a cross section through a central longitudinal plane through the device 201. The device 201 is shown with the consumable 202 engaged therewith.

[0127] The device 201 comprises a heater 204 comprising heating element 223. The heater 204 forms part of the body 209 of the device 201 and is rigidly mounted to the body 209. In the illustrated embodiment, the heater 204 is a rod heater with a heating element 223 having a circular transverse profile. In other embodiments the heater may be in the form of a blade heater (e.g. heating element with a rectangular transverse profile) or a tube heater (e.g. heating element with a tubular form).

[0128] The heating element 223 of the heater 204 projects from an internal base of the cavity 222 along a longitudinal axis towards the opening 221. As is apparent from the figure, the length (i.e. along the longitudinal axis) of the heating element is less than a depth of the cavity

222. In this way, the heating element 223 does not protrude from or extend beyond the opening 221.

[0129] When the consumable 202 is received in the cavity 222 (as is shown in Figure 3E), the heating element 223 penetrates the aerosol-forming substrate 213 of the consumable 202. In particular, the heating element 223 extends for nearly the entire axial length of the aerosol-forming substrate 213 when inserted therein. Thus, when the heater 204 is activated, heat is transferred radially from an outer circumferential surface the heating element 223 to the aerosol-forming substrate 213.

[0130] The device 201 further comprises an electronics cavity 224. A power source, in the form of a rechargeable battery 205 (a lithium ion battery), is located in electronics cavity 224.

[0131] The device 201 includes a connector (i.e. forming part of an IO module of the device 201) in the form of a USB port 206. The connector may alternatively be, for example, a micro-USB port or a USB-C port for examples. The USB port 206 may be used to recharge the rechargeable battery 205.

[0132] The device 201 includes a controller (not shown) located in the electronics cavity 224. The controller comprises a microcontroller mounted on a printed circuit board (PCB). The USB port 206 is also connected to the controller 208 (i.e. connected to the PCB and microcontroller).

[0133] The controller 208 is configured to control at least one function of the device 202. For example, the controller 208 is configured to control the operation of the heater 204. Such control of the operation of the heater 204 may be accomplished by the controller toggling the electrical connection of the rechargeable battery 205 to the heater 204. For example, the controller 208 is configured to control the heater 204 in response to a user depressing the button 212. Depressing the button 212 may cause the controller to allow a voltage (from the rechargeable battery 205) to be applied to the heater 204 (so as to cause the heating element 223 to be heated).

[0134] The controller is also configured to control the LEDs 211 in response to (e.g. a detected) a condition of the device 201 or the consumable 202. For example, the controller may control the LEDs to indicate whether the device 201 is in an on state or an off state (e.g. one or more of the LEDs may be illuminated by the controller when the device is in an on state).

[0135] The device 201 comprises a further input means (i.e. in addition to the button 212) in the form of a puff sensor 225. The puff sensor 225 is configured to detect a user drawing (i.e. inhaling) at the downstream end 218 of the consumable 202. The puff sensor 225 may, for example, be in the form of a pressure sensor, flowmeter or a microphone. The puff sensor 225 is operatively connected to the controller 208 in the electronics cavity 224, such that a signal from the puff sensor 225, indicative of a puff state (i.e. drawing or not drawing), forms an input to the controller 208 (and can thus be responded to by the controller 208).

[0136] Figures 4A and 4B illustrate an e-cigarette smoking substitute system 300. The system 300 is an example of the systems 100, 100' of Figures 2A and 2B and comprises an e-cigarette device 301 and an e-cigarette consumable 302. The description of Figures 2A and 2B above is applicable to the system of Figures 4A and 4B, and will not be repeated.

[0137] The device 301 and the consumable 302 are configured such that the consumable 302 can be engaged with the device 301. Figure 4A shows the device 301 and the consumable 302 in an engaged state, whilst Figure 4B shows the device 301 and the consumable 302 in a disengaged state. During engagement a portion of the consumable 302 is received in a cavity 322 of the device 301. The consumable 302 is retained in the device 301 via an interference fit (although in other embodiments, the device and consumable could be engaged by screwing one onto (or onto) the other, through a bayonet fitting, or by way of a snap engagement mechanism).

[0138] The consumable 302 includes a tank 327. The tank 327 defines a reservoir for the storage of an aerosol-former, which in this embodiment, is in the form of e-liquid.

[0139] In this present embodiment, the consumable 302 is a "single-use" consumable. That is, upon exhausting the e-liquid in the tank 327, the intention is that the user disposes of the whole consumable 302. In other embodiments, the e-liquid (i.e. aerosol former) may be the only part of the system that is truly "single-use". In such embodiments, the tank may be refillable with e-liquid or the e-liquid may be stored in a non-consumable component of the system. For example, the e-liquid may be stored in a tank located in the device or stored in another component that is itself not single-use (e.g. a refillable cartomizer).

[0140] In the illustrated system 300, a heater 304 is located in the consumable 302 and is configured to heat and vaporise the e-liquid (stored in the tank 327). Although not shown, the heater 304 comprises a porous wick and a resistive heating element. The porous wick conveys e-liquid from the tank 327 to the heating element. The heating element is a heating filament that is helically wound around a portion of the porous wick, such that when the heating element is heated (e.g. by the action of electrical current passing through the heating element), heat is transferred from the heating element to the e-liquid conveyed by the wick. This transfer of heat vaporises the e-liquid and the resultant vapour is entrained in an airflow passing through the consumable 302 (i.e. driven by a user drawing on a downstream end 318 of the consumable 302). Between the vaporisation point at the coil and the downstream end 318 (i.e. the mouth end), the vapour condenses into an aerosol, and is subsequently inhaled by the user.

[0141] Like the previously described embodiment, the device 301 comprises a power source in the form of a rechargeable battery (not shown) and a connector in the form of a USB port (not shown). The device 301 further

comprises controller (also not shown). The rechargeable battery, connector and controller are similar (and operate in a similar manner) to the corresponding components of the embodiment described above with respect to Figure 2A to 2E.

[0142] The consumable 302 includes a pair of heater electrical contacts 328 disposed on a device-facing end surface of the consumable 302. The heater electrical contacts 328 are electrically connected to the heater 304 in the consumable 302, such that a voltage applied across the heater electrical contacts 328 generally corresponds to a voltage applied across the resistive heating element of the heater 304.

[0143] When the consumable 302 is engaged with the device 301, the heater electrical contacts 328 are brought into electrical contact with corresponding device electrical contacts (not shown) on the device 301. The device electrical contacts are electrically connected (directly or indirectly) to the rechargeable battery. The controller may thus be configured to control the voltage applied across the device electrical contacts from the rechargeable battery. By controlling the voltage applied across the device electrical contacts, the voltage applied to the heater 304 is correspondingly controlled.

[0144] The device 301 includes an output means (forming part of the UI of the system 300) in the form of a single light-emitting diode ("LED") 311. The LED 311 is operatively connected to the controller, such that controller can control the illumination of the LED 311. The controller is configured to illuminate the LED when then the heater 304 is active.

[0145] The device 301 also includes an input means in the form of a puff sensor (not shown). The puff sensor is the same as that described above with respect to the embodiment shown in Figure 3A to 3E.

[0146] The features disclosed in the foregoing description, or in the following claims, or in the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for obtaining the disclosed results, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

[0147] While the invention has been described in conjunction with the exemplary embodiments described above, many equivalent modifications and variations will be apparent to those skilled in the art when given this disclosure. Accordingly, the exemplary embodiments of the invention set forth above are considered to be illustrative and not limiting. Various changes to the described embodiments may be made without departing from the spirit and scope of the invention.

[0148] For the avoidance of any doubt, any theoretical explanations provided herein are provided for the purposes of improving the understanding of a reader. The inventors do not wish to be bound by any of these theoretical explanations.

[0149] Any section headings used herein are for or-

ganizational purposes only and are not to be construed as limiting the subject matter described.

[0150] Throughout this specification, including the claims which follow, unless the context requires otherwise, the words "have", "comprise", and "include", and variations such as "having", "comprises", "comprising", and "including" will be understood to imply the inclusion of a stated integer or step or group of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

[0151] It must be noted that, as used in the specification and the appended claims, the singular forms "a," "an," and "the" include plural referents unless the context clearly dictates otherwise. Ranges may be expressed herein as from "about" one particular value, and/or to "about" another particular value. When such a range is expressed, another embodiment includes from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by the use of the antecedent "about," it will be understood that the particular value forms another embodiment. The term "about" in relation to a numerical value is optional and means, for example, +/- 10%.

[0152] The words "preferred" and "preferably" are used herein refer to embodiments of the invention that may provide certain benefits under some circumstances. It is to be appreciated, however, that other embodiments may also be preferred under the same or different circumstances. The recitation of one or more preferred embodiments therefore does not mean or imply that other embodiments are not useful, and is not intended to exclude other embodiments from the scope of the disclosure, or from the scope of the claims.

Claims

1. A packaging for a smoking substitute device comprising:

a cover; and
a tray comprising a cavity for receiving the smoking substitute system, wherein the tray is configured to be peripherally received in the cover and thereby defining an airflow channel therebetween;
wherein the airflow channel is configured to provide fluid communication between the cavity and an external environment.

2. A packaging according to claim 1, wherein at least a portion of a sidewall of the tray is configured to space from an adjacent portion of a sidewall of the cover when said tray is received in the cover, so as to define the air flow channel.

3. A packaging according to claim 2, wherein the sidewalls of the cover and the tray are configured to

space from each other by one or more protrusions extending from respective sidewalls of the cover and/or the tray, wherein said air flow channel is defined around the one or more protrusions.

4. A packaging according to any one of the preceding claims, wherein the sidewalls of the cover and the tray are configured to space from each other by one or more grooves formed on respective sidewalls of the cover and/or the tray, wherein said air flow channel is defined along the one or more grooves.

5. A packaging according to claim 4, wherein the one or more sidewalls of the cover and/or the tray comprises a corrugated surface having the grooves defined thereon.

6. A packaging according to any one of the preceding claims, wherein one or more corners of the tray is truncated to define the air flow channel.

7. A packaging according to any one of the preceding claims, wherein the airflow channel may comprise one or more vents opened on respective sidewalls of the cover and/or the tray.

8. A packaging according to claim 7, wherein the one or more vents each comprises an air permeable valve or membrane for preventing liquid ingress to the cavity.

9. A packaging according to claim 8, wherein the one or more vents each comprises a one way valve to allow an airflow to enter into the cavity.

10. A packaging according to any one of the claims 7 to 9, wherein the one or more vents opened on a sidewall of the cover each aligns with corresponding one or more vents opened on the tray when the tray is received in the cover.

11. A smoking substitute system comprising:

the packaging as claimed in any one of the claims 1 to 10; and
a smoking substitute device, the smoking substitute device is configured to be received in the cavity of the packaging.

12. A smoking substitute product according to claim 11, wherein the smoking substitute system further comprises an aerosol-forming article for use with the smoking substitute device.




FIG 1A




FIG 1 B




FIG 2A




FIG 2B




FIG 3A





FIG 3B






FIG 3D




FIG 3E




FIG 4A




FIG 4B



EUROPEAN SEARCH REPORT

 Application Number
 EP 19 02 0211

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 2 809 775 A (WHITE ROGER L) 15 October 1957 (1957-10-15) * column 1, line 15 - column 5, line 40 * * figures 1-9 *	1-5,7-12	INV. B65D5/42 ADD. B65D5/68
X	US 2006/213958 A1 (VALENZUELA JUAN Z [CL] ET AL) 28 September 2006 (2006-09-28) * paragraphs [0001] - [0060] * * figures 1-11 *	1,2,4,5, 7-12	
X	GB 832 987 A (FIELD SONS & CO LTD) 21 April 1960 (1960-04-21) * page 1, line 9 - page 3, line 10 * * figures 1-4 *	1,2,4-9, 11,12	
X	GB 729 657 A (THOMPSON AND NORRIS MFG COMPAN) 11 May 1955 (1955-05-11) * page 1, line 9 - page 6, line 8 * * figures 1-9 *	1,2,4-12	
X	GB 2 220 195 A (ST REGIS PACKAGING LTD [GB]) 4 January 1990 (1990-01-04) * pages 1-7 * * figures 1-6 *	1,4,5, 7-12	TECHNICAL FIELDS SEARCHED (IPC) B65D
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 24 June 2019	Examiner Duc, Emmanuel
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 19 02 0211

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

24-06-2019

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2809775 A	15-10-1957	NONE	
US 2006213958 A1	28-09-2006	AR 053175 A1 AU 2006227685 A1 BR PI0611559 A2 CA 2600880 A1 CN 101203433 A EP 1858764 A2 NZ 561611 A US 2006213958 A1 WO 2006101946 A2	25-04-2007 28-09-2006 21-09-2010 28-09-2006 18-06-2008 28-11-2007 27-08-2010 28-09-2006 28-09-2006
GB 832987 A	21-04-1960	NONE	
GB 729657 A	11-05-1955	NONE	
GB 2220195 A	04-01-1990	NONE	