



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
30.09.2020 Bulletin 2020/40

(21) Application number: **18879636.1**

(22) Date of filing: **25.10.2018**

(51) Int Cl.:
G01N 35/00 (2006.01) **G01N 35/08** (2006.01)
G01N 31/22 (2006.01) **G01N 21/78** (2006.01)
B01L 3/00 (2006.01) **G01N 21/75** (2006.01)
G01N 21/77 (2006.01)

(86) International application number:
PCT/KR2018/012738

(87) International publication number:
WO 2019/098563 (23.05.2019 Gazette 2019/21)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
KH MA MD TN

(30) Priority: **20.11.2017 KR 20170154395**
10.05.2018 KR 20180053639

(71) Applicant: **LG Chem, Ltd.**
Seoul 07336 (KR)


(72) Inventors:
• **PARK, Byung Hyun**
Daejeon 34122 (KR)
• **KIM, Byoung Hyoun**
Daejeon 34122 (KR)
• **KIM, Dong Hyun**
Daejeon 34122 (KR)
• **HAN, Su Youn**
Daejeon 34122 (KR)

(74) Representative: **Goddard, Heinz J.**
Boehmert & Boehmert
Anwaltpartnerschaft mbB
Pettenkoferstrasse 22
80336 München (DE)

(54) **DEVICE AND METHOD FOR QUALITATIVE AND QUANTITATIVE ANALYSIS OF HEAVY METALS UTILIZING ROTARY DISC SYSTEM**

(57) The present invention relates to a device and a method for qualitative analysis and quantitative analysis of heavy metals and, more particularly, to a device and a method for qualitative analysis and quantitative analysis of heavy metals using a rotatable disk system.

[FIG. 1D]



DescriptionBACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] This application claims priority to Korean Patent Application No. 10-2017-0154395, filed on November 20, 2017, and Korean Patent Application No. 10-2018-0053639, filed on May 10, 2018, the disclosures of which are incorporated herein by reference.

[0002] The present invention relates to a device and a method for qualitative analysis and quantitative analysis of heavy metals and, more particularly, to a device and a method for qualitative analysis and quantitative analysis of heavy metals using a rotatable disk system.

2. Description of the Related Art

[0003] In general, the most widely used method for detecting heavy metals is spectroscopic analysis such as inductively coupled plasma mass spectrometry or atomic absorption/emission spectrometry. Mass spectrometry and spectroscopy based heavy metal detection methods are accurate and have high detection limits, but they are expensive and require skilled analytical techniques, making it difficult to perform a heavy metal analysis in the field quickly and simply.

[0004] It is required to develop economical and cost-effective color development based heavy metal analysis system for replacing expensive mass spectrometry and spectroscopy based heavy metal analysis equipment, and development of miniaturized analysis system that can be conveniently applied in the field is required. In addition, it is required to develop a system capable of qualitative analysis as well as qualitative analysis of heavy metals while shortening analysis time by performing simultaneous detection of multiple heavy metals.

[0005] In addition, in the case where a plurality of heavy metals exist in one fluid sample, it is required to implement a method for performing the analysis more easily and quickly

[0006] In addition, when a fluid sample containing heavy metals is developed in a detection unit and quantitative analysis is performed according to a development distance, a method for performing a more accurate quantitative analysis is required. Further, there is a need for a method for performing the movement of the fluid sample more uniformly when the fluid sample is developed in the detection unit and preventing the moisture condensation phenomenon in the detection unit.

SUMMARY OF THE INVENTION

[0007] The present invention pertains to a device for qualitative analysis and quantitative analysis comprising a rotatable platform and a plurality of microfluidic structures disposed radially and symmetrically on the rotatable platform. Each of the plurality of the microfluidic structures comprises a sample injection unit into which a fluid sample containing heavy metals is injected; a microfluidic channel (a siphon channel) which is a passage through which the sample can be moved to a detection unit and connects the sample injection unit to the one end of the detection unit; the detection unit comprising a plurality of detection members, which is coated with an organic substance capable of causing the color development reaction with the heavy metals of the sample; and a ruler for measuring the color developed distance. Each of the plurality of the microfluidic structures may receive different kinds of samples. The rotation of the device is controlled so that the sample moves from the sample injection unit to the microfluidic channel and then to the detection unit, and the qualitative analysis through the color development reaction of the heavy metals in the detection unit and the quantitative analysis through the measurement of the color developed distance may be possible.

[0008] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, each of the plurality of the detection members may be coated with respective different reagents.

[0009] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, each of the plurality of the detection members may comprise a plurality of sections coated with organic ligands of respective different concentrations.

[0010] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the detection unit may comprise a reservoir area which connects each one end of the plurality of the detection members with the microfluidic channel.

[0011] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, each of the detection members comprises a plurality of sections coated with organic ligands of respective different concentrations, and the concentration of the organic ligand coated in the section located i-th from the reservoir area may be lower than the concentration of the organic ligand coated in the section located i-1-th from the reservoir area, wherein i may be a natural number from 1 to n.

[0012] Further, the device for qualitative analysis and quantitative analysis according to the present invention further comprises an air circulation channel connecting between the sample injection unit and the other end of the detection unit, wherein the air circulation channel can increase the rate of evaporation of the fluid sample in the detection unit and prevent moisture condensation phenomenon in the detection unit.

[0013] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the sample injection unit may include a space capable of receiving the sample and an opening through which the sample can be injected.

[0014] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the control of the rotation of the device can be accomplished by rotating the device firstly and then stopping so that the sample injected into the sample injection unit is moved to the microfluidic channel; rotating the device secondarily so that the sample moved to the microfluidic channel is moved to the reservoir area; and stopping the device so that the sample moved to the reservoir area is developed in the detection unit.

[0015] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the microfluidic channel may include a portion of a "U" shaped tube so that the sample can be received within the microfluidic channel after the first rotation and before the second rotation of the device.

[0016] Also, in the device for qualitative analysis and quantitative analysis according to the present invention, the first rotation may be performed at 2000 to less than 4000 RPM for 5 to 20 seconds and the second rotation may be performed at 4000 to 6000 RPM for 3 to 10 seconds.

[0017] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the rotatable platform is a circular disk and may have a diameter of 12 cm to 20 cm.

[0018] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the heavy metals that may be included in the sample may comprise Fe^{2+} , Zn^{2+} , Hg^{2+} , Cr^{6+} , Ni^{2+} , or Cu^{2+} .

[0019] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the organic material previously applied to the detection unit may comprise any one selected from the group consisting of dimethylglyoxime, bathophenanthroline, dithiooxamide, dithizone, diphenylcarbazide and 1-(2-pyridylazo)-2-naphthol.

[0020] Further, the present invention pertains to an analytic method of a fluid sample containing heavy metals by using the qualitative analysis and quantitative analysis device according to the present invention. The analytic method comprises: (S1) injecting the sample into the sample injection unit; (S2) controlling the rotation of the device; and (S3) performing at least one of qualitative analysis and quantitative analysis of the sample developed in the detection unit.

[0021] Further, in the analytic method of a fluid sample containing heavy metals according to the present invention, the injection of the sample into the sample injection unit of the step (S1) may comprise injecting the fluid sample containing different kinds of the heavy metals into each of the plurality of the microfluidic structures, or injecting the fluid sample containing same kinds of the heavy metals of varying concentrations into each of the plurality of the microfluidic structures.

[0022] Further, in the analytic method of a fluid sample containing heavy metals according to the present invention, the controlling of the rotation of the device of the step (S2) may comprise (S2-1) rotating the device firstly and then stopping so that the sample injected into the sample injection unit is moved to the microfluidic channel; (S2-2) rotating the device secondarily so that the sample moved to the microfluidic channel is moved to the reservoir area; and (S2-3) stopping the rotation of the device so that the sample moved to the reservoir area is developed in the detection unit.

[0023] Further, in the analytic method of a fluid sample containing heavy metals according to the present invention, the performance of at least one of qualitative analysis and quantitative analysis of the sample of the step (S3) may comprise performing at least one of (S3-1) qualitative analysis through the color development reaction of the sample developed in the detection unit and (S3-2) quantitative analysis through the measurement of the color developed distance.

EFFECT OF THE INVENTION

[0024] According to the device for qualitative analysis and quantitative analysis and the analysis method of the sample using the same according to one embodiment of the present invention, the increase of the detection limit of heavy metals through the control of the automated fluidic control and the control of the torque and capillary force is possible. It is possible to improve the detection limit of heavy metal ions by the torque control. That is, it is possible to improve the detection limit by controlling the color development reaction time and the colored area via adjustment of the centrifugal force and the capillary force by control of the rotation of the device.

[0025] According to the device for qualitative analysis and quantitative analysis and the analysis method of the sample using the same according to one embodiment of the present invention, qualitative analysis and quantitative analysis of several heavy metals can be performed with one device. According to the present invention, economical and rapid multi-metal qualitative/quantitative analysis is possible. It is more economical than conventional expensive spectroscopy or mass spectrometry based heavy metal detector and can shorten analysis time. In addition, the configurations for qualitative analysis and quantitative analysis can be integrated into one miniaturized device, and can be applied quickly and conveniently in the field where qualitative/quantitative analysis of heavy metals is required.

[0026] In addition, since the channel (a microfluidic channel) and the detection unit are all patterned in one device, the fabrication of the device for qualitative analysis and quantitative analysis is simple.

[0027] In addition, in the device for qualitative analysis and quantitative analysis according to the present invention, even when multiple heavy metals are present in one fluid sample, the analysis can be performed more simply and quickly

[0028] In addition, it is possible to improve the accuracy of the measurement even in the quantitative analysis of heavy metals contained in the fluid sample, by coating each of the detection members with organic ligands with a concentration gradient in place of coating with the same concentration of the organic ligands throughout each of the detection members.

[0029] Further, according to the device for qualitative analysis and quantitative analysis and the analysis method of the sample using the qualitative analysis and quantitative analysis device according to one embodiment of the present invention, the air circulation channel is provided so that the moisture condensation in the detection unit can be prevented when the fluid sample is developed in the detection unit and the reservoir area is provided at the end of the microfluidic channel so that one end of the detection unit is located in the reservoir area, and thus the fluid sample can move more uniformly when the fluid sample is developed in the detection unit.

BRIEF DESCRIPTION OF THE DRAWINGS

[0030]

FIG. 1A shows a device for qualitative analysis and quantitative analysis according to one embodiment of the present invention, and FIGS. 1B and 1C show microfluidic structures of the device for qualitative analysis and quantitative analysis of FIG. 1A.

FIG. 1D shows a device for qualitative analysis and quantitative analysis according to another embodiment of the present invention, and FIGS. 1E and 1F show microfluidic structures of the device for qualitative analysis and quantitative analysis of FIG. 1D.

FIG. 1G shows a device for qualitative analysis and quantitative analysis according to another embodiment of the present invention, and FIGS. 1H and 1I show microfluidic structures of the device for qualitative analysis and quantitative analysis of FIG. 1G.

FIG. 2A illustrates a device for qualitative analysis and quantitative analysis according to another embodiment of the present invention, and FIG. 2B shows microfluidic structures of the device for qualitative analysis and quantitative analysis of FIG. 2A.

FIGS. 3A to 3C show each layer of a rotatable platform comprising microfluidic structures of the device for qualitative analysis and quantitative analysis according to FIGS. 1A, 1D and 1G, respectively.

FIGS. 4A to 4D show each layer of a rotatable platform comprising microfluidic structures of the device for qualitative analysis and quantitative analysis according to FIG. 2A.

FIG. 5 shows an example of a color development reaction between heavy metal ions and organic complexing agents.

FIG. 6 shows an example of simultaneous qualitative analysis of heavy metals using the device for qualitative analysis and quantitative analysis according to the present invention.

FIGS. 7A and 7B show examples of quantitative analysis of heavy metals using the device for qualitative analysis and quantitative analysis according to the present invention.

FIG. 8 shows a flowchart of a method of analyzing a sample using the device for qualitative analysis and quantitative analysis according to the present invention.

FIG. 9 shows a system for qualitative analysis and quantitative analysis that includes and can rotate the device for qualitative analysis and quantitative analysis according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0031] In the device for qualitative analysis and quantitative analysis comprising a rotatable platform and a plurality of microfluidic structures disposed radially and symmetrically on the rotatable platform according to present invention, each of the plurality of the microfluidic structures comprises a sample injection unit into which a fluid sample containing heavy metals is injected; a microfluidic channel which is a passage through which the sample can be moved to a detection unit and connects the sample injection unit to the one end of the detection unit; the detection unit comprising a plurality of detection members, which is coated with an organic substance capable of causing the color development reaction with the heavy metals of the sample; and a ruler for measuring the color developed distance. Each of the plurality of the microfluidic structures may receive different kinds of samples. The rotation of the device is controlled so that the sample moves from the sample injection unit to the microfluidic channel and then to the detection unit, and the qualitative analysis through the color development reaction of the heavy metals in the detection unit and the quantitative analysis through the measurement of the color developed distance may be possible.

[0032] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, each

of the plurality of detection members may be coated with respective different reagents.

[0033] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, each of the detection members may comprise a plurality of sections coated with organic ligands of respective different concentrations.

[0034] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the detection unit may comprise a reservoir area which connects each one end of the plurality of detection members with the microfluidic channel.

[0035] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the development area comprises a plurality of sections coated with organic ligands of respective different concentrations, and the concentration of the organic ligand coated in the section located i -th from the reservoir area may be lower than the concentration of the organic ligand coated in the section located $i-1$ -th from the reservoir area, wherein i may be a natural number from 1 to n . Further, the device for qualitative analysis and quantitative analysis according to the present invention further comprises an air circulation channel connecting between the sample injection unit and the other end of the detection unit, wherein the air circulation channel can increase the rate of evaporation of the fluid sample in the detection unit and prevent moisture condensation phenomenon in the detection unit.

[0036] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the sample injection unit may include a space capable of receiving the sample and an opening through which the sample can be injected.

[0037] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the control of the rotation of the device can be accomplished by rotating the device firstly and then stopping so that the sample injected into the sample injection unit is moved to the microfluidic channel; rotating the device secondarily so that the sample moved to the microfluidic channel is moved to the reservoir area; and stopping the device so that sample moved to the reservoir area is developed in the detection unit.

[0038] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the microfluidic channel may include a portion of a "U" shaped tube so that the sample can be received within the microfluidic channel after the first rotation and before the second rotation of the device.

[0039] Also, in the device for qualitative analysis and quantitative analysis according to the present invention, the first rotation may be performed at 2000 to 4000 RPM for 5 to 20 seconds and the second rotation may be performed at 4000 to 6000 RPM for 3 to 10 seconds.

[0040] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the rotatable platform is a circular disk and may have a diameter of 12 cm to 20 cm.

[0041] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the heavy metals that may be included in the sample may comprise Fe^{2+} , Zn^{2+} , Hg^{2+} , Cr^{6+} , Ni^{2+} , or Cu^{2+} .

[0042] Further, in the device for qualitative analysis and quantitative analysis according to the present invention, the organic material previously applied to the detection unit may comprise any one selected from the group consisting of dimethylglyoxime, bathophenanthroline, dithiooxamide, dithizone, diphenylcarbazide and 1-(2-pyridylazo)-2-naphthol.

[0043] Further, in the analytic method of a fluid sample containing heavy metals by using the qualitative analysis and quantitative analysis device according to the present invention, the method comprises: (S1) injecting the sample into the sample injection unit; (S2) controlling the rotation of the device; and (S3) performing at least one of qualitative analysis and quantitative analysis of the sample developed in the detection unit.

[0044] Further, in the analytic method of a fluid sample containing heavy metals according to the present invention, the injection of the sample into the sample injection unit of the step (S1) may comprise injecting the fluid sample containing different kinds of the heavy metals into each of the plurality of the microfluidic structures, or injecting the fluid sample containing same kinds of the heavy metals of varying concentrations into each of the plurality of the microfluidic structures.

[0045] Further, in the analytic method of a fluid sample containing heavy metals according to the present invention, the controlling of the rotation of the device of the step (S2) may comprise (S2-1) rotating the device firstly and then stopping so that the sample injected into the sample injection unit is moved to the microfluidic channel; (S2-2) rotating the device secondarily so that the sample moved to the microfluidic channel is moved to the reservoir area; and (S2-3) stopping the rotation of the device so that the sample moved to the reservoir area is developed in the detection unit.

[0046] Further, in the analytic method of a fluid sample containing heavy metals according to the present invention, the performance of at least one of qualitative analysis and quantitative analysis of the sample of the step (S3) may comprise performing at least one of (S3-1) qualitative analysis through the color development reaction of the sample developed in the detection unit and (S3-2) quantitative analysis through the measurement of the color developed distance.

[0047] Hereinafter, the device and the method for qualitative analysis and quantitative analysis of heavy metals using a rotatable disk system according to the present invention will be described in detail. The accompanying drawings, which are included to provide a further understanding of the invention, illustrate embodiments of the present invention and the technical scope of the present invention is not limited thereto.

[0048] In addition, the same or corresponding components are denoted by the same reference numbers regardless

of the figures, and redundant description thereof will be omitted. For convenience of explanation, the size and shape of each constituent member shown may be exaggerated or reduced.

[0049] FIG. 1A shows a device for qualitative analysis and quantitative analysis (1) according to one embodiment of the present invention, and FIG. 1B shows microfluidic structures (20) of the rotatable disk system of FIG. 1A.

[0050] First, referring FIG. 1A, the device for qualitative analysis and quantitative analysis (1) includes the rotatable platform (10) and a plurality of the microfluidic structures (20) provided on the rotatable platform (10). The rotatable platform (10) may be, for example, a circular disk, and the size may be, for example, in one embodiment, 12 cm to 20 cm in diameter, and in another embodiment, less than 12 cm in diameter.

[0051] The rotatable platform (10) includes the plurality of the microfluidic structures (20) which are positioned radially and symmetrically on the rotatable platform (10). For example, the plurality of the microfluidic structures (20) may comprise two, three, four, six, eight, ten, or twelve of the structures. In FIG. 1A, three microfluidic structures (20) are shown disposed on the rotatable platform (10).

[0052] Referring to FIG. 1B, each microfluidic structure (20) of the plurality of the microfluidic structures (20) is shown. The microfluidic structures (20) include a top layer (see FIG. 3A), a detection unit (120) coated with an organic substance capable of causing a color development reaction with the heavy metals in a fluid sample, and a bottom layer (see FIG. 3A). The top layer includes a sample injection unit (100) into which a fluid sample containing the heavy metals is injected, a microfluidic channel (110) through which the fluid sample can move to the detection unit, a portion where the detection unit (120) can be inserted, and a ruler (130) for measuring the color developed distance. The bottom layer is a pressure-sensitive adhesive layer which is not patterned.

[0053] Each microfluidic structure (20) of the plurality of the microfluidic structures (20) may receive the fluid sample containing different kinds of the heavy metals. The heavy metals that may be included in the fluid sample may include, for example, Fe^{2+} , Zn^{2+} , Hg^{2+} , Cr^{6+} , Ni^{2+} , Cu^{2+} , etc.

[0054] The sample injection unit (100) includes a space for accommodating a fluid sample containing the heavy metals and an opening (100a) through which the fluid sample can be injected into the space. The sample injection unit (100) and one end of the detection unit (120) may be connected to the microfluidic channel (110). Further, the sample injection unit (100) may include a blocking unit (100b) which prevents the sample injected through the opening (100a) from flowing directly into the microfluidic channel (110) and stores the sample in the inner space of the sample injection unit (100) by using drop of the channel. Since the vicinity of the rear end portion (100c) of the sample injection unit (100) where the microfluidic channel (110) is connected to the sample injection unit (100) has, for example, a streamlined shape, when the fluid sample injected into the injection unit (100) moves to the microfluidic channel (110), the resistance of the fluid sample is minimized and all of the fluid sample injected into the sample injection unit (100) is moved to the microfluidic channel (110).

[0055] The microfluidic channel (110) may have a width of 1 mm and a depth of 100 μm . The microfluidic channel (110) may comprise, for example, a portion of a "U" shaped tube. As will be described below, the fluid sample including the heavy metals after the first rotation and before the second rotation of the device for qualitative analysis and quantitative analysis (1) can move along the channel which is a passage through which the fluid sample moves due to the hydrophilicity of the microfluidic channel (110), and as a result, the fluid sample can be accommodated in the microfluidic channel (110).

[0056] The detection unit (120) may be made of a porous hydrophilic material, for example, paper, nitrocellulose, cotton, silica based sol-gel matrix, etc., and may be preferably made of paper.

[0057] Meanwhile, the detection unit (120) comprises a plurality of the detection members (121, 122, 123). Although FIGS. 1A and 1B show one detection unit (120) comprising three detection members (121, 122, 123), the present invention is not limited thereto and the number of the detection members may be adjusted according to various environments in which the present invention is implemented. Each of the plurality of the detection members (121, 122, 123) of the detection unit (120) may be coated with different reagents. These pre-applied reagents each contain a specific organic material (organic ligand) that can cause a color development reaction with the heavy metals in the fluid sample (see FIG. 5 and Table 1). Therefore, when one organic sample injected into the sample injection unit (100) includes a plurality of the heavy metals, the plurality of the heavy metals may be detected in each of the plurality of the detection members (121, 122, 123) coated with each of the different reagents. For example, PAN (1-(2-pyridylazo)-2-naphthol) for detecting Zn^{2+} may be coated in the detection member (121), Bphen (bathophenanthroline) for detecting Fe^{2+} may be coated in the detection member (122), and DMG (dimethylglyoxime) for detecting Ni^{2+} may be coated in the detection member (123).

[0058] Also, the detection unit (120) comprises a reservoir area (124) connecting the microfluidic channel (110) to the plurality of the detection members (121, 122, 123). The reservoir area (124) may or may not be coated with an organic material. The reservoir area (124) is connected to each one end of the plurality of the detection members (121, 122, 123). Further, the microfluidic channel (110) is connected to the reservoir area (124). The fluid sample moved from the sample injection unit (100) to the microfluidic channel (110) during the first rotation of the rotatable platform (10) is moved from the microfluidic channel (110) to the reservoir area (124) of the detection unit (120) connected to the microfluidic channel (110) during the secondary rotation of the rotatable platform (10). At this time, the fluid sample remains in the

reservoir area (124) without being developed into the plurality of the detection members (121, 122, 123) of the detection unit (120) by the centrifugal force due to the rotation. When the secondary rotation of the rotatable platform (10) is stopped, the fluid sample is developed from the reservoir area (124) to each of the plurality of the detection members (121, 122, 123). A more detailed description thereof will be given below with reference to FIG. 8.

[0059] The ruler (130) is positioned alongside of the detection unit (120) in the vicinity of the detection unit (120). The ruler (130) may be, for example, scaled in millimeters (mm). Alternatively, it may be scaled in units of concentration such as ppm, ppb, etc., in addition to the length unit such as mm in the scale unit (130). In the case where the scale is expressed in terms of the concentration unit in the ruler (130), it may be expressed in terms of a concentration unit obtained by substituting the development distance of the relevant heavy metals into a calibration curve (see FIGS. 6A and 6B).

[0060] FIG. 1C shows exemplary dimensions of the microfluidic structures (20) of the rotatable disk system of FIG. 1B. Exemplary dimensions of the microfluidic structures (20) are not limited to those shown in FIG. 1C, but may be modified or changed according to various environments embodied in the present invention.

[0061] FIG. 1D shows a device for qualitative analysis and quantitative analysis (1') according to another embodiment of the present invention, and FIG. 1E shows the microfluidic structures (20') of the rotatable disk system of FIG. 1D.

[0062] Each of the plurality of the detection members (121', 122', 123') of the detection unit (120') is not coated with the organic ligands of the same concentration but coated with organic ligands of different concentrations by providing a concentration gradient in a plurality of (n, where n is a natural number of 2 or more) sections of the detection members (121', 122', 123') as shown in FIG. 1E. The number n of sections may be, for example, 2 or more and 10 or less, or 5 or 6, for example.

[0063] More specifically, upon checking the detection member (121'), the first section (121'₁) closest to the reservoir area (124) is coated with the highest concentration of the organic ligand, and the next adjacent second section (121'₂) is coated with a lower concentration than that of the organic ligand coated in the first section (121'₁). The next third section (121'₃) is coated with a lower concentration than that of the organic ligand coated in the second section (121'₂), and the subsequent sections are also coated with increasingly lower concentrations of the organic ligands. And the n-th section (121'_n) farthest from the reservoir area (124) is coated with the lowest concentration of the organic ligand. That is, the concentration of the organic ligand coated in the i-th section (121'_i) from the reservoir area (124) is lower than that of the organic ligand coated in the (i-1)-th section (121'_{i-1}). Here, i is a natural number from 1 to n.

[0064] The amount of the fluid sample developed from the n-th section (121'_n) farthest to the reservoir area (124) toward the first section (121'₁) closest to the reservoir area (124) increases. According to the present invention, the concentration of the coated organic ligand is increased toward the first section (121'₁) closest to the reservoir area (124) from the n-th section (121'_n) farthest from the reservoir area (124). It is possible to prevent the speed at which the fluid sample is developed at the detection member (121') from being increased faster than the rate at which the organic ligand coated on the detection member (121') reacts with the heavy metals in the fluid sample (color development reaction) so that in the analysis of the heavy metals in the fluid sample, the accuracy of the measurement can be further increased. On the other hand, the detection member (122') and the detection member (123') are also coated with organic ligands with the concentration gradient in the above-described manner with respect to the detection member (121').

[0065] For example, when in order to detect Zn²⁺, PAN (1- (2-pyridylazo)-2-naphthol) as an organic substance is coated on one of the detection members (121', 122', 123') (for example, the detection member (121')). When the number of sections of the detection member is 5, the concentration of the organic ligand coated on each of the first section (121'₁), the second section (121'₂), the third section (121'₃), the fourth section (121'₄) and the fifth section (121'₅) is 50, 35, 20, 5 and 1 mM, respectively.

[0066] Also, for example, when in order to detect Fe²⁺, Bphen (bathophenanthroline) as an organic substance is coated on one of the detection members (121', 122', 123') (for example, the detection member (121')). When the number of sections of the detection member is 5, the concentration of the organic ligand coated on each of the first section (121'₁), the second section (121'₂), the third section (121'₃), the fourth section (121'₄) and the fifth section (121'₅) is 10, 5, 1, 0.5 and 0.1 mM, respectively.

[0067] Further, for example, when in order to detect Ni²⁺, DMG (dimethylglyoxime) as an organic substance is coated on one of the detection members (121', 122', 123') (for example, the detection member (121')). When the number of sections of the detection member is 5, the concentration of the organic ligand coated on each of the first section (121'₁), the second section (121'₂), the third section (121'₃), the fourth section (121'₄) and the fifth section (121'₅) is 50, 10, 5, 1 and 0.5 mM, respectively.

[0068] Also, for example, when in order to detect Cu²⁺, DTO (dithiooxamide) as an organic substance is coated on one of the detection members (121', 122', 123') (for example, the detection member (121')). When the number of sections of the detection member is 5, the concentration of the organic ligand coated on each of the first section (121'₁), the second section (121'₂), the third section (121'₃), the fourth section (121'₄) and the fifth section (121'₅) is 10, 8, 6, 4 and 2 mM, respectively.

[0069] Further, for example, when in order to detect Cr⁶⁺, DCB (diphenylcarbazide) supplemented with 1% H₂SO₄ as

an organic substance is coated on one of the detection members (121', 122', 123') (for example, the detection member (121')). When the number of sections of the detection member is 5, the concentration of the organic ligand coated on each of the first section (121'₁), the second section (121'₂), the third section (121'₃), the fourth section (121'₄) and the fifth section (121'₅) is 20, 10, 5, 2 and 1 mM, respectively.

[0070] Also, for example, when in order to detect Hg²⁺, DTZ (dithizone) as an organic substance is coated on one of the detection members (121', 122', 123') (for example, the detection member (121')). When the number of sections of the detection member is 5, the concentration of the organic ligand coated on each of the first section (121'₁), the second section (121'₂), the third section (121'₃), the fourth section (121'₄) and the fifth section (121'₅) is 50, 25, 10, 5 and 1 mM, respectively.

[0071] FIG. 1F shows exemplary dimensions of the microfluidic structures (20') of the rotatable disk system of FIG. 1D. Exemplary dimensions of the microfluidic structures (20') are not limited to those shown in FIG. 1F, but may be modified or changed according to various environments embodied in the present invention.

[0072] FIG. 1G shows a device for qualitative analysis and quantitative analysis (1'') according to another embodiment of the present invention, and FIG. 1H shows the microfluidic structures (20'') of the rotatable disk system of FIG. 1G. The device for qualitative analysis and quantitative analysis (1'') of FIG. 1H, like the device for qualitative analysis and quantitative analysis (1) of FIG. 1A, comprises the rotatable platform (10) and a plurality of the microfluidic structures (20'') provided in and the rotatable platform (10). The top layer of the rotatable platform (10) includes the sample injection unit (100) into which a fluid sample containing the heavy metals is injected and the microfluidic channel (110) which is a passage through which the fluid sample can move to the detection unit. The portion of the top layer where the detection unit (120'') is positioned may be variously modified and changed so that the detection unit (120'') can be inserted, including a concave portion in conformity with the shape of the detection unit (120''). Also, the depth of the concave portion can be variously modified and changed according to the environment in which the present invention is actually implemented. The bottom layer includes a portion where the detection unit (120'') can be inserted (see FIG. 3C) and a ruler (130) for measuring the color developed distance.

[0073] Meanwhile, the device for qualitative analysis and quantitative analysis (1'') of FIG. 1G comprises an air circulation channel (140) unlike the device for qualitative analysis and quantitative analysis (1, 1') of FIGS. 1A and 1D. The air circulation channel (140) connects between the sample injection unit (100) and the other end of each of the plurality of the detection members (121', 122', 123') of the detection unit (120'). Due to this, the sample injection unit (100), the microfluidic channel (110), the detection unit (120'), the air circulation channel (140), and the sample injection unit (100) are connected to be circulated in order. By introducing the air circulation channel (140), the evaporation rate of the fluid sample of the detection unit (120') may be increased, and the moisture condensation phenomenon in the detection unit (120') may be prevented. On the other hand, with respect to the sample injection unit (100), since the air circulation channel (140) is located at the center of the circular disk-shaped rotatable platform (10) and the microfluidic channel (110) is positioned toward the edge of the rotatable platform (10), when the rotatable platform (10) rotates, the sample of the sample injection unit (100) moves to the microfluidic channel (110) by the centrifugal force and does not move to the air circulation channel (140). Additionally, in order to prevent the possibility of movement, a hole having a depth of about 1 mm and a diameter of about 0.8 mm is drilled at a point where the sample injection unit (100) and the air circulation channel (140) are connected to each other to form a capillary valve operated by an air pressure, thereby preventing the sample from moving from the sample injection unit (100) to the air circulating channel (140).

[0074] FIG. 1I shows exemplary dimensions of the microfluidic structures (20'') of the rotatable disk system of FIG. 1G. Exemplary dimensions of the microfluidic structures (20'') are not limited to those shown in FIG. 1I, but may be modified or changed according to various environments embodied in the present invention.

[0075] FIG. 2A illustrates a device for qualitative analysis and quantitative analysis (1''') according to another embodiment of the present invention, and FIG. 2B shows the microfluidic structures (20''') of the rotatable disk system of FIG. 2A. The device for qualitative analysis and quantitative analysis (1''') of FIG. 2A comprises, like the device for qualitative analysis and quantitative analysis (1) of FIG. 1A, the rotatable platform (10) and a plurality of the microfluidic structures (20''') provided in and the rotatable platform (10). The top layer of the rotatable platform (10) includes the sample injection unit (100) into which a fluid sample containing the heavy metals is injected and the microfluidic channel (110) which is a passage through which the fluid sample can move to the detection unit. The portion of the top layer where the detection unit (120''') is positioned may be variously modified and changed so that the detection unit (120''') can be inserted, including a concave portion in conformity with the shape of the detection unit (120'''). Also, the depth of the concave portion can be variously modified and changed according to the environment in which the present invention is actually implemented. The bottom layer includes a portion where the detection unit (120''') can be inserted (see FIG. 4D) and a ruler (130) for measuring the color developed distance.

[0076] The device for qualitative analysis and quantitative analysis (1''') of FIG. 2A comprises an air circulation channel (140') like the device for qualitative analysis and quantitative analysis (1'') of FIG. 1G. The air circulation channel (140') connects between the sample injection unit (100) and the other end of the detection unit (120''). Due to this, the sample injection unit (100), the microfluidic channel (110), the detection unit (120''), the air circulation channel (140'), and the

sample injection unit (100) are connected to be circulated in order.

[0077] Meanwhile, in the device for qualitative analysis and quantitative analysis (1'') of FIG. 2A, the detection unit (120'') comprises one detection member. Further, the detection unit (120'') does not have different concentrations of the organic ligands in each section unlike in the device for qualitative analysis and quantitative analysis (1, 1') of FIGS. 1D and 1G. Further, in the device for qualitative analysis and quantitative analysis (1'') of FIG. 2A, the entire detection unit (120'') is coated with an organic material capable of causing the color development reaction with the heavy metals of the fluid sample so that the fluid sample can be developed and includes a reserve region (150) provided separately from the detection unit (120''). One end of the detection unit (120'') is accommodated in the reservoir region (150). The reservoir region (150) is a recessed patterned area in each of the lower surface of the top layer and the upper surface of the bottom layer of the rotatable platform (10) of FIG. 4A so as to accommodate the fluid sample therein. The fluid sample accommodated in the microfluidic channel (110) during the first rotation of the rotatable platform (10) moves from the microfluidic channel (110) to the reservoir region (150) during the second rotation of the rotatable platform (10) and then is stored (i.e., trapped) in the reservoir area (150) without being developed into the detection unit (120'') by the centrifugal force due to the rotation. When the second rotation of the rotatable platform (10) is stopped, the fluid sample is moved from the reservoir area (150) into the detection unit (120'') where the fluid sample is developed. A more detailed description thereof will be given below with reference to FIG. 8.

[0078] In the description of the device for qualitative analysis and quantitative analysis (1'') of FIG. 2A and the microfluidic structures (20'') of FIG. 2B, the description of the components that overlap with those in the device for qualitative analysis and quantitative analysis (1, 1', 1'') and the microfluidic structures (20, 20', 20'') of FIGS. 1A to 1H refers to the descriptions of FIGS. 1A to 1H.

[0079] FIGS. 3A and 3B illustrate each layer of the rotatable platform (10) comprising the microfluidic structures (20, 20') of FIGS. 1A and 1D, respectively. The rotatable platform (10) including the microfluidic structures (20, 20') is mainly composed of two layers. In a top layer, the sample injection unit (100), the microfluidic channel (110), a space in which the detection unit (120, 120') can be inserted, and the ruler (130) are positioned. The thickness of the top layer may be, for example, 1.0 mm, and the materials of the top layer may include, for example, polycarbonate (PC), polymethyl methacrylate (PMMA) and the like. The sample injection unit (100) and the microfluidic channel (110) are provided within the top layer, and the sample injection unit (100) and the microfluidic channel (110) can be formed through a patterning process using micro-milling. The portion of the top layer where the detection unit (120, 120') is positioned may be variously modified and changed so that the detection unit (120, 120') can be inserted, including a concave portion in conformity with the shape of the detection unit (120, 120'). Also, the depth of the concave portion can be variously modified and changed according to the environment in which the present invention is actually implemented. The bottom layer is not patterned but is a pressure sensitive adhesion layer that can be bonded to the top layer. The material thereof may include, for example, a polyolefin series and the like.

[0080] FIG. 3C illustrates each layer of the rotatable platform (10) comprising the microfluidic structures (20'') of FIG. 1G. As shown in FIG. 3C, the rotatable platform (10) including the microfluidic structures (20'') is mainly composed of three layers, each of which corresponds to the top layer wherein the sample injection unit (100) and the microfluidic channel (110) are positioned, a bottom layer (see FIG. 4D) for inserting the detection unit, and a PSA (Pressure sensitive adhesion) layer for bonding the top and bottom layers. The materials of the top and bottom layers may include, for example, polycarbonate (PC), polymethyl methacrylate (PMMA) and the like. The sample injection unit (100) and the microfluidic channel (110) are provided within the top layer, and the sample injection unit (100) and the microfluidic channel (110) can be formed through a patterning process using micro-milling. The portion of the top layer where the detection unit (120'') is positioned may be variously modified and changed so that the detection unit (120'') can be inserted, including a concave portion in conformity with the shape of the detection unit (120''). Also, the depth of the concave portion can be variously modified and changed according to the environment in which the present invention is actually implemented. A hydrophilic material is coated on the inside of the microfluidic channel (110) to receive the fluid sample containing the heavy metals. To have a space in which the detection unit (120'') can be inserted in the bottom layer, the lower surface of the top layer may include a concave portion in conformity with the shape of the detection unit (120''). The ruler (130) is patterned in the bottom layer. The PSA layer is an adhesive layer serving to bond the top layer and the bottom layer, and can be formed into, for example, an acrylic based double-sided adhesive tape. In a tape or a plate having an adhesive component corresponding to the size of the rotatable platform (10), the region corresponding to the sample injection unit (100) and the microfluidic channel (110) in the top layer, and the region corresponding to the detection unit (120'') in the bottom layer may be removed by cutting or the like. On the other hand, the top layer and the PSA layer are made of a transparent material so that the development of the sample in the detection unit (120'') and the ruler in the bottom layer can be identified. However, the present invention is not limited to the above-described embodiments, and various modifications and changes are possible, for example, the ruler (130) may be patterned on the top layer.

[0081] FIGS. 4A to 4D illustrate each layer of the rotatable platform (10) comprising the microfluidic structures (20'') of FIG. 2A. As shown in FIG. 4A, the rotatable platform (10) including the microfluidic structures (20'') is mainly composed of three layers, each of which corresponds to the top layer wherein the sample injection unit (100) and the microfluidic

channel (110) are positioned (see FIG. 4B), a bottom layer (see FIG. 4D) for inserting the detection unit, and a PSA (Pressure sensitive adhesion) layer (see FIG. 4C) for bonding the top and bottom layers. In FIGS. 4A to 4D, the description of the device for qualitative analysis and quantitative analysis (1''') of FIG. 2A and the microfluidic structures (20''') of FIG. 2B, and the respective layer that overlap with those in the device for qualitative analysis and quantitative analysis (1'') of FIG. 1G and the microfluidic structures (20''), and the respective layer refers to the descriptions of FIG. 3C.

[0082] According to the device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') of the present invention, the rotation of the device for qualitative analysis and quantitative analysis (1) is controlled so that the fluid sample containing the heavy metals moves from the sample injecting unit (100) into the microfluidic channel (110), and then moves to the detection unit (120, 120', 120''). For example, after the fluid sample containing the heavy metals is injected into the sample injection unit (100), when the device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') is first rotated for 10 seconds at 3000 RPM and then stopped, the fluid sample containing the heavy metals moves to the microfluidic channel (110). When the device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') is secondarily rotated at 5,000 RPM for 5 seconds, the fluid sample containing the heavy metals in the microfluidic channel (110) of the top layer is injected to the detection unit (120, 120', 120'') inserted in the bottom layer by the centrifugal force. When the rotation of the device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') is stopped, the fluid sample containing the heavy metals is developed on the detection units (120, 120', 120'') by the capillary force.

[0083] The fluid sample including the heavy metals developed on the detection unit (120, 120', 120'') reacts with the reagents previously coated on the detection unit (120, 120', 120'') to indicate colors related to the heavy metals. As an organic substance that can be previously applied to the detection unit (120, 120', 120''), for example, an organic chelating agent may be used. In one embodiment, organic substances based on a reaction list between heavy metal ions and the organic chelating agents as shown in Table 1 below may be used.

Table 1

Heavy Metals	Form	Chelating agent (concentration)
Nickel (Ni^{2+})	Sulfate	Dimethylglyoxime (100 mM)
Iron (Fe^{2+})	Sulfate	Bathophenanthroline (5mM)
Copper (Cu^{2+})	Sulfate	Dithiooxamide (20mM)
Mercury (Hg^{2+})	Sulfate	Dithizone (5mM)
Chromium (Cr^{6+})	Oxide	Diphenylcarbazide (10mM)
Zinc (Zn^{2+})	Sulfate	1-(2-Pyridylazo)-2-naphthol (5mM)

[0084] FIG. 5 shows the color development reaction between heavy metal ions and the organic chelating agents according to Table 1. In the embodiment of FIG. 5, PAN (1-(2-pyridylazo)-2-naphthol), Bphen (bathophenanthroline), DMG (dimethylglyoxime), DTO (dithiooxamide), DCB (diphenylcarbazide) and DTZ (dithizone) were used as the organic chelating agents. And 1% H_2SO_4 was added to DCB for Cr^{6+} to improve the reaction selectivity of Cr^{6+} ion for DCB and the color development reaction.

[0085] The device for qualitative analysis and quantitative analysis (1, 1') according to the present invention can provide a simultaneous qualitative analysis up to a level of 25 ppm for a plurality of the heavy metals such as Fe^{2+} , Zn^{2+} , Hg^{2+} , Cr^{6+} , Ni^{2+} , or Cu^{2+} within 15 minutes.

[0086] The qualitative analysis can be performed on the heavy metals contained in the fluid sample with the hue according to the color development reaction on the detection unit (120, 120', 120''). For example, when the hue according to the color development reaction is observed with the naked eyes, the types of the heavy metals contained in the fluid sample can be identified. FIG. 6 shows an example of a simultaneous qualitative analysis for six heavy metals (100 ppm) using the device for qualitative analysis and quantitative analysis (1''') of FIG. 2A.

[0087] In addition, the degree of development of the fluid sample including the heavy metals on the detection unit (120, 120', 120'') can be quantitatively analyzed by using the ruler (130). Referring to the example of FIG. 6, it can be seen that the degree of development of the fluid sample including the heavy metals on the detection unit (120'') of each of the plurality of the microfluidic structures (20''') is different from each other. It is possible to measure the extent to which a fluid sample containing the heavy metals is developed by using the respective ruler (130). The development distance of the corresponding fluid sample on the detection unit (120) is measured using the ruler (130), the types of heavy metals contained in the fluid sample are determined by the above qualitative analysis, and the quantitative analysis of the heavy metals can be performed by substituting the development distance into a calibration curve for the heavy metals (see FIGS. 7A and 7B). As an example of the quantitative analysis, FIG. 7A shows a case where Cr^{6+} is quantitatively analyzed and FIG. 7B shows a case where Fe^{2+} is quantitatively analyzed using the device for qualitative

analysis and quantitative analysis (1''') of FIG. 2A. For example, the numbers of 1 ppm, 5 ppm, 10 ppm, 25 ppm, 50 ppm, and 100 ppm described in FIG. 7A are the results of quantitative analysis of Cr^{6+} . This is a method in which the degree of purple development corresponding to Cr^{6+} on the six detection units (120'') is measured using the ruler (130) and then the measured development distance is substituted into the calibration curve of Cr^{6+} to obtain the concentration on the x axis corresponding to the degree of development on the y axis of the calibration curve so as that the quantitative analysis of Cr^{6+} can be performed. In the case of Fe^{2+} in FIG. 7B, the quantitative analysis can be performed in the same manner. At this time, in the case of Cr^{6+} , the detection limit of the qualitative analysis is 1 ppm and the detection limit of the quantitative analysis is 5 ppm. In the case of Fe^{2+} , the detection limit of the qualitative analysis is 25 ppm and the detection limit of the quantitative analysis is 50 ppm.

[0088] Hereinafter, with reference to FIG. 8, a method (2) of analyzing a fluid sample containing the heavy metals using the device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') according to one embodiment of the present invention will be described. The steps of the method for analyzing a sample (2) according to an embodiment of the present invention are as follows:

Step 1: Injecting a fluid sample into the sample injection unit (100) of the device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') (S1);
 Step 2: Controlling the rotation of the device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') (S2); and
 Step 3: Performing at least one of qualitative analysis and quantitative analysis (S3).

Step 1: Injecting a fluid sample into the sample injection unit (100) of the device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') (S1)

[0089] The fluid sample is injected into each sample injection unit (100) of the plurality of the microfluidic structures (20) of the device for qualitative analysis and quantitative analysis (1, 1', 1'', 1'''). For example, about 40 μl of the fluid sample each can be injected into each sample injection unit (100). However, the present invention is not limited to this embodiment, and the amount of the injection can be variously adjusted according to various environments in which the present invention is implemented. The fluid sample containing different kinds of the heavy metals are respectively injected into each of the plurality of the microfluidic structures (20, 20', 20'', 20''') (S1-1) to perform qualitative analysis and/or quantitative analysis as described below, and the fluid sample containing the same kind of the heavy metals of varying concentrations are respectively injected into each of the microfluidic structures (20, 20', 20'', 20''') (S1-2) to perform qualitative analysis and/or quantitative analysis as described below.

Step 2: Controlling the rotation of the device for qualitative analysis and quantitative analysis (1, 1') (S2)

[0090] The device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') is mounted on a system for qualitative analysis and quantitative analysis (3) capable of rotating the device for qualitative analysis and quantitative analysis (1, 1', 1'', 1'''), for example, a rotatable system for qualitative analysis and quantitative analysis (3) as shown in FIG. 9, and the device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') is rotated. This step (S2) includes the following detailed steps:

Step 2-1: The device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') is initially rotated at 2000 to 4000 RPM for 5 to 20 seconds and then is stopped to move the fluid sample including the heavy metals injected into the sample injection unit (100) located at the top layer of the microfluidic structure (20, 20', 20'', 20''') to the microfluidic channel (110) (S2-1).

Step 2-2: The device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') is secondarily rotated at 4000 to 6000 RPM for 3 to 10 seconds to flow the fluid sample including the heavy metals transferred to the microfluidic channel (110) at step 2-1 into the reservoir region (124, 150) of the microfluidic structures (20, 20', 20'', 20''') (S2-2).

Step 2-3: The rotation of the device for qualitative analysis and quantitative analysis (1, 1', 1'', 1''') is stopped so that the fluid sample including the heavy metals are guided by the capillary force to be developed on the detection unit (120, 120', 120'') (S2-3).

Step 3: Performing at least one of qualitative analysis and quantitative analysis (S3)

[0091] A qualitative analysis can be performed on the fluid sample developed on the detection unit (120, 120', 120'') by a method of analyzing the color development reaction on the detection unit (120, 120', 120'') with the naked eyes (S3-1), or a quantitative analysis can be performed by measuring the degree of development of the fluid sample developed on the detection unit (120, 120', 120'') by using a ruler (130) and then substituting the measured values to the calibration curves of the corresponding heavy metals developed on the scale (S3-2), or both of the qualitative analysis and the

quantitative analysis can be performed (S3-1 and S3-2). Examples related to this are described above with reference to FIGS. 6, 7A and 7B.

[0092] In summary, the device for qualitative analysis and quantitative analysis (1, 1', 1", 1''') according to an embodiment of the present invention includes the microfluidic structures (20) having the same structure that can detect a plurality of types (for example, six kinds) of the heavy metals on the rotatable platform (10) (for example, a circular disk), wherein each microfluidic structure (20) is arranged radially and symmetrically along the rotational direction of the rotatable platform (10) and comprises the detection unit (120, 120', 120'') coated with an organic substance that can cause a color development reaction with the heavy metals.

[0093] According to the device for qualitative analysis and quantitative analysis (1, 1', 1", 1''') and the method of analyzing the sample using the same (2) according to the embodiment of the present invention, the centrifugal force generated upon rotation of the device for qualitative analysis and quantitative analysis (1, 1', 1", 1''') can move the fluid sample containing the heavy metals to the detection unit (120, 120', 120'') and the qualitative analysis can be performed through the color development reaction. Further, the fluid can be developed by the paper capillary force when the rotation of the device stops and the quantification may be performed by identifying the color developed distance with the ruler (130) patterned on the device for qualitative analysis and quantitative analysis (1, 1', 1", 1'''). It is possible to increase the detection limit of the heavy metals through automatic fluid control and control of torque and capillary force. It is possible to improve the detection limit of the heavy metal ions by the torque control. That is, by adjusting the centrifugal force and the capillary force by the rotation control, it is possible to improve the detection limit by controlling the reaction time of color development and the colored area. Specifically, on the detection unit, when the development speed of the sample containing the heavy metals due to the capillary force becomes faster than the speed at which the heavy metals and the organic chelating agent react with each other, the sample containing the heavy metals fails to sufficiently react with the organic chelating agent and develops on the entire detection unit. In the case of a heavy metal sample having a high concentration, there is no problem in detection because of the color development, but there is a possibility that the quantitative property is lowered. In the case of a heavy metal sample having a low concentration, there is a possibility that the detection sensitivity and limit are lowered because the sample fails to sufficiently react with the organic chelating agent on the detection unit, and thus the color development does not occur. However, according to the present invention, since the centrifugal force acts on the opposite side of the capillary force, the centrifugal force is applied to control the solution development speed by the capillary force so that the color development reaction can be sufficiently performed on the detection unit to improve the detection limitations.

[0094] Further, according to the device for qualitative analysis and quantitative analysis (1, 1', 1", 1''') and the method of analyzing the sample (2) using the same according to the embodiment of the present invention, it is economical and quick in the qualitative/quantitative analysis of multiple heavy metals. It is more economical than conventional expensive spectroscopy or mass spectrometry based heavy metal detector and can shorten analysis time. Thus, it can be applied quickly and conveniently in the field where the qualitative/quantitative analysis of heavy metals is required.

[0095] The technical constitution of the present invention as described above will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention. It is therefore to be understood that the above-described embodiments are illustrative in all aspects and not restrictive. In addition, the scope of the present invention is indicated by the appended claims rather than the detailed description of the invention. Also, all changes or modifications derived from the meaning and scope of the claims and their equivalents should be construed as being included within the scope of the present invention.

[Explanation of reference numbers]

[0096]

1, 1', 1", 1'''	Device for qualitative analysis and quantitative analysis
2	Method of analyzing a sample
3	System for qualitative analysis and quantitative analysis
10	Rotatable platform
20, 20', 20'', 20'''	Microfluidic structure
100	Sample injection unit
110	Microfluidic channel
120, 120', 120''	Detection unit
130	Ruler

Claims

1. A device for qualitative analysis and quantitative analysis comprising a rotatable platform and a plurality of microfluidic structures disposed radially and symmetrically on the rotatable platform, wherein each of the plurality of the microfluidic structures comprises:

a sample injection unit into which a fluid sample containing heavy metals is injected;
 a microfluidic channel (a siphon channel) which is a passage through which the sample is moved to a detection unit and connects the sample injection unit to the one end of the detection unit;
 the detection unit comprising a plurality of detection members, which is coated with an organic substance capable of causing the color development reaction with the heavy metals of the sample; and
 a ruler for measuring the color developed distance,
 wherein each of the plurality of the microfluidic structures receives different kinds of the samples,
 wherein the sample moves from the sample injection unit to the microfluidic channel and then to the detection unit by controlling the rotation of the device, and
 wherein the qualitative analysis is possible through the color development reaction of the heavy metals in the detection unit and the quantitative analysis is possible through the measurement of the color developed distance.

2. The device for qualitative analysis and quantitative analysis according to claim 1, wherein each of the plurality of the detection members is coated with respective different reagents.

3. The device for qualitative analysis and quantitative analysis according to claim 1, wherein each of the plurality of the detection members comprises a plurality of sections coated with organic ligands of respective different concentrations.

4. The device for qualitative analysis and quantitative analysis according to claim 1, wherein the detection unit comprises a reservoir area which connects each one end of the plurality of the detection members with the microfluidic channel.

5. The device for qualitative analysis and quantitative analysis according to claim 4, wherein each of the detection members comprises a plurality of sections coated with organic ligands of different concentrations, and the concentration of the organic ligand coated in the section located i -th from the reservoir area is lower than the concentration of the organic ligand coated in the section located $i-1$ -th from the reservoir area, wherein i is a natural number from 1 to n .

6. The device for qualitative analysis and quantitative analysis according to claim 1, further comprising an air circulation channel connecting between the sample injection unit and the other end of the detection unit, wherein the air circulation channel increases the rate of evaporation of the fluid sample in the detection unit and prevents moisture condensation phenomenon in the detection unit.

7. The device for qualitative analysis and quantitative analysis according to claim 4, wherein the control of the rotation of the device is accomplished by:

rotating the device firstly and then stopping so that the sample injected into the sample injection unit is moved to the microfluidic channel;
 rotating the device secondarily so that the sample moved to the microfluidic channel is moved to the reservoir area; and
 stopping the device so that the sample moved to the reservoir area is developed in the detection unit.

8. The device for qualitative analysis and quantitative analysis according to claim 7, wherein the microfluidic channel includes a portion of a "U" shaped tube so that the sample is received within the microfluidic channel after the first rotation and before the second rotation of the device.

9. The device for qualitative analysis and quantitative analysis according to claim 7, wherein the first rotation of the device is performed at 2000 to less than 4000 RPM for 5 to 20 seconds and the second rotation of the device is performed at 4000 to 6000 RPM for 3 to 10 seconds.

10. The device for qualitative analysis and quantitative analysis according to claim 1, wherein the heavy metals included in the sample comprise Fe^{2+} , Zn^{2+} , Hg^{2+} , Cr^{6+} , Ni^{2+} , or Cu^{2+} .

11. The device for qualitative analysis and quantitative analysis according to claim 10, wherein the organic material previously applied to the detection unit comprises any one selected from the group consisting of dimethylglyoxime, bathophenanthroline, dithiooxamide, dithizone, diphenylcarbazide and 1-(2-pyridylazo)-2-naphthol.

12. An analytic method of a fluid sample containing heavy metals by using the device according to any one of claims 1 to 11, comprising:

(S1) injecting the sample into the sample injection unit;

(S2) controlling the rotation of the device; and

(S3) performing at least one of qualitative analysis and quantitative analysis of the sample developed in the detection unit.

13. The analytic method of a fluid sample according to claim 12, wherein the injection of the sample into the sample injection unit of the step (S1) comprises:

injecting the fluid sample containing different kinds of the heavy metals into each of the plurality of the microfluidic structures; or

injecting the fluid sample containing same kinds of the heavy metals of varying concentrations into each of the plurality of the microfluidic structures.

14. An analytic method of a fluid sample containing heavy metals by using the device according to any one of claims 4 to 11, comprising:

(S1) injecting the sample into the sample injection unit;

(S2) controlling the rotation of the device; and

(S3) performing at least one of qualitative analysis and quantitative analysis of the sample developed in the detection unit,

wherein the controlling of the rotation of the device of the step (S2) comprises:

(S2-1) rotating the device firstly and then stopping so that the sample injected into the sample injection unit is moved to the microfluidic channel;


(S2-2) rotating the device secondarily so that the sample moved to the microfluidic channel is moved to the reservoir area; and

(S2-3) stopping the rotation of the device so that the sample moved to the reservoir area is developed in the detection unit.


15. The analytic method of a fluid sample according to claim 12, wherein the performance of at least one of qualitative analysis and quantitative analysis of the sample of the step (S3) comprises:

performing at least one of (S3-1) qualitative analysis through the color development reaction of the sample developed in the detection unit and (S3-2) quantitative analysis through the measurement of the color developed distance.


[FIG. 1A]




[FIG. 1B]




[FIG. 1C]




[FIG. 1D]




[FIG. 1E]




[FIG. 1F]




[FIG. 1G]




[FIG. 1H]




[FIG. 1I]




[FIG. 2A]




[FIG. 2B]




[FIG. 3A]




[FIG. 3B]




[FIG. 3C]




[FIG. 4A]




[FIG. 4B]




[FIG. 4C]




[FIG. 4D]





[FIG. 5]





[FIG. 6]




[FIG. 7A]




[FIG. 7B]



[FIG. 8]

2

[FIG. 9]



INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR2018/012738

A. CLASSIFICATION OF SUBJECT MATTER

G01N 35/00(2006.01)i, G01N 35/08(2006.01)i, G01N 31/22(2006.01)i, G01N 21/78(2006.01)i, B01L 3/00(2006.01)i, G01N 21/75(2006.01)i, G01N 21/77(2006.01)i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G01N 35/00; B04B 1/02; G01N 21/05; G01N 33/48; G01N 35/08; G01N 37/00; G01N 31/22; G01N 21/78; B01L 3/00; G01N 21/75; G01N 21/77

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean Utility models and applications for Utility models: IPC as above

Japanese Utility models and applications for Utility models: IPC as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eCOMPASS (KIPO internal) & Keywords: rotary platform, microfluidic structure, sample injection part, detection part, microfluidic channel, ruler

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	KR 10-1256474 B1 (UNIST ACADEMY-INDUSTRY RESEARCH CORPORATION) 23 April 2013 See paragraphs [0024]-[0042], [0052]-[0059], [0079]-[0135]; claims 8, 26, 31; and figures 1, 3-5, 9.	1-2,4,7-15
Y		3,5-6
Y	KR 10-2011-0079570 A (SAMSUNG ELECTRONICS CO., LTD.) 07 July 2011 See page 11, line 45-page 22, line 29; and figures 2, 13.	3,5
Y	JP 2007-278741 A (MATSUSHITA ELECTRIC IND., CO., LTD.) 25 October 2007 See paragraph [0044]; and figure 2.	6
A	KR 10-2015-0027939 A (SAMSUNG ELECTRONICS CO., LTD.) 13 March 2015 See paragraphs [0023]-[0053]; and figures 1-8.	1-15
A	JP 2013-156070 A (SOKA UNIV et al.) 15 August 2013 See paragraphs [0018]-[0071]; and figures 1-7.	1-15

☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

09 FEBRUARY 2019 (09.02.2019)

Date of mailing of the international search report

11 FEBRUARY 2019 (11.02.2019)

Name and mailing address of the ISA/KR



Korean Intellectual Property Office
Government Complex Daejeon Building 4, 189, Cheongsu-ro, Seo-gu,
Daejeon, 35208, Republic of Korea
Facsimile No. +82-42-481-8578

Authorized officer

Telephone No.

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/KR2018/012738

Patent document cited in search report	Publication date	Patent family member	Publication date
KR 10-1256474 B1	23/04/2013	KR 10-2013-0000009 A	02/01/2013
KR 10-2011-0079570 A	07/07/2011	CN 101971035 A	09/02/2011
		CN 101971035 B	16/10/2013
		CN 103472241 A	25/12/2013
		CN 103472241 B	17/06/2015
		EP 2239583 A2	13/10/2010
		EP 2239583 A4	02/09/2015
		KR 10-1608749 B1	06/04/2016
		US 2010-0297659 A1	25/11/2010
		US 2014-0186935 A1	03/07/2014
		US 8969070 B2	03/03/2015
		WO 2009-093838 A2	30/07/2009
		WO 2009-093838 A3	22/10/2009
		WO 2009-093838 A9	10/09/2009
JP 2007-278741 A	25/10/2007	NONE	
KR 10-2015-0027939 A	13/03/2015	US 2015-0064774 A1	05/03/2015
		US 9737889 B2	22/08/2017
JP 2013-156070 A	15/08/2013	NONE	

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- KR 20170154395 [0001]
- KR 1020180053639 [0001]