

(19)



(11)

EP 3 719 195 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
22.09.2021 Bulletin 2021/38

(51) Int Cl.:
D06F 39/12 ^(2006.01) **D06F 39/08** ^(2006.01)

(21) Application number: **19167598.2**

(22) Date of filing: **05.04.2019**

(54) **TOP-LOADING LAUNDRY WASHING MACHINE**

TOPLADERWASCHMASCHINE

MACHINE À LAVER À CHARGEMENT PAR LE DESSUS

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

- **VALENT, Lucio**
33080 Porcia (IT)
- **PASQUETTI, Silvia**
33080 Porcia (IT)

(43) Date of publication of application:
07.10.2020 Bulletin 2020/41

(74) Representative: **Electrolux Group Patents**
AB Electrolux
Group Patents
S:t Göransgatan 143
105 45 Stockholm (SE)

(73) Proprietor: **ELECTROLUX APPLIANCES**
AKTIEBOLAG
105 45 Stockholm (SE)

(72) Inventors:
• **MAIERO, Marco**
33080 Porcia (IT)

(56) References cited:
EP-A1- 3 354 786 KR-A- 20030 055 970
US-A- 3 608 339

EP 3 719 195 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

[0001] The present invention relates to a top-loading laundry washing machine.

[0002] More in detail, the present invention relates to a top-loading laundry washing machine for domestic use, to which the following description specifically refers purely by way of example and without this implying any loss of generality.

[0003] As is known, a top-loading home laundry washing machine may have an horizontally-oriented drum or a vertically-oriented drum.

[0004] Generally a top-loading home laundry washing machine with an horizontally-oriented drum firstly comprises: a substantially parallelepiped-shaped, self-supporting boxlike casing structured for resting on the floor; a nearly barrel-shaped, washing tub which, in use, contains the washing liquid and is suspended in floating manner inside the casing with its upper opening directly facing a huge, vertically-oriented hopper incorporated into the top wall of the casing; an elastically-deformable tubular bellows connecting the lower mouth of the hopper to the facing upper opening of the washing tub; and a substantially cylindrical and evenly perforated, hollow rotatable drum which is fitted in axially rotatable manner inside the washing tub so as to be able to freely rotate about its, substantially horizontally-oriented, central axis inside the same washing tub, and which is provided, on the peripheral wall, with a manually-openable, huge laundry loading-unloading hatch allowing the user to put the laundry to be washed inside the drum.

[0005] The aforesaid laundry washing machine additionally comprises: a manually-openable, upper door which is hinged to the top wall of the casing so as to be able to freely rotate about an horizontal axis to and from a closing position in which the door closes the upper mouth of the hopper for approximately watertight sealing the washing tub; an electrically-powered motor assembly which is structured for driving into rotation the rotatable drum inside the washing tub; a detergent dispenser which is structured for selectively feeding into the washing tub a given amount of detergent, softener and/or other washing agent suitably mixed with the water arriving from the water mains; and an electrically-operated, water supply circuit which is connectable to the water mains and is structured for selectively channelling the water of the water mains towards the detergent dispenser and/or directly towards the washing tub.

[0006] More specifically, the water supply circuit usually comprises a number of solenoid valves that are generally located on the vertical rear wall of the casing, and a corresponding number of connection pipes which connect the solenoid valves to the detergent dispenser and/or to the washing tub.

[0007] The laundry washing machine finally comprises an electronic control unit that controls the various components of the washing machine to perform the washing cycle manually-selected by the user.

[0008] Even if the top-loading laundry washing machines are less prone to water leakages than front-loading laundry washing machines because gravity can reliably keep water from spilling out of the door on top of the casing, in the last years even the top-loading laundry machines have been provided with an aqua-stop safety system to avoid the problems of the solenoid valve/s getting stuck in the open position.

[0009] The aqua-stop safety system basically comprises: a long flexible hosepipe having the proximal end in direct communication with the water inlet of the solenoid valve/s, at the rear wall of the casing, and the distal end suitably structured to watertight couple in detachable manner with the tap of the water mains; and a normally-closed, auxiliary solenoid valve which is located at the distal end of the hosepipe for directly controlling the entry of water into the same hosepipe. Therefore water can flow along the hosepipe towards the main solenoid valves only when the auxiliary solenoid valve is in the open position.

[0010] In addition to the above, one of the lateral walls of the hopper is provided with a large pass-through opening that works as overflow for immediately draining the exceeding water out of the hopper and straight down to the bottom wall of the boxlike casing, where there is located a water sensor capable of automatically detecting the presence of water and immediately deactivating the auxiliary solenoid valve of the aqua-stop safety system.

[0011] Generally a discrete muffler assembly is moreover firmly coupled to the lateral wall of the hopper, outside of the same hopper, so as to form an extension of the overflow opening that reduces the washing noise coming out of the washing tub via the same overflow opening.

[0012] EP3354786 A1 discloses a washing machine which includes: a drum for accommodating laundry; a tub for accommodating the drum; a packing water-sealing part having a packing component arranged between an upper end part of the tub and an upper end part of the drum to inhibit water from leaking outwards from the tub; a labyrinth part adopting a labyrinth structure and for arranging ribs lower than the packing water-sealing part between a tub cover and the upper end part of the drum at an inner side of the packing water-sealing part; and a heightened drum arranged integrally with the tub cover for retaining water whose water level is higher than a water level at the upper end of the drum.

[0013] Despite being essential for minimizing the in-use noise of the laundry washing machine, the muffler assembly has significantly raised the overall production costs of the hopper assembly because the manual coupling of the muffler manifold to the body of the hopper is relatively complicated and time consuming.

[0014] Furthermore the large overflow opening is clearly visible on the lateral wall of the hopper with all esthetical problems that this entails.

[0015] Aim of the present invention is to realize a muffler assembly that can solve the drawback referred

above.

[0016] In compliance with the above aims, according to the present invention there is provided a laundry washing machine comprising: a boxlike casing structured for resting on the floor; a vertically-oriented, hopper which is located on a top wall of said casing; a washing tub which is arranged inside the casing beneath the hopper, and is superiorly provided with an access opening that directly communicates with a lower mouth of the hopper for allowing insertion and extraction of the laundry in/from the washing tub via said hopper; and an overflow assembly for draining out of the hopper the exceeding water; said overflow assembly comprises: an upwards-extending overflow duct which is located on a sidewall of said hopper, so that a lower mouth of the overflow duct is located roughly on the perimeter edge/rim of the lower mouth of the hopper and that an upper mouth of the overflow duct is located on the outer face of the same sidewall of the hopper, spaced above the lower mouth of hopper; and an outwards-extending, tubular member which is associated to the upper mouth of the overflow duct so as protrude from the sidewall of the hopper towards the facing wall of the casing, forming an extension of said overflow duct.

[0017] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the overflow duct is substantially reversed-L shaped.

[0018] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the overflow duct is integrally formed with the sidewall of said hopper.

[0019] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the tubular member is roughly S-shaped so as to form a siphon-like extension of said overflow duct.

[0020] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the tubular member extends substantially horizontally.

[0021] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the outlet mouth of the tubular member is nearly horizontally aligned to the upper mouth of the overflow duct.

[0022] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the preceding claims, wherein the tubular member is dimensioned so as to reach/touch the facing upright wall of the casing, for channelling the exceeding water up to the same upright wall of the casing.

[0023] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the outlet mouth of the tubular member has a plate-like protruding lip/flap which is dimensioned to abut against the inner face of the facing upright wall of said casing.

[0024] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that said plate-like protruding lip/flap has a roughly comb-shaped structure.

[0025] Preferably, though not necessarily, the laundry

washing machine is furthermore characterized in that said plate-like protruding lip/flap is slightly slopped downwards.

[0026] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that said overflow assembly additionally comprises a hiding member which is located in the lower mouth of the overflow duct so as to hide the same lower mouth, and is provided with a number of waterways allowing the exceeding water to freely enter into the overflow duct by-passing at once the same hiding member

[0027] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the hiding member is almost completely fitted/recessed into a starting segment of the overflow duct and/or is firmly locked to the body of the hopper via a snap-lock fastening system.

[0028] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the hiding member has a substantially rectangular and tray-shaped structure, and is fitted into the overflow duct so that a first segment of its raised perimeter edge is roughly flush with the lower mouth of overflow duct.

[0029] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the hiding member is fitted into the overflow duct so that a second segment of its raised perimeter edge, opposite to said first segment, is arranged inside the overflow duct spaced above an elbow/bend of said overflow duct.

[0030] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the overflow duct is divided into a first and a second consecutive segments; the first segment being nearly rectilinear and extending upwards inside the sidewall of the hopper, starting from the perimeter edge/rim of the lower mouth of the hopper; the second segment being nearly rectilinear and being inclined with respect to the first segment by an angle lower than 90°.

[0031] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the second segment of the overflow duct is inclined with respect to the vertical by an angle ranging between 70° and 80°.

[0032] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that said overflow assembly is located on the sidewall directly faced to a nearly vertical front wall of the casing.

[0033] Preferably, though not necessarily, the laundry washing machine is furthermore characterized by additionally comprising: a detergent dispenser which is located inside the casing and is structured for selectively feeding into the washing tub a given amount of detergent, softener and/or other washing agent suitably mixed with the water arriving from the water mains; and an electrically-operated, water supply circuit which is located inside the casing, is connectable to the water mains via an external feeding pipe, and is suitably structured for selectively channelling the water of the water mains towards

the detergent dispenser and/or directly towards the washing tub.

[0034] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the water supply circuit comprises one or more solenoid valves that are accommodated inside a substantially basin-shaped container which is fixed to the rear wall of the casing, beside the hopper.

[0035] Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that said substantially basin-shaped container is made in one piece with the hopper.

[0036] A non-limiting embodiment of the present invention will now be described, by way of example, with reference to the accompanying drawings, in which:

- Figure 1 is a perspective view of a top-loading laundry washing machine realized in accordance with the teachings of the present invention;
- Figure 2 is a side view of the laundry washing machine shown in Figure 1, sectioned along the midplane of the same laundry washing machine and with parts removed for clarity's sake;
- Figure 3 is a perspective view of the hopper assembly of the laundry washing machine shown in Figures 1 and 2, with parts removed for clarity's sake;
- Figure 4 is an enlarged and partly exploded perspective view of the hopper assembly shown in Figure 3; whereas
- Figure 5 is an enlarged side view of the hopper assembly shown in Figures 3 and 4, sectioned along the midplane of the washing machine and with parts exploded for clarity; whereas
- Figure 6 is an enlarged side view of the front portion of hopper assembly shown in Figure 5, with parts removed for clarity's sake.

[0037] With reference to Figures 1 and 2, reference number 1 denotes as a whole a top-loading laundry washing machine 1 preferably suitable for domestic use.

[0038] The laundry washing machine 1 firstly comprises: a preferably substantially parallelepiped-shaped, self-supporting boxlike casing 2 which is preferably made of metal and is structured for stably resting on the floor; a substantially vertically-oriented, hopper 3 which is incorporated into, or forms part of, the top wall of casing 2; and a preferably nearly barrel-shaped, washing tub 4 which, in use, contains the washing liquid, is arranged inside the casing 2 beneath the hopper 3, and is superiorly provided with a large access opening 5 that directly communicates with the superjacent hopper 3, preferably via an elastically-deformable tubular bellows 6 that preferably substantially watertight connects the access opening 5 of washing tub 4 to the lower mouth of hopper 3. The hopper 3 allows manual insertion and extraction of the laundry in/from the washing tub 4.

[0039] In the example shown, in particular, the washing tub 4 is preferably suspended in floating manner inside

the boxlike casing 2 preferably via a suspension system that preferably comprises at least one and more conveniently a number of coil springs 7 connecting the washing tub 4 to the upper part of casing 2, and at least one and more conveniently a number of vibration dampers 8 connecting the washing tub 2 to the bottom part of casing 2.

[0040] Preferably the laundry washing machine 1 additionally comprises: a nearly cylindrical-shaped, hollow rotatable drum 9 with a water-permeable structure, which is structured for accommodating the laundry to be washed, and is stably fitted inside the washing tub 4 with the capability of freely rotating about its, preferably substantially horizontally-oriented, central axis A which is optionally also substantially perpendicular to the midplane of the laundry washing machine 1; and an electrically-powered motor assembly 10 which is preferably attached to the washing tub 4, and is structured for driving into rotation the rotatable drum 9 about central axis A, inside washing tub 4. The laundry is inserted into and extracted from the rotatable drum 9 via the hopper 3.

[0041] More in detail, the rotatable drum 9 preferably has a substantially evenly-perforated cylindrical peripheral wall, and includes a manually-openable laundry loading-unloading hatch 11 that is located on the cylindrical peripheral wall of the drum and is dimensioned to allow the user to easily manually put the laundry to be washed inside the rotatable drum 9.

[0042] The electrically-powered motor assembly 10, in turn, is preferably fastened underneath the washing tub 4.

[0043] With reference to Figures 1 and 2, preferably the laundry washing machine 1 is moreover provided with a manually-openable, upper door 12 which is flag hinged to the top of boxlike casing 2 so as to be able to rotate, preferably about a substantially horizontally-oriented reference axis B also locally perpendicular to the midplane of the laundry washing machine 1, to and from a closing position (see Figures 1 and 2) in which the upper door 12 closes the upper mouth of hopper 3 to seal the washing tub 4 preferably substantially in watertight manner.

[0044] With reference to Figures 2-5, preferably the laundry washing machine 1 additionally comprises: a detergent dispenser 13 which is located inside the casing 2 and is structured for selectively feeding into the washing tub 4 a given amount of detergent, softener and/or other washing agent suitably mixed with the water arriving from the water mains; an electrically-operated, water supply circuit 14 which is located inside the casing 2, is connectable to the water mains preferably via an external feeding pipe, and is suitably structured for selectively channelling the water of the water mains towards the detergent dispenser 13 and/or directly towards the washing tub 4; and optionally also an electrically-powered heating member 15 (namely a resistor) which is preferably located inside the washing tub 4, and is adapted to selectively heat up the washing liquid contained into the washing tub 4.

[0045] In the example shown, in particular, the detergent dispenser 13 is preferably located inside the hopper

3, immediately underneath the upper door 12, so that the mixture of water and detergent, softener and/or other washing agent is allowed to freely drop by gravity into the beneath-located washing tub 4.

[0046] Additionally the detergent dispenser 13 is preferably attached in manually-removable manner to a lateral wall of hopper 3.

[0047] More in detail, in the example shown the detergent dispenser 13 is preferably fitted/recessed in manually-removable manner into a corresponding and roughly complementary-shaped concave seat or recess 16 specifically formed on the rear wall of hopper 3, preferably next to the hinge/s 17 connecting the upper door 12 to the top wall of casing 2.

[0048] The water supply circuit 14, in turn, preferably comprises: at least one and more conveniently a plurality of solenoid valves 18 that are preferably located adjacent to the rear wall of casing 2, preferably substantially horizontally aligned the hopper 3, and are preferably connected to a common manifold 19 that preferably receives the water of the water mains from the aforesaid external feeding pipe; and preferably a corresponding number of connection pipes 20 each of which connects a respective solenoid valve 18 to the detergent dispenser 13 and/or to the washing tub 4.

[0049] Furthermore, in the example shown the common water-distribution manifold 19, the solenoid valve/s 18 and the corresponding connection pipe/s 20 are preferably located inside a substantially basin-shaped container 22 which is fixed to the rear wall of casing 2, beside the hopper 3.

[0050] Preferably the substantially basin-shaped container 22 is furthermore made in one piece with the adjacent hopper 3.

[0051] In other words, the hopper 3 and the substantially basin-shaped container 22 preferably form a monolithic structure and the upper door 12 is preferably hinged to said monolithic structure.

[0052] More in detail, hopper 3 and the adjacent, substantially basin-shaped container 22 are preferably permanently connected by a rigid bridge portion 23, and the hinge/s 17 connecting the upper door 12 to the top wall of casing 2, or rather to the monolithic structure formed by the hopper 3 and the basin-shaped container 22, is/are preferably located on said bridge portion 23.

[0053] Preferably said monolithic structure incorporating hopper 3 and container 22 is furthermore made of plastic material, preferably via an injection molding process.

[0054] With particular reference to Figures 1 and 2, preferably the rear wall of casing 2 moreover has, spaced beneath the solenoid valve/s 18 - or rather the basin-shaped container 22 accommodating the solenoid valve/s 18 -, a huge outwards bulging portion 24 which is substantially horizontally aligned to the washing tub 4 and the rotatable drum 9, and which optionally also substantially copies the rounded profile of the side of washing tub 4.

[0055] The heating member 15, in turn, is preferably located within a tray-shaped portion 26 formed on the bottom of washing tub 4, so as to be submerged by the washing liquid. The heating member 15 is therefore arranged spaced above the motor assembly 10.

[0056] With reference to Figures 3-6, the hopper 3 additionally includes an overflow assembly 30 which is located/incorporated on a sidewall of the same hopper 3, and is specifically structured for immediately draining the exceeding water out of hopper 3 and straight down to the bottom of casing 2. The overflow assembly 30 is additionally structured to minimize the noise coming out of washing tub 4 via the same overflow assembly 30 when the laundry washing machine 1 operates.

[0057] More in detail, the overflow assembly 30 is preferably located on the front sidewall 31 of hopper 3, so as to face the adjacent and nearly vertical, front wall of casing 2.

[0058] Preferably the overflow assembly 30 is furthermore structured to channel the exceeding water coming out of hopper 3 up to the immediately facing, front wall of casing 2, so as to force said water to flow downwards by gravity along the same front wall of casing 2.

[0059] More in detail, with particular reference to Figures 5 and 6, the hopper 3 is preferably provided with a large, upwards-extending and preferably also nearly reverse-L shaped, overflow duct 32 which is integrally formed with the front sidewall 31 of hopper 3, so that the lower mouth 32a of the overflow duct 32 is located roughly on the perimeter edge/rim of the lower mouth of hopper 3 and that the upper mouth 32b of the overflow duct 32 is located on the outer face of the front sidewall 31 of hopper 3, spaced above the lower mouth of hopper 3.

[0060] The overflow assembly 30 furthermore includes: an outwards-extending and preferably substantially horizontally-oriented, tubular member 33 which is associated/fitted into the upper mouth 32b of the overflow duct 32 so as jut out from the front sidewall 31 of hopper 3 towards the immediately facing, front wall of casing 2, while forming an extension of the overflow duct 32 and preferably also while remaining substantially perpendicular to the same front wall of casing 2; and preferably also a hiding member 34, which is inserted/plugged into the lower mouth 32a of the overflow duct 32 so as to hide the same lower mouth, and is provided with a number of waterways allowing the exceeding water to freely enter into the overflow duct 32 bypassing at once the same hiding member 34.

[0061] More in detail, the tubular member 33 is preferably fitted into the upper mouth 32b of overflow duct 32 in substantially watertight manner, preferably by welding or by known connection devices eventually associated to sealing methods/devices, and is preferably also dimensioned so as to reach/touch the immediately facing, front wall of casing 2, for channelling the exceeding water up to the immediately facing, nearly-vertical front wall of casing 2.

[0062] Preferably the tubular member 33 is further-

more roughly S-shaped so to form a substantially siphon-like extension of the overflow duct 32.

[0063] More specifically, the tubular member 33 is preferably S-shaped so that the outlet mouth of the tubular member 33 is nearly horizontally aligned to the upper mouth 32b of overflow duct 32.

[0064] In the example shown, in particular, the lower mouth 32a of overflow duct 32 is preferably straight and oblong in shape, whereas the upper mouth 32b of overflow duct 32 is preferably substantially rectangular in shape and optionally also wider than the lower mouth 32a.

[0065] Preferably the overflow duct 32 is furthermore divided into a first and a second consecutive segments. The first segment is nearly rectilinear and extends roughly upwards inside the front sidewall 31 of hopper 3, starting from the perimeter edge/rim of the lower mouth of hopper 3. The second segment, in turn, is nearly rectilinear and is inclined with respect to the first segment by an angle preferably slightly lower than 90°, so as to be slightly slopped downwards.

[0066] More specifically, the second segment of overflow duct 32 is inclined with respect to the vertical by an angle preferably ranging between 70° and 80°.

[0067] With particular reference to Figures 4, 5 and 6, the hiding member 34, on the other hand, has a water-permeable structure, is preferably almost completely fitted/ recessed into the first segment of the overflow duct 32, and is preferably firmly locked to the body of hopper 3 via a snap-lock fastening system.

[0068] More in detail, the hiding member 34 preferably has a substantially rectangular and tray-shaped structure, and is fitted into the first segment of overflow duct 32 so that a first segment 35 of its raised perimeter edge is preferably roughly flush with the lower mouth 32a of overflow duct 32. Moreover the hiding member 34 is preferably fitted into the first segment of overflow duct 32 so that a second segment 36 of its raised perimeter edge, opposite to said first segment 35, is arranged inside the overflow duct 32 spaced above the elbow/bend connecting the first and second consecutive segments of the overflow duct 32.

[0069] Preferably the bottom wall of the substantially tray-shaped hiding member 34 moreover has a number of large pass-through openings allowing the exceeding water to easily reach the second downwards-slopped segment of the overflow duct 32.

[0070] Furthermore, the bottom wall of the substantially tray-shaped, hiding member 34 is preferably additionally provided with a cantilever snap-fit tab 37 adapted to snap on a sharp edge at the elbow/bend connecting the first and second consecutive segments of the overflow duct 32.

[0071] Finally, in the examples shown, the substantially tray-shaped water-permeable hiding member 34 is preferably made of plastic material, preferably via an injection molding process.

[0072] With particular reference to Figures 4 and 6, the

tubular member 33, in turn, has a substantially rectangular cross-section, locally complementary to that of the upper mouth 32b of overflow duct 32, or rather of the second segment of overflow duct 32, so as to be telescopically fitted into the second segment of overflow duct 32.

[0073] Moreover, the outlet mouth of tubular member 33 is preferably provided with a plate-like protruding lip or flap 38 that preferably has a flexible and/or roughly comb-shaped structure, and is dimensioned to abut against the inner face of the facing, nearly vertical, front wall of casing 2, so as to channel the water coming out from the upper mouth 32b of overflow duct 32 up to the immediately facing, nearly vertical front wall of casing 2. Preferably the plate-like protruding flap 38 is furthermore slightly slopped downwards.

[0074] Finally, in the examples shown, the nearly S-shaped tubular member 33 is preferably made of plastic material, preferably via an injection molding process.

[0075] With reference to Figures 1 and 2, preferably the laundry washing machine 1 additionally comprises an electronic control unit 27 which is located inside the casing 2 and which preferably controls the motor assembly 10 and/or the water supply circuit 14 and/or the heating member 15, so as to perform the washing cycle manually-selected by the user via an appliance control panel 28 which, in turn, is preferably located/incorporated on the top wall of casing 2, preferably above the solenoid valve/s 18 of water supply circuit 14.

[0076] Preferably the laundry washing machine 1 finally includes an aqua-stop safety system 40 which is adapted to channel the water mains to the water supply circuit 14.

[0077] The aqua-stop safety system 40 preferably comprises: a long flexible hosepipe 41 having the proximal end in direct communication with the water supply circuit 14, or rather with the water-distribution manifold 19 of water supply circuit 14, and the distal end suitably structured to watertight couple, preferably in manually detachable manner, with the tap of the water mains; and a normally-closed, auxiliary solenoid valve (not shown) which is located at the distal end of the hosepipe 41 for directly controlling the entry of water into the same hosepipe 41. Therefore the fresh water of the water mains can enter within and flow along the hosepipe 41 towards the solenoid valve/s 18 of water supply circuit 14 solely when the auxiliary solenoid valve is in the open position.

[0078] The normally-closed, auxiliary solenoid valve is preferably directly controlled by the electronic control unit 27 on the basis of a water presence sensor 43 which is capable of detecting the presence of water and is preferably located on the bottom of casing 2 where the water dropping from tubular member 33 accumulates.

[0079] Operation of laundry washing machine 1 is almost identical to that of any other top-loading home laundry washing machine and therefore does not require further explanations.

[0080] The overflow assembly 30 of hopper 3, in turn,

is capable of quickly and silently draining the exceeding water out of washing tub 4.

[0081] More in detail, in case a solenoid valve 18 gets stuck in the open position, the level of water inside the washing tub 4 start rising up to reach the height of the bend of the roughly S-shaped tubular member 33. Then the exceeding water starts flowing along the tubular member 33, up to the immediately facing and nearly vertical, front wall of casing 2.

[0082] When arrives to the inner face of the front wall of casing 2, the exceeding water starts flowing downwards on surface of the front wall of casing 2, up to the bottom of casing 2 where it starts accumulating until the water presence sensor 43 detects the presence of water and immediately stops powering the normally-closed, auxiliary solenoid valve. Deactivation of the auxiliary solenoid valve, in turn, interrupts the flow of fresh water into the washing tub 4.

[0083] The extension of tubular member 33 up to touch the inner face of the nearly-vertical front of casing 2 prevents the exceeding water from freely dropping/falling down to the bottom of casing 2, thus avoiding the noise of the water droplets violently bumping against the bottom wall of casing 2.

[0084] The comb-shaped plate-like protruding lip or flap 38, in turn, spreads the water coming out from tubular member 33 on a large portion of the inner face of the front wall of casing 2.

[0085] The L-form of the overflow duct 32 and the hiding member 34, finally, reduces the propagation of the washing noise up to the tubular member 33.

[0086] The advantages resulting from the particular structure of the overflow assembly 30 are remarkable.

[0087] First of all, due to the particular shape of both overflow duct 32 and tubular member 33, the overflow assembly 30 is capable of quickly draining the exceeding water out of washing tub 4 while efficiently preventing, at same time, the washing noise from coming out of washing tub 4.

[0088] Moreover the lower mouth 32a of overflow duct 32 is located on the perimeter edge/rim of the lower mouth of hopper 3 where it totally hidden from view.

[0089] Clearly changes and modifications may be made to the laundry washing machine 1 without, however, departing from the scope of the present invention.

[0090] For example, according to a first, non-shown alternative embodiment the overflow duct 32 is integrally formed with a lateral sidewall of hopper 3. The nearly S-shaped, tubular member 33, in turn, juts out from the same lateral sidewall of hopper 3 towards the immediately facing and nearly vertical, lateral wall of boxlike casing 2, preferably so as to reach/touch the same lateral wall of casing 2.

[0091] According to a second, non-shown and less-sophisticated alternative embodiment, the upwards-extending and preferably also nearly reverse-L-shaped, overflow duct 32, rather than being incorporated into the front or lateral sidewall of hopper 3, is at least partially

formed/incorporated on a separate piece which is firmly attached/coupled to the sidewall of hopper 3.

[0092] According to a third, non-shown alternative embodiment, moreover, the hiding element 34 can be integrally formed on the overflow duct 32, with a shape suitable to create a sort of water barrier toward the bottom side of the machine, and allowing at the same time the free passage of water in case of the water reaching the overflow level. Accordingly, the alternative shape of hiding element 34, preferably integrated in the outflow duct 32, will be adapted to the constraints of the manufacturing process, eventually requiring modifications departing from the shape of the element depicted in Figures 4, 5 and 6.

Claims

1. A laundry washing machine (1) comprising: a boxlike casing (2) structured for resting on the floor; a vertically-oriented, hopper (3) which is located on a top wall of said casing (2); a washing tub (4) which is arranged inside the casing (2) beneath the hopper (3), and is superiorly provided with an access opening (5) that directly communicates with a lower mouth of the hopper (3) for allowing insertion and extraction of the laundry in/from the washing tub (4) via said hopper (3); and an overflow assembly (30) for draining out of the hopper (3) the exceeding water; wherein said overflow assembly (30) comprises: an upwards-extending overflow duct (32) which is located on a sidewall (31) of said hopper (3), so that a lower mouth (32a) of the overflow duct (32) is located roughly on the perimeter edge/rim of the lower mouth of the hopper (3) and that an upper mouth (32b) of the overflow duct (32) is located on the outer face of the same sidewall (31) of the hopper (3), spaced above the lower mouth of hopper (3); **characterized in that** said overflow assembly (30) further comprises an outwards-extending, tubular member (33) which is associated to the upper mouth (32b) of the overflow duct (32) so as to protrude from the sidewall (31) of the hopper (3) towards the facing wall of the casing (2), forming an extension of said overflow duct (32).
2. Laundry washing machine according to Claim 1, wherein the overflow duct (32) is substantially reversed-L shaped.
3. Laundry washing machine according to Claim 1 or 2, wherein the tubular member (33) is roughly S-shaped so as to form a siphon-like extension of said overflow duct (32).
4. Laundry washing machine according to any one of the preceding claims, wherein the tubular member (33) extends substantially horizontally.

5. Laundry washing machine according to any one of the preceding claims, wherein the outlet mouth of the tubular member (33) is nearly horizontally aligned to the upper mouth (32b) of the overflow duct (32). 5
6. Laundry washing machine according to any one of the preceding claims, wherein the tubular member (33) is dimensioned so as to reach/touch the facing upright wall of the casing (2), for channelling the exceeding water up to the same upright wall of the casing (2). 10
7. Laundry washing machine according to Claim 6, wherein the outlet mouth of the tubular member (33) has a plate-like protruding lip/flap (38) which is dimensioned to abut against the inner face of the facing upright wall of said casing (2). 15
8. Laundry washing machine according to Claim 7, wherein said plate-like protruding lip/flap (38) has a comb-shaped structure. 20
9. Laundry washing machine according to Claim 7 or 8, wherein said plate-like protruding lip/flap (38) is sloped downwards. 25
10. Laundry washing machine according to any one of the preceding claims, wherein said overflow assembly (30) additionally comprises a hiding member (34) which is located in the lower mouth (32a) of the overflow duct (32) so as to hide the same lower mouth, and is provided with a number of waterways allowing the exceeding water to freely enter into the overflow duct (32) bypassing at once the same hiding member (34). 30 35
11. Laundry washing machine according to Claim 10, wherein the hiding member (34) is almost completely fitted/recessed into a starting segment of the overflow duct (32) and/or is firmly locked to the body of the hopper (3) via a snap-lock fastening system (37). 40
12. Laundry washing machine according to Claim 11, wherein the hiding member (34) has a substantially rectangular and tray-shaped structure, and is fitted into the overflow duct (32) so that a first segment (35) of its raised perimeter edge is roughly flush with the lower mouth (32a) of overflow duct (32). 45 50
13. Laundry washing machine according to Claim 12, wherein the hiding member (34) is fitted into the overflow duct (32) so that a second segment (36) of its raised perimeter edge, opposite to said first segment (35), is arranged inside the overflow duct (32) spaced above an elbow/bend of said overflow duct (32). 55
14. Laundry washing machine according to any one of

Claims 2-13, wherein the overflow duct (32) is divided into a first and a second consecutive segments; the first segment being nearly rectilinear and extending upwards inside the sidewall (31) of the hopper (3), starting from the perimeter edge/rim of the lower mouth of the hopper (3); the second segment being nearly rectilinear and being inclined with respect to the first segment by an angle lower than 90°.

15. Laundry washing machine according to any one of the preceding claims, wherein said overflow assembly (30) is located on the sidewall (31) directly faced to a nearly vertical front wall of the casing (2).

Patentansprüche

1. Waschmaschine (1), umfassend: ein kastenartiges Gehäuse (2), das dazu strukturiert ist, auf dem Boden zu ruhen, einen vertikal ausgerichteten Eingabetrichter (3), der an einer oberen Wand des Gehäuses (2) angeordnet ist, einen Laugenbehälter (4), der in dem Gehäuse (2) unter dem Eingabetrichter (3) angeordnet und oben mit einer Zugangsöffnung (5) versehen ist, die direkt mit einer unteren Mündung des Eingabetrichters (3) in Verbindung steht, um das Einführen und Herausnehmen des Waschguts in den/aus dem Laugenbehälter (4) über den Eingabetrichter (3) zu gestatten, und eine Überlaufanordnung (30), um das überschüssige Wasser aus dem Eingabetrichter (3) abzuführen, wobei die Überlaufanordnung (30) Folgendes umfasst: einen sich nach oben erstreckenden Überlaufkanal (32), der an einer Seitenwand (31) des Eingabetrichters (3) angeordnet ist, so dass eine untere Mündung (32a) des Überlaufkanals (32) ungefähr an dem Umfangsrand/der Umfangskante der unteren Mündung des Eingabetrichters (3) angeordnet ist und dass eine obere Mündung (32b) des Überlaufkanals (32) an der Außenfläche derselben Seitenwand (31) des Eingabetrichters (3) oberhalb der unteren Mündung des Eingabetrichters (3) beabstandet angeordnet ist, **dadurch gekennzeichnet, dass** die Überlaufanordnung (30) ferner ein sich nach außen erstreckendes rohrförmiges Glied (33) umfasst, das der oberen Mündung (32b) des Überlaufkanals (32) zugeordnet ist, um von der Seitenwand (31) des Eingabetrichters (3) zu der zugewandten Wand des Gehäuses (2) vorzuragen und eine Verlängerung des Überlaufkanals (32) bildet.
2. Waschmaschine nach Anspruch 1, wobei der Überlaufkanal (32) im Wesentlichen umgekehrt L-förmig ist.
3. Waschmaschine nach Anspruch 1 oder 2, wobei das rohrförmige Glied (33) ungefähr S-förmig ist, um eine siphonartige Verlängerung des Überlaufkanals (32)

zu bilden.

4. Waschmaschine nach einem der vorhergehenden Ansprüche, wobei sich das rohrförmige Glied (33) im Wesentlichen horizontal erstreckt. 5
5. Waschmaschine nach einem der vorhergehenden Ansprüche, wobei die Auslassmündung des rohrförmigen Glieds (33) fast horizontal auf die obere Mündung (32b) des Überlaufkanals (32) ausgerichtet ist. 10
6. Waschmaschine nach einem der vorhergehenden Ansprüche, wobei das rohrförmige Glied (33) so bemessen ist, dass es die zugewandte aufrechte Wand des Gehäuses (2) erreicht/berührt, um das überschüssige Wasser dieselbe aufrechte Wand des Gehäuses (2) hinaufzuleiten. 15
7. Waschmaschine nach Anspruch 6, wobei die Auslassmündung des rohrförmigen Glieds (33) eine plattenartige vorragende Lippe/Lasche (38) hat, die so bemessen ist, dass sie an der inneren Fläche der zugewandten aufrechten Wand des Gehäuses (2) anliegt. 20
8. Waschmaschine nach Anspruch 7, wobei die plattenartige vorragende Lippe/Lasche (38) eine kammförmige Struktur hat. 25
9. Waschmaschine nach Anspruch 7 oder 8, wobei die plattenartige vorragende Lippe/Lasche (38) nach unten geneigt ist. 30
10. Waschmaschine nach einem der vorhergehenden Ansprüche, wobei die Überlaufanordnung (30) zusätzlich ein Abdeckglied (34) umfasst, das in der unteren Mündung (32a) des Überlaufkanals (32) angeordnet ist, um dieselbe untere Mündung abzudecken, und mit mehreren Ablauföffnungen versehen ist, dank derer das überschüssige Wasser frei und unter sofortiger Umgehung desselben Abdeckglieds (34) in den Überlaufkanal (32) eintreten kann. 35
11. Waschmaschine nach Anspruch 10, wobei das Abdeckglied (34) fast vollständig in einem Startabschnitt des Überlaufkanals (32) angebracht/vertieft ist und/oder über ein Einrastbefestigungssystem (37) fest mit dem Körper des Eingabetrichters (3) verriegelt ist. 40
12. Waschmaschine nach Anspruch 11, wobei das Abdeckglied (34) eine im Wesentlichen rechteckige und schalenartige Struktur hat und in dem Überlaufkanal (32) angebracht ist, so dass ein erster Abschnitt (35) seines erhabenen Umfangsrandes ungefähr mit der unteren Mündung (32a) des Überlaufkanals (32) bündig ist. 45

13. Waschmaschine nach Anspruch 12, wobei das Abdeckglied (34) in dem Überlaufkanal (32) angebracht ist, so dass ein dem ersten Abschnitt (35) gegenüberliegender zweiter Abschnitt (36) seines erhabenen Umfangsrandes in dem Überlaufkanal (32) oberhalb einer Krümmung/Biegung des Überlaufkanals (32) beabstandet angeordnet ist. 50
14. Waschmaschine nach einem der Ansprüche 2 - 13, wobei der Überlaufkanal (32) in einen ersten und einen zweiten aufeinanderfolgenden Abschnitt unterteilt ist, wobei der erste Abschnitt nahezu geradlinig ist und sich in der Seitenwand (31) des Eingabetrichters (3) ausgehend von dem Umfangsrand/der Umfangskante der unteren Mündung des Eingabetrichters (3) nach oben erstreckt, wobei der zweite Abschnitt nahezu geradlinig und bezüglich des ersten Abschnitts in einem Winkel von kleiner 90° geneigt ist. 55
15. Waschmaschine nach einem der vorhergehenden Ansprüche, wobei die Überlaufanordnung (30) an der Seitenwand (31) angeordnet ist, die der nahezu vertikalen Vorderwand des Gehäuses (2) direkt zugewandt ist.

Revendications



1. Lave-linge (1) comprenant : une enceinte (2) semblable à caisse structurée pour reposer sur le sol ; une trémie (3) à orientation verticale qui est située sur une paroi supérieure de ladite enceinte (2) ; une cuve de lavage (4) qui est disposée à l'intérieur de l'enceinte (2) sous la trémie (3), et est pourvue, au niveau de sa partie supérieure, d'une ouverture d'accès (5) qui communique directement avec un orifice inférieur de la trémie (3) pour permettre l'insertion et l'extraction de linge dans/à partir de la cuve de lavage (4) à travers ladite trémie (3) ; et un ensemble de trop-plein (30) pour évacuer l'excès d'eau de la trémie (3) ;
ledit ensemble de trop-plein (30) comprenant : un conduit de trop-plein (32) s'étendant vers le haut qui est situé sur une paroi latérale (31) de ladite trémie (3), de telle sorte qu'un orifice inférieur (32a) du conduit de trop-plein (32) est situé approximativement sur le bord périphérique/contour de l'orifice inférieur de la trémie (3) et qu'un orifice supérieur (32b) du conduit de trop-plein (32) est situé sur la face extérieure de la même paroi latérale (31) de la trémie (3), de manière espacée au-dessus de l'orifice inférieur de la trémie (3) ; **caractérisé en ce que** ledit ensemble de trop-plein (30) comprend en outre un élément tubulaire (33) s'étendant vers l'extérieur qui est associé à l'orifice supérieur (32b) du conduit de trop-plein (32) de façon à faire saillie à partir de la paroi latérale (31) de la trémie (3) en direction de la

paroi en regard de l'enceinte (2), formant un prolongement dudit conduit de trop-plein (32).

2. Lave-linge selon la revendication 1, dans lequel le conduit de trop-plein (32) présente essentiellement la forme d'un L à l'envers. 5
3. Lave-linge selon la revendication 1 ou 2, dans lequel l'élément tubulaire (33) présente approximativement la forme d'un S de façon à former un prolongement dudit conduit de trop-plein (32) ressemblant à un siphon. 10
4. Lave-linge selon l'une quelconque des revendications précédentes, dans lequel l'élément tubulaire (33) s'étend essentiellement horizontalement. 15
5. Lave-linge selon l'une quelconque des revendications précédentes, dans lequel l'orifice de sortie de l'élément tubulaire (33) est aligné presque horizontalement avec l'orifice supérieur (32b) du conduit de trop-plein (32). 20
6. Lave-linge selon l'une quelconque des revendications précédentes, dans lequel l'élément tubulaire (33) est dimensionné de façon à atteindre/venir en contact avec la paroi verticale en regard de l'enceinte (2), afin d'acheminer l'excès d'eau jusqu'à ladite paroi verticale de l'enceinte (2). 25
7. Lave-linge selon la revendication 6, dans lequel l'orifice de sortie de l'élément tubulaire (33) comporte une lèvre/ailette saillante (38) semblable à une plaque qui est dimensionnée pour venir en appui contre la face intérieure de la paroi verticale en regard de ladite enceinte (2). 30
8. Lave-linge selon la revendication 7, dans lequel ladite lèvre/ailette saillante (38) semblable à une plaque présente une structure en forme de peigne. 35
9. Lave-linge selon la revendication 7 ou 8, dans lequel ladite lèvre/ailette saillante (38) semblable à une plaque est inclinée vers le bas. 40
10. Lave-linge selon l'une quelconque des revendications précédentes, dans lequel ledit ensemble de trop-plein (30) comprend en outre un élément de masquage (34) qui est situé dans l'orifice inférieur (32a) du conduit de trop-plein (32) de façon à masquer ledit orifice inférieur, et est pourvu d'un certain nombre de passages d'écoulement permettant à l'excès d'eau de pénétrer librement dans le conduit de trop-plein (32) en contournant en même temps ledit élément de masquage (34). 45
11. Lave-linge selon la revendication 10, dans lequel l'élément de masquage (34) est presque complète-

ment logé/enfoncé dans un segment initial du conduit de trop-plein (32) et/ou est solidement assujéti au corps de la trémie (3) par le biais d'un système de fixation à emboîtement-pression (37).

12. Lave-linge selon la revendication 11, dans lequel l'élément de masquage (34) présente une structure essentiellement rectangulaire et en forme de plateau, et est logé dans le conduit de trop-plein (32) de telle sorte qu'un premier segment (35) de son bord périphérique surélevé soit approximativement de niveau avec l'orifice inférieur (32a) du conduit de trop-plein (32). 50
13. Lave-linge selon la revendication 12, dans lequel l'élément de masquage (34) est logé dans le conduit de trop-plein (32) de telle sorte qu'un second segment (36) de son bord périphérique surélevé, opposé audit premier segment (35), soit disposé à l'intérieur du conduit de trop-plein (32) de manière espacée au-dessus d'un coude/d'une courbure dudit conduit de trop-plein (32). 55
14. Lave-linge selon l'une quelconque des revendications 2 à 13, dans lequel le conduit de trop-plein (32) est divisé en premier et second segments consécutifs ; le premier segment étant presque rectiligne et s'étendant vers le haut à l'intérieur de la paroi latérale (31) de la trémie (3), en partant du bord périphérique/contour de l'orifice inférieur de la trémie (3) ; le second segment étant presque rectiligne et étant incliné par rapport au premier segment d'un angle inférieur à 90°. 60
15. Lave-linge selon l'une quelconque des revendications précédentes, dans lequel ledit ensemble de trop-plein (30) est situé sur la paroi latérale (31) directement face à une paroi avant presque verticale de l'enceinte (2). 65






Fig. 2





Fig. 4






Fig. 6

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- EP 3354786 A1 [0012]